

# Sample 7-4

## 幾何学処理

有理数比の解像度変換

画像処理特論

村松 正吾

動作確認: MATLAB R2023a

## Geometric image processing

Resizing w/ rational factor

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2023a

## 準備

(Preparation)

```
close all
```

## 補間率の設定

(Setting of upsampling factor)

- $M$ : 補間率 (upsampling factor)

```
% Upsampling factor  
uFactor = 5;
```

## 間引き率の設定

(Setting of downsampling factor)

- $M$ : 間引き率 (downsampling factor)

```
% Downsampling factor  
dFactor = 3;
```

## フィルタの設定

(Setting of filter)

平均フィルタのインパルス応答 (Impulse response of averaging filter)

$$h[n] = \begin{cases} \frac{1}{M_d} & 0 \leq n \leq M_d - 1 \\ 0 & \text{otherwise} \end{cases}$$

- $\{h[n]\}_n$ : インパルス応答 (Impulse response)

```
% Impulse response of averaging filter
h = ones(1,dFactor)/dFactor;
```

線形補間フィルタのインパルス応答 (Impulse response of linear interpolation filter)

$$f[n] = \begin{cases} \frac{1}{M_u}(M_u - |n|) & -M_u + 1 \leq n \leq M_u - 1 \\ 0 & \text{otherwise} \end{cases}$$

ただし、非因果性に注意。 (Note that the incausal property.)

- $\{f[n]\}_n$ : インパルス応答 (Impulse response)

```
% Impulse response of interpolation filter
f = 1-abs(-(uFactor-1):(uFactor-1))/uFactor;
```

縦続フィルタのインパルス応答 (Impulse response of the cascade filter)


$$g[n] = h[n] * f[n]$$

```
% Impulse response of the combination
g = conv(h,f);
```


## フィルタ特性の表示

(Display of filter characteristics)

```
% Impulse response
figure(1)
impz(g)
ax = gca;
ax.XLim = [-1 length(g)];
ax.YLim = [-0.2 1];
```



```
% Frequency response
figure(2)
freqz(g)
ax = gca;
hold on
line([0 min(1/uFactor,1/dFactor) min(1/uFactor,1/dFactor)], [20*log10(uFactor)
20*log10(uFactor) ax.YLim(1)],...
    'LineStyle',':', 'LineWidth',2, 'Color','red');
hold off
```



## 画像への適用

(Application to images)

$$v[\mathbf{m}] = \sum_{\ell \in \mathbb{Z}^2} u[\mathbf{M}_u \ell] g[\mathbf{M}_d \mathbf{m} - \mathbf{M}_u \ell]$$

ただし, (where)

$$g[\mathbf{n}] = h[\mathbf{n}] * f[\mathbf{n}]$$

$$h[\mathbf{n}] = \begin{cases} \frac{1}{|\det \mathbf{M}_d|} & \mathbf{n} \in \mathcal{N}(\mathbf{M}_d) \\ 0 & \text{otherwise} \end{cases}$$

$$f[\mathbf{n}] = \begin{cases} \text{prod}(\mathbf{1} - \text{abs}(\mathbf{M}_u^{-1} \mathbf{n})) & \mathbf{n} \in \{\mathbf{M}_u \mathbf{x} \in \mathbb{Z}^2 \mid \mathbf{x} \in (-1, 1)^2\} \\ 0 & \text{otherwise} \end{cases}$$

ただし, 非因果性に注意. (Note that the incausal property.)

- $\{g[\mathbf{n}]\}_n$ : インパルス応答 (Impulse response)

```
% Reading an image
u = imread('cameraman.tif');

% Generating the bilinear interpolation filter
```

```


[n1,n2] = ndgrid(-uFactor+1:uFactor-1);
f = (1-abs(n1)/uFactor).*(1-abs(n2)/uFactor);

% Generating the average filter
h = fspecial('average',dFactor);

% Combination of h and f
g = conv2(f,h);
[n1,n2] = ndgrid(-uFactor-floor(dFactor/2)+1:uFactor+floor(dFactor/2)-1);

% Impulse response
figure(3)
stem3(n2,n1,g,'filled')
axis ij
ax = gca;
ax.XLim = ax.XLim + [-1 1];
ax.YLim = ax.YLim + [-1 1];


```



```

% Frequency response
figure(4)
freqz2(g)
axis ij

```



```
% Bivariate upsampling function
upsample2 = @(x,n) ...
    shiftdim(upsample(...
    shiftdim(upsample(x,...
    n(1)),1),...
    n(2)),1);

% Bivariate downsampling function
downsample2 = @(x,n) ...
    shiftdim(downsampling(...
    shiftdim(downsampling(x,...
    n(1)),1),...
    n(2)),1);

% Interpolation with upsampling and filtering
x = padarray(u,[1 1],'replicate','both');
w = imfilter(upsample2(x,uFactor*[1 1]),g,'conv');
s = ceil(uFactor/2);
y = w(s+1:s+uFactor*size(u,1),s+1:s+uFactor*size(u,2));
v = downsample2(y,dFactor*[1 1]);
```

## 画像表示

(Display image)

原画像 (Original)

```
figure(5)
imshow(u)
title('Original')
```



結果画像 (Result)

```
% Display result
figure(6)
imshow(v)
title('Result')
```



```
% Imresize
figure(7)
z = imresize(u,uFactor/dFactor);
imshow(z)
title('Imresize')
```

Imresize



© Copyright, Shogo MURAMATSU, All rights reserved.