

# Sample 11-4

## 画像ノイズ除去

勾配降下法

画像処理特論

村松 正吾

動作確認: MATLAB R2023a

## Image denoising

Gradient descent

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2023a

## 準備

(Preparation)

```
clear
close all
import msip.download_img
msip.download_img
```

```
kodim01.png already exists in ./data/
kodim02.png already exists in ./data/
kodim03.png already exists in ./data/
kodim04.png already exists in ./data/
kodim05.png already exists in ./data/
kodim06.png already exists in ./data/
kodim07.png already exists in ./data/
kodim08.png already exists in ./data/
kodim09.png already exists in ./data/
kodim10.png already exists in ./data/
kodim11.png already exists in ./data/
kodim12.png already exists in ./data/
kodim13.png already exists in ./data/
kodim14.png already exists in ./data/
kodim15.png already exists in ./data/
kodim16.png already exists in ./data/
kodim17.png already exists in ./data/
kodim18.png already exists in ./data/
kodim19.png already exists in ./data/
kodim20.png already exists in ./data/
kodim21.png already exists in ./data/
kodim22.png already exists in ./data/
kodim23.png already exists in ./data/
kodim24.png already exists in ./data/
See Kodak Lossless True Color Image Suite
```

## 問題設定

(Problem settings)

- 
- 
- 
- 

```
D = [2 1]/3;  
v = 0.5;
```

## パラメータ設定


(Parameter settings)

```
lambda = 0.2;  
gamma = 0.4;  
niters = 20;
```

## 関数プロット

(Function plot)

```
% Function setting  
f = @(x0,x1) 0.5*(v-(D(1)*x0+D(2)*x1)).^2 + lambda*0.5*(x0.^2+x1.^2);  
% Variable settings  
s0 = linspace(-1,1,21);  
s1 = linspace(-1,1,21);  
% Surf plot of cost function f()  
figure  
[S0,S1] = ndgrid(s0,s1);  
J = f(S0,S1);  
hf = surf(s0,s1,J);  
hf(1).FaceAlpha = 0.25;  
hf(1).EdgeAlpha = 0.25;  
hf(1).EdgeColor = 'interp';  
hf(2).LineWidth = 1;  
set(gca,'YDir','reverse')  
ylabel('s_0')  
xlabel('s_1')  
zlabel('f(s)')  
hold on
```



## 勾配降下法

(Gradient descent)

1. Initialization: ,
2. Gradient descent:
3. If a stopping criteria is satisfied then finish, otherwise and go to Step 2.

【Example】

- 
- 

初期化 (Initialization)

```
sp = 2*rand(2,1)-1; % in [-1,1]^2
```


勾配降下 (Gradient descent)

```
for idx=0:niters-1
    % Preious state
    s(1,1) = sp(1); % s0
    s(2,1) = sp(2); % s1
    % Gradient descent
    sc = sp-gamma*(D'*(D*sp-v)+lambda*sp);
    % Current state
```

```

s(1,2) = sc(1); % s0
s(2,2) = sc(2); % s1
% Quiver plot
xp = s(2,1);
yp = s(1,1);
xn = s(2,2);
yn = s(1,2);
hp = quiver(xp,yp,xn-xp,yn-yp);
hp.Marker = 'o';
hp.ShowArrowHead = 'on';
hp.MaxHeadSize = 120;
hp.MarkerSize = 6;
hp.MarkerEdgeColor = 'r';
hp.Color = 'r';
hp.LineWidth = 2;
% Update
sp = sc;
end
hold off

```



## パラメータ設定

(Parameter settings)

- sgm: ノイズ標準偏差 (Standard deviation of noise)

- nlevels: ウェーブレット段数 (Wavelet levels)

```
% Parameter settings
isaprxleft = true;
lambda = 10^1
```

```
lambda = 10
```

```
gamma = 10^-1
```

```
gamma = 0.1000
```

```
sgmuint8 = 30;
sgm = sgmuint8/255;
nlevels = 3;
niters = 80;
```

## 画像の読込

(Read image)

```
u = im2double(imread('./data/kodim23.png'));
if size(u,3) == 3
    u = rgb2gray(u);
end
```

## 観測画像

(Observation image)

- 
- 
- 
- 

```
v = imnoise(u,'gaussian',0,sgm^2);
```

## 非間引きハール DWT

(Undecimated Haar DWT)

```
import msip.udhaarwtdec2
import msip.udhaarwtrec2
```

## 完全再構成の確認 (Check the perfect reconstruction)

非間引きハール DWT はパーセバルタイト性 (The undecimated DWT satisfies the Parseval tight property,)

を満たすため、 の転置システムは完全再構成分析システムとなり得る。 (and thus Its transposition system can be a PR analysis system.)

```
[coefs,scales] = udhaarwtdec2(v,nlevels);
r = udhaarwtrec2(coefs,scales);
assert(norm(v-r,"fro")^2/numel(v)<1e-18,'Perfect reconstruction is violated.')
```

合成辞書と転置辞書の定義 (Definition of synthesis dictionary and its adjoint)

```
% Definiton of dictionary and its adjoint
adjdic = @(x) udhaarwtdec2(x,nlevels); % D
syndic = @(x) udhaarwtrec2(x,scales); % D.'
```

## 勾配降下法

(Gradient descent method)

1. Initialization: ,
2. Gradient descent:
3. If a stopping criteria is satisfied then finish, otherwise and go to Step 2.

【Example】

- 
- 

初期化 (Initialization)

```
sp = coefs;
```

勾配降下 (Gradient descent)

```
if isaprxleft
    mask = ones(size(coefs));
    mask(1:prod(scales(1,:))) = 0;
    lambda = lambda * mask;
end
for idx=0:niters-1
    % Gradient descent
    sc = sp-gamma*(adjdic(syndic(sp))-v)+lambda.*sp);
    % Update
    sp = sc;
end
```

## ノイズ除去画像

(Denoised image)

```
r = syndic(sc);
```

## 画像表示

(Image show)

```
figure
imshow(u);
title('Original image u')
```



```
figure
imshow(v)
title(sprintf('Noisy image v : PSNR = %5.2f [dB]',psnr(u,v)))
```



Noisy image v: PSNR = 18.73 [dB]



```
figure
imshow(r)
title(sprintf('Denoised image r : PSNR = %5.2f [dB]',psnr(u,r)))
```



Denoised image r: PSNR = 27.66 [dB]



© Copyright, Shogo MURAMATSU, All rights reserved.