Sample 5-1

周波数解析

単変量畳み込み

画像処理特論

村松 正吾

動作確認: MATLAB R2020a

Fourier analysis

Univariate convolution

Advanced Topics in Image Processing

Shogo MURAMATSU

Verified: MATLAB R2020a

準備

(Preparation)

close all

入力信号 $\{u[n]\}_n$

(Input signal $\{u[n]\}_n$)

% Input u[n]
u = [1 2 3];

線形シフト不変システムのインパルス応答 $\{h[n]\}_n$

(Impulse response of a linear shift-invariant system $\{h[n]\}_n$)

% Impulse response h[n]
h = [1 1 1]/3;

線形シフト不変システムの出力応答 $\{v[n]\}_n$

(The linear shift-invariant system response $\{v[n]\}_n$)

畳み込み演算 (Convolution)

$$\{v[n]\}_n = \{h[n]\}_n * \{u[n]\}_n = \sum_{k=-\infty}^{\infty} u[k]\{h[n-k]\}_n$$

```
% Output v[n]
v = conv(h,u);
```

入力信号 $\{u[n]\}_n$ のスペクトル

(Spectrum of input signal $\{u[n]\}_n$)

$$U(e^{\mathrm{j}\omega}) = \sum_{n=-\infty}^{\infty} u[n]e^{-\mathrm{j}\omega n}, \ \omega \in \mathbb{R}$$

DFT(FFT)によるDTFTの周波数サンプル計算 (Frequency sampling of DTFT by DFT (FFT))

$$U[k] = U(e^{j\omega})\big|_{\omega = \frac{2\pi}{N}k}, \ k \in \left\{0, 1, 2, \cdots, N-1\right\}$$

% Setting the number of frequency sample points in $[0,2\pi)$ nPoints = 128;

% Spectrum of u[n]
U = fft(u,nPoints);

フィルタ $\{h[n]\}_n$ の周波数応答

(Frequency response of filter $\{h[n]\}_n$)

$$H(e^{\mathrm{j}\omega}) = \sum_{n=-\infty}^{\infty} h[n] e^{-\mathrm{j}\omega n}, \ \omega \in \mathbb{R}$$

DFT(FFT)によるDTFTの周波数サンプル計算 (Frequency sampling of DTFT by DFT (FFT))

$$H[k] = H(e^{j\omega})\big|_{\omega = \frac{2\pi}{N}k}, \ k \in \left\{0, 1, 2, \cdots, N-1\right\}$$

% Frequency response of h[n]

H = fft(h,nPoints);

出力信号 $\{v[n]\}_n$ のスペクトル

(Spectrum of input signal $\{v[n]\}_n$)

$$V(e^{\mathrm{j}\omega}) = \sum_{n=-\infty}^{\infty} v[n]e^{-\mathrm{j}\omega n}, \ \omega \in \mathbb{R}$$

DFT(FFT)によるDTFTの周波数サンプル計算 (Frequency sampling of DTFT by DFT (FFT))

$$V[k] = V(e^{\mathrm{j}\omega})\big|_{\omega = \frac{2\pi_k}{N}}, \ k \in \left\{0, 1, 2, \cdots, N-1\right\}$$

% Frequency response of v[n]

```
V = fft(v,nPoints);
```


スペクトルと周波数応答の表示

(Display of spectra and frequency response)

 $V(e^{\mathrm{j}\omega}) = H(e^{\mathrm{j}\omega})U(e^{\mathrm{j}\omega})$

```
% Frequency sample points
w = 0:2*pi/nPoints:2*pi-1/nPoints;

% Display of spectra and frequency response
figure(1)
ax = gca;
plot(ax,w,abs(U),'b',w,abs(H),'k:',w,abs(V),'r-.')
grid(ax,'on')
xlabel(ax,'Normalized angular frequency \omega [rad]')
ylabel(ax,'Magnitude [-]')
legend(ax,'|U(e^{{j\omega}})|','|H(e^{{j\omega}})|','|V(e^{{j\omega}})|')
ax.XLim = [0 2*pi];
ax.XTick = [0 pi 2*pi];
ax.XTickLabel = {'0', '\pi', '2\pi' };
```



線形シフト不変システムの解析


(Analysis of linear shift-invariant systems)

インパルス応答

(Impulse respone)

$$h[n],\ n\in\mathbb{Z}$$

figure(2)
impz(h)




伝達関数

(Transfer function)

$$H(z)=\sum_{n=-\infty}^{\infty}h[n]z^{-n},\ z\in\mathbb{C}$$

figure(3)
zplane(h)




周波数応答

(Frequency response)

$$H(e^{\mathrm{j}\omega})=H(z)\big|_{z=e^{\mathrm{j}\omega}},\ \omega\in\mathbb{R}$$

- 振幅応答 (Magnitude response): $|H(e^{\mathrm{j}\omega})|$
- _{位相応答} (Phase response): ∠ $H(e^{j\omega})$

figure(4)
freqz(h)



© Copyright, Shogo MURAMATSU, All rights reserved.