
JARVIS

# How Jarvis Works

Architecture, components, tech stack and pipelines — from a spoken sentence to a team of AI experts acting in your apps, teaching with animations, and supervising Claude Code for you.




Edition 2: Jarvis v1 + natural voice, Lessons, visual maths, Documents & code, the team, coding supervisor, reminders, board, installer

Date: 9 November 2026

Written for: the Jarvis author, as a detailed guide to understanding the app before changing it

Source of truth: the code in this repository (SPEC.md, PLAN.md, app/, brain/, gateway/, roles/, router/, supervisor/, tools/, speech/, security/)

# Contents


1. Jarvis in one page
2. Tech stack
3. The big picture: processes and layers
4. The life of one spoken request
5. The app shell (Electron)
6. Orchestrator and routing
7. The Brain: driving the Claude Code CLI
8. The Gateway: the only door to your apps
9. The apps and tools at a glance
10. The team of experts
11. Lessons and visual maths
12. Documents, code and web search
13. The coding supervisor
14. Reminders, morning plan and project board
15. Accounts, sign-in and secrets
16. Voice: hearing and speaking
17. The user interface layer
18. Token saving: how Jarvis stays cheap
19. Safety and privacy model
20. Where data lives
21. Testing and quality
22. Windows, macOS and the installer
23. Source code map
24. Limitations and next steps
25. Glossary


## 1. Jarvis in one page

Jarvis is a desktop assistant for Windows and macOS. You talk to it by typing or by voice. Behind one front desk sits a **team of AI experts** — **Maya** (personal assistant), **Alan** (educator), **Ryan** (project manager), **Sara** (doctor) and **Victor** (finance) — each with its own skills, apps, natural voice and memory. They work in the apps you connect (mail, calendars, Notion, GitHub…) only in the ways you allow, teach with narrated animated lessons, read your PDFs and code with exact references, remind you of your day, and can run and supervise **Claude Code** on your projects while you do something else.

Seven ideas shape the design:

**1 · Claude is the brain, through the CLI**

Jarvis never calls an AI API directly. It starts the official **Claude Code command-line tool** ( `claude -p` ), so everything runs on **your own Claude Pro plan**.

**2 · One door to every app: the Gateway**

Claude gets exactly one tool provider, the **Jarvis Gateway**. Every action passes through it, and it enforces your **Off / Ask me first / Allowed** settings in code, not in the prompt.

**3 · A team, not one assistant**

Each expert has its own instructions, **only its own apps**, its own conversation, voice and notes. They ask each other for help — one hop only, so they never loop.

**4 · Local first**

Simple commands and routing never reach Claude. Speech is heard and spoken **on your computer** (whisper.cpp, Kokoro). Memory, history, reminders and the board are files in your Jarvis folder.

### 5 · Careful with tokens

Short prompts, built-in tools off, trimmed results, short sessions, smaller images, cheaper model for look-ups, and per-role tool lists. The fixed cost of a request was cut by **93%** (measured).

### 6 · Fast to talk to

Replies are spoken **while Claude is still writing**; spoken questions get spoken-length answers. First word in about **2.8 s** (was 6–7 s).

### 7 · Safety by construction

Deleting is never automatic; content from emails, pages, files and screens is **data, never instructions**; secrets live only in the OS keychain; Claude Code's permission checks are never skipped; everything is logged.

### Size of the codebase

About **19,400 lines** of TypeScript/HTML/CSS in 134 files, plus **242 automated tests** in 15 files. One codebase for both operating systems.

## 2. Tech stack

| Layer | Technology (version) | Why it was chosen / what it does |
|---|---|---|
| Language | TypeScript 5.9 (strict) | One typed language for windows, main process, Gateway, team, supervisor and tests. |
| Desktop shell | Electron 45.2.3 (Chromium 156, Node 24) | One codebase for Windows and macOS; global hotkeys, screen capture, audio, worker threads, secure IPC. |
| AI brain | Claude Code CLI 2.1.318 ( `claude -p` ) | Runs on the user's Claude Pro login; MCP tools, sessions ( `--resume` ), streaming JSON, partial messages, permission-prompt tool, hooks. |
| Models | `haiku` , `sonnet` | Haiku for look-ups and the small helpers (advisor, memory summaries); Sonnet for explaining, drafting, lessons. |
| Tool protocol | MCP, `@modelcontextprotocol/sdk` 1.32 | Jarvis runs MCP *servers* (Gateway shim, supervisor) and an MCP *client* (added apps, web search). |
| Secure storage | `@napi-rs/keyring` 2.1 | Windows Credential Manager / macOS Keychain for tokens and keys. |
| Speech-to-text | whisper.cpp b5130, model `ggml-base.en` | Local; downloads pinned with SHA-256. |
| Text-to-speech | Kokoro-82M (fp32 ONNX) via `kokoro-js` 1.2.1, ONNX Runtime 1.21, Transformers.js 3.8 | Natural voice on the CPU in a worker thread, about 4–6× faster than real time; 21 voices; 326 MB download checked with SHA-256. |
| Diagrams | Mermaid 12.1.0 | Flowcharts, sequence, state, mind-map, timeline, class and ER diagrams in lessons (strict security mode). |
| Equations | KaTeX 0.19.0 | LaTeX maths in lessons, with colour commands ( `\blue{x}` ); trust off. |
| Code highlighting | highlight.js 11.12.0 | Colours code shown in lessons, with line numbers and marked lines. |
| PDF text | pdf.js (pdfjs-dist) 6.4.299 | Reads the text of PDFs you pick, page by page, for page-accurate citations. |
| Web search | Exa hosted MCP ( `mcp.exa.ai` ) | Optional one-click app: web search and page reading, no account needed. |
| Bundler / tests | esbuild 0.28 · Vitest 4 | Builds every window and helper script in about a second; 242 tests that cost no tokens. |
| Packaging | electron-builder 26.18 | Windows NSIS installer (built, 167 MB); universal macOS .dmg (configured). |
| External APIs | Gmail v1, Google Calendar v3, Microsoft Graph v1.0, remote MCP servers | Called with OAuth tokens from the keychain. |

> **Why the CLI instead of the API?**
>
> The SPEC requires Jarvis to run on the user's existing Claude Pro subscription. The Claude Code CLI is the supported way to do that from a program: it handles the login; Jarvis starts it, gives it a prompt and reads the answer. A `Brain` interface keeps this swappable.

## 3. The big picture: processes and layers

Jarvis is a small group of programs. The **Electron main process** coordinates; windows draw; `claude` processes think; tiny helper scripts connect Claude back to Jarvis.





Figure 1 — Processes and layers. Only *claude* processes talk to Anthropic; only the Gateway (inside the main process) talks to your apps.

### The kinds of process

| Process | Started by | Job |
|---|---|---|
| Electron main | you | Coordinator: windows, IPC, Orchestrator, Brain, Gateway core, control server, team, supervisor, PA clock, voice, accounts, files. |

| Process | Started by | Job |
| --- | --- | --- |
| Renderers (up to 6 windows) | main | Draw the UI. Sandboxed: no Node.js access; only the functions the preload bridge exposes. |
| `claude` (request) | Brain, once per request | Runs as Jarvis or as one expert, calls tools through the Gateway, streams the reply, exits. |
| `claude` (helpers) | main | Tiny tool-less Haiku runs: the supervisor's advisor and the memory summariser. |
| `claude` (coding task) | coding supervisor | Claude Code working in your project; every permission prompt and question goes to Jarvis. |
| Gateway / supervisor shim | a `claude` process | The same small MCP program in two modes; forwards to the control server over HTTP. Runs on Jarvis's own runtime. |
| Kokoro worker | main (worker thread) | Turns text into speech, one request at a time, so the app never freezes. |
| `whisper-cli` | voice controller | Converts a WAV file to text, locally. |
| Claude Code hook script | your own Claude Code sessions | Only if you switch it on: tells Jarvis that a session you started finished or needs you, then exits. |

## 4. The life of one spoken request

Follow a real example: you press **Ctrl+Alt+Space** and say **"Maya, what's on my calendar today?"**. Times are typical on this laptop.





Figure 2 — A spoken request. Blue: calls. Amber dashed: results. Speaking starts at step 12, long before the reply is finished (step 15).

**1–2** **Hearing.** Push-to-talk records until 1.2 s of quiet, whisper.cpp turns the audio into text on your PC, and the text goes to the voice card. If Claude Code is waiting on one of *your* coding questions, a clear answer like "go with yours" is sent to the supervisor instead.

**3–5** **Routing (0 tokens).** The Orchestrator checks local commands, then decides **who answers**: a name at the start ("Maya, …") wins, then the chat's chosen member, then topic words, then a short follow-up stays with the last member. It immediately tells the voice card "Maya · PA" and her voice.

**6** **The Brain starts `claude` as Maya**: her own system prompt, a time stamp, her notes (only for a new conversation) and a `[spoken: answer in at most 3 short, plain sentences…]` tag, with partial messages switched on.

**7–9** **Only Maya's tools.** The shim sends her role with every call; the Gateway lists and runs only her apps (mail, calendars, reminders, board, team…), checks your setting, calls the API, trims and logs.

**10–14** **Speaking while writing.** Each text piece is forwarded to the voice card. As soon as a sentence is complete it is sent to the Kokoro worker; audio pieces come back trimmed and with natural pauses, and play back to back.

**15–17** **Finishing.** The final result brings the session id and token counts. The Orchestrator logs usage (flagged only if 3× more than usual for Maya), the message pair is added to the shared chat history (and appears in the main window), and the exchange is queued for Maya's memory.

# 5. The app shell (Electron)

## 5.1 Windows

| Window | How it is made | Purpose |
|---|---|---|
| Main window | Hidden title bar; OS buttons drawn over the top menu. Kept awake while hidden. | Chat (with team chips), Team, Tool Hub, Whiteboard, Usage, Activity, Settings. Also where the microphone is captured. |
| Floating box | Frameless, always on top; `?mode=box`. | Quick typing from any app (Ctrl+Shift+Space). |
| Voice card | Frameless, 480 px, above the taskbar; `?mode=voice`; hidden by default. | Spoken requests (shows the member's name and colour, the words as they arrive), reminders and the morning plan. Ctrl+Alt+J shows/hides it; speech continues. |
| Lesson window | Own page `lesson.html`; frameless; placed on an empty side of the screen or full screen. | Narrated lessons with diagrams, charts, graphs, maths stages, code, quotes and screen cut-outs. |
| Supervisor card | Own page `supervisor.html`; 440 px, bottom-right, never takes focus. | Ryan's coding card: Claude's questions with his advice, risky requests, updates, test results, changed files. |
| Badges | Tiny, not focusable, excluded from screen captures. | REC, Listening, "Jarvis looked at your screen". |

## 5.2 The preload bridge and IPC

Renderers are sandboxed. `app/preload.ts` exposes one object, `window.jarvis`; each function maps to one IPC channel in `app/main.ts`.

| Channel(s) | What it does |
|---|---|
| `ask`, `ask:start`, `ask:partial` | Send a request (optionally streamed): who answers, then the reply as it is written. |
| `confirm:*`, `screen:pick/area` | "Ask me first" popups and screen pickers, in the window that asked. |
| `hub:*`, `accounts:*` | Tool Hub, sign-in, added and suggested apps. |
| `team:*` | Team page: members, names, voices, memory (save, summarise, forget). |
| `lesson:*` | Show a lesson, place it (side / full), close. |
| `sup:*` | Supervisor card: state, answers, stop, open in VS Code, settings, watching your own sessions. |
| `pa:*`, `reminders:*`, `board:*`, `planner:changed` | Morning plan, reminders, project board. |
| `history:*` | Shared chat history: load, live additions from other windows, switch off, clear. |
| `tts:*`, `voice:*`, `speech:*`, `audio:*` | Natural voice, voice card, speech engine, microphone audio. |
| `usage:summary`, `activity:list`, `settings:*` | Usage, Activity and Settings pages. |

### 5.3 "Popups follow the window that asked"

Main remembers which window sent each request. A Yes/No popup, picker or file dialog appears **only there**; the floating box or voice card grows to fit it and then returns. The main window never pops up for voice or box requests. Background jobs (the morning plan) use the voice card.

## 6. Orchestrator and routing

`app/orchestrator.ts` has no Electron code, so it is tested directly.

```
handle(text, picked member, { spoken, onRole, onText }):
  role, text = routeRole(text, picked, last member, names)   # router/roles.ts, 0 tokens
  if matchLocalCommand(text): return runLocal(...)          # 0 tokens
  model    = pickModel(text, override)                      # haiku / sonnet
  session  = sessions[role].current()                       # one conversation per member
  onRole(role)                                              # window shows name + voice now
  prefix   = [notes, if new conversation] [now: …] [level: …] [spoken: …]
  result   = brain.ask(prefix + text, session, model, { role, onText, onProgress })
  usage.add(role, tokens); expensive = 3 × that member's usual
  memory.remember(role, text, reply)                        # summarised every 4 turns
  return reply, role, model, tokens, expensive, newConversation
```

### 6.1 Who answers (router/roles.ts)

| # | Rule | Example |
|---|---|---|
| 1 | A name at the start | "Sara, …", "hey Maya", "Dr. Sara", "ask the teacher…", "PA, …" (names you set on the Team page work too) |
| 2 | The member chosen with the chips above the chat | Chip "Victor" → every message goes to Finance |
| 3 | Topic words (strong words count 1, generic words like "explain" count ½) | "Explain my blood test report" → Doctor; "Explain the chain rule" → Educator |
| 4 | Follow-up within 5 minutes | "and for lunch?" stays with Sara |
| 5 | Otherwise | Jarvis, the front desk (all apps) |

### 6.2 Local commands, model, sessions

- **Local commands** (T1): "start/stop recording", "open/clear whiteboard", "new conversation" (resets every member's conversation), "open tool hub", "show usage", "mute/unmute" — handled without Claude.
- **Model** (T9): drafting, explaining, teaching, learning, screen, whiteboard → Sonnet; reading, listing, checking → Haiku; unclear → Sonnet; your Settings override wins.
- **Sessions** (T6): each member keeps its own Claude session ( `--resume` ); a fresh one after 10 minutes idle or 20 turns. Memory notes are added only to the first message of a new session.
- **Levels:** Settings → "How Jarvis explains things" adds `[level: eli5 | student | professional]` ; Automatic adds nothing.

### 6.3 Usage: "3× more than usual"

Every request is logged with its member (`usage.jsonl`). A request is flagged ▲ when it uses more than **3× the median of that member's last 30 requests**, so the flag keeps working as apps are added. Until there are 5 requests to compare with, the one-off setup baseline is used. The Usage page shows tokens reused from Claude's prompt cache separately (they cost far less).

## 7. The Brain: driving the Claude Code CLI

```
interface Brain {
  ask(text, session_id, model, { onProgress, signal, role, consult, onText }) →
      { reply, session_id, tokens_used, is_error, usage, limit_reached, model }
}
```

`ClaudeCLIBrain` (`brain/claude-cli.ts`) answers requests; `brain/coder.ts` runs coding tasks and the small Haiku helpers. These and the setup check are the **only code that starts `claude`** (a test proves it). Flags for a request (`brain/args.ts`):

| Flag | Meaning / why |
|---|---|
| `-p <request>` | Headless: answer and exit. |
| `--output-format stream-json --verbose` | One JSON event per line: progress, usage, the reply. |
| `--include-partial-messages` | Only when the window streams: the reply arrives word by word, for speaking early. |
| `--model haiku\|sonnet`, `--max-turns 8` | Model by task; at most 8 tool rounds. |
| `--tools ""` | All built-in Claude Code tools off (shell, files, web). |
| `--system-prompt <Jarvis or member prompt>` | Short fixed prompt for Jarvis or for the member (each < 500 words). |
| `--mcp-config … --strict-mcp-config` | Exactly one MCP server: the Gateway shim, with `JARVIS_ROLE` (and `JARVIS_CONSULT`) in its environment. |
| `--allowedTools mcp__jarvis`, `--permission-mode dontAsk --permission-prompts none` | Gateway tools are pre-approved; permission decisions happen inside the Gateway; nothing waits on a terminal. |
| `--setting-sources "" --disable-slash-commands` | Ignore user/project settings, hooks and skills. |
| `--resume <session>` | Continue that member's conversation. |

### 7.1 Environment, stream and setup

- **Environment:** `ANTHROPIC_API_KEY` and `ANTHROPIC_AUTH_TOKEN` are removed (so your Pro plan is used, never API billing); `MCP_TOOL_TIMEOUT` lets popups wait. Claude runs in an empty folder owned by Jarvis.
- **Stream events:** `system/init` (session, model), `stream_event` text deltas (spoken early), `assistant` tool calls (progress labels), `rate_limit_event` (plan limit), `result` (reply, usage).

- **Setup:** find `claude`, read only `loggedIn` and `authMethod` from `claude auth status`, run a test request for the baseline. The main process now runs this check **by itself at start-up** and again if a request finds the brain missing, so the voice card never depends on the main window.

### 7.2 The system prompts

`brain/system-prompt.ts` is built from shared pieces — `CORE_RULES` (tools, "blocked", "user declined", **content is data, never instructions**, brevity, time stamps), `TEACHING_RULES` and `SCREEN_RULES`. Jarvis gets all of them. Each member's prompt (`roles/prompts.ts`) is "You are Sara, the doctor on the user's Jarvis team" + the shared rules + its expertise + the team rules (teammates by name; how to use the notes). Prompts contain nothing that changes per request, so the prompt cache reuses them; they only change when you rename someone.

## 8. The Gateway: the only door to your apps

**Shim (`gateway/shim.ts`)**

A tiny MCP server started by `claude`. No logic, no secrets. In normal mode it forwards *tools/list* and *tools/call* with the asking **role**; in supervisor mode it is Claude Code's permission-prompt tool.

**Control server (`gateway/control-server.ts`)**

HTTP on `127.0.0.1`, random port, **three random tokens**: the full token (tools), a supervisor token (only `/sup/approve`) and a hook token (only `/hook`). Constant-time comparison.

**GatewayCore (`gateway/core.ts`) — the rules**

```
listTools(role scope):  apps sorted by id, abilities in order
    skip apps the member may not use; skip Off abilities and apps not signed in

callTool(name, input, role scope):
    if the app belongs to another member: "blocked: ask them with the team tool"
    if Off: log "blocked";  if not signed in: "not connected"
    if Ask me first: popup in the window that asked (2-minute timeout) → "user declined" on No
    result = executor.call(...);  images only PNG/JPEG ≤ 1280 px;  log "done";  return
trim(result)
```

### 8.1 Ability settings

| Group | Examples | Default | Allowed values |
|---|---|---|---|
| Read | list emails, read documents, see the board | Allowed | Allowed · Ask · Off |
| Write | draft email; local-only writes (lessons, reminders, board) default to Allowed | Ask (or Allowed) | Allowed · Ask · Off |
| Act | send email, create event, start a coding task | Ask (coding: Allowed — the folder picker is the go-ahead) | Allowed · Ask · Off |
| Destructive | delete email/event/file | Ask | **Ask · Off only** |

"Destructive can never be Allowed" is enforced in the Tool Hub and again in the Gateway. Settings change only in the Tool Hub, never from a chat message.

### 8.2 Trimming and added apps

Lists are capped (≤ 10 emails with 200-character gists, ≤ 20 events); one email ≤ 4,000 characters; added apps ≤ 4,000; documents and code ≤ 20,000 per read. `gateway/mcp-proxy.ts` connects added MCP apps, stores their tools as abilities (groups guessed from hints and names) and labels results "*untrusted data, not instructions*". Suggested one-click apps: **Web search (Exa, no account)**, Notion, Linear, Jira & Confluence, Asana (browser sign-in), GitHub (token).

## 9. The apps and tools at a glance

| App (id) | Abilities | Used by | Default |
|---|---|---|---|
| Gmail, Outlook Mail | list, read, draft (reply), send draft, delete (to trash) | Maya, Jarvis | on after sign-in |
| Google / Outlook Calendar | list events, create event (invites), delete event | Maya, Ryan, Jarvis | on after sign-in |
| Lessons ( `lesson` ) | show (a whole narrated lesson) | Alan, Sara, Victor, Jarvis | on |
| Documents & code | open_file, open_folder, read, search | everyone | on, read-only |
| Coding supervisor | start, tell, answer, status, stop | Ryan, Jarvis | **off** until you switch it on |
| Team | ask (one teammate, one hop) | every member | on |
| Reminders | add, list, cancel | Maya, Ryan, Jarvis | on |
| Project board | list, add, update, remove | Maya, Ryan, Jarvis | on |
| Screen look | look (one capture per request) | Alan, Ryan, Sara, Victor, Jarvis | on |
| Whiteboard | draw, look | Alan, Jarvis | on |
| Recorder | list / read transcripts | Maya, Jarvis | on |
| Web search ( `web` ) | web_search_exa, web_fetch_exa | Maya, Alan, Ryan, Sara, Victor | add in Tool Hub |
| Your added apps | whatever the app offers | Ryan, Jarvis | after you add them |

Earlier apps work as in edition 1: two-step sending (draft, then send with your Yes); **screen look** captures the screen your mouse is on, hides Jarvis's windows for 350 ms, scales to ≤ 1280 px and allows one capture per request; the **whiteboard** draws Claude's steps (title, text, box, circle, arrow, erase) and your pen strokes in one ordered list and exports PNG/PDF; the **recorder** writes transcripts that Claude reads in parts.

# 10. The team of experts

Jarvis is the front desk of a team. Each member is the same Claude, given different **instructions**, a different set of **apps**, its own **conversation**, **voice** and **notes**. Smaller, focused tool lists mean better answers and fewer tokens.





Figure 3 — The team. Each member only sees its own apps. Members can ask one teammate for help (purple); the one asked cannot ask again.

## 10.1 What makes each member different

| Part | How it works | Code |
|---|---|---|
| Definition | Id, role name, human name, title, colour, apps, default voice, names it answers to, topic words, example questions. | `roles/roles.ts` |
| Instructions | "You are Sara, the doctor…" + shared rules + expertise + team rules. Doctor: practical, evidence-based, never diagnoses with certainty, sends emergencies to real help. Finance: numbers, assumptions, risks; not regulated advice; never asks for passwords. Educator: the full teaching rules. PM: briefs, milestones, the board. PA: day plans, reminders, drafts. | `roles/prompts.ts` |
| Apps | The shim sends `JARVIS_ROLE`; the control server turns it into a filter; the Gateway lists and runs only those apps. | `roleUsesApp`, `control-server.ts` |
| Conversation | One Claude session per member. | `app/orchestrator.ts` |
| Names | Maya, Alan, Ryan, Sara, Victor by default; rename on the Team page (2–20 letters, unique). Routing, prompts, badges and voice samples follow. | `peopleNames`, `team:setName` |
| Voice | A natural voice per member, chosen by you on the Team page (Play sample). Lessons use the Educator's voice; the supervisor card uses the Project Manager's. | `roleVoice` in main |

### 10.2 Memory, kept in your Jarvis folder

1. After each answer, the exchange is appended to `roles/<member>/recent.jsonl` (cut to 800 characters, with anything that looks like a card number, password, PIN, OTP or key removed).
2. Every **4** exchanges, a tool-less Haiku call merges them into `notes.md`: lasting facts only (preferences, goals, routines, conditions, decisions), at most 180 words, never secrets. If summarising fails, the recent exchanges are kept for next time.
3. When a new conversation with that member starts, the notes go in front of your first message as `[your notes about the user: …]`. The prompt tells the member to use them quietly.
4. On the Team page you can read and edit the notes, "Summarise now", or "Forget everything" (deletes the folder).

### 10.3 Asking a teammate (one hop)

The `team__ask` tool runs the question as the other member (their prompt, apps and notes) and returns "*Ryan (Project Manager) says:* …". The consulted run is started with `JARVIS_CONSULT=1`, and the scope then hides the team tool, so a consulted member cannot consult anyone else — no loops, bounded cost.

## 11. Lessons and visual maths

When you ask to understand something, the member calls `lesson__show` **once with the whole lesson**. Jarvis checks it, opens the lesson window and returns at once ("the lesson narrates itself") so Claude does not wait.

### 11.1 How Jarvis decides how to explain

| Question | Format |
|---|---|
| Simple fact or quick question | Just a few plain sentences, no lesson. |
| An idea that is clearer when seen | A short lesson of 2–6 steps. |
| A problem, derivation or deep how/why | Four parts in order: **Problem** → **Intuition** → **Solution** → **Recap**, 6–12 steps. |
| Level | ELI5 (tiny words, everyday analogies), student, or professional (precise terms, trade-offs, real code) — from Settings, from your words, or inferred. |

### 11.2 The lesson format (tools/lesson/spec.ts)

A lesson is plain data: a title, a placement and steps. Each step has `say` (spoken), optional `part`, `focus`, `clear`, and up to 5 visuals. Every field is checked and limited (≤ 30 steps); nothing from Claude is ever inserted as HTML except through Mermaid (strict mode) and KaTeX (trust off).

| Visual | What it draws |
|---|---|
| heading, text, bullets, note, table | Written explanation; bullets appear one by one across the narration; notes as Tip / Watch out / Example / Key idea. |
| math | KaTeX equations; a list of steps morphs one equation into the next; `\blue{…}`-style colours link symbols to pictures. |

| Visual | What it draws |
|---|---|
| diagram | Mermaid; nodes fade in one by one, then connections draw themselves. |
| chart | Line, bar, scatter, pie, with legends, direct labels, hover values; validated colour-blind-safe palette. |
| plot | Function graphs from a safe maths reader ( `tools/lesson/expr.ts` ); a `t` range animates waves in a loop. |
| scene + animate | Shapes (rect, circle, line, arrow, text, path) that move, fade, recolour, loop or bounce. |
| **stage + play** | The visual-maths engine (below). |
| quote, code, snip | References: exact words with "p. 4"; highlighted code with line numbers and marked lines; a cut-out of *your* screenshot with a glowing box. All sources are numbered and listed under **References**. |

### 11.3 Visual maths stages (tools/lesson/stage.ts, app/renderer/stage.ts)

A **stage** is an interactive coordinate plane in the picture-first teaching style. It holds sliders ( `params` ), objects and actions:

- **Objects:** function, parametric curve, vector, point (draggable, bound to sliders), line, segment, tangent (of a function at a point), area, Riemann rectangles, circle, polygon, label. Coordinates may be expressions of the sliders, e.g. `at: ["a", "a^2"]` .
- **Actions:** create (draw on), set (slide a parameter smoothly), matrix (bend the whole plane, with î and ĵ), highlight, fade, show, zoom, wait. Later steps continue on the same stage with `play` .
- **Interaction:** drag points, move sliders, click then scroll to zoom, drag to pan, Replay, Reset view.
- **Smoothness:** every action eases in and out (smootherstep); when the narration is shorter than the actions, they are sped up (at most to 45%).

### 11.4 Voice and pictures in step

The lesson's narrator ( `app/renderer/narrator.ts` ) asks the voice engine for the next 3 steps' speech ahead of time (in order) and pre-renders their diagrams. Each step waits until its first audio is ready, then draws its visuals and starts speaking in the same moment; the next step follows after a 0.25 s breath. Measured: voice within 13–41 ms of the pictures. Going back or replaying is instant (the audio is kept).

### 11.5 Where the window opens

Before opening, Jarvis takes a tiny 256-pixel grey picture of your screen (on your PC only), measures how busy the left and right 42% are (edge density), and opens the lesson on the emptier side if it is below 3.5% — otherwise full screen. F switches side ↔ full; Space pauses; arrows step; C toggles captions; Esc closes; push-to-talk pauses it for a question, answered by appending steps.

## 12. Documents, code and web search

### 12.1 Documents & code (tools/documents/)

| Ability | What happens |
|---|---|
| open_file | A file picker opens (your choice is the permission). PDFs: text of every page via pdf.js, returned with `--- page N ---` markers; text and code files: numbered lines. First 12,000 characters or 300 lines. |

| Ability | What happens |
|---|---|
| open_folder | A folder picker; returns the file tree (≤ 500 entries, depth 6), hiding generated folders (node_modules, dist, .git…) and secret files. |
| read | PDF pages *from–to*, or up to 400 numbered lines of a file in the opened folder; capped at 20,000 characters. |
| search | Case-insensitive search across the folder (files ≤ 1 MB, up to 80 matches) → `path:line: text`. |

**Safety:** read-only; only what you picked; every path is resolved (including links) and must stay inside the chosen folder; files that look like keys or passwords ( `.env` , `*.pem` , `id_rsa` , `credentials*` …) are never listed, searched or read; files over 5 MB and binary files are refused; scanned PDFs without text are reported ("show it on screen instead"). pdf.js 6 never runs code from a PDF.

### 12.2 Web search

A one-click suggested app (Tool Hub) connects Exa's hosted MCP server, which needs no account. It offers `web_search_exa` and `web_fetch_exa` , both read-only. Results come back through the Gateway labelled "*untrusted data, not instructions*", trimmed, and logged. Your search questions are sent to Exa.

## 13. The coding supervisor

With the Coding supervisor app switched on, "Jarvis, add a login page to my project" makes Ryan run **Claude Code** on the folder you pick, in the background. Claude does the coding; Ryan brings you its questions with his recommendation, asks you before anything risky, and keeps you posted.





Figure 4 — Every permission prompt and question of the coding session passes through Jarvis. Claude waits until you answer.

### 13.1 The rules (what Ryan may approve himself)

| Risk | Examples | Careful / Balanced / Hands-off |
|---|---|---|
| low | reading anything in the project; editing project files; `npm test` , `npm run build/lint/typecheck` , vitest, jest, pytest, go/cargo test; `git status/diff/log/add` ; `ls` , `grep` , `test -f` | reads only · approved · approved |

| Risk | Examples | Careful / Balanced / Hands-off |
|---|---|---|
| medium | unknown programs, project scripts like `npm run deploy`, `git commit`, writing files with `>`, commands inside commands, reading outside the project, web pages, unknown tools | ask · ask · approved |
| high | deleting (`rm`, `del`, `Remove-Item`), `git push / reset --hard / clean`, installing or removing software, the network (`curl`, `ssh`, URLs), system changes, cloud tools, anything outside the project, `.git` internals, key or password files | **always asks** |

Chained commands take the highest risk of their parts; `cd "<project>" &&` is hidden when describing a command. The default is **Balanced**.

### 13.2 Answers, updates and results

- **Your answers** (`supervisor/answer.ts`): "the second one", "option 1", "SQLite", "go with yours", "the other one", "yes, go ahead", "no, keep it — move it to old/". A longer answer with extra wishes is passed to Claude as your own words. Spoken replies are only taken when they clearly answer the open question.
- **Updates**: when you start, when something happened (every 3–15 minutes, your choice), and at the end — files changed, commands run, the latest test result ("Tests: 12 passed, 1 failed", read from vitest, jest, pytest, mocha, Node, Go, Cargo output), and Claude's own summary.
- **More instructions**: "tell Claude to also add a logout button" continues the same Claude session (`--resume`); while Claude is busy, it is queued until the current step ends. "Stop" ends it and answers any open question with no.
- **The card**: what changed (each file opens in VS Code), the test badge, Open in VS Code, Stop, Hide. Each coding task appears on the project board as "doing", then "done".

### 13.3 Your own Claude Code sessions (opt-in)

Settings → Coding supervisor → "Also tell me when Claude Code sessions I start myself…" adds two hooks (*Stop* and *Notification*), marked `jarvis-claude-hook`, to your Claude Code settings file, keeping a copy of the original; switching off removes exactly those. Claude Code (through Git Bash on Windows) then runs `dist/supervisor/jarvis-claude-hook.mjs` with Jarvis's own runtime; the script posts the folder and Claude's last message to `/hook` with the hook-only token and exits at once. Ryan says "Claude finished in my-shop. It says: …" or "your session needs you". Sessions Jarvis itself supervises carry `JARVIS_SUPERVISED=1` and are skipped, so nothing is announced twice.

## 14. Reminders, morning plan and project board

- **Reminders** (`reminders.json`): Maya adds them with an exact time ("remind me at 6 pm to call Mom"). A clock in the main process checks every 15 s; a due reminder appears on the voice card and is spoken in Maya's voice. Reminders missed while Jarvis was closed are still given if they are under 2 hours old; older ones are dropped quietly. Upcoming reminders are listed (and can be cancelled) on Maya's Team card.
- **Morning plan**: switch it on and pick a time on Maya's card. Once a day (within 3 hours of that time, if Jarvis is not busy) the clock asks Maya to check today's calendar and important email, give a short plan, and add a reminder 10 minutes before each meeting. The plan is shown and spoken on the voice card. "Plan my day now" runs it any time.

- **Project board** ( `board.json` ): tasks with title, project, due date and status To do / Doing / Done; shared by Maya and Ryan through `board__*` tools, shown on the Team page (overdue dates in red), and filled automatically by coding tasks.

## 15. Accounts, sign-in and secrets

Unchanged from edition 1. Google and Microsoft use **OAuth with PKCE** and a loopback redirect: Jarvis opens your browser with a challenge and a state value, listens on `127.0.0.1` (Google) or `localhost` (Microsoft) for 5 minutes, checks the state, and exchanges the code plus its private verifier for tokens.

- **Scopes:** Google `gmail.modify` + `calendar.events` (no permanent delete); Microsoft `offline_access User.Read Mail.ReadWrite Mail.Send Calendars.ReadWrite` .
- **Tokens:** refresh tokens in the OS keychain, access tokens in memory only; one shared refresh; rotated tokens saved; `invalid_grant` disconnects and asks you to sign in again.
- **Windows limit:** a Credential Manager entry holds at most 1,280 characters, so `ChunkedSecretStore` splits long values into numbered pieces.
- **Added apps:** automatic client registration + the same PKCE flow; the browser opens only when you click Sign in.

## 16. Voice: hearing and speaking

### 16.1 Hearing

- **Speech engine:** whisper.cpp b5130 (Windows download, pinned SHA-256; macOS via Homebrew), model `ggml-base.en` ; runs `whisper-cli` on a WAV file, locally.
- **Capture:** microphone (and computer sound for meetings on Windows) → 16 kHz AudioWorklet → 100 ms batches of PCM to the main process.
- **Push-to-talk** (Ctrl+Alt+Space, macOS Option+Space): toggles; speech above 0.02 RMS; stops 1.2 s after you stop; gives up after 8 s of silence; 30 s maximum. Pressing it also stops any speech and pauses an open lesson.
- **Meeting recorder:** 30-second segments transcribed while the meeting goes on; one transcript at the end; an automatic summary request follows.

### 16.2 Speaking: the natural voice

| Piece | How it works |
|---|---|
| Model | Kokoro-82M, **full precision (fp32)**, 326 MB, pinned revision and SHA-256. Loaded in a worker thread with 8 CPU threads; requests run one at a time, in order. Jarvis updates an older installed model by itself and deletes the old file. |
| Why fp32 | The smaller fp16 model produced broken audio (NaN samples) for some voices — Heart failed on 4 of 5 test sentences — which sounded like speech cutting off. fp32 is clean and about as fast; any non-finite sample is also replaced with silence as a safety net. |
| Pieces | Text is made speakable (no markdown, links or code), split into sentences; tiny sentences join the next; sizes grow (≤ 80, ≤ 140, then ≤ 220 characters) so each piece is ready before the previous one ends; long sentences split at commas. |

| Piece | How it works |
|---|---|
| Smooth joins | The model pads every piece with 0.2–0.8 s of silence. Jarvis trims it (keeping 25 ms, with tiny fades) and adds a natural pause: 0.28 s after a full stop, 0.18 s after a colon, 0.09 s after a comma. |
| Speaking while writing | For streamed replies, `speakStream` collects text as Claude writes it and sends each finished sentence to the voice at once; audio pieces play back to back. |
| Voices | 21 English voices; each team member has its own (your choice); speed 0.8–1.3×; the OS voice is the fallback. |

### 16.3 Measured speed (same question, "Hey Maya, what can you do?")

| | before | now |
|---|---|---|
| First word you hear | ≈ 6–7 s | **≈ 2.8 s** |
| Reply length | ≈ 800 characters of bullets | 3 short sentences (≈ 300) |
| Silence between pieces | up to ≈ 1 s | 0.1–0.3 s natural pauses |
| Waiting for the next piece | up to 0.95 s | 0 s |

The remaining time is mostly whisper (≈ 0.5–1 s), the 1.2 s of quiet that ends your sentence, and starting Claude Code (≈ 2 s per request).

## 17. The user interface layer

Plain TypeScript and DOM (no framework), bundled by esbuild. Text from outside is inserted with `textContent`; the only HTML from libraries comes from Mermaid (sanitised), KaTeX (trust off) and highlight.js (escapes code).

| Page / part | What it shows |
|---|---|
| Design system | Soft dark: charcoal canvas with an animated dotted world map, glassy cards, a glass pill that follows the mouse in the top menu, large thin titles, green / red / amber status colours. |
| Chat | Team chips above the message box (Auto, Jarvis, Maya, Alan, Ryan, Sara, Victor); a coloured name badge on each reply; examples from each member on the empty screen; the **shared history** (chat, voice and box together, kept after restarts). |
| Team | One card per member: name (Rename), role, apps, voice picker with Play sample, "What … remembers" (edit, Summarise now, Forget everything), Talk to. Maya's card adds the morning plan and upcoming reminders. Below: the project board. |
| Tool Hub | Accounts, apps with their abilities and settings, "Used by" (which members), suggested apps (Web search, Notion, Linear…), add any MCP app. |
| Usage | Tokens today, requests, tokens reused from cache, "unusually large" count, a bar chart of recent requests, the costliest requests. |
| Settings | Model, speak replies aloud, chat history (keep / clear), explanation level, coding supervisor (autonomy, updates, speech, watch your own sessions), Jarvis's natural voice, speech engine, shortcuts. |
| Voice card | The member's name and colour, the words as they arrive; reminders and the morning plan. |

| Page / part | What it shows |
| --- | --- |
| Lesson window, supervisor card | See sections 11 and 13. |

## 18. Token saving: how Jarvis stays cheap

| Rule | What | Where |
| --- | --- | --- |
| T1 | Local commands and routing (0 tokens) | `router/commands.ts`, `router/roles.ts` |
| T2 | Short fixed prompts (< 500 words each) | `brain/system-prompt.ts`, `roles/prompts.ts` |
| T3 | Built-in Claude Code tools off | `--tools ""` |
| T4 | Only usable tools, and only the member's apps | `GatewayCore.listTools(scope)` |
| T5 | Trimmed results | `gateway/trim.ts`, tool limits |
| T6 | Short sessions per member | `brain/session.ts` |
| T7 | Images ≤ 1280 px | `tools/screen`, image guard |
| T8 | Speech stays local | `speech/` |
| T9 | Haiku for look-ups and helpers | `router/model.ts`, advisor, memory |
| T10 | Byte-identical prompts and tool lists (cache reuse) | fixed text, sorted tools |
| T11 | At most 8 tool rounds | `--max-turns 8` |
| new | Spoken questions get short answers; lessons and coding tasks return at once | orchestrator, executors |

Measured at the start of the project: Claude Code defaults 41,136 tokens for "say hello" vs Jarvis 2,742 → **93.3% less**. Today the lesson tool adds about 1,600 tokens of description and the documents tools about 280 — but only for members that use them; the Doctor's requests no longer carry email, calendar or coding tools. Prompt caching reuses most of this between requests.

## 19. Safety and privacy model

| Promise | How it is enforced |
| --- | --- |
| Your ability settings are the law | Checked in `GatewayCore` on every call; Off abilities are never listed; members only see their own apps. |
| Deleting always needs your Yes | Destructive abilities cannot be Allowed; the supervisor treats deleting as high risk at every level. |
| Content is data, not instructions | Emails, documents, code, screenshots, web results, transcripts and Claude Code output are labelled untrusted; every prompt says so; any action still passes your settings. |

| Promise | How it is enforced |
|---|---|
| Claude Code's checks are never skipped | Coding sessions are forced to permission mode "manual"; the bypass flag appears nowhere in the code (tested). |
| Least-privilege tokens | The coding session's token only opens `/sup/approve`; the hook script's only `/hook`; neither can use your mail or calendars (tested). |
| Only what you pick | Documents and folders through a picker; paths cannot leave the folder; key/password files never read; the supervisor never approves anything outside the project. |
| Secrets never in files | Keychain only; memory, history and recent exchanges have card numbers, passwords, PINs, OTPs and keys removed before saving. |
| Your Claude login is never read | Only `loggedIn` / `authMethod`; API-key variables removed from every `claude` process. |
| Screen, mic and your settings only when you ask | One screenshot per request with a badge; mic only in push-to-talk or recording; your Claude Code settings changed only by the opt-in switch, with a backup. |
| Medical and money advice is careful | Doctor: no certain diagnoses, emergencies sent to real help. Finance: not regulated advice, never asks for credentials. |
| Downloads verified, servers private | whisper.cpp and Kokoro pinned with SHA-256; all local servers bind to 127.0.0.1 with random tokens. |

## 20. Where data lives

"Jarvis folder" = `%APPDATA%\Jarvis` on Windows, `~/Library/Application Support/Jarvis` on macOS. It is kept when you uninstall; delete it to remove everything.

| Data | Location |
|---|---|
| Passwords, tokens, API keys, Google client secret | OS keychain only |
| Settings (abilities, names, voices, levels, supervisor, morning plan) | `settings.json` (no secrets) |
| Chat history (chat, voice, box) | `history.jsonl` (last 1,000 messages; can be off or cleared) |
| Team memory | `roles/<member>/notes.md` and `recent.jsonl` |
| Reminders, project board | `reminders.json`, `board.json` |
| Activity and usage logs | `activity.jsonl`, `usage.jsonl`, `baseline.json` |
| Meeting transcripts (text only) | `transcripts/` |
| Speech engine, natural voice | `speech/`, `speech/kokoro/` |
| Where the hook script finds Jarvis | `hook-endpoint.json` (address + hook-only token) |
| Your Claude Code hooks (only if switched on) | `~/.claude/settings.json` + `settings.json.before-jarvis` |
| Claude conversations | Claude Code's own session store (not shown in Claude Desktop or claude.ai) |

## 21. Testing and quality

**242 automated tests** in 15 files (239 run everywhere; 3 run only where the real speech or voice engine is installed). They use no Claude tokens.

| Test file | What it proves |
|---|---|
| setup-brain, token-saving, starter-apps, tool-hub, safety | The SPEC's acceptance criteria C01–C33: installer config, setup, flags, no API key, only brain/ starts claude, token rules, sending needs Yes, destructive never Allowed, prompt-injection email, no secrets in files. |
| phase2-*, phase3, phase4 | Keychain chunking, OAuth flows, Outlook, screen look, whiteboard, recorder, push-to-talk, verified downloads, real whisper (gated). |
| natural-voice | Speakable text, pinned files, tampered downloads rejected, piece sizes, trimming and pauses, live sentence splitting, real engine and **no broken audio for any member's voice** (gated). |
| lessons | Maths reader (and refusing code), lesson checking, parts, placement, stages, references. |
| documents | Reading picked files/folders, no escape from the folder, no secrets, PDF pages (real pdf.js), levels. |
| supervisor | 20 commands × risk, autonomy, answers, the whole supervising flow with a fake Claude, limited tokens, test-result reading. |
| team | Routing, prompts < 500 words, apps per member, one-hop consults, memory, per-member sessions, streaming, no duplicate page ids. |
| planner | Names and renames, reminders, board, hooks install/remove, hook token, chat history, usage per member, web search. |

**Real checks done once** (they use your plan or your screen, so they are not in the suite): token measurement; real whisper and Kokoro; Claude Code answering through the supervisor (question, writes, risky commands); members seeing only their tools; hooks from a real Claude Code session; time to first speech; the packaged app's voice, PDF reading and keychain. **UI checks**: pages rendered in hidden, muted off-screen windows and inspected as images, so testing never touches your desktop.

## 22. Windows, macOS and the installer

| Feature | Windows 10/11 | macOS 13+ |
|---|---|---|
| Status | **Built and tested** (Windows 11) | Built from the same code, **not yet tested** on a Mac |
| Secrets | Credential Manager (chunked) | Keychain |
| Speech engine | Auto-download, verified | `brew install whisper-cpp` |
| Meeting audio | Mic + computer sound | Mic only (for now) |
| Shortcuts | Ctrl+Alt+Space, Ctrl+Alt+J, Ctrl+Shift+Space | Option+Space, … |
| Claude Code hooks | Run through Git Bash (required by Claude Code) | Run through the shell |

| Feature | Windows 10/11 | macOS 13+ |
|---|---|---|
| Installer | **NSIS, built**: `release/Jarvis-Setup-0.1.0.exe` (167 MB), per-user, choose folder, desktop shortcut | Universal .dmg configured; must be built on a Mac with both chips' native packages installed |

### How the installer is put together

- `npm run dist` = build + electron-builder. Only three libraries are needed at run time (`kokoro-js` with ONNX Runtime and Transformers.js, `pdfjs-dist`, `@napi-rs/keyring`); everything else is bundled into `dist/` by esbuild, so it is not packed again.
- Files are stored unpacked (`asar: false`) because the voice worker loads native code and Claude Code runs the shim and hook scripts by path.
- Other platforms' and Arm64 voice-engine binaries and the PDF drawing library are left out (PDF text does not need it).
- Not code-signed yet: Windows SmartScreen asks once (More info → Run anyway). The default Electron icon is used.

## 23. Source code map

| Path | Role |
|---|---|
| `app/main.ts` | Electron entry: windows, IPC, popups, lesson placement, supervisor card, PA clock, hooks, history, start-up wiring. |
| `app/orchestrator.ts`, `app/history.ts` | Routing → local command or Brain, per-member sessions, memory, usage; shared chat history. |
| `app/apps.ts`, `app/voice.ts`, `app/preload.ts` | App catalog; voice controller; the `window.jarvis` bridge. |
| `app/renderer/` | index.html + renderer.ts (all main pages), lesson.html/.ts (+ narrator.ts, stage.ts), supervisor.html/.ts, whiteboard, world map, audio, badges. |
| `router/` | commands.ts (local commands), model.ts (haiku/sonnet), roles.ts (who answers). |
| `roles/` | roles.ts (the team), prompts.ts (instructions), memory.ts (notes). |
| `brain/` | claude-cli.ts, coder.ts (coding sessions, Haiku helpers), args.ts, env.ts, stream.ts, session.ts, usage.ts, setup.ts, system-prompt.ts. |
| `gateway/` | core.ts, control-server.ts, shim.ts, settings.ts, types.ts, trim.ts, image-guard.ts, activity-log.ts, mcp-proxy.ts, mcp-auth.ts, suggested.ts. |
| `supervisor/` | supervisor.ts, policy.ts, answer.ts, tests-result.ts, reminders.ts (reminders + board), hooks.ts, jarvis-claude-hook.ts. |
| `tools/` | email, calendar, screen, whiteboard, recorder, lesson (spec, expr, stage, placement), documents, coding, team, planner. |

| Path | Role |
|---|---|
| `speech/` | whisper.ts, ptt.ts, pcm.ts, kokoro.ts, kokoro-worker.ts, kokoro-files.ts, chunks.ts, speakable.ts, tts.ts, download.ts. |
| `security/` | secrets.ts, oauth.ts, accounts.ts, destructive-lock.ts. |
| `tests/`, `scripts/`, `docs/` | Tests and fakes; build/start/measure/docs scripts; setup guides and this document. |

### Build and run

```
npm install          # dependencies
npm start            # build + launch Jarvis
npm test             # 242 tests, no tokens used
npm run typecheck    # TypeScript strict check
npm run dist         # Windows installer in release/
npm run docs:pdf     # rebuild this PDF
```

## 24. Limitations and next steps

| Limitation | Idea |
|---|---|
| Starting Claude Code takes about 2 s per request. | Keep a warm Claude process ready for the likely next member. |
| Jarvis (front desk) still carries every app's tools. | Route more requests to members, or send an app's tools only when it is mentioned. |
| The installer is unsigned and uses the default icon; macOS untested. | Code-signing certificate, a Jarvis icon, a test on a Mac. |
| Supervisor answers come from your own sessions only as notifications. | Answer your own sessions' permission prompts from Jarvis (PermissionRequest hook). |
| Reminders work only while Jarvis is running. | Start Jarvis with Windows / at login (optional). |
| Push-to-talk toggles; macOS meetings record the mic only. | Native hold-to-talk; ScreenCaptureKit system audio. |
| Wider release needs Anthropic's approval (SPEC open question 1). | Ask Anthropic, or add an API-key Brain. |

## 25. Glossary

| | |
|---|---|
| **Claude Code CLI** | Anthropic's command-line tool. Jarvis runs it in "print" mode ( `claude -p` ). |
| **Team member / role** | One expert (PA, Educator, Project Manager, Doctor, Finance): same Claude, own instructions, apps, conversation, voice and notes. |
| **Token** | A small piece of text (~¾ of a word); plan limits are counted in tokens. |
| **Prompt cache** | Claude reuses identical text from recent requests more cheaply; why prompts and tool lists stay identical. |

| | |
|---|---|
| **MCP** | Model Context Protocol: how Claude lists and calls tools offered by a "server". |
| **Gateway / shim** | Jarvis's rule engine and the tiny MCP program that connects Claude to it. |
| **Permission-prompt tool** | A Claude Code setting that sends every permission question to a program (here, the supervisor) instead of a terminal. |
| **Hook** | A command Claude Code runs on events such as "finished" (Stop) or "needs you" (Notification). |
| **Streaming / partial messages** | Receiving the reply word by word as it is written, so speaking can start early. |
| **Stage** | An interactive, animated coordinate plane in a lesson (sliders, draggable points, matrices, zoom). |
| **Kokoro, fp32 / fp16** | The local natural-voice model; fp32 = full-precision numbers (clean), fp16 = half precision (broke some voices). |
| **whisper.cpp** | Fast local speech recognition. |
| **OAuth / PKCE** | Standard sign-in that gives Jarvis a limited token instead of your password. |
| **Keychain** | The OS's secure password store. |
| **Renderer / main process** | In Electron, renderers draw windows; the main process controls the app and the OS. |