

AgileROHFinder and AgileROHFilterer

Command line applications for the detection of autozygous regions from Exome or Affymetrix microarray SNP data.

Data format

AgileROHFinder can identify autozygous regions using genotype data formatted as VCF files as well as older Affymetrix xls and birdseed files which have the required fields/columns. Similarly, AgileROHFilterer will process a VCF file (but not microArray genotype data), creating a second VCF that only contains variants within the autozygous regions. The format and required fields of the VCF and microarray input files is described [here](#).

Note:

These programs will only analyse one patient per file, if a file contains data on multiple individuals only one person will be analysed.

Creating the programs

The source code can be compiled on both Linux and Windows computers as described [here](#).

Prebuild programs

Both programs have been prebuilt for Linux and Windows and placed in the Program folder. Select the appropriate OS version and download the programs ([Linux](#) or [Windows](#)). Due to the security policies of some organisations, downloading programs on a Windows computer may not be straight forward, however this [guide](#) may help.

Running the programs

These programs are console applications and so do not have a user interface and run within a terminal environment. On Linux this will typically be in a bash terminal while on windows it will be a "Command Prompt" or "PowerShell" terminal. If the analysis is preformed on a remote server the application would typically be run from the inbuilt bash terminal on Linux or Mac and from a third party terminal such as Putty on windows connected to the server via an SSH connection.

The examples below use the Linux file structure were /data/in.vcf refers to a file in the "data" folder, the equivalent on Windows would be "C:\data\in.vcf".

Commands

Both programs require very similar commands, with **AgileROHFilterer** requiring the name of a vcf file to save the filtered variants too. The structure of the commands to run **AgileROHFinder** and **AgileROHFilterer** are shown below and described in greater detail in the table.

AgileROHFinder

```
/path/AgileROHFinder.exe /data/in.vcf /data/out.txt -t
```

AgileROHFilterer

```
/path/AgileROHFilterer.exe /data/in.vcf /data/out.vcf /data/out.txt 500000 -t
```

Note

If a folder or file name contains a space the file name and its location must be placed in speech marks
i.e /my data/my file.vcf should be entered as "/my data/my file.vcf"


Command fragment	Description	Note
/path/AgileROHFinder.exe or /path/AgileROHFilterer.exe	Name of the program with it's location	
/data/in.vcf	The name (with location) of the data file to process.	AgileROHFilterer will only process vcf files while AgileROHFinder will process vcf files and Affymetrix microarray genotype files
/data/out.vcf	Name of a file to save the filtered variant data too. This option is only present in AgileROHFilterer	This option is only present in AgileROHFilterer While it will create this file, it will not create any directories, so the path to the location most exist before the program is run.
/data/out.txt	The name with location of the file to save the list of autozygous regions too	While it will create this file, it will not create any directories, so the path to the location most exist before the program is run.
Any whole positive number	The reported regions are be extended by this number of bases when AgileROHFilterer filters the variants by position, such that variants just outside a region are also retain	This option is only present in AgileROHFilterer
Export format options -t, -b or -a	Sets the format of the data results file	See below for examples
Process all variants: -Y or -N	By default only variants with an RS ID are processed, if -Y is set then all SNPs (with one alternative allele) will be used	Optional

Feedback

As the programs run, they will report their current status to the in the terminal window.


A successful analysis:

Figure 1: AgileROHFilterer



```
msjmc@login1.arc4:~/myPrograms/AgileROH
Reading data file CHRNG-6.vcf
Including SNP without RS ids
Saved 34261 SNP and rejected 617 SNPs
Processing data and finding autozygous regions
Created homozygous run data
SNP counts per chromosome
3429    on 1
2236    on 2
1811    on 3
1287    on 4
1536    on 5
2315    on 6
1606    on 7
1192    on 8
1413    on 9
1454    on 10
2480    on 11
1805    on 12
547     on 13
1160    on 14
1076    on 15
1566    on 16
2158    on 17
561     on 18
2329    on 19
980     on 20
414     on 21
860     on 22
Filtering the VCF file
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 2: AgileROHFinder



```
msjmc@login1.arc4:~/myPrograms/AgileROH
Reading data file CHRNG-6.vcf
Including SNP without RS ids
Saved 34261 SNP and rejected 617 SNPs
Processing data
Created homozygous run data
SNP counts per chromosome
3429    on 1
2236    on 2
1811    on 3
1287    on 4
1536    on 5
2315    on 6
1606    on 7
1192    on 8
1413    on 9
1454    on 10
2480    on 11
1805    on 12
547     on 13
1160    on 14
1076    on 15
1566    on 16
2158    on 17
561     on 18
2329    on 19
980     on 20
414     on 21
860     on 22
Completed task
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 1


Figures 1 and 2 show a typical status report from the analysis of a exome vcf file by **AgileROHFilterer** and **AgileROHFinder** respectively.

- Initially, the program states which file is being process.
- Next it states whether it will process variants without an RS ID. "*Including SNP without RS ids*" indicates it will process all variants, while "*Ignoring SNPs without RS IDs*" indicates unnamed variants will be excluded.
- Once the file has been read, the program displays the number of SNPs saved and the number rejected. Only single base SNPs on the autosomal chromosomes are counted with the main reasons for a variant being rejected is either a low total read count or skewed allele read ratios.
- Next the program states that it is analysing the SNP data to find autozygous regions ("*Processing data and finding autozygous regions*") followed by "*Created homozygous run data*" when the analysis is completed.
- The next 23 lines form a table of the number of SNPs analysed on each autosomal chromosome. Typically, the number of variants depends on the length of the chromosome and for exome data the number of genes on the chromosome.
- Finally, **AgileROHFilterer** will state "*Filtering the VCF file*" indicating it is creating the results files. Since **AgileROHFinder** does not filter the variants, it just states "*Completed task*".

Failed analysis

Wrong input file name

Figure 3: Wrong input file




```
msjmc@login1.arc4:~/myPrograms/AgileROH
/CHRNA-10.vcf: No such file or directory
Can not open the 'input file'
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 3: Feedback if the input file is incorrectly entered. A similar message will be displayed if the program can not open the file because it is open for editing in another program.

Trying to export data to a folder that doesn't exist

Figure 4: Folder does not exist




```
msjmc@login1.arc4:~/myPrograms/AgileROH
/new_folder/CHRNA-6.txt: No such file or directory
Can not create the 'output file'
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 4: Feedback if the folder the export file is to be saved too does not exist. The programs can create results files, but will not create folders/directories.

The input data file's extension is not recognised

Figure 5: Unrecognised file extension




```
msjmc@login1.arc4:~/myPrograms/AgileROH
Reading data file CHRNA-6.doc
File names must have '.vcf', '.txt' or '.xls' file
extensions
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 5: Feedback if the input file does not recognise the file extension. While Linux itself does not use file extensions, these programs do use them to decide what type of data file is been used. If the file extension is not '.vcf', '.txt' or '.xls' the program will not process them.

The input data file's extension does not match the data type

Figure 6: Wrong file extension




```
msjmc@login1.arc4:~/myPrograms/AgileROH
Reading data file VCF_Sample_File.vcf
This file does not contain all the data needed please
include the following data:
Allele depth (AD)
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 6: Feedback if the input file's extension does not match it's format. In this case the file is a vcf file, but its extension has been changed to txt. Consequently, the program tries to processed it as a microarray file and found that it does not contain the expected data fields/columns.

The input data file does not contain all the required data fields/columns

Figure 7: Missing data fields


A terminal window titled 'msjmc@login1.arc4:~/myPrograms/AgileROH' with standard window controls. The terminal output shows the program attempting to read 'VCF_Sample_File.vcf' and failing with the message: 'This file does not contain all the data needed please include the following data: Allele depth (AD)'. The prompt '(base) [msjmc@login1.arc4 AgileROH]\$' is visible with a green cursor.

```
msjmc@login1.arc4:~/myPrograms/AgileROH
Reading data file VCF_Sample_File.vcf
This file does not contain all the data needed please include the following data:
Allele depth (AD)
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 7 shows the program feedback if input file does not contain the expected data fields/columns. In this case the vcf file contains the total read depth value for each variant, but not the read depths for each allele.

The input data file's format is completely wrong

Figure 8: Wrong totally file format

A terminal window titled 'msjmc@login1.arc4:~/myPrograms/AgileROH' with standard window controls. The terminal output shows the program attempting to read 'VCF_Sample_File_results.vcf' and crashing with a C++ error message: 'terminate called after throwing an instance of 'std::out_of_range'' followed by 'what(): vector::_M_range_check' and 'Aborted'. The prompt '(base) [msjmc@login1.arc4 AgileROH]\$' is visible with a green cursor.

```
msjmc@login1.arc4:~/myPrograms/AgileROH
Reading data file VCF_Sample_File_results.vcf
terminate called after throwing an instance of 'std::out_of_range'
what():  vector::_M_range_check
Aborted
(base) [msjmc@login1.arc4 AgileROH]$
```

Figure 8: Feedback if the input file format is totally wrong and the program crashes reading it. In this case a results text file was given a vcf file extension and then entered as a vcf data file. The program as attempted to read data that does not exist and crashed. This will create a cryptic error message, if the problem persists after checking the files format, you may need to contact me.