

Aglet CLI Reference

Concepts · Terminal Interface · Command Line

The Aglet Project

2026-06-13

Contents

1	Aglet Reference — Concepts	4
1.1	How to Use This Manual	4
1.2	Index	4
2	Overview	6
2.1	About Aglet	6
2.2	Starter Workflows	7
2.3	Quick Start	7
3	Keys and Commands	9
4	Core Concepts	10
4.1	Items	10
4.2	Categories	10
4.3	Views	11
4.4	Sections	12
4.5	Columns	12
4.6	Notes	13
4.7	Dependencies	14
4.8	Reserved Categories	14
5	Category Types	16
6	Category Types	17
6.1	Tag Categories	17
6.2	Numeric Categories	17
6.3	Exclusive Categories	18
6.4	The Category Hierarchy	19
6.5	Subsumption	19
7	View Types	21
8	View Types	22
8.1	Standard Views	22
8.2	Datebook Views	22
8.3	The All Items View	23

9	Auto-Assignment	24
9.1	Automatic Assignment (Implicit String Matching)	24
10	Aglet TUI Guide	25
10.1	How to Use This Manual	25
10.2	Index	25
11	Keys and Commands	27
11.1	TUI: Normal Mode Keys	27
11.2	TUI: Category Manager Keys	28
11.3	TUI: View Editor Keys	29
11.4	TUI: Item Editor Keys	29
11.5	TUI: Datebook Keys	30
12	Working with Items	31
12.1	Add an Item	31
12.2	Edit an Item	32
12.3	Add a Note to an Item	32
12.4	Mark an Item Done	33
12.5	Recurrence	33
12.6	Delete an Item	34
12.7	Restore a Deleted Item	34
12.8	Move an Item Between Sections	35
12.9	Search Items	35
12.10	Select Multiple Items	36
13	Working with Categories	37
13.1	Add a Category	37
13.2	Assign a Category to an Item	38
13.3	Unassign a Category	38
13.4	Review Classification Suggestions	39
13.5	Set a Numeric Value	39
13.6	Format a Numeric Column	40
13.7	Organize the Category Hierarchy	40
13.8	Discard a Category	41
14	Working with Views	42
14.1	Create a View	42
14.2	View Criteria	42
14.3	Add a Section to a View	43
14.4	Add a Column to a Section	43
14.5	Column Summary Functions	44
14.6	Create a Datebook View	44
14.7	Browse a Datebook View	45
14.8	The View Editor	45
14.9	View Aliases	46
14.10	Clone a View	46
14.11	Discard a View	47

15 Working with Dependencies	48
15.1 Create a Dependency Link	48
15.2 Remove a Link	48
15.3 Filter Blocked / Not-Blocked Items	49
15.4 The Link Wizard	49
16 Settings and Indicators	51
16.1 Global Settings	51
16.2 The Status and Hint Footer	51
16.3 The Item Assignment Profile	52
17 Aglet CLI Reference	53
17.1 How to Use This Manual	53
17.2 Index	53
18 Overview	55
18.1 About the CLI	55
18.2 The AGLET_DB Environment Variable	55
18.3 About .ag Files	56
18.4 CLI: Command Chart	56
19 Concepts	58
20 Item Commands	59
20.1 CLI Item Commands	59
21 Category Commands	60
21.1 CLI Category Commands	60
21.2 Profile Conditions	61
21.3 Date Conditions	61
21.4 Actions	62
22 View Commands	63
22.1 CLI View Commands	63
23 Link Commands	65
23.1 CLI Link Commands	65
24 Filtering and Sorting	66
24.1 CLI Filtering and Sorting	66
25 Import and Export	67
25.1 CLI Import and Export	67
26 Workflow Commands	68
26.1 Claim an Item	68
26.2 Release a Claim	68
26.3 The Ready List	69

Chapter 1

Aglet Reference — Concepts

[« Home](#) | [TUI Guide](#) | [CLI Reference](#)

1.1 How to Use This Manual

PURPOSE Core concepts in aglet: items, categories, views, and the rules that connect them. This document explains what things ARE; for how to operate them see the TUI Guide or the CLI Reference.

1.1.0.1 SEE ALSO

[Home](#)

1.2 Index

OVERVIEW

- About Aglet
- Starter Workflows
- Quick Start

CORE CONCEPTS

- Items
- Categories
- Views
- Sections
- Columns
- Notes

Dependencies

Reserved Categories

CATEGORY TYPES

Tag Categories

Numeric Categories

Exclusive Categories

The Category Hierarchy

Subsumption

VIEW TYPES

Standard Views

Datebook Views

The All Items View

AUTO-ASSIGNMENT

Automatic Assignment (Implicit String Matching)

Chapter 2

Overview

2.1 About Aglet

PURPOSE	Aglet is a personal information manager that gives you control over tasks, notes, facts, numbers, and dates. You capture information as short items, then organize them with categories and look at them through views.
USES	People use aglet to: · Keep a GTD-style to-do list · Plan and track projects · Build a personal knowledgebase · Track budgets and bills · Collect research notes · Track maintenance logs
HOW IT WORKS	You type information first and structure it afterward. Aglet can also assign categories automatically when a category name appears in an item's text or note. The same items can appear in many views at once, each a different perspective on the same database.
BASIC STEPS	1. Enter items of information. 2. Organize them into categories (by hand or automatically). 3. Display views of those items and categories.
INTERFACES	Aglet has two faces over one SQLite database: · A TUI - the interactive terminal interface (run "aglet"). · A CLI - one-shot commands for scripts and agents.

2.1.0.1 SEE ALSO

[Items](#), [Categories](#), [Views](#), [Quick start](#), [» Index](#)

2.2 Starter Workflows

PURPOSE	Aglet has no fixed application templates. Instead, the same items can serve many purposes by organizing them into views. Here are common ways people set aglet up.
TO-DO LIST	Capture tasks as items. Create a Priority category (exclusive, with High/Normal/Low children) and a Status category. Make a "Today" or "Next" view that includes the categories you want to focus on and excludes Done.
FINANCE	Create numeric categories such as Cost or Amount. Group bills and budget lines into a view with sections per area and a per-section column total (Sum).
PROJECTS	Create a Project category with one child per project. View the same items grouped by project, with columns for status, priority, and effort, or as a Kanban board by status.
KNOWLEDGEBASE	Capture reference notes as items with longer notes attached. Tag them by topic and group them in a research view alongside follow-up tasks that share the same status model.
SCHEDULING	Give items a When date. A datebook view buckets dated items into calendar ranges so upcoming work and deadlines line up.

2.2.0.1 SEE ALSO

[Views](#), [Numeric categories](#), [Datebook views](#), [» Index](#)

2.3 Quick Start

PURPOSE	Get a working database and add your first items.
THE DATABASE	Aglet keeps everything in one SQLite file with a .ag extension. Choose a path; it is created on first use.

You can name the database two ways:

- `--db work.ag` on every command, or
- `AGLET_DB=work.ag` exported once in your shell.

OPEN THE TUI `aglet --db work.ag`

Running `aglet` with no command opens the TUI. On a new database `aglet` creates the reserved categories and the All Items view for you. Press `?` at any time for the in-app help panel.

ADD AN ITEM

1. Press `n` to open the new-item editor.
2. Type an item, such as: Review Work budget Friday
3. Press `Tab` to move to the note field; add longer context.
4. Press `Ctrl-S` to save. (Enter also saves from the title field; `Esc` cancels.)

FROM THE CLI `aglet --db work.ag add "Buy groceries" --note "Milk, eggs"`
`aglet --db work.ag list`

NEXT Add categories (`c`), then a view (`v`) to focus the list.

2.3.0.1 SEE ALSO

[Add an item](#), [Add a category](#), [Create a view](#), [About .ag files](#), [» Index](#)

Chapter 3

Keys and Commands

Chapter 4

Core Concepts

4.1 Items

PURPOSE An item is a line or two of information that you want to keep track of in aglet. You can assign each item to any number of categories.

EXAMPLES

- Call newspapers today to respond to stories about costs.
- Fix database connection pooling.
- Meeting with whole staff every Thursday at 11:00.

PARTS

- Text - the short title (up to about 350 characters).
- Note - optional longer text attached to the item.
- Dates - Entry (created), When (to happen), Done.
- Status - open or done.
- Links - dependencies and relations to other items.

NOTE To add more text than the title holds, attach a note. Aglet parses dates from item text when it can, and matching category names in the text or note can be assigned automatically.

4.1.0.1 SEE ALSO

[Add an item](#), [Notes](#), [Categories](#), [Mark an item done](#), [Dependencies](#), » [Index](#)

4.2 Categories

PURPOSE Categories are names you use to group related items. An item can be assigned to many categories at once (multifiling).

HOW THEY WORK Categories are hierarchical: each category can have a parent and children. You display and change the hierarchy in the category manager.

Priority
High
Normal
Low

TYPES Aglet has two value kinds of category:

KIND	SYMBOL	CONTENTS
Tag		Boolean membership: the item is in it or not.
Numeric	N	Carries a decimal value per item (Cost, Qty).

In addition, categories can be marked Exclusive (only one child assignable per item) and can use automatic assignment (implicit string matching), conditions, and actions.

RESERVED Every database has the reserved categories Done, When, and Entry. They cannot be modified, deleted, or used as child category names.

4.2.0.1 SEE ALSO

Tag categories, Numeric categories, Exclusive categories, The hierarchy, Automatic assignment, Reserved categories, » [Index](#)

4.3 Views

PURPOSE A view is a saved perspective over the same items. Each view can filter to certain categories, hide completed items, group items into sections, and show custom columns. A database can hold many views.

EXAMPLES

- A "Work Queue" view shows open work tasks by priority.
- A "Finance" view shows bills grouped by area with totals.
- A "Projects" view groups the same items by project.
- A "Scheduling" datebook view shows dated items by week.

HOW THEY WORK A view does not own items; it selects them. Add an item and it appears in every view whose criteria it meets. Views are saved lenses, not separate lists.

4.3.0.1 SEE ALSO

Standard views, Datebook views, The All Items view, [Create a view](#), [Sections](#), » [Index](#)

4.4 Sections

PURPOSE A section is a group within a view that collects items matching its own criteria, under a heading. Sections let one view show several lanes of related items.

EXAMPLE A "Calls" section and a "Letters" section in the same view:

Calls

- Call John re: DW deal
- Call Karla for quotes

Letters

- Send Wendy an offer
- Answer client request

HOW THEY WORK Each section has its own include / exclude / OR criteria, and can optionally show its children as sub-groupings. Sections can be laid out stacked vertically or as horizontal lanes (a Kanban board). Each section can carry a column summary such as a total.

FILTERS In Normal mode, / scopes a search to the focused section only; Esc clears that section's filter.

4.4.0.1 SEE ALSO

[Views](#), [Add a section](#), [Columns](#), [Column summaries](#), » [Index](#)

4.5 Columns

PURPOSE A column shows a piece of data next to each item in a section, such as a numeric category value or a date.

TYPES

- Numeric column - shows a numeric category's value per item, and can carry a per-section summary (Sum, Avg, Min, Max).
- Date column - shows a date such as When or Entry.
- Category value - shows whether/which category applies.

IN THE TUI

+ adds a column, - removes one, H / L move it left or right. With the highlight on a column cell, Enter edits that value. f cycles a numeric column's display format; F cycles its summary function. s / S (or < / >) sort the section by the column.

EXAMPLE A finance section with a Cost column and a Sum footer:

Renewals	Cost
• Domain renewal	12.00
• Insurance	480.00
Sum	492.00

4.5.0.1 SEE ALSO

[Add a column](#), [Column summaries](#), [Numeric categories](#), [Format a numeric column](#), [» Index](#)

4.6 Notes

PURPOSE A note lets you add longer information to an item. The title stays short; the note holds the detail.

EXAMPLES

- A meeting agenda attached to a reminder item.
- The full description of a bug attached to a task.
- Reference text for a knowledgebase entry.

HOW TO ADD In the item editor, press Tab to reach the note field and type. To edit a long note in your external editor, press Ctrl-G to open \$EDITOR. From the CLI, use --note, --append-note, or --note-stdin on add and edit.

NOTE Automatic assignment scans note text as well as item text. A category name appearing only in the note can still trigger an automatic assignment.

4.6.0.1 SEE ALSO

[Add a note to an item](#), [Automatic assignment](#), [Edit an item](#), » [Index](#)

4.7 Dependencies

PURPOSE Dependencies are typed links between items. They let aglet track which items are waiting on others.

TYPES	LINK	MEANING
	-----	-----
	depends-on	This item needs the other item done first.
	blocks	This item is the prerequisite of the other (the inverse of depends-on).
	related	A non-blocking, bidirectional association.

BLOCKED An item is "blocked" when it has at least one prerequisite (depends-on) that is not yet done. When the prerequisite is marked done, the dependent item is no longer blocked. Blocked state is computed at query time from the link graph.

HOW TO ADD In the TUI, press b or B to open the link wizard. From the CLI, use "aglet link depends-on", "link blocks", or "link related".

4.7.0.1 SEE ALSO

[Create a dependency](#), [Filter blocked items](#), [The link wizard](#), [Mark an item done](#), » [Index](#)

4.8 Reserved Categories

PURPOSE Every aglet database contains a few built-in categories with special meaning. They are created automatically and cannot be modified, deleted, or reused as child category names.

THE RESERVED CATEGORIES	CATEGORY	MEANING
	-----	-----
	Entry	The date/time the item was created.
	When	The date/time the item is to happen.
	Done	The date/time the item was marked done.

NOTE These categories do not use implicit string matching and are

non-actionable. To create a workflow category that means "finished" under an exclusive Status parent, use a name such as Complete or Completed - not Done, which is reserved.

4.8.0.1 SEE ALSO

[Categories](#), [Mark an item done](#), [Claim an item](#), [» Index](#)

Chapter 5

Category Types

Chapter 6

Category Types

6.1 Tag Categories

PURPOSE A tag category records boolean membership: an item either has it or does not. This is the default kind of category.

EXAMPLES Work, Personal, Urgent, Bug, Frontend, Backend.

HOW TO MAKE `aglet category create "Urgent"`

In the category manager, press n (sibling) or N (child) and type the name.

NOTE A tag category can be a parent of other categories, can be exclusive, and can use automatic assignment, conditions, and actions.

6.1.0.1 SEE ALSO

Numeric categories, [Add a category](#), [Assign a category](#), » [Index](#)

6.2 Numeric Categories

PURPOSE A numeric category carries a decimal value per item, instead of plain membership. The name is up to you: Cost, Miles, Qty, Effort, Amount.

HOW TO MAKE `aglet category create "Cost" --type numeric`

The value lives on the assignment between an item and the category, so each item can have its own Cost.

SET A VALUE `aglet category set-value    Cost 450.00`

In the TUI, put the highlight on the numeric column cell and press Enter, or edit it inline in the item editor's category list. Setting a value for the first time is the usual way to assign a numeric category to an item.

DISPLAY Numeric columns can show a per-section summary (Sum, Avg, Min, Max) and can be formatted with decimals, a currency symbol, and thousands separators.

6.2.0.1 SEE ALSO

[Set a numeric value](#), [Format a numeric column](#), [Columns](#), [Column summaries](#), » [Index](#)

6.3 Exclusive Categories

PURPOSE An exclusive category allows an item to be assigned to only one of its children at a time. Assigning a second child replaces the first.

EXAMPLE Priority (exclusive) with children High, Normal, Low. An item can be High or Normal or Low, but never two at once. Assigning Low to an item already marked High silently switches it to Low.

HOW TO MAKE `aglet category create "Priority" --exclusive`

In the category manager, the details pane shows an Exclusive flag you can toggle.

USES Priority, Status, Stage - anything where exactly one value should apply.

6.3.0.1 SEE ALSO

[Categories](#), [The hierarchy](#), [Assign a category](#), » [Index](#)

6.4 The Category Hierarchy

PURPOSE Categories form a tree. A category can have a parent and any number of children, and the database can have several root categories. The hierarchy groups related categories so you can organize and filter at different levels.

EXAMPLE

- Area
 - Backend
 - Frontend
- Priority [exclusive]
 - High
 - Normal
 - Low

WHERE You see and change the hierarchy in the category manager (c or F9). H/J/K/L reorder a category; << and >> change its depth.

NOTE A category cannot be deleted while it still has children; reparent or delete the children first. Reparenting to the root level is done with --root on the CLI.

6.4.0.1 SEE ALSO

[Organize the hierarchy](#), [Subsumption](#), [Discard a category](#), [» Index](#)

6.5 Subsumption

PURPOSE Subsumption is the rule that assigning a child category also implies its parent. If an item is in Backend, it is also treated as being in Backend's parent, Area.

EXAMPLE Assigning "Backend" to an item makes it match a view that filters on "Area", because Backend is a child of Area. The parent assignment is shown with reason "Subsumption".

WHY Subsumption lets you filter broadly (everything in Area) or narrowly (just Backend) from the same assignments, without tagging each item twice.

6.5.0.1 SEE ALSO

The hierarchy, [The assignment profile](#), [View criteria](#), [» Index](#)

Chapter 7

View Types

Chapter 8

View Types

8.1 Standard Views

PURPOSE	A standard view displays any items and any categories, filtered by criteria and optionally grouped into sections. It is the general-purpose view type.
CRITERIA	• Include - item must have ALL of these categories (AND). • OR-include - item must have AT LEAST ONE of these. • Exclude - item must have NONE of these.
LAYOUT	Items can be shown one line each or multi-line, and sections can be stacked vertically or arranged as horizontal lanes for a Kanban board (toggle with m).

8.1.0.1 SEE ALSO

[Views](#), [View criteria](#), [Datebook views](#), [Create a view](#), [» Index](#)

8.2 Datebook Views

PURPOSE	A datebook view buckets dated items into calendar ranges, so upcoming work, appointments, renewals, and deadlines line up by date.
CONFIGURE	A datebook view has: • A date source - When, Entry, Done, or a date category. • A period - day, week, month, and so on. • An interval - how many periods per bucket.

- An anchor - where the buckets start.

BROWSE In the TUI, { and } step buckets, (and) step the window, and 0 jumps to today. From the CLI, "aglet view datebook-browse" shifts the window with --offset and --step.

NOTE You create a datebook view with "aglet view create-datebook"; a standard view and a datebook view are different types and one cannot be converted to the other.

8.2.0.1 SEE ALSO

[Create a datebook view](#), [Browse a datebook view](#), [Datebook keys](#), » [Index](#)

8.3 The All Items View

PURPOSE All Items is the built-in view that shows every item in the database with no filtering. It is created automatically and is a system view.

ACCESS In the TUI, press ga to jump to it. From the CLI:
aglet view show "All Items"

NOTE All Items is immutable - you cannot edit or delete it - but you can clone it into a new, mutable view if you want a copy to customize. "aglet list" without --view uses All Items when it is present, then falls back to the first stored view.

8.3.0.1 SEE ALSO

[Views](#), [Clone a view](#), [Create a view](#), » [Index](#)

Chapter 9

Auto-Assignment

9.1 Automatic Assignment (Implicit String Matching)

PURPOSE Let aglet file items for you when a category name appears in an item's text or note.

HOW IT WORKS When implicit string matching is enabled for a category, aglet checks both the item title and the full note text. If the category name is present, the category is assigned automatically. Assigning a child also subsumes its parent. These live matches can break automatically if the text changes; manual, action, and accepted-suggestion assignments remain sticky.

EXAMPLES Adding "Refactor Backend auth module" auto-assigns Backend (and its parent Area) because "Backend" appears in the title.

NOTE Command examples or acceptance criteria inside a note can accidentally match categories such as Ready, CLI, or TUI. Inspect "aglet show" provenance before assuming an assignment was manual. Turning off `enable_implicit_string` evicts live matches but not older sticky derived assignments.

9.1.0.1 SEE ALSO

[Categories](#), [Assign a category](#), [Profile conditions](#), [Subsumption](#), [Review suggestions](#), » [Index](#)

Chapter 10

Aglet TUI Guide

[« Home](#) | [Concepts](#) | [CLI Reference](#)

10.1 How to Use This Manual

PURPOSE Complete guide to the aglet terminal interface: keybindings, interactive workflows, and the view/category editors. For scripting and batch use see the CLI Reference.
Core concepts are in the Concepts Reference.

10.1.0.1 SEE ALSO

[Home](#)

10.2 Index

KEYS AND COMMANDS

- TUI: Normal Mode Keys
- TUI: Category Manager Keys
- TUI: View Editor Keys
- TUI: Item Editor Keys
- TUI: Datebook Keys

WORKING WITH ITEMS

- Add an Item
- Edit an Item
- Add a Note to an Item

- Mark an Item Done
- Recurrence
- Delete an Item
- Restore a Deleted Item
- Move an Item Between Sections
- Search Items
- Select Multiple Items

WORKING WITH CATEGORIES

- Add a Category
- Assign a Category to an Item
- Unassign a Category
- Review Classification Suggestions
- Set a Numeric Value
- Format a Numeric Column
- Organize the Category Hierarchy
- Discard a Category

WORKING WITH VIEWS

- Create a View
- View Criteria
- Add a Section to a View
- Add a Column to a Section
- Column Summary Functions
- Create a Datebook View
- Browse a Datebook View
- The View Editor
- View Aliases
- Clone a View
- Discard a View

WORKING WITH DEPENDENCIES

- Create a Dependency Link
- Remove a Link
- Filter Blocked / Not-Blocked Items
- The Link Wizard

SETTINGS AND INDICATORS

- Global Settings
- The Status and Hint Footer
- The Item Assignment Profile

Chapter 11

Keys and Commands

11.1 TUI: Normal Mode Keys

PURPOSE	Normal mode is the main board where items are displayed. These keys work while the highlight is on an item or column.
ITEMS	n Add a new item to the focused section e / Enter Edit selected item (Enter adds when empty) a Assign categories to current item or selection d / D Toggle done on selected item(s) r / x Remove from view / delete selected item(s) b / B Open dependency link wizard (blocked-by/blocks) = Classify selected item(s) now p / i / o Toggle preview sidebar / cycle preview mode
SELECTION	Space Toggle selection on current item a / d / x / = .. Batch assign, done, delete, or classify b / B Link selected items with a dependency Esc Clear selection
NAVIGATION	Up/k Down/j Move between items; scroll preview when focused Left/h Right/l . Move between sections or columns Tab / S-Tab Next / previous section (J/K jump section) [/] Move item to previous / next section (or S-Up/S-Down) m / z Cycle lane layout / card size
SEARCH	/ Search the focused section g/ Search all sections

	Esc Clear the active section filter
COLUMNS	Enter Edit column value (on a column cell)
	+ / - Add / remove a board column
	H / L Move board column left / right
	f Cycle numeric column format
	F Cycle column summary (Sum/Avg/Min/Max)
	s / S or < / > . Sort section by column (ascending/descending)
VIEWS	v / V / F8 Open the view picker
	, / Previous / next view
	ga Jump to the All Items view
DATEBOOK	{ / } Step previous / next date bucket
	(/) Step the browse window
	0 Jump to today
GLOBAL	C Review pending classification suggestions
	g s / F10 Open Global Settings
	c / F9 Open the category manager
	u Toggle the hide-dependent-items filter
	Ctrl-L Reload data from disk
	Ctrl-Z Undo
	Ctrl-Shift-Z ... Redo
	? Toggle the help panel
	q Quit

11.1.0.1 SEE ALSO

Category manager keys, View editor keys, Select multiple items, » [Index](#)

11.2 TUI: Category Manager Keys

PURPOSE	The category manager is a full-screen mode for working with the category hierarchy. Open it with c or F9; press Esc to return.
NAVIGATION	Up/k Down/j Move through the category tree
	Tab Move focus between the tree and the details pane
EDIT	n Create a sibling at the selected level
	N Create a child of the selected category
	e / F2 Edit the selected category name

	S / Ctrl-S Save category edits
	Esc Return to the main view
REORDER	H / J / K / L .. Reorder the selected category
	<< / >> Change the category's depth (promote / demote)
DETAILS	The details pane shows flags (Exclusive, Auto-match, Actionable), the value type (Tag or Numeric), conditions, actions, and a free-form note. Workflow roles (such as the claim category) are set in Global Settings.

11.2.0.1 SEE ALSO

[Categories](#), Organize the category hierarchy, [Actions](#), » [Index](#)

11.3 TUI: View Editor Keys

PURPOSE	The view editor configures a view's filter criteria, sections, columns, layout, and aliases.
NAVIGATION	Tab Move between the editor regions (such as SECTIONS and DETAILS) Up/k Down/j Move within a region
EDIT	Edit criteria (include / exclude / OR-include), date ranges, display mode (single-line or multi-line), section flow (vertical stacked or horizontal lanes), unmatched-item visibility, and category aliases.
SAVE	S / Ctrl-S Save the view Esc Cancel without saving
NOTE	Section and per-section filters are reset when you switch views or save the editor.

11.3.0.1 SEE ALSO

[Views](#), Create a view, View criteria, View aliases, » [Index](#)

11.4 TUI: Item Editor Keys

PURPOSE	The item editor (opened with n to add or e to edit) is a panel
---------	--

with a title field, a note field, and an inline category list.

FIELDS	Tab / S-Tab Cycle focus: Title -> Note -> Categories -> Save -> Cancel Ctrl-S Save from any field Enter Save from the title field Esc Cancel
CATEGORIES	Within the inline category list: j / k Move through categories Space Toggle a tag assignment (a numeric category shows an inline editable value field) / Filter the category list n Create a new category inline
NOTES	Ctrl-G Open \$EDITOR to edit the title or note in your external editor

11.4.0.1 SEE ALSO

Add an item, Edit an item, Add a note, Assign a category, » [Index](#)

11.5 TUI: Datebook Keys

PURPOSE	A datebook view buckets dated items into calendar ranges. These keys move the visible date window.
KEYS	{ Step to the previous date bucket } Step to the next date bucket (..... Step the browse window backward) Step the browse window forward 0 Jump to today
NOTE	A datebook view groups items by a date source (When, Entry, Done, or a date category) over a period such as day, week, or month.

11.5.0.1 SEE ALSO

[Datebook views](#), Create a datebook view, Browse a datebook view, » [Index](#)

Chapter 12

Working with Items

12.1 Add an Item

PURPOSE Add a new item to the database. An item is a single line of free-form text, optionally with a longer note.

TUI STEPS

1. Press `n` to open the new-item editor (the item is added to the focused section).
2. Type the item text, such as "Review Work budget Friday".
3. Press `Tab` to move to the Note field and the inline category checklist if you want to add detail or assignments.
4. Press `Ctrl-S` to save from any field. `Enter` also saves from the title field; `Esc` cancels.

CLI STEPS

```
aglet add "Review Work budget Friday"
aglet add "Pay insurance" --note "Renews annually in March"
```

HOW IT WORKS When an item is saved, `aglet` scans its text and note against category names. Categories whose names appear are assigned automatically (see Automatic assignment), and recognizable dates are parsed into the When date. The CLI prints the new item id and a `new_assignments` count.

NOTE Short item-id prefixes returned by "aglet add" can be used anywhere an item id is accepted. Parse the "created " line for the id; it is not always the last line of output.

12.1.0.1 SEE ALSO

[Items](#), [Edit an item](#), [Automatic assignment](#), [Add a note](#), [Item editor keys](#), [» Index](#)

12.2 Edit an Item

PURPOSE Change an item's text, note, or done state.

TUI STEPS

1. Select the item.
2. Press e (or Enter) to open the editor.
3. Edit the text or Tab to the note. Toggle inline category assignments if desired.
4. Press Ctrl-S to save, Esc to cancel.

CLI STEPS

```
aglet edit --text "New title"
aglet edit --note "Updated note text"
aglet edit --done           # mark done
aglet edit --not-done       # reopen
```

HOW IT WORKS Editing text re-runs automatic assignment: implicit-string matches may be added or evicted, but manual and accepted-suggestion assignments stay sticky. Press Ctrl-G in the TUI text or note field to open the item in \$EDITOR.

NOTE On an empty section, pressing Enter starts a new item rather than editing.

12.2.0.1 SEE ALSO

[Add an item](#), [Add a note](#), [Mark an item done](#), [Automatic assignment](#), [» Index](#)

12.3 Add a Note to an Item

PURPOSE Attach a longer body of text to an item. Notes hold detail that does not belong in the one-line title.

TUI STEPS

1. Open the item with e (or n for a new item).
2. Press Tab to move from the title to the Note field.
3. Type freely; the note is multi-line.
4. Press Ctrl-G to edit the note in \$EDITOR for longer text.
5. Press Ctrl-S to save.

CLI STEPS	<pre>aglet add "Plan offsite" --note "Book venue, send agenda" aglet edit --note "Revised plan"</pre>
HOW IT WORKS	Note text participates in automatic assignment: a category name appearing only in the note still triggers an implicit-string match. Inspect "aglet show" provenance before assuming a visible category was assigned manually.
NOTE	In compact list output an item with a note shows a note marker; use --verbose or "aglet show" to read the full note.

12.3.0.1 SEE ALSO

[Notes](#), [Edit an item](#), [Automatic assignment](#), [» Index](#)

12.4 Mark an Item Done

PURPOSE	Record that an item is complete. Done is a reserved category that also drives recurrence and dependency resolution.
TUI STEPS	Select an item (or several with Space) and press d to toggle done. D toggles done on the whole current selection.
CLI STEPS	<pre>aglet edit --done aglet edit --not-done</pre>
HOW IT WORKS	Completing an item assigns the reserved Done category. A done prerequisite no longer blocks items that depend on it. If the item carries a recurrence rule, completing it schedules the next occurrence (see Recurrence).
NOTE	Done items are hidden from most views that exclude Done and from "aglet list" unless you pass --include-done.

12.4.0.1 SEE ALSO

[Reserved categories](#), [Recurrence](#), [Dependencies](#), [» Index](#)

12.5 Recurrence

PURPOSE	Make an item repeat on a schedule. When a recurring item is completed, aglet generates the next occurrence automatically.
---------	---

HOW IT WORKS A recurrence rule is attached to a dated item. Completing the current occurrence (marking it Done) advances the When date to the next scheduled date and reopens the item, so recurring chores, bills, and maintenance reappear without re-entry.

EXAMPLES A monthly "Pay insurance" item set to recur reappears with next month's date each time you mark it done.

NOTE Recurrence works together with the reserved When and Done categories.

12.5.0.1 SEE ALSO

Mark an item done, [Reserved categories](#), [Datebook views](#), » [Index](#)

12.6 Delete an Item

PURPOSE Remove an item from the database. Deletion is logged so the item can be restored.

TUI STEPS Select the item(s) and press x to delete. (Press r to remove an item from the current view without deleting it from the database.)

CLI STEPS

```
aglet delete
aglet deleted          # list deletion-log entries
aglet restore          # restore by log entry id
```

HOW IT WORKS Deleting writes a deletion-log entry rather than erasing the item immediately. "aglet deleted" lists log entries with their ids; "aglet restore" brings an item back.

NOTE r (remove from view) and x (delete) are different. Remove only changes view membership; delete affects the whole database.

12.6.0.1 SEE ALSO

Restore a deleted item, [Items](#), [CLI item commands](#), » [Index](#)

12.7 Restore a Deleted Item

PURPOSE Bring back an item that was deleted, using the deletion log.

CLI STEPS	1. <code>aglet deleted</code> # find the log entry id 2. <code>aglet restore</code> # restore that entry
HOW IT WORKS	Every delete appends an entry to the deletion log. Restoring recreates the item with its text, note, and recorded state.
NOTE	Restore brings the item back exactly as it was deleted; the deletion log keeps a history you can recover from.

12.7.0.1 SEE ALSO

Delete an item, [CLI item commands](#), » [Index](#)

12.8 Move an Item Between Sections

PURPOSE	Reposition an item into a different section of the current view.
TUI STEPS	Select the item and press <code>[</code> to move it to the previous section or <code>]</code> to move it to the next section. Shift-Up and Shift-Down do the same. Use <code>h/l</code> (or Left/Right) to move between sections or columns, and <code>Tab</code> / <code>Shift-Tab</code> to move focus between sections.
HOW IT WORKS	Sections in a standard view are defined by category criteria. Moving an item between sections adjusts its category assignments so it matches the destination section's criteria.
NOTE	In horizontal (kanban) lane layouts, moving an item between lanes is the same operation; <code>aglet</code> remembers the per-lane selection.

12.8.0.1 SEE ALSO

[Sections](#), Add a section, Normal mode keys, » [Index](#)

12.9 Search Items

PURPOSE	Find items by text in their title or note.
TUI STEPS	Press <code>/</code> to search within the focused section, or <code>g/</code> to search across all sections. Type the query; press <code>Esc</code> to clear the active section filter.

CLI STEPS	<pre>aglet search "budget" aglet search "budget" --not-blocked</pre>
HOW IT WORKS	CLI and TUI search both route through the same matcher over item title and note text. Per-section filters in the TUI are scoped to the focused section and reset on view switch.
NOTE	Search matches note text, so a query can match items whose title does not contain the term.

12.9.0.1 SEE ALSO

[Items](#), [Select multiple items](#), [CLI filtering](#), [» Index](#)

12.10 Select Multiple Items

PURPOSE	Operate on several items at once - assign, complete, delete, or classify them together.
TUI STEPS	1. Press Space to toggle selection on the current item; repeat to build a selection. 2. Apply a batch operation: a (assign categories), d (done), x (delete), = (classify now), or b / B (link with a dependency). 3. Press Esc to clear the selection.
HOW IT WORKS	Selection lets a single command act on many items at once. Batch operations act on every selected item.
NOTE	With no explicit selection, the same keys act on the single item under the cursor.

12.10.0.1 SEE ALSO

[Assign a category](#), [Mark an item done](#), [Create a dependency](#), [Review suggestions](#), [» Index](#)

Chapter 13

Working with Categories

13.1 Add a Category

PURPOSE Create a new category - the basic filing unit. Categories can be top-level or nested under a parent.

TUI STEPS

1. Press `c` or `F9` to open the category manager.
2. Press `n` to create a category at the selected level, or `N` to create a child of the selected category.
3. Type the name (Work, Personal, Urgent, ...).
4. Adjust flags such as exclusive, implicit matching, and notes in the details pane.
5. Press `Ctrl-S` to save, `Esc` to return.

CLI STEPS

```
aglet category create "Work"
aglet category create "High" --parent Priority
aglet category create "Priority" --exclusive
aglet category create "Cost" --type numeric
```

NOTE The reserved names Done, When, and Entry cannot be used. For a workflow child under an exclusive Status parent, use names such as Complete or Completed, not Done.

13.1.0.1 SEE ALSO

[Categories](#), [Tag categories](#), [Numeric categories](#), [Exclusive categories](#), [Organize the hierarchy](#), » [Index](#)

13.2 Assign a Category to an Item

PURPOSE	Manually file an item under a category.
TUI STEPS	1. Select the item (or several with Space). 2. Press a to open the inline category picker. 3. Press Space to toggle a category's assignment without closing, or Enter to apply the current result and close. 4. Press / to filter; from the filter box Tab, Shift-Tab, Up, or Down returns focus to the narrowed list.
CLI STEPS	<pre>aglet category assign Work aglet category assign High</pre>
HOW IT WORKS	Manual assignments are durable user choices: they stay sticky even when text changes. Assigning a child also displays its parent (assigning High also shows Priority). For exclusive parents, only one child can be assigned.
NOTE	Use the inline checklist in the item editor to assign categories while adding or editing an item.

13.2.0.1 SEE ALSO

Unassign a category, [Automatic assignment](#), [Exclusive categories](#), Set a numeric value, » [Index](#)

13.3 Unassign a Category

PURPOSE	Remove a category from an item.
TUI STEPS	Press a on the item, then Space on the assigned category to toggle it off; Enter applies and closes.
CLI STEPS	<pre>aglet category unassign Work</pre>
HOW IT WORKS	Unassigning removes the explicit assignment row and reprocesses the item. If the category still matches by implicit string or profile condition, a live (non-sticky) assignment may reappear; sticky manual/action/accepted-suggestion assignments do not.
NOTE	To stop a category from auto-matching entirely, turn off its

implicit-string matching rather than repeatedly unassigning.

13.3.0.1 SEE ALSO

Assign a category, [Automatic assignment](#), Discard a category, [» Index](#)

13.4 Review Classification Suggestions

PURPOSE	Accept or reject category suggestions, including experimental LLM-based ones, before they are applied.
TUI STEPS	Press = to classify the selected item(s) now. Press C to review pending classification suggestions in the suggestion-review mode, where you can accept or dismiss each one.
HOW IT WORKS	Classification proposes categories for an item from its text and rules. Accepting a suggestion creates a sticky assignment; dismissing it does not. It runs aglet's rule-based and LLM-based suggestions on demand for review.
NOTE	aglet has experimental support for LLM-based categorization in addition to implicit-string and profile-condition matching.

13.4.0.1 SEE ALSO

[Automatic assignment](#), [Profile conditions](#), Assign a category, [» Index](#)

13.5 Set a Numeric Value

PURPOSE	Give an item a number under a numeric category - a cost, quantity, mileage, or effort estimate.
TUI STEPS	On a numeric column cell, press Enter to edit the value inline. In the item editor's inline category list, an assigned numeric category shows - [N] with an editable value field.
CLI STEPS	aglet category set-value Cost 450.00
HOW IT WORKS	The value is stored on the assignment edge between the item and the numeric category. A numeric column then displays the value and can be summarized per section (sum, average, min, max).

NOTE Editing a numeric column cell is the primary way to assign a value to an item for the first time.

13.5.0.1 SEE ALSO

[Numeric categories](#), [Format a numeric column](#), [Column summaries](#), [Add a column](#), [» Index](#)

13.6 Format a Numeric Column

PURPOSE Control how a numeric category's values are displayed - decimal places, currency, and thousands separators.

TUI STEPS On a numeric column, press `f` to cycle the column's display format.

CLI STEPS `aglet category format ...`

HOW IT WORKS Formatting is a display property of the numeric category; it does not change the stored value. The same value can appear as 1450, 1,450.00, or \$1,450.00 depending on format.

NOTE Use `F` (capital) to cycle the column's summary function; `f` sets the value format. See [Column summaries](#).

13.6.0.1 SEE ALSO

[Numeric categories](#), [Set a numeric value](#), [Column summaries](#), [» Index](#)

13.7 Organize the Category Hierarchy

PURPOSE Rearrange categories - reparent, promote, demote, and reorder siblings.

TUI STEPS In the category manager, use `H/J/K/L` to reorder and move categories, and `<< / >>` to change a category's depth level.

CLI STEPS

```
aglet category reparent --parent
aglet category reparent --root      # make top-level
aglet category rename "New Name"
```

HOW IT WORKS Child order matters for exclusive parents: when several derived siblings match, the earlier child in parent order wins. Manual and

accepted-suggestion assignments remain durable regardless of order.

NOTE Workflow roles (which categories mean Ready, claim-target, etc.) are set in Global Settings, not by hierarchy position.

13.7.0.1 SEE ALSO

[The category hierarchy](#), [Exclusive categories](#), [Subsumption](#), [Global settings](#), [» Index](#)

13.8 Discard a Category

PURPOSE Delete a category you no longer need.

TUI STEPS In the category manager, select the category and delete it.

CLI STEPS `aglet category delete "Old Category"`

HOW IT WORKS Deleting a category removes it and its assignments. Reserved categories (Done, When, Entry) cannot be deleted.

NOTE Consider turning off implicit matching instead of deleting if you only want to stop auto-assignment but keep past filings.

13.8.0.1 SEE ALSO

[Add a category](#), [Unassign a category](#), [Reserved categories](#), [» Index](#)

Chapter 14

Working with Views

14.1 Create a View

PURPOSE Save a lens over the item database - a filtered, sectioned, and columned presentation you can return to.

TUI STEPS

1. Press `v`, `V`, or `F8` to open the view picker.
2. Press `n` to create a new view and name it (Work Queue).
3. Add include/exclude criteria and any sections.
4. Press `Ctrl-S` (or `S`) to save.

CLI STEPS

```
aglet view create "Work Queue" --include Work --exclude Done
aglet view list
aglet view show "Work Queue"
```

HOW IT WORKS A view stores its criteria, sections, columns, layout, and aliases. It updates automatically as items are added or reassigned.

NOTE Include criteria are AND-based: `--include Work --include Urgent` matches only items with both categories.

14.1.0.1 SEE ALSO

[Views](#), [View criteria](#), [Add a section](#), [The view editor](#), [Clone a view](#), [» Index](#)

14.2 View Criteria

PURPOSE Control which items a view includes.

CLI STEPS `aglet view create "My View" --include High --include Pending`
 `aglet view edit ...`

HOW IT WORKS Include filters are AND-based - every included category must be present. Do not use repeated includes for mutually exclusive siblings such as Pending and In Progress; use separate sections or views instead. Views also persist `hide_dependent_items`, which hides items that are blocked dependents.

NOTE Toggle the hide-dependent-items filter in the TUI with `u`.

14.2.0.1 SEE ALSO

Create a view, [CLI filtering](#), Filter blocked items, Add a section, » [Index](#)

14.3 Add a Section to a View

PURPOSE Group a view's items into labelled lanes by category criteria.

CLI STEPS `aglet view section add ...`
 `aglet view section update ...`
 `aglet view section remove ...`

TUI STEPS Open the view editor (from the view picker), focus the SECTIONS pane, and add or edit sections there.

HOW IT WORKS Each section has its own include criteria. Items that match land in that section; section flow can be vertical (stacked) or horizontal (kanban lanes). Unmatched-item visibility is a view setting.

NOTE Moving an item between sections adjusts its category assignments to match the destination section.

14.3.0.1 SEE ALSO

[Sections](#), Add a column, Move an item between sections, The view editor, » [Index](#)

14.4 Add a Column to a Section

PURPOSE Show a numeric category's value as a column beside each item, with

an optional per-section summary.

TUI STEPS Press + to add a board column and - to remove one. Use H / L to move a column left or right, and Enter on a column cell to edit a value.

CLI STEPS aglet view column add ...
aglet view column update ...
aglet view column remove ...

HOW IT WORKS Columns display numeric category values. Each column can carry a summary function shown in the section footer.

NOTE Columns are numeric in aglet; there is no free-text column type.

14.4.0.1 SEE ALSO

[Columns](#), [Column summaries](#), [Set a numeric value](#), [Format a numeric column](#), »
[Index](#)

14.5 Column Summary Functions

PURPOSE Aggregate a numeric column across a section - a total, average, or extreme.

TUI STEPS Press F to cycle a numeric column's summary (Sum / Avg / Min / Max). Sort a section by a column with s / S (or < / >).

CLI STEPS aglet view set-summary ...

HOW IT WORKS The summary is computed over the items in the section and shown in the section footer - for example a budget total or average effort.

NOTE f cycles the value display format; F cycles the summary function.

14.5.0.1 SEE ALSO

[Add a column](#), [Numeric categories](#), [Format a numeric column](#), » [Index](#)

14.6 Create a Datebook View

PURPOSE Build a view that buckets dated items into calendar ranges.

CLI STEPS `aglet view create-datebook "Scheduling" ...`

HOW IT WORKS A datebook view is a distinct view type that groups items by their When date into date-interval buckets (days, weeks, etc.). It is ideal for upcoming work, appointments, renewals, and deadlines.

NOTE A standard view and a datebook view are different types; one cannot be converted into the other.

14.6.0.1 SEE ALSO

[Datebook views](#), Browse a datebook view, [Date conditions](#), Datebook keys, [» Index](#)

14.7 Browse a Datebook View

PURPOSE Move the visible date window of a datebook view forward and back.

TUI STEPS { and } step to the previous / next bucket. (and) step the window. 0 jumps to today.

CLI STEPS `aglet view datebook-browse ...`

HOW IT WORKS Browsing shifts which date interval is shown without changing the view definition.

NOTE 0 (today) is the quickest way to recenter after browsing.

14.7.0.1 SEE ALSO

Create a datebook view, [Datebook views](#), Datebook keys, [» Index](#)

14.8 The View Editor

PURPOSE Configure a view's filters, sections, columns, layout, aliases, and preview behavior in one screen.

TUI STEPS Open a view in the editor from the view picker. Tab moves between regions (Criteria, Datebook, Sections, Unmatched). Enter operates the focused row or inline input. Save with S or Ctrl-S.

HOW IT WORKS The editor edits mutable view properties: include/exclude

criteria, date ranges, display mode (single- or multi-line), section flow (stacked or lanes), unmatched-item visibility, and category aliases. A live preview reflects changes.

NOTE The All Items view is immutable; clone it first to edit a copy.

14.8.0.1 SEE ALSO

Create a view, View criteria, Add a section, View aliases, View editor keys, » [Index](#)

14.9 View Aliases

PURPOSE Show a category under a different display name inside one view, without changing the category itself.

CLI STEPS `aglet view alias set "Display Name"`
`aglet view alias clear`

HOW IT WORKS An alias is per-view display metadata mapping a category to a label. It affects only how the category is shown in that view.

NOTE Aliases do not change category identity, filters, section titles, generated subsection labels, or board column headings.

14.9.0.1 SEE ALSO

The view editor, [Views](#), [CLI view commands](#), » [Index](#)

14.10 Clone a View

PURPOSE Make an editable copy of an existing view, including the immutable All Items view.

CLI STEPS `aglet view clone "All Items" "My Items"`

HOW IT WORKS Cloning copies the source view's criteria, sections, columns, and settings into a new, mutable view that you can then customize.

NOTE Cloning is the way to start from All Items, which cannot itself be edited.

14.10.0.1 SEE ALSO

Create a view, [The All Items view](#), Discard a view, » [Index](#)

14.11 Discard a View

PURPOSE Delete a view you no longer need.

CLI STEPS

```
aglet view delete "Old View"
aglet view rename "Old Name" "New Name"
```

HOW IT WORKS Deleting a view removes the saved presentation only; the items it showed remain in the database. The All Items view cannot be deleted.

NOTE Deleting a view never deletes items - it only discards the lens.

14.11.0.1 SEE ALSO

Create a view, Clone a view, [The All Items view](#), » [Index](#)

Chapter 15

Working with Dependencies

15.1 Create a Dependency Link

PURPOSE	Record that one item must wait for another, or relate two items.
TUI STEPS	Press <code>b</code> or <code>B</code> on an item (or selection) to open the dependency link wizard and choose the blocked-by / blocks relationship.
CLI STEPS	<code>aglet link depends-on</code> <code>aglet link blocks</code> <code>aglet link related</code>
HOW IT WORKS	<code>depends-on</code> and <code>blocks</code> are two vocabularies for the same directed relationship; <code>related</code> is bidirectional. An item with an unresolved <code>depends-on</code> prerequisite is "blocked". Done prerequisites do not block.
NOTE	Do not create synthetic links to mean "someone is working on this" - use <code>claim</code> for that. Links are for real prerequisites.

15.1.0.1 SEE ALSO

[Dependencies](#), [Remove a link](#), [Filter blocked items](#), [The link wizard](#), » [Index](#)

15.2 Remove a Link

PURPOSE	Delete a dependency or related link between two items.
CLI STEPS	<code>aglet unlink depends-on</code>

```
aglet unlink blocks
aglet unlink related
```

HOW IT WORKS Removing the last unresolved depends-on prerequisite unblocks the dependent item, which can make it claimable again.

NOTE unlink is the canonical entry point; the depends-on and blocks forms remove the same underlying relationship from either direction.

15.2.0.1 SEE ALSO

Create a dependency, [Dependencies](#), Filter blocked items, » [Index](#)

15.3 Filter Blocked / Not-Blocked Items

PURPOSE Show only items that are waiting on a prerequisite, or only those that are free to start.

TUI STEPS Press u to toggle the hide-dependent-items filter for the current view.

CLI STEPS

```
aglet list --blocked
aglet list --not-blocked
aglet search --blocked
aglet view show "" --not-blocked
```

HOW IT WORKS blocked means the item has at least one unresolved depends-on prerequisite, computed at query time from the dependency graph. Done dependencies do not count.

NOTE Dependency-state filters are derived, not assignable categories; you cannot assign "blocked" to an item.

15.3.0.1 SEE ALSO

[Dependencies](#), Create a dependency, [The ready list](#), [CLI filtering](#), » [Index](#)

15.4 The Link Wizard

PURPOSE Create dependency links interactively in the TUI.

TUI STEPS Press `b` or `B` on an item or a multi-item selection to open the wizard, then pick the other item and the relationship direction (blocked-by or blocks).

HOW IT WORKS The wizard writes the same depends-on / blocks links as the CLI. With a selection, it can link several items at once.

NOTE Use the wizard for prerequisites; use claim/release for "who is working on it".

15.4.0.1 SEE ALSO

Create a dependency, Select multiple items, [CLI link commands](#), » [Index](#)

Chapter 16

Settings and Indicators

16.1 Global Settings

PURPOSE	Adjust application-wide preferences and workflow roles.
TUI STEPS	Press <code>g s</code> or <code>F10</code> to open Global Settings.
HOW IT WORKS	Global Settings control display and behavior preferences such as auto-refresh, section borders, note glyphs, and search mode, and they define workflow roles - which categories act as Ready and as the claim target used by claim/release/ready.
NOTE	Workflow roles live here, not in the category hierarchy; reorder or rename categories without changing which one is "Ready".

16.1.0.1 SEE ALSO

[Claim an item](#), [The ready list](#), [Organize the hierarchy](#), [» Index](#)

16.2 The Status and Hint Footer

PURPOSE	Read the two-row footer at the bottom of the TUI.
HOW IT WORKS	The footer has two rows. The top row shows transient status - the result of your last action or a brief message. The bottom row shows persistent key hints for the current mode, so the available keys change as you move between Normal view, the category manager, the view editor, and the item editor.

NOTE Press ? at any time to open the full in-app help panel, which lists every key for the current context.

16.2.0.1 SEE ALSO

Normal mode keys, Assignment profile, » [Index](#)

16.3 The Item Assignment Profile

PURPOSE Understand the assignments and provenance shown by "aglet show".

HOW IT WORKS "aglet show" prints an item's text, note, status, and its assignments. Displayed category lists include both assigned categories and their parents (assigning High also shows Priority). Provenance distinguishes manual assignments from auto-classified ones (implicit_string or other providers), so you can see why a category is present.

NOTE Implicit matches scan the note as well as the title, so a category can appear because of text inside the note. Check provenance before assuming a visible category was set by hand.

16.3.0.1 SEE ALSO

[Automatic assignment](#), Assign a category, [Categories](#), [CLI item commands](#), » [Index](#)

Chapter 17

Aglet CLI Reference

[« Home](#) | [Concepts](#) | [TUI Guide](#)

17.1 How to Use This Manual

PURPOSE Complete reference for the aglet command-line interface.
For interactive use see the
TUI Guide.
Core concepts are in the
Concepts Reference.

17.1.0.1 SEE ALSO

[Home](#)

17.2 Index

OVERVIEW

- About the CLI
- The AGLET_DB Environment Variable
- About .ag Files
- CLI: Command Chart

ITEM COMMANDS

- CLI Item Commands

CATEGORY COMMANDS

- CLI Category Commands
- Profile Conditions

Date Conditions

Actions

VIEW COMMANDS

CLI View Commands

LINK COMMANDS

CLI Link Commands

FILTERING AND SORTING

CLI Filtering and Sorting

IMPORT AND EXPORT

CLI Import and Export

WORKFLOW COMMANDS

Claim an Item

Release a Claim

The Ready List

Chapter 18

Overview

18.1 About the CLI

PURPOSE Drive aglet from the command line - useful for scripting and for LLM coding agents.

USAGE aglet [--db]

HOW IT WORKS Running aglet with no subcommand opens the TUI; with a subcommand it performs that action and exits. Short item-id prefixes work anywhere an item id is accepted (case-insensitive, hyphens stripped); an ambiguous prefix returns an error listing the matches. list and search default to compact one-line rows; use --verbose for multi-line output and --format json for scripts.

EXAMPLES aglet --db notes.ag list
aglet --db notes.ag add "Buy groceries"

NOTE aglet list without --view uses All Items when present, then the first stored view.

18.1.0.1 SEE ALSO

CLI command chart, CLI item commands, CLI category commands, CLI view commands, The AGLET_DB variable, » [Index](#)

18.2 The AGLET_DB Environment Variable

PURPOSE Choose which database aglet acts on without repeating --db.

HOW IT WORKS The CLI reads the database path from `--db` or, if that is absent, the `AGLET_DB` environment variable. Set `AGLET_DB` once in your shell to run a series of commands against the same file.

EXAMPLES

```
export AGLET_DB=~/.notes.ag
aglet list
aglet add "Pick up parts"
```

NOTE `--db` on a single command overrides `AGLET_DB` for that command.

18.2.0.1 SEE ALSO

About .ag files, About the CLI, » [Index](#)

18.3 About .ag Files

PURPOSE Understand where aglet keeps your data.

HOW IT WORKS An aglet database is a single SQLite file with the .ag extension. It holds every item, category, view, link, and the deletion log. A new database is created automatically with the built-in categories (Done, When, Entry) and the All Items view the first time you open it.

EXAMPLES

```
cargo run --bin aglet -- --db getting-started.ag
```

NOTE Because the database is one file, you back it up or move it by copying that file. Schema repair runs idempotently on open.

18.3.0.1 SEE ALSO

The `AGLET_DB` variable, [Reserved categories](#), About the CLI, » [Index](#)

18.4 CLI: Command Chart

COMMAND	PURPOSE
-----	-----
add	Add a new item
edit	Edit an item's text, note, and/or done state
show	Show a single item with its assignments
list	List items (optionally filtered)

search	Search item text and note
export	Export items as Markdown
delete	Delete an item (writes a deletion log entry)
deleted	List deletion log entries
restore	Restore an item from the deletion log
claim	Atomically claim an eligible item for active work
ready	List items eligible to be claimed
release	Remove the active claim category (alias: unclaim)
tui	Launch the interactive TUI
category	Category commands (see CLI: Category commands)
view	View commands (see CLI: View commands)
link	Item-to-item link commands
unlink	Remove item-to-item links
import	Structured import commands (CSV)
item	Item commands in alternative noun-verb syntax
OPTIONS	 --db SQLite database path (or set AGLET_DB) -h, --help Print help for any command or subcommand
NOTE	Run "aglet" with no command to launch the TUI. Every command accepts --help for its own options.

18.4.0.1 SEE ALSO

About the CLI, [Item commands](#), [Category commands](#), [View commands](#), [» Index](#)

Chapter 19

Concepts

Chapter 20

Item Commands

20.1 CLI Item Commands

PURPOSE Create, inspect, modify, and remove items from the command line.

COMMANDS

add	Add a new item (--note, returns the created id)
edit	Edit text, note, and/or done state (--text, --note, --done, --not-done)
show	Show a single item with its assignments
list	List items, optionally filtered
search	Search item text and note
export	Export items as Markdown
delete	Delete an item (writes deletion log)
deleted	List deletion-log entries
restore	Restore an item from the deletion log by log id
item	Alternative noun-verb syntax for item commands

EXAMPLES

```
aglet add "Plan offsite" --note "Book venue"
aglet show
aglet export > items.md
```

NOTE Parse the "created " line from add for the new id; it is not always the last line printed.

20.1.0.1 SEE ALSO

[Add an item](#), [Edit an item](#), [Delete an item](#), [CLI filtering](#), [CLI import and export](#), [» Index](#)

Chapter 21

Category Commands

21.1 CLI Category Commands

PURPOSE Manage categories, assignments, conditions, and actions from the command line.

COMMANDS	<code>list</code>	List categories as a tree
	<code>show</code>	Show details for a category
	<code>create</code>	Create a category (<code>--parent</code> , <code>--exclusive</code> , <code>--type numeric</code>)
	<code>delete</code>	Delete a category by name
	<code>rename</code>	Rename a category
	<code>reparent</code>	Reparent (<code>--root</code> makes it top-level)
	<code>update</code>	Update category flags
	<code>assign</code>	Assign an item to a category
	<code>unassign</code>	Unassign an item from a category
	<code>set-value</code>	Set a numeric value assignment
	<code>format</code>	Configure numeric formatting
	<code>add-condition</code>	Add a profile condition
	<code>add-date-condition</code>	Add a date condition
	<code>set-condition-mode</code>	Set how explicit conditions combine
	<code>remove-condition</code>	Remove a condition by 1-based index
	<code>add-action</code>	Add an action
	<code>remove-action</code>	Remove an action by 1-based index

EXAMPLES

```
aglet category create "Priority" --exclusive
aglet category create "High" --parent Priority
aglet category assign High
aglet category set-value Cost 450.00
```

NOTE Done, When, and Entry are reserved and cannot be created, renamed, or deleted.

21.1.0.1 SEE ALSO

[Add a category](#), [Assign a category](#), [Profile conditions](#), [Actions](#), [Set a numeric value](#), [» Index](#)

21.2 Profile Conditions

PURPOSE Assign a category based on structured rules about an item, beyond a plain name match.

CLI STEPS `aglet category add-condition ...`
`aglet category set-condition-mode ...`
`aglet category remove-condition`

HOW IT WORKS A category can carry one or more explicit conditions. The condition mode controls how multiple conditions combine. When an item satisfies the conditions, the category is derived automatically. Derived (non-sticky) assignments can break if the item stops matching.

NOTE In the category manager the left pane shows a readable rule-count badge such as [2 conditions]. Conditions are re-evaluated when an item's text or dates change.

21.2.0.1 SEE ALSO

[Automatic assignment](#), [Date conditions](#), [Actions](#), [CLI category commands](#), [» Index](#)

21.3 Date Conditions

PURPOSE Assign a category based on an item's date - for example, to bucket items by when they are due.

CLI STEPS `aglet category add-date-condition ...`

HOW IT WORKS A date condition tests an item's When date against a range or relative window. When it matches, the category is derived. Date conditions power date-range categories used to build datebook

views and date-grouped sections.

NOTE Direct SQLite writes do not sync the reserved When assignment; use aglet/CLI logic so date conditions see the date.

21.3.0.1 SEE ALSO

Profile conditions, [Datebook views](#), [Reserved categories](#), » [Index](#)

21.4 Actions

PURPOSE Make assigning one category automatically assign or remove another.

CLI STEPS `aglet category add-action ...`
`aglet category remove-action`

HOW IT WORKS An action fires when its owning category is assigned to an item. An Assign action adds another category; a Remove action removes one. Actions are event-driven: adding or editing an action does not retroactively fire for items that already have the owning category. Action-applied assignments are sticky.

NOTE The category manager shows an action badge such as [1 action] in the left pane.

21.4.0.1 SEE ALSO

Profile conditions, [Automatic assignment](#), CLI category commands, » [Index](#)

Chapter 22

View Commands

22.1 CLI View Commands

PURPOSE Create and edit views, sections, columns, aliases, and datebooks from the command line.

COMMANDS	list	List views
	show	Show the contents of a view
	create	Create a view from include/exclude
	edit	Edit mutable view properties
	clone	Clone into a new mutable view
	rename	Rename a view
	delete	Delete a view by name
	section add/remove/update	Section authoring
	column add/remove/update	Column authoring
	alias set/clear	Per-view category display alias
	set-summary	Set a column summary function
	set-item-label	Set or clear the item column label
	set-remove-from-view	Replace the remove-from-view category set
	create-datebook	Create a datebook (date-interval) view
	datebook-browse	Shift a datebook view's window

EXAMPLES

```
aglet view create "Work Queue" --include Work --exclude Done
aglet view show "Work Queue"
aglet view clone "All Items" "My Items"
```

NOTE --include criteria are AND-based; use sections or separate views for mutually exclusive siblings.

22.1.0.1 SEE ALSO

[Create a view](#), [Add a section](#), [Add a column](#), [View aliases](#), [Create a datebook view](#), » [Index](#)

Chapter 23

Link Commands

23.1 CLI Link Commands

PURPOSE	Create and remove item-to-item links from the command line.		
COMMANDS	link depends-on	ITEM depends on DEPENDS_ON_ITEM	
	link blocks	BLOCKER blocks BLOCKED	
	link related	Bidirectional related link	
	unlink depends-on / blocks / related	Remove the corresponding link (canonical entry)	
EXAMPLES	aglet link depends-on		
	aglet link related		
	aglet unlink depends-on		
NOTE	depends-on and blocks describe the same directed relationship from opposite ends; related is symmetric.		

23.1.0.1 SEE ALSO

[Create a dependency](#), [Remove a link](#), [Dependencies](#), [» Index](#)

Chapter 24

Filtering and Sorting

24.1 CLI Filtering and Sorting

PURPOSE	Narrow and order the output of list, search, and view show.	
FLAGS	--category	Repeatable, AND semantics
	--any-category	Repeatable, OR semantics
	--exclude-category	Repeatable, NOT semantics
	--blocked / --not-blocked	Dependency-state filters (derived)
	--value-eq	Numeric value equals
	--value-in	Numeric value in a set
	--value-max	Numeric value at most
	--sort	Sort order
	--view	Use a specific view
	--include-done	Include done items
	--format	Output format (e.g. json)
	--verbose	Multi-line human output
EXAMPLES	aglet list --category High --not-blocked aglet list --any-category Work --any-category Personal aglet list --sort Cost:desc --format json	
NOTE	Repeated --category is AND; for OR across siblings use --any-category. blocked/not-blocked are derived, not categories.	

24.1.0.1 SEE ALSO

[View criteria](#), [Filter blocked items](#), [Search items](#), [CLI item commands](#), » [Index](#)

Chapter 25

Import and Export

25.1 CLI Import and Export

PURPOSE	Move items into and out of aglet.
COMMANDS	<code>import</code> Structured import commands (e.g. CSV) <code>export</code> Export items as Markdown
EXAMPLES	<code>aglet export > items.md</code> <code>aglet import ...</code>
HOW IT WORKS	Export writes items as Markdown to standard output. Import brings structured data in. Prefer the CLI/import path over direct SQLite writes so dates and reserved When provenance are handled correctly.
NOTE	Direct SQLite imports must use the store datetime format YYYY-MM-DD HH:MM:SS; ISO strings will not load as dates.

25.1.0.1 SEE ALSO

CLI item commands, [About the CLI](#), [About .ag files](#), [» Index](#)

Chapter 26

Workflow Commands

26.1 Claim an Item

PURPOSE Atomically take an eligible item for active work, marking it as yours.

CLI STEPS `aglet claim`

HOW IT WORKS Claiming applies the configured claim-target category. An item is claimable only if it has the configured Ready category, does not already have the claim-target category, is not done, and is not blocked by an unresolved depends-on prerequisite. Claimability is computed, not a link type.

NOTE If a claim races and fails because the item is already In Progress, pick another item rather than force-assigning.

26.1.0.1 SEE ALSO

The ready list, Release a claim, [Filter blocked items](#), [Global settings](#), [» Index](#)

26.2 Release a Claim

PURPOSE Give up an item you previously claimed.

CLI STEPS `aglet release`
 `aglet unclaim        # alias`

HOW IT WORKS Releasing removes the active claim-target category, returning the

item to the pool of claimable work if it still has the Ready category.

NOTE release and unclaim are the same command.

26.2.0.1 SEE ALSO

Claim an item, The ready list, » [Index](#)

26.3 The Ready List

PURPOSE See the items that are eligible to be claimed right now.

CLI STEPS `aglet ready`

HOW IT WORKS ready lists items that have the Ready category and are not done, not already claimed, and not blocked by unresolved dependencies. It is the recommended way to pick the next piece of work.

NOTE Because ready already excludes done, claimed, and blocked items, prefer it over scanning a full list when choosing work.

26.3.0.1 SEE ALSO

Claim an item, Release a claim, [Filter blocked items](#), » [Index](#)