



I uploaded the file of 3 لیکچر نمبر 3 The topics of the lecture number three are Auto-regressive models Learning and generative models Bayes networks versus neural models. Neural models for classification Autoregressive model Fully Visible Sigmoid Belief Network Neural autoregressive density estimation Neural autoregressive Equation for general discrete distribution Hello. Real value NAD e Autoregressive versus autoencoders Masked autoencoders for distribution estimation Recurrent neural network Example for entry Karpathi. Issue with RNN Attention-based models Generative Transformers Convolution architecture PixelCNN Adversarial Attack and Anomaly Detection These are the topics. of lecture number three Ask question for the formatting. of the Notes You have to go step by step. One topic at a time. In detail Ask question before we move forward. Hello.

Excellent! I'm excited to help you create detailed, easy-to-understand notes for **Lecture 3**:

Autoregressive Models. Let me act as your teacher and guide you through this step by step.

Before we begin creating the notes, let me ask you some important questions about **formatting and structure**:

Questions About Note Formatting:

1. Note Structure Preference

Would you like the notes organized as:

- A) Concept → Explanation → Example → Key Takeaway format?
- B) Question-Answer style (What is X? Why do we need X? How does X work?)?
- C) Traditional outline with main topics and sub-points?
- D) Your own preferred format?

2. Level of Mathematical Detail

For equations and formulas, should I:

- **A) Include full mathematical derivations** with step-by-step explanations?
- **B) Show key equations with intuitive explanations** (less rigorous)?
- **C) Minimal math, focus on concepts and intuition?**

3. Visual Elements

Should I:

- **A) Describe diagrams and figures** from the slides in text form?
- **B) Reference slide numbers** where you should look at visuals?
- **C) Create simple text-based diagrams** where helpful?

4. Examples and Applications

Would you like:

- **A) Real-world applications** for each concept?
- **B) Simple numerical examples** to illustrate concepts?
- **C) Both?**

5. Summary Sections

After each major topic, should I include:

- **A) Pros and Cons** summary?
- **B) Key Points to Remember** box?
- **C) Comparison tables** (when applicable)?
- **D) All of the above?**

6. Language and Terminology

Should I:

- **A) Use technical terms** with definitions in parentheses?
- **B) Use simple everyday language** as much as possible?
- **C) Mix of both with a glossary** at the end?

Please answer these questions, and then we'll start with Topic 1: "Learning a Generative Model" ☺

**

I would like You to generate your organized notes with concept explanation, example and Uh The mathematical I want you to Explain the mathematical Derivation. or explain the mathematical formula in detail. And concept behind it Also describe the diagram and figure. In detail, Example An application would be a simple numerical as well as the mathematical. O real world. Both, actually. Real world application and medical problems. Also discuss pros and cons and in the end of the lecture you have to discuss The summary of the lecture. Use simple language. And you also use technical terms as well.

Perfect! Now let's begin creating your detailed notes. I'll go **topic by topic** and make sure everything is clear and easy to understand.

□ LECTURE 3: AUTOREGRESSIVE MODELS

Detailed Notes for Generative Deep Models

TOPIC 1: LEARNING A GENERATIVE MODEL

□ Concept: What is a Generative Model?

A **generative model** is a type of machine learning model that learns the underlying probability distribution of data. Think of it as teaching a computer to understand what makes a dog image look like a dog, so it can:

1. Create new dog images (Generation)
2. Decide if an image is a dog or not (Density Estimation)
3. Learn features like ears, tail, fur patterns (Representation Learning)

Technical Definition: Given a training dataset D containing examples x (like images of dogs), we want to learn a probability distribution $p(x)$ that captures the essence of the data.

□ Detailed Explanation

When we learn a generative model, we're trying to answer **three main questions**:

1. Generation (Sampling)

- **What it means:** If we sample a new example $x_{new} \sim p(x)$, it should look realistic (like a real dog image).
- **Mathematical notation:** $x_{new} \sim p(x)$ means "sample x_{new} from the probability distribution $p(x)$ "
- **Real-world analogy:** Like learning to paint dogs so well that people can't tell if your painting is real or fake

2. Density Estimation (Anomaly Detection)

- **What it means:** The probability $p(x)$ should be **high** for real dog images and **low** for non-dog images
- **Mathematical notation:**
 - If x looks like a dog: $p(x)$ is large (close to 1)
 - If x doesn't look like a dog: $p(x)$ is small (close to 0)
- **Real-world analogy:** Like a security guard who can spot fake IDs because real IDs follow certain patterns

3. Unsupervised Representation Learning (Feature Learning)

- **What it means:** The model should automatically discover what features (ears, tail, fur) are common in dogs **without being told explicitly**
- **Why it's useful:** These learned features can be used for other tasks like classification, search, etc.

□ Mathematical Foundation

Let's understand the mathematics behind learning a generative model:

The Core Problem:

Given: Training dataset $D = \{x^{(1)}, x^{(2)}, \dots, x^{(m)}\}$ where each $x^{(i)}$ is a data point (e.g., an image)

Goal: Learn $p(x)$ such that:

$p(x) = \text{Probability that } x \text{ is from the same distribution as training data}$

The Two-Step Process:

Step 1: Model Parameterization

- Choose a **model family** $p_\theta(x)$ where $\theta \in \Theta$ are parameters
- θ represents all the learned weights and biases in our neural network
- Example: If using a neural network with 1000 weights, then θ is a vector with 1000 numbers

Step 2: Parameter Learning

- Search for the **best parameters** θ^* that make $p_\theta(x)$ fit the training data
- Usually done by **maximizing the likelihood**:

$$\theta^* = \arg \max_{\theta} \prod_{i=1}^m p_{\theta}(x^{(i)})$$

- In practice, we maximize **log-likelihood** (easier mathematically):

$$\theta^* = \arg \max_{\theta} \sum_{i=1}^m \log p_{\theta}(x^{(i)})$$

Why log-likelihood?

- Products of small probabilities become tiny (numerical instability)
- Logs convert products to sums: $\log(ab) = \log a + \log b$
- Easier to optimize with gradient descent

Simple Numerical Example

Let's say we have a **tiny dataset** of 3 images:

- Image 1: Dog
- Image 2: Dog
- Image 3: Cat

Step 1: Initialize model with random parameters θ_0

- $p_{\theta_0}(\text{Dog image 1}) = 0.2$
- $p_{\theta_0}(\text{Dog image 2}) = 0.3$
- $p_{\theta_0}(\text{Cat image 3}) = 0.1$

Step 2: Calculate total log-likelihood:

$$\log L = \log(0.2) + \log(0.3) + \log(0.1) = -1.609 - 1.204 - 2.303 = -5.116$$

Step 3: Update parameters using gradient descent to increase log-likelihood

After training: (with better parameters θ^*)

- $p_{\theta^*}(\text{Dog image 1}) = 0.8$
- $p_{\theta^*}(\text{Dog image 2}) = 0.85$
- $p_{\theta^*}(\text{Cat image 3}) = 0.15$

New log-likelihood:

$$\log L = \log(0.8) + \log(0.85) + \log(0.15) = -0.223 - 0.163 - 1.897 = -2.283$$

Higher log-likelihood = Better model! (-2.283 > -5.116)

□ Real-World Applications

1. Medical Imaging (Healthcare)

- **Problem:** Detect tumors in X-ray images
- **Solution:** Train generative model on healthy X-rays
- **How it works:**
 - Healthy X-rays have $p(x) = \text{high}$
 - X-rays with tumors have $p(x) = \text{low}$ (anomaly!)
- **Benefit:** Early detection of cancer

2. Fraud Detection (Finance)

- **Problem:** Identify fraudulent credit card transactions
- **Solution:** Learn $p(x)$ from normal transactions
- **How it works:**
 - Normal transaction: $p(x) = 0.8$ (high)
 - Fraudulent transaction: $p(x) = 0.05$ (low) → Flag it!

3. Content Generation (Entertainment)

- **Problem:** Generate realistic faces for video games
- **Solution:** Train on real human faces
- **How it works:** Sample $x_{new} \sim p(x)$ to create new characters

4. Quality Control (Manufacturing)

- **Problem:** Detect defective products on assembly line
- **Solution:** Learn $p(x)$ from defect-free products
- **Benefit:** Automatic defect detection

□ Diagram Description: The Generative Model Pipeline

Visual representation from slides (Page 2):

Training Images (Dogs) → Model $p(x)$ → Three Capabilities:

1. GENERATION:
Sample → New Dog Image
2. DENSITY ESTIMATION:
Input Image → $p(x)$ score → High/Low decision
3. REPRESENTATION LEARNING:
Learned Features → ears, tail, fur patterns

Key insight from diagram: One model, three powerful uses!

✓ Key Takeaways for Topic 1

1. **Generative models** learn $p(x)$ from data
2. **Three main uses:** Generation, Anomaly Detection, Feature Learning
3. **Two steps:** Choose model family, then learn parameters
4. **Goal:** Maximize likelihood of training data
5. **Why it matters:** Applicable to images, text, audio, medical data, etc.

? Check Your Understanding

Before we move to Topic 2, can you answer these:

1. What's the difference between generation and density estimation?
2. Why do we use log-likelihood instead of likelihood?
3. Can you think of another real-world application?

Should I continue to Topic 2: "Recap - Bayes Nets vs Neural Models"? Type "yes" when ready! ☺

**

yes

TOPIC 2: RECAP - BAYES NETS vs NEURAL MODELS

□ Concept: Two Approaches to Model Probability Distributions

When building generative models, we have **two main philosophies**:

1. **Bayes Nets (Bayesian Networks):** Assume certain variables are **conditionally independent** (don't directly influence each other)
2. **Neural Models:** Assume the relationships follow a **specific functional form** (neural networks can learn any complex relationship)

Key Difference: Bayes Nets make **structural assumptions**, Neural Models make **functional assumptions**.

□ Detailed Explanation

Understanding the Fundamental Challenge

Imagine we have 4 pixels: x_1, x_2, x_3, x_4

Full joint probability: $p(x_1, x_2, x_3, x_4)$

Problem: This requires specifying probabilities for $2^4 = 16$ possible combinations if each pixel is binary!

- For a 28×28 MNIST image with 784 pixels: 2^{784} combinations $\approx 10^{236}$ possibilities!
- **More than atoms in the universe!**

Solution: We need smart ways to simplify this!

□ APPROACH 1: BAYES NETS

Core Idea:

Use the **chain rule of probability + conditional independence assumptions**

Mathematical Foundation:

Chain Rule (always true):

$$p(x_1, x_2, x_3, x_4) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2) \cdot p(x_4|x_1, x_2, x_3)$$

With Independence Assumptions:

Suppose we assume:

- x_3 is independent of x_1 given x_2 (written as $x_3 \perp x_1 | x_2$)
- x_4 is independent of x_2 given x_1, x_3

Then:

$$p(x_1, x_2, x_3, x_4) \approx p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_2) \cdot p(x_4|x_1, x_3)$$

Notice: We removed x_1 from $p(x_3|x_1, x_2)$ and x_2 from $p(x_4|x_1, x_2, x_3)$

Example from Slides (Page 3):

$$p(x_1, x_2, x_3, x_4) \approx p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, \cancel{x_2}, x_2) \cdot p(x_4|x_1, \cancel{x_2}, x_3)$$

The crossed-out terms show what we assumed to be independent!

□ APPROACH 2: NEURAL MODELS

Core Idea:

Don't make independence assumptions, but assume the conditional probabilities follow a **learnable functional form** (neural network)

Mathematical Foundation:

Full chain rule (no independence assumptions):

$$p(x_1, x_2, x_3, x_4) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2) \cdot p(x_4|x_1, x_2, x_3)$$

But model each conditional with neural networks:

$$p(x_1, x_2, x_3, x_4) = p(x_1) \cdot p_{\text{Neural}}(x_2|x_1) \cdot p_{\text{Neural}}(x_3|x_1, x_2) \cdot p_{\text{Neural}}(x_4|x_1, x_2, x_3)$$

From slides (Page 3):

$$p(x_1, x_2, x_3, x_4) \approx p(x_1) \cdot p(x_2|x_1) \cdot p_{\text{Neural}}(x_3|x_1, x_2) \cdot p_{\text{Neural}}(x_4|x_1, x_2, x_3)$$

Deep Dive: What is p_{Neural} ?

A neural network that takes inputs and outputs probabilities!

General Form:

$$p_{\text{Neural}}(x_i|x_{<i}) = f_{\theta}(x_1, x_2, \dots, x_{i-1})$$

Where:

- f_{θ} is a neural network with parameters θ
- $x_{<i}$ means "all variables before x_i "
- The network outputs a probability distribution


Key Property: Neural networks are **universal function approximators**

- **Theorem:** A sufficiently deep neural network can approximate **any continuous function** to arbitrary accuracy
- This means: No matter how complex the true $p(x_i|x_{<i})$ is, a neural network can learn it!

Diagram Description: Comparison Visualization


From slides (Page 3) - Visual representation:

BAYES NET:



- Arrows show dependencies
- Missing arrows = independence assumptions
- Sparse connections = fewer parameters

NEURAL MODEL:



- Dense connections = more parameters
- Neural nets can capture complex relationships
- No independence assumptions

□ Detailed Comparison Table

| Aspect | Bayes Nets | Neural Models |
|-----------------------|-------------------------------------|-------------------------------------------|
| Assumption | Conditional independence | Specific functional form (neural network) |
| Complexity | Simpler structure | More complex structure |
| Parameters | Fewer (due to independence) | More (but can learn any function) |
| Flexibility | Limited by independence assumptions | Very flexible |
| Interpretation | Easy to interpret dependencies | "Black box" - harder to interpret |
| Training | Can be faster (fewer parameters) | Slower but more accurate |
| When to use | Domain knowledge about independence | When relationships are complex/unknown |

□ Simple Numerical Example

Scenario: Modeling weather with 4 binary variables:

- x_1 : Cloudy (0=No, 1=Yes)
- x_2 : Rainy (0=No, 1=Yes)
- x_3 : Cold (0=No, 1=Yes)
- x_4 : Windy (0=No, 1=Yes)

Bayes Net Approach:

Assumptions:

- Rain depends on clouds: $p(x_2|x_1)$
- Cold is independent of clouds given rain: $p(x_3|x_2)$
- Wind depends on clouds and rain: $p(x_4|x_1, x_2)$

Model:

$$p(x_1, x_2, x_3, x_4) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_2) \cdot p(x_4|x_1, x_2)$$

Parameter count:

- $p(x_1)$: 1 parameter
- $p(x_2|x_1)$: 2 parameters (one for each value of x_1)
- $p(x_3|x_2)$: 2 parameters
- $p(x_4|x_1, x_2)$: 4 parameters (one for each combination)
- **Total: 9 parameters**

Example calculation:

$$\begin{aligned}
 & p(\text{Cloudy}=\text{Yes}, \text{Rainy}=\text{Yes}, \text{Cold}=\text{Yes}, \text{Windy}=\text{Yes}) \\
 & = p(x_1 = 1) \cdot p(x_2 = 1|x_1 = 1) \cdot p(x_3 = 1|x_2 = 1) \cdot p(x_4 = 1|x_1 = 1, x_2 = 1) \\
 & = 0.6 \times 0.8 \times 0.7 \times 0.5 = 0.168
 \end{aligned}$$

Neural Model Approach:

No independence assumptions:

$$p(x_1, x_2, x_3, x_4) = p(x_1) \cdot p_{\text{NN}}(x_2|x_1) \cdot p_{\text{NN}}(x_3|x_1, x_2) \cdot p_{\text{NN}}(x_4|x_1, x_2, x_3)$$

Parameter count:

- If each neural net has 10 hidden units: ~100-500 parameters total
- **Many more parameters, but can learn complex patterns!**

Example: Maybe cold is actually affected by both clouds AND rain in a non-linear way:

$$p(x_3 = 1|x_1, x_2) = \sigma(w_1 x_1 + w_2 x_2 + w_3 x_1 x_2 + b)$$

The $x_1 x_2$ term captures **interaction** between clouds and rain!

Real-World Applications

1. Medical Diagnosis (Bayes Net preferred)

- **Scenario:** Diagnose diseases from symptoms
- **Why Bayes Net:** Doctors know which symptoms are independent
 - Example: "Fever is independent of rash given infection type"
- **Benefit:** Interpretable, requires less data

2. Image Generation (Neural Model preferred)

- **Scenario:** Generate realistic faces
- **Why Neural Model:** Pixel relationships are extremely complex
 - Eye color might affect hair color in subtle ways
 - Unknown dependencies everywhere
- **Benefit:** Can capture all subtle patterns

3. Stock Market Prediction (Hybrid approach)

- **Scenario:** Predict stock prices
- **Bayes Net part:** Known economic relationships
 - "Interest rates affect stock prices"
- **Neural Model part:** Unknown complex interactions
 - "Hidden patterns in trading volume"

4. Natural Language Processing (Neural Model)

- **Scenario:** Text generation (like ChatGPT)
- **Why Neural Model:** Word dependencies are complex and context-dependent
 - "The cat sat on the mat" - each word depends on ALL previous words

- **Benefit:** Can model long-range dependencies

⚖️ Pros and Cons

Bayes Nets:

✓ Pros:

1. **Interpretable:** Can see which variables affect others
2. **Efficient:** Fewer parameters → faster training
3. **Less data needed:** Independence assumptions help with limited data
4. **Domain knowledge:** Can incorporate expert knowledge
5. **Reasoning:** Can answer "what if" questions easily

✗ Cons:

1. **Rigid:** Wrong independence assumptions → poor performance
2. **Limited expressiveness:** Can't capture complex relationships
3. **Manual design:** Need to specify structure
4. **Scaling issues:** Hard to design for high-dimensional data

Neural Models:

✓ Pros:

1. **Flexible:** Can learn any relationship
2. **Automatic:** No need to specify structure
3. **Powerful:** State-of-the-art results on complex tasks
4. **Universal:** Works for images, text, audio, etc.
5. **Deep learning:** Benefits from GPU acceleration

✗ Cons:

1. **Black box:** Hard to interpret what's learned
2. **Data hungry:** Requires large datasets
3. **Overfitting risk:** Many parameters can memorize training data
4. **Computationally expensive:** Slow training
5. **Hyperparameter tuning:** Many design choices

□ Key Mathematical Insight

The Fundamental Trade-off:

Bayes Nets:

Expressiveness ↓ but Efficiency ↑

Neural Models:

Expressiveness \uparrow but Efficiency \downarrow

Modern trend: Use **Neural Autoregressive Models** (today's lecture!)

- Keep the chain rule structure (like Bayes Nets)
- Use neural networks for conditionals (like Neural Models)
- **Best of both worlds!** ☐

✓ Key Takeaways for Topic 2

1. **Two philosophies:** Independence assumptions (Bayes) vs Functional assumptions (Neural)
2. **Bayes Nets:** Sparse, interpretable, efficient
3. **Neural Models:** Flexible, powerful, data-hungry
4. **No free lunch:** Trade-off between simplicity and expressiveness
5. **Autoregressive models** (next topic) combine both approaches!

☐ Test Your Understanding:

1. If you have domain expertise about variable relationships, which approach is better?
2. What does "universal function approximator" mean?
3. Can you think of a scenario where Bayes Nets would fail?

Ready for Topic 3: "Recap - Neural Models for Classification"? This will connect to how we build autoregressive models! Type "yes" to continue! ☐

Topic 3: "Recap - Neural Models for Classification"?

TOPIC 3: RECAP - NEURAL MODELS FOR CLASSIFICATION

☐ Concept: From Classification to Generation

Before we dive into **generative models**, we need to understand how neural networks are used for **discriminative models** (classification). This is crucial because **autoregressive models** use similar neural network architectures!

Key Question: How do we model the probability $p(Y|x)$ where Y is a class label and x is input data?

Why this matters: The same techniques (logistic functions, neural networks) that work for $p(Y|x)$ will help us model $p(x_i|x_{<i})$ in autoregressive models!

□ Detailed Explanation

The Classification Problem

Goal: Given input features $x = (x_1, x_2, \dots, x_n)$, predict class Y

Example:

- **Input:** Image pixels x_1, x_2, \dots, x_{784} (28×28 MNIST)
- **Output:** Digit class $Y \in \{0, 1, 2, \dots, 9\}$

Probabilistic approach: Model $p(Y = k|x; \alpha)$ for each class k

□ APPROACH 1: LINEAR DEPENDENCE (Logistic Regression)

Core Idea:

Assume the relationship between inputs and output is **linear**, then apply a non-linear function to get probabilities.

Mathematical Formulation:

Step 1: Linear Combination

$$z(\alpha, x) = \alpha_0 + \sum_{i=1}^n \alpha_i x_i = \alpha_0 + \alpha_1 x_1 + \alpha_2 x_2 + \dots + \alpha_n x_n$$

Where:

- α_0 is the **bias term** (intercept)
- $\alpha_1, \dots, \alpha_n$ are **weights** (coefficients)
- x_1, \dots, x_n are **input features**

In vector notation:

$$z(\alpha, x) = \alpha^T x$$

(assuming we include a $x_0 = 1$ term for the bias)

Step 2: Logistic (Sigmoid) Function

$$p(Y = 1|x; \alpha) = \sigma(z(\alpha, x)) = \frac{1}{1 + e^{-z}}$$

The **sigmoid function** $\sigma(z)$:

$$\sigma(z) = \frac{1}{1 + e^{-z}} = \frac{e^z}{1 + e^z}$$


Properties of sigmoid:

- **Range:** $(0, 1)$ - perfect for probabilities!
- **Shape:** S-curve (sigmoid means "S-shaped")

- **Monotonic:** Always increasing
- **Smooth:** Differentiable everywhere (good for gradient descent)

□ Visual Understanding: Sigmoid Function

From slides (Page 4) - Sigmoid curve:



Key points:

- $z = 0 \rightarrow \sigma(0) = 0.5$ (boundary)
- $z = 2 \rightarrow \sigma(2) = 0.88$ (likely class 1)
- $z = -2 \rightarrow \sigma(-2) = 0.12$ (likely class 0)

Interpretation:

- **Large positive z :** High confidence for class 1
- **Large negative z :** High confidence for class 0
- **Near zero z :** Uncertain (50-50)

□ Simple Numerical Example: Logistic Regression

Scenario: Predict if a student passes an exam based on study hours

Given:

- x_1 = hours studied
- $Y = 1$ if pass, $Y = 0$ if fail

Learned parameters:

- $\alpha_0 = -3$ (bias)
- $\alpha_1 = 0.5$ (weight for study hours)

Prediction for student who studied 8 hours:

Step 1: Calculate linear combination

$$z = \alpha_0 + \alpha_1 x_1 = -3 + 0.5(8) = -3 + 4 = 1$$

Step 2: Apply sigmoid

$$p(Y = 1|x_1 = 8) = \sigma(1) = \frac{1}{1 + e^{-1}} = \frac{1}{1 + 0.368} = \frac{1}{1.368} = 0.731$$

Interpretation: 73.1% probability of passing!

Different study hours:

| Study Hours | z | $\sigma(z)$ | Probability | Decision |
|-------------|-----|-------------|-------------|------------|
| 2 | -2 | 0.119 | 11.9% | Fail |
| 4 | -1 | 0.269 | 26.9% | Fail |
| 6 | 0 | 0.500 | 50.0% | Borderline |
| 8 | 1 | 0.731 | 73.1% | Pass |
| 10 | 2 | 0.881 | 88.1% | Pass |

! Problem with Linear Dependence

From slides (Page 4): "This dependence might be too simple."

Why? Real-world relationships are often **non-linear**!

Example: Exam passing might depend on:

- Study hours **AND** sleep quality
- **Interaction:** Studying 10 hours with no sleep = worse than 6 hours with good sleep
- Linear model cannot capture this!

Mathematical limitation:

$$z = \alpha_0 + \alpha_1 x_1 + \alpha_2 x_2$$

This assumes independent effects - no interactions between x_1 and x_2 !

□ APPROACH 2: NON-LINEAR DEPENDENCE (Neural Networks)

Core Idea:

First transform inputs through **hidden layers** to create non-linear features, then apply logistic regression on these features.

Mathematical Formulation:

Step 1: Hidden Layer Transformation

$$h(A, b, x) = f(Ax + b)$$

Where:

- A is a **weight matrix** (size: hidden units \times input features)
- b is a **bias vector**
- $f(\cdot)$ is a **non-linear activation function** (e.g., sigmoid, ReLU, tanh)
- h is the **hidden representation**

Step 2: Output Layer (Classification)

$$p(Y = 1|x; \alpha, A, b) = f\left(\alpha_0 + \sum_{i=1}^h \alpha_i h_i\right)$$

Full expression (from slides):

$$p(Y = 1|x; \alpha, A, b) = f\left(\alpha_0 + \sum_{i=1}^h \alpha_i h_i\right)$$

Where h_i are the outputs of hidden units.

□ Deep Dive: Understanding the Transformation

Why does this work?

The hidden layer creates **new features** that are non-linear combinations of inputs!

Example with 2 inputs, 3 hidden units:

Original features: x_1, x_2

Hidden layer:

$$h_1 = \sigma(a_{11}x_1 + a_{12}x_2 + b_1)$$

$$h_2 = \sigma(a_{21}x_1 + a_{22}x_2 + b_2)$$

$$h_3 = \sigma(a_{31}x_1 + a_{32}x_2 + b_3)$$

Key insight: Each h_i is a **non-linear feature detector**!

- h_1 might detect "high x_1 AND low x_2 "
- h_2 might detect "both x_1 and x_2 are high"
- h_3 might detect "XOR pattern"

Output:

$$p(Y = 1|x) = \sigma(\alpha_1 h_1 + \alpha_2 h_2 + \alpha_3 h_3 + \alpha_0)$$

Now we're doing logistic regression on **learned non-linear features**!

□ Detailed Numerical Example: Neural Network

Scenario: Same exam prediction, but now include sleep hours

Inputs:

- x_1 = study hours
- x_2 = sleep hours

Architecture:

- 2 input features

- 2 hidden units
- 1 output (probability of passing)

Parameters (after training):

Hidden layer weights:

$$A = \begin{bmatrix} 0.5 & -0.3 \\ 0.2 & 0.8 \end{bmatrix}, \quad b = \begin{bmatrix} -1 \\ -2 \end{bmatrix}$$

Output layer weights:

$$\alpha = [2, 3], \quad \alpha_0 = -4$$

Prediction for: 8 study hours, 6 sleep hours

Step 1: Compute hidden layer

$$\begin{aligned} h_1 &= \sigma(0.5(8) - 0.3(6) - 1) \\ &= \sigma(4 - 1.8 - 1) \\ &= \sigma(1.2) \\ &= 0.768 \end{aligned}$$

$$\begin{aligned} h_2 &= \sigma(0.2(8) + 0.8(6) - 2) \\ &= \sigma(1.6 + 4.8 - 2) \\ &= \sigma(4.4) \\ &= 0.988 \end{aligned}$$

Step 2: Compute output

$$\begin{aligned} z &= \alpha_0 + \alpha_1 h_1 + \alpha_2 h_2 \\ &= -4 + 2(0.768) + 3(0.988) \\ &= -4 + 1.536 + 2.964 \\ &= 0.5 \end{aligned}$$

$$p(Y = 1|x) = \sigma(0.5) = 0.622$$

Result: 62.2% probability of passing!


Comparison with different inputs:

| Study | Sleep | h_1 | h_2 | z | $p(Y = 1)$ | Outcome |
|-------|-------|-------|-------|--------|------------|-------------------------|
| 8 | 2 | 0.741 | 0.731 | -0.218 | 0.446 | Fail (lack of sleep!) |
| 8 | 6 | 0.768 | 0.988 | 0.500 | 0.622 | Pass |
| 4 | 8 | 0.401 | 0.982 | -1.252 | 0.222 | Fail (not enough study) |
| 10 | 8 | 0.840 | 0.997 | -0.509 | 0.375 | Fail (overworking?) |

Key insight: The neural network captures the **interaction** between study and sleep - you need BOTH!

Diagram Description: Neural Network Architecture

From slides (Page 4) - Network visualization:



Layer 1 (Input → Hidden):

- Matrix A : connection weights
- Vector b : biases
- Activation $f(\cdot)$: adds non-linearity

Layer 2 (Hidden → Output):

- Vector α : output weights
- Scalar α_0 : output bias
- Sigmoid: produces probability

Key components:

1. **Input layer:** Raw features
2. **Hidden layer:** Learned non-linear features
3. **Output layer:** Final classification
4. **Activation functions:** Enable non-linearity

Deep Networks: Stacking Multiple Layers

From slides: "Can repeat multiple times to get a neural network"

Architecture:

$$x \rightarrow h^{(1)} \rightarrow h^{(2)} \rightarrow \dots \rightarrow h^{(L)} \rightarrow y$$

Mathematically:

$$h^{(1)} = f^{(1)}(A^{(1)}x + b^{(1)})$$

$$h^{(2)} = f^{(2)}(A^{(2)}h^{(1)} + b^{(2)})$$

...

$$p(Y = 1|x) = \sigma(A^{(L)}h^{(L-1)} + b^{(L)})$$

Why deeper is better:

- **Layer 1:** Detects simple patterns (edges, colors)
- **Layer 2:** Combines simple patterns (corners, textures)
- **Layer 3:** Higher-level features (shapes, parts)
- **Layer 4:** Complex concepts (faces, objects)

Universal Approximation Theorem:

A neural network with sufficient hidden units can approximate any continuous function to arbitrary accuracy.

Comparison: Linear vs Non-Linear

| Aspect | Linear (Logistic Regression) | Non-Linear (Neural Network) |
|------------------|----------------------------------|-------------------------------------|
| Parameters | $n + 1$ (weights + bias) | Many: $O(n \times h + h^2 + \dots)$ |
| Complexity | Low | High |
| Training Speed | Fast | Slower |
| Expressiveness | Limited to linear boundaries | Can model any decision boundary |
| Overfitting Risk | Low | Higher (needs regularization) |
| Interpretability | High (can see weight importance) | Low ("black box") |
| When to use | Simple, linearly separable data | Complex, non-linear patterns |

Real-World Applications

1. Medical Diagnosis: Diabetes Prediction

Linear Model:

- **Inputs:** Blood sugar level
- **Model:** $p(\text{Diabetes}|x) = \sigma(-5 + 0.5 \times \text{blood sugar})$
- **Works well:** Simple, clear relationship

Neural Network:

- **Inputs:** Blood sugar, BMI, age, blood pressure, family history
- **Hidden layers:** Capture complex interactions
- **Example:** High blood sugar is worse if you're older AND have family history
- **Better accuracy:** Can model non-linear interactions

2. Spam Email Detection

Linear Model:

- **Features:** Word counts ("free", "money", "winner")
- **Simple weights:** "free" = +2.5, "money" = +1.8
- **Fast and interpretable**

Neural Network:

- **Features:** Word embeddings (semantic representations)
- **Hidden layers:** Capture context and relationships

- **Example:** "free" is spam-like in "free money" but not in "feel free to reply"
- **Higher accuracy:** Context-aware

3. Credit Card Fraud Detection

Linear Model:

- **Features:** Transaction amount, location
- **Decision boundary:** Straight line

Neural Network:

- **Features:** Amount, location, time, merchant type, user history
- **Complex patterns:** "Large transactions late at night in foreign country from new merchant type"
- **Adaptive:** Learns new fraud patterns automatically

□ Key Mathematical Insights

1. Why Sigmoid?

Desired properties for $p(Y = 1|x)$:

1. **Range** $[0, 1]$ ✓
2. **Monotonic** (larger $z \rightarrow$ higher probability) ✓
3. **Smooth** (differentiable for gradient descent) ✓
4. **Interpretable** (log-odds interpretation) ✓

Log-odds connection:

$$\log \left(\frac{p(Y = 1|x)}{1 - p(Y = 1|x)} \right) = z(\alpha, x)$$

This means the linear combination z represents **log-odds!**

2. Why Non-linearity in Hidden Layers?

Without non-linearity:

$$h = Ax + b$$

$$y = Ch + d = C(Ax + b) + d = (CA)x + (Cb + d)$$

Result: Still linear! Multiple layers collapse to one layer.

With non-linearity:

$$h = f(Ax + b)$$

Now we can't simplify - true depth!

⌚ Pros and Cons

Linear Models (Logistic Regression):

✓ Pros:

1. **Fast training:** Few parameters
2. **Interpretable:** Can see feature importance
3. **Less data needed:** Fewer parameters to learn
4. **No overfitting risk:** (with regularization)
5. **Stable:** Convex optimization (guaranteed convergence)

✗ Cons:

1. **Limited expressiveness:** Only linear boundaries
2. **Feature engineering required:** Must manually create good features
3. **Poor on complex tasks:** Can't capture interactions
4. **Underfitting:** Too simple for real-world data

Neural Networks:

✓ Pros:

1. **Automatic feature learning:** No manual engineering
2. **Universal approximation:** Can learn any function
3. **State-of-the-art:** Best performance on complex tasks
4. **Flexible:** Same architecture for images, text, audio
5. **Transfer learning:** Pre-trained models available

✗ Cons:

1. **Data hungry:** Needs large datasets
2. **Computationally expensive:** Slow training
3. **Black box:** Hard to interpret
4. **Hyperparameters:** Many design choices (layers, units, activation, etc.)
5. **Overfitting risk:** Many parameters can memorize training data

□ Connection to Autoregressive Models

This is crucial for understanding upcoming topics!

Classification: $p(Y|x; \theta)$

- Model probability of class Y given features x

Autoregressive: $p(x_i|x_1, \dots, x_{i-1}; \theta)$

- Model probability of next feature x_i given previous features $x_{<i}$

Same techniques:

- Use sigmoid/softmax for probabilities
- Use neural networks for complex dependencies
- Train with maximum likelihood

Key insight: In autoregressive models:

- **Classification target:** Next pixel/word/token
- **Input features:** All previous pixels/words/tokens
- **Architecture:** Exactly what we just learned!

✓ Key Takeaways for Topic 3

1. **Logistic regression:** Linear model with sigmoid activation
2. **Neural networks:** Non-linear transformations via hidden layers
3. **Hidden layers create new features** that capture complex patterns
4. **Universal approximation:** Neural networks can learn any function
5. **Trade-off:** Simplicity vs expressiveness
6. **Connection to generation:** Same math, different application!

□ Check Your Understanding:

1. Why can't we stack linear layers without activation functions?
2. What happens to $\sigma(z)$ when $z \rightarrow \infty$?
3. In a neural network with 10 inputs, 5 hidden units, and 1 output, how many parameters?
 - **Answer:** $10 \times 5 + 5 + 5 \times 1 + 1 = 61$ parameters

Ready for Topic 4: "Running Example - MNIST"? This will show how we apply these concepts to real image data! Type "yes" to continue! ☺

"Running Example - MNIST"

TOPIC 4: RUNNING EXAMPLE - MNIST

□ Concept: The Standard Benchmark for Generative Models

MNIST (Modified National Institute of Standards and Technology) is a dataset of **handwritten digits** that serves as the "Hello World" of machine learning. We'll use it to understand how to build generative models for images.

Key Challenge: How do we learn a probability distribution over images so we can generate new, realistic digit images?

This topic bridges theory to practice - everything we've learned will now be applied to real data!

□ Detailed Explanation

What is MNIST?

Dataset Composition:

- **Training set:** 60,000 grayscale images
- **Test set:** 10,000 grayscale images
- **Image size:** 28×28 pixels = 784 pixels total
- **Content:** Handwritten digits (0-9)
- **Preprocessing:** Centered, normalized

For generative modeling, we use "binarized MNIST":

- Each pixel is either **black (0)** or **white (1)**
- Simplifies the problem (binary instead of 256 gray levels)
- Each image becomes a vector: $x \in \{0, 1\}^{784}$

□ Visual Understanding: MNIST Images

From slides (Page 5) - Sample digits:

Actual images from dataset:

```
9 3 0 2 6 0 1 4 5 7  
8 6 2 3 6 8 4 1 9 4  
4 6 9 3 1 1 1 5 9 6  
...
```

Each image:

- 28 pixels wide
- 28 pixels tall
- Black/white only (binary)
- Represents one handwritten digit

Key observation: Even though they're the same digit (e.g., all "3"s), each person writes differently!

□ The Mathematical Challenge

The Enormous Space

Problem statement:

- Each pixel: 2 choices (black or white)
- Total pixels: 784
- Total possible images: 2^{784}

Let's understand how big 2^{784} is:

$$2^{784} \approx 1.2 \times 10^{236}$$

For comparison:

- **Atoms in observable universe:** $\approx 10^{80}$
- **Seconds since Big Bang:** $\approx 10^{18}$
- **All possible images:** 10^{236} (incomprehensibly larger!)

From slides (Page 5): "Remember, $2^{(784)}$ possible images!"

Implication: We can't store probabilities for all possible images - we need a smart model!

The Goal: Learn $p(x)$

Mathematical formulation:

Given dataset $D = \{x^{(1)}, x^{(2)}, \dots, x^{(m)}\}$ where each $x^{(i)} \in \{0, 1\}^{784}$

Goal: Learn probability distribution:

$$p(x) = p(x_1, x_2, \dots, x_{784})$$

Such that:

If $x \sim p(x)$, then x looks like a handwritten digit

Notation breakdown:

- $x = (x_1, x_2, \dots, x_{784})$: A single image (784 pixels)
- $x_i \in \{0, 1\}$: The i -th pixel (black or white)
- $p(x)$: Probability that this particular image configuration appears
- $x \sim p(x)$: Sample a new image from the distribution

□ The Two-Step Approach

From slides (Page 5):

Step 1: Parameterize a Model Family $p_\theta(x)$

What this means:

- Choose a **model architecture** (how to represent $p(x)$)
- Define **parameters** $\theta \in \Theta$ that control the model
- Create a **flexible family** of distributions

Example architectures:

1. **Fully independent model** (naive):

$$p_\theta(x) = \prod_{i=1}^{784} p_{\theta_i}(x_i)$$

- Each pixel independent
- **Problem:** Ignores relationships between pixels!

2. Autoregressive model (today's focus):

$$p_{\theta}(x) = \prod_{i=1}^{784} p_{\theta_i}(x_i | x_1, \dots, x_{i-1})$$

- Each pixel depends on previous pixels
- **Better:** Captures dependencies!

3. Neural network conditional:

$$p_{\theta}(x_i | x_{<i}) = \text{Neural Net}_{\theta}(x_1, \dots, x_{i-1})$$

- Use neural networks for flexible modeling
- **Best:** Can learn complex patterns!

Step 2: Search for Model Parameters θ Based on Training Data

Objective: Maximum Likelihood Estimation (MLE)

$$\theta^* = \arg \max_{\theta} \prod_{j=1}^m p_{\theta}(x^{(j)})$$

In practice, use log-likelihood:

$$\theta^* = \arg \max_{\theta} \sum_{j=1}^m \log p_{\theta}(x^{(j)})$$

Why log-likelihood?

1. **Numerical stability:** Products of small numbers → underflow
2. **Easier optimization:** Sums are easier than products
3. **Equivalent:** $\arg \max$ doesn't change
4. **Additive:** Can process in mini-batches

Average log-likelihood (more common):

$$\mathcal{L}(\theta) = \frac{1}{m} \sum_{j=1}^m \log p_{\theta}(x^{(j)})$$

This is what we **maximize** during training!

□ Detailed Mathematical Example

Let's work with a **tiny 2×2 image** (4 pixels) to understand the process.

Setup:

- Image: $2 \times 2 = 4$ pixels
- Pixels ordered: top-left \rightarrow top-right \rightarrow bottom-left \rightarrow bottom-right
- Each pixel: $x_i \in \{0, 1\}$

Sample images:

Image 1: $[1 \ 0]$ \rightarrow $x = [1, 0, 1, 1]$
 $[1 \ 1]$

Image 2: $[0 \ 1]$ \rightarrow $x = [0, 1, 0, 0]$
 $[0 \ 0]$

Naive Independent Model:

$$p_\theta(x) = p(x_1) \cdot p(x_2) \cdot p(x_3) \cdot p(x_4)$$

Parameters: $\theta = (\theta_1, \theta_2, \theta_3, \theta_4)$

Where $\theta_i = p(x_i = 1)$

Example: If $\theta = (0.7, 0.3, 0.6, 0.8)$

For Image 1: $x = [1, 0, 1, 1]$

$$\begin{aligned} p_\theta(x) &= p(x_1 = 1) \cdot p(x_2 = 0) \cdot p(x_3 = 1) \cdot p(x_4 = 1) \\ &= 0.7 \times (1 - 0.3) \times 0.6 \times 0.8 \\ &= 0.7 \times 0.7 \times 0.6 \times 0.8 \\ &= 0.2352 \end{aligned}$$

Log-likelihood:

$$\log p_\theta(x) = \log(0.7) + \log(0.7) + \log(0.6) + \log(0.8) = -1.446$$

Problem: This model assumes pixels are independent - unrealistic!

Autoregressive Model:

$$p_\theta(x) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2) \cdot p(x_4|x_1, x_2, x_3)$$

Parameters: Different θ for each conditional

Example: For Image 1: $x = [1, 0, 1, 1]$

$$\begin{aligned} p(x_1 = 1) &= 0.6 \\ p(x_2 = 0|x_1 = 1) &= 0.7 \\ p(x_3 = 1|x_1 = 1, x_2 = 0) &= 0.8 \\ p(x_4 = 1|x_1 = 1, x_2 = 0, x_3 = 1) &= 0.9 \end{aligned}$$

$$p_\theta(x) = 0.6 \times 0.7 \times 0.8 \times 0.9 = 0.302$$

Notice: Higher probability than independent model ($0.302 > 0.2352$) because it captures dependencies!

□ Practical Example: Training on MNIST

Let's see how training works with actual MNIST data.

Training Dataset (simplified):

Sample images in training set:

$x^{(1)}$: Image of "3" $\rightarrow p_\theta(x^{(1)})$ should be high

$x^{(2)}$: Image of "7" $\rightarrow p_\theta(x^{(2)})$ should be high

$x^{(3)}$: Image of "1" $\rightarrow p_\theta(x^{(3)})$ should be high

...

$x^{(60000)}$: Image of "9" $\rightarrow p_\theta(x^{(60000)})$ should be high

Objective Function:

$$\mathcal{L}(\theta) = \frac{1}{60000} \sum_{j=1}^{60000} \log p_\theta(x^{(j)})$$

Goal: Find θ^* that maximizes $\mathcal{L}(\theta)$

Training Process (Gradient Descent):

Initialize: Random parameters θ_0

Iteration t :

1. **Compute gradient:** $\nabla_\theta \mathcal{L}(\theta_t)$
2. **Update parameters:** $\theta_{t+1} = \theta_t + \eta \nabla_\theta \mathcal{L}(\theta_t)$
 - η is learning rate (e.g., 0.001)

Convergence: When $\mathcal{L}(\theta)$ stops improving

Example Numbers:

| Epoch | Avg Log-Likelihood | Interpretation |
|------------|--------------------|-----------------|
| 0 (random) | -547.2 | Poor model |
| 10 | -320.5 | Getting better |
| 50 | -162.3 | Good model |
| 100 | -95.7 | Very good model |
| 500 | -84.2 | Near optimal |

Higher log-likelihood = Better model!

Pixel Ordering: Raster Scan

From slides (Page 5): Images show a specific ordering of pixels.

What is Raster Scan Order?

Definition: Read pixels left-to-right, top-to-bottom (like reading English text)

Visual representation:

28x28 MNIST Image:

| | | | | | |
|------------------|------------------|------------------|-----|------------------|----------|
| X ₁ | X ₂ | X ₃ | ... | X ₂₈ | (row 1) |
| X ₂₉ | X ₃₀ | X ₃₁ | ... | X ₅₆ | (row 2) |
| X ₅₇ | X ₅₈ | X ₅₉ | ... | X ₈₄ | (row 3) |
| ... | | | | | |
| X ₇₅₇ | X ₇₅₈ | X ₇₅₉ | ... | X ₇₈₄ | (row 28) |

Ordering: $x_1, x_2, x_3, \dots, x_{784}$

Why this matters for autoregressive models:

When predicting x_{100} (pixel at position 100):

- **Can use:** x_1, x_2, \dots, x_{99} (all previous pixels)
- **Cannot use:** $x_{101}, x_{102}, \dots, x_{784}$ (future pixels)

This ordering creates causality: Past → Present (never Future → Present)

Diagram Description: MNIST Example Visualization

From slides (Page 5) - Multiple components:

1. Training Data Visualization:

Grid of handwritten digits:

| | | | | | | | | | |
|-----|---|---|---|---|---|---|---|---|---|
| 9 | 3 | 0 | 2 | 6 | 0 | 1 | 4 | 5 | 7 |
| 8 | 6 | 2 | 3 | 6 | 8 | 4 | 1 | 9 | 4 |
| ... | | | | | | | | | |

Key observations:

- Same digit looks different (variation)
- Clear patterns for each digit
- Some digits similar (6 vs 0, 1 vs 7)

2. Probability Distribution Concept:

Model Family (M):

P_{data} ← → P_θ

d(P_{data}, P_θ)

$$\theta \in M$$

- Goal: Find θ that makes $P\theta \approx P_{\text{data}}$
- P_{data} : true distribution (unknown)
 - $P\theta$: our model
 - $d(\cdot, \cdot)$: distance measure

3. Data Representation:

$$x_t \sim P_{\text{data}}$$
$$t = 1, 2, \dots, n$$

Multiple samples from true data distribution
Learn to match this distribution

□ Real-World Applications Beyond MNIST

1. Medical Imaging: X-Ray Analysis

Scenario: Learn probability distribution of healthy lung X-rays

Approach:

- **Training data:** 100,000 healthy lung X-rays
- **Image size:** $256 \times 256 = 65,536$ pixels
- **Model:** Autoregressive neural network
- **Application:** Detect pneumonia, tumors (low $p(x)$ = anomaly)

Benefits:

- No need for labeled abnormal data
- Can detect novel diseases
- Provides probability score for severity

2. Manufacturing: PCB Inspection

Scenario: Quality control for printed circuit boards (PCBs)

Approach:

- **Training data:** Images of defect-free PCBs
- **Model:** Learn $p(x)$ for correct PCBs
- **Detection:** Defective PCB has low $p(x)$

Advantages:

- Faster than human inspection
- Consistent quality standards
- Real-time processing

3. Document Verification: Signature Detection

Scenario: Verify authentic signatures for bank checks

Approach:

- **Training data:** 1,000 genuine signatures from a person
- **Model:** Learn personal signature distribution
- **Verification:** Forged signature has low probability

Implementation:

- Mobile banking apps
- ATM check deposits
- Legal document verification

4. Astronomy: Galaxy Classification

Scenario: Identify unusual cosmic events

Approach:

- **Training data:** Millions of "normal" galaxy images
- **Model:** Learn typical galaxy patterns
- **Discovery:** Rare phenomena have low $p(x)$

Real discoveries:

- New galaxy types
- Gravitational lenses
- Supernova precursors

□ Parameter Count Analysis

Understanding model complexity:

For MNIST (784 pixels):

1. Fully Independent Model:

$$\text{Parameters} = 784$$

Each pixel has one parameter (probability of being white)

2. Fully Visible Sigmoid Belief Network (FVSBN):

$$\text{Parameters} = 1 + 2 + 3 + \dots + 784 = \frac{784 \times 785}{2} = 307,720$$

Calculation explanation:

- x_1 : 1 parameter (no dependencies)

- x_2 : 2 parameters (depends on x_1 , needs α_0^2, α_1^2)
- x_3 : 3 parameters (depends on x_1, x_2)
- ...
- x_{784} : 784 parameters

Total: Arithmetic series sum = $\frac{n(n+1)}{2}$

3. NADE (Neural Autoregressive):

$$\text{Parameters} = d \times n + d + n \times (d + 1)$$

If $d = 500$ hidden units and $n = 784$:

$$\text{Parameters} = 500 \times 784 + 500 + 784 \times 501 = 785,284$$

Components:

- $W \in \mathbb{R}^{d \times n}$: 392,000 parameters (shared weights)
- $c \in \mathbb{R}^d$: 500 parameters (hidden biases)
- $\alpha_i, b_i \in \mathbb{R}^{d+1}$: 784×501 parameters (output layers)

⚖ Trade-offs for MNIST Models

| Model Type | Parameters | Expressiveness | Training Speed | Generation Quality |
|-------------|------------|----------------|-----------------|---------------------|
| Independent | 784 | Very Low | Very Fast | Poor (no structure) |
| FVSBN | 307K | Medium | Medium | Good |
| NADE | 785K | High | Medium | Very Good |
| PixelRNN | 1M+ | Very High | Slow | Excellent |
| PixelCNN | 1M+ | Very High | Fast (parallel) | Excellent |

▣ Key Mathematical Insights

1. The Curse of Dimensionality

$$2^{784} \approx 10^{236} \text{ possible images}$$

Implication: Cannot enumerate all possibilities - need structured model!

2. Chain Rule Decomposition

$$p(x_1, \dots, x_{784}) = \prod_{i=1}^{784} p(x_i | x_1, \dots, x_{i-1})$$

Power: Breaks huge problem into 784 smaller problems!

3. Log-Likelihood Objective

$$\mathcal{L}(\theta) = \frac{1}{m} \sum_{j=1}^m \sum_{i=1}^{784} \log p_\theta(x_i^{(j)} | x_{<i}^{(j)})$$

Interpretation: Average surprise of model over all pixels and all training examples

Lower surprise = Better model!

✓ Key Takeaways for Topic 4

1. **MNIST is the standard testbed** for generative models (784-dimensional binary images)
2. **Challenge:** 2^{784} possible images - cannot store all probabilities
3. **Solution:** Parameterize model family $p_\theta(x)$ and learn θ
4. **Two steps:** Choose architecture, optimize parameters via maximum likelihood
5. **Ordering matters:** Raster scan creates causal structure for autoregressive models
6. **Scalability:** Same principles apply to larger images, text, audio, etc.
7. **Real applications:** Medical imaging, quality control, fraud detection, astronomy

□ Check Your Understanding:

1. Why can't we store probabilities for all 2^{784} possible MNIST images?
2. What's the difference between $p(x)$ and $p_\theta(x)$?
3. How many parameters in a FVSBN for a 4×4 image (16 pixels)?
 - o **Answer:** $\frac{16 \times 17}{2} = 136$ parameters
4. Why do we maximize log-likelihood instead of likelihood?

Ready for Topic 5: "Autoregressive Models - Core Concept"? This is where everything comes together! We'll see how to actually build these models! Type "yes" to continue! ☺

Topic 5: "Autoregressive Models - Core Concept"?

TOPIC 5: AUTOREGRESSIVE MODELS - CORE CONCEPT

□ Concept: Decomposing Complex Distributions into Sequential Predictions

Autoregressive (AR) models are a class of generative models that break down the problem of modeling a complex joint distribution $p(x_1, x_2, \dots, x_n)$ into a **sequence of simpler conditional distributions**.

Core Idea: Instead of modeling the entire image at once, predict **one pixel at a time**, conditioning each prediction on all previous pixels.

Why "Autoregressive"?

- "Auto" = Self (the variable predicts itself)
- "Regressive" = Using past values to predict future values
- Unlike traditional regression (predicting external label Y), here we predict the data itself!

□ Detailed Explanation

The Fundamental Problem

Direct approach (intractable):

$$p(x_1, x_2, \dots, x_{784}) \text{ requires } 2^{784} - 1 \text{ parameters}$$

Why -1? Probabilities must sum to 1, so the last one is determined.

Autoregressive approach (tractable):

$$p(x_1, x_2, \dots, x_{784}) = \prod_{i=1}^{784} p(x_i | x_1, \dots, x_{i-1})$$

Now we need to specify 784 conditional distributions instead of one massive joint distribution!

□ STEP 1: Chain Rule Factorization

Mathematical Foundation:

Chain Rule of Probability (always true, no assumptions):

$$p(x_1, x_2, x_3, x_4) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2) \cdot p(x_4|x_1, x_2, x_3)$$

General form for n variables:

$$p(x_1, \dots, x_n) = \prod_{i=1}^n p(x_i | x_1, \dots, x_{i-1})$$

Compact notation:

$$p(x) = \prod_{i=1}^n p(x_i | x_{<i})$$

Where $x_{<i}$ means "all variables before position i"

□ Proof of Chain Rule (for understanding):

For 3 variables:

Start with joint probability:

$$p(x_1, x_2, x_3)$$

Step 1: Apply definition of conditional probability:

$$p(x_3|x_1, x_2) = \frac{p(x_1, x_2, x_3)}{p(x_1, x_2)}$$

Rearrange:

$$p(x_1, x_2, x_3) = p(x_3|x_1, x_2) \cdot p(x_1, x_2)$$

Step 2: Apply again to $p(x_1, x_2)$:

$$p(x_1, x_2) = p(x_2|x_1) \cdot p(x_1)$$

Step 3: Substitute back:

$$p(x_1, x_2, x_3) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2)$$

Key insight: This is ALWAYS true - no assumptions made!

□ Simple Numerical Example: Chain Rule

Scenario: Weather for 3 days (Sunny=1, Rainy=0)

Given probabilities:

- $p(x_1 = 1) = 0.7$ (70% chance sunny on day 1)
- $p(x_2 = 1|x_1 = 1) = 0.8$ (if day 1 sunny, 80% chance day 2 sunny)
- $p(x_2 = 1|x_1 = 0) = 0.4$ (if day 1 rainy, 40% chance day 2 sunny)
- $p(x_3 = 1|x_1 = 1, x_2 = 1) = 0.9$ (both sunny → 90% chance day 3 sunny)

Calculate: $p(x_1 = 1, x_2 = 1, x_3 = 1)$ = "All three days sunny"

$$\begin{aligned} p(x_1 = 1, x_2 = 1, x_3 = 1) &= p(x_1 = 1) \cdot p(x_2 = 1|x_1 = 1) \cdot p(x_3 = 1|x_1 = 1, x_2 = 1) \\ &= 0.7 \times 0.8 \times 0.9 \\ &= 0.504 \end{aligned}$$

Interpretation: 50.4% probability of three consecutive sunny days!

Compare with: $p(x_1 = 0, x_2 = 1, x_3 = 1)$ = "Rainy, then two sunny"

$$\begin{aligned} &= p(x_1 = 0) \cdot p(x_2 = 1|x_1 = 0) \cdot p(x_3 = 1|x_1 = 0, x_2 = 1) \\ &= 0.3 \times 0.4 \times 0.7 \\ &= 0.084 \end{aligned}$$

Much less likely! (8.4% vs 50.4%)

□ STEP 2: Choosing an Ordering

Why Order Matters

Key fact: The chain rule works for **ANY ordering** of variables!

Different orderings give different factorizations:

Ordering 1: x_1, x_2, x_3, x_4

$$p(x) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2) \cdot p(x_4|x_1, x_2, x_3)$$

Ordering 2: x_4, x_3, x_2, x_1 (reverse)

$$p(x) = p(x_4) \cdot p(x_3|x_4) \cdot p(x_2|x_3, x_4) \cdot p(x_1|x_2, x_3, x_4)$$

Ordering 3: x_2, x_4, x_1, x_3 (random)

$$p(x) = p(x_2) \cdot p(x_4|x_2) \cdot p(x_1|x_2, x_4) \cdot p(x_3|x_1, x_2, x_4)$$

All compute the same $p(x)$, but with different conditional structures!


For Images: Raster Scan Ordering

From slides (Page 6):

"We can pick an ordering of all the random variables, e.g., **raster scan ordering** of pixels from top-left (X_1) to bottom-right ($X_{n=784}$)"

Visual representation:

28×28 MNIST Image:



Ordering: Natural reading order (left→right, top→bottom)

Why raster scan?

1. **Natural:** Matches how humans read/scan
2. **Spatial locality:** Nearby pixels are nearby in sequence
3. **Efficient:** Easy to implement
4. **Hardware-friendly:** Matches image storage format

Other possible orderings:

- **Spiral:** Start from center, spiral outward
- **Hilbert curve:** Space-filling curve (preserves locality)
- **Random:** Sometimes used for robustness

- **Learned:** Let model learn optimal ordering

□ STEP 3: Modeling the Conditionals

The Challenge:

Now we have:

$$p(x_1, \dots, x_{784}) = p(x_1) \cdot p(x_2|x_1) \cdot p(x_3|x_1, x_2) \dots \cdot p(x_{784}|x_1, \dots, x_{783})$$

Problem: How do we specify each $p(x_i|x_{<i})$?

From slides (Page 6): "Avoid complex conditionals, assume a functional form"

Approach: Use Parametric Models

General form:

$$p(x_1, \dots, x_n) = p_{\text{CPT}}(x_1; \alpha^1) \prod_{i=2}^n p_{\text{logit}}(x_i|x_{<i}; \alpha^i)$$

Components:

- **CPT** (Conditional Probability Table): For first variable (no dependencies)
- **logit** (Logistic regression): For subsequent variables

Detailed: Logistic Regression for Conditionals

From slides (Page 6):

For binary variables ($x_i \in \{0, 1\}$):

$$p_{\text{logit}}(X_i = 1|x_{<i}; \alpha^i) = \sigma \left(\alpha_0^i + \sum_{j=1}^{i-1} \alpha_j^i x_j \right)$$

Where $\sigma(z) = \frac{1}{1+e^{-z}}$ is the sigmoid function.

Equivalently:

$$p(X_i = 0|x_{<i}; \alpha^i) = 1 - \sigma \left(\alpha_0^i + \sum_{j=1}^{i-1} \alpha_j^i x_j \right)$$

□ Specific Examples from Slides (Page 6):

First pixel (no dependencies):

$$p_{\text{CPT}}(X_1 = 1; \alpha^1) = \alpha^1$$

$$p(X_1 = 0) = 1 - \alpha^1$$

Simple probability parameter: $\alpha^1 \in [0, 1]$

Second pixel (depends on x_1):

$$p_{\text{logit}}(X_2 = 1|x_1; \alpha^2) = \sigma(\alpha_0^2 + \alpha_1^2 x_1)$$

Expanding:

$$p(X_2 = 1|x_1; \alpha^2) = \frac{1}{1 + \exp(-\alpha_0^2 - \alpha_1^2 x_1)}$$

Parameters: $\alpha^2 = (\alpha_0^2, \alpha_1^2)$ - two parameters

Two cases:

- If $x_1 = 0$: $p(X_2 = 1|x_1 = 0) = \sigma(\alpha_0^2)$
- If $x_1 = 1$: $p(X_2 = 1|x_1 = 1) = \sigma(\alpha_0^2 + \alpha_1^2)$

Third pixel (depends on x_1, x_2):

$$p_{\text{logit}}(X_3 = 1|x_1, x_2; \alpha^3) = \sigma(\alpha_0^3 + \alpha_1^3 x_1 + \alpha_2^3 x_2)$$

Parameters: $\alpha^3 = (\alpha_0^3, \alpha_1^3, \alpha_2^3)$ - three parameters

Four cases:

- $x_1 = 0, x_2 = 0$: $p = \sigma(\alpha_0^3)$
- $x_1 = 1, x_2 = 0$: $p = \sigma(\alpha_0^3 + \alpha_1^3)$
- $x_1 = 0, x_2 = 1$: $p = \sigma(\alpha_0^3 + \alpha_2^3)$
- $x_1 = 1, x_2 = 1$: $p = \sigma(\alpha_0^3 + \alpha_1^3 + \alpha_2^3)$

□ Comprehensive Numerical Example

Scenario: Tiny 2×2 image (4 pixels)

$$\begin{bmatrix} x_1 & x_2 \\ x_3 & x_4 \end{bmatrix}$$

Goal: Model $p(x_1, x_2, x_3, x_4)$ using autoregressive model with logistic regression

Model Specification:

First pixel:

$$p(X_1 = 1) = \alpha^1 = 0.6$$

Second pixel:

$$p(X_2 = 1|x_1) = \sigma(\alpha_0^2 + \alpha_1^2 x_1)$$

with $\alpha_0^2 = -0.5, \alpha_1^2 = 1.0$

Third pixel:

$$p(X_3 = 1|x_1, x_2) = \sigma(\alpha_0^3 + \alpha_1^3 x_1 + \alpha_2^3 x_2)$$

with $\alpha_0^3 = -1.0, \alpha_1^3 = 0.8, \alpha_2^3 = 1.5$

Fourth pixel:

$$p(X_4 = 1|x_1, x_2, x_3) = \sigma(\alpha_0^4 + \alpha_1^4 x_1 + \alpha_2^4 x_2 + \alpha_3^4 x_3)$$

with $\alpha_0^4 = -0.8, \alpha_1^4 = 0.5, \alpha_2^4 = 0.7, \alpha_3^4 = 1.2$

Example 1: Calculate $p(x = [1, 0, 1, 1])$

Step 1: $p(x_1 = 1)$

$$p(x_1 = 1) = 0.6$$

Step 2: $p(x_2 = 0|x_1 = 1)$

$$\begin{aligned} p(x_2 = 1|x_1 = 1) &= \sigma(-0.5 + 1.0 \cdot 1) \\ &= \sigma(0.5) \\ &= \frac{1}{1 + e^{-0.5}} \\ &= 0.622 \end{aligned}$$

$$p(x_2 = 0|x_1 = 1) = 1 - 0.622 = 0.378$$

Step 3: $p(x_3 = 1|x_1 = 1, x_2 = 0)$

$$\begin{aligned} p(x_3 = 1|x_1 = 1, x_2 = 0) &= \sigma(-1.0 + 0.8 \cdot 1 + 1.5 \cdot 0) \\ &= \sigma(-0.2) \\ &= 0.450 \end{aligned}$$

Step 4: $p(x_4 = 1|x_1 = 1, x_2 = 0, x_3 = 1)$

$$\begin{aligned} p(x_4 = 1|x_1 = 1, x_2 = 0, x_3 = 1) &= \sigma(-0.8 + 0.5 \cdot 1 + 0.7 \cdot 0 + 1.2 \cdot 1) \\ &= \sigma(0.9) \\ &= 0.711 \end{aligned}$$

Final calculation:

$$\begin{aligned} p(x = [1, 0, 1, 1]) &= 0.6 \times 0.378 \times 0.450 \times 0.711 \\ &= 0.0726 \end{aligned}$$

Log-likelihood:

$$\log p(x) = \log(0.6) + \log(0.378) + \log(0.450) + \log(0.711) = -2.623$$

Example 2: Calculate $p(x = [0, 1, 1, 0])$

Step 1: $p(x_1 = 0) = 1 - 0.6 = 0.4$

Step 2: $p(x_2 = 1|x_1 = 0) = \sigma(-0.5 + 1.0 \cdot 0) = \sigma(-0.5) = 0.378$

Step 3: $p(x_3 = 1|x_1 = 0, x_2 = 1) = \sigma(-1.0 + 0 + 1.5) = \sigma(0.5) = 0.622$

Step 4: $p(x_4 = 0|x_1 = 0, x_2 = 1, x_3 = 1)$

$$p(x_4 = 1| \dots) = \sigma(-0.8 + 0 + 0.7 + 1.2) = \sigma(1.1) = 0.750$$
$$p(x_4 = 0| \dots) = 1 - 0.750 = 0.250$$


Final:

$$p(x = [0, 1, 1, 0]) = 0.4 \times 0.378 \times 0.622 \times 0.250 = 0.0235$$

Interpretation: This configuration is less likely than !^[8]

□ Diagram Description: Autoregressive Structure

From slides (Page 7) - Key visual:



Explanation:

- **Auto (Self):** The variable predicts **itself** (part of the data)
- **Regressive:** Uses **regression** (logistic) to make predictions
- **Contrast:** Regular logistic regression predicts external label Y
- **Here:** Predict next pixel from previous pixels (internal prediction)

From slides (Page 6) - Autoregressive factorization:

$$\begin{aligned} p(x_1, x_2, x_3, \dots, x_{784}) &= \\ p(x_1) &\times \\ p(x_2|x_1) &\times \\ p(x_3|x_1, x_2) &\times \\ \dots &\times \\ p(x_n|x_1, \dots, x_{n-1}) \end{aligned}$$

Each conditional: $p(x_i|x_{<i}; \alpha^i) = \sigma(\alpha_0^i + \sum_j \alpha_j^i x_j)$

Sequential structure:

$x_1 \rightarrow [\text{Predict } x_2] \rightarrow x_2 \rightarrow [\text{Predict } x_3] \rightarrow x_3 \rightarrow \dots$

□ Real-World Applications

1. Time Series Forecasting: Stock Prices

Scenario: Predict tomorrow's stock price

Autoregressive formulation:

$$p(\text{price}_t | \text{price}_{t-1}, \text{price}_{t-2}, \dots, \text{price}_{t-30})$$

Model:

- **Ordering:** Time (natural for sequences)
- **Conditionals:** Neural network or linear regression
- **Prediction:** Generate future prices by sampling

Application:

- Trading algorithms
- Risk management
- Portfolio optimization

2. Text Generation: Language Models

Scenario: Generate coherent sentences

Autoregressive formulation:

$$p(w_1, w_2, \dots, w_n) = \prod_{i=1}^n p(w_i | w_1, \dots, w_{i-1})$$

Example: "The cat sat on the ___"

- $p(\text{"mat"} | \text{"The cat sat on the"}) = 0.4$
- $p(\text{"chair"} | \text{"The cat sat on the"}) = 0.3$
- $p(\text{"moon"} | \text{"The cat sat on the"}) = 0.001$

Real systems: GPT-3, GPT-4, ChatGPT (all autoregressive!)

3. Music Generation: Composing Melodies

Scenario: Generate piano music

Autoregressive formulation:

- **Variables:** Musical notes over time
- **Ordering:** Temporal (note by note)
- **Conditionals:** RNN or Transformer

Application:

- Background music for videos
- Personalized playlists
- Composition assistance

4. Medical: Patient Health Monitoring

Scenario: Monitor patient vital signs in ICU

Autoregressive formulation:

$$p(\text{vitals}_t | \text{vitals}_{<t}, \text{medications}, \text{patient history})$$

Variables:

- Heart rate
- Blood pressure
- Oxygen saturation
- Temperature

Application:

- Early warning system (low $p(\text{vitals}_t)$ = alarm!)
- Treatment planning
- Resource allocation

□ Key Mathematical Insights

1. No Loss of Generality

Chain rule is exact:

$$p(x_1, \dots, x_n) = \prod_{i=1}^n p(x_i | x_{<i})$$

No assumptions made! This is always true for any probability distribution.

The modeling happens: When we choose functional forms for $p(x_i | x_{<i})$

2. Sequential Decomposition

Huge problem → Many small problems:

Before:

- Model $p(x)$ over 2^{784} configurations

After:

- Model 784 conditionals $p(x_i | x_{<i})$

- Each conditional is a binary classification problem!

Advantage: Binary classification is well-understood (logistic regression, neural networks)

3. Sampling is Sequential

To generate a new image:

```
# Pseudocode
x = [] # empty image
for i in 1 to 784:
    # Sample pixel i given all previous pixels
    prob_i = model(x[1:i-1])
    x[i] = sample_bernoulli(prob_i)
return x
```

Must be sequential: Can't parallelize generation (but can parallelize training!)

4. Exact Likelihood Computation

Given any image x , we can compute exact $p(x)$:

$$\log p(x) = \sum_{i=1}^n \log p(x_i | x_{<i})$$

Advantage over other generative models:

- VAEs: Only approximate likelihood
- GANs: No likelihood at all!
- Autoregressive: **Exact likelihood ✓**

⚖ Pros and Cons of Autoregressive Models

✓ **Pros:**

1. **Exact likelihood:** Can compute $p(x)$ exactly
 - Good for density estimation
 - Good for model comparison
 - Good for anomaly detection
2. **Flexible:** Works for any data type
 - Images (pixels)
 - Text (words)
 - Audio (samples)
 - Time series (values)
3. **Theoretically sound:** Based on probability chain rule

- No approximations in the decomposition
 - Well-understood mathematics
4. **Easy to extend:** Can model different variable types
- Binary (Bernoulli)
 - Categorical (Softmax)
 - Continuous (Gaussian)
5. **State-of-the-art:** Achieves excellent results
- Text: GPT-4
 - Images: PixelCNN++
 - Audio: WaveNet

✗ Cons:

1. **Sequential generation:** Slow sampling
 - Must generate pixel-by-pixel
 - Can't generate all pixels in parallel
 - 784 forward passes for one MNIST image!
2. **Arbitrary ordering:** Must choose an ordering
 - Different orderings = different models
 - No clear "best" ordering for some data
 - Images: raster scan reasonable
 - Graphs: no natural ordering!
3. **Long-range dependencies:** Hard to capture
 - x_{784} should depend on x_1, \dots, x_{783}
 - Information bottleneck in hidden states
 - Attention mechanisms help but add complexity
4. **No natural features:** Unlike VAEs
 - VAEs have latent code z (useful representation)
 - Autoregressive: no explicit feature vector
 - Harder for downstream tasks (classification, search)
5. **Exposure bias during training:**
 - Train: condition on **true** previous pixels
 - Test: condition on **generated** previous pixels
 - Mismatch can cause error accumulation

□ Deep Dive: Why "Autoregressive"?

Comparison with traditional regression:

Traditional Regression:

$$p(Y|X) = f(X; \theta)$$

- **Y:** External target (label)
- **X:** Input features
- **Example:** Predict house price from size, location, age

Autoregressive:

$$p(X_i|X_1, \dots, X_{i-1}) = f(X_1, \dots, X_{i-1}; \theta)$$

- **Target:** Part of the data itself (X_i)
- **Input:** Other parts of data ($X_{<i}$)
- **Example:** Predict pixel 100 from pixels 1-99

Key difference: Autoregressive models predict the **data onto itself** - "auto" (self) regression!

✓ Key Takeaways for Topic 5

1. **Chain rule factorization:** Break $p(x)$ into product of conditionals
2. **Always exact:** Chain rule is mathematically exact, no approximations
3. **Ordering required:** Must choose sequence for variables
4. **Logistic regression:** Model each conditional with parametric function
5. **"Autoregressive":** Self-predicting (predict data from itself)
6. **Exact likelihood:** Can compute $p(x)$ exactly (major advantage)
7. **Sequential sampling:** Must generate one variable at a time (slow)
8. **State-of-the-art:** Used in modern systems (GPT, PixelCNN, WaveNet)

□ Check Your Understanding:

1. **Why is chain rule exact?** (It's just factoring probabilities, always valid)
2. **What's the difference between Bayes Net and autoregressive?**
 - Bayes Net: Independence assumptions
 - Autoregressive: Full chain rule (no independence assumed)
3. **Calculate:** For 3 binary variables with ordering x_1, x_2, x_3 , how many parameters needed if using logistic regression for conditionals?
 - x_1 : 1 parameter
 - x_2 : 2 parameters (α_0^2, α_1^2)
 - x_3 : 3 parameters ($\alpha_0^3, \alpha_1^3, \alpha_2^3$)

- Total: 6 parameters
4. Why can't we parallelize sampling? (Need x_{i-1} before generating x_i)

Ready for Topic 6: "Fully Visible Sigmoid Belief Network (FVSBN)"? This is our first concrete autoregressive architecture! Type "yes" to continue! ☺

✿

"Fully Visible Sigmoid Belief Network (FVSBN)"?

TOPIC 6: FULLY VISIBLE SIGMOID BELIEF NETWORK (FVSBN)

□ Concept: The Simplest Autoregressive Model

Fully Visible Sigmoid Belief Network (FVSBN) is the **most basic autoregressive model** that uses **logistic regression** for each conditional probability. It's "fully visible" because every variable can see (depend on) all previous variables - no hidden variables!

Key Idea: Model each pixel as a Bernoulli random variable whose probability depends on all previous pixels through a simple linear function passed through a sigmoid.

Why it matters: FVSBN is the foundation - understanding this makes all advanced models (NADE, PixelCNN, etc.) easier to understand!

□ Detailed Explanation

What is FVSBN?

Components of the name:

- **Fully Visible:** All variables are observed (no latent/hidden variables)
- **Sigmoid:** Uses sigmoid function $\sigma(z) = \frac{1}{1+e^{-z}}$
- **Belief Network:** A directed graphical model (Bayesian network)

Structure:

- Each variable X_i depends on **ALL** previous variables X_1, \dots, X_{i-1}
- No independence assumptions (unlike simpler Bayes Nets)
- Uses logistic regression for conditional probabilities

□ Mathematical Formulation

Core Equation (from slides, Page 9):

For binary variables $X_i \in \{0, 1\}$, the conditional probabilities are:

$$\hat{x}_i = p(X_i = 1 | x_1, \dots, x_{i-1}; \alpha^i) = p(X_i = 1 | x_{<i}; \alpha^i) = \sigma \left(\alpha_0^i + \sum_{j=1}^{i-1} \alpha_j^i x_j \right)$$

Where:

- \hat{x}_i : Predicted probability that pixel i is white (1)
- $x_{<i} = (x_1, \dots, x_{i-1})$: All previous pixel values
- $\alpha^i = (\alpha_0^i, \alpha_1^i, \dots, \alpha_{i-1}^i)$: Parameters for conditional i
- $\sigma(z) = \frac{1}{1+e^{-z}}$: Sigmoid/logistic function

Expanding the summation:

$$\hat{x}_i = \sigma(\alpha_0^i + \alpha_1^i x_1 + \alpha_2^i x_2 + \dots + \alpha_{i-1}^i x_{i-1})$$

Full Joint Distribution:

$$p(x_1, \dots, x_n) = \prod_{i=1}^n p(x_i | x_{<i}; \alpha^i)$$

For each conditional:

$$p(x_i | x_{<i}; \alpha^i) = \begin{cases} \hat{x}_i & \text{if } x_i = 1 \\ 1 - \hat{x}_i & \text{if } x_i = 0 \end{cases}$$

Compact form (Bernoulli):

$$p(x_i | x_{<i}; \alpha^i) = \hat{x}_i^{x_i} (1 - \hat{x}_i)^{1-x_i}$$

Parameter Count Analysis

From slides (Page 9): "How many parameters?"

$$\text{Total parameters} = 1 + 2 + 3 + \dots + n = \frac{n(n+1)}{2}$$

Breakdown:

- Variable X_1 : 1 parameter (α_0^1)
- Variable X_2 : 2 parameters (α_0^2, α_1^2)
- Variable X_3 : 3 parameters ($\alpha_0^3, \alpha_1^3, \alpha_2^3$)
- ...
- Variable X_n : n parameters

This is an arithmetic series:

$$S_n = \frac{n(n+1)}{2}$$

For MNIST (n=784 pixels):

$$\text{Parameters} = \frac{784 \times 785}{2} = 307,720$$

Memory/computation grows quadratically with image size!

□ Simple Numerical Example: 4-Pixel Image

Let's work through a complete example with a **2×2 image (4 pixels)**.

Image structure:

$$\begin{bmatrix} x_1 & x_2 \\ x_3 & x_4 \end{bmatrix}$$

Raster scan order: $x_1 \rightarrow x_2 \rightarrow x_3 \rightarrow x_4$

Step 1: Define Model Parameters

Pixel 1 (no dependencies):

$$\alpha^1 = [\alpha_0^1] = [0.2]$$

$$\hat{x}_1 = \sigma(0.2) = \frac{1}{1 + e^{-0.2}} = 0.550$$

Pixel 2 (depends on x_1):

$$\alpha^2 = [\alpha_0^2, \alpha_1^2] = [-0.5, 1.5]$$

$$\hat{x}_2 = \sigma(-0.5 + 1.5x_1)$$

Pixel 3 (depends on x_1, x_2):

$$\alpha^3 = [\alpha_0^3, \alpha_1^3, \alpha_2^3] = [-1.0, 0.8, 1.2]$$

$$\hat{x}_3 = \sigma(-1.0 + 0.8x_1 + 1.2x_2)$$

Pixel 4 (depends on x_1, x_2, x_3):

$$\alpha^4 = [\alpha_0^4, \alpha_1^4, \alpha_2^4, \alpha_3^4] = [-0.3, 0.6, 0.9, 1.1]$$

$$\hat{x}_4 = \sigma(-0.3 + 0.6x_1 + 0.9x_2 + 1.1x_3)$$

Total parameters: $1 + 2 + 3 + 4 = 10$

Step 2: Evaluate Probability for Image $x = [0, 1, 1, 0]$

From slides (Page 9): "How to evaluate $p(x_1, \dots, x_4)$? Multiply all the conditionals"

$$p(x_1 = 0, x_2 = 1, x_3 = 1, x_4 = 0) = p(x_1 = 0) \times p(x_2 = 1|x_1 = 0) \times p(x_3 = 1|x_1 = 0, x_2 = 1)$$

Calculate $p(x_1 = 0)$:

$$\hat{x}_1 = \sigma(0.2) = 0.550$$

$$p(x_1 = 0) = 1 - \hat{x}_1 = 1 - 0.550 = 0.450$$

Calculate $p(x_2 = 1|x_1 = 0)$:

$$\hat{x}_2 = \sigma(-0.5 + 1.5 \times 0) = \sigma(-0.5) = \frac{1}{1 + e^{0.5}} = \frac{1}{1.649} = 0.378$$

$$p(x_2 = 1|x_1 = 0) = \hat{x}_2 = 0.378$$

Calculate $p(x_3 = 1|x_1 = 0, x_2 = 1)$:

$$\hat{x}_3 = \sigma(-1.0 + 0.8 \times 0 + 1.2 \times 1) = \sigma(0.2) = 0.550$$

$$p(x_3 = 1|x_1 = 0, x_2 = 1) = \hat{x}_3 = 0.550$$

Calculate $p(x_4 = 0|x_1 = 0, x_2 = 1, x_3 = 1)$:

$$\hat{x}_4 = \sigma(-0.3 + 0.6 \times 0 + 0.9 \times 1 + 1.1 \times 1) = \sigma(1.7) = \frac{1}{1 + e^{-1.7}} = 0.846$$

$$p(x_4 = 0|x_1 = 0, x_2 = 1, x_3 = 1) = 1 - \hat{x}_4 = 1 - 0.846 = 0.154$$

Final probability:

$$\begin{aligned} p(x = [0, 1, 1, 0]) &= 0.450 \times 0.378 \times 0.550 \times 0.154 \\ &= 0.0144 \end{aligned}$$

Log-likelihood:

$$\log p(x) = \log(0.450) + \log(0.378) + \log(0.550) + \log(0.154) = -4.240$$

From slides (Page 9) - Example calculation:

$$\begin{aligned} p(x_1=0, x_2=1, x_3=1, x_4=0) &= (1 - \hat{x}_1) \times \hat{x}_2 \times \hat{x}_3 \times (1 - \hat{x}_4) \\ &= (1 - \hat{x}_1) \times \hat{x}_2(X_1=0) \times \hat{x}_3(X_1=0, X_2=1) \times (1 - \hat{x}_4(X_1=0, X_2=1, X_3=1)) \end{aligned}$$

This matches our calculation!

Sampling from FVSBN

From slides (Page 9): "How to sample $p(x_1, \dots, x_{784})$?"

Algorithm (Ancestral Sampling):

1. Sample $x_1' \sim p(x_1)$
2. Sample $x_2' \sim p(x_2 \mid x_1 = x_1')$
3. Sample $x_3' \sim p(x_3 \mid x_1 = x_1', x_2 = x_2')$
- ...
- n. Sample $x_n' \sim p(x_n \mid x_1 = x_1', \dots, x_{n-1} = x_{n-1}')$

Sequential process: Must generate pixels one at a time!

Detailed Sampling Example:

Using our 4-pixel model, let's generate a sample image.

Step 1: Sample x'_1

$$p(X_1 = 1) = \hat{x}_1 = 0.550$$

- Draw random number $u_1 \sim \text{Uniform}(0, 1)$
- Suppose $u_1 = 0.62$
- Since $0.62 > 0.550$, set $x'_1 = 0$

Step 2: Sample x'_2 given $x'_1 = 0$

$$p(X_2 = 1|x_1 = 0) = \sigma(-0.5 + 1.5 \times 0) = 0.378$$

- Draw $u_2 = 0.25$
- Since $0.25 < 0.378$, set $x'_2 = 1$

Step 3: Sample x'_3 given $x'_1 = 0, x'_2 = 1$

$$p(X_3 = 1|x_1 = 0, x_2 = 1) = \sigma(-1.0 + 0 + 1.2) = 0.550$$

- Draw $u_3 = 0.80$
- Since $0.80 > 0.550$, set $x'_3 = 0$

Step 4: Sample x'_4 given $x'_1 = 0, x'_2 = 1, x'_3 = 0$

$$p(X_4 = 1|x_1 = 0, x_2 = 1, x_3 = 0) = \sigma(-0.3 + 0 + 0.9 + 0) = \sigma(0.6) = 0.646$$

- Draw $u_4 = 0.50$
- Since $0.50 < 0.646$, set $x'_4 = 1$

Generated image:

$$x' = [0, 1, 0, 1]$$


```
[0  1]  
[0  1]
```

Key observation: Each sample is different! We can generate infinitely many samples.

□ Diagram Description: FVSBN Structure

From slides (Page 9) - Network visualization:

Graphical Model:



Connections (bottom row):

- x_1 : No inputs (marginal)
- x_2 : Connected to x_1
- x_3 : Connected to x_1, x_2
- x_4 : Connected to x_1, x_2, x_3

Parameter sets:

- τ_1 : Parameters for \hat{x}_1
- τ_2 : Parameters for \hat{x}_2
- τ_3 : Parameters for \hat{x}_3
- τ_4 : Parameters for \hat{x}_4

Key insights:

1. **Fully connected:** Each variable connected to ALL previous ones
2. **No hidden layers:** Direct mapping from previous variables to prediction
3. **Directed acyclic graph (DAG):** Arrows only go forward in sequence
4. **Increasing complexity:** Later variables have more inputs

□ Real-World Applications

1. Medical Imaging: Caltech 101 Silhouettes

From slides (Page 10): "Training data on the left (Caltech 101 Silhouettes). Samples from the model on the right."

Application: Generate realistic object silhouettes

Dataset:

- Binary images (black/white)
- Various object categories (animals, vehicles, etc.)
- Used for shape analysis

Results:

- FVSBN can generate plausible new silhouettes
- Maintains shape coherence
- Some samples look realistic, others less so

Use cases:

- Data augmentation for classification
- Shape completion (fill in missing parts)
- Anomaly detection (unusual shapes)

2. Handwriting Generation: MNIST Digits

Application: Generate synthetic handwritten digits

Process:

1. Train FVSBN on 60,000 MNIST training images
2. Sample new digits from learned distribution
3. Use for:
 - Expanding training datasets
 - Testing digit recognition systems
 - Creating CAPTCHA systems

Quality:

- Generated digits recognizable
- Some variability in style
- Occasional unrealistic samples

3. Document Binarization

Application: Convert grayscale documents to black/white

Approach:

- Train FVSBN on clean binary documents
- Use model to predict whether each pixel should be black/white
- Denoising: $p(x_i = 1 | \text{noisy neighbors})$

Benefits:

- Removes noise
- Preserves text structure
- OCR-friendly output

4. Texture Synthesis

Application: Generate seamless textures

Examples:

- Wood grain patterns
- Fabric weaves
- Stone surfaces

Method:

- Train on texture samples
- Generate larger textures by sampling
- Ensure local consistency through autoregressive structure

□ Deep Dive: Why It Works

The Linear Predictor

Each conditional uses a **linear combination** of previous pixels:

$$z_i = \alpha_0^i + \sum_{j=1}^{i-1} \alpha_j^i x_j$$

Interpretation:

- α_0^i : **Bias** - baseline probability when all previous pixels are 0
- α_j^i : **Weight** - how much pixel j influences pixel i
 - **Positive weight:** If $x_j = 1$, increases probability of $x_i = 1$
 - **Negative weight:** If $x_j = 1$, decreases probability of $x_i = 1$

Example interpretation for MNIST:

- Pixel 400 (middle of digit)
- Positive weight from pixel 371 (directly above) → vertical continuity
- Positive weight from pixel 399 (left neighbor) → horizontal continuity
- Large negative weight from distant background pixel → context awareness

The Sigmoid Transform

$$\hat{x}_i = \sigma(z_i) = \frac{1}{1 + e^{-z_i}}$$

Why sigmoid?

1. **Maps to:** Valid probability range [0, 1]
2. **Smooth:** Gradients exist everywhere (good for learning)

3. **Interpretable:** Relates to log-odds

4. **Bounded:** Never goes to exactly 0 or 1 (numerical stability)

Log-odds interpretation:

$$\log \left(\frac{\hat{x}_i}{1 - \hat{x}_i} \right) = z_i$$

The linear predictor z_i represents **log-odds** that pixel is white!

⌚ Training FVSBN

Objective: Maximum Likelihood Estimation

$$\theta^* = \arg \max_{\theta} \sum_{k=1}^m \log p_{\theta}(x^{(k)})$$

Expanding for FVSBN:

$$\log p_{\theta}(x^{(k)}) = \sum_{i=1}^n \log p(x_i^{(k)} | x_{<i}^{(k)}; \alpha^i)$$

Bernoulli log-likelihood:

$$\log p(x_i | x_{<i}; \alpha^i) = x_i \log \hat{x}_i + (1 - x_i) \log(1 - \hat{x}_i)$$

This is binary cross-entropy loss!

Gradient Descent Update

For each parameter α_j^i :

$$\alpha_j^i \leftarrow \alpha_j^i + \eta \frac{\partial \mathcal{L}}{\partial \alpha_j^i}$$

Gradient (using chain rule):

$$\frac{\partial \mathcal{L}}{\partial \alpha_j^i} = \sum_{k=1}^m (x_i^{(k)} - \hat{x}_i^{(k)}) \cdot x_j^{(k)}$$

Intuition:

- If $x_i = 1$ but \hat{x}_i is low \rightarrow increase α_j (if $x_j = 1$)
- If $x_i = 0$ but \hat{x}_i is high \rightarrow decrease α_j (if $x_j = 1$)

□ Computational Complexity

Training:

Forward pass (one image):

- For each pixel i : compute $\sum_{j=1}^{i-1} \alpha_j^i x_j$
- Total operations: $1 + 2 + \dots + n = O(n^2)$

For MNIST: $O(784^2) \approx 614,000$ operations per image

Backward pass: Similar complexity $O(n^2)$

Total training time: Manageable for small images, slow for large images

Sampling:

Generate one image:

- Must sample sequentially: n forward passes
- Each pass: $O(i)$ operations for pixel i
- Total: $O(n^2)$

For MNIST: Cannot parallelize - takes time!

❖ Pros and Cons of FVSBN

✓ Pros:

1. Simple and interpretable:

- Just logistic regression at each step
- Can inspect learned weights α_j^i
- Understand pixel dependencies

2. Exact likelihood:

- Can compute $p(x)$ exactly for any image
- Good for anomaly detection
- Model comparison via likelihood

3. Flexible:

- Works for any binary data
- Easy to extend to categorical (use softmax)
- No complex architectures needed

4. Well-understood:

- Based on standard logistic regression
- Convex optimization for each conditional

- Stable training
- 5. Baseline:**
- Good starting point for research
 - Compare more complex models against FVSBN

✗ Cons:

1. Quadratic parameters: $O(n^2)$

- For 784 pixels: 307,720 parameters
- For 256×256 image: 2.1 billion parameters!
- Memory intensive

2. Quadratic computation:

- Training: $O(n^2)$ per image
- Sampling: $O(n^2)$ per sample
- Doesn't scale to large images

3. Linear dependencies only:

- Each conditional is simple logistic regression
- Cannot capture complex non-linear relationships
- Example: XOR patterns between pixels

4. Slow sampling:

- Must generate pixel-by-pixel (sequential)
- Cannot parallelize generation
- Takes ~784 forward passes for one MNIST digit

5. Limited expressiveness:

- No hidden representations
- Direct pixel-to-pixel connections only
- May underfit complex distributions

6. Ordering-dependent:

- Different orderings give different models
- Raster scan may not be optimal
- No easy way to try all orderings

□ Connection to More Advanced Models

FVSBN is the **foundation** - other models build on it:

FVSBN → NADE:

- Add hidden layer for non-linear features
- Shared weights across conditionals

- More expressive, similar parameter count

FVSBN → MADE:

- Use autoencoder architecture
- Masking to preserve autoregressive structure
- Parallel computation during training

FVSBN → PixelRNN:

- Use RNN to summarize history
- Constant memory (no growing parameter count)
- Better for long sequences

FVSBN → PixelCNN:

- Use convolutional architecture
- Exploit spatial structure
- Much faster training

□ Key Mathematical Insights

1. Factorization is Everything

$$p(x) = \prod_{i=1}^n p(x_i | x_{<i})$$

Each term is independent once we condition on previous variables!

Implication: Can train each conditional separately (though we usually train jointly)

2. Log-Likelihood Decomposes

$$\log p(x) = \sum_{i=1}^n \log p(x_i | x_{<i})$$

Implication: Loss is a sum - can compute gradients efficiently

3. Bernoulli Distribution

Each pixel is Bernoulli with parameter \hat{x}_i :

$$X_i | x_{<i} \sim \text{Bernoulli}(\hat{x}_i)$$

PMF:

$$p(x_i) = \hat{x}_i^{x_i} (1 - \hat{x}_i)^{1-x_i}$$

Elegant notation that handles both $x_i = 0$ and $x_i = 1$ cases!

✓ Key Takeaways for Topic 6

1. **FVSBN = Simplest autoregressive model** using logistic regression
2. **Fully visible:** No hidden variables, all previous pixels visible
3. **Parameters scale quadratically:** $\frac{n(n+1)}{2}$ for n pixels
4. **Exact likelihood:** Can compute and maximize exact $p(x)$
5. **Sequential sampling:** Generate pixel-by-pixel (slow)
6. **Linear conditionals:** Each prediction is linear combination + sigmoid
7. **Foundation:** Understanding FVSBN makes advanced models easier
8. **Trade-off:** Simple but limited expressiveness

□ Check Your Understanding:

1. **Why "fully visible"?** (All variables observed, no hidden layers)
2. **Calculate parameters for 10-pixel image:**
 - o Answer: $\frac{10 \times 11}{2} = 55$ parameters
3. **Why is sampling slow?** (Must generate sequentially, can't parallelize)
4. **What's the main limitation?** (Linear dependencies only, no non-linearity)
5. **How does FVSBN relate to logistic regression?** (Each conditional IS logistic regression)

Ready for Topic 7: "Neural Autoregressive Density Estimation (NADE)"? This addresses FVSBN's limitations by adding hidden layers! Type "yes" to continue! ☺

**

Topic 7: "Neural Autoregressive Density Estimation (NADE)"?

TOPIC 7: NEURAL AUTOREGRESSIVE DENSITY ESTIMATION (NADE)

□ Concept: Adding Non-Linearity to Autoregressive Models

NADE (Neural Autoregressive Density Estimation) improves upon FVSBN by replacing simple logistic regression with **one-layer neural networks**. This allows the model to learn **non-linear relationships** between pixels while keeping the parameter count manageable.

Key Innovation: Instead of directly mapping previous pixels to predictions, NADE first creates **hidden features** that capture complex patterns, then uses these features for predictions.

Why it matters: NADE achieves better performance than FVSBN with similar computational cost - it's the "sweet spot" between simplicity and expressiveness!

□ Detailed Explanation

The Limitation of FVSBN

FVSBN problem:

$$p(x_i|x_{<i}) = \sigma(\alpha_0^i + \sum_{j=1}^{i-1} \alpha_j^i x_j)$$

This is purely linear! Cannot capture:

- Non-linear interactions (e.g., "pixel is white if BOTH left AND top neighbors are white")
- Complex patterns (e.g., corners, edges, textures)
- Higher-order dependencies

Example failure case:

- XOR pattern: $x_i = 1$ if exactly one of x_{i-1} or x_{i-2} is 1
- Linear model cannot learn XOR!

Solution: Add hidden layer(s) for non-linear feature extraction!

□ NADE Architecture

Mathematical Formulation (from slides, Page 11):

Two-step process for each conditional:

Step 1: Compute hidden layer

$$\mathbf{h}_i = \sigma(A_i \mathbf{x}_{<i} + \mathbf{c}_i)$$

Step 2: Compute output (prediction)

$$\hat{x}_i = p(x_i|x_1, \dots, x_{i-1}; A_i, \mathbf{c}_i, \boldsymbol{\alpha}_i, b_i) = \sigma(\boldsymbol{\alpha}_i \mathbf{h}_i + b_i)$$

Where:

- $\mathbf{x}_{<i} = (x_1, \dots, x_{i-1})$: Previous pixel values (input)
- A_i : Weight matrix from inputs to hidden layer
- \mathbf{c}_i : Bias vector for hidden layer
- \mathbf{h}_i : Hidden layer activations (learned features)
- $\boldsymbol{\alpha}_i$: Weights from hidden layer to output
- b_i : Bias for output
- $\sigma(\cdot)$: Sigmoid activation (applied element-wise to vectors)

Expanded Form (from slides, Page 11):

For a specific example:

$$\mathbf{h}_2 = \sigma \left(\begin{pmatrix} \vdots \\ \vdots \\ \vdots \end{pmatrix} x_1 + \begin{pmatrix} \vdots \\ \vdots \\ \vdots \end{pmatrix} \right)$$
$$\mathbf{h}_3 = \sigma \left(\begin{pmatrix} \vdots & \vdots \\ \vdots & \vdots \end{pmatrix} \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} + \begin{pmatrix} \vdots \\ \vdots \end{pmatrix} \right)$$

With proper notation:

For \mathbf{h}_2 (depends on x_1 only):

$$\mathbf{h}_2 = \sigma(A_2 x_1 + \mathbf{c}_2)$$

where A_2 is a column vector (or matrix with one column)

For \mathbf{h}_3 (depends on x_1, x_2):

$$\mathbf{h}_3 = \sigma \left(A_3 \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} + \mathbf{c}_3 \right)$$

where A_3 is a matrix with two columns

□ Key Innovation: Weight Tying

From slides (Page 12): "Tie weights to reduce the number of parameters and speed up computation"

The Problem with Naive NADE

If we use **different** weight matrices for each conditional:

- A_1 for \mathbf{h}_1
- A_2 for \mathbf{h}_2
- ...
- A_n for \mathbf{h}_n

Parameter count explodes!

The Solution: Shared Weight Matrix

Instead of different matrices, use ONE shared matrix $W \in \mathbb{R}^{d \times n}$:

$$\mathbf{h}_i = \sigma(W_{:, <i} \mathbf{x}_{<i} + \mathbf{c})$$

Notation: $W_{:, <i}$ means "columns of W up to position $i - 1$ "

From slides (Page 12):

$$\mathbf{h}_i = \sigma(W_{:, <i} \mathbf{x}_{<i} + \mathbf{c})$$

$$\hat{x}_i = p(x_i | x_1, \dots, x_{i-1}) = \sigma(\boldsymbol{\alpha}_i \mathbf{h}_i + b_i)$$

Concrete Example with Weight Tying:

Shared weight matrix:

$$W = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \end{bmatrix}$$

(Assume $d = 2$ hidden units, $n = 3$ pixels)

Shared bias:

$$\mathbf{c} = \begin{bmatrix} c_1 \\ c_2 \end{bmatrix}$$

For \mathbf{h}_2 (use only first column):

$$\mathbf{h}_2 = \sigma \left(\begin{bmatrix} w_{11} \\ w_{21} \end{bmatrix} x_1 + \begin{bmatrix} c_1 \\ c_2 \end{bmatrix} \right)$$

For \mathbf{h}_3 (use first two columns):

$$\mathbf{h}_3 = \sigma \left(\begin{bmatrix} w_{11} & w_{12} \\ w_{21} & w_{22} \end{bmatrix} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + \begin{bmatrix} c_1 \\ c_2 \end{bmatrix} \right)$$

From slides (Page 12) - Visual representation:

$$h_2 = \sigma([w_1] \cdot x_1 + c) \quad h_3 = \sigma([w_1 \ w_2] \cdot [x_1/x_2] + c) \quad h_4 = \sigma([w_1 \ w_2 \ w_3] \cdot [x_1/x_2/x_3] + c)$$

$\underbrace{}_{W:, <2} \quad \underbrace{}_{W:, <3} \quad \underbrace{}_{W:, <4}$

Key insight: We reuse the same weight columns! w_1 appears in all three computations.

□ Parameter Count (from slides, Page 12)

Question: "If $h_i \in \mathbb{R}^d$, how many total parameters?"

Components:

1. **Weight matrix** $W \in \mathbb{R}^{d \times n}$: $d \times n$ parameters
2. **Shared bias** $\mathbf{c} \in \mathbb{R}^d$: d parameters
3. **Output weights and biases:** For each pixel i , we need $\boldsymbol{\alpha}_i \in \mathbb{R}^d$ and $b_i \in \mathbb{R}$
 - Total: $n \times (d + 1)$ parameters

Total parameters:

$$\boxed{\text{Parameters} = d \times n + d + n \times (d + 1) = d(n + 1) + n(d + 1) = d + n + 2dn}$$

Simplified:

$$\text{Parameters} = d + n + 2dn \approx O(dn)$$

Linear in $n!$ (compared to FVSBN's $O(n^2)$)

Example: MNIST with $d = 500$ hidden units

For MNIST: $n = 784$ pixels, $d = 500$ hidden units

$$\begin{aligned}\text{Parameters} &= 500 \times 784 + 500 + 784 \times 501 \\ &= 392,000 + 500 + 392,784 \\ &= 785,284\end{aligned}$$

Compare to FVSBN: 307,720 parameters

NADE has more parameters but much more expressive!

□ Detailed Numerical Example: 4-Pixel NADE

Let's work through a complete example with **4 pixels** and $d = 2$ hidden units.

Setup: Model Parameters

Shared weight matrix:

$$W = \begin{bmatrix} 0.5 & -0.3 & 0.8 & 0.2 \\ 0.7 & 0.4 & -0.2 & 0.6 \end{bmatrix} \in \mathbb{R}^{2 \times 4}$$

Shared bias:

$$\mathbf{c} = \begin{bmatrix} -0.5 \\ 0.3 \end{bmatrix}$$

Output weights (different for each pixel):

$$\boldsymbol{\alpha}_1 = \text{N/A} \quad (\text{first pixel has no dependencies})$$

$$\boldsymbol{\alpha}_2 = \begin{bmatrix} 1.2 \\ 0.8 \end{bmatrix}, \quad b_2 = -0.4$$

$$\boldsymbol{\alpha}_3 = \begin{bmatrix} 0.9 \\ 1.1 \end{bmatrix}, \quad b_3 = -0.6$$

$$\boldsymbol{\alpha}_4 = \begin{bmatrix} 1.5 \\ 0.6 \end{bmatrix}, \quad b_4 = -0.3$$

First pixel (special case):

$$\hat{x}_1 = \text{Simple probability parameter} = 0.6$$

Calculate $p(x = [1, 0, 1, 1])$

Step 1: $p(x_1 = 1)$

$$p(x_1 = 1) = 0.6$$

Step 2: $p(x_2 = 0|x_1 = 1)$

Compute hidden layer:

$$\begin{aligned}\mathbf{h}_2 &= \sigma(W_{:,1}x_1 + \mathbf{c}) = \sigma\left(\begin{bmatrix} 0.5 \\ 0.7 \end{bmatrix} \cdot 1 + \begin{bmatrix} -0.5 \\ 0.3 \end{bmatrix}\right) \\ &= \sigma\left(\begin{bmatrix} 0.5 - 0.5 \\ 0.7 + 0.3 \end{bmatrix}\right) = \sigma\left(\begin{bmatrix} 0 \\ 1.0 \end{bmatrix}\right) \\ &= \begin{bmatrix} \sigma(0) \\ \sigma(1.0) \end{bmatrix} = \begin{bmatrix} 0.500 \\ 0.731 \end{bmatrix}\end{aligned}$$

Compute output:

$$\begin{aligned}\hat{x}_2 &= \sigma(\boldsymbol{\alpha}_2^T \mathbf{h}_2 + b_2) = \sigma\left(\begin{bmatrix} 1.2 & 0.8 \end{bmatrix} \begin{bmatrix} 0.500 \\ 0.731 \end{bmatrix} - 0.4\right) \\ &= \sigma(1.2 \times 0.500 + 0.8 \times 0.731 - 0.4) \\ &= \sigma(0.6 + 0.585 - 0.4) = \sigma(0.785) = 0.687\end{aligned}$$

Therefore:

$$p(x_2 = 0|x_1 = 1) = 1 - 0.687 = 0.313$$

Step 3: $p(x_3 = 1|x_1 = 1, x_2 = 0)$

Compute hidden layer:

$$\begin{aligned}\mathbf{h}_3 &= \sigma\left(W_{:,1:2} \begin{bmatrix} x_1 \\ x_2 \end{bmatrix} + \mathbf{c}\right) \\ &= \sigma\left(\begin{bmatrix} 0.5 & -0.3 \\ 0.7 & 0.4 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \end{bmatrix} + \begin{bmatrix} -0.5 \\ 0.3 \end{bmatrix}\right) \\ &= \sigma\left(\begin{bmatrix} 0.5 \\ 0.7 \end{bmatrix} + \begin{bmatrix} -0.5 \\ 0.3 \end{bmatrix}\right) = \sigma\left(\begin{bmatrix} 0 \\ 1.0 \end{bmatrix}\right) \\ &= \begin{bmatrix} 0.500 \\ 0.731 \end{bmatrix}\end{aligned}$$

Compute output:

$$\begin{aligned}\hat{x}_3 &= \sigma\left(\begin{bmatrix} 0.9 & 1.1 \end{bmatrix} \begin{bmatrix} 0.500 \\ 0.731 \end{bmatrix} - 0.6\right) \\ &= \sigma(0.9 \times 0.500 + 1.1 \times 0.731 - 0.6)\end{aligned}$$

$$= \sigma(0.45 + 0.804 - 0.6) = \sigma(0.654) = 0.658$$

Therefore:

$$p(x_3 = 1 | x_1 = 1, x_2 = 0) = 0.658$$

Step 4: $p(x_4 = 1 | x_1 = 1, x_2 = 0, x_3 = 1)$

Compute hidden layer:

$$\begin{aligned} \mathbf{h}_4 &= \sigma \left(\begin{bmatrix} 0.5 & -0.3 & 0.8 \\ 0.7 & 0.4 & -0.2 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \\ 1 \end{bmatrix} + \begin{bmatrix} -0.5 \\ 0.3 \end{bmatrix} \right) \\ &= \sigma \left(\begin{bmatrix} 0.5 + 0.8 \\ 0.7 - 0.2 \end{bmatrix} + \begin{bmatrix} -0.5 \\ 0.3 \end{bmatrix} \right) \\ &= \sigma \left(\begin{bmatrix} 0.8 \\ 0.8 \end{bmatrix} \right) = \begin{bmatrix} 0.690 \\ 0.690 \end{bmatrix} \end{aligned}$$

Compute output:

$$\begin{aligned} \hat{x}_4 &= \sigma \left([1.5 \quad 0.6] \begin{bmatrix} 0.690 \\ 0.690 \end{bmatrix} - 0.3 \right) \\ &= \sigma(1.5 \times 0.690 + 0.6 \times 0.690 - 0.3) \\ &= \sigma(1.035 + 0.414 - 0.3) = \sigma(1.149) = 0.759 \end{aligned}$$

Therefore:

$$p(x_4 = 1 | x_1 = 1, x_2 = 0, x_3 = 1) = 0.759$$

Final Joint Probability:

$$\begin{aligned} p(x = [1, 0, 1, 1]) &= 0.6 \times 0.313 \times 0.658 \times 0.759 \\ &= 0.0937 \end{aligned}$$

Log-likelihood:

$$\log p(x) = \log(0.6) + \log(0.313) + \log(0.658) + \log(0.759) = -2.367$$

□ Diagram Description: NADE Architecture

From slides (Page 11) - Network visualization:

OUTPUT LAYER (Predictions):

$$\begin{array}{cccc} \hat{x}_1 & \hat{x}_2 & \hat{x}_3 & \hat{x}_4 \\ \uparrow & \uparrow & \uparrow & \uparrow \end{array}$$

HIDDEN LAYER:

$$\begin{array}{ccccccc} h_1 & & h_2 & & h_3 & & h_4 \\ \uparrow & / & \uparrow & / & \uparrow & / & \uparrow \\ | & / & | / & | / & | & & | \end{array}$$

INPUT LAYER:

X₁ X₂ X₃ X₄

Key features:

- Each h_i computed from $x_{<i}$
- Hidden units create non-linear features
- Output layer uses hidden features
- Autoregressive structure preserved

From slides (Page 11) - NADE diagram shows:

- 4 input nodes (bottom)
- 4 hidden layer groups (middle)
- 4 output nodes (top)
- Progressive connections (each hidden layer sees more inputs)

NADE Results on MNIST

From slides (Page 13): "Samples from a model trained on MNIST on the left. Conditional probabilities \hat{x}_i on the right."

Left side: Generated Samples

Generated handwritten digits:

7 9 3 1 1 9 0 9 6 6
8 6 2 3 6 8 4 1 9 4
4 6 9 3 1 1 1 5 9 6
...

Quality observations:

- Much better than FVSBN
- Digits are recognizable
- More coherent structure
- Some variability in style
- Occasional artifacts

Right side: Conditional Probability Heatmaps

Shows \hat{x}_i values as grayscale:

- **White areas:** High probability of white pixel
- **Black areas:** High probability of black pixel
- **Gray areas:** Uncertain

Interpretation:

- Model learns digit structure
- High confidence in digit strokes
- Lower confidence at boundaries
- Captures thickness variations

□ Real-World Applications

1. Medical Imaging: MRI Reconstruction

Problem: MRI scans are slow - can we reconstruct full image from partial measurements?

NADE approach:

- Train on complete MRI scans
- Given partial scan, use NADE to predict missing pixels
- $p(x_{\text{missing}} | x_{\text{observed}})$

Benefits:

- Faster scans (less radiation exposure)
- Better image quality
- Artifact removal

Real deployment:

- Hospitals use similar techniques
- Research: "Deep learning for MRI reconstruction"

2. Natural Language Processing: Text Completion

Problem: Predict next word in a sentence

NADE variant (word-level):

$$p(w_i | w_1, \dots, w_{i-1})$$

Example:

- Input: "The weather today is very"
- Predictions:
 - $p(\text{"nice"}) = 0.3$
 - $p(\text{"hot"}) = 0.25$
 - $p(\text{"cold"}) = 0.2$

Applications:

- Autocomplete in search engines
- Predictive text on smartphones
- Writing assistants

3. Financial Time Series: Stock Price Prediction

Problem: Predict next day's stock movement

NADE formulation:

- Variables: Daily price changes
- Hidden layer: Captures market patterns
- $p(\text{price}_t | \text{price}_{<t}, \text{volume}_{<t}, \text{news}_{<t})$

Benefits over linear models:

- Captures non-linear patterns
- Models complex market dynamics
- Handles multiple indicators

Use cases:

- Algorithmic trading
- Risk assessment
- Portfolio optimization

4. Climate Modeling: Weather Prediction

Problem: Predict future weather patterns

NADE approach:

- Variables: Temperature, pressure, humidity, wind speed
- Spatial ordering: Grid cells from west to east
- Temporal ordering: Time steps

Model:

$$p(\text{weather}_{t,x,y} | \text{weather}_{<t}, \text{weather}_{t,<x}, \text{weather}_{t,x,<y})$$

Applications:

- Short-term forecasts
- Extreme event prediction
- Climate change modeling

□ Extensions of NADE

1. NADE for General Discrete Distributions

From slides (Page 14): "How to model non-binary discrete random variables $X_i \in \{1, \dots, K\}^?$ "

Problem: Pixel intensities from 0 to 255 (K=256 values)

Solution: Use Softmax

$$\mathbf{h}_i = \sigma(W_{:, < i} \mathbf{x}_{< i} + \mathbf{c})$$

$$p(x_i | x_1, \dots, x_{i-1}) = \text{Cat}(p_i^1, \dots, p_i^K)$$

$$\hat{\mathbf{x}}_i = (p_i^1, \dots, p_i^K) = \text{softmax}(A_i \mathbf{h}_i + \mathbf{b}_i)$$

Softmax function (from slides):

$$\text{softmax}(\mathbf{a}) = \text{softmax}(a^1, \dots, a^K) = \left(\frac{\exp(a^1)}{\sum_i \exp(a^i)}, \dots, \frac{\exp(a^K)}{\sum_i \exp(a^i)} \right)$$

Properties of Softmax:

1. **Output is probability distribution:** Each component in, sum to 1 [10]
2. **Generalizes sigmoid:** For K=2, reduces to logistic regression
3. **Differentiable:** Good for gradient descent
4. **Interpretable:** Larger inputs \rightarrow higher probabilities

Example: 3-valued pixel

Suppose $X_i \in \{0, 1, 2\}$ (e.g., low/medium/high intensity)

Compute:

$$\mathbf{z}_i = A_i \mathbf{h}_i + \mathbf{b}_i = \begin{bmatrix} 2.0 \\ -1.0 \\ 0.5 \end{bmatrix}$$

Apply softmax:

$$\exp(\mathbf{z}_i) = \begin{bmatrix} e^{2.0} \\ e^{-1.0} \\ e^{0.5} \end{bmatrix} = \begin{bmatrix} 7.389 \\ 0.368 \\ 1.649 \end{bmatrix}$$

Sum: $7.389 + 0.368 + 1.649 = 9.406$

Probabilities:

$$\hat{\mathbf{x}}_i = \begin{bmatrix} 7.389/9.406 \\ 0.368/9.406 \\ 1.649/9.406 \end{bmatrix} = \begin{bmatrix} 0.785 \\ 0.039 \\ 0.175 \end{bmatrix}$$

Interpretation:

- 78.5% chance of value 0

- 3.9% chance of value 1
- 17.5% chance of value 2

2. Real-Valued NADE (RNADE)

From slides (Page 15): "How to model continuous random variables $X_i \in \mathbb{R}^n$?"

Examples: Speech signals, temperatures, sensor readings

Solution: Mixture of Gaussians

$$p(x_i | x_1, \dots, x_{i-1}) = \sum_{j=1}^K \frac{1}{K} \mathcal{N}(x_i; \mu_i^j, \sigma_i^j)$$

Where:

- K : Number of mixture components
- μ_i^j, σ_i^j : Mean and std dev of component j
- These parameters are outputs of the neural network!

Network outputs:

$$\hat{\mathbf{x}}_i = (\mu_i^1, \dots, \mu_i^K, \sigma_i^1, \dots, \sigma_i^K) = f(\mathbf{h}_i)$$

Ensuring positivity: Use exponential for standard deviations

$$\sigma_i^j = \exp(\text{network output}_j)$$

From slides (Page 16) - Visual representation:

Mixture of Gaussians example:

- Blue dashed curves: Individual Gaussian components
- Red solid curve: Final mixture distribution
- Can model complex, multimodal distributions

Key advantage: Can capture multiple modes

Example: "Pixel can be either very dark OR very bright"

Example: Audio waveform prediction

Continuous value: Amplitude at time t

RNADE model:

$$p(a_t | a_{<t}) = \frac{1}{3} \mathcal{N}(a_t; \mu_1, \sigma_1) + \frac{1}{3} \mathcal{N}(a_t; \mu_2, \sigma_2) + \frac{1}{3} \mathcal{N}(a_t; \mu_3, \sigma_3)$$

Network predicts:

- $\mu_1 = -0.5, \sigma_1 = 0.1$ (low amplitude mode)
- $\mu_2 = 0.0, \sigma_2 = 0.05$ (silence mode)
- $\mu_3 = 0.8, \sigma_3 = 0.15$ (high amplitude mode)

Applications:

- Speech synthesis
- Music generation
- Audio compression

⌚ Training NADE Efficiently

Key Insight: Parallel Training

From slides (Page 12): "probability is evaluated in $O(nd)$ "

During training:

- Given complete image x , compute ALL conditionals simultaneously
- Use cumulative weight matrices efficiently

Algorithm:

```
For image x:  
    # Forward pass  
    h1 = σ(W1, 0 · [] + c)           # Empty input  
    h2 = σ(W2, 1 · [x1] + c)  
    h3 = σ(W3, 1:2 · [x1, x2] + c)  
    ...  
    hn = σ(Wn, 1:n-1 · [x1, ..., xn-1] + c)  
  
    # Output layer  
    For i = 1 to n:  
        x̂i = σ(aiT hi + bi)  
  
    # Compute loss  
    loss = -Σi [xi log(x̂i) + (1-xi) log(1-x̂i)]
```

Complexity: $O(nd)$ for one image

Much faster than FVSBN's $O(n^2)$!

⚖ Pros and Cons of NADE

✓ Pros:

1. Non-linear modeling:

- Hidden layer captures complex patterns
- Can learn XOR, interactions, etc.
- Much more expressive than FVSBN

2. Efficient parameterization:

- $O(nd)$ parameters (linear in n)
- Weight sharing reduces redundancy

- Comparable to FVSBN parameter count

3. Fast training:

- $O(nd)$ computation per image
- Can compute all conditionals in parallel
- GPU-friendly operations

4. Flexible:

- Binary (sigmoid)
- Categorical (softmax)
- Continuous (mixture of Gaussians)

5. State-of-the-art (at its time):

- Better results than FVSBN
- Competitive with more complex models
- Good baseline for research

6. Exact likelihood:

- Can compute $p(x)$ exactly
- Good for model comparison
- Anomaly detection

✗ Cons:

1. Still sequential sampling:

- Must generate pixel-by-pixel
- n forward passes per sample
- Slow generation (same as FVSBN)

2. Multiple forward passes during training:

- Need to compute n hidden states per image
- More computation than single-pass models
- Can be optimized but still costly

3. Shallow architecture:

- Only one hidden layer (original NADE)
- Limited depth
- Deep NADE variants exist but more complex

4. Ordering dependence:

- Must choose pixel ordering
- Different orderings = different models
- No principled way to choose

5. No natural features:

- Unlike VAEs, no explicit latent code

- Hidden layer changes for each conditional
- Harder to use for downstream tasks

6. Memory requirements:

- Must store $W \in \mathbb{R}^{d \times n}$
- For large images and many hidden units, can be large
- Example: 256×256 image, 1000 hidden \rightarrow 65M parameters just for W

□ Key Mathematical Insights

1. Hidden Layer as Feature Extractor

$$\mathbf{h}_i = \sigma(W_{:, < i} \mathbf{x}_{< i} + \mathbf{c})$$

Interpretation: Each hidden unit is a **non-linear feature detector**

Example: For MNIST digit recognition, hidden units might detect:

- Vertical edges
- Horizontal edges
- Corners
- Curved strokes
- Thickness patterns

2. Two-Stage Prediction

Stage 1: Feature extraction (non-linear)

$$\text{Raw pixels} \rightarrow \mathbf{h}_i \rightarrow \text{Learned features}$$

Stage 2: Prediction (linear combination of features)

$$\text{Features} \rightarrow \hat{x}_i \rightarrow \text{Probability}$$

Key: Non-linearity in Stage 1 allows complex patterns, simplicity in Stage 2 keeps training stable

3. Weight Sharing Reduces Overfitting

Without sharing: Each conditional has its own weights

- More parameters \rightarrow More flexibility
- But also more risk of overfitting!

With sharing: Same weights used everywhere

- **Regularization effect:** Model must learn general features
- **Data efficiency:** Each weight sees all training examples
- **Better generalization**

4. Computational Efficiency

Clever incremental computation:

Instead of recomputing from scratch:

$$\mathbf{h}_i = \sigma(W_{:, <i} \mathbf{x}_{<i} + \mathbf{c})$$

We can update incrementally:

$$\mathbf{h}_{i+1} = \sigma(\mathbf{z}_i + W_{:, i} \mathbf{x}_i)$$

where $\mathbf{z}_i = W_{:, <i} \mathbf{x}_{<i} + \mathbf{c}$ was computed for \mathbf{h}_i

Amortized cost: $O(d)$ per pixel instead of $O(id)$

✓ Key Takeaways for Topic 7

1. **NADE adds hidden layer** to capture non-linear patterns
2. **Weight sharing** keeps parameter count linear: $O(nd)$
3. **Two-stage process:** Feature extraction → Prediction
4. **Parallel training:** Compute all conditionals simultaneously
5. **Sequential sampling:** Still generate pixel-by-pixel (slow)
6. **Extensions:** Softmax for discrete, Gaussians for continuous
7. **Better than FVSBN:** More expressive with similar efficiency
8. **Foundation for modern models:** Ideas used in PixelRNN, PixelCNN

□ Check Your Understanding:

1. **What's the main advantage of NADE over FVSBN?**
 - Non-linear hidden layer captures complex patterns
2. **How many parameters for 784 pixels, 500 hidden units?**
 - $500 \times 784 + 500 + 784 \times 501 = 785,284$
3. **Why is training faster than FVSBN despite more parameters?**
 - Parallel computation of conditionals: $O(nd)$ vs $O(n^2)$
4. **Can NADE learn XOR patterns?**
 - Yes! Hidden layer provides non-linearity
5. **What does weight sharing mean?**
 - Same weight matrix W used for all conditionals (different columns)

Ready for Topic 8: "Autoregressive Models vs Autoencoders"? This clarifies a common confusion!
Type "yes" to continue! ☺

Topic 8: "Autoregressive Models vs Autoencoders"?

TOPIC 8: AUTOREGRESSIVE MODELS vs AUTOENCODERS

□ Concept: Understanding the Fundamental Difference

This topic addresses a **common source of confusion** in deep learning: NADE and FVSBN **look similar** to autoencoders, but they serve **completely different purposes!**

Key Question: If both have inputs, hidden layers, and outputs that try to reconstruct the input, what's the difference?

Short Answer:

- **Autoencoders:** Representation learning (learn compressed features)
- **Autoregressive models:** Generative modeling (learn probability distribution)

Why it matters: Understanding this distinction is crucial for choosing the right model for your task!

□ Detailed Explanation

The Surface-Level Similarity

From slides (Page 17): "On the surface, FVSBN and NADE look similar to an autoencoder"

Both architectures have:

1. **Input layer:** Original data \mathbf{x}
2. **Hidden layer(s):** Intermediate representation
3. **Output layer:** Reconstruction $\hat{\mathbf{x}}$

Visual similarity:

```
Input → Hidden → Output  
x     →      h     →      x̂
```

This superficial similarity causes confusion!

□ AUTOENCODERS: Representation Learning

Architecture and Purpose

Goal: Learn a **compressed representation** of data that captures essential information

Components:

1. **Encoder $e(\cdot)$:** Maps input to hidden representation
$$\mathbf{h} = e(\mathbf{x}; \theta_e)$$

2. **Decoder** $d(\cdot)$: Reconstructs input from representation

$$\hat{\mathbf{x}} = d(\mathbf{h}; \theta_d)$$

From slides (Page 18) - Example encoder:

$$e(\mathbf{x}) = \sigma(W^2(\sigma(W^1\mathbf{x} + \mathbf{b}^1)) + \mathbf{b}^2)$$

Example decoder:

$$d(\mathbf{h}) = \sigma(V\mathbf{h} + \mathbf{c})$$

Loss Function (from slides, Page 18)

Objective: Minimize reconstruction error over dataset D

For binary variables:

$$\min_{W^1, W^2, \mathbf{b}^1, \mathbf{b}^2, V, \mathbf{c}} \sum_{\mathbf{x} \in D} \sum_i [-x_i \log \hat{x}_i - (1 - x_i) \log(1 - \hat{x}_i)]$$

For continuous variables:

$$\min_{W^1, W^2, \mathbf{b}^1, \mathbf{b}^2, V, \mathbf{c}} \sum_{\mathbf{x} \in D} \sum_i (x_i - \hat{x}_i)^2$$

This is just reconstruction error - NOT probability!

Key Characteristics of Autoencoders

1. **Bottleneck architecture:** Hidden layer typically smaller than input

- Example: $784 \rightarrow 128 \rightarrow 784$ (compression ratio: 6.125:1)
- Forces learning of compressed representation

2. **Bidirectional:** All inputs used to predict all outputs

- No ordering or causality
- \hat{x}_i can depend on x_j for any i, j

3. **Deterministic:** Given \mathbf{x} , always produces same \mathbf{h} and $\hat{\mathbf{x}}$

- No randomness or sampling

4. **Not a probability model:**

- Doesn't define $p(\mathbf{x})$
- Cannot compute likelihood
- Cannot sample new data points (properly)

5. **Feature learning:**

- $\mathbf{h} = e(\mathbf{x})$ is a useful representation
- Can be used for classification, clustering, etc.

□ AUTOREGRESSIVE MODELS: Generative Modeling

Architecture and Purpose

Goal: Learn a **probability distribution** $p(\mathbf{x})$ to generate new data

Structure:

$$p(\mathbf{x}) = \prod_{i=1}^n p(x_i | x_1, \dots, x_{i-1})$$

For NADE:

$$\mathbf{h}_i = \sigma(W_{:, < i} \mathbf{x}_{< i} + \mathbf{c})$$

$$\hat{x}_i = p(x_i | \mathbf{x}_{< i}) = \sigma(\boldsymbol{\alpha}_i^T \mathbf{h}_i + b_i)$$

Key Characteristics of Autoregressive Models

1. **Directed structure:** Must follow ordering

- x_i can only depend on x_1, \dots, x_{i-1}
- No "future" information used

2. **Probabilistic:** Each \hat{x}_i is a probability

- Can compute exact likelihood $p(\mathbf{x})$
- Can sample new data: $\mathbf{x}_{\text{new}} \sim p(\mathbf{x})$

3. **Variable hidden layers:** Different \mathbf{h}_i for each position

- \mathbf{h}_1 uses no inputs
- \mathbf{h}_2 uses x_1
- \mathbf{h}_3 uses x_1, x_2
- etc.

4. **No fixed bottleneck:** Hidden layer size is hyperparameter

- Can be larger or smaller than input
- Not about compression




5. **Generative model:**

- Defines valid probability distribution
- Can generate unlimited new samples
- Can detect anomalies (low $p(\mathbf{x})$)

□ Visual Comparison (from slides, Pages 17-18)

Diagram Description:

From slides (Page 17) - Three architectures:



- No ordering constraint

□ Detailed Comparison Table

| Aspect | Autoencoder | Autoregressive (NADE/FVSBN) |
|------------------------------|------------------------------------------------------|----------------------------------------------------------|
| Primary Goal | Feature learning / dimensionality reduction | Density estimation / generation |
| Output interpretation | Reconstruction (deterministic) | Probability distribution (stochastic) |
| Hidden representation | Single \mathbf{h} for entire input | Different \mathbf{h}_i for each position |
| Ordering | No ordering needed | Requires ordering (e.g., raster scan) |
| Causality | Bidirectional (all inputs \rightarrow all outputs) | Unidirectional (only past \rightarrow present) |
| Bottleneck | Typically yes (compression) | No (hidden size is free parameter) |
| Probability model | No (cannot compute $p(\mathbf{x})$) | Yes (exact $p(\mathbf{x})$ computable) |
| Sampling | Cannot properly sample new data | Can sample: $\mathbf{x}_{\text{new}} \sim p(\mathbf{x})$ |
| Likelihood | No likelihood defined | Exact log-likelihood |
| Loss function | Reconstruction error | Negative log-likelihood |
| Use cases | Denoising, compression, pretraining | Generation, anomaly detection |
| Training constraint | Bottleneck size | Autoregressive structure |
| Feature extraction | Yes (explicit \mathbf{h}) | No (implicit, varies per position) |

□ Detailed Example: MNIST Digit "3"

Let's see how both models handle the same input.

Input Image:

```
28x28 binary image of digit "3":  
x = [0,0,0,1,1,1,0,0, ..., 0,0,0]  
~~~~~ top row ~~~~~ bottom row
```

Autoencoder Processing:

Step 1: Encode entire image

$$\mathbf{h} = e(\mathbf{x}) = \sigma(W^2 \sigma(W^1 \mathbf{x} + \mathbf{b}^1) + \mathbf{b}^2)$$

Suppose $\mathbf{h} \in \mathbb{R}^{64}$ (compressed from 784 to 64)

Result: Single vector capturing "essence of 3"

$$\mathbf{h} = [0.23, 0.89, 0.12, \dots, 0.67] \quad (64 \text{ numbers})$$

Interpretation:

- Maybe h_1 encodes "has vertical stroke"
- Maybe h_2 encodes "has curves"
- Maybe h_3 encodes "orientation"

Step 2: Decode to reconstruction

$$\hat{\mathbf{x}} = d(\mathbf{h}) = \sigma(V\mathbf{h} + \mathbf{c})$$

Result: Reconstructed image (hopefully similar to input)

$$\hat{\mathbf{x}} = [0.02, 0.01, 0.03, 0.91, 0.88, 0.92, 0.04, 0.01, \dots]$$

Goal: $\hat{\mathbf{x}} \approx \mathbf{x}$

Use of \mathbf{h} :

- Feed to classifier to predict "3"
- Use for image search (similar \mathbf{h} = similar images)
- Visualize to understand what model learned

NNADE Processing:

Step 1: Predict first pixel (no input)

$$p(x_1) = \text{simple parameter} = 0.05$$

(First pixel usually background \rightarrow low probability)

Step 2: Predict second pixel given first

$$\mathbf{h}_2 = \sigma(W_{:,1}x_1 + \mathbf{c})$$

Suppose $x_1 = 0$:

$$\mathbf{h}_2 = \sigma(\mathbf{c}) = [0.45, 0.62, 0.31, \dots] \quad (500 \text{ numbers})$$

$$\hat{x}_2 = p(x_2 = 1|x_1 = 0) = \sigma(\boldsymbol{\alpha}_2^T \mathbf{h}_2 + b_2) = 0.08$$

Step 3: Predict third pixel given first two

$$\mathbf{h}_3 = \sigma(W_{:,1:2}[x_1, x_2]^T + \mathbf{c})$$

And so on for all 784 pixels...

Final output: Probability of entire image

$$p(\mathbf{x}) = \prod_{i=1}^{784} p(x_i|x_{<i}) = 0.05 \times 0.92 \times 0.87 \times \dots = 10^{-142}$$

(Tiny number - typical for high-dimensional discrete distributions!)

Log-likelihood: $\log p(\mathbf{x}) = -327.5$

Use:

- Generate new "3" images by sampling
- Detect fake "3" (low probability)
- Compare models (higher likelihood = better)

Real-World Application Examples

1. Medical Imaging: Autoencoder vs Autoregressive

Scenario: Brain MRI scans

Autoencoder approach (Feature Extraction):

- **Goal:** Find compressed representation of healthy brains
- **Input:** 3D MRI scan (millions of voxels)
- **Output:** 512-dimensional feature vector
- **Use case:**
 - Cluster patients by brain structure
 - Dimensionality reduction for visualization
 - Pretrain encoder for tumor classification

Autoregressive approach (Anomaly Detection):

- **Goal:** Learn probability distribution of healthy brains
- **Input:** 3D MRI scan
- **Output:** $p(\text{scan})$ probability value
- **Use case:**
 - Detect tumors: Scan with tumor has low $p(\text{scan})$
 - Localize anomaly: Which region has lowest conditional probability?
 - Generate synthetic training data

Which to use?

- Need features for downstream task? → Autoencoder
- Need to detect abnormalities? → Autoregressive
- Need both? → Use both! (VAE combines both ideas)

2. Natural Language: Text Representation vs Generation

Autoencoder approach (Sentence Embeddings):

- **Goal:** Map sentences to fixed-size vectors
- **Input:** "The cat sat on the mat" (7 words)
- **Hidden:** 128-dimensional sentence embedding

- **Output:** Reconstructed sentence
- **Applications:**
 - Semantic search (find similar sentences)
 - Machine translation (use as intermediate representation)
 - Sentiment analysis (classify from embedding)

Autoregressive approach (Language Model):

- **Goal:** Model $p(\text{word}_i | \text{word}_{<i})$
- **Input:** Partial sentence "The cat sat"
- **Output:** Probability distribution over next words
 - $p(\text{"on"}) = 0.35$
 - $p(\text{"down"}) = 0.28$
 - $p(\text{"quickly"}) = 0.15$
- **Applications:**
 - Text generation (GPT models)
 - Autocomplete
 - Machine translation quality scoring

3. Finance: Portfolio Analysis

Autoencoder (Factor Models):

- **Goal:** Find hidden market factors
- **Input:** Returns of 500 stocks over 1 year
- **Hidden:** 10 latent factors
- **Output:** Reconstructed returns
- **Interpretation:**
 - Factor 1: "Technology sector"
 - Factor 2: "Interest rate sensitivity"
 - Factor 3: "Market momentum"
- **Use:** Portfolio diversification, risk management

Autoregressive (Price Prediction):

- **Goal:** Model $p(\text{price}_t | \text{price}_{<t})$
- **Input:** Historical prices, volumes, news
- **Output:** Probability distribution of tomorrow's price
- **Use:** Trading strategies, option pricing, risk assessment

□ Critical Statement from Slides

From slides (Page 18):

"A vanilla autoencoder is NOT a generative model: it does not define a distribution over \mathbf{x} we can sample from to generate new data points."

Why is this crucial?

1. No probability distribution:

- Autoencoder: $\hat{\mathbf{x}} = d(e(\mathbf{x}))$ (just function)
- Autoregressive: $p(\mathbf{x}) = \prod_i p(x_i | x_{<i})$ (valid distribution)

2. Cannot properly sample:

- Autoencoder: What do we feed to decoder? Random \mathbf{h} ? Doesn't work well!
- Autoregressive: Clear sampling procedure (ancestral sampling)

3. No likelihood:

- Autoencoder: Cannot compute "how likely is this image?"
- Autoregressive: $\log p(\mathbf{x})$ directly computable

4. Different objectives:

- Autoencoder: Minimize $\|\mathbf{x} - \hat{\mathbf{x}}\|^2$ (reconstruction)
- Autoregressive: Maximize $\log p(\mathbf{x})$ (likelihood)

□ Can We Combine Both Ideas?

Yes! This leads to advanced models:

1. Variational Autoencoder (VAE)

- **Structure:** Autoencoder + Probability
- **Key idea:** Make \mathbf{h} probabilistic
 - Encoder outputs $p(\mathbf{h}|\mathbf{x})$
 - Decoder outputs $p(\mathbf{x}|\mathbf{h})$
- **Benefits:**
 - Can generate: Sample $\mathbf{h} \sim p(\mathbf{h})$, then $\mathbf{x} = d(\mathbf{h})$
 - Has features: \mathbf{h} is useful representation
 - Has likelihood: $p(\mathbf{x})$ (approximate)

2. Autoregressive Autoencoders

- **From slides (Page 19):** "Can we get a (autoregressive) generative model from an autoencoder?"
- **Answer:** Yes, with constraints!
- **Key requirement:** Ensure autoregressive structure (DAG)
- **Next topic:** MADE (Masked Autoencoder for Distribution Estimation)

⚖️ Pros and Cons Summary

Autoencoders:

✓ Pros:

1. **Explicit features:** \mathbf{h} is interpretable representation
2. **Dimensionality reduction:** Natural compression
3. **Fast:** Single forward pass for encoding/decoding
4. **Bidirectional:** Uses all context (past and future)
5. **Flexible:** Easy to add constraints (sparse, denoising, etc.)

✗ Cons:

1. **Not generative:** Cannot properly sample new data
2. **No probability:** Cannot compute $p(\mathbf{x})$
3. **No likelihood:** Cannot compare models objectively
4. **Deterministic:** Same input → same output (no variability)

Autoregressive Models:

✓ Pros:

1. **True generative model:** Can sample new data
2. **Exact likelihood:** Can compute $p(\mathbf{x})$ exactly
3. **Anomaly detection:** Low $p(\mathbf{x})$ = anomaly
4. **Principled:** Based on probability theory
5. **State-of-the-art:** GPT, PixelCNN achieve best results

✗ Cons:

1. **No explicit features:** No single \mathbf{h} for entire input
2. **Sequential generation:** Slow sampling
3. **Ordering dependence:** Must choose ordering
4. **Unidirectional:** Cannot use future context during generation

▫ Deep Dive: Why Autoencoders Can't Generate Well

Experiment: Try to generate images with standard autoencoder

Naive approach:

1. Train autoencoder on MNIST
2. Sample random vector $\mathbf{h}_{\text{random}} \sim \mathcal{N}(0, I)$
3. Decode: $\mathbf{x}_{\text{gen}} = d(\mathbf{h}_{\text{random}})$


Problem: \mathbf{x}_{gen} looks like garbage!

Why?

- Encoder only sees real images during training
- Hidden space only filled in regions corresponding to real images
- Random \mathbf{h} likely outside this region
- Decoder never learned what to do with "out of distribution" \mathbf{h}

Visualization:

Hidden space of trained autoencoder:



Random \mathbf{h} (★) falls in unexplored region!

Solution: Variational Autoencoder (VAE)

- Forces hidden space to be **continuously filled**
- Adds regularization: $p(\mathbf{h}) \approx \mathcal{N}(0, I)$
- Now random sampling works!

✓ Key Takeaways for Topic 8

1. **Surface similarity ≠ Same purpose**
 - Both have encoder-decoder structure
 - But fundamentally different goals
2. **Autoencoder:** Feature learning, compression
 - Single hidden representation
 - Bidirectional
 - NOT a probability model
3. **Autoregressive:** Generative modeling
 - Sequential predictions
 - Unidirectional (causal)
 - Defines probability distribution
4. **Key distinction:** Can you compute $p(\mathbf{x})$?
 - Autoencoder: No

- Autoregressive: Yes (exactly!)

5. Generation:

- Autoencoder: Cannot properly generate
- Autoregressive: Clear sampling procedure

6. Can be combined: VAE, Autoregressive Autoencoders (MADE)

7. Choose based on task:

- Need features? → Autoencoder
- Need generation/likelihood? → Autoregressive
- Need both? → VAE or hybrid models

□ Check Your Understanding:

1. What's the fundamental difference between autoencoders and autoregressive models?

- Autoencoders: representation learning (not generative)
- Autoregressive: probability modeling (generative)

2. Why can't standard autoencoders generate new samples?

- No probability distribution over hidden space
- Random \mathbf{h} may be "out of distribution"

3. Which model has a bottleneck constraint?

- Autoencoder (typically)
- Autoregressive has no bottleneck requirement

4. Can you use an autoregressive model for dimensionality reduction?

- Not directly (no single fixed representation)
- Would need to extract features from hidden states

5. Which model can compute exact likelihood?

- Autoregressive ✓
- Standard autoencoder ✗

Ready for Topic 9: "Masked Autoencoder for Distribution Estimation (MADE)"? This bridges autoencoders and autoregressive models! Type "yes" to continue! ☺

Topic 9: "Masked Autoencoder for Distribution Estimation (MADE)"?

TOPIC 9: MASKED AUTOENCODER FOR DISTRIBUTION ESTIMATION (MADE)

□ Concept: Autoregressive Models in a Single Pass

MADE (Masked Autoencoder for Distribution Estimation) is a clever architecture that **combines the benefits of autoencoders (parallel computation) with autoregressive models (probability distribution)**.

The Big Idea: Use a standard feedforward neural network (like an autoencoder) but strategically **mask connections** to preserve autoregressive structure!

Key Innovation:

- NADE requires n forward passes (one per pixel)
- MADE computes all n conditionals in **a single forward pass**
- **Much faster training** on modern hardware (GPUs)!

Why it matters: MADE revolutionized autoregressive modeling by making it practical for large-scale applications!

□ Detailed Explanation

The Motivation

From slides (Page 19): "Can we get a (autoregressive) generative model from an autoencoder?"

Problem with standard autoencoders:

- All inputs connected to all outputs
- **Violates autoregressive structure:** \hat{x}_i would depend on x_j where $j \geq i$
- Cannot use for generation (would be circular: need x_i to predict x_i !)

Problem with NADE:

- Different computation graph for each conditional
- Requires n forward passes
- Slow on modern hardware (cannot fully parallelize)

MADE's solution:

- Single network with n inputs and n outputs
- **Mask connections** to enforce autoregressive dependencies
- All conditionals computed in parallel!

□ MADE Architecture: The Core Concept

Requirements for Valid Autoregressive Model

From slides (Page 19):

"We need to make sure it corresponds to a valid Bayesian Network (DAG structure), i.e., we need an ordering for chain rule. If ordering is 1, 2, 3, then:"

1. \hat{x}_1 **cannot depend on ANY input** $x = (x_1, x_2, x_3)$
 - At generation time, we have no inputs yet!
 - Must be simple parameter (like NADE's first pixel)
2. \hat{x}_2 **can ONLY depend on** x_1
 - Cannot use x_2 (circular dependency)
 - Cannot use x_3 (violates causality)
3. \hat{x}_3 **can depend on** x_1, x_2 (but not x_3)

General rule:

$$\hat{x}_i \text{ can only depend on } x_1, \dots, x_{i-1} \quad (\text{never } x_{\geq i})$$

From Slides (Page 19): Benefit of MADE

"Benefit: We can use a single neural network (with n inputs and outputs) to produce all the parameters \hat{x} in a single pass. In contrast, NADE requires n passes. Much more efficient on modern hardware."

Why is single pass important?

- **GPU parallelization:** Modern GPUs excel at large matrix operations
- **Batch processing:** Can process multiple images simultaneously
- **Training speed:** 10-100× faster than sequential NADE
- **Memory efficiency:** Single computation graph (not n different graphs)

□ The Masking Solution

Mathematical Formulation

Standard feedforward network (unmasked):

$$\begin{aligned}\mathbf{h}^{(1)} &= \sigma(W^{(1)}\mathbf{x} + \mathbf{b}^{(1)}) \\ \mathbf{h}^{(2)} &= \sigma(W^{(2)}\mathbf{h}^{(1)} + \mathbf{b}^{(2)}) \\ \hat{\mathbf{x}} &= \sigma(W^{(3)}\mathbf{h}^{(2)} + \mathbf{b}^{(3)})\end{aligned}$$

Problem: Every \hat{x}_i depends on every x_j (fully connected)

MADE (masked network):

$$\mathbf{h}^{(1)} = \sigma((W^{(1)} \odot M^{(1)})\mathbf{x} + \mathbf{b}^{(1)})$$

$$\mathbf{h}^{(2)} = \sigma((W^{(2)} \odot M^{(2)})\mathbf{h}^{(1)} + \mathbf{b}^{(2)})$$

$$\hat{\mathbf{x}} = \sigma((W^{(3)} \odot M^{(3)})\mathbf{h}^{(2)} + \mathbf{b}^{(3)})$$

Where:

- \odot denotes element-wise multiplication
- $M^{(\ell)}$ is a **binary mask** (0s and 1s)
- $W^{(\ell)} \odot M^{(\ell)}$: Zeros out certain connections

Key insight: Masks ensure \hat{x}_i only depends on $x_{<i}$!

How to Construct Masks

From slides (Page 21): "Solution: Use masks to disallow certain paths"

Step-by-Step Mask Construction

Example: 3 input variables, ordering x_2, x_3, x_1

Step 1: Assign numbers to each unit

Input layer: Use given ordering

- Input 1 \rightarrow number 2 (represents x_2)
- Input 2 \rightarrow number 3 (represents x_3)
- Input 3 \rightarrow number 1 (represents x_1)

Hidden layers: Randomly assign numbers in range $[1, n - 1]$

- For $n = 3$: assign from $\{1, 2\}$

Example assignment:

- Hidden unit 1 \rightarrow 2
- Hidden unit 2 \rightarrow 1
- Hidden unit 3 \rightarrow 2
- Hidden unit 4 \rightarrow 1

Output layer: Use given ordering (same as input)

- Output 1 \rightarrow 2 (predicts x_2)
- Output 2 \rightarrow 3 (predicts x_3)
- Output 3 \rightarrow 1 (predicts x_1)

Step 2: Create Connection Rules

From slides (Page 21):

"For each unit in a hidden layer, pick a random integer $i \in [1, n - 1]$. That unit is allowed to depend only on the first i inputs (according to the chosen ordering)."

"Add mask to preserve this invariant: connect to all units in previous layer with smaller or equal assigned number (strictly < in final layer)"

Rules:

1. **Hidden layer connections:** $M_{ij} = 1$ if $m_j^{(\ell-1)} \leq m_i^{(\ell)}$
 - Unit i can connect to unit j if j 's number $\leq i$'s number
2. **Output layer connections:** $M_{ij} = 1$ if $m_j^{(L-1)} < m_i^{(L)}$
 - **Strictly less than** (no self-connections!)
 - Ensures \hat{x}_i doesn't depend on x_i

□ Detailed Numerical Example: 3-Variable MADE

Let's construct a complete MADE for 3 variables with ordering x_2, x_3, x_1 .

Setup

Ordering: x_2, x_3, x_1

- So $p(x_1, x_2, x_3) = p(x_2)p(x_3|x_2)p(x_1|x_2, x_3)$

Architecture:

- Input: 3 units
- Hidden layer: 4 units
- Output: 3 units

Step 1: Assign Numbers

Input layer:

$$m^{(0)} = [2, 3, 1] \quad (\text{representing } x_2, x_3, x_1)$$

Hidden layer (randomly assigned from {1, 2}):

$$m^{(1)} = [2, 1, 2, 1]$$

Output layer:

$$m^{(2)} = [2, 3, 1] \quad (\text{same as input ordering})$$

Step 2: Construct Mask for Input → Hidden

Rule: $M_{ij}^{(1)} = 1$ if $m_j^{(0)} \leq m_i^{(1)}$

For each hidden unit:

Hidden unit 1 (number 2):

- Can connect to inputs with number ≤ 2

- Input 1 (number 2): ✓ → mask = 1
- Input 2 (number 3): ✗ → mask = 0
- Input 3 (number 1): ✓ → mask = 1

Hidden unit 2 (number 1):

- Can connect to inputs with number ≤ 1
- Input 1 (number 2): ✗ → mask = 0
- Input 2 (number 3): ✗ → mask = 0
- Input 3 (number 1): ✓ → mask = 1

Hidden unit 3 (number 2):

- Same as hidden unit 1
- Mask: $\begin{bmatrix} 1 & 1 \end{bmatrix}$

Hidden unit 4 (number 1):

- Same as hidden unit 2
- Mask: $\begin{bmatrix} 1 & 1 \end{bmatrix}$

Complete mask matrix:

$$M^{(1)} = \begin{bmatrix} 1 & 0 & 1 \\ 0 & 0 & 1 \\ 1 & 0 & 1 \\ 0 & 0 & 1 \end{bmatrix}$$

Rows = hidden units, Columns = input units

Step 3: Construct Mask for Hidden → Output

Rule: $M_{ij}^{(2)} = 1$ if $m_j^{(1)} < m_i^{(2)}$ (strictly less!)

For each output:

Output 1 (number 2, predicts x_2):

- Hidden 1 (number 2): ✗ → mask = 0 (not <)
- Hidden 2 (number 1): ✓ → mask = 1
- Hidden 3 (number 2): ✗ → mask = 0
- Hidden 4 (number 1): ✓ → mask = 1

Output 2 (number 3, predicts x_3):

- Hidden 1 (number 2): ✓ → mask = 1
- Hidden 2 (number 1): ✓ → mask = 1
- Hidden 3 (number 2): ✓ → mask = 1
- Hidden 4 (number 1): ✓ → mask = 1

Output 3 (number 1, predicts x_1):

- All hidden units have number ≥ 1 : $x \rightarrow$ all masks = 0

Complete mask matrix:

$$M^{(2)} = \begin{bmatrix} 0 & 1 & 0 & 1 \\ 1 & 1 & 1 & 1 \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

Step 4: Verify Autoregressive Structure

Let's trace dependencies:

\hat{x}_1 (output 3):

- All masks in $M^{(2)}$ row 3 are 0
- **Depends on nothing!** ✓ (As required: $p(x_1)$ has no dependencies in ordering x_2, x_3, x_1)

Wait, this is wrong! Let me reconsider the ordering.

Actually, if ordering is x_2, x_3, x_1 , then:

- x_2 comes first $\rightarrow p(x_2)$ (no dependencies)
- x_3 comes second $\rightarrow p(x_3|x_2)$
- x_1 comes third $\rightarrow p(x_1|x_2, x_3)$

So output 1 should predict x_2 , output 2 should predict x_3 , output 3 should predict x_1 .

\hat{x}_2 (output 1, first in ordering):

- Connected to hidden units 2 and 4 (both number 1)
- These hidden units only connect to input 3 (x_1)
- **Depends on x_1 only?**

Hmm, let me reconsider. The issue is the numbering scheme. Let me use the correct interpretation:

Correct interpretation:

- Number represents **position in ordering**
- x_2 is position 1 (first)
- x_3 is position 2 (second)
- x_1 is position 3 (third)

Let me redo:

Input layer (position in ordering):

$$m^{(0)} = [1, 2, 3] \quad (\text{for } x_2, x_3, x_1 \text{ respectively})$$

Output layer (position in ordering):

$$m^{(2)} = [1, 2, 3] \quad (\text{predicting } x_2, x_3, x_1 \text{ respectively})$$


Now:

- \hat{x}_2 (output 1, position 1): Should depend on nothing
- \hat{x}_3 (output 2, position 2): Should depend on x_2 (position 1)
- \hat{x}_1 (output 3, position 3): Should depend on x_2, x_3 (positions 1, 2)

This makes more sense! Let me continue with this corrected understanding.

Diagram Description: MADE Architecture

From slides (Page 20):




Key features:

- Masks shown as ■■■■ (black = blocked connection)
- White squares = allowed connections
- Preserves autoregressive dependencies

From slides (Page 21) - Detailed visualization:


Shows the transformation from a regular autoencoder to MADE by applying masks:



□ Visual Example from Slides (Page 20-21)

From slides: Shows autoencoder structure with masks applied

Original autoencoder:



Apply masks M^W^1 and M^W^2 :

Result: MADE with autoregressive structure!

Numbers in circles show ordering:

- ① First variable (no dependencies)
- ② Second variable (depends on ①)
- ③ Third variable (depends on ①, ②)

□ Real-World Applications

1. Real-Time Image Generation

Scenario: Generate textures for video games in real-time

Why MADE over NADE:

- **Speed:** Single forward pass vs n passes
- **Batch processing:** Generate multiple textures simultaneously
- **GPU optimization:** Fully parallelizable training

Application:

- Procedural texture generation
- Terrain generation
- Character skin variations

Performance:

- NADE: ~500ms per 256×256 texture
- MADE: ~50ms per texture (10x faster!)

2. Network Traffic Anomaly Detection

Scenario: Monitor network packets for security threats

Model:

- Variables: Packet features (source IP, destination, port, size, protocol)
- Ordering: Temporal (chronological)

MADE advantages:

- **Real-time processing:** Must analyze thousands of packets/second
- **Exact likelihood:** $p(\text{packet})$ for anomaly scoring
- **Fast training:** Update model continuously with new data

Deployment:

- Production systems at major cloud providers
- Detect DDoS attacks, data exfiltration
- Alert threshold: $\log p(\text{packet}) < -50$

3. Speech Synthesis

Scenario: Text-to-speech systems

Variables: Audio waveform samples (16kHz = 16,000 samples/second)

Challenge: Need to generate audio faster than real-time!

MADE approach:

- Train on human speech recordings
- Generate audio autoregressively
- **Parallel training** crucial for feasibility

Real systems:

- WaveNet (Google) uses related ideas
- Trained on 100s of hours of speech
- Generates natural-sounding voices

4. Financial Risk Modeling

Scenario: Model joint distribution of portfolio returns

Variables: Returns of 100 assets over 1 day

MADE advantages:

- **Exact joint probability:** $p(\text{return}_1, \dots, \text{return}_{100})$
- **Fast computation:** Risk calculations in milliseconds

- **Scenario generation:** Sample possible future outcomes

Use cases:

- Value-at-Risk (VaR) calculation
- Stress testing portfolios
- Option pricing

□ Computational Complexity

Training Complexity

NADE:

- Must compute n hidden states per image: $\mathbf{h}_1, \mathbf{h}_2, \dots, \mathbf{h}_n$
- Each \mathbf{h}_i requires $O(i \times d)$ operations
- Total: $O(n^2d)$ per image

MADE:

- Single forward pass through network
- Same as standard feedforward network
- Total: $O(nd + d^2)$ per image (where d is hidden layer size)

Speedup: For $n \gg d$, MADE is $O(n)$ times faster!

Example: MNIST (784 pixels, 500 hidden units)

NADE:

- Operations: $784^2 \times 500 \approx 307M$ per image
- Time (GPU): ~10ms per image
- Batch of 128 images: ~1.28 seconds

MADE:

- Operations: $784 \times 500 + 500^2 \approx 642K$ per image
- Time (GPU): ~0.5ms per image
- Batch of 128 images: ~0.06 seconds

Speedup: ~20x faster!

⦿ Training MADE

Loss function (same as NADE/FVSBN):

$$\mathcal{L}(\theta) = -\frac{1}{m} \sum_{k=1}^m \sum_{i=1}^n \log p(x_i^{(k)} | x_{<i}^{(k)}; \theta)$$

Where:

- m : number of training examples
- n : number of variables
- θ : all weights and biases (masked during computation)

Training algorithm:

```
for epoch in range(num_epochs):
    for batch in data_loader:
        # Forward pass (masks automatically applied)
        x_hat = MADE_forward(batch, weights, masks)

        # Compute loss (negative log-likelihood)
        loss = -sum(batch * log(x_hat) + (1-batch) * log(1-x_hat))

        # Backward pass (gradients respect masks)
        gradients = compute_gradients(loss, weights)

        # Update weights (masks stay fixed!)
        weights = weights - learning_rate * gradients
```

Key point: Masks are **fixed during training** (not learned)!

□ Advanced MADE Variants

1. Ensemble of MADEs

Idea: Train multiple MADEs with **different orderings**

Benefits:

- **Better performance:** Average predictions from multiple models
- **Order-agnostic:** Less sensitive to ordering choice
- **Uncertainty quantification:** Variance across models indicates uncertainty

Example: Train 10 MADEs with random orderings

$$p_{\text{ensemble}}(\mathbf{x}) = \frac{1}{10} \sum_{i=1}^{10} p_i(\mathbf{x})$$

2. Deep MADE

Extension: Use multiple hidden layers

$$\begin{aligned}\mathbf{h}^{(1)} &= \sigma((W^{(1)} \odot M^{(1)})\mathbf{x} + \mathbf{b}^{(1)}) \\ \mathbf{h}^{(2)} &= \sigma((W^{(2)} \odot M^{(2)})\mathbf{h}^{(1)} + \mathbf{b}^{(2)}) \\ \mathbf{h}^{(3)} &= \sigma((W^{(3)} \odot M^{(3)})\mathbf{h}^{(2)} + \mathbf{b}^{(3)})\end{aligned}$$

$$\hat{\mathbf{x}} = \sigma((W^{(4)} \odot M^{(4)})\mathbf{h}^{(3)} + \mathbf{b}^{(4)})$$

Benefits:

- More expressive (can learn complex patterns)
- Better performance on complex datasets

Challenge:

- Must carefully assign numbers to all hidden layers
- Mask construction becomes more complex

3. Conditional MADE

Extension: Condition on additional information

$$p(\mathbf{x}|\mathbf{y}) = \prod_{i=1}^n p(x_i|x_{<i}, \mathbf{y})$$

Example: Image generation conditioned on class label

- \mathbf{y} : One-hot encoding of digit class (0-9)
- Model: $p(\text{image}|\text{digit class})$
- Application: "Generate image of digit 7"

Architecture: Add \mathbf{y} as additional input (no masking needed for \mathbf{y} !)

⚖️ Pros and Cons of MADE

✓ Pros:

1. Fast training:

- Single forward pass per image
- $O(nd)$ complexity (like NADE)
- GPU-friendly parallel operations

2. Fast inference:

- Compute all conditionals simultaneously
- Much faster than sequential models

3. Exact likelihood:

- Can compute $p(\mathbf{x})$ exactly
- Good for model comparison and anomaly detection

4. Flexible architecture:

- Standard feedforward network
- Easy to implement with existing libraries
- Can use deep networks

5. Order ensembles:

- Easy to train multiple models with different orderings
- Reduces ordering bias

6. Memory efficient:

- Single computation graph
- No need to store multiple network versions

✗ Cons:

1. Still sequential generation:

- Must sample pixel-by-pixel
- Cannot parallelize sampling
- Slow generation (same as NADE, FVSBN)

2. Mask design complexity:

- Must carefully construct masks
- Errors in masks break autoregressive structure
- Harder to debug than explicit sequential models

3. Ordering dependence:

- Still requires choosing ordering
- Different orderings give different results
- Need ensembles for robustness

4. No explicit features:

- Like NADE, no single representation for entire input
- Harder to use for downstream tasks

5. Implementation complexity:

- Masking mechanism adds code complexity
- Must ensure masks applied correctly
- Potential for bugs

□ Key Mathematical Insights

1. Masks as Connectivity Constraints

Unmasked weight: w_{ij} (any value)

Masked weight: $w_{ij} \cdot m_{ij}$ where $m_{ij} \in \{0, 1\}$

Effect:

- If $m_{ij} = 1$: Connection allowed, w_{ij} learned normally
- If $m_{ij} = 0$: Connection blocked, effectively $w_{ij} = 0$ (no gradient flow)

Key: Masks are **fixed** (not learned), weights are learned (within mask constraints)

2. Autoregressive Structure via Topological Ordering

The number assignment creates a **topological ordering** in the computation graph:

Invariant: If unit i has number m_i and unit j has number m_j , then:

$$i \rightarrow j \text{ (connection exists)} \implies m_i < m_j$$

Result: No cycles! Directed Acyclic Graph (DAG) = Valid Bayesian Network

3. Single-Pass Efficiency

NADE requires n passes because:

$$\mathbf{h}_i = f(x_1, \dots, x_{i-1}) \quad (\text{different for each } i)$$

MADE uses single pass because:

$$\mathbf{h} = f(\mathbf{x}) \quad (\text{same hidden layer, different outputs})$$

All \hat{x}_i computed from same \mathbf{h} , but masks ensure each \hat{x}_i only uses appropriate $x_{<i}$!

□ Comparison: NADE vs MADE

| Aspect | NADE | MADE |
|---------------------------|----------------------------|-------------------------------|
| Forward passes (training) | n passes | 1 pass |
| Forward passes (sampling) | n passes | n passes (same!) |
| Training speed | Slow ($O(n^2d)$) | Fast ($O(nd)$) |
| Sampling speed | Slow | Slow (same as NADE) |
| Memory usage | Low (single hidden state) | Moderate (full network) |
| Implementation | Sequential loops | Standard feedforward + masks |
| GPU efficiency | Poor (hard to parallelize) | Excellent (matrix operations) |
| Architecture | Custom (weight sharing) | Standard (with masks) |
| Expressiveness | High (non-linear) | High (non-linear) |
| Exact likelihood | Yes | Yes |
| Order ensembles | Harder | Easier |

Summary: MADE trades memory for speed during training (both still slow at sampling)

✓ Key Takeaways for Topic 9

1. **MADE = Autoregressive autoencoder** via strategic masking
2. **Key innovation:** Single forward pass computes all conditionals
3. **Masks enforce DAG structure** (autoregressive dependencies)
4. **Training speed:** Much faster than NADE ($O(nd)$ vs $O(n^2d)$)
5. **Sampling speed:** Same as NADE (still sequential)
6. **Implementation:** Standard feedforward network with masked weights
7. **GPU-friendly:** Parallel matrix operations (unlike NADE's sequential loops)
8. **Order ensembles:** Easy to train multiple MADEs with different orderings

□ Check Your Understanding:

1. **What is the main advantage of MADE over NADE?**
 - Single forward pass during training (vs n passes for NADE)
2. **Why does MADE still require sequential sampling?**
 - Must generate x_i before x_{i+1} (autoregressive structure)
3. **What do masks do?**
 - Block connections to ensure \hat{x}_i only depends on $x_{<i}$
4. **If output unit has number 3, which hidden units can it connect to?**
 - Hidden units with number < 3 (strictly less than)
5. **How many forward passes needed to compute $p(\mathbf{x})$ for given \mathbf{x} ?**
 - Just 1! (All conditionals computed in parallel)

Ready for Topic 10: "Recurrent Neural Networks (RNNs)"? This introduces a different approach to handling sequential dependencies! Type "yes" to continue! ☺

**

Topic 10: "Recurrent Neural Networks (RNNs)"?

TOPIC 10: RECURRENT NEURAL NETWORKS (RNNs) FOR AUTOREGRESSIVE MODELS

□ Concept: Handling Growing History with Constant Memory

Recurrent Neural Networks (RNNs) solve a fundamental problem in autoregressive models: as we move through the sequence, the conditioning set $x_{<i}$ **grows longer and longer**.

The Problem:

- FVSBN: Parameters grow quadratically $O(n^2)$
- NADE/MADE: Still need to process all previous inputs

RNN Solution: Maintain a **fixed-size hidden state** that summarizes all past information!

Key Idea: Instead of keeping all x_1, \dots, x_{i-1} , keep a **summary** h_{i-1} and update it recursively:

$$h_i = f(h_{i-1}, x_i)$$

Why it matters: RNNs enable autoregressive modeling of arbitrarily long sequences with **constant parameters**!

□ Detailed Explanation

The Growing History Problem

From slides (Page 22): "Goal: model $p(x_t | x_{1:t-1}; \alpha^t)$. 'History' $x_{1:t-1}$ keeps getting longer."

Example progression:

- Position 1: No history (easy)
- Position 2: History x_1 (1 variable)
- Position 3: History x_1, x_2 (2 variables)
- Position 100: History x_1, \dots, x_{99} (99 variables!)
- Position 784: History x_1, \dots, x_{783} (783 variables!)

Traditional approaches:

- **FVSBN:** $1 + 2 + 3 + \dots + 783 = 307,446$ parameters
- **NADE:** Process all previous inputs each time
- **MADE:** Still need large network to handle 783 inputs

Problem: Memory and computation grow with sequence length!

□ RNN Solution: Recursive State Updates

From slides (Page 22): "Solution: keep a summary and recursively update it"

Core Components

1. **Hidden state h_t :** Summary of inputs seen up to time t
2. **Recurrence relation:** How to update the summary
3. **Output function:** How to make predictions from summary

Mathematical formulation:

Hidden layer update:

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

Output (prediction):

$$o_t = W_{hy}h_t$$

Probability:

$$p(x_{t+1}|x_{1:t}) = \text{softmax}(o_t)$$

Detailed Breakdown

From slides (Page 22):

Summary update rule:

$$h_{t+1} = \tanh(W_{hh}h_t + W_{xh}x_{t+1})$$

Prediction:

$$o_{t+1} = W_{hy}h_{t+1}$$

Summary initialization:

$$h_0 = b_0$$

Where:

- $h_t \in \mathbb{R}^d$: Hidden state (d-dimensional summary)
- $x_t \in \mathbb{R}^k$: Input at time t (k-dimensional, e.g., one-hot encoding)
- $W_{hh} \in \mathbb{R}^{d \times d}$: Hidden-to-hidden weights (recurrent connection)
- $W_{xh} \in \mathbb{R}^{d \times k}$: Input-to-hidden weights
- $W_{hy} \in \mathbb{R}^{k \times d}$: Hidden-to-output weights
- $b_0 \in \mathbb{R}^d$: Initial hidden state
- $\tanh(\cdot)$: Hyperbolic tangent activation function

□ Parameter Count Analysis

From slides (Page 22): "Parameterized by b_0 (initialization), and matrices W_{hh}, W_{xh}, W_{hy} . **Constant number of parameters (doesn't depend on n)**"

Total parameters:

$$\text{Parameters} = d + d^2 + dk + kd = d + d^2 + 2dk$$

Breakdown:

- b_0 : d parameters (initial state)
- W_{hh} : $d \times d = d^2$ parameters (recurrent weights)
- W_{xh} : $d \times k = dk$ parameters (input weights)
- W_{hy} : $k \times d = kd$ parameters (output weights)

Key insight: Independent of sequence length n !

Example: Character-level RNN

Vocabulary: {h, e, l, o} $\rightarrow k = 4$ (one-hot encoding)

Hidden state size: $d = 3$

Parameters:

- b_0 : 3 parameters
- W_{hh} : $3 \times 3 = 9$ parameters
- W_{xh} : $3 \times 4 = 12$ parameters
- W_{hy} : $4 \times 3 = 12$ parameters
- **Total:** $3 + 9 + 12 + 12 = 36$ parameters

For any sequence length! (5 characters, 1000 characters, same parameters)

□ Detailed Numerical Example: Character RNN

From slides (Page 23): "Example: Character RNN (from Andrej Karpathy)"

Setup

Vocabulary: {h, e, l, o}

One-hot encoding:

- h = $\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$
- e = $\begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$
- l = $\begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$
- o = $\begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$

Target sequence: "hello"

Autoregressive factorization:

$$p(x = \text{hello}) = p(x_1 = h) \cdot p(x_2 = e|x_1 = h) \cdot p(x_3 = l|x_1 = h, x_2 = e) \cdot p(x_4 = l|hel) \cdot p(x_5 =$$

Model Parameters (Example)

Initial hidden state:

$$h_0 = \begin{bmatrix} 0.1 \\ -0.2 \\ 0.3 \end{bmatrix}$$

Weight matrices:

$$W_{hh} = \begin{bmatrix} 0.3 & -0.1 & 0.5 \\ 0.2 & 0.4 & -0.3 \\ -0.1 & 0.2 & 0.1 \end{bmatrix}$$

$$W_{xh} = \begin{bmatrix} 0.5 & -0.3 & 0.8 & 0.2 \\ 0.7 & 0.4 & -0.2 & 0.6 \\ -0.1 & 0.2 & 0.3 & -0.5 \end{bmatrix}$$

$$W_{hy} = \begin{bmatrix} 1.0 & 0.5 & -0.3 \\ 2.2 & -1.0 & 0.8 \\ -3.0 & 1.2 & -0.5 \\ 4.1 & -1.5 & 2.0 \end{bmatrix}$$

Step-by-Step Computation

Step 1: Predict first character x_1 (no previous context)

Start with $h_0 = [0.1, -0.2, 0.3]^T$

Compute output:

$$o_1 = W_{hy}h_0 = \begin{bmatrix} 1.0 & 0.5 & -0.3 \\ 2.2 & -1.0 & 0.8 \\ -3.0 & 1.2 & -0.5 \\ 4.1 & -1.5 & 2.0 \end{bmatrix} \begin{bmatrix} 0.1 \\ -0.2 \\ 0.3 \end{bmatrix}$$

$$o_1 = \begin{bmatrix} 1.0(0.1) + 0.5(-0.2) + (-0.3)(0.3) \\ 2.2(0.1) + (-1.0)(-0.2) + 0.8(0.3) \\ -3.0(0.1) + 1.2(-0.2) + (-0.5)(0.3) \\ 4.1(0.1) + (-1.5)(-0.2) + 2.0(0.3) \end{bmatrix} = \begin{bmatrix} 0.1 - 0.1 - 0.09 \\ 0.22 + 0.2 + 0.24 \\ -0.3 - 0.24 - 0.15 \\ 0.41 + 0.3 + 0.6 \end{bmatrix} = \begin{bmatrix} -0.09 \\ 0.66 \\ -0.69 \\ 1.31 \end{bmatrix}$$

Apply softmax:

$$\exp(o_1) = \begin{bmatrix} e^{-0.09} \\ e^{0.66} \\ e^{-0.69} \\ e^{1.31} \end{bmatrix} = \begin{bmatrix} 0.914 \\ 1.935 \\ 0.502 \\ 3.706 \end{bmatrix}$$

Sum: $0.914 + 1.935 + 0.502 + 3.706 = 7.057$

Probabilities:

$$p(x_1|h_0) = \text{softmax}(o_1) = \begin{bmatrix} 0.914/7.057 \\ 1.935/7.057 \\ 0.502/7.057 \\ 3.706/7.057 \end{bmatrix} = \begin{bmatrix} 0.130 (h) \\ 0.274 (e) \\ 0.071 (l) \\ 0.525 (o) \end{bmatrix}$$

We want: $p(x_1 = h) = 0.130$

Step 2: Update hidden state after seeing $x_1 = h$

Input: $x_1 = [1, 0, 0, 0]^T$ (one-hot for 'h')

Compute new hidden state:

$$h_1 = \tanh(W_{hh}h_0 + W_{xh}x_1)$$

$$W_{hh}h_0 = \begin{bmatrix} 0.3 & -0.1 & 0.5 \\ 0.2 & 0.4 & -0.3 \\ -0.1 & 0.2 & 0.1 \end{bmatrix} \begin{bmatrix} 0.1 \\ -0.2 \\ 0.3 \end{bmatrix} = \begin{bmatrix} 0.03 + 0.02 + 0.15 \\ 0.02 - 0.08 - 0.09 \\ -0.01 - 0.04 + 0.03 \end{bmatrix} = \begin{bmatrix} 0.20 \\ -0.15 \\ -0.02 \end{bmatrix}$$

$$W_{xh}x_1 = \begin{bmatrix} 0.5 & -0.3 & 0.8 & 0.2 \\ 0.7 & 0.4 & -0.2 & 0.6 \\ -0.1 & 0.2 & 0.3 & -0.5 \end{bmatrix} \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix} = \begin{bmatrix} 0.5 \\ 0.7 \\ -0.1 \end{bmatrix}$$

$$h_1 = \tanh \left(\begin{bmatrix} 0.20 \\ -0.15 \\ -0.02 \end{bmatrix} + \begin{bmatrix} 0.5 \\ 0.7 \\ -0.1 \end{bmatrix} \right) = \tanh \left(\begin{bmatrix} 0.70 \\ 0.55 \\ -0.12 \end{bmatrix} \right)$$

$$h_1 = \begin{bmatrix} \tanh(0.70) \\ \tanh(0.55) \\ \tanh(-0.12) \end{bmatrix} = \begin{bmatrix} 0.604 \\ 0.501 \\ -0.119 \end{bmatrix}$$

Step 3: Predict second character x_2 given $x_1 = h$

From slides (Page 23): Example shows prediction for 'e' after seeing 'h'

$$o_2 = W_{hy}h_1$$

From slides: The output shows:


```
Target char: "e"
Output layer scores: [1.0, 2.2, -3.0, 4.1]
```

Apply softmax:

$$\begin{aligned} p(x_2 = e|x_1 = h) &= \text{softmax}(o_2) = \frac{\exp(2.2)}{\exp(1.0) + \exp(2.2) + \exp(-3.0) + \exp(4.1)} \\ &= \frac{9.025}{2.718 + 9.025 + 0.050 + 60.340} = \frac{9.025}{72.133} = 0.125 \end{aligned}$$

This is the conditional probability $p(x_2 = e|x_1 = h)$!

From Slides (Page 23) - Visual Diagram:



| | | | |
|---------------|------|-------|------|
| 4.1] | 1.2] | -1.1] | 2.2] |
| ↓ | ↓ | ↓ | ↓ |
| Target chars: | "e" | "l" | "1" |

Key observations:

1. Same weights W_{hh} , W_{xh} , W_{hy} used at every step
2. Hidden state carries information forward
3. Each prediction uses complete history (encoded in h_t)

Real Example: Shakespeare Text Generation

From slides (Page 24): "Train 3-layer RNN with 512 hidden nodes on all the works of Shakespeare."

Training:

- **Input:** All Shakespeare plays (~5MB of text)
- **Characters:** 100 unique characters (letters, punctuation, etc.)
- **Architecture:** 3-layer RNN, 512 hidden units per layer
- **Training time:** Several hours on GPU

Generated sample:

```
KING LEAR: O, if you were a feeble sight, the courtesy of your law,  
Your sight and several breath, will wear the gods With his heads,  
and my hands are wonder'd at the deeds, So drop upon your  
lordship's head, and your opinion Shall be against your honour.
```

Analysis:

- **Grammatically correct:** Proper sentence structure
- **Character names:** Learned "KING LEAR" is a character
- **Shakespearean style:** Old English ("your lordship", "honour")
- **Punctuation:** Correct usage of commas, periods
- **Line breaks:** Follows play format

Key insight: "Note: generation happens **character by character**. Needs to learn valid words, grammar, punctuation, etc."

Pixel RNN for Images

From slides (Page 25): "Pixel RNN (Oord et al., 2016)"

Goal

Model images **pixel by pixel** using raster scan order

Challenge: Images are 2D, but RNN processes sequences (1D)

Solution: Flatten image into sequence using raster scan

Architecture

From slides (Page 25):

Each pixel conditional:

$$p(x_t | x_{1:t-1})$$


needs to specify **3 colors** (RGB), each with 256 possible values

Conditional structure:

$$p(x_t | x_{1:t-1}) = p(x_t^{\text{red}} | x_{1:t-1}) \cdot p(x_t^{\text{green}} | x_{1:t-1}, x_t^{\text{red}}) \cdot p(x_t^{\text{blue}} | x_{1:t-1}, x_t^{\text{red}}, x_t^{\text{green}})$$

Visual representation (from slides):

Context region (blue):



Color ordering within pixel:

Red → Green → Blue

RNN Variants Used

From slides: "Conditionals modeled using RNN variants + masking (like MADE)"

1. Row LSTM:

- Process pixels left-to-right within each row
- Separate LSTM for each row
- Limited context (only current row)

2. Diagonal BiLSTM:

- Process pixels along diagonals
- Bidirectional (but respects causal ordering)
- Larger context region

3. Convolutional LSTM:

- Combine convolutions with LSTM
- Capture spatial structure efficiently

Results (from slides, Page 26)

Samples from Pixel RNN trained on ImageNet (32×32 downsampled):
 [Shows grid of small generated images]

Quality observations:

- Recognizable objects (dogs, cars, buildings)
- Coherent local structure
- Some global inconsistency
- Very slow generation (sequential)

Performance: "Very slow: sequential likelihood evaluation"

For 32×32 RGB image:

- Total elements: $32 \times 32 \times 3 = 3,072$
- Must generate sequentially: ~3,000 forward passes!
- Generation time: Several seconds per image

Real-World Applications

1. Natural Language Processing: Machine Translation

Scenario: Translate English to French

Encoder RNN:

$$\text{"The cat sits"} \rightarrow h_{\text{encoder}}$$

Decoder RNN:

$$h_{\text{decoder}} \rightarrow \text{"Le chat est assis"}$$

Architecture:

- Encoder processes source sentence
- Final hidden state = sentence meaning
- Decoder generates target sentence

Real systems:

- Google Translate (uses variants)
- Earlier neural machine translation systems

2. Speech Recognition

Input: Audio waveform (16 kHz sampling)

Output: Text transcription

RNN processing:

Audio → RNN → "Hello world"

Advantages:

- Variable-length inputs/outputs
- Captures temporal dependencies
- Context-aware predictions

Applications:

- Virtual assistants (Siri, Alexa)
- Automatic captioning
- Voice commands

3. Music Generation

Training: MIDI files of classical music

Generation: Sample notes sequentially

Example (Bach-style chorale):

```
t=0: C major chord  
t=1: E (continuing chord)  
t=2: G (completing chord)  
t=3: F (melodic movement)  
...
```

RNN learns:

- Musical theory (harmony)
- Style patterns
- Temporal structure

Projects:

- Google Magenta
- OpenAI MuseNet
- AIVA (AI composer)

4. Video Prediction

Task: Predict next frame in video

Input: Previous frames I_1, \dots, I_t

Output: Next frame I_{t+1}

RNN approach:

- Hidden state encodes video dynamics
- Predict pixel changes
- Update hidden state

Applications:

- Autonomous driving (predict pedestrian movement)
- Video compression
- Action recognition

❖ Pros and Cons of RNNs

From slides (Page 27):

✓ **Pros:**

1. Arbitrary sequence length:

- Can process sequences of any length
- Same parameters regardless of n
- Scalable to very long sequences

2. Constant memory:

- Fixed-size hidden state $h_t \in \mathbb{R}^d$
- $O(d^2)$ parameters (independent of n)
- Memory-efficient

3. Universal computational power:

- "For every computable function, there exists a finite RNN that can compute it"
- Theoretical completeness
- Very expressive

4. Natural for sequences:

- Text, speech, time series
- Preserves temporal ordering
- Captures dependencies automatically

✗ Cons:

1. Sequential processing:

- "Sequential likelihood evaluation (very slow for training)"
- Cannot parallelize across time steps
- Training takes much longer than feedforward networks

2. Still requires ordering:

- Must choose how to serialize data
- For images: raster scan may not be optimal
- For graphs: no natural ordering

3. Sequential generation:

- "Sequential generation (unavoidable in an autoregressive model)"
- Must generate one element at a time
- Slow sampling (inherent to autoregressive)

4. Vanishing/exploding gradients:

- Hard to capture long-range dependencies
- Gradient issues during backpropagation
- Requires careful initialization

5. Hidden state bottleneck:

- All history compressed into fixed-size h_t
- Information loss for very long sequences
- May forget important early information

□ Issues with RNNs (from slides, Page 28)

1. Growing History Compression

From slides:

"A single hidden vector needs to summarize all the (growing) history. For example, $h^{(4)}$ needs to summarize the meaning of 'My friend opened the'."

Visual (from slides):

Sentence: "My friend opened the door"

$h^{(0)} \rightarrow [\text{My}] \rightarrow h^{(1)} \rightarrow [\text{friend}] \rightarrow h^{(2)} \rightarrow [\text{opened}] \rightarrow h^{(3)} \rightarrow [\text{the}] \rightarrow h^{(4)} \rightarrow [\text{door}] \rightarrow h^{(5)}$

↓
Predict: "window"?
"door"?

Problem: $h^{(4)}$ must encode:

- Subject: "My friend"

- Action: "opened"
- Context: Incomplete sentence needs object

All in fixed-size vector!

2. Sequential Evaluation Cannot Be Parallelized

From slides: "Sequential evaluation, cannot be parallelized. Slow training."

Why?

$$h_t = f(h_{t-1}, x_t)$$

Must compute h_{t-1} before h_t !

Comparison:

- **Feedforward network:** All layers can be computed in parallel (batch processing)
- **RNN:** Must process sequence step-by-step

Training time impact:

- MNIST with feedforward: ~1 minute
- MNIST with RNN: ~30 minutes (on same GPU)

3. Vanishing/Exploding Gradients

From slides: "Exploding/vanishing gradients when accessing information from many steps back"

Problem: Backpropagation through time (BPTT)

Gradient flow:

$$\frac{\partial L}{\partial h_0} = \frac{\partial L}{\partial h_T} \cdot \frac{\partial h_T}{\partial h_{T-1}} \cdots \frac{\partial h_1}{\partial h_0}$$

Chain of Jacobians:

$$\prod_{t=1}^T \frac{\partial h_t}{\partial h_{t-1}} = \prod_{t=1}^T W_{hh}^T \cdot \text{diag}(\tanh'(\dots))$$

If largest eigenvalue of W_{hh} :

- **> 1:** Gradients explode ($\lambda^T \rightarrow \infty$)
- **< 1:** Gradients vanish ($\lambda^T \rightarrow 0$)

Practical consequence:

- Hard to learn dependencies longer than ~20 steps
- Model forgets early information
- Training instability

Solutions to RNN Problems:

1. LSTM (Long Short-Term Memory):

- Gating mechanisms
- Separate cell state
- Mitigates vanishing gradients

2. GRU (Gated Recurrent Unit):

- Simplified LSTM
- Fewer parameters
- Similar performance

3. Attention mechanisms:

- Directly access any previous state
- No compression bottleneck
- Foundation for Transformers

□ Key Mathematical Insights

1. Recurrence as State Space Model

RNN can be viewed as a dynamical system:

State equation:

$$h_t = f(h_{t-1}, x_t; \theta)$$

Observation equation:

$$o_t = g(h_t; \theta)$$


This is a **Markov model**:

$$p(x_{t+1}|x_1, \dots, x_t) = p(x_{t+1}|h_t)$$

where h_t is a **sufficient statistic** for the history!

2. Unrolled Computation Graph

Unrolled RNN:



Same weights at each step:

- W_{hh}, W_{xh}, W_{hy} shared across all time steps
- Training: Backpropagation Through Time (BPTT)

- Gradients accumulated across entire sequence

3. Computational Complexity

Per time step:

- Hidden update: $O(d^2 + dk)$
- Output computation: $O(dk)$

For sequence of length T :

- Total: $O(T(d^2 + dk))$
- Linear in sequence length!

Compare to FVSBN:

- $O(n^2)$ parameters
- RNN: $O(d^2)$ parameters (independent of n)

□ Deep Dive: Tanh Activation

Why tanh instead of sigmoid?

Tanh properties:

$$\tanh(z) = \frac{e^z - e^{-z}}{e^z + e^{-z}}$$

- **Range:** $(-1, 1)$ (zero-centered!)
- **Derivative:** $\tanh'(z) = 1 - \tanh^2(z)$
- **Maximum derivative:** 1 (at $z = 0$)

Sigmoid:

- **Range:** $(0, 1)$ (not zero-centered)
- **Maximum derivative:** 0.25

Advantage of tanh:

- Zero-centered helps gradient flow
- Stronger gradients
- Better for recurrent connections

□ Comparison Table: All Autoregressive Models So Far

| Model | Parameters | Training | Sampling | Parallelization | Memory |
|-------|------------|-----------|----------|------------------|----------|
| FVSBN | $O(n^2)$ | $O(n^2)$ | $O(n^2)$ | Some (per image) | $O(n^2)$ |
| NADE | $O(nd)$ | $O(n^2d)$ | $O(nd)$ | No (sequential) | $O(nd)$ |
| MADE | $O(nd)$ | $O(nd)$ | $O(nd)$ | Yes (training) | $O(nd)$ |

| Model | Parameters | Training | Sampling | Parallelization | Memory |
|-------|------------|-----------|-----------|-----------------|--------|
| RNN | $O(d^2)$ | $O(nd^2)$ | $O(nd^2)$ | No (sequential) | $O(d)$ |

Key differences:

- RNN has **constant parameters** (doesn't grow with n)
- All have **sequential sampling** (autoregressive constraint)
- MADE has fastest training (parallel)
- RNN most memory-efficient

✓ Key Takeaways for Topic 10

1. **RNNs use recursive hidden state** to summarize growing history
2. **Constant parameters** $O(d^2)$ independent of sequence length
3. **Recurrence relation:** $h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$
4. **Universal approximation:** Can compute any function theoretically
5. **Sequential processing:** Cannot parallelize across time (slow training)
6. **Vanishing gradients:** Hard to capture long-range dependencies
7. **Memory efficient:** Fixed-size hidden state for any sequence length
8. **Applications:** Text, speech, time series, video

□ Check Your Understanding:

1. **Why does RNN have constant parameters?**
 - Same weights reused at every time step
2. **What does hidden state h_t represent?**
 - Summary of all inputs seen up to time t
3. **Can we train RNN in parallel across time steps?**
 - No, must compute sequentially (h_t depends on h_{t-1})
4. **How many parameters for RNN with $d = 100$ hidden units, vocabulary size $k = 50$?**
 - $d + d^2 + 2dk = 100 + 10000 + 10000 = 20,100$
5. **What causes vanishing gradients in RNNs?**
 - Repeated multiplication of weight matrices during backpropagation

Ready for Topic 11: "Attention-Based Models & Transformers"? This solves the RNN bottleneck problem! Type "yes" to continue! ☺

✿

Topic 11: "Attention-Based Models & Transformers"?

TOPIC 11: ATTENTION-BASED MODELS & GENERATIVE TRANSFORMERS

□ Concept: Solving the RNN Bottleneck

Attention mechanisms revolutionized sequence modeling by addressing the fundamental limitation of RNNs: the **single hidden state bottleneck**. Instead of compressing all history into one vector, attention allows the model to **selectively focus** on relevant parts of the history.

The Revolutionary Idea: When predicting the next word, don't rely solely on a compressed summary—**look back directly** at all previous words and decide which ones are important!

Transformers take this further: **eliminate recurrence entirely** and use **only attention mechanisms**, enabling full parallelization during training.

Why it matters: Transformers power modern AI (GPT-4, ChatGPT, BERT, etc.) and represent the **state-of-the-art** for autoregressive models!

□ Detailed Explanation

The RNN Bottleneck Problem (Recap)

From slides (Page 28):

Problem 1: Single Hidden Vector

"A single hidden vector needs to summarize all the (growing) history. For example, $h^{(4)}$ needs to summarize the meaning of 'My friend opened the'."

Example:

Sentence: "My friend opened the _____"

RNN processing:

$h_0 \rightarrow [\text{My}] \rightarrow h_1 \rightarrow [\text{friend}] \rightarrow h_2 \rightarrow [\text{opened}] \rightarrow h_3 \rightarrow [\text{the}] \rightarrow h_4$

↓

Must predict: "door"

Issue: h_4 must encode:

- **Subject:** "My friend" (who is doing the action?)
- **Action:** "opened" (what happened?)
- **Article:** "the" (indicates a noun is coming)
- **Context:** What objects can be opened?

All compressed into fixed-size vector $h_4 \in \mathbb{R}^{512}$!

For very long sentences (100+ words), early information gets "forgotten"!

Problem 2: Sequential Computation

- Cannot parallelize across time steps
- Training is slow
- Cannot leverage modern GPU parallelism effectively

Problem 3: Vanishing Gradients

- Hard to learn long-range dependencies
- Gradient flow deteriorates over many steps

□ ATTENTION MECHANISM: The Solution

From slides (Page 29): "Attention mechanism to compare a **query** vector to a set of **key** vectors"

Core Idea

Instead of relying only on current hidden state, **attend to all previous hidden states**:

1. **Compare** current state (query) to all past states (keys)
2. **Compute attention weights** (how relevant is each past state?)
3. **Aggregate** past states weighted by attention
4. **Use aggregated information** to make prediction

Mathematical Formulation

From slides (Page 29):

Step 1: Compare query to keys (compute similarity)

"Compare current hidden state (query) to all past hidden states (keys), e.g., by taking a dot product"

$$\text{similarity}_i = h_t^T h_i \quad \text{for } i = 1, \dots, t-1$$

Where:

- h_t : Current hidden state (query)
- h_i : Past hidden state at position i (key)
- $h_t^T h_i$: Dot product (measures similarity)

Alternative similarity functions:

- Scaled dot product: $\frac{h_t^T h_i}{\sqrt{d}}$
- Additive: $v^T \tanh(W_q h_t + W_k h_i)$
- Multiplicative: $h_t^T W h_i$

Step 2: Construct attention distribution

"Construct attention distribution to figure out what parts of the history are relevant, e.g., via a softmax"

$$\alpha_{t,i} = \frac{\exp(h_t^T h_i)}{\sum_{j=1}^{t-1} \exp(h_t^T h_j)}$$

Properties:

- $\alpha_{t,i} \in [0, 1]$: Attention weight for position i
- $\sum_{i=1}^{t-1} \alpha_{t,i} = 1$: Valid probability distribution
- **High $\alpha_{t,i}$:** Position i is relevant for predicting at t
- **Low $\alpha_{t,i}$:** Position i is not relevant

Step 3: Construct summary of history

"Construct a summary of the history, e.g., by weighted sum"

$$c_t = \sum_{i=1}^{t-1} \alpha_{t,i} h_i$$

Where:

- c_t : **Context vector** (weighted summary of history)
- Combines information from all past states
- Weights determined by relevance (attention)

Step 4: Make prediction

"Use summary and current hidden state to predict next token/word"

$$o_t = f(h_t, c_t)$$

$$p(x_{t+1}|x_{\leq t}) = \text{softmax}(o_t)$$

The context vector c_t provides direct access to relevant history!

□ Detailed Numerical Example: Attention in Action

Scenario: Predicting next word in sentence

Sentence: "My friend opened the ____"

Vocabulary: {door, window, book, computer, ...} (10,000 words)

RNN hidden states (after processing):

| Position | Word | Hidden state |
|----------|----------|---------------------------------------------------------|
| 1 | "My" | $h_1 = [0.2, 0.5, -0.1, 0.8, \dots]$ (d=512 dimensions) |
| 2 | "friend" | $h_2 = [0.4, 0.3, 0.2, 0.1, \dots]$ |
| 3 | "opened" | $h_3 = [-0.1, 0.7, 0.5, 0.3, \dots]$ |
| 4 | "the" | $h_4 = [0.3, 0.2, -0.2, 0.6, \dots]$ |

Step 1: Compute similarities (dot products)

Current state (query): h_4 (at position "the")

Similarities with past states:

$$s_1 = h_4^T h_1 = 0.3(0.2) + 0.2(0.5) + (-0.2)(-0.1) + 0.6(0.8) + \dots = 1.2$$

$$s_2 = h_4^T h_2 = 0.3(0.4) + 0.2(0.3) + (-0.2)(0.2) + 0.6(0.1) + \dots = 0.8$$

$$s_3 = h_4^T h_3 = 0.3(-0.1) + 0.2(0.7) + (-0.2)(0.5) + 0.6(0.3) + \dots = 2.5$$

Interpretation:

- High similarity with h_3 ("opened"): Most relevant!
- Lower similarity with h_1 ("My") and h_2 ("friend")

Step 2: Compute attention weights (softmax)

$$\alpha_{4,1} = \frac{\exp(1.2)}{\exp(1.2) + \exp(0.8) + \exp(2.5)} = \frac{3.32}{3.32 + 2.23 + 12.18} = \frac{3.32}{17.73} = 0.187$$

$$\alpha_{4,2} = \frac{\exp(0.8)}{17.73} = \frac{2.23}{17.73} = 0.126$$

$$\alpha_{4,3} = \frac{\exp(2.5)}{17.73} = \frac{12.18}{17.73} = 0.687$$

Attention distribution:

| Position | Word | Attention weight |
|----------|----------|-------------------------|
| 1 | "My" | 18.7% (some attention) |
| 2 | "friend" | 12.6% (less attention) |
| 3 | "opened" | 68.7% (most attention!) |

Interpretation: The model focuses primarily on "opened" (68.7%) when predicting what comes after "the"!

Step 3: Construct context vector

$$c_4 = 0.187 \cdot h_1 + 0.126 \cdot h_2 + 0.687 \cdot h_3$$

$$c_4 = 0.187 \begin{bmatrix} 0.2 \\ 0.5 \\ -0.1 \\ 0.8 \\ \vdots \end{bmatrix} + 0.126 \begin{bmatrix} 0.4 \\ 0.3 \\ 0.2 \\ 0.1 \\ \vdots \end{bmatrix} + 0.687 \begin{bmatrix} -0.1 \\ 0.7 \\ 0.5 \\ 0.3 \\ \vdots \end{bmatrix}$$

$$c_4 \approx \begin{bmatrix} -0.02 \\ 0.62 \\ 0.36 \\ 0.36 \\ \vdots \end{bmatrix}$$

This vector emphasizes information from "opened"!

Step 4: Predict next word

$$o_4 = W_o[h_4; c_4] + b_o$$

(Concatenate current state and context, apply linear transformation)

$$p(\text{next word} | \text{"My friend opened the"}) = \text{softmax}(o_4)$$


Predictions:

```
p("door") = 0.35      ← Highest (makes sense!)
p("window") = 0.25
p("book") = 0.15
p("computer") = 0.10
p("car") = 0.08
...
...
```

The model correctly predicts physical objects that can be opened, focusing on the action word "opened"!

Diagram Description: Attention Mechanism

From slides (Page 29):



Visual from slides:

- Bar chart showing attention distribution
- Heights indicate attention weights
- Taller bars = more attention to that position
- Example: "door" gets high attention to "opened"

GENERATIVE TRANSFORMERS (GPT Architecture)

From slides (Page 30): "Current state of the art (GPTs): replace RNN with Transformer"

Key Innovations

1. **No recurrence:** Eliminate RNN entirely
2. **Self-attention only:** Use attention to process entire sequence
3. **Parallel processing:** All positions computed simultaneously
4. **Positional encodings:** Add position information explicitly

Architecture Components

From slides (Page 30):

1. Multi-Head Attention

- Multiple attention mechanisms in parallel
- Each "head" learns different patterns
- Richer representations

2. Feed-Forward Networks

- Applied to each position independently
- Non-linear transformations
- Same network for all positions (like RNN weight sharing)

3. Layer Normalization

- Stabilizes training
- Normalizes activations

4. Residual Connections

- Skip connections around each sub-layer
- Helps gradient flow
- Enables very deep networks

5. Masked Self-Attention

"Needs masked self-attention to preserve autoregressive structure"

Crucial for generation: Position i can only attend to positions $j \leq i$ (not future!)

Mathematical Formulation

Multi-Head Attention:

For each attention head k :

$$\text{head}_k = \text{Attention}(QW_k^Q, KW_k^K, VW_k^V)$$

Where:

- Q : Query matrix (all positions)
- K : Key matrix
- V : Value matrix
- W_k^Q, W_k^K, W_k^V : Learned projection matrices for head k

Scaled Dot-Product Attention:

$$\text{Attention}(Q, K, V) = \text{softmax} \left(\frac{QK^T}{\sqrt{d_k}} \right) V$$

Multi-head output:

$$\text{MultiHead}(Q, K, V) = \text{Concat}(\text{head}_1, \dots, \text{head}_h)W^O$$

Masked Attention (for autoregressive):

Mask matrix M :

$$M_{ij} = \begin{cases} 0 & \text{if } i \geq j \\ -\infty & \text{if } i < j \end{cases}$$


Applied to attention scores:


$$\text{Attention}(Q, K, V) = \text{softmax} \left(\frac{QK^T}{\sqrt{d_k}} + M \right) V$$

Effect: Position i has $-\infty$ attention to positions $j > i$, so after softmax, attention weight is 0!

Diagram Description: Transformer Decoder

From slides (Page 30):





Key visualization from slides:

- Shows stacked decoder layers
- Masked self-attention block highlighted
- Feed-forward neural network
- Residual connections (arrows wrapping around)
- Position "t+1" only sees positions 1 to t

Real-World Applications

1. GPT Models (OpenAI)

GPT-3 / GPT-4:

- **Parameters:** 175 billion (GPT-3)
- **Architecture:** Transformer decoder (autoregressive)
- **Training:** Massive text corpus (hundreds of billions of words)

Applications:

- ChatGPT (conversational AI)
- Code generation (GitHub Copilot)
- Creative writing
- Translation
- Question answering

Example:

Prompt: "Write a Python function to compute Fibonacci"

GPT-4 output:

```

def fibonacci(n):
    if n <= 1:
        return n
    return fibonacci(n-1) + fibonacci(n-2)
  
```

2. GitHub Copilot

Task: Code completion and generation

Architecture: GPT-based transformer trained on code

Example:

```
# User types:  
def calculate_prime_numbers(n):  
    """Return list of prime numbers up to n"""  
  
# Copilot generates:  
    primes = []  
    for num in range(2, n + 1):  
        is_prime = True  
        for i in range(2, int(num ** 0.5) + 1):  
            if num % i == 0:  
                is_prime = False  
                break  
        if is_prime:  
            primes.append(num)  
    return primes
```

Adoption: Millions of developers worldwide

3. AlphaCode (DeepMind)

Task: Competitive programming

Architecture: Transformer-based autoregressive model

Performance:

- Solves programming competition problems
- Ranks in top 54% of human competitors
- Generates thousands of candidate solutions, selects best

Application: Automated software development assistance

4. Stable Diffusion (Text-to-Image)

Uses transformers for text encoding

Example:

```
Prompt: "A photorealistic image of a cat astronaut in space"  
→ Transformer encodes text  
→ Diffusion model generates image
```

Applications:

- Digital art creation

- Product design
- Game asset generation

□ Computational Complexity

RNN vs Transformer

RNN (Sequential):

- Time complexity per layer: $O(n \cdot d^2)$
- Cannot parallelize across sequence
- Total operations: Sequential

Transformer (Parallel):

- Time complexity per layer: $O(n^2 \cdot d)$ (attention)
- Can parallelize across sequence
- Total operations: Parallel

Training speed comparison (NVIDIA A100 GPU):

- RNN on 1000-token sequence: ~5 seconds
- Transformer on 1000-token sequence: ~0.5 seconds (10x faster!)

Trade-off:

- RNN: $O(n \cdot d^2)$ but sequential
- Transformer: $O(n^2 \cdot d)$ but parallel

For modern GPUs: Parallelization wins! Transformers much faster despite higher complexity.

❖ Advantages of Transformers over RNNs

From slides (Page 30):

✓ Pros:

1. **Attention mechanisms to adaptively focus only on relevant context**
 - No information bottleneck
 - Direct access to any position
 - Learns what to attend to
2. **Avoid recursive computation**
 - No sequential dependencies
 - All positions processed in parallel
 - Much faster training
3. **Use only self-attention to enable parallelization**
 - GPU-friendly operations

- Batch processing efficient
- Scales to very long sequences

4. Better long-range dependencies

- Direct connections between any positions
- No vanishing gradient through time
- Captures relationships 1000+ tokens apart

5. State-of-the-art performance

- Best results on NLP benchmarks
- Powers modern LLMs (GPT, PaLM, LLaMA)
- Extensible to vision (ViT), audio, multimodal

✗ Cons:

1. Quadratic memory in sequence length

- Attention matrix: $n \times n$
- Memory: $O(n^2 \cdot d)$
- Problematic for very long sequences (>10k tokens)

2. Still sequential generation

- Must generate token-by-token
- Cannot parallelize sampling
- Slow for long outputs

3. Requires positional encoding

- Must explicitly add position information
- Various schemes (sinusoidal, learned)
- No inherent temporal structure

4. No recurrence

- Cannot naturally process streaming data
- Fixed context window
- Must reprocess entire sequence for each new token

5. Computationally expensive

- Large models (billions of parameters)
- High training cost (millions of dollars)
- Inference cost scales with model size


Deep Dive: Why Attention Works

1. Information Flow

RNN bottleneck:

$x_1 \rightarrow h_1 \rightarrow h_2 \rightarrow h_3 \rightarrow \dots \rightarrow h_{100}$
↓
Information from x_1 must flow through 100 recurrent steps!

Attention direct access:



Information from x_1 accessed directly!

2. Gradient Flow

RNN backpropagation:

$$\frac{\partial L}{\partial h_1} = \frac{\partial L}{\partial h_{100}} \prod_{t=2}^{100} \frac{\partial h_t}{\partial h_{t-1}}$$

Problem: 99 matrix multiplications → vanishing/exploding gradients

Transformer backpropagation:

$$\frac{\partial L}{\partial x_1} = \frac{\partial L}{\partial \text{attention}} \frac{\partial \text{attention}}{\partial x_1}$$

Advantage: Direct path, no long multiplication chains

3. Learned Relevance

Attention learns which positions matter:

Example: Pronoun resolution

Sentence: "The dog ran to the park because it was excited"

When predicting after "it":

Attention weights:

- "dog": 0.85 ← High attention (referent!)
- "park": 0.10
- "excited": 0.05

The model learns "it" refers to "dog"!

□ Key Mathematical Insights

1. Scaled Dot-Product Attention

Why scale by $\sqrt{d_k}$?

$$\text{Attention}(Q, K, V) = \text{softmax} \left(\frac{QK^T}{\sqrt{d_k}} \right) V$$

Reason: If d_k is large, dot products grow large \rightarrow softmax saturates \rightarrow small gradients

Example:

- Without scaling: QK^T values around 100 \rightarrow softmax $\approx [1, 0, 0, 0, \dots]$
- With scaling: $QK^T / \sqrt{d_k}$ values around 10 \rightarrow softmax $\approx [0.7, 0.2, 0.1, \dots]$

Scaling stabilizes training!

2. Multi-Head Attention Benefit

Single head: One attention pattern

Multi-head (e.g., 8 heads): 8 different attention patterns

Example heads might learn:

- Head 1: Syntactic dependencies (verb-object)
- Head 2: Semantic similarity (synonyms)
- Head 3: Positional proximity (nearby words)
- Head 4: Long-range dependencies
- ...

Richer representation from multiple perspectives!

3. Autoregressive Masking Mathematics

Unmasked attention: Position 3 can see positions 1, 2, 3, 4, 5

Masked attention: Position 3 can only see positions 1, 2, 3

Implementation:

$$\text{scores} = \frac{QK^T}{\sqrt{d_k}} + M$$

Where M is upper triangular with $-\infty$:

$$M = \begin{bmatrix} 0 & -\infty & -\infty & -\infty \\ 0 & 0 & -\infty & -\infty \\ 0 & 0 & 0 & -\infty \\ 0 & 0 & 0 & 0 \end{bmatrix}$$

After softmax: $\text{softmax}(-\infty) = 0 \rightarrow$ no attention to future!

□ Performance Comparison

| Model | Long-Range_deps | Training Speed | Generation Speed | Memory | SOTA |
|-------------|------------------------|-------------------|-----------------------|--------|------|
| RNN | Poor (vanishing grads) | Slow (sequential) | Slow | Low | No |
| LSTM | Better (gating) | Slow (sequential) | Slow | Medium | No |
| Transformer | Excellent (direct) | Fast (parallel) | Slow (autoregressive) | High | Yes |

Conclusion: Transformers dominate modern NLP despite higher memory usage!

✓ Key Takeaways for Topic 11

1. **Attention solves RNN bottleneck** by direct access to all past states
2. **Three-step attention:** Compute similarity \rightarrow Softmax \rightarrow Weighted sum
3. **Transformers eliminate recurrence** entirely (self-attention only)
4. **Parallel training:** All positions processed simultaneously
5. **Masked attention:** Preserves autoregressive structure (no future peeking)
6. **State-of-the-art:** GPT, ChatGPT, most modern LLMs use transformers
7. **Trade-off:** $O(n^2)$ memory but massive parallelization wins
8. **Applications:** Text generation, translation, code, question answering

□ Check Your Understanding:

1. **What problem does attention solve?**
 - RNN's single hidden state bottleneck (information compression)
2. **Why can transformers train in parallel but RNNs cannot?**
 - Transformers: No sequential dependencies (attention computed independently)
 - RNNs: Must compute h_t before h_{t+1}
3. **What is masked self-attention?**
 - Prevents position i from attending to positions $j > i$ (preserves causality)
4. **Why scale attention scores by $\sqrt{d_k}$?**
 - Prevents saturation of softmax for large dimensions
5. **Can transformers parallelize generation?**
 - No! Still autoregressive (must generate token-by-token)

We've completed the major autoregressive architectures! Ready for Topic 12: "Convolutional Autoregressive Models (PixelCNN)"? This brings spatial structure to image generation! Type "yes" to continue! ☺

Ready for Topic 12: "Convolutional Autoregressive Models (PixelCNN)"?

TOPIC 12: CONVOLUTIONAL AUTOREGRESSIVE MODELS (PixelCNN)

□ Concept: Exploiting Spatial Structure in Images

PixelCNN combines the power of **convolutional neural networks (CNNs)** with **autoregressive modeling** to generate images. Instead of treating pixels as an arbitrary sequence, PixelCNN leverages the **2D spatial structure** of images using convolutions while maintaining autoregressive dependencies.

Key Innovation: Use **masked convolutions** to ensure each pixel only depends on previous pixels in raster scan order, while gaining the efficiency and inductive biases of convolutional architectures.

Why it matters: PixelCNN achieves performance similar to PixelRNN but with **much faster training** due to parallelizable convolutions!

□ Detailed Explanation

Why Convolutions for Images?

From slides (Page 31): "Convolutions are natural for image data and easy to parallelize on modern hardware."

Problems with fully-connected models (NADE, MADE, FVSBN):

1. **No spatial awareness:** Treat pixels as flat vector
 - Pixel 100 and pixel 101 treated independently
 - Ignores fact they're neighbors in 2D space!
2. **Too many parameters:** Fully-connected layers scale poorly
 - For 32×32 RGB image: 3,072 input features
 - Hidden layer of 512: 1.57 million parameters just for first layer!
3. **No translation equivariance:** Must learn same pattern at every location
 - Edge detector learned for top-left must be relearned for top-right
 - Inefficient use of parameters

Advantages of Convolutions:

1. **Spatial locality:** Neighboring pixels processed together
 - Natural for images (nearby pixels highly correlated)
 - Captures local patterns (edges, textures, corners)

2. **Parameter sharing:** Same filter applied everywhere
 - Learn "edge detector" once, use everywhere
 - Dramatically reduces parameters
3. **Translation equivariance:** Pattern detected anywhere in image
 - If filter detects edge in top-left, also detects in bottom-right
 - Generalizes better
4. **Hardware efficiency:** Convolutions highly optimized on GPUs
 - Parallel operations
 - Fast matrix multiplications
 - Modern GPUs have specialized hardware for convolutions

PixelCNN Architecture

From slides (Page 32): "PixelCNN (Oord et al., 2016)"

Goal


"Use convolutional architecture to predict next pixel given context (a neighborhood of pixels)."

Challenge: Convolutions are **not naturally autoregressive!**

Standard convolution: Each output depends on **all inputs in receptive field** (past, current, future)

Problem for generation:

Standard 3x3 convolution:




Can't use this! Would create circular dependency.

Solution: Masked Convolutions

From slides (Page 32): "Challenge: Has to be autoregressive. **Masked convolutions** preserve raster scan order."

Idea: Zero out parts of convolution filter to block future information!

Type A Mask (for first layer):



| | | | | |
|---|---|---|--|------------------------------------|
| ✓ | 0 | 0 | | ← Pixels to left, but NOT current! |
| 0 | 0 | 0 | | ← No pixels below |
| 0 | 0 | 0 | | |

Type B Mask (for subsequent layers):

| | | | | |
|---|---|---|--|-----------------------------------------------------|
| ✓ | ✓ | ✓ | | ← All pixels above |
| ✓ | ✓ | 0 | | ← Include current pixel (already masked in layer 1) |
| 0 | 0 | 0 | | ← No pixels below |

Mathematical Formulation:

Standard convolution:

$$y_{i,j} = \sum_{k,l} w_{k,l} \cdot x_{i+k,j+l}$$

Masked convolution:

$$y_{i,j} = \sum_{k,l} (w_{k,l} \odot m_{k,l}) \cdot x_{i+k,j+l}$$

Where $m_{k,l} \in \{0, 1\}$ is the mask (0 = blocked, 1 = allowed)

□ Detailed Example: 5×5 Image with PixelCNN

Let's work through a complete example.

Setup

Image: 5×5 grayscale (25 pixels)

Raster scan order:

| | | | | | |
|----|----|----|----|----|--|
| 1 | 2 | 3 | 4 | 5 | |
| 6 | 7 | 8 | 9 | 10 | |
| 11 | 12 | 13 | 14 | 15 | |
| 16 | 17 | 18 | 19 | 20 | |
| 21 | 22 | 23 | 24 | 25 | |

PixelCNN architecture:

- Input: 5×5×1 (grayscale)

- Layer 1: Masked Conv (3×3, Type A mask)
- Layer 2: Masked Conv (3×3, Type B mask)
- Output: 5×5×256 (probability distribution over 256 intensities for each pixel)

Predicting Pixel 13 (Center Pixel)

Step 1: First convolutional layer (Type A mask)

Receptive field for pixel 13:

Context (what pixel 13 can see):

| | | | | |
|----|----|---|--|-----------------------------------|
| 7 | 8 | 9 | | Row above (all visible) |
| 11 | 12 | | | Current row (only left neighbors) |
| | | | | Row below (nothing visible) |

Apply 3×3 Type A masked convolution:

Mask pattern:

$$M_A = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Filter weights (example):

$$W = \begin{bmatrix} 0.1 & 0.2 & 0.1 \\ 0.2 & 0.5 & 0.2 \\ 0.1 & 0.2 & 0.1 \end{bmatrix}$$

Masked filter:

$$W \odot M_A = \begin{bmatrix} 0.1 & 0.2 & 0.1 \\ 0.2 & 0 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

Computation:

$$\begin{aligned} h_{13}^{(1)} &= 0.1 \cdot x_7 + 0.2 \cdot x_8 + 0.1 \cdot x_9 + 0.2 \cdot x_{11} + 0.0 \cdot x_{12} \\ &= 0.1(0.8) + 0.2(0.9) + 0.1(0.7) + 0.2(0.6) \\ &= 0.08 + 0.18 + 0.07 + 0.12 \\ &= 0.45 \end{aligned}$$

Apply activation: $h_{13}^{(1)} = \text{ReLU}(0.45) = 0.45$

Step 2: Second convolutional layer (Type B mask)

Now use Type B mask (includes center):

$$M_B = \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 0 \\ 0 & 0 & 0 \end{bmatrix}$$

This layer processes the hidden representation from layer 1:

$$h_{13}^{(2)} = \text{Conv}_{M_B}(h^{(1)})$$

Step 3: Output layer (predict probability distribution)

$$\hat{x}_{13} = \text{softmax}(W_{\text{out}} h_{13}^{(2)} + b_{\text{out}})$$

Output: 256-dimensional probability vector

$$\hat{x}_{13} = [p(x_{13} = 0), p(x_{13} = 1), \dots, p(x_{13} = 255)]$$

Example output:


```
p(x13 = 0) = 0.001    (very dark - unlikely)
p(x13 = 100) = 0.15   (medium dark)
p(x13 = 150) = 0.45   (medium - most likely!)
p(x13 = 200) = 0.25   (bright)
p(x13 = 255) = 0.001  (very bright - unlikely)
```

The model predicts pixel 13 is most likely to have intensity ~150!

Diagram Description: Masked Convolutions

From slides (Page 32) - Multiple visualizations:

1. Receptive Field Visualization



Legend:

- █ (Dark blue) = Available context
- █ (Medium) = Current pixel
- █ (Light) = Blocked (future)

2. Mask Visualization for RGB

From slides: "Additional masking for colors order"

Color channel ordering: Red → Green → Blue

For predicting RED channel:

- No color information from current pixel
- All colors from previous pixels

For predicting GREEN channel:

- RED from current pixel
- All colors from previous pixels

For predicting BLUE channel:

- RED and GREEN from current pixel
- All colors from previous pixels


Mathematical representation:

$$p(x_i^R, x_i^G, x_i^B | x_{<i}) = p(x_i^R | x_{<i}) \cdot p(x_i^G | x_{<i}, x_i^R) \cdot p(x_i^B | x_{<i}, x_i^R, x_i^G)$$

3. Blind Spot Issue

From slides (Page 32) - Shows potential "blind spot":

Problem with naive masking:



After stacking masked convolutions,
top-right pixel never influences X!
(diagonal blind spot)

Solution: Use **two stacks** (vertical and horizontal) and combine

□ PixelCNN Architecture Variants

1. Gated PixelCNN

Improvement: Add gating mechanisms (like LSTM)

Gated activation:

$$y = \tanh(W_f * x) \odot \sigma(W_g * x)$$

Where:

- $W_f * x$: Feature convolution
- $W_g * x$: Gate convolution
- \odot : Element-wise multiplication
- σ : Sigmoid function

Benefits:

- Better gradient flow
- More expressive
- Improved performance

2. PixelCNN++

Multiple improvements:

1. Discretized logistic mixture likelihood:

- More flexible than softmax over 256 values
- Continuous-like distribution
- Better modeling of gradients

2. Downsampling:

- Process at multiple scales
- Faster computation
- Larger receptive field

3. Conditioning:

- Can condition on class labels
- $p(x|y)$ where y is digit class

State-of-the-art results on image generation!

□ PixelCNN Results

From slides (Page 33): "Samples from the model trained on Imagenet (32×32 pixels). Similar performance to PixelRNN, but much faster."

Generated Samples

Grid of 32×32 generated images:
 [Shows various objects: dogs, cars, flowers, buildings, etc.]

Quality observations:

- ✓ Recognizable objects
- ✓ Consistent local structure
- ✓ Realistic textures
- ✓ Proper color distributions
- ✗ Some global inconsistencies

- ✗ Occasional artifacts
- ✗ Limited semantic coherence

Performance Metrics

Bits per dimension (lower is better):

Dataset: CIFAR-10 (32×32 RGB)

| Model | Bits/dim | Training Time |
|------------|----------|------------------|
| FVSBN | 3.05 | Fast |
| NADE | 3.00 | Medium |
| PixelRNN | 2.92 | Very Slow (days) |
| PixelCNN | 2.95 | Fast (hours) |
| PixelCNN++ | 2.88 | Fast |

Key insight: PixelCNN achieves near PixelRNN performance with 10-100x faster training!

Real-World Applications

1. Image Inpainting (Hole Filling)

Task: Fill in missing regions of images

Approach:

- Train PixelCNN on complete images
- Given image with hole, use $p(x_{\text{hole}} | x_{\text{known}})$
- Generate pixels in missing region

Example:

```
Input: [Photo with face partially obscured]
Output: [Plausible completion of face]
```

Applications:

- Photo restoration
- Object removal
- Content-aware fill (Photoshop)

2. Super-Resolution

Task: Generate high-resolution image from low-resolution input

Approach:

- Train PixelCNN on high-res images
- Condition on low-res version
- Generate high-res details

Example:

Input: 16×16 blurry image

Output: 64×64 sharp image

Applications:

- Medical imaging enhancement
- Satellite imagery
- Old photo restoration
- Enhance surveillance footage

3. Image Compression

Task: Compress images more efficiently than JPEG

Approach:

- Train PixelCNN as probabilistic model $p(x)$
- Use entropy coding based on learned probabilities
- Arithmetic coding achieves $-\log_2 p(x)$ bits

Benefits:

- Near-optimal compression
- Adapts to image content
- Better than traditional codecs for learned domains

Research: Google's learned image compression

4. Texture Synthesis

Task: Generate seamless textures (wood, fabric, stone)

Approach:

- Train PixelCNN on texture samples
- Generate arbitrarily large textures
- Ensures consistency

Applications:

- Video game assets
- 3D rendering
- Architectural visualization
- Virtual reality environments

5. Anomaly Detection in Manufacturing

Task: Detect defects in products

Approach:

- Train PixelCNN on defect-free products
- Compute $p(x)$ for new products
- Low probability → anomaly!

Example: Semiconductor wafer inspection

```
Normal wafer: log p(x) = -2500
Defective wafer: log p(x) = -4800 ← Flag for inspection!
```

Benefits:

- No need for defect examples
- Automatic detection
- Real-time processing

□ Computational Complexity

Training Complexity

PixelCNN (single forward pass):

For image of size $H \times W$ with C channels and L layers:

Operations per layer:

$$O(H \cdot W \cdot C \cdot K^2 \cdot D)$$

Where:

- K : Kernel size (e.g., 3 for 3×3)
- D : Number of filters/channels

Total for L layers:

$$O(L \cdot H \cdot W \cdot C \cdot K^2 \cdot D)$$

Example: CIFAR-10 (32×32 RGB)

- $H = W = 32$
- $C = 3$ (RGB)
- $L = 15$ layers
- $K = 3$
- $D = 128$ filters

Operations:

$$15 \times 32 \times 32 \times 3 \times 9 \times 128 \approx 141 \text{ million ops per image}$$

GPU (NVIDIA A100): ~1000 images/second

Training time: Few hours on single GPU

Sampling Complexity

Generation is still sequential:

- Must generate $H \times W \times C$ pixels one at a time
- Each pixel requires one forward pass
- Total: $H \times W \times C$ forward passes

For 32×32 RGB: 3,072 forward passes per image!

Generation time: ~1-5 seconds per image (depending on hardware)

Much slower than non-autoregressive models (GANs generate in ~0.01 seconds)!

❖ Pros and Cons of PixelCNN

✓ Pros:

1. Fast parallel training:

- All pixels processed simultaneously during training
- GPU-optimized convolutions
- 10-100× faster than PixelRNN

2. Spatial structure:

- Convolutions naturally capture 2D relationships
- Local patterns learned efficiently
- Parameter sharing reduces model size

3. Exact likelihood:

- Can compute $p(x)$ exactly
- Good for model evaluation
- Anomaly detection

4. Scalable:

- Can scale to larger images
- Stack more layers for larger receptive fields
- Proven on 256×256 images

5. State-of-the-art (when published):

- Best autoregressive model for images
- Competitive with other generative models
- Foundation for later work

✗ Cons:

1. Slow generation:

- Sequential pixel-by-pixel sampling
- Cannot parallelize generation
- Seconds per image (vs milliseconds for GANs)

2. Blind spot problem:

- Naive masking creates unreachable regions
- Requires careful architecture design
- Need multiple stacks (vertical + horizontal)

3. Limited receptive field:

- Each layer sees small neighborhood
- Need many layers for global context
- Deep networks harder to train

4. Still requires ordering:

- Raster scan may not be optimal
- Different orderings not easily comparable
- Arbitrary choice for 2D data

5. Quadratic parameters for images:

- For n pixels, full model needs many filters
- Memory grows with image size
- Large models for high-resolution images

6. No latent representation:

- Like other autoregressive models, no explicit features
- Harder to use for downstream tasks
- Cannot easily interpolate between images

□ Deep Dive: Why Masking Works

Mathematical Guarantee

Theorem: Masked convolutions preserve autoregressive structure.

Proof sketch:

1. **First layer:** Type A mask ensures $h_i^{(1)}$ only depends on x_j where $j < i$
2. **Hidden layers:** Type B masks ensure $h_i^{(\ell)}$ only depends on $h_j^{(\ell-1)}$ where $j \leq i$
3. **By induction:** $h_i^{(L)}$ only depends on x_j where $j < i$
4. **Output:** $\hat{x}_i = f(h_i^{(L)})$ only depends on $x_{<i}$ ✓

Key insight: Masks create a **computational graph that respects causality!**

Receptive Field Growth

With stacked masked convolutions, receptive field grows:

Layer 1: 3×3 neighborhood

Layer 2: 5×5 neighborhood

Layer 3: 7×7 neighborhood

...

Layer L : $(2L + 1) \times (2L + 1)$ neighborhood

For large context: Stack many layers

Trade-off: Deeper networks harder to train (vanishing gradients)

□ Key Mathematical Insights

1. Convolution as Weight Sharing

Fully-connected: Separate weight for each pair of pixels

$$\text{Parameters} = n^2$$

Convolutional: Same filter applied everywhere

$$\text{Parameters} = K^2 \times D \times L$$

Dramatic reduction!

- FC: ~600,000 parameters for 32×32 image
- Conv: ~1,500 parameters (400x reduction!)

2. Autoregressive Factorization

Despite using convolutions, still autoregressive:

$$p(x) = \prod_{i=1}^{H \times W} p(x_i | x_{<i})$$

Each conditional modeled by masked CNN:

$$p(x_i | x_{<i}) = \text{PixelCNN}_\theta(x_{<i})$$

Exact likelihood computable (sum log probabilities)

3. Masking as Structured Sparsity

Mask matrix M : Binary matrix selecting allowed connections

Effective weight: $W_{\text{eff}} = W \odot M$

During training:

- Gradient flows only through unmasked connections
- Masked weights stay at 0 (or not updated)
- Network learns within structural constraints

Elegant way to enforce causality without architecture changes!

□ Comparison Table: Image Autoregressive Models

| Aspect | NADE | MADE | PixelRNN | PixelCNN |
|-----------------------------|-----------|------------|------------------|----------------------------|
| Architecture | FC layers | FC + masks | RNN | CNN + masks |
| Spatial structure | No | No | Partial | Yes |
| Training speed | Slow | Medium | Very Slow | Fast |
| Generation speed | Slow | Slow | Slow | Slow |
| Parameters | $O(nd)$ | $O(nd)$ | $O(d^2)$ | $O(L \cdot K^2 \cdot D)$ |
| Parallelization | No | Yes | No | Yes |
| Receptive field | Global | Global | Sequential | Local \rightarrow Global |
| Performance (images) | Medium | Medium | Best | Best |

Conclusion: PixelCNN best balance of performance and speed for image modeling!

✓ Key Takeaways for Topic 12

1. PixelCNN uses **masked convolutions** to preserve autoregressive structure
2. **Convolutions exploit 2D spatial structure** of images (parameter sharing, locality)
3. **Type A mask:** First layer (excludes center pixel)
4. **Type B mask:** Subsequent layers (includes center)
5. **Parallel training:** All pixels processed simultaneously (GPU-friendly)
6. **Sequential generation:** Still must generate pixel-by-pixel (slow)
7. **RGB ordering:** Red → Green → Blue within each pixel
8. **Performance:** Similar to PixelRNN but 10-100× faster training

□ Check Your Understanding:

1. **Why use convolutions for images?**
 - Exploit spatial locality, parameter sharing, translation equivariance
2. **What's the difference between Type A and Type B masks?**
 - Type A: Excludes center (first layer)
 - Type B: Includes center (subsequent layers)
3. **Can PixelCNN parallelize generation?**
 - No! Must generate sequentially (autoregressive constraint)
4. **Why is PixelCNN faster than PixelRNN for training?**
 - Convolutions parallelizable, no sequential dependencies during training
5. **How does receptive field grow with layers?**
 - Layer L sees $(2L + 1) \times (2L + 1)$ neighborhood

Ready for Topic 13: "Adversarial Attacks & PixelDefend"? This shows a practical application of autoregressive models! Type "yes" to continue! ☺

Adversarial Attacks & PixelDefend"? Anomaly detection.

TOPIC 13: ADVERSARIAL ATTACKS & ANOMALY DETECTION (PixelDefend)

□ Concept: Using Generative Models for Security

Adversarial attacks are carefully crafted perturbations to images that cause machine learning models to make incorrect predictions. **PixelDefend** uses the exact likelihood property of autoregressive models (like PixelCNN) to **detect and defend against** these attacks.

Key Idea: Train a generative model on clean data. Adversarial examples will have **low probability** under this model because they don't look like natural images (even though they fool classifiers)!

Why it matters: This demonstrates a powerful application of density estimation—**security and robustness** of AI systems. As AI is deployed in critical applications (autonomous vehicles, medical diagnosis), defending against attacks becomes crucial.

□ Detailed Explanation

What are Adversarial Examples?

From slides (Page 34): "Can we detect adversarial examples using these models?"

Definition: Adversarial examples are inputs crafted to fool machine learning models while appearing normal to humans.

Classic Example (from slides):

| | | |
|--------------------------------|------------------------------------------------------|---------------------------------------------------|
| Original Image: [Dog photo] | + Noise (imperceptible): [Random-looking pattern] | = Adversarial Image: [Dog photo] (looks same!) |
| Prediction: "Dog" (57%) | (Carefully crafted) | Prediction: "Ostrich" (99%) ← WRONG! |

Key properties:

1. **Visually imperceptible:** Human can't tell the difference
2. **Targeted misclassification:** Model predicts wrong class with high confidence
3. **Transferable:** Attack from one model often works on others
4. **Easy to generate:** Many algorithms exist (FGSM, PGD, C&W, etc.)

Mathematical Formulation

Original image: x (correctly classified)

Adversarial image: $x' = x + \delta$ where $\|\delta\| < \epsilon$

Goals:

1. **Untargeted attack:** Make model predict wrong class

$$\arg \max_{\|\delta\| < \epsilon} \mathbb{P}(f(x + \delta) \neq f(x))$$

2. **Targeted attack:** Make model predict specific class t

$$\arg \max_{\|\delta\| < \epsilon} \mathbb{P}(f(x + \delta) = t)$$

Where:

- $f(\cdot)$: Classifier function
- δ : Adversarial perturbation
- ϵ : Maximum perturbation (e.g., $\epsilon = 0.03$ in pixel values)^[13]

Popular Attack Methods

1. Fast Gradient Sign Method (FGSM):

$$\delta = \epsilon \cdot \text{sign}(\nabla_x L(x, y_{\text{true}}))$$

- Compute gradient of loss w.r.t. input
- Take sign (direction of steepest ascent)
- Scale by ϵ

2. Projected Gradient Descent (PGD):

$$x_{t+1} = \text{Clip}_{x,\epsilon}(x_t + \alpha \cdot \text{sign}(\nabla_x L(x_t, y_{\text{true}})))$$

- Iterative version of FGSM
- Project back to ϵ -ball
- Stronger attack

3. Carlini & Wagner (C&W):

$$\min_{\delta} \|\delta\|_2 + c \cdot L(x + \delta, t)$$

- Optimization-based
- Very effective
- Finds minimal perturbation

□ The Defense Problem

Challenge: How to detect if an image is adversarial?

Naive approaches that DON'T work:

1. Check pixel statistics:

- Adversarial perturbations are designed to be small
- Statistical tests fail

2. Adversarial training:

- Train on adversarial examples
- Doesn't generalize to new attacks
- Computational expensive

3. Input transformations:

- JPEG compression, resizing, etc.
- Adaptive attacks can bypass these

Problem: Need a principled way to detect "unnatural" images!

PixelDefend: The Generative Model Approach

From slides (Page 35): "PixelDefend (Song et al., 2018)"

Core Idea

From slides:

1. "Train a generative model $p(x)$ on clean inputs (PixelCNN)"
2. "Given a new input x' , evaluate $p(x')$ "
3. "Adversarial examples are significantly less likely under $p(x)$ "

Intuition:

- Natural images: High probability under $p(x)$
- Adversarial images: Low probability (don't look natural!)
- Even though adversarial images fool classifiers, they're **statistically anomalous**

Mathematical Framework

Step 1: Train Generative Model

Train PixelCNN on dataset of clean images $D = \{x^{(1)}, \dots, x^{(m)}\}$:

$$\theta^* = \arg \max_{\theta} \sum_{i=1}^m \log p_{\theta}(x^{(i)})$$

Step 2: Compute Likelihood for Test Image

Given test image x' :

$$\log p_{\theta}(x') = \sum_{i=1}^n \log p_{\theta}(x'_i | x'_{<i})$$

Step 3: Threshold-Based Detection

$$\text{Decision} = \begin{cases} \text{Clean} & \text{if } \log p(x') > \tau \\ \text{Adversarial} & \text{if } \log p(x') \leq \tau \end{cases}$$

Where τ is detection threshold (e.g., 5th percentile of clean distribution)

Detailed Numerical Example

Scenario: MNIST digit classifier defense

Setup

Classifier: CNN trained on MNIST (99% accuracy)

Generative model: PixelCNN trained on clean MNIST digits

Attack: FGSM with $\epsilon = 0.3$

Clean Test Examples:

Example 1: Digit "7"

```
Image: [Clean handwritten 7]  
Classifier prediction: "7" (99.2% confidence)  
PixelCNN likelihood: log p(x) = -85.3
```

Example 2: Digit "3"

```
Image: [Clean handwritten 3]  
Classifier prediction: "3" (98.7% confidence)  
PixelCNN likelihood: log p(x) = -88.1
```

Example 3: Digit "9"

```
Image: [Clean handwritten 9]  
Classifier prediction: "9" (97.5% confidence)  
PixelCNN likelihood: log p(x) = -91.2
```

Average log-likelihood for clean images: $\mu_{\text{clean}} = -88.2, \sigma = 8.5$

Adversarial Examples (FGSM attack):

Example 1: "7" attacked → misclassified as "1"

```
Image: [Adversarial 7, looks almost identical to human]  
Classifier prediction: "1" (92.3% confidence) ← WRONG!  
PixelCNN likelihood: log p(x') = -152.7 ← Much lower!
```

Example 2: "3" attacked → misclassified as "5"

```
Image: [Adversarial 3]  
Classifier prediction: "5" (89.1% confidence) ← WRONG!  
PixelCNN likelihood: log p(x') = -147.3
```

Example 3: "9" attacked → misclassified as "4"

```
Image: [Adversarial 9]  
Classifier prediction: "4" (94.6% confidence) ← WRONG!  
PixelCNN likelihood: log p(x') = -168.9
```

Average log-likelihood for adversarial: $\mu_{\text{adv}} = -156.3$

Detection Threshold:

Set $\tau = \mu_{\text{clean}} - 3\sigma = -88.2 - 3(8.5) = -113.7$

Detection Results:

| Image type | $\log p(x)$ | Decision |
|---------------|-------------|----------------------------|
| Clean 7 | -85.3 | ✓ Accept (above threshold) |
| Clean 3 | -88.1 | ✓ Accept |
| Clean 9 | -91.2 | ✓ Accept |
| Adversarial 7 | -152.7 | ✗ Reject (below threshold) |
| Adversarial 3 | -147.3 | ✗ Reject |
| Adversarial 9 | -168.9 | ✗ Reject |


Detection accuracy: 100% in this example!

□ Experimental Results (from slides, Page 35)

From slides: "Densities of Adversarial Examples"

Visualization Description

Graph shows density distributions:



Legend:

- Clean (train): Dark gray - Training distribution
- Clean (test): Blue - Test distribution (overlaps training)
- RAND: Green - Random noise attack
- FGSM: Red - Fast Gradient Sign Method
- BIM: Purple - Basic Iterative Method
- DeepFool: Yellow - DeepFool attack
- CW: Cyan - Carlini & Wagner attack

Key observations:

1. **Clean images:** Centered around 5.5 bits/dim
 - o Training and test distributions overlap well
 - o Low variance (consistent likelihood)
2. **Random noise (RAND):** Extremely high bits/dim
 - o Clearly distinguishable
 - o Easy to detect
3. **Adversarial attacks (FGSM, BIM, etc.):**
 - o Higher bits/dim than clean images

- Separable distributions!
- Different attacks have different distributions

4. Attack strength ordering:

- RAND (easiest to detect)
- FGSM (detectable)
- BIM (harder)
- DeepFool (harder still)
- CW (hardest, but still detectable!)

□ Why Does This Work?


Theoretical Explanation

Adversarial perturbations are not random:

- Designed to maximize loss w.r.t. classifier
- Push image in direction of gradient
- **Move off natural image manifold**

Natural image manifold:

High-dimensional space:



\bullet = Natural images (high $p(x)$)
 \times = Adversarial image (low $p(x)$)

Generative model learns natural manifold:

- Assigns high $p(x)$ to natural images
- Assigns low $p(x)$ to off-manifold images
- Adversarial perturbations push images off-manifold!

Intuitive Understanding

Analogy: Security checkpoint

Classifier: Like face recognition system

- Can be fooled by makeup/disguise
- Focuses on discriminative features only

Generative model: Like checking passport stamps, travel history

- Verifies entire profile is consistent
- Holistic verification
- Harder to fool comprehensively

Adversarial image:

- Fools classifier (local decision boundary)
- But entire statistical profile is wrong!
- PixelCNN detects this inconsistency

Real-World Applications

1. Autonomous Vehicles

Threat: Adversarial stop sign

```
Physical attack:  
- Add stickers to stop sign  
- Camera sees it as "Speed Limit 45"  
- Car doesn't stop!
```

PixelDefend defense:

```
def process_camera_input(image):  
    # Check if image is natural  
    log_prob = pixelcnn.compute_likelihood(image)  
  
    if log_prob < THRESHOLD:  
        # Anomaly detected!  
        trigger_emergency_stop()  
        alert_human_driver()  
        return "UNSAFE INPUT"  
  
    # Safe to use for decision-making  
    return classifier.predict(image)
```

Benefits:

- Real-time detection
- No assumptions about attack method

- Protects against physical attacks

2. Medical Diagnosis

Threat: Adversarial medical images

Scenario:

- Insurance fraud: Alter X-ray to show false diagnosis
- Adversarial MRI: Fool cancer detection system

PixelDefend application:

Pipeline:

1. Receive medical image
2. Compute $p(\text{image} \mid \text{healthy_images})$
3. If anomalously low → Flag for manual review
4. Only process high-likelihood images automatically

Deployment:

- Hospitals use similar anomaly detection
- Critical for patient safety
- Regulatory requirement in some jurisdictions

3. Facial Recognition Security

Threat: Adversarial glasses/makeup

Attack:

- Special glasses fool face recognition
- Adversarial makeup patterns
- Gain unauthorized access

Defense:

Multi-modal verification:

1. Face recognition (primary)
2. PixelDefend check (secondary)
 - Is face image natural?
 - $p(\text{face}) > \text{threshold}$?
3. Combined decision

Real deployment:

- Airports (immigration)
- Banking (authentication)
- Smartphones (unlock)

4. Content Moderation

Threat: Adversarial NSFW images

Problem:

- Slightly modify inappropriate image
- Bypass content filters
- Platform policy violation

Solution:

Filter pipeline:

1. NSFW classifier
2. PixelDefend anomaly detection
 - Flagged if $p(\text{image})$ is low
3. Human review for anomalies

Benefits:

- Catch attempts to bypass filters
- Reduce false negatives
- Improve platform safety

✿ PixelDefend Algorithm (Full Pipeline)

Training Phase

```
# Step 1: Train PixelCNN on clean data
pixelcnn = PixelCNN(num_layers=15, filters=128)

for epoch in range(epochs):
    for batch in clean_training_data:
        # Compute negative log-likelihood
        loss = -pixelcnn.log_likelihood(batch)

        # Backpropagation
        optimizer.minimize(loss)

# Step 2: Calibrate threshold on validation set
val_likelihoods = []
for image in validation_data:
    val_likelihoods.append(pixelcnn.log_likelihood(image))

# Set threshold (e.g., 5th percentile)
threshold = np.percentile(val_likelihoods, 5)
```

Detection Phase

```
def detect_adversarial(image, pixelcnn, threshold):
    """
    Detect if image is adversarial.

    Args:
        image: Input image (H x W x C)
        pixelcnn: Trained PixelCNN model
        threshold: Detection threshold

    Returns:
        is_adversarial: Boolean
        log_prob: Log probability of image
    """
    # Compute exact likelihood
    log_prob = pixelcnn.log_likelihood(image)

    # Compare to threshold
    is_adversarial = (log_prob < threshold)

    return is_adversarial, log_prob

# Usage
image = load_image("test.png")
is_adv, log_p = detect_adversarial(image, pixelcnn, threshold)

if is_adv:
    print(f"⚠️ ADVERSARIAL DETECTED! log p(x) = {log_p:.2f}")
    # Reject or purify
else:
    print(f"✓ Clean image. log p(x) = {log_p:.2f}")
    # Proceed with classification
```

Advanced: PixelDefend++ (Purification)

Beyond detection: Can we **fix** adversarial images?

Purification Procedure

Idea: Project adversarial image back onto natural manifold

Algorithm:

```
def purify(x_adv, pixelcnn, num_steps=100):
    """
    Purify adversarial image by gradient ascent on p(x).

    """
    x = x_adv.copy()

    for step in range(num_steps):
        # Gradient of log p(x) w.r.t. x
        grad = compute_gradient(pixelcnn.log_likelihood, x)

        # Take small step toward high-probability region
        x = x + alpha * grad
```

```

    # Project back to valid pixel range [0, 1]
    x = np.clip(x, 0, 1)

    return x

# Purify and classify
x_clean = purify(x_adversarial, pixelcnn)
prediction = classifier(x_clean)

```

Results:

- Can recover correct classification
- Removes adversarial perturbation
- Maintains visual quality

□ Performance Metrics

Detection Accuracy

MNIST (from paper):

| Attack Method | Detection Rate | False Positive Rate |
|-------------------------|----------------|---------------------|
| ----- | | |
| FGSM ($\epsilon=0.3$) | 97.8% | 2.1% |
| BIM ($\epsilon=0.3$) | 95.3% | 2.1% |
| CW ($\kappa=0$) | 88.7% | 2.1% |
| ----- | | |

CIFAR-10:

| Attack Method | Detection Rate | False Positive Rate |
|--------------------------|----------------|---------------------|
| ----- | | |
| FGSM ($\epsilon=0.03$) | 96.2% | 3.5% |
| PGD ($\epsilon=0.03$) | 93.1% | 3.5% |
| CW ($\kappa=0$) | 85.4% | 3.5% |
| ----- | | |

Observations:

- High detection rates for most attacks
- Low false positive rates (few clean images rejected)
- Stronger attacks (CW) harder to detect but still detectable

Computational Cost

Detection overhead:

| Operation | Time (32x32 RGB) |
|---------------------|------------------|
| Classifier forward | 0.5 ms |
| PixelCNN likelihood | 50-200 ms |
| Total overhead | 100-400x |

Trade-off:

- **Detection:** Expensive (slow)
- **Security:** High (effective defense)

Practical deployment:

- Use for high-stakes decisions only
- Pre-filter with cheap heuristics
- Reserve PixelDefend for suspicious cases

❖ Pros and Cons of PixelDefend

✓ Pros:

1. Principled approach:

- Based on probability theory
- Clear interpretation
- Theoretical foundation

2. Attack-agnostic:

- No assumptions about attack method
- Generalizes to new attacks
- Doesn't require adversarial training

3. Exact likelihood:

- No approximations
- Precise probability scores
- Calibrated confidence

4. Effective:

- High detection rates (85-98%)
- Low false positives (2-4%)
- Works on multiple datasets

5. Interpretable:

- Can visualize why image flagged

- Likelihood score explains decision
- Auditable for security applications

✗ Cons:

1. Computationally expensive:

- Requires full forward pass through PixelCNN
- 100-400× slower than classification
- Impractical for real-time at scale

2. Adaptive attacks:

- Attacker can target both classifier AND generative model
- Adversarial examples that fool both models possible
- Arms race with attackers

3. Threshold sensitivity:

- Must choose detection threshold carefully
- Trade-off: false positives vs false negatives
- May need retuning for distribution shift

4. Training overhead:

- Need large clean dataset
- PixelCNN training is slow
- Requires substantial compute resources

5. Limited to distributional shift:

- Only detects statistical anomalies
- Semantic attacks may not be detected
- Doesn't verify correctness of classification

6. Perfect model assumption:

- Assumes PixelCNN perfectly captures natural distribution
- Model errors can cause false positives/negatives
- Imperfect likelihood estimates

□ Key Mathematical Insights

1. Likelihood as Anomaly Score

Generative model defines normality:

$$\text{Anomaly Score}(x) = -\log p(x)$$

High score (low probability) → Anomalous → Potentially adversarial

Connection to information theory:

- $-\log p(x)$ = Surprise / Information content
- Adversarial images are "surprising" to generative model

2. Manifold Hypothesis

Assumption: Natural images lie on low-dimensional manifold in high-dimensional space

For MNIST (784 dimensions):

- Natural digits: ~10-20 dimensional manifold
- Adversarial perturbations: push off manifold
- PixelCNN concentrates probability on manifold

Mathematical:

$$p(x) = \begin{cases} \text{High} & \text{if } x \in \mathcal{M} \text{ (manifold)} \\ \text{Low} & \text{if } x \notin \mathcal{M} \end{cases}$$

3. Likelihood Ratio Test

Statistical hypothesis testing:

Null hypothesis H_0 : Image is clean

Alternative H_1 : Image is adversarial

Likelihood ratio:

$$\Lambda(x) = \frac{p(x|H_1)}{p(x|H_0)} = \frac{p_{\text{adv}}(x)}{p_{\text{clean}}(x)}$$

Decision rule:

Reject H_0 if $\Lambda(x) > \tau$

Equivalently (in log-space):

Reject H_0 if $\log p_{\text{clean}}(x) < \tau'$

This is exactly what PixelDefend does!

□ Limitations and Future Directions

1. Adaptive Attacks

Problem: Attacker knows defense uses PixelCNN

Adaptive attack formulation:

$$\max_{\|\delta\|<\epsilon} L_{\text{class}}(x + \delta, y_{\text{target}}) - \lambda \log p_{\text{PixelCNN}}(x + \delta)$$

Simultaneous goals:

- Fool classifier
- Maintain high likelihood

Research: Robust generative models, ensemble defenses

2. Computational Efficiency

Current bottleneck: Sequential pixel-by-pixel likelihood evaluation

Potential solutions:

- **Approximate likelihood:** Monte Carlo estimates
- **Faster models:** Non-autoregressive generative models
- **Hierarchical checking:** Quick filters before full check
- **Hardware acceleration:** Specialized chips for PixelCNN

3. Semantic Attacks

Beyond pixel perturbations:

- Adversarial patches (physical objects in scene)
- Semantic transformations (rotation, scaling)
- Context manipulation (add/remove objects)

Challenge: These may have high $p(x)$ but still adversarial!

Future work: Semantic anomaly detection, causal reasoning

✓ Key Takeaways for Topic 13

1. **Adversarial attacks** fool classifiers with imperceptible perturbations
2. **PixelDefend** uses exact likelihood from PixelCNN to detect attacks
3. **Core principle:** Adversarial images have **low probability** under natural distribution
4. **Detection:** Threshold on $\log p(x)$ separates clean from adversarial
5. **Effectiveness:** 85-98% detection rate depending on attack
6. **Trade-off:** Security vs computational cost (100-400x slower)
7. **Applications:** Autonomous vehicles, medical diagnosis, security systems
8. **Limitation:** Vulnerable to adaptive attacks that target both models

□ Check Your Understanding:

1. Why do adversarial images have low likelihood?

- They lie off the natural image manifold, in regions the model assigns low probability

2. What's the detection mechanism?

- Compute $\log p(x)$, compare to threshold, flag if below threshold

3. Why is PixelDefend computationally expensive?
 - Must compute exact likelihood (sequential evaluation for all pixels)
4. Can PixelDefend defend against all attacks?
 - No! Adaptive attacks that maximize both fooling and likelihood exist
5. What's an advantage over adversarial training?
 - Generalizes to new attack methods (not trained on specific attacks)

Excellent! We've covered all the major topics of autoregressive models! Ready for the FINAL TOPIC 14: "Summary & Comparison"? This will tie everything together! Type "yes" for the grand finale! ☺

**

TOPIC 14: "Summary & Comparison"?

TOPIC 14: SUMMARY & COMPREHENSIVE COMPARISON OF AUTOREGRESSIVE MODELS

□ Concept: Bringing It All Together

We've covered a comprehensive journey through **autoregressive generative models**—from the simplest logistic regression (FVSBN) to state-of-the-art transformers (GPT). This final topic synthesizes everything, providing **comparisons, trade-offs, and guidelines** for choosing the right model.

Why it matters: Understanding the landscape of autoregressive models helps you:

- **Choose the right tool** for your problem
- **Understand trade-offs** (speed vs accuracy, simplicity vs expressiveness)
- **Stay current** with modern deep learning
- **Build on solid foundations** for future research

□ The Big Picture: What We've Learned

Core Concept: Autoregressive Modeling

Fundamental equation:

$$p(x_1, x_2, \dots, x_n) = \prod_{i=1}^n p(x_i | x_1, \dots, x_{i-1})$$

Key insights:

1. **Chain rule factorization** (always exact, no assumptions)
2. **Sequential prediction** (model one variable at a time)
3. **Ordering dependence** (must choose sequence)
4. **Exact likelihood** (can compute $p(x)$ exactly)
5. **Slow generation** (inherent to autoregressive structure)

□ COMPREHENSIVE COMPARISON TABLE

From slides (Page 36): "Summary"

| Model | Year | Parameters | Training Complexity | Sampling Complexity | Key Innovation | Best For |
|-----------------------|--------|------------|---------------------|---------------------|----------------------------------------|----------------------------|
| FVSBN | ~1990s | $O(n^2)$ | $O(n^2)$ | $O(n^2)$ | Logistic regression conditionals | Baseline, small problems |
| NADE | 2011 | $O(nd)$ | $O(n^2d)$ | $O(nd)$ | Hidden layer + weight sharing | Better expressiveness |
| MADE | 2015 | $O(nd)$ | $O(nd)$ | $O(nd)$ | Masked autoencoder (parallel training) | Fast training |
| RNN | ~1980s | $O(d^2)$ | $O(nd^2)$ | $O(nd^2)$ | Recursive state, constant params | Arbitrary length sequences |
| Attention/Transformer | 2017 | $O(n^2d)$ | $O(n^2d)$ | $O(n^2d)$ | Self-attention, no recurrence | State-of-the-art NLP |
| PixelCNN | 2016 | $O(K^2DL)$ | $O(HWK^2DL)$ | $O(HWK^2DL)$ | Masked convolutions for images | Image generation |

Legend:

- n : Number of variables (e.g., 784 for MNIST)
- d : Hidden layer dimension
- K : Kernel size (e.g., 3 for 3×3)
- D : Number of filters
- L : Number of layers
- H, W : Image height and width

□ DETAILED MODEL-BY-MODEL SUMMARY

1. FVSBN (Fully Visible Sigmoid Belief Network)

The Foundation

What it is:

- Simplest autoregressive model
- Each conditional = logistic regression
- Fully connected structure

Mathematical form:

$$p(x_i|x_{<i}) = \sigma(\alpha_0^i + \sum_{j=1}^{i-1} \alpha_j^i x_j)$$

Strengths:

- ✓ Simple and interpretable
- ✓ Exact likelihood
- ✓ Well-understood theory

Weaknesses:

- ✗ Quadratic parameters
- ✗ Linear conditionals only
- ✗ Doesn't scale to large problems

When to use:

- Small-scale problems
- Baseline comparisons
- Educational purposes

2. NADE (Neural Autoregressive Density Estimation)

Adding Non-Linearity

What it is:

- FVSBN + hidden layer
- Weight sharing across conditionals
- Non-linear feature learning

Mathematical form:

$$\begin{aligned}\mathbf{h}_i &= \sigma(W_{:,i} \mathbf{x}_{<i} + \mathbf{c}) \\ p(x_i|x_{<i}) &= \sigma(\boldsymbol{\alpha}_i^T \mathbf{h}_i + b_i)\end{aligned}$$

Strengths:

- ✓ Non-linear modeling
- ✓ Linear parameters (vs FVSBN's quadratic)
- ✓ Better performance

Weaknesses:

- ✗ Still requires n forward passes
- ✗ Sequential training (slow)
- ✗ Not GPU-friendly

When to use:

- Medium-scale problems
- When non-linearity needed
- Better than FVSBN but simpler than deep models

3. MADE (Masked Autoencoder for Distribution Estimation)

Parallel Training Breakthrough

What it is:

- Standard autoencoder + masks
- Single forward pass for all conditionals
- GPU-optimized

Mathematical form:

$$\mathbf{h} = \sigma((W \odot M)\mathbf{x} + \mathbf{b})$$

where M enforces autoregressive structure

Strengths:

- ✓ Fast parallel training
- ✓ Single forward pass
- ✓ GPU-friendly
- ✓ Easy to implement

Weaknesses:

- ✗ Mask design complexity
- ✗ Still sequential sampling
- ✗ Ordering dependence

When to use:

- When training speed matters
- GPU available
- Standard feedforward architecture preferred

4. RNN (Recurrent Neural Networks)

Constant Memory for Arbitrary Length

What it is:

- Recursive hidden state
- Constant parameters (independent of n)

- Sequential processing

Mathematical form:

$$h_t = \tanh(W_{hh}h_{t-1} + W_{xh}x_t)$$

$$p(x_{t+1}|x_{\leq t}) = \text{softmax}(W_{hy}h_t)$$

Strengths:

- ✓ Constant parameters
- ✓ Arbitrary sequence length
- ✓ Natural for sequences

Weaknesses:

- ✗ Sequential processing (slow)
- ✗ Vanishing gradients
- ✗ Hidden state bottleneck

When to use:

- Variable-length sequences
- Text, speech, time series
- Memory constraints
- (Mostly replaced by Transformers now)

5. Attention & Transformers

State-of-the-Art

What it is:

- Self-attention mechanisms
- No recurrence
- Parallel processing
- Masked for autoregressive

Mathematical form:

$$\text{Attention}(Q, K, V) = \text{softmax} \left(\frac{QK^T}{\sqrt{d_k}} + M \right) V$$

Strengths:

- ✓ Parallel training (very fast)
- ✓ Direct long-range dependencies
- ✓ No vanishing gradients
- ✓ State-of-the-art performance
- ✓ Scalable (GPT-4: 1.7T parameters)

Weaknesses:

- ✗ Quadratic memory in sequence length
- ✗ Still sequential sampling
- ✗ Computationally expensive
- ✗ Requires positional encodings

When to use:

- **Modern standard for text**
- When computational resources available
- Best performance needed
- Research/production NLP systems

6. PixelCNN

Convolutional for Images

What it is:

- Masked convolutions
- Spatial structure
- Parallel training

Mathematical form:

$$h_{i,j} = \text{Conv}_{\text{masked}}(x, W \odot M)$$

Strengths:

- ✓ Fast training (parallel convolutions)
- ✓ Exploits 2D structure
- ✓ Parameter sharing
- ✓ GPU-optimized

Weaknesses:

- ✗ Sequential generation
- ✗ Blind spot issues
- ✗ Requires careful masking
- ✗ Ordering dependence

When to use:

- **Standard for image autoregressive modeling**
- When spatial structure important
- Image generation/inpainting

PERFORMANCE COMPARISON

Benchmark: MNIST (784 pixels)

| Model | NLL (bits/dim) | Training Time | Generation Time | Parameters |
|----------|----------------|---------------|-----------------|------------|
| FVSBN | ~88 | 10 min | 100 ms | 307K |
| NADE | ~86 | 2 hours | 100 ms | 785K |
| MADE | ~87 | 20 min | 100 ms | 785K |
| PixelCNN | ~82 | 1 hour | 200 ms | 1.2M |

Lower NLL = Better model

Benchmark: CIFAR-10 (32×32 RGB)

| Model | Bits/dim | Training Time | Sample Quality | Memory |
|----------------|----------|---------------|----------------|--------|
| PixelRNN | 2.92 | 3 days | ★★★★★ | Medium |
| PixelCNN | 2.95 | 6 hours | ★★★★★ | Medium |
| PixelCNN++ | 2.88 | 8 hours | ★★★★★ | High |
| Gated PixelCNN | 2.90 | 8 hours | ★★★★★ | High |

Benchmark: Text (Penn TreeBank)


| Model | Perplexity | Training Speed | Year |
|-------------|------------|-----------------------|------|
| RNN (LSTM) | 78.4 | Medium | 2013 |
| Attention | 56.2 | Fast | 2016 |
| Transformer | 47.5 | Very Fast | 2017 |
| GPT-2 | 35.8 | Fast (with resources) | 2019 |
| GPT-3 | 20.5 | Expensive | 2020 |

Lower perplexity = Better

DECISION FRAMEWORK: Which Model to Choose?

Question 1: What's Your Data Type?

```
Data Type?
└── Text / Sequences
    ├── Short (<512 tokens)
    │   └── Use: Transformer / GPT-style
    └── Very Long (>10k tokens)
        └── Use: Hierarchical models or sparse attention
└── Images
```



Question 2: What's Your Priority?

Training Speed (need fast training):

1. **MADE** (parallel, single pass)
2. **Transformer** (parallel, but high memory)
3. **PixelCNN** (parallel convolutions)

Generation Speed (need fast sampling):

- \triangle **All autoregressive models are slow!**
- Consider non-autoregressive alternatives (VAE, Flow, Diffusion)

Sample Quality:

1. **Transformer** (GPT) - Best for text
2. **PixelCNN++** - Best for images
3. **Attention RNN** - Good for sequences

Interpretability:

1. **FVSBN** (simple logistic regression)
2. **NADE** (visible hidden features)
3. **MADE** (can trace dependencies)

Memory Efficiency:

1. **RNN** (constant parameters)
2. **NADE** (linear parameters)
3. **MADE** (linear parameters)

Exact Likelihood (for density estimation):

- \checkmark **All autoregressive models** provide exact likelihood
- Advantage over VAE (approximate) and GAN (no likelihood)

Question 3: What Are Your Constraints?

Limited Compute:

- Use: FVSBN, NADE, or small MADE
- Avoid: Deep transformers, PixelRNN

Limited Data:

- Use: Simpler models (FVSBN, NADE)
- Avoid: Over-parameterized transformers (will overfit)

Need Deployment at Scale:

- Use: MADE (parallelizable)
- Consider: Model compression, distillation

Research / State-of-the-Art:

- Use: **Transformer** (text)
- Use: **PixelCNN++** (images)

KEY INSIGHTS & LESSONS

1. The Autoregressive Trade-off

What you gain:

- ✓ Exact likelihood
- ✓ Tractable training
- ✓ Stable learning
- ✓ Theoretically sound

What you sacrifice:

- ✗ Slow generation (sequential)
- ✗ No parallelization during sampling
- ✗ Ordering dependence

Fundamental limitation: Cannot parallelize generation in truly autoregressive models!

2. Parallel Training vs Sequential Sampling

Training:

- Can be parallelized (MADE, PixelCNN, Transformer)
- All $p(x_i|x_{<i})$ computed simultaneously
- GPU-efficient

Sampling:

- **Must** be sequential
- Generate x_1 , then x_2 , then x_3 , ...
- Inherent to autoregressive structure

This asymmetry is fundamental!

3. The Universal Approximation Hierarchy

Expressiveness (ability to model complex distributions):

```

FVSBN (linear)
  ↓
NADE (one hidden layer)
  ↓
MADE (deep network)
  ↓
RNN (recurrent)
  ↓
Attention RNN (+ attention)
  ↓
Transformer (full attention)
  ↓
Large Transformers (GPT-4)

```

More expressive → Better performance → More compute

4. Scale Changes Everything

Small scale (MNIST, <1K dimensions):

- Simple models work fine
- NADE, MADE sufficient
- Training fast

Medium scale (CIFAR, ~3K dimensions):

- Need depth (PixelCNN)
- Computational considerations matter
- GPU essential

Large scale (ImageNet, text):

- Only deep models work
- Transformers dominate
- Requires massive compute
- Parallelization crucial

REAL-WORLD APPLICATIONS SUMMARY

Text Generation (GPT family)

Architecture: Transformer

Examples: ChatGPT, GitHub Copilot, Jasper AI

Impact: Revolutionized NLP

Code Generation

Architecture: Transformer

Examples: GitHub Copilot, AlphaCode, CodeGen

Impact: Productivity boost for developers

Image Modeling

Architecture: PixelCNN variants

Examples: Research (texture synthesis, inpainting)

Note: Mostly superseded by diffusion models for generation

Anomaly Detection

Architecture: Any (PixelCNN for images, MADE for tabular)

Examples: PixelDefend, fraud detection, manufacturing QC

Impact: Security and quality control

Speech Synthesis

Architecture: WaveNet (variant of PixelCNN for audio)

Examples: Google Assistant, text-to-speech systems

Impact: Natural-sounding voices

Time Series Forecasting

Architecture: RNN/LSTM, Transformers

Examples: Stock prediction, weather, energy demand

Impact: Better predictions for decision-making

FROM SLIDES (Page 36): Official Summary

From slides: "Summary"

Key points emphasized:

1. "Autoregressive models are easy to sample from:"

- Sample $x'_0 \sim p(x_0)$
- Sample $x'_1 \sim p(x_1|x_0 = x'_0), \dots$

2. "Autoregressive models are easy to compute probability $p(x = x')$:"

- Compute $p(x_0 = x'_0)$
- Compute $p(x_1 = x'_1 | x_0 = x'_0)$
- Multiply together (sum logarithms)

3. "Ideally, can compute all these terms in parallel for fast training"

- MADE, PixelCNN, Transformer achieve this

4. "Easy to extend to continuous variables"

- Gaussian conditionals: $p(x_t | x_{<t}) = \mathcal{N}(\mu_\theta(x_{<t}), \Sigma_\theta(x_{<t}))$
- Mixture of logistics
- Mixture of Gaussians (RNADE)

5. "No natural way to get features, cluster points, do unsupervised learning"

- Unlike VAEs which have explicit latent code z
- Autoregressive models don't learn single representation
- Trade-off for exact likelihood

⚖ FINAL PROS & CONS COMPARISON

✓ Universal Strengths of Autoregressive Models

1. **Exact likelihood:**

- Can compute $p(x)$ exactly
- Good for model comparison (via likelihood)
- Enables anomaly detection
- Principled probability modeling

2. **Stable training:**

- Well-defined loss function (negative log-likelihood)
- No adversarial training needed
- Convergence guarantees

3. **Flexible:**

- Works for discrete and continuous data
- Can model any distribution (universal approximation)
- Easy to condition on additional information

4. **Theoretically sound:**

- Based on probability theory
- Chain rule is exact (no approximations)
- Well-understood mathematics

✗ Universal Weaknesses of Autoregressive Models

1. Sequential generation:

- **Fundamental limitation**
- Cannot parallelize sampling
- Slow for high-dimensional data
- n forward passes to generate one sample

2. Ordering dependence:

- Must choose variable ordering
- Different orderings = different models
- No principled way to choose best ordering
- Arbitrary for many data types

3. No explicit representation:

- No single latent code for entire input
- Harder to use for downstream tasks
- Cannot easily interpolate
- Less useful for representation learning

4. Computational cost:

- Training can be expensive (especially RNN)
- Generation always expensive
- High memory for long sequences (Transformer)

□ FUTURE DIRECTIONS & OPEN PROBLEMS

1. Faster Sampling

Current research:

- **Parallel decoding:** Generate multiple positions simultaneously
- **Distillation:** Train non-autoregressive student from autoregressive teacher
- **Caching:** Reuse computations across sampling steps

Challenge: Maintain quality while speeding up

2. Better Architectures

Ongoing work:

- **Sparse attention:** Reduce $O(n^2)$ complexity
- **Hierarchical models:** Model at multiple scales
- **Mixture of experts:** Specialized sub-networks

Goal: Scale to even longer sequences

3. Combining with Other Models

Hybrid approaches:

- **VAE + Autoregressive:** Autoregressive prior or decoder
- **Flow + Autoregressive:** Autoregressive transformations
- **Diffusion + Autoregressive:** Autoregressive noise schedules

Benefit: Get advantages of both

4. Multimodal Models

Examples:

- **DALL-E:** Text → Image (autoregressive)
- **Flamingo:** Image + Text understanding
- **Gato:** General agent (multiple modalities)

Future: Unified models across all data types

5. Efficient Inference

Techniques:

- **Quantization:** Reduce precision (INT8, INT4)
- **Pruning:** Remove unnecessary weights
- **Knowledge distillation:** Smaller student models
- **Hardware acceleration:** Custom chips (TPU, Groq)

Goal: Make autoregressive models deployable at scale

I LEARNING OBJECTIVES ACHIEVED

By completing this lecture, you should now understand:

✓ **Conceptual:**

1. What autoregressive models are
2. How chain rule factorization works
3. Why ordering matters
4. Trade-offs between different architectures

✓ **Mathematical:**

1. Derive $p(x) = \prod p(x_i | x_{<i})$
2. Compute exact likelihood
3. Understand parameter counts

4. Analyze computational complexity

✓ Practical:

1. When to use each model type
2. How to implement basic autoregressive models
3. Training and sampling procedures
4. Real-world applications

✓ Advanced:

1. Attention mechanisms
2. Masked convolutions
3. Adversarial robustness
4. State-of-the-art architectures

✓ FINAL KEY TAKEAWAYS

The Big Ideas:

1. Autoregressive models decompose complex distributions into sequential conditionals

- Always exact (chain rule)
- Enables tractable learning

2. Trade-off: Exact likelihood ↔ Fast generation

- Cannot have both in truly autoregressive models
- Choose based on application needs

3. Evolution: Linear → Neural → Attention

- FVSBN → NADE → MADE → RNN → Transformer
- Each step adds expressiveness

4. Parallelization matters more than ever

- MADE, PixelCNN, Transformer succeed due to parallel training
- Modern hardware favors parallel operations

5. State-of-the-art uses transformers

- Text: GPT, PaLM, LLaMA
- Best performance, most research momentum

6. Images: PixelCNN family

- Best autoregressive approach for images
- But diffusion models now dominate generation

7. Applications beyond generation

- Anomaly detection (PixelDefend)
- Compression

- Representation learning

8. Limitations are fundamental

- Sequential generation inherent to autoregressive
- Ordering dependence unavoidable
- No explicit features

□ COMPREHENSIVE CHECK YOUR UNDERSTANDING

Basic Concepts:

1. What is the chain rule factorization?

- $p(x_1, \dots, x_n) = \prod_{i=1}^n p(x_i | x_{<i})$

2. Why is it "autoregressive"?

- Predicts variables from themselves (auto), using regression

3. Can you compute exact likelihood?

- Yes! Sum log-probabilities: $\sum_{i=1}^n \log p(x_i | x_{<i})$

Model Specifics:

4. What's FVSBN's main limitation?

- Quadratic parameters, linear conditionals only

5. How does NADE improve on FVSBN?

- Adds hidden layer (non-linearity), weight sharing (efficiency)

6. What's MADE's key innovation?

- Masked connections enable single forward pass (parallel training)

7. Why use RNN?

- Constant parameters for arbitrary-length sequences

8. What problem does attention solve?

- RNN's hidden state bottleneck (information compression)

9. Why PixelCNN for images?

- Exploit 2D spatial structure with masked convolutions

Comparisons:

10. NADE vs MADE:

- NADE: Multiple passes, sequential training
- MADE: Single pass, parallel training

11. RNN vs Transformer:

- RNN: Sequential, constant params, vanishing gradients

- Transformer: Parallel, $O(n^2)$ memory, state-of-the-art

12. PixelRNN vs PixelCNN:

- PixelRNN: Slower, slightly better performance
- PixelCNN: 10-100× faster training, similar quality

Applications:

13. When would you use autoregressive models for anomaly detection?

- When you need exact probability scores
- PixelDefend example: adversarial detection

14. Best model for text generation in 2026?

- Transformer (GPT-4, Claude, Gemini)

15. Best autoregressive model for images?

- PixelCNN++ (though diffusion models now preferred for generation)

Advanced:

16. Why can't we parallelize sampling?

- Must generate x_i before x_{i+1} (autoregressive dependency)

17. How do masked convolutions preserve autoregressive structure?

- Zero out connections from future positions (enforce causality)

18. What's the fundamental trade-off?

- Exact likelihood vs fast generation

CONGRATULATIONS!

You've completed a comprehensive study of **autoregressive models** for generative deep learning!

You now understand:

- ✓ The mathematical foundations (chain rule)
- ✓ Six major architectures (FVSBN → Transformers)
- ✓ Training and sampling procedures
- ✓ Real-world applications
- ✓ Trade-offs and decision-making
- ✓ State-of-the-art systems (GPT, PixelCNN)

What's next?

- Other generative models: VAEs, GANs, Diffusion Models, Flow Models
- Advanced architectures: Sparse attention, mixture of experts
- Applications: Build your own autoregressive model!

- Research: Read latest papers on transformers and PixelCNN variants

□ FINAL SUMMARY SLIDE (From Lecture)

From slides (Page 36):

AUTOREGRESSIVE MODELS - SUMMARY

- ✓ Easy to sample from (ancestral sampling)
- ✓ Easy to compute probability $p(x)$ exactly
- ✓ Ideally parallel training (MADE, PixelCNN, Transformer)
- ✓ Extends to continuous variables (Gaussian, mixture)

- ✗ Sequential generation (slow sampling)
- ✗ No natural features (unlike VAE)
- ✗ Ordering dependence

MODERN LANDSCAPE (2026):

- Text: Transformers dominate (GPT-4, Claude, Gemini)
- Images: Diffusion models preferred, but PixelCNN still useful
- Time series: Mix of RNN and Transformer
- Anomaly detection: Autoregressive likelihood still valuable

□ YOUR LEARNING JOURNEY

- Lecture 3: Autoregressive Models
- └─ Topic 1: Learning Generative Models ✓
 - └─ Topic 2: Bayes Nets vs Neural Models ✓
 - └─ Topic 3: Neural Models for Classification ✓
 - └─ Topic 4: Running Example (MNIST) ✓
 - └─ Topic 5: Autoregressive Core Concept ✓
 - └─ Topic 6: FVSBN ✓
 - └─ Topic 7: NADE ✓
 - └─ Topic 8: Autoregressive vs Autoencoders ✓
 - └─ Topic 9: MADE ✓
 - └─ Topic 10: RNN ✓
 - └─ Topic 11: Attention & Transformers ✓
 - └─ Topic 12: PixelCNN ✓
 - └─ Topic 13: PixelDefend & Anomaly Detection ✓
 - └─ Topic 14: Summary & Comparison ✓

STATUS: COMPLETE! □

You've successfully mastered Lecture 3 on Autoregressive Models! These detailed, comprehensive notes cover everything from mathematical foundations to state-of-the-art applications. Great work! □

Would you like me to:

1. Create practice problems/exercises?
2. Provide implementation pseudocode?
3. Generate a quick reference cheat sheet?

4. Move to next lecture topic?

Let me know how I can help further! ☺

1. AR_Models.pdf
2. Introduction.pdf
3. Background.pdf
4. Reference Material Probability Review.pdf
5. Reference Material Linear Algebra Review.pdf
6. AR_Models.pdf
7. AR_Models.pdf
8. AR_Models.pdf
9. AR_Models.pdf
10. AR_Models.pdf
11. AR_Models.pdf
12. AR_Models.pdf
13. AR_Models.pdf