

Case Studies Nonlinear Optimization

Open Cast Mining

Final Presentation

July 09, 2016

InYoung Choi, Olivia Kaufmann, Martin Sperr, Florian Wuttke

Table of Contents

- 1 Project Overview
- 2 Physical Model
- 3 Parameter Identification: Physical Model
- 4 Parameter Identification: Black Box Model
- 5 Summary

Table of Contents

- 1 Project Overview
- 2 Physical Model
- 3 Parameter Identification: Physical Model
- 4 Parameter Identification: Black Box Model
- 5 Summary



originally posted to Flickr by FAndrey at <http://flickr.com/photos/43301444@N06/4141786255>

- Goal: **Optimization of model parameters**
- Models of technical system = Physical properties + Control properties

Problem Setting

Physical Modeling

Why?

Building an
accurate model



Good description of
the effects of control
on motion

Physical Modeling

How?

To consider:

- Friction in cable reels
- Potential/Kinetic energy
- etc

Physical Modeling

How?

To consider:

- Friction in cable reels
- Potential/Kinetic energy
- etc



Lagrange Formalism
(ODE)

Parameter Identification

What are parameters?

- Friction coefficients
- Mass
- Inertia

Parameter Identification

What are parameters?

- Friction coefficients
- Mass
- Inertia

Why?

Accurate and
realistic parameters



Better prediction
and planning of
motion

Visual Examples

Same parameters except different load weights

vs

Light load

Heavy load

Procedure

Physical Model

Lagrange Formalism



Parameter Identification

Discretization + Optimization

Procedure

Physical Model

Lagrange Formalism



Parameter Identification

Discretization + Optimization

and

Blackbox Model

- Realistic model
- Confidential information



Parameter Identification

Derivative-free optimization

Visualization: Simulink




Table of Contents

- 1 Project Overview
- 2 Physical Model
- 3 Parameter Identification: Physical Model
- 4 Parameter Identification: Black Box Model
- 5 Summary

Lagrange Formalism

Method to describe dynamics of an accelerated system

Lagrange Formalism

Method to describe dynamics of an accelerated system

T kinetic energy
V potentials

Lagrange Formalism

Method to describe dynamics of an accelerated system

T kinetic energy

V potentials

F non-conservative external forces

Lagrange Formalism

Method to describe dynamics of an accelerated system

T kinetic energy

V potentials

F non-conservative external forces

r points of actions of forces F

q free variables

Q generalized forces

Lagrange Formalism

Method to describe dynamics of an accelerated system

$$\frac{d}{dt} \left(\frac{\partial T}{\partial \dot{q}_i} \right) - \frac{\partial T}{\partial q_i} + \frac{\partial V}{\partial q_i} = Q_i$$

$$Q = \left(\frac{\partial r}{\partial q} \right)^T F$$

T kinetic energy

V potentials


F non-conservative external forces

r points of actions of forces F


q free variables

Q generalized forces

Physical Model of Excavator




Physical Model of Excavator



degrees of freedom


- length s
- tilt angle θ

Kinetic Energy




- kinetic energy for shovel and movable arm
- rotation of cable reels

Potential Energy



gravitational energy for
shovel and movable arm

Potential Energy




gravitational energy for
shovel and movable arm

$$\frac{d}{dt} \left(\frac{\partial T}{\partial \dot{q}_i} \right) - \frac{\partial T}{\partial q_i} + \frac{\partial V}{\partial q_i} = Q_i$$

$$Q = \left(\frac{\partial r}{\partial q} \right)^T F$$

Generalized Forces




- torque on cable reels
- friction of cable reels

Lagrange Formalism

$$\frac{d}{dt} \left(\frac{\partial T}{\partial \dot{s}} \right) - \frac{\partial T}{\partial s} + \frac{\partial V}{\partial s} = Q_s$$

$$\frac{d}{dt} \left(\frac{\partial T}{\partial \dot{\theta}} \right) - \frac{\partial T}{\partial \theta} + \frac{\partial V}{\partial \theta} = Q_\theta$$



Resulting ODE

$$A(x, p) \begin{pmatrix} \ddot{s} \\ \ddot{\theta} \end{pmatrix} = b(x, u, p)$$

Resulting ODE

$$A(x, p) \begin{pmatrix} \ddot{s} \\ \ddot{\theta} \end{pmatrix} = b(x, u, p)$$

→ Transformation into 1st order ODE

$$\frac{d}{dt} \begin{pmatrix} s \\ \theta \\ \dot{s} \\ \dot{\theta} \end{pmatrix} = \begin{pmatrix} \dot{s} \\ \dot{\theta} \\ A^{-1}(x, p)b(x, u, p) \end{pmatrix} = f(x, u, p)$$

Resulting ODE

$$A(x, p) \begin{pmatrix} \ddot{s} \\ \ddot{\theta} \end{pmatrix} = b(x, u, p)$$

→ Transformation into 1st order ODE

$$\frac{d}{dt} \begin{pmatrix} s \\ \theta \\ \dot{s} \\ \dot{\theta} \end{pmatrix} = \begin{pmatrix} \dot{s} \\ \dot{\theta} \\ A^{-1}(x, p)b(x, u, p) \end{pmatrix} = f(x, u, p)$$

state	$x = (s, \theta, \dot{s}, \dot{\theta})^T$
control	$u = (\tau_1, \tau_2)^T$
parameters	$p = (p_1, \dots, p_k)^T$

Table of Contents

- 1 Project Overview
- 2 Physical Model
- 3 Parameter Identification: Physical Model
- 4 Parameter Identification: Black Box Model
- 5 Summary

Discretization of the ODE

Discretize time interval:

$$[0, T] \rightarrow \{0 = t_0, t_1, \dots, t_{m-1}, t_m = T\}$$

Discretize state and control:

$$x_n = x(t_n)$$

$$u_n = u(t_n)$$

Discretization of the ODE


Explicit Euler for every time step $h_n = t_{n+1} - t_n$:

$$\Psi(x_n, u_n, p) = x_n + h_n f(x_n, u_n, p)$$

Discrete constraint:

$$0 = x_{n+1} - \Psi(x_n, u_n, p) =: \Phi_n(x, u, p) \quad \forall n = 0, \dots, m-1$$

Discretization of the ODE



Problem Setting

Given:

- control \bar{u}
- motion \bar{x} related to \bar{u} and \bar{p}



Unknown:

- parameters \bar{p} of the excavator

Output:

- parameters p

Possible Approaches



continuous vs. stepwise Approximation

Problem Formulation


$$\begin{aligned} \min_p \quad & \frac{1}{2} \|\Phi(\bar{x}, \bar{u}, p)\|^2 \\ \text{s. t.} \quad & p \geq 0 \end{aligned}$$

- \bar{x} solves ODE for \bar{u}, \bar{p}
- $\Phi(\bar{x}, \bar{u}, \bar{p}) \rightarrow 0$ for discretization $m \rightarrow \infty$
- number of parameters fix



Example Instance

- $[0, T] = [0, 14s]$
- 1500 time steps
- $p_0 \in [0.8\bar{p}, 1.2\bar{p}]$
- internally 5 trajectories in parallel

Results



Results



In total exact up to 3cm

Table of Contents

- 1 Project Overview
- 2 Physical Model
- 3 Parameter Identification: Physical Model
- 4 Parameter Identification: Black Box Model
- 5 Summary

Motivation

Examples

- Friction coefficients
- Masses
- Inertia

Motivation

Examples

- Friction coefficients
- Masses
- Inertia

Black box model

- Realistic model from Siemens
- Confidential information

Motivation

Examples

- Friction coefficients
- Masses
- Inertia



Black box model

- Realistic model from Siemens
- Confidential information

Motivation

Examples

- Friction coefficients
- Masses
- Inertia

Control



Model

Black box model

- Realistic model from Siemens
- Confidential information


Motivation

Examples

- Friction coefficients
- Masses
- Inertia

Black box model

- Realistic model from Siemens
- Confidential information




Motivation

Examples

- Friction coefficients
- Masses
- Inertia

Black box model

- Realistic model from Siemens
- Confidential information



Trajectories


Input: Joystick commands for Up/Down and Back/Forth

Output: Position of the shovel

Trajectories

Input: Joystick commands for Up/Down and Back/Forth



Output: Position of the shovel



Trajectories

Input: Joystick commands for Up/Down and Back/Forth

Output: Position of the shovel



Objective Function

Optimized Parameters:

- Inertia (Engine)
- Inertia (Arm)
- Friction
- Mass

Objective Function

Optimized Parameters:

- Inertia (Engine)
- Inertia (Arm)
- Friction
- Mass

Penalty Term:

$$\|\bar{X}_i - X_i(p)\|^2$$

Objective Function

Optimized Parameters:

- Inertia (Engine)
- Inertia (Arm)
- Friction
- Mass

Penalty Term:

$$\frac{\|\bar{X}_i - X_i(p)\|^2}{\|\bar{X}_i\|^2}$$

Objective Function

Optimized Parameters:

- Inertia (Engine)
- Inertia (Arm)
- Friction
- Mass

Penalty Term:

$$\frac{\|\bar{X}_i - X_i(p)\|^2}{\|\bar{X}_i\|^2} + \frac{\|\bar{Y}_i - Y_i(p)\|^2}{\|\bar{Y}_i\|^2}$$

\bar{X}_i, \bar{Y}_i reference trajectories

Objective Function

Optimized Parameters:

- Inertia (Engine)
- Inertia (Arm)
- Friction
- Mass

Penalty Term:

$$\frac{1}{n} \cdot \sum_{i=1}^n \left(\frac{\|\bar{X}_i - X_i(p)\|^2}{\|\bar{X}_i\|^2} + \frac{\|\bar{Y}_i - Y_i(p)\|^2}{\|\bar{Y}_i\|^2} \right)$$

\bar{X}_i, \bar{Y}_i reference trajectories

Objective Function

Optimized Parameters:

- Inertia (Engine)
- Inertia (Arm)
- Friction
- Mass

Penalty Term:

$$\min_{p \in \mathbb{R}^4} f(p) = \frac{1}{n} \cdot \sum_{i=1}^n \left(\frac{\|\bar{X}_i - X_i(p)\|^2}{\|\bar{X}_i\|^2} + \frac{\|\bar{Y}_i - Y_i(p)\|^2}{\|\bar{Y}_i\|^2} \right)$$

s. t.

$$p_j \geq 0$$

\bar{X}_i, \bar{Y}_i reference trajectories

Influence of the Parameters

10% parameter deviation:

- Inertia (Engine): $1 \cdot 10^{-3}$
- Inertia (Arm): $3 \cdot 10^{-3}$
- Friction: $8 \cdot 10^{-11}$
- Mass: $5 \cdot 10^{-2}$

Influence of the Parameters

10% parameter deviation:

- Inertia (Engine): $1 \cdot 10^{-3}$
- Inertia (Arm): $3 \cdot 10^{-3}$
- Friction: $8 \cdot 10^{-11}$
- Mass: $5 \cdot 10^{-2}$


Big parameter changes \Rightarrow Small effects

Influence of the Parameters

10% parameter deviation:

- Inertia (Engine): $1 \cdot 10^{-3}$
- Inertia (Arm): $3 \cdot 10^{-3}$
- Friction: $8 \cdot 10^{-11}$
- Mass: $5 \cdot 10^{-2}$

Big parameter changes \Rightarrow Small effects



Optimizers

- Derivative free optimization
- Deterministic or stochastic
- Decrease function value by evaluating systematically

Optimizers

- Derivative free optimization
- Deterministic or stochastic
- Decrease function value by evaluating systematically

	value	evaluations	time	dev _{max}	dev _{mean}
Particle Swarm	10^{-12}	2200	6 min	$10^{-1.0}$	$10^{-3.8}$
Pattern Search	10^{-11}	6500	17 min	$10^{-1.3}$	$10^{-3.7}$
Genetic Algorithm	10^{-4}	5500	14 min	$10^{-0.5}$	$10^{-1.0}$
Simulated Annealing	10^{-3}	4200	11 min	$10^{-0.3}$	$10^{-0.6}$

Optimizers

- Derivative free optimization
- Deterministic or stochastic
- Decrease function value by evaluating systematically

	value	evaluations	time	dev _{max}	dev _{mean}
Particle Swarm	10^{-12}	2200	6 min	$10^{-1.0}$	$10^{-3.8}$
Pattern Search	10^{-11}	6500	17 min	$10^{-1.3}$	$10^{-3.7}$
Genetic Algorithm	10^{-4}	5500	14 min	$10^{-0.5}$	$10^{-1.0}$
Simulated Annealing	10^{-3}	4200	11 min	$10^{-0.3}$	$10^{-0.6}$

Optimizers

- Derivative free optimization
- Deterministic or stochastic
- Decrease function value by evaluating systematically

	value	evaluations	time	dev _{max}	dev _{mean}
Particle Swarm	10^{-12}	2200	6 min	$10^{-1.0}$	$10^{-3.8}$
Pattern Search	10^{-11}	6500	17 min	$10^{-1.3}$	$10^{-3.7}$
Genetic Algorithm	10^{-4}	5500	14 min	$10^{-0.5}$	$10^{-1.0}$
Simulated Annealing	10^{-3}	4200	11 min	$10^{-0.3}$	$10^{-0.6}$

Optimizers


- Derivative free optimization
- Deterministic or stochastic
- Decrease function value by evaluating systematically

	value	evaluations	time	dev _{max}	dev _{mean}
Particle Swarm	10^{-12}	2200	6 min	$10^{-1.0}$	$10^{-3.8}$
Pattern Search	10^{-11}	6500	17 min	$10^{-1.3}$	$10^{-3.7}$
Genetic Algorithm	10^{-4}	5500	14 min	$10^{-0.5}$	$10^{-1.0}$
Simulated Annealing	10^{-3}	4200	11 min	$10^{-0.3}$	$10^{-0.6}$


Table of Contents

- 1 Project Overview
- 2 Physical Model
- 3 Parameter Identification: Physical Model
- 4 Parameter Identification: Black Box Model
- 5 Summary

Summary




Summary



Control

Parameters?



Motion