



Extension Elements and Functions Catalog



Extension Elements and Functions Catalog

Note

Before using this information or the product it supports, read the information in “Notices and trademarks” on page 221.

First Edition (January 2009)

This edition applies to the following releases and to all subsequent releases and modifications until otherwise indicated in new editions:

- Version 3, release 7, modification 2 of IBM WebSphere DataPower XML Accelerator XA35
- Version 3, release 7, modification 2 of IBM WebSphere DataPower XML Security Gateway XS40
- Version 3, release 7, modification 2 of IBM WebSphere DataPower XML Integration Appliance XI50
- Version 1, release 0, modification 0 of IBM WebSphere DataPower B2B Appliance XB60
- Version 1, release 0, modification 0 of IBM WebSphere DataPower Low Latency Messaging Appliance XM70

© Copyright International Business Machines Corporation 2004, 2009.

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Preface vii

How this document is organized	vii
Publications	viii
Installation and upgrade documentation	viii
Administration documentation	viii
Development documentation	viii
Reference documentation	ix
Integration documentation	ix
Problem determination documentation	x
Supplemental documentations	x
Namespace declarations	x
Data types	x
Reading syntax statements	xi
Typeface conventions	xi

Chapter 1. Extension elements 1

accept	1
append-request-header	2
append-response-header	2
canonicalize	3
dump-nodes	5
freeze-headers	5
increment-integer	6
parse	7
reject	8
remove-http-request-header	9
remove-http-response-header	9
remove-mime-header	10
send-error	10
serialize	11
set-http-request-header	12
set-http-response-header	13
set-local-variable	14
set-metadata	15
set-mime-header	16
set-request-header	16
set-response-header	17
set-target	18
set-variable	20
sql-execute	21
strip-attachments	29
url-open (generic)	30
url-open (FTP URLs)	39
url-open (ICAP URLs)	41
url-open (IMS Connect)	42
url-open (MQ URLs)	45
url-open (NFS URLs)	48
url-open (SMTP URLs)	49
url-open (SNMP URLs)	50
url-open (SQL URLs)	51
url-open (TCP URLs)	52
url-open (TIBCO EMS URLs)	53
url-open (WebSphere JMS URLs)	55
xreject	57
xset-target	58

Chapter 2. Metadata extension

functions 61

accepting().	61
binary-decode().	62
binary-encode().	62
client-ip-addr().	63
client-ip-port().	63
client-issuer-dn().	63
client-subject-dn().	65
decode().	68
encode().	68
exter-correlator().	69
generate-uuid().	70
get-metadata().	71
http-request-header().	72
http-request-method().	72
http-response-header().	73
http-url().	74
index-of().	74
last-index-of().	75
local-variable().	75
mime-header().	76
mq-queue-depth().	77
original-http-url().	78
original-url().	79
parse().	79
request-header().	80
responding().	81
response-header().	81
schema-validate().	82
soap-call().	83
sql-execute().	85
substring-base64().	86
time-value().	86
transform().	86
url().	87
variable().	88
wsm-agent-append().	89

Chapter 3. Cryptographic extension

functions 93

aaa-derive-context-key().	93
aaa-get-context-info().	94
aaa-new-security-context().	95
aaa-set-context-info().	96
auth-info().	97
base64-cert().	99
c14n-hash().	100
c14n-hash-attachment().	101
c14n-hash-set().	102
canonicalize().	103
cert-from-issuer-serial().	105
concat-base64().	106
decrypt-attachment().	107
decrypt-data().	108

decrypt-key()	109
deflate()	111
encrypt-attachment()	112
encrypt-data()	113
encrypt-key()	114
encrypt-string()	116
exc-c14n-hash()	117
exc-c14n-hash-set()	118
generate-key()	120
generate-passticket()	121
get-cert-details()	122
get-cert-issuer()	124
get-cert-serial()	126
get-cert-ski()	127
get-cert-subject()	129
get-cert-thumbprintsha1()	131
get-kerberos-apreq()	133
hash()	134
hash-base64()	134
inflate()	135
ldap-authen()	136
ldap-search()	137
ldap-simple-query()	139
ocsp-validate-certificate()	141
ocsp-validate-response()	145
parse-kerberos-apreq()	148
random-bytes()	150
radix-convert()	150
same-dn()	151
sign()	152
sign-hmac()	154
sign-hmac-set()	156
substring-base64()	159
unwrap-key()	159
validate-certificate()	160
verify()	163
verify-hmac()	165
verify-hmac-set()	167
wrap-key()	170
zosnss-authen()	171
zosnss-author()	172
zosnss-passticket-authen()	173

Chapter 4. XSLT and XPath

extensions	175
xsl:import	175
xsl:include	176
xsl:message	176
xsl:output	176

Chapter 5. EXSLT extensions

Common module	179
node-set()	180
object-type()	180
Dates and Times module	180
add()	181
add-duration()	181
date()	181
date-time()	181
day-abbreviation()	181

day-in-month()	181
day-in-week()	181
day-in-year()	182
day-name()	182
day-of-week-in-month()	182
difference()	182
duration()	182
hour-in-day()	182
leap-year()	182
minute-in-hour()	182
month-abbreviation()	183
month-in-year()	183
month-name()	183
second-in-minute()	183
seconds()	183
sum()	183
time()	183
week-in-month()	183
week-in-year()	183
year()	184
Dynamic module	184
evaluate()	184
Functions module	184
function	184
result	185
Math module	185
max()	185
min()	186
Random module	186
Regular Expressions module	186
match()	186
replace()	186
test()	186
Sets module	187
difference()	187
distinct()	187
has-same-node()	187
intersection()	187
leading()	187
trailing()	188
Strings module	188
concat()	188
decode-uri()	188
encode-uri()	189
padding()	190
split()	190
tokenize()	190

Chapter 6. WebGUI extensions

param	191
summary	192

Appendix A. Working with variables

Service variables	196
General service variables	196
Multi-Protocol Gateway and Web Service Proxy	
service variables	197
Configuration services service variables	198
Load balancer service variables	199
MQ-specific service variables	199

Multistep variables	201
Transaction variables	202
Asynchronous transaction variables	202
Error handling transaction variables	203
Headers transaction variables	204
Information transaction variables	205
Persistent connection transaction variables	206
Routing transaction variables	206
Statistics variables	207
URL-based transaction variables	207
Web Services Management transaction variables	208
Extension variables	210
System variables	212

List of available variables	213
---------------------------------------	-----

Appendix B. Getting help and technical assistance 219

Searching knowledge bases	219
Getting a fix	219
Contacting IBM Support	220

Notices and trademarks 221

Trademarks	221
----------------------	-----

Index 223

Preface

This document lists and describes the IBM® WebSphere® DataPower® XSLT extension elements, extension functions, and variables. The extension elements and functions provide experienced XSLT users with a means to take maximum advantage of the capabilities offered by the DataPower XSLT processor. Experienced users can employ extensions to develop XSL style sheets that are tailored to their local, site-specific, processing, or security requirements.

IBM WebSphere DataPower, however, strongly encourages users to define processing policies from the WebGUI. The style sheets that support the WebGUI processing policies have undergone rigorous internal testing. Additionally, most customers use these processing policies on a daily basis in critical applications. Again, developing and deploying custom XSLT should not be the initial, but the final option, for the majority of users.

Note: DataPower XSLT processing does not support third party extension functions.

How this document is organized

This document has the following organization:

- Chapter 1, “Extension elements”
Provides documentation about DataPower XSLT extension elements. Each element topic contains sections with the following information:
- Chapter 2, “Metadata extension functions”
Provides documentation about extension functions that you can use for protocol headers and message manipulation.
- Chapter 3, “Cryptographic extension functions,” on page 93
Provides documentation about extension functions that you can use to perform standard cryptographic operations (encryption, decryption, document signature, signature verification, and so forth). Cryptographic functions are available on XS40 and platforms only.
- Chapter 4, “XSLT and XPath extensions,” on page 175
Provides documentation about the DataPower-specific changes to the supported XSLT and XPath extensions.
- Chapter 5, “EXSLT extensions”
Lists supported EXSLT extension functions. These functions support the EXSLT community effort to provide a standardized set of common functions to enhance style sheet portability.
- Chapter 6, “WebGUI extensions,” on page 191
Provides documentation about the DataPower-specific elements that control the presentation of custom style sheets in the processing policy editor.
- Appendix A, “Working with variables”
Lists the various system variables that you can access with the `<set-variable>` and `dp:variable()` extensions.
- Appendix B, “Getting help and technical assistance”
Provides information about working with IBM support.

Publications

The IBM WebSphere DataPower library is organized into the following categories:

- “Installation and upgrade documentation”
- “Administration documentation”
- “Development documentation”
- “Reference documentation” on page ix
- “Integration documentation” on page ix
- “Problem determination documentation” on page x
- “Supplemental documentations” on page x

Installation and upgrade documentation

- *IBM WebSphere DataPower SOA Appliances: 9003: Installation Guide*
Provides instructions for installing and powering up the Type 7993 (9003) appliance, creating a startup configuration script, and placing the appliance in operation.
- *IBM WebSphere DataPower SOA Appliances: Type 9235: Installation Guide*
Provides instructions for installing and powering up the Type 9235 appliance, creating a startup configuration script, and placing the appliance in operation.
- *IBM WebSphere DataPower SOA Appliances: Type 9235: Hardware Problem Determination and Service Guide*
Provides information about diagnosing and troubleshooting hardware problems, ordering consumable replacement parts, and replacing parts.
- *IBM WebSphere DataPower SOA Appliances: Upgrade and Rollback Guide: Generation 2 Firmware*
Provides instructions for upgrading Generation 2 firmware and for rolling back firmware upgrades.

Administration documentation

- *IBM WebSphere DataPower SOA Appliances: Appliance Overview*
Provides an introduction and understanding of the IBM Websphere DataPower SOA appliances.
- *IBM WebSphere DataPower SOA Appliances: Administrators Guide*
Provides instructions for using the DataPower GUI for managing user access, network access, appliance configuration and system configuration of the appliance.
- *IBM WebSphere DataPower SOA Appliances: Hardware Security Module Guide*
A user guide for using a Hardware Security Module (HSM) installed in the appliance.

Development documentation

- *IBM WebSphere DataPower SOA Appliances: XSL Accelerator Developers Guide*
Provides instructions for using the WebGUI to configure XSL Proxy and XSL Co-Processor services.
- *IBM WebSphere DataPower SOA Appliances: XML Firewall Developers Guide*
Provides instructions for using the WebGUI to configure XML Firewall services.
- *IBM WebSphere DataPower SOA Appliances: Web Application Firewall Developers Guide*

Provides instructions for using the WebGUI to configure Web Application Firewall services.

- *IBM WebSphere DataPower SOA Appliances: Multi-Protocol Gateway Developers Guide*

Provides instructions for using the WebGUI to configure Multiple-Protocol Gateway services.

- *IBM WebSphere DataPower SOA Appliances: Web Service Proxy Developers Guide*

Provides instructions for using the WebGUI to configure Web Service Proxy services.

- *IBM WebSphere DataPower SOA Appliances: B2B Gateway Developers Guide*

Provides instructions for using the WebGUI to configure B2B Gateway services.

- *IBM WebSphere DataPower SOA Appliances: Low Latency Messaging Developers Guide*

Provides instructions for using the WebGUI to configure a DataPower appliance for low latency messaging.

Reference documentation

- Product-specific documentation for using commands from the command line. The documentation is specific to each of the following products. Each document provides an alphabetical listing of all commands with syntactical and functional descriptions.

- *IBM WebSphere DataPower XML Accelerator XA35: Command Reference*
- *IBM WebSphere DataPower XML Security Gateway XS40: Command Reference*
- *IBM WebSphere DataPower XML Integration Appliance XI50: Command Reference*
- *IBM WebSphere DataPower B2B Appliance XB60: Command Reference*
- *IBM WebSphere DataPower Low Latency Messaging Appliance XM70: Command Reference*

- *IBM WebSphere DataPower SOA Appliances: Extension Elements and Functions Catalog*

Provides programming information about the usage of DataPower XSLT extension elements and extension functions.

Integration documentation

The following documents are available for managing the integration of related products that can be associated with the DataPower appliance:

- *IBM WebSphere DataPower SOA Appliances: Integrating with ITCAM*

Provides concepts for integrating the DataPower appliance with IBM Tivoli Composite Application Management for SOA.

- *IBM WebSphere DataPower SOA Appliances: Integrating with WebSphere Transformation Extender*

Provides concepts for integrating the DataPower appliance with WebSphere Transformer Extender.

- *IBM WebSphere DataPower XML Integration Appliance XI50: WebSphere MQ Interoperability*

Explains the concepts and common use patterns for connecting DataPower services to WebSphere MQ systems.

Problem determination documentation

- *IBM WebSphere DataPower SOA Appliances: Problem Determination Guide*
Provides troubleshooting and debugging tools.

Supplemental documentations

- *IBM WebSphere DataPower SOA Appliances: Understanding Web Services Policy*
Provides conceptual information about how the DataPower appliance can use Web Services Policy (WS-Policy).
- *IBM WebSphere DataPower SOA Appliances: Understanding WS-Addressing*
Provides conceptual information about how the DataPower appliance can use WS-Addressing.
- *IBM WebSphere DataPower SOA Appliances: Understanding LTPA*
Provides conceptual information about how the DataPower appliance can use Lightweight Third Party Authentication.
- *IBM WebSphere DataPower SOA Appliances: Understanding SPNEGO*
Provides conceptual information about how the DataPower appliance can use SPNEGO.
- *IBM WebSphere DataPower SOA Appliances: Optimizing through Streaming*
Provides conceptual information about and procedures for optimizing the DataPower appliance through streaming.
- *IBM WebSphere DataPower SOA Appliances: Securing the Last Mile*
Provides conceptual information about and procedures for understanding the DataPower appliance while securing the last mile.
- *IBM WebSphere DataPower SOA Appliances: Configuring the DoD PKI*
Provides conceptual information about and procedures for configuring the DataPower appliance with Department of Defense Public Key Infrastructure.

Namespace declarations

Style sheets that contain extension elements and functions must contain the following namespace declarations:

- `xmlns:dp="http://www.datapower.com/extensions"`
- `extension-element-prefixes="dp"`

Refer to individual EXSLT functions for required namespace declarations.

Data types

Arguments that the caller passes to extension functions are of the following standard XPath data types:

- Boolean
- Node set
- Number
- String

Most argument types that a style sheet pass to the code that implements a function are XPath expressions. Refer to the Guidelines section for information that is specific to each extension.

Reading syntax statements

The reference documentation uses the following special characters to define syntax:

- [] Identifies optional options. Options not enclosed in brackets are required.
- ... Indicates that you can specify multiple values for the previous option.
- | Indicates mutually exclusive information. You can use the option to the left of the separator or the option to the right of the separator. You cannot use both options in a single use.
- { } Delimits a set of mutually exclusive options when one of the options is required. If the options are optional, they are enclosed in brackets ([]).

Typeface conventions

The following typeface conventions are used in the documentation:

- bold** Identifies commands, functions, programming keywords, and GUI controls.
- italics* Identifies words and phrases used for emphasis and user-supplied variables.
- monospaced Identifies elements, user-supplied input, and computer output.

Chapter 1. Extension elements

This chapter provides documentation about available DataPower XSLT extension elements. The documentation for each element contains the following sections:

- Element name
- Platform availability
- Declarations for required namespace and extension prefix
- Syntax
- Attributes with data type
- Guidelines
- Return values or results, if any
- Examples

accept

Allows or rejects further message processing.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:accept/>
```

Guidelines

You can invoke multiple `dp:accept`, `dp:reject`, and `dp:xreject` elements. The last processed element determines the disposition of the message.

Results

None

Examples

```
⋮  
<dp:reject/>  
<xsl:choose>  
  ⋮  
  <xsl:when test="$responsecode = '200'">  
    <dp:accept/>  
  </xsl:when>  
  
  <xsl:otherwise>  
    <dp:reject>Denied by access file</dp:reject>  
  </xsl:otherwise>  
</xsl:choose>
```

```
</xs1:choose>
:
```

append-request-header

Appends a value you specify to a protocol client request header field.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:append-request-header
  name="field"
  value="value" />
```

Attributes

field (xs:string) Identifies a client request header field to edit.

value (xs:string) Specifies the value to append to the header field.

Guidelines

If the header field exists in the incoming client request, appends the specified value to the header and inserts a comma between the header field and value.

If the header field does not exist in the incoming client request, adds the values for header field and value to the client request header.

The element passes all attributes as XPath expressions.

Results

None

Examples

```
:
```

```
<dp:append-request-header name="'ValidatedSig'" value="$signature"/>
```

```
:
```

append-response-header

Appends a value you specify to a protocol server response header field.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```


Syntax

```
<dp:append-response-header  
  name="field"  
  value="value" />
```

Attributes

field (xs:string) Identifies a server response header field to edit.

value (xs:string) Specifies the value to append to the header field.

Guidelines

If the header specified by the header field exists in the incoming server response, appends the specified value specified to the header and inserts a comma between header field and the value.

If the header field does not exist in the incoming server response, adds the values for the header field and the value to the server response header.

The element passes all attributes as XPath expressions.

Results

None

Examples

```
⋮  
<dp:append-response-header name="'SchemaValidated'" value="$targetSchema"/>  
⋮
```

canonicalize

Writes the canonicalization of a specified node set to a file that you specify in the temporary: directory.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:canonicalize  
  file="fileName"  
  nodes="nodeSet"  
  algorithm="c14nAlgorithm"  
  prefixes="nsPrefixes"  
  deep="boolean" />
```

Attributes

file="*fileName*"
(xs:string) Identifies the file in the temporary: directory to receive the canonicalized output.

nodes="nodeSet"

(xs:string) Identifies the target node set to canonicalize.

algorithm="c14nAlgorithm"

(xs:string) Optionally specifies the method to canonicalize the node set.

<http://www.w3.org/TR/2001/REC-xml-c14n-20010315>

Identifies the c14n algorithm (does not include comments in the canonicalized output)

<http://www.w3.org/TR/2001/REC-xml-c14n-20010315#WithComments>

Identifies the c14n algorithm (includes comments in the canonicalized output)

<http://www.w3.org/2001/10/xml-exc-c14n#>

(Default) Identifies the c14n exclusive algorithm (does not include comments in the output)

<http://www.w3.org/2001/10/xml-exc-c14n#WithComments>

Identifies the c14n exclusive algorithm (includes comments in the output)

prefixes="nsPrefixes"

(xs:string) Optionally specifies a comma-separated list of prefixes to include in the output.

Use the optional *nsPrefixes* attribute to specify the exclusive canonicalization algorithm method. By default, this algorithm produces a namespace prefix declaration only if the prefix is in an element in the node set to canonicalize.

The *nsPrefixes* attribute overrides the default prefix declaration behavior of the exclusive canonicalization algorithm. The *nsPrefixes* attribute allows you to specify a set of namespace prefixes to include in the namespace prefix declarations.

Specifying *nsPrefixes* as null (the default) generates an empty set of prefixes.

deep="boolean"

(xs:boolean) Optionally specifies how to process descendants of the nodes in the target node set.

- If true, the default, processes all descendants of the nodes in the target node set.
- If false, processes only the nodes in the target node set, which excludes descendants.

Guidelines

The element passes **file**, **nodes**, **algorithm**, and **prefixes** attributes as XPath expressions; the **deep** attribute passes as a literal.

Results

An xs:string that contains the canonicalized node set.

Examples

```
⋮  
<dp:canonicalize file="c14exc.debug" nodes="$nodes"/>  
⋮
```

dump-nodes

Outputs a node set to a file in the temporary: directory.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:dump-nodes  
  file="fileName"  
  nodes="nodeSet"  
  emit-xml-decl="boolean"/>
```

Attributes

file="fileName"
(xs:string) Identifies the file in the temporary: directory to receive the output.

nodes="nodeSet"
(xs:node-set) Identifies the target node set to output to a file.

emit-xml-decl="boolean"
(xs:string) Indicates whether to include XML declarations in the output.

yes	Include XML declarations.
no	(Default) Excludes XML declarations.

Guidelines

The element passes the **file** and **nodes** attributes as XPath expressions and the **emit-xml-decl** attribute passes as a literal.

Examples

```
⋮  
<xsl:if test="$checkStats">  
  <dp:dump-nodes file="'stats.xml'" nodes="$sec-entries"/>  
</xsl:if>  
⋮
```

freeze-headers

Locks header values and prevents further processing.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:freeze-headers/>
```

Guidelines

Use `dp:freeze-headers` exclusively with the `dp:set-http-request-header` and `dp:set-http-response-header` extension elements.

Results

None

Examples

```
⋮  
<xsl:template match="/">  
  <dp:set-http-request-header name="'Foo'" value="'Foo header'"/>  
  <dp:set-http-response-header name="'My-Response'" value="'Okay'"/>  
  <dp:freeze-headers/>  
  <xsl:copy-of select="."/>  
</xsl:template>  
⋮
```

increment-integer

Enables style sheet control of a message monitor counter.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:increment-integer  
  name="counterName"  
  ipaddr="ipAddress" />
```

Attributes

name="*/count-monitor/counterName*"
(*xs:string*) Specifies the name of the object that identifies the counter to increment.

ipaddr="*ipAddress*"
(*xs:string*) An optional attribute to associate an IP address with the message counter.

Guidelines

The element passes all attributes as XPath expressions.

Examples

```
⋮
<xsl:if test="string($processingdoc/Counter) != ''">
  <dp:increment-integer name="'/count-monitor/SLACounter-1'" />
</xsl:if>
⋮
```

parse

Parses a well-formed XML document to produce a node set.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:parse
  select="arbitraryXML"
  encoding="base-64" />
```

Attributes

select="*arbitraryXML*"

(xs:string) Specifies the well-formed XML document to parse to produce a node set.

encoding="base-64"

(xs:string) Optionally assigns a value of base-64 to this attribute to treat the XML document as Base64 encoded. The extension element first decodes then parses the XML document.

Guidelines

If the input XML document is not well formed, dp:parse issues an error message. This element does not support external DTD and entity references.

The element passes the **select** attribute as an XPath expression and the **encoding** attribute as an ATV.

Results

Returns a node set, if successful. Otherwise, writes a parse error message to the var://local/_extension/error variable.

Examples

Tests the validity of a document before performing further processing. Also, checks the var://local/_extension/error variable for an error message indicating that the document could not be parsed. If there is an error, sends the variable contents with xsl:message.

```
⋮
<dp:parse select="$arbitraryData" encoding="base-64" />
<xsl:if test="dp:variable('var://local/_extension/error')">/>
  <xsl:message terminate="yes">
```

```

        <xsl:copy-of-select="dp:variable('var:/local/_extension/error')"/>
      </xsl:message>
    </xsl:if>
    :

```

reject

Denies access through the DataPower service.

Availability

All products except XA35

Namespace declaration

```

xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"

```

Syntax

```

<dp:reject
  override="true | false">
  text
</dp:reject>

```

Attributes

override="true | false"

(xs:boolean) Optionally specifies whether this rejection decision supersedes previous rejection decisions.

true Indicates that this rejection supersedes previous decisions.

false (Default) Indicates that this rejection does not override previous decisions.

textString

(xs:string) Specifies the reason for denying access through the XML Firewall or Multi-Protocol Gateway. The element includes *text* in the SOAP fault message.

Guidelines

The appliance sends the denial message to the client in a SOAP fault message. Also stops document processing and optionally invokes the error rule for custom error handling.

dp:xreject is an extended version of the dp:reject element. dp:xreject uses an XPath expression to construct the rejection text that the appliance sends back to the client in a SOAP fault message.

The element passes the **override** attribute and the rejection message text as literals.

Results

None

Examples

```

:
<xsl:choose>
  <xsl:when test="$allowed">

```

```
        <dp:accept />
      </xsl:when>
      <xsl:otherwise>
        <dp:reject>Denied by access file</dp:reject>
      </xsl:otherwise>
    </xsl:choose>
    ⋮
  
```

remove-http-request-header

Specifies a header field to remove from the HTTP header of a client request.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:remove-http-request-header
  name="httpHeaderField"/>
```

Attributes

```
name="httpHeaderField"
(xs:string) Identifies the HTTP request header field to remove.
```

Guidelines

The element passes the attribute as an AVT.

Examples

```
⋮
<dp:remove-http-request-header name="ValidatedSig"/>
⋮

```

remove-http-response-header

Specifies a header field to remove from the HTTP header of a server response.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:remove-http-response-header
  name="httpHeaderField"/>
```

Attributes

`name="httpHeaderField"`
(xs:string) Identifies the HTTP response header field to remove.

Guidelines

The element passes all attributes as an AVT.

Examples

```
⋮  
<dp:remove-http-response-header name="ValidatedSig"/>  
⋮
```

remove-mime-header

Removes the MIME root part header.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:remove-mime-header name="header-name" context="context" />
```

Attributes

header-name
(xs:string) Specifies the name of the header to set.

context
(xs:string) Optionally specifies the name of the multistep context.

Guidelines

The remove-mime-header element removes the specific header that comes in the beginning (before the preamble) from the MIME message.

Examples

```
⋮  
<xsl:output method="xml" />  
<xsl:template match="/">  
  <dp:remove-mime-header name="Content-Type" />  
  <xsl:copy-of select="." />  
</xsl:template>  
⋮
```

send-error

Stops transaction and sends a custom error message to the client.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:send-error  
  override="true | false">  
  arbitraryXML  
</dp:send-error>
```

Attributes

override="true | false"
(xs:boolean) Specifies whether this failure response supersedes previous failure responses.

true Indicates that this failure response supersedes previous failure responses.

false (Default) Indicates that this failure response does not supersede previous failure responses.

arbitraryXML
(xs:string) Specifies an XML construct that contains the failure response.

Guidelines

The element passes all attributes as literals.

Examples

```
⋮  
<xsl:template match="/faultme">  
  <dp:reject>Text to replace with the custom error</dp:reject>  
  <dp:send-error override='true'>  
    <x:error xmlns:x='http://www.example.com'>  
      The custom error packet  
      <code xmlns='uri:foo'>FaultyAssign</code>  
    </x:error>  
  </dp:send-error>  
</xsl:template>  
⋮
```

serialize

Sends the output for a specified node set as a byte stream.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:serialize  
  select="nodeSet"  
  omit-xml-decl="yes | no"/>
```

Attributes

select="*nodeSet*"
(*xs:string*) Identifies the node set to serialize.

omit-xml-decl="yes | no"
(*xs:string*) Optionally specifies whether to include XML declarations in the output.

yes Omits XML declarations.

no (Default) Includes XML declarations.

Guidelines

Set the **omit-xml-decl** attribute to yes to exclude the node set XML declaration, for example, `<?XML version="1.0">` in the serialized output.

The element passes the **select** attribute as an XPath expression and the **omit-xml-decl** attribute as an AVT.

Results

None

Examples

- Writes the contents of the specified node set, including XML declarations, to the myvar variable.
:
`<xsl:variable name="myvar">`
 `<dp:serialize select="$something"/>`
`</xsl:variable>`
:
- Writes the contents of the specified node set, excluding XML declarations, to the myvar variable.
:
`<xsl:variable name="myvar">`
 `<dp:serialize select="$something" omit-xml-decl="yes"/>`
`</xsl:variable>`
:

set-http-request-header

Inserts a specific header field and its associated value into the HTTP header of a client request.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`
`extension-element-prefixes="dp"`

Syntax

```
<dp:set-http-request-header  
  name="httpHeaderField"  
  value="httpHeaderFieldValue"/>
```

Attributes

name="httpHeaderField"
(xs:string) Identifies an HTTP header field to add to a client request.

value="httpHeaderFieldValue"
(xs:string) Specifies the value to place in the HTTP header field.

Guidelines

If a client request already includes the field identified by the **name** attribute, this extension element overwrites the specified header field value in the client request.

If the header field does not exist, this extension function adds the specified **name** and **value** to the client request.

The element passes all attributes as XPath expressions.

Examples

```
⋮  
<dp:set-http-request-header name="ValidatedSig" value="$signature"/>  
⋮
```

set-http-response-header

Inserts a specific header field and its associated value into the HTTP header of a server response.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-http-response-header  
  name="httpHeaderField"  
  value="httpHeaderFieldValue"/>
```

Attributes

name="httpHeaderField"
(xs:string) Identifies an HTTP header field to add to a server response.

value="httpHeaderFieldValue"
(xs:string) Specifies the value to place in the server response header field.

Guidelines

If the server response already includes the **name** attribute, this extension element overwrites the specified header field value in the server response.

If the header field does not exist, the extension element adds the specified **name** and **value** to the server response.

The element passes all attributes as XPath expressions.

Examples

```
⋮  
<dp:set-http-response-header name="SchemaValidated" value="$targetSchema"/>  
⋮
```

set-local-variable

Assigns a value to a local context variable.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-local-variable  
  name="variableName"  
  value="variableValue"/>
```

Attributes

name="variableName"
(xs:string) Specifies the name of the variable.

value="variableValue"
(node set, result-tree-fragment, xs:boolean, xs:double, or xs:string)
Specifies the value of *variableName*.

Guidelines

Similar to `dp:set-variable` except that the scope of `dp:set-local-variable` is a single execution context, while `dp:set-variable` operates within the global multistep scope.

The element passes the **name** and **value** attributes as XPath expressions.

Examples

```
⋮  
<xsl:template name="set-counter">  
  <xsl:param name="counter" select="''" />  
  <xsl:param name="value" select="''" />  
  <xsl:param name="inc" select="''" />  
  <xsl:if test="not($counter = '')">  
    <xsl:choose>  
      <xsl:when test="not($value = '')  
        and not(string(number($value))= 'NaN')">  
        <dp:set-local-variable  
          name="$counter" value="$value" />  
      </xsl:when>  
      <xsl:when test="not($inc = '') and not(string(number($inc))= 'NaN')">  
        <xsl:variable name="counter-value"  
          select="number(dp:local-variable($counter))"/>  
        <dp:set-local-variable name="$counter"  
          value="string(number($counter-value)+ number($inc))" />  
      </xsl:when>  
    </xsl:choose>  
  </xsl:if>  
</xsl:template>
```

```
</xsl:if>
</xsl:template>
:
```

set-metadata

Sets the value of specified metadata items.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-metadata>
  arbitraryXML
</dp:set-metadata>
```

Attributes

arbitraryXML

Specifies the metadata to access and the actions to perform on the metadata.

Guidelines

The set-metadata element changes metadata for a response message. Additionally, the element modifies a request message if the lower level services provide support.

The action attribute supports the following values:

overwrite

(Default) If the metadata item already exists, overwrites the existing value. If the metadata item does not exist, the input value creates a new metadata item.

delete Deletes the metadata item and ignores the input value. Not supported by all protocols.

append Assumes the specified metadata item is an array. The input value creates another metadata item with the same name.

The element passes all attributes as literals.

Examples

```
<dp:set-metadata>
  <metadata category="wasjms">
    <transaction-id action="overwrite">1D67B8976543A113</transaction-id>
    <foo action="overwrite">foo-value</foo>
    <bar action="delete">bar-value</bar>
  </metadata>
</dp:set-metadata>
```

- Overwrites the predefined metadata item transaction-id with the value 1D67B8976543A11.

- Overwrites the user-defined metadata item `foo` with the value `foo-value`. If `foo` does not exist, creates `foo` with the specified value (`foo-value`).
- Deletes the user-defined metadata item `bar`.

set-mime-header

Sets the MIME root part header.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-mime-header name="header-name" value="value" context="context" />
```

Attributes

header-name

(xs:string) Specifies the name of the header to set.

value (xs:string) Specifies the value for the header.

context

(xs:string) Optionally specifies the name of the multistep context.

Guidelines

The `set-mime-header` element sets the value for a specific header that comes in the beginning (before the preamble) of the MIME message.

Examples

```
...  
<xsl:output method="xml" />  
<xsl:template match="/">  
  <dp:set-mime-header name="Content-Type"  
    value="dp:variable('var://local/attachment-manifest')/  
    manifest/media-type/value" />  
  <xsl:copy-of select="." />  
</xsl:template>  
...
```

set-request-header

Inserts a specified header field and its associated value in the protocol header of a client request.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-request-header  
  name="headerField"  
  value="headerFieldValue"/>
```

Attributes

name="headerField"
(xs:string) Identifies the request header field to add to a client request.

value="headerFieldValue"
(xs:string) Specifies the value for the request header field.

Guidelines

Supported protocols are HTTP (all appliance models) and WebSphere MQ, in licensed.

If the client request contains the header specified by *headerField*, the element overwrites the field value for that header with the value in *headerFieldValue*.

If *headerField* does not exist in the client request, the element adds *headerField* and *headerFieldValue* to the request header.

The element passes all attributes as XPath expressions.

Examples

```
⋮  
<dp:set-request-header name="$mqHeader-1" value="$contents"/>  
⋮
```

set-response-header

Inserts a specified header field and its associated value in the protocol header of a server response.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-response-header  
  name="headerField"  
  value="headerFieldValue"/>
```

Attributes

name="headerField"
(xs:string) Identifies the response header field to add to a server response.

value="headerFieldValue"
(xs:string) Specifies the value for the response header field.

Guidelines

Supported protocols are HTTP (all appliance models) and WebSphere MQ, in licensed.

If the server response contains the header specified by *headerField*, the element overwrites the field value for that header with the value in *headerFieldValue*.

If *headerField* does not exist in the server response, the element adds *headerField* and *headerFieldValue* to the response header.

The element passes all attributes as XPath expressions.

Examples

```
⋮  
<dp:set-response-header name="$mqHeader-2" value="$contents"/>  
⋮
```

set-target

Specifies the target server of a client request.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:set-target>  
  <host>host</host>  
  <port ssl="true" | "false" sslid="sslProxyProfile">  
    port  
  </port>  
</dp:set-target>
```

Attributes

host (xs:string) Specifies the IP address or host name of the target server.

port (xs:double) Identifies the port number on the server.

ssl="true" | "false"

(xs:boolean) Optionally indicates whether the connection to the target server is secure (SSL-enabled).

true Specifies a secure connection to the target server.

false (Default) Specifies a nonsecure connection to the target server.

sslid="sslProxyProfile"

(xs:string) Identifies the SSL Proxy Profile to use to establish a secure connection.

This attribute is required when the **ssl** attribute is **true**; otherwise, it is not used.

Guidelines

Use the `dp:set-target` element when you configure a DataPower service with a dynamic backend. You can call this element multiple times, with the last one taking precedence. A connection is started immediately, while other processing is occurring and less data might be buffered.

The `dp:set-target` element overrides the value of the target server that is specified with the `var://service/routing-url` variable. For Multi-Protocol Gateway and Web Service Proxy services, the honoring of the URI is based on the setting of the **Propagate URI** toggle (WebGUI) or **propagate-uri** command.

The `host` node, the `port` node, and the `ssl` attribute are passed as literals. The `sslid` attribute is passed as an AVT.

Results

None

Examples

- Specifies a target server based on a select XPath match.

```
⋮
<xsl:template match="/">
  <xsl:choose>
    <xsl:when test="/*[local-name()='Envelope']/*[local-
      name()='Body']/*[local-name()='CheckRequestElement']">
      <dp:set-target>
        <host>10.10.36.11</host>
        <port>2068</port>
      </dp:set-target>
    </xsl:when>
    <xsl:when test="/*[local-name()='Envelope']/*[local-
      name()='Body']/*[local-name()='request']">
      <dp:set-target>
        <host>10.10.36.11</host>
        <port>2064</port>
      </dp:set-target>
    </xsl:when>
    <xsl:otherwise>
      <dp:set-target>
        <host>10.10.36.11</host>
        <port>8080</port>
      </dp:set-target>
    </xsl:otherwise>
  </xsl:choose>
</xsl:template>
⋮
```

- Specifies a target server for an XML Firewall service that might override the routing URL.

```
⋮
<xsl:template match="/">
  <xsl:choose>
    <xsl:when test="/*[local-name()='Envelope']/*[local-
      name()='Body']/*[local-name()='CheckRequestElement']">
      <dp:set-variable name="'var://service/routing-url'"
        value="'http://10.10.36.11:2068'" />
      <dp:set-variable name="'var://service/URI'"
        value="'/SomeBank/services/checking'" />
    </xsl:when>
    <xsl:when test="/*[local-name()='Envelope']/*[local-
      name()='Body']/*[local-name()='request']">
      <dp:set-variable name="'var://service/routing-url'"

```

```

        value="'http://10.10.36.11:2064'" />
      <dp:set-variable name="'var://service/URI'"
        value="'/services'" />
    </xsl:when>
    <xsl:otherwise>
      <dp:set-target>
        <host>10.10.36.11</host>
        <port>8080</port>
      </dp:set-target>
    </xsl:otherwise>
  </xsl:choose>
</xsl:template>
⋮

```

set-variable

Assigns a value to a global context variable.

Availability

All products

Namespace declaration

```

xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"

```

Syntax

```

<dp:set-variable
  name="variableName"
  value="variableValue" />

```

Attributes

name="*variableName*"
(xs:string) Specifies the name of the variable.

value="*variableValue*"
(node set, result-tree-fragment, xs:boolean, xs:double, or xs:string)
Specifies the value of *variableValue*.

Guidelines

Similar to `dp:set-local-variable` except that the scope of `dp:set-variable` is a global multistep context, while `dp:set-local-variable` operates in a single execution context.

The element passes the name (xs:string) and value (any type) attributes as XPath expressions.

Refer to Appendix A, “Working with variables,” on page 195 for a list of system variables.

Examples

```

⋮
<xsl:if test="$attachment/url-open/responsecode = '201'">
  <xsl:message dp:type="{ $dpconfig:LogCategory}" dp:priority="error">
    Virus reported in attachment '<xsl:value-of select="$location"/>'
  </xsl:message>
  <dp:reject override="true">Virus Found</dp:reject>

```

```

        <dp:set-variable name="'var://service/error-subcode'" value="0x01d30005"/>
    </xsl:if>
    <xsl:if test="$attachment/url-open/responsecode = '200'">
        <dp:accept />
    </xsl:if>
    :
    :
    <xsl:template name="SQL-Injection-Test">
        <xsl:param name="text" />
        <xsl:param name="searchRegex" />
        <xsl:param name="attackName" />
        <xsl:param name="message" />
        <xsl:variable name="injectionMatch"
            select="regexp:match($text, $searchRegex, 'i')" />

        <xsl:if test="$dpconfig:SQLDEBUG">
            <xsl:message dp:priority="debug">
                **DEBUG**: regexp:match("
                <xsl:value-of select="$text" />
                "
                <xsl:value-of select="$searchRegex" />
                , "i") returned
                <xsl:value-of select="count($injectionMatch)" />
                matches
            </xsl:message>
        </xsl:if>

        <xsl:if test="count($injectionMatch) > 0">
            <dp:set-variable
                name="'var://context/__SQL_INJECTION_FILTER__/hit'" value="'1'" />
            <dp:reject>Message contains restricted content</dp:reject>
            <xsl:message dp:priority="error">
                ***SQL INJECTION FILTER***: Message from
                <xsl:value-of select="dp:client-ip-addr()" />
                contains possible SQL Injection Attack of type '
                <xsl:value-of select="$attackName" />
                '. Offending content: '
                <xsl:value-of select="string($injectionMatch)" />
                '. Full Message: '
                <dp:serialize select="$message" />
                '
            </xsl:message>
        </xsl:if>
    </xsl:template>
    :
    :

```

sql-execute

Executes a query statement against a database using parameter markers.

Availability

All products with SQL/ODBC support

Namespace declaration

```

xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"

```

Syntax

```

<dp:sql-execute
    source="datasource"
    statement="statement">
    <arguments>
        <argument type="sqlType" mode="mode" isNull="{true|false}"

```

```

    precision="precision" scale="scale" nullable="{true|false}">
      value
    </argument>
    ...
  </arguments>
  ...
</dp:sql-execute>

```

Attributes

source="datasource"

(xs:string) Specifies the name of an enabled SQL Data Source object that was previously created either from the WebGUI or from the command line. This object provides the data (IP address, monitored port, database type, and so forth) that is required to access a remote database.

statement="statement"

(xs:string) Specifies the SQL statement or the XQuery statement to execute.

Note the use of the <argument> node, which has the following format:

```

<argument type="sqlType" mode="mode" isNull="{true|false}"
  precision="precision" scale="scale" nullable="{true|false}">
  value
</argument>

```

type="sqlType"

(xs:string) Indicates the SQL data type for the parameter marker. This data type provides the mapping to make the conversion from an xs:string to the underlying SQL type. This attribute supports the keywords in Table 1.

Note: If the SQL data type does not have an associated vendor in Table 1, that SQL data type for an argument to that database is not a supported combination, and the behavior is undefined.

Table 1. Keywords for SQL data types

SQL data type	Vendor	Vendor-specific data type
SQL_BIGINT	DB2® version 9	BIGINT
	DB2 version 8 and earlier	BIGINT
	Sybase	Bigint, Unsigned Bigint
SQL_BINARY	DB2 version 9	BINARY
	DB2 version 8 and earlier	CHAR FOR BIT DATA
	Microsoft® SQL Server	Binary
	Sybase	Binary
SQL_BIT	DB2 version 9	CHAR FOR BIT DATA
	Microsoft SQL Server	Bit
	Sybase	Bit
SQL_BLOB	DB2 version 9	BLOB

Table 1. Keywords for SQL data types (continued)

SQL data type	Vendor	Vendor-specific data type
SQL_CHAR	DB2 version 9	CHAR
	DB2 version 8 and earlier	CHAR
	Microsoft SQL Server	Char
	Oracle	Char
	Sybase	Char
SQL_CLOB	DB2 version 9	CLOB
SQL_TYPE_DATE	DB2 version 9	DATE
	DB2 version 8 and earlier	DATE
	Sybase	Date
SQL_DBCLOB	DB2 version 9	DBCLOB
SQL_DECFLOAT	DB2 version 9	DECFLOAT
SQL_DECIMAL	DB2 version 9	DECIMAL
	DB2 version 8 and earlier	DECIMAL
	Microsoft SQL Server	Decimal, Decimal Identity, Money, Smallmoney
	Oracle	Number(p,s)
	Sybase	Decimal, Money, Smallmoney
SQL_DOUBLE	DB2 version 9	DOUBLE
	DB2 version 8 and earlier	DOUBLE, FLOAT
	Oracle	Binary Float, Number
SQL_FLOAT	DB2 version 9	FLOAT
	Microsoft SQL Server	Float
	Sybase	Float
SQL_GRAPHIC	DB2 version 9	GRAPHIC
SQL_GUID	Microsoft SQL Server	Uniqueidentifier
SQL_INTEGER	DB2 version 9	INTEGER
	DB2 version 8 and earlier	INTEGER
	Microsoft SQL Server	Int, Unsigned Int
	Sybase	Int, Int Identity
SQL_LONGVARBINARY	DB2 version 9	LONG VARCHAR FOR BIT DATA
	DB2 version 8 and earlier	BLOB, LONG VARCHAR FOR BIT DATA
	Microsoft SQL Server	Image, Varbinary(max)
	Oracle	Bfile, Blob, Long Raw
	Sybase	Image

Table 1. Keywords for SQL data types (continued)

SQL data type	Vendor	Vendor-specific data type
SQL_LONGVARCHAR	DB2 version 9	LONG VARCHAR
	DB2 version 8 and earlier	CLOB, LONG VARCHAR
	Microsoft SQL Server	Text, Varchar(max)
	Oracle	Clob, Long
	Sybase	Text
SQL_LONGVARGRAPHIC	DB2 version 9	LONG VARGRAPHIC
SQL_NUMERIC	DB2 version 9	NUMERIC
	DB2 version 8 and earlier	NUMERIC
	Microsoft SQL Server	Numeric, Numeric Identity
	Sybase	Numeric
SQL_REAL	DB2 version 9	REAL
	DB2 version 8 and earlier	REAL
	Microsoft SQL Server	Real
	Oracle	Binary Double
	Sybase	Real
SQL_SMALLINT	DB2 version 9	SMALLINT
	DB2 version 8 and earlier	SMALLINT
	Microsoft SQL Server	Smallint, Smallint Identity
	Sybase	Smallint, Unsigned Smallint
SQL_TYPE_TIME	DB2 version 9	TIME
	DB2 version 8 and earlier	TIME
	Sybase	Time
SQL_TYPE_TIMESTAMP	DB2 version 9	TIMESTAMP
	DB2 version 8 and earlier	TIMESTAMP
	Microsoft SQL Server	Datetime, Smalldatetime
	Oracle	Date, Temestamp, Timestamp with Local Timezone
	Sybase	Datetime, Smalldatetime
SQL_TINYINT	DB2 version 9	CHAR
	Microsoft SQL Server	Tinyint, Tinyint Identity
	Sybase	Tinyint,
SQL_VARBINARY	DB2 version 9	VARBINARY, VARCHAR FOR BIT DATA
	DB2 version 8 and earlier	VARCHAR FOR BIT DATA
	Microsoft SQL Server	Timestamp, Varbinary
	Oracle	Raw
	Sybase	Timestamp, Varbinary

Table 1. Keywords for SQL data types (continued)

SQL data type	Vendor	Vendor-specific data type
SQL_VARCHAR	DB2 version 9	VARCHAR
	DB2 version 8 and earlier	VARCHAR
	Microsoft SQL Server	Varchar
	Oracle	Timestamp with Timezone, Varchar2
	Sybase	Sysname, Varchar
SQL_VARGRAPHIC	DB2 version 9	VARGRAPHIC
SQL_WCHAR	DB2 version 9	WCHAR
	DB2 version 8 and earlier	GRAPHIC
	Microsoft SQL Server	Nchar
	Oracle	Char(UTF-8)
SQL_WVARCHAR	DB2 version 9	VARGRAPHIC
	DB2 version 8 and earlier	VARGRAPHIC
	Microsoft SQL Server	nchar, sysname
	Oracle	Varchar(UTF-8)
SQL_WLONGVARCHAR	DB2 version 9	LONG VARGRAPHIC
	DB2 version 8 and earlier	DBCLOB, LONG VARGRAPHIC
	Microsoft SQL Server	ntext, nvarchar(max), xml
	Oracle	Clob(UTF-8), Long(UTF-8)
SQL_XML	DB2 version 9	XML

mode="mode"

(xs:string) Indicates the keyword for the direction of the parameter marker. This attribute supports the following keywords:

INPUT (Default) Indicates one of the following conditions:

- Indicates that the parameter marker is for an SQL statement that is not a stored procedure call
- Marks the parameter as an input parameter to a called stored procedure

INPUT_OUTPUT

Marks the parameter as an input-output parameter to a called stored procedure.

OUTPUT Indicates one of the following conditions:

- Marks the parameter as an output parameter to a called stored procedure
- Indicates that the parameter marker is the return value of a stored procedure

isNull="{true|false}"

(xsd:boolean) Indicates whether a NULL value should be specified for the parameter. When the direction is INPUT_OUTPUT or OUTPUT for a stored procedure call, indicates whether a value will be returned the parameter. The direction is defined by the keyword for the mode attribute.

true Indicates that the value should be NULL. When the direction is INPUT_OUTPUT or OUTPUT, the value for the parameter marker will be NULL in the result set.

false (Default) Indicates contents of the <argument> node will be used.

precision="precision"

(xsd:integer) Specifies the precision of the corresponding parameter marker. Precision is the total number of digits.

scale="scale"

(xsd:integer) Specifies the scale of the corresponding parameter marker. Scale is the total number of digits to the right of the decimal point.

nullable="{true|false}"

(xsd:boolean) Indicates whether a parameter can have a value of NULL.

true Can have a value of NULL.

false Cannot have a value of NULL.

value Defines the value for the argument (in the <argument> node) to pass. Generally, the value is an <xsl:value-of> element or an <xsl:copy-of> element.

To use a binary value, specify the value as hexadecimal.

Guidelines

The `dp:sql-execute` extension element is different from the `dp:sql-execute()` extension function. The `dp:sql-execute` element provides a superset of the capabilities that are provided by the `dp:sql-execute()` function. While both execute SQL statements without parameter markers, the `dp:sql-execute` element provides support for parameter markers in SQL statements.

The `dp:sql-execute` element executes SQL statements against data stores using parameter markers. Parameter markers are represented by the question mark (?) character. A parameter marker acts as a temporary placeholder.

All arguments are passed as XPath expressions.

Results

All databases return results in an <sql> element.

If the `isNull` attribute is not present and there is no child element or text, the value is interpreted as an empty string.

Values from binary columns (parameters) are returned in hexadecimal. To convert these values to a Base64 representation, use the `dp:radix-convert()` extension function.

For query invocations:

Query invocations can receive a single results set. The result is the same as the `dp:sql-execute()` function. For both, the result does not include <resultSet> nodes to delimit the content. In the following sample, shows a successful query that contains data for two columns in a single row. The *name1* column has the *value1* value, but the *name2* column has the NULL value.

```
<sql result="success">
  <row>
    <column>
```



```

        <name>name1</name>
        <value>value1</value>
    </column>
    <column>
        <name>name2</name>
        <value isNull="true"/>
    </column>
    ...
</row>
...
</sql>

```

For a stored procedure:

Stored procedures can receive multiple result sets. Each `<parameter>` element contains the values of any input-output parameter or of any output parameter that is returned as a result of executing the stored procedure against a database. If the value of the `<parameter>` element is NULL, the `<parameter>` element contains the `isNull` attribute set to true.

Each `<resultSet>` node delimits the contents of a single result set.

- The `<metadata>` node provides information about the structure and type of the result set in each `<columnInfo>` element.
- The `<row>` node is the same as for a query invocation.

```

<sql result="success">
  <parameter position="1">pvalue</parameter>
  <parameter position="2" isNull="true"/>
  ...
  <resultSet>
    <metadata>
      <columnInfo index="index" nullable="nullable" name="name"
        precision="precision" scale="scale" type="type"/>
      ...
    </metadata>
    <row>
      <column>
        <name>name1</name>
        <value>value1</value>
      </column>
      <column>
        <name>name2</name>
        <value isNull="true"/>
      </column>
      ...
    </row>
    ...
  </resultSet>
  <resultSet>
    <metadata>...</metadata>
    <row>...</row>
    ...
  </resultSet>
  ...
</sql>

```

For an error:

Unsuccessful queries result in an error message.

```

<sql result="error">
  <message>error-message</message>
</sql>

```

Examples

- Performs a simple **SELECT** operation. This call is equivalent to using the **dp:sql-execute()** extension function within the select attribute of an `<xsl:copy-of>` element.

```
...
<xsl:output indent="yes" encoding="UTF-8" version="1.0" method="xml"/>

<xsl:template match="/">
  <dp:sql-execute source="'DB2LUW95'"
    statement="'SELECT * FROM TBIRSMF'"/>
</xsl:template>
...
```

- Performs an **INSERT** operation. Uses an `<xsl:for-each>` element to insert multiple rows.

```
...
<xsl:output indent="yes" encoding="UTF-8" version="1.0" method="xml"/>

<xsl:template match="/*[local-name()='Return']">
  <dp:sql-execute source="'DB2LUW95'"
    statement="'INSERT INTO TBIRSMF VALUES(?,?,?,?)'">
    <xsl:for-each select="*[local-name()='ReturnData']/*">
      <arguments>
        <argument>
          <xsl:value-of select="../*[local-name()='ReturnId']/text()"/>
        </argument>
        <argument>
          <xsl:value-of select="./@documentId"/>
        </argument>
        <argument>
          <xsl:value-of select="./@documentName"/>
        </argument>
        <argument>
          <xsl:copy-of select="."/>
        </argument>
      </arguments>
    </xsl:for-each>
  </dp:sql-execute>
</xsl:template>
...
```

- Performs a batch **SELECT** operation for an SQL statement. Uses an `<xsl:for-each>` element as the trigger.

```
...
<xsl:output indent="yes" encoding="UTF-8" version="1.0" method="xml"/>

<xsl:template match="/*[local-name()='Return']">
  <dp:sql-execute source="'DB2LUW95'"
    statement="'SELECT DOCUMENT FROM TBIRSMF WHERE RETURNID = ?'">
    <xsl:for-each select="*[local-name()='ReturnData']/*">
      <arguments>
        <argument>
          <xsl:value-of select="../*[local-name()='ReturnId']/text()"/>
        </argument>
      </arguments>
    </xsl:for-each>
  </dp:sql-execute>
</xsl:template>
...
```

- Uses parameter markers to call a stored procedure. This procedure has input, input-output, and output parameters.

```
...
<xsl:output indent="yes" encoding="UTF-8" version="1.0" method="xml"/>
```

```

<xsl:template match="/">
  <dp:sql-execute source="'DB2LUW95'" statement="'CALL MY_PROC(?,?,?)'">
    <arguments>
      <argument type="SQL_CHAR" mode="INPUT">
        <xsl:value-of select="//@title"/>
      </argument>
      <argument type="SQL_VARCHAR" mode="INPUT_OUTPUT">
        <xsl:value-of select="//@isbn"/>
      </argument>
      <argument type="SQL_XML" mode="OUTPUT"/>
    </arguments>
  </dp:sql-execute>
</xsl:template>
...

```

- Writes the error message to a variable.

```

<xsl:variable name="result">
  <dp:sql-execute statement "$Statement=" source="'DB2LUW95'">
    <!-- execute statement -->
  </dp:sql-execute>
</xsl:variable>
<xsl:choose>
  <xsl:when test="$result/sql[@result = 'error']">
    <!-- treat error - for example, write to variable -->
    <dp:set-variable value="$result/sql/message/text()"
      name="'var://service/error-message'">
  </xsl:when>
  <xsl:otherwise>
    <!-- format result -->
  </xsl:otherwise>
</xsl:choose>

```

strip-attachments

Removes an attachment from a message.

Availability

All products

Namespace declaration

```

xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"

```

Syntax

```

<dp:strip-attachments
  uri="attachmentURI"
  context="contextName" />

```

Attributes

uri="*attachmentURI*"

(xs:string) Identifies the attachment to strip from a message.

context="*contextName*"

(xs:string) Identifies the context, for example INPUT or OUTPUT, for stripping the attachment. If you do not specify a context name, the element defaults to the output of your transform action.

Guidelines

There are several different methods you can use to identify and strip an attachment from a message. You can construct the URI with Content-ID, Content-Location, and the thismessage protocol. Use thismessage with a Content-Location header. The most common method for referencing an attachment is to specify an attachment with a globally unique Content-ID header.

- To construct the URI with Content-ID, use the `cid:string` format that points to the attachment to strip.
- Alternatively, specify an absolute or relative reference to a Content-Location value that points to the attachment to strip.
 - To construct the URI with an absolute reference, use the `http://www.someplace.com/string` format. `http://www.someplace.com` must be defined as the Content-Location header in the message package.
 - To construct the URI with a relative reference, use the `/string` format. Use the relative reference method when there is no Content-Location header in the message package.
- You can also use the thismessage protocol to build the URI when there is no Content-Location header in the message package. To construct the URI with thismessage, use the `thismessage:string` format.

The element passes all attributes as AVTs.

Examples

- Uses Content-ID to strip an attachment.

```
⋮
<dp:strip-attachment URI="CID:ID1"/>
⋮
```
- Uses Content-Location and an absolute path to strip an attachment.

```
⋮
<dp:strip-attachment URI="http://www.someplace.com/locattach1"/>
⋮
```
- Uses Content-Location and a relative path to strip an attachment.

```
⋮
<dp:strip-attachment URI="locattach1"/>
⋮
```
- Uses thismessage protocol and Content-Location to strip an attachment.

```
⋮
<dp:strip-attachment URI="thismessage:locattach1"/>
⋮
```

url-open (generic)

Uses a specified protocol to send data to or receive data from an arbitrary URL.

Availability

All products (depending on the transport protocol)

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:url-open
  target="url"
  response="xml | binaryNode | ignore | responsecode |
    responsecode-ignore | savefile"
  resolve-mode="xml | ignore"
  base-uri-node="nodeSet"
  data-type="xml | ignore"
  http-headers="xpathExpression"
  content-type="contentType"
  ssl-proxy="sslProxyName"
  timeout="timerValue">
</dp:url-open>
```

Attributes

target="url"

(xs:string) Identifies the target URL of the message destination or the message source. dp:url-open supports the following protocols:

- FTP (File Transfer Protocol) — Available on all models
Refer to “url-open (FTP URLs)” on page 39 for URL information.
- HTTP/HTTPS (Hypertext Transfer Protocol) — Available on all models
- ICAP (Internet Contents Adaptation Protocol) — Available on all models
Refer to “url-open (ICAP URLs)” on page 41 for URL information.
- IMS (Information Management System) — Available on specifically licensed XI50 models only
Refer to “url-open (IMS Connect)” on page 42 for URL information.
- MQ (WebSphere Network Communication Protocol) — Available on XI50 models only
Refer to “url-open (MQ URLs)” on page 45 for URL information.
- NFS (Network File System) — Available on all models
Refer to “url-open (NFS URLs)” on page 48 for URL information.
- SMTP (Simple Mail Transfer Protocol) — Available on all models
Refer to “url-open (SMTP URLs)” on page 49 for URL information.
- SNMP (Simple Network Management Protocol) — Available on all models
Refer to “url-open (SNMP URLs)” on page 50 for URL information.
- SQL (Structured Query Language) — Available on specifically licensed XI50 models only
Refer to “url-open (SQL URLs)” on page 51 for URL information.
- TCP (Transmission Control Protocol) — Available on all models
Refer to “url-open (TCP URLs)” on page 52 for URL information.
- TIBCO EMS (TIBCO Enterprise Message Services) — Available on licensed XI50 models only
Refer to “url-open (TIBCO EMS URLs)” on page 53 for URL information.
- WebSphere JMS (WebSphere Java™ Messaging Services) — Available on XI50 models only
Refer to “url-open (WebSphere JMS URLs)” on page 55 for URL information.
- WebSphere MQ (IBM WebSphere MQ Protocol) — Available on XI50 models only

Refer to “url-open (FTP URLs)” on page 39 for URL information.

response="xml | binaryNode | ignore | responsecode | responsecode-ignore | savefile"

(xs:string) Optionally specifies how the appliance handles the response (if any) from the target URL.

xml (Default) Indicates that the appliance parses the response as XML

binaryNode

Indicates that the appliance treats any received response from the target URL as non-parsed binary data

ignore

Indicates that the appliance ignore any response received from the target URL

responsecode and responsecode-ignore

Enable testing of received protocol status codes

responsecode

For testing HTTP transmissions.

- All successful HTTP transactions return the following element, when you set the **response** attribute to responsecode:

```
<url-open>
  <responsecode>200</responsecode>
</url-open>
```

- All failed HTTP transactions return the following element, when you set the **response** attribute to responsecode:

```
<url-open>
  <responsecode>500</responsecode>
</url-open>
```

- All successful MQ transactions return the following element, when you set the **response** attribute to responsecode:

```
<url-open>
  <responsecode>0</responsecode>
</url-open>
```

- All failed MQ transactions typically return one of the following elements when you set the **response** attribute to responsecode:

2009 Cannot access queue

2059 Cannot establish connection

```
<url-open>
  <responsecode>2059</responsecode>
</url-open>
```

- All successful FTP transactions return the following element, when you set the **response** attribute to responsecode:

```
<url-open/>
```

- All failed FTP transactions return the following element, when you set the **response** attribute to responsecode:

```
<url-open>
  <response> ... returned data ... </response>
</url-open>
```

responsecode-ignore

For testing MQ **PUT** operations.

- All successful HTTP transactions return the following element, when you set the **response** attribute to `responsecode-ignore`:

```
<url-open>
  <responsecode>200</responsecode>
</url-open>
```
- All failed HTTP transactions return the following element, when you set the **response** attribute to `responsecode-ignore`:

```
<url-open>
  <responsecode>500</responsecode>
</url-open>
```
- All successful MQ transactions return the following element, when you set the **response** attribute to `responsecode-ignore`:

```
<url-open>
  <responsecode>0</responsecode>
</url-open>
```
- All failed MQ transactions typically return one of the following elements, when you set the **response** attribute to `responsecode-ignore`:

```
2009    Cannot access queue
2059    Cannot establish connection
<url-open>
  <responsecode>2059</responsecode>
</url-open>
```
- All successful FTP transactions return the following element, when you set the **response** attribute to `responsecode-ignore`:

```
<url-open/>
```
- All failed FTP transactions return the following element, when you set the **response** attribute to `responsecode-ignore`:

```
<url-open>
  <statuscode>n</statuscode>
</url-open>
```

savefile

Indicates that the appliance saves any response from a target URL in the default domain temporary: directory. The appliance saves responses in a file named `temp_0000n`, and the value of *n* increments with each save operation. Saving the response in its original state does not effect any subsequent style sheet-based manipulation of the response data.

Note: The appliance does not provide a provision to limit or purge temporary files. You must purge temporary files before they consume available storage space.

Refer to the Guidelines section for additional information on the format of received data.

resolve-mode="xml | swa"

(`xs:string`) Is optional and meaningful only if the target URL points to an attached document.

swa Indicates that the target URL is a SOAP with Attachments document.

If you set **resolve-mode** to `swa`, `<url-open/>` attempts to resolve the URL as an attachment. For example, the element returns any attachment whose `Content-Location` header matches the target URL.

If `<url-open/>` does not locate a SOAP with Attachments document, or it cannot find a URL/Content-Location match, the element stops processing (ignoring any other attributes you might have specified).

`xml` (Default) Indicates a non-SWA operational environment.

base-uri-node="*nodeSet*"

(a node set) Is similar to the base URI argument for the **document()** function. If the target URL is relative, the extension element uses the first node in the specified node set to determine the base URI (according to the XML base mechanism). If you do not specify a node set, `<url-open/>` uses the current node in the input document to determine the base URI.

data-type="xml | base64 | filename"

(`xs:string`) Describes the input data to the extension element.

`xml` (Default) Indicates that the input data is XML.

`base64`

Indicates that the input data is Base64 encoded and the extension element decodes the data before it resumes further processing.

`filename`

Indicates that a local file contains the input data and the extension element content identifies the target file. For example:

```
<url-open target="www.datapower.com/application.jsp">
  local://myFile
</url-open>
```

http-headers="*nodeSet*"

(node set) Specifies HTTP headers that you can append to this connection. The node set you pass to the extension element can contain one or more `<header>` elements with a `name` attribute that specifies the name of the HTTP header. The content of the header element specifies the value of the HTTP header.

For example:

```
<xsl:variable name="headerValues">
  <header name="SOAPAction">ClientRequest</header>
  <header name="Stuff">OK</header>
</xsl:variable>
```

content-type="*contentType*"

(`xs:string`) Optionally specifies the value you can place in the HTTP Content-Type header.

ssl-proxy="*sslProxyName*"

(`xs:string`) Optionally identifies an SSL Proxy Profile that this extension element can use to establish a secure (SSL-enabled) connection to the target URL.

If you do not specify a value for this attribute, `dp:url-open` uses the current User Agent mappings for SSL connections.

The element does not use this attribute for SQL connections.

timeout="*timerValue*"

(`xs:string`) optionally specifies an integer value, in seconds, for the backend timeout. Use an integer in the range of 1 through 86400. Use a value of -1 to use the current default value set by a User Agent or the system default of 300 seconds, if the User Agent does not have a configured timeout.

A timeout occurs in the following cases:

- The appliance cannot establish a connection within the timeout period for an initial connection.
- An established connection is idle for longer than the timeout period.

Guidelines

The appliance serializes and sends all the values you specify inside the `dp:url-open` element to the target URL. If you specify `xml` for the **response** attribute, the appliance parses the response from the target URL and inserts the content in the output for the `dp:url-open` element. If you specify `ignore` for the **response** attribute, the appliance discards any response from the target URL and does not produce output.

The semantics for send and receive depend on the type of URL. For HTTP, send corresponds to a client **POST** and receive corresponds to the server response.

If you do not specify content in the `dp:url-open` element, the appliance performs an HTTP **GET** instead of a POST.

Some protocols (for example, SMTP) might not support the retrieval of data.

If you specify a `BasicAuth` header using the **http-headers** attribute, it has a higher priority than a `BasicAuthPolicy` configured with User Agent Configuration.

The `dp:url-open` element passes the **target**, **data-type**, **content-type**, and **ssl-proxy** attributes (all of type `xs:string`) as AVTs. It also passes the **response** and **resolve-mode** attributes (both of type `xs:string`) as literals and the `base-uri-node` and **http-headers** attributes (both node sets) as XPath expressions.

Received Data Format:

- If the **response** attribute characterizes the response data received from the target URL as `xml` or omitted, the element outputs the returned data as parsed XML.
- If the **response** attribute characterizes the response data received from the target URL as `responsecode` or `savefile`, the element outputs the returned data in the following format.

```
<url-open>
  <statusCode>0</statusCode>
  <responsecode>0</responsecode>
  <errorcode>0</errorcode>
  <errorstring>error</errorstring>
  <contenttype>text/xml</contenttype>
  <headers>
    <header name="contenttype">text/xml</header>
  :
    <header name="foo">bar</header>
  </headers>
  <response> ... returned data ... </response>
</url-open>
```

- If the **response** attribute characterizes the response data received from the target URL as `responsecode-ignore` (meaning to ignore any response data), the element outputs the returned data in the following format.

```
<url-open>
  <statusCode>0</statusCode>
  <responsecode>0</responsecode>
  <errorcode>0</errorcode>
  <errorstring>error</errorstring>
```

```

<contenttype>text/xml</contenttype>
<headers>
  <header name="contenttype">text/xml</header>
  :
  <header name="foo">bar</header>
</headers>
</url-open>

```

- If the **response** attribute characterizes the response data received from the target URL as `binaryNode` or `ignore`, the element fetches binary input without an XML parse. The element outputs the returned data in the following format.

```

<result>
  <statusCode>0</statusCode>
  <binary> ... binary data ... </binary>
</result>

```

Examples

- HTTP examples:
 - The `dp:url-open` element sends a serialized copy of the content of `$some-nodes` to `http://www.datapower.com/application.jsp`. The element parses the response and saves the output in the `$jsp-response` variable.


```

<xsl:variable name="jsp-response">
  <dp:url-open target="http://www.datapower.com/application.jsp">
    <xsl:copy-of select="$some-nodes">
  </dp:url-open>
</xsl:variable>

```
 - The `dp:url-open` element does not send any content to the target URL. Similar to a `Get` and `Put` action, the element parses the response, `foo.xml`, and inserts the file into the output. This example of `dp:url-open` usage is similar to a `document()` call, except the element inserts the response directly into the output.


```

<dp:url-open target="http://www.datapower.com/foo.xml"/>

```
 - The `dp:url-open` element specifies a relative URL, so the element uses the base URI of the `/doc` node in the input document. The base URI defines a location from which the element can open files. For example, if the URI were `http://www.yahoo.com`, the element would fetch `http://www.yahoo.com/foo.xml`

```

<dp:url-open target="foo.xml" base-uri-node="/doc"/>

```
 - The `dp:url-open` element posts some data to a mythical application, `draw-a-gif.jsp`. The application returns a gif file, which the element ignores and does not attempt to parse as XML.


```

<dp:url-open target="http://www.datapower.com/draw-a-gif.jsp"
  response="ignore">
  :
</dp:url-open>

```
 - The `dp:url-open` element specifies `httpHeaders` that you can append to this connection. The node set you pass to the extension element contains two `<header>` elements with `name` attributes that specify the name of the HTTP header. The content of the header elements specify the values of the HTTP headers.


```

<xsl:variable name="httpHeaders">
  <header name="SOAPAction">doit</header>
  <header name="Stuff">andjunk</header>
</xsl:variable>

```

```

<dp:url-open target="http://127.0.0.1:9070/foo" response="xml"
  http-headers="$httpHeaders">
  <xsl:copy-of select="$call"/>
</dp:url-open>

```

- ICAP Example:

- Uses dp:url-open to send material to a virus-scan service. The element scans the service response, written to the \$attachment variable, for a 403 response code. If the element detects a 403 response code, indicating the presence of a virus, it rejects the message. Receipt of a 200 or 204 response code results in message acceptance.

Note the use of AVT syntax with the target attribute.

```

<?xml version="1.0"?>
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:dpconfig="http://www.datapower.com/param/config"
  extension-element-prefixes="dp"
  exclude-result-prefixes="dp dpconfig"
  version="1.0">

  <xsl:output method="xml"/>

  <xsl:variable name="location" select="content-location=pic"/>

  <!-- how to specify binary attachments? -->
  <xsl:variable name="binarydata">
    <dp:url-open target="{concat($location,'?Encode=base64')}" />
  </xsl:variable>

  <xsl:variable name="httpHeaders">
    <header name="Host">127.0.0.1</header>
    <header name="Allow">204</header>
  </xsl:variable>

  <!-- Reject by default -->
  <dp:reject>Could not scan</dp:reject>
  <xsl:variable name="attachment">
    <dp:url-open target="icap://x.xx.xx.xx:nn/AVSCAN?action=SCAN"
      response="responsecode" data-type="base64"
      http-headers="$httpHeaders">
      <xsl:value-of select="$binarydata/base64"/>
    </dp:url-open>
  </xsl:variable>

  <xsl:if test="$attachment/url-open/responsecode = '403'">
    <dp:reject override="true">Virus Found</dp:reject>
  </xsl:if>
  <xsl:if test="$attachment/url-open/responsecode = '200'">
    <dp:accept/>
  </xsl:if>
  <xsl:if test="$attachment/url-open/responsecode = '204'">
    <dp:accept/>
  </xsl:if>

```

- SMTP Example:

- Uses dp:url-open to send a mail message containing log information to a recipient on a SMTP mail server.

```

<xsl:variable name="log-message">
  <MyError>
    <Date>
      <xsl:value-of select="date:date()" />
    </Date>
    <Time>
      <xsl:value-of select="date:time()" />
    </Time>
  </MyError>

```

```

    <Domain>
      <xsl:value-of select="dp:variable('var://service/domain-name')" />
    </Domain>
    <TransactionID>
      <xsl:value-of select="dp:variable('var://service/transaction-id')" />
    </TransactionID>
    <ErrorCode>
      <xsl:value-of select="dp:variable('var://service/error-code')" />
    </ErrorCode>
    <ErrorMessage>
      <xsl:value-of select="dp:variable('var://service/error-message')" />
    </ErrorMessage>
    <Payload>
      <!-- show request sent -->
      <xsl:copy-of select="*" />
    </Payload>
  </MyError>
</xsl:variable>

  <!-- send log to remote location -->
  <dp:url-open target="smtp://9.56.228.182/?Recpt=joedoe%40us.ibm.com
&Sender=drecluse%40us.ibm.com
&Subject=DP-Error-Dev" response="responsecode">
    <xsl:copy-of select="$log-message" />
  </dp:url-open>

```

- SQL Example:

- Sends a SQL request to a SQL data source. Cambridge_DB2 is the name of the SQL data source object on the DataPower appliance.

```

<xsl:variable name="selectStmt">
  SELECT name FROM table where id=6
</xsl:variable>
<dp:url-open target="sql//:Cambridge_DB2/static?$selectStmt"/>
</xsl:variable>

```

- TIBCO EMS Example:

- Uses dp:url-open to send a message to a TIBCO EMS request queue. Note that style sheet reflects the names and values of the TIBCO EMS headers in the http-headers attribute.

```

<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:dpconfig="http://www.datapower.com/param/config"
  extension-element-prefixes="dp"
  exclude-result-prefixes="dp dpconfig">

  <xsl:output method="xml"/>
  <xsl:template match="/">
    <xsl:copy-of select="." />

    <xsl:variable name="headers">
      <header name="DP_EMSType">text</header>
      <header name="UBER">VERY</header>
      <header name="UnTO">NUNCA</header>
    </xsl:variable>

    <dp:url-open target="dptibems://tibems/?RequestQueue=Vecchio"
      http-headers="$headers">
      TESTING TESTING2
    </dp:url-open>
  </xsl:template>

  – Uses dp:url-open to retrieve a message from a TIBCO EMS reply queue.
  :
  <xsl:variable name="msgContents">
    <dp:url-open target="dptibems://tibems/?ReplyQueue=Bernini">

```

```

        </dp:url-open>
      </xsl:variable>
      :
    
```

- WebSphere JMS Example:

- Uses dp:url-open to send a message to a WebSphere JMS request queue. The style sheet reflects the names and values of the WebSphere JMS headers in the http-headers attribute.

```

<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:dpconfig="http://www.datapower.com/param/config"
  extension-element-prefixes="dp"
  exclude-result-prefixes="dp dpconfig">

  <xsl:output method="xml"/>

  <xsl:template match="/">
    <xsl:copy-of select="."/>

    <xsl:variable name="headers">
      <header name="DP_JMSMessageType">text</header>
      <header name="UBER">VERY</header>
      <header name="UnTO">NUNCA</header>
    </xsl:variable>
    <dp:url-open target="dpwasjms://wasjms/?RequestQueue=Vecchio"
      http-headers="$headers">
      TESTING TESTING2
    </dp:url-open>
  </xsl:template>

  – Uses dp:url-open to retrieve a message from a WebSphere JMS reply queue.
  :
  :
  <xsl:variable name="msgContents">
    <dp:url-open target="dpwasjms://wasjms/?ReplyQueue="Bernini">
    </dp:url-open>
  </xsl:variable>
  :
  :

```

url-open (FTP URLs)

Syntax for FTP URLs with dp:url-open.

Availability

All products

Syntax

To specify a relative path from the user's home directory

ftp://user:password@host:port/URI?queryParameters

To specify an absolute path from the root directory

ftp://user:password@host:port/%2FURI?queryParameters

ftp://host:port/URI?queryParameters

Attributes

ftp Indicates the required protocol identifier.

user is a user ID on the target host.

You must encode a colon (":"), an at sign ("@"), or a forward slash ("/") if these characters appear in the user ID.

You can omit the user ID can if the target host supports anonymous login.

password

is the password corresponding to the user ID.

You must encode a colon (":"), an at sign ("@"), or a forward slash ("/") if these characters appear in the password.

You can omit the user password if the target host supports anonymous login.

host

is the fully qualified domain name or IP address of the target host.

port

optionally identifies the connection port on the host. The default is 21.

URI

for a **PUT** (write) operation specifies the remote location that receives the file. *URI* for a **GET** (read) operation specifies the location from which the element fetches the file.

The presence or absence of content within the `dp:url-open` element determines whether or not the semantics for `url-open` is a **PUT** or a **GET**. If the element contains content, it performs a **PUT**. If there is no content, the element performs a **GET**.

You must encode question mark "?" characters that appear in the path.

URI supports relative and absolute FTP paths.

- For example, the relative path `ftp://user@host/foo/bar.txt` puts or gets the file `bar.txt` that resides in the subdirectory `foo` of the default FTP directory for user.
- For example, the absolute path `ftp://user@host/%2Ffoo/bar.txt` puts or gets the file `bar.txt` that resides in the subdirectory `foo` of the root file system. Note that `%2F` is the URL-encoded value of `"/`.

queryParameters

Specifies name-value pairs that follow the URI. Use a question mark ("?",) character after the URI but before the first query parameter. Use an ampersand ("&") character between query parameters.

You must URL-encode the question mark ("?",) character within an URI with `%3F` if you do not want to signify a query parameter. The following example shows this URL encoding:

`http://host:port/something%3Fmore?sessionId=3`

CreateDir

Specifies a value that represents whether to create directories.

`false` (Default) Does not create directories specified by *URI* if they do not exist. Instead, fail the operation.

`true` create directories specified by *URI* if they do not exist. Meaningful only for an FTP **GET**.

Encoding

Specifies a value that represents whether to decode or encode data.

`base64` Decodes or encodes data using Base64.

- On **GET**, encodes binary data that is retrieved from the server.
- On **PUT**, decodes binary data placed on the server.

	<code>node</code> (Default) Does not encode data.
Type	Specifies a value that represents the type of data representation used for data transfer and storage.
	<code>ascii</code> Indicates ASCII mode.
	<code>bin</code> (Default) Indicates binary mode.

You can specify the previous query parameters (`CreateDir`, `Encoding`, and `Type`) with the defaults listed, by a user-agent FTP Policy, or by explicit assignment with query parameters. In case of conflicts, the resolution precedence is as follows:

1. Explicit assignment via query parameter
2. FTP Policy
3. Absolute defaults

`Delete` Specifies a value that represents whether to delete files.

<code>false</code>	(Default) Does not delete file.
<code>true</code>	Deletes the file specified by <i>URI</i> . Meaningful only for a GET . The returned XML is <code><?xml version="1.0" encoding="UTF-8"?><FTPDelete/></code> in this case.

`Rename=newName`

Specifies a value that represents whether to rename a file.

- On **GET**, renames the file first and then reads. If the rename fails, the read also fails.
- On **PUT**, writes the file first and then renames. This query parameter is useful for writing a file to a temporary location and then renaming the file.

Guidelines

RFC 959, *File Transfer Protocol (FTP)*, initially described the syntax for FTP URLs. You can obtain additional information regarding FTP URLs from RFC 1738, *Uniform Resource Locators (URL)*, RFC 2228, *FTP Security Extensions*, and RFC 4217, *Securing FTP with TLS*.

Examples

Uses `dp:url-open` for FTP URLs to place a message in the default FTP queue.

```

:
:
<xsl:variable name="ftp-put-url"
  select="'ftp://user1:123456@x.xx.xx.xxx/foo.xml'"/>
<dp:url-open target="{ $ftp-put-url }" response="ignore">
  <xsl:copy-of select=""/>
</dp:url-open>
:
:

```

url-open (ICAP URLs)

Syntax for ICAP URLs with `dp:url-open`.

Availability

All products

Syntax

icap://server:port/URI?parameters

Attributes

<i>icap</i>	Indicates the required protocol identifier.
<i>server</i>	Specifies the domain name or IP address of the target ICAP server.
<i>port</i>	Specifies the port number monitored by the ICAP server for incoming requests. If not specified, the default is 1344.
<i>URI</i>	Specifies a series of directories followed by a file name that identifies the requested service.
<i>parameters</i>	Specifies optional or required ICAP server or service-specific query parameters.

Guidelines

RFC 3507 describes ICAP (Internet Content Adaptation Protocol), which is an open standard commonly used to access antivirus servers. The ICAP protocol provides simple object-based content vectoring for HTTP services. ICAP is a lightweight protocol for executing a remote procedure call (RPC) on HTTP messages. It allows ICAP clients to pass HTTP messages to ICAP servers for some sort of transformation or other processing (adaptation). The server executes its transformation service on messages and sends back responses to the client.

The appliance uses ICAP to contact an antivirus server which scans documents (the element content) for viruses. The element content can include SOAP attachments in numerous file formats (including, but not limited to, MIME, DIME, ZIP, GZIP, BZIP2, and TAR) fetched from a remote FTP, NFS, or HTTP server. The *dp:url-open* element can also retrieve files from an MQ, TIBCO, or WAS-JMS queue.

url-open (IMS Connect)

Syntax for IMS™ Connect URLs with *dp:url-open*.

Availability

XI50 and XB60 only

Syntax

dpims://Connect-object/?parameters

dpimssl://Connect-object/?parameters

Attributes

dpims Identifies the required protocol identifier. Alternatively, use *dpimssl* to identify a secure (SSL-enabled) connection.

Connect-object

Specifies the name of an enabled IMS Connect object that was previously created with either the WebGUI or the command line. The object provides the necessary information to access a remote IMS Connect server.

parameters

Identifies query parameters. Use a question mark to denote the first query parameter and separate subsequent query parameters with a semicolon.

TranCode=code

Specifies the IMS transaction code. This is a required parameter. The default is an 8 character blank string.

DataStoreID=ID

Specifies the datastore name (IMS destination ID). This is a required parameter. The default is an eight-character blank string.

ExitID=ID

Specifies the identifier of the user exit reserved after a complete message is received. Use one of the following keywords:

IRMREQ Identifies HWSIMS00.

IRMRE1 Identifies HWSIMS01.

SAMPLE (Default) Identifies HWSSMPL0.

SAMPL1 Identifies HWSSMPL1.

HWSJAV Identifies HWSJAVA0.

HWCSCL Identifies HWCSCL00.

ClientIDPrefix=prefix

If not blank, generates a client ID for the request with the supplied prefix. The default is a two-character blank string. This parameter does not correspond to an IMS Connect header.

ClientID=ID

Specifies the name of the client ID that IMS Connect uses. If not supplied by *ClientIDPrefix* or the client, the user exit must generate it. If *ClientIDPrefix* is also supplied, the appliance ignores the *ClientID* value and generates client ID with *ClientIDPrefix*. The default is an 8 character blank string.

RACFUserID=ID

Specifies the Resource Access Control Facility (RACF®) user ID. To use RACF, which is security functionality that controls access to IMS resources, the appliance must provide the RACF ID. The default is an eight-character blank string.

RACFGroupName=groupname

Specifies the RACF group name. To use RACF, the appliance must provide the RACF group name. The default is an eight-character blank string.

Password=password

Specifies the RACF password or PassTicket. To use RACF, the appliance must provide the RACF password. The default is an eight-character blank string.

LtermName=Lterm

Specifies the name of a logical terminal. The default is an eight-character blank string.

Timer=duration

Specifies the appropriate wait time for IMS to return data to the IMS Connect server. The default is 0 (infinite time).

EncodingScheme=*scheme*

Specifies the Unicode encoding schema. Use one of the following values:

- 0 (Default) No encoding schema.
- 1 Uses the UTF-8 schema
- 2 Uses the UCS-2 schema or UTF-16 schema

PersistentSocket=*value*

Specifies the type of client socket connection. Use one of the following values:

- 0 Identifies a transaction socket. The socket connection last across a single transaction.
- 1 Identifies a persistent socket. The socket connection last across multiple transactions.

EBCDIC=*value*

Specifies whether an ASCII-to-EBCDIC conversion needs to be performed on header data so that an IMS application can interpret the data. This parameter does not correspond to an IMS Connect header field. Use one of the following values:

- 0 Identifies that conversion to EBCDIC is not needed.
- 1 (Default) Identifies that conversion to EBCDIC is needed.

Conversion of message content must be done as input to the appliance or as a binary transform (xformbin) action in the processing policy.

Guidelines

IMS Connect provides high performance communications for IMS between one or more TCP/IP clients and one or more IMS systems. IMS Connect provides commands to manage the communication environment. The appliance sends messages using TCP/IP to IMS Connect. An IMS Connect request message consists of a header, message content, and a footer. The appliance constructs the header from the supplied parameters. The request message consists of binary data in the following format

LLZZDATA

where:

LLZZ Specifies the total length of the segment. Includes LL (length) and ZZ (binary zeroes).

DATA Specifies the IMS transaction code followed by transaction data

IMS Connect receives response messages from the datastore and passes them back to the appliance. Because IMS Connect is a binary protocol, the response parameter must be binaryNode.

An example of an IMS Connect URL is:

dpims://xxx.xxx.xxx.xxx:nnnn/?TranCode=IVTN0;DataStoreID=IMS1;PersistentSocket=0

Alternatively, you can substitute the following URL for the previous one to define *host*, *port*, *DataStoreID*, and *PersistentSocket* in an *IMS-object*:

dpims://IMSConnectObject/?TranCode=IVTN0

Examples

The following example captures binary data in an XML node and sends to URL-open for processing. URL-open calls IMS Connect and stores the output response in the \$tmp variable. The imsout context variable holds the output response for further manipulation.

```
⋮
<xsl:variable name='_root' select='/'/>
<xsl:template match='/' mode="imsurl-open.xml">
  <xsl:variable name="tmp">
    <dp:url-open target="dpims://xxx.xxx.xxx.xxx:nnnn/?TranCode=IVTN0;
      DataStoreID=IMS1;ExitID=*IRMREQ*" response="binaryNode">
      <xsl:copy-of select="$_root/BLOB[1]/blob[1]/node()" />
    </dp:url-open>
  </xsl:variable>
  <dp:set-variable name="'var://context/imsout'"
    value="$tmp/result/binary/child::node()" />
⋮
```

url-open (MQ URLs)

Syntax for MQ URLs with dp:url-open.

Availability

All products with WebSphere MQ support

Syntax

Static URL to send a message

```
dpmq://mqQueueManagerObject/
URI?RequestQueue=requestQueueName;queryParameters
```

Static URL to retrieve a message

```
dpmq://mqQueueManagerObject/
URI?ReplyQueue=replyQueueName;queryParameters
```

Dynamic URL to send or retrieve a message

```
mq://host:port?MQQueueMgr=queueManager;
UserName=username;Channel=channelName;ChannelTimeout=channelTimeout;
channelLimit=channelLimit; MaximumMessageSize=maxMsgSize
;queryParameters
```

Attributes

- dpmq Indicates the required protocol identifier for a static MQ backend. For a secure connection, you must use the **ssl-proxy** attribute to identify the instance of the SSL Proxy Profile object that supports the secure connection.
- mq Identifies the required protocol identifier for a dynamic URL.
- mqQueueManagerObject Specifies the name of a static MQ Queue Manager object stored on the appliance. The object provides the connection information needed to access a remote MQ Queue Manager that provides messaging services for communicating applications.
- URI Specifies the URI portion of the path to the target queue.

host Specifies the dotted decimal IP address or the host name of the target MQ server.

port Specifies the associated port on the target MQ server.

QueueManager=QueueManagerName
Specifies the name of an existing MQ Queue Manager object. The object provides the necessary information to access a remote MQ server.

UserName=user
Specifies the plaintext string to identify the client to the MQ server.

Channel=channelName
Specifies the name of the channel, defined in MQ, to connect to the MQ Queue Manager.

ChannelTimeout=timeout
Specifies an integer that specifies the number of seconds that the DataPower appliance retains (keeps alive) a dynamic connection in the connection cache. Specify a value that is greater than the negotiated heartbeat interval but less than the keep alive interval.

- The negotiated heartbeat interval is between the DataPower appliance and the backend MQ server.
- The keep alive (timeout) interval is on the backend MQ server. The KAIMT attribute on the MQ server defines the timeout value for a channel.

Not all channels have a defined, explicit keep alive interval on the MQ server. Some queue managers use an automatic timeout setting (the KAIMT attribute set to AUTO). In these cases, the keep alive interval is the negotiated heartbeat interval plus 60 seconds.

When an inactive connection reaches this threshold, the appliance removes that dynamic connection from the cache. When the cache no longer contains dynamic connections, the appliance deletes the dynamic queue manager. Without a dynamic queue manager, there is no connection with the backend MQ server.

ChannelLimit=maxChannels
Specifies the maximum number of open channels to allow between the appliance and the remote MQ Queue Manager. Use an integer in the range of 2 through 5000.

maxMsgSize
Specifies the maximum size of messages that the MQ Queue Manager accepts. Use an integer between 1024 bytes and 1 GB.

queryParameters
Specifies optional or required query parameters for static and dynamic URLs.

RequestQueue=requestQueueName
Specifies the name of the backend MQ request queue. This queue is where the client puts request messages. The URL must minimally contain either the request or reply queue name.

ReplyQueue=replyQueueName
Specifies the name of the backend MQ reply queue. This queue is where the client gets response messages.

TimeOut=timeout

Specifies the timeout value for a **GET** message operation in milliseconds.

Transactional={true|false}

Specifies a Boolean that specifies that URL open call executes as part of a transaction and requires a **COMMIT** or **ROLLBACK** operation when the processing policy completes.

Sync={true|false}

Optionally enforces transactional units of work in the communication. When true, the appliance does not consider the message to be successfully posted to a queue until it receives a response. In other words, the appliance performs a **COMMIT** operation after a **PUT** but before a **GET**. Within a unit of work, a message is made visible to other programs only when the program commits the unit of work.

GMO=optionsValue

Specifies an integer that identifies a field option for a MQ GMO **GET** operation. For example, 64 represents MQGMO_ACCEPT_TRUNCATED_MSG.

PMO=optionsValue

Optionally sets the value for MQPMO.Options. The value is a cumulative value in decimal format of all acceptable options. A value of 2052 (hexadecimal 0x0804) sets the following MQPMO options:

- MQPMO_NO_SYNCPOINT (decimal 4, hexadecimal 0x00000004)
- MQPMO_SET_ALL_CONTEXT (decimal 2048, hexadecimal 0x00000800)

The PMO parameter allows the user to set the MQPMO.Options field on the **MQPUT** call that is used to place the request message of the backend request queue. Table 2 lists the values that the MQ API defines.

Table 2. MQPMO.Options available for MQPUT calls

Option	Hexadecimal	Decimal
MQPMO_SYNCPOINT	0x00000002	2
MQPMO_NO_SYNCPOINT	0x00000004	4
MQPMO_NEW_MSG_ID	0x00000040	64
MQPMO_NEW_CORREL_ID	0x00000080	128
MQPMO_LOGICAL_ORDER	0x00008000	32768
MQPMO_NO_CONTEXT	0x00004000	16384
MQPMO_DEFAULT_CONTEXT	0x00000020	32
MQPMO_PASS_IDENTITY_CONTEXT	0x00000100	256
MQPMO_PASS_ALL_CONTEXT	0x00000200	512
MQPMO_SET_IDENTITY_CONTEXT	0x00000400	1024
MQPMO_SET_ALL_CONTEXT	0x00000800	2048
MQPMO_ALTERNATE_USER_AUTHORITY	0x00001000	4096
MQPMO_FAIL_IF_QUIESCING	0x00002000	8192
MQPMO_NONE	0x00000000	0

By default, only MQPMO_NO_SYNCPOINT is set.

`MatchOptions=optionValue`

Specifies an integer that identifies a field MatchOption for a MQ GMO GET operation. Used to control the selection criteria for a GET operation, or how to retrieve a message from a queue. For example, you might retrieve a message by matching a MessageId or CorrelationId.

`ParseHeaders={true|false}`

Specifies a Boolean that parses and strips headers from message data.

`SetReplyTo={true|false}`

Specifies a Boolean that sets the ReplyToQ MQMD header value for a request message placed to the backend (PUT operation).

`Browse={first|next|current}`

Used with the ReplyQueueName parameter to browse (retrieve without removing) messages from a queue. Use one of the following values:

`first` Browses the first message in a queue

`next` Steps through many messages in incremental order on the queue. For example, if you specify next after browsing message one, url-open returns message two. Specifying next on the first url-open attempt reads the first message in the queue.

`current`

Reads the last message retrieved from the queue.

`ContentTypeHeader=header`

Specifies the name of the MQ header that identifies the content type of the message data.

`ContentTypeXPath=expression`

Specifies an XPath expression to run on parsed MQ header (specified in ContentTypeHeader parameter) to extract the content type of the message data.

Guidelines

Use the URL formats to send and to retrieve messages from a backend MQ system using either a static or a dynamic URL. The static URL for sending or retrieving messages uses a fixed server address that is defined in a MQ Queue Manager object on the appliance.

The URL formats require a prior configuration of an MQ Queue Manager object whose configuration properties provide the information (for example, host name and channel name) that is required to access the MQ server. In the absence of a locally-configured MQ Queue Manager object, use an alternative URL format to establish a dynamic connection to an MQ server.

url-open (NFS URLs)

Syntax for NFS URLs with `dp:url-open`.

Availability

All products

Syntax

`dpnfs://host:port/URI`

Attributes

`dpnfs` Indicates the required protocol identifier.

`host` Specifies the fully qualified domain name or IP address of the target host.

`port` Specifies the port to which to connect. If not specified, the default is 2049.

`URI` Specifies a hierarchical directory path.

`/directory/.../file`

Specifies a URI that is relative to the user's home directory.

`//directory/.../file`

Specifies an absolute URI from the directory root (".").

The path can contain only characters in the ASCII character set. Within a *directory* or *file* component, you must encode the reserved forward slash character ("/") as described in Section 2.2 of RFC 1738.

Guidelines

It is possible to employ parameters in the `dpnfs:` syntax. The following example includes parameters:

`dpnfs://fred/test.xml?a=b&c=d`

Note: When you specify parameters in the URL syntax, the appliance will first attempt to open a file with a name that includes the parameter specifications. If that fails, the appliance will then attempt to open the file using the name specified prior to the ? in the URL.

NFS URLs are described in RFC 2224, *NFS URL Scheme*.

All NFS operations from the DataPower appliance are done under UID 0 and GID 0.

url-open (SMTP URLs)

Syntax for SMTP URLs with `dp:url-open`.

Availability

All products

Syntax

`smtp://mailExchangerName/?Recpt=msgRecipient`

`smtp://msgRecipient@mailExchangerName/queryParameters`

Attributes

`smtp` is the required protocol identifier.

`mailExchangerName`

is the IP address or domain name of an SMTP server.

msgRecipient

is the URL-escaped email address of the message recipient. For example, you specify johndoe@us.ibm.com as address:

johndoe%40us.ibm.com

queryParameters

are name-value pairs that provide arguments to the URL. Use an ampersand symbol (&), not the ampersand (&) character, before the first query parameter and between query parameters. You must URL-encode special characters in query parameters.

Domain=smtpClientID

Provides the argument to the SMTP **HELO** (HELLO) command that the element uses to identify the SMTP client to the SMTP server. Conventionally, you specify the fully qualified domain name of the SMTP client if one is available. If you do not specify this query parameter, the element uses the IP address of the sending interface as the client identifier.

MIME=true | false

Enables (true) or disables (the default, false) MIME (Multipurpose Internet Mail Extensions) formatting. MIME formatting of the message body enables:

- Textual message bodies in character sets other than ASCII.
- Extensible set of different formats for non-textual message bodies.
- Multipart message bodies.
- Textual header information in character sets other than ASCII.

Recpt=destinationEmailAddress

Provides the contents of the To header in the email message.

Sender=returnAddress

Provides the argument to the SMTP **MAIL FROM** command. Use *returnAddress* to specify the contents of the From header in the email message.

Subject=subjectText

Provides the contents of the Subject header in the email message.

Guidelines

You can construct a full SMTP URL as follows:

```
smtp://m81bw03.qpl.ibm.com/?Recpt=richroe%40us.ibm.com
&Sender=johndoe%40us.ibm.com&Subject=Re%3A%20Your%20Previous%20Request%20
&Domain=johndoe.cambridge.ibm.com
```

The URL could be then used as follows:

```
<dp:url-open target="smtp://m81bw03.qpl.ibm.com/?Recpt=richroe%40us.ibm.com
&Sender=johndoe%40us.ibm.com&Subject=Re%3A%20Your%20Previous%20Request%20
&Domain=johndoe.cambridge.ibm.com" response="ignore">
  <xsl:copy-of select="$predefined-variable"/>
</dp:url-open>
```

url-open (SNMP URLs)

Syntax for SNMP URLs with dp:url-open.

Availability

All products

Guidelines

Use `dp:url-open` to transmit SNMP traps to specified SNMP users and logging recipients. SNMP traps are alerts or notifications generated by agents on a managed appliance. The appliance is responsible for constructing the required URL.

Refer to the *IBM WebSphere DataPower SOA Appliances: Administrators Guide* for instructions on generating SNMP traps.

url-open (SQL URLs)

Syntax for SQL URLs with `dp:url-open`.

Availability

All products with SQL/ODBC support

Syntax

`sql://datasource/derivation?statement`

Attributes

`sql` Indicates the required protocol identifier.

datasource

Specifies the name of an enabled SQL Data Source object previously created with either the WebGUI or the command line. The object provides the necessary information to access a remote database.

derivation

Specifies a keyword that specifies the method used to derive the SQL. Use one of the following values:

`static` The SQL statement is a string that follows the `static` keyword. Do not enclose in quotes.

`stylesheet`

Derives the SQL statement by executing a style sheet against the contents of the action input context. Specify the name of the style sheet.

`variable`

A specified multistep variable (not XSL) that contains the SQL statement

statement

With *derivation* provides the SQL statement.

- If *derivation* is `static`, *statement* contains the SQL statement. The SQL statement runs against the database referenced by *datasource*.
- If *derivation* is `stylesheet`, *statement* contains the location of a local style sheet that the element uses to derive the SQL statement. Use the format `localDirectory:///filename` to express the location of the style sheet. The SQL statement runs against the database referenced by *datasource*.

- If *derivation* is variable, *statement* identifies the multistep variable (not XSL) that contains the SQL statement. Use the format *variableType?variableName* to express the variable. The SQL statement runs against the database referenced by *datasource*.

Guidelines

SQL URLs are implementation specific because a standard format for SQL URLs does not currently exist. The **sql-execute()** function also lets you access a database without constructing a SQL URL.

Examples

- The following example extracts EmployeeID from the Managers table.
sql://dbObject-Oracle1/static?SELECT EmployeeID FROM Managers
- The following example derives a SQL statement by transforming the contents of the action input context with the sqlXformcontext.xml style sheet in the store: directory.
sql://dbObject-Oracle1/stylesheet?store:///sqlXformcontext.xml
- The following example uses the SQL statement contained in the session/sqlKey variable to run against the database referenced by dbObject-Oracle1.
sql://dbObject-Oracle1/variable?session/sqlKey

url-open (TCP URLs)

Syntax for TCP URLs with dp:url-open.

Availability

All products

Syntax

tcp://ipAddress:portNumber/

Attributes

tcp is the required protocol identifier.

ipAddress

is the IP address of the target TCP process.

portNumber

is the port number monitored by the target TCP process.

Examples

The following dp:url-open example sends a serialized copy of \$raw-xml to 192.168.13.45:3071. The \$raw-xml variable contains raw (unencapsulated) XML with no headers or preamble of any sort. The element saves the raw XML response in the \$raw-response variable.

```
<xsl:variable name="raw-response">
  <dp:url-open target="192.168.13.45:3071">
    <xsl:copy-of select="$raw-xml">
  </dp:url-open>
</xsl:variable>
```

url-open (TIBCO EMS URLs)

Syntax for the TIBCO EMS URL with `dp:url-open`.

Availability

All products with TIBCO EMS support

Syntax

Static URL to send a message to a request queue or to a request topic space
`dptibems://server-object/?RequestQueue=queue;RequestReply=queue;
query-parameters`

Static URL to retrieve a message from a reply queue or from a reply topic space
`dptibems://server-object/?ReplyQueue=queue;query-parameters`

Dynamic URL to send a message to a request queue or to a request topic space
`tibems://host:port?UserName=user;Password=password;
ClientID=identifier;RequestQueue=queue;RequestReply=queue;
query-parameters`

Dynamic URL to retrieve a message from a reply queue or from a reply topic space
`tibems://host:port?UserName=user;Password=password;
ClientID=identifier;ReplyQueue=queue;query-parameters`

Attributes

`dptibems`

Identifies the required protocol identifier for a static URL. Alternatively, use `dptibemss` to identify a secure (SSL-enabled) connection.

`tibems` Identifies the required protocol identifier for a dynamic URL.

`server-object`

Specifies the name of an enabled TIBCO EMS object that was previously created either from the WebGUI or from the command line. This object provides the information to access the remote EMS server.

If the protocol identifier specifies a secure connection, use the **ssl-proxy** command to identify the SSL Proxy Profile that supports the secure connection.

`host` Specifies the dotted decimal IP address or the host name of the server.

`port` Specifies the associated port on the server. The default is 7222.

`UserName=user`

Specifies the plaintext string to identify the account to use to access the server.

`Password=password`

Specifies the password for the user account.

`ClientID=identifier`

Specifies the plaintext string to identify the client connection.

`RequestQueue=queue`

Specifies the name of the EMS request queue or topic space that receives the message.

- To specify a queue, use the `RequestQueue=queue` format.

- To specify a topic space, use the `RequestQueue=topic:topic-space` format.

`RequestReply=queue`

Indicates that the reply from the server will be placed on a temporary queue. The `RequestReply` parameter is relevant only when the request queue is defined. If the `RequestReply` parameter and the reply queue are both defined, the DataPower service uses the temporary queue.

`ReplyQueue=queue`

Specifies the name of the EMS reply queue or topic space that contains the message to be retrieved.

- To specify a queue, use the `ReplyQueue=queue` format.
- To specify a topic space, use the `ReplyQueue=topic:topic-space` format.

`query-parameters`

Specifies optional query parameters.

`selector=expression`

Defines a SQL-like expression to select messages from the reply queue. This query parameter cannot be used with topic spaces or with the request queue.

The message selector is a conditional expression based on a subset of SQL 92 conditional expression syntax. The conditional expression enables the `dp:url-open` element to identify messages of interest.

If you specify a message selector, the element retrieves the first queue message that matches the criteria specified by the SQL expression.

`Timeout=timer`

Specifies the operational timeout in milliseconds.

Guidelines

In messaging systems, queues are for point-to-point while topics are for publish and for subscribe.

With a dynamic URL, the host-port pair can be a collection of load-balanced, fault-tolerant, or load-balanced and fault-tolerant servers.

- To specify a unique server, use the `host:port` format.
- To specify a pair of fault-tolerant server, separate the host-port pair with a comma. In other words, use the following format:

`host-1:port-1,host-A:port-A`

- To specify a set of load-balanced servers, separate each host-port pair with a vertical bar. In other words, use the following format:

`host-1:port-1|host-2:port-2`

- To specify a set of load-balanced servers with fault-tolerance, use the following format:

`host-1:port-1,host-A:port-A|host-2:port-2,host-B:port-B`

In this situation, load-balancing takes precedence over fault-tolerance.

The selector conditional expression examines the required EMS headers and EMS properties (proprietary user-created headers that might appear between the required headers and the message body). The selector conditional expression does not operate on the body of the message.

The required headers are as follows:

Destination

Contains the queue name that is the destination of the request message.

DeliveryMode

Contains the delivery mode (PERSISTENT or NON_PERSISTENT).

Expiration

Contains a message TTL (time to live) or a value of 0 indicating an unlimited TTL.

Priority

Contains the message priority expressed as a digit from 0 (lowest priority) to 9 (highest priority).

MessageID

Contains a unique message identifier starting with the prefix ID: string or a null value. A null value effectively disables the message ID.

Timestamp

Contains the time the message was handed off for transmission, not the time it was actually sent.

CorrelationID

Contains a means of associating one message (for example, a response) with another message (for example, the original request).

ReplyTo

Contains the queue name that is the destination of the reply to message.

Type

Contains a message identifier provided by the application.

Redelivered

Contains a Boolean that indicates that the message was delivered, but not acknowledged.

To create an expression that matches the first nonpersistent message in the queue with a priority of 9, the selector query parameter would be as follows:

`selector="Priority='9' and DeliveryMode like NON_PERSISTENT"`

url-open (WebSphere JMS URLs)

Syntax for the WebSphere JMS URL with `dp:url-open`.

Availability

All products with WebSphere JMS support

Syntax

Static URL to send a message to a request queue

`dpwasjms://server-object/?RequestQueue=queue;RequestReply=queue;
query-parameters`

Static URL to send a message to a request topic space

`dpwasjms://server-object/?RequestTopicSpace=topic-space;
RequestReply=queue;query-parameters`

Static URL to retrieve a message from a reply queue

`dpwasjms://server-object/?ReplyQueue=queue;query-parameters`

Static URL to retrieve a message from a reply topic space
`dpwasjms://server-object/?ReplyTopicSpace=topic-space;
query-parameters`

Attributes

`dpwasjms`

Identifies the required protocol identifier. Alternatively, use `dpwasjmss` to identify a secure (SSL-enabled) connection.

server-object

Specifies the name of an enabled WebSphere JMS object that was previously created either from the WebGUI or from the command line. This object provides the information to access the remote JMS provider.

If the protocol identifier specifies a secure connection, use the **ssl-proxy** command to identify the SSL Proxy Profile that supports the secure connection.

`RequestQueue=queue`

Specifies the name of the JMS request queue that receives the message.

`RequestTopicSpace=topic-space`

Specifies the name of the JMS topic space that receives the message.

`RequestReply=queue`

Indicates that the reply from the server will be placed on a temporary queue. The `RequestReply` parameter is relevant only when the request queue is defined. If the `RequestReply` parameter and the reply queue are both defined, the DataPower service uses the temporary queue.

`ReplyQueue=queue`

Specifies the name of the JMS reply queue that contains the message to be retrieved.

`ReplyTopicSpace=topic-space`

Specifies the name of the JMS reply topic space that contains the message to be retrieved.

query-parameters

Specifies optional query parameters.

`selector=expression`

Defines a SQL-like expression to select messages from the reply queue. This query parameter cannot be used with topic spaces or with the request queue.

The message selector is a conditional expression based on a subset of SQL 92 conditional expression syntax. The conditional expression enables the `dp:url-open` element to identify messages of interest.

If you specify a message selector, the element retrieves the first queue message that matches the criteria specified by the SQL expression.

`Timeout=timer`

Specifies the operational timeout in milliseconds.

Guidelines

In messaging systems, queues are for point-to-point while topics are for publish and for subscribe.

The selector conditional expression does not operate on the body of the message, rather it examines the required JMS headers and JMS properties (proprietary user-created headers that can appear between the required headers and the message body).

The required headers are as follows:

Destination

Contains the message destination (queue).

DeliveryMode

Contains the delivery mode (PERSISTENT or NON_PERSISTENT).

Expiration

Contains a message TTL or a value of 0 indicating an unlimited TTL.

Priority

Contains the message priority expressed as a digit from 0 (lowest priority) to 9 (highest priority).

MessageID

Contains a unique message identifier starting with the prefix ID: or a null value. A null value effectively disables the message ID.

Timestamp

Contains the time the message was handed off for transmission, not the time it was actually sent.

CorrelationID

Contains a means of associating one message (for example, a response) with another message (for example, the original request).

ReplyTo

Contains the destination (queue) to which a reply to this message should be sent.

Type

Contains a message identifier provided by the application.

Redelivered

Contains a Boolean indicating that the message was delivered, but not acknowledged.

To create an expression that matches the first nonpersistent message in the queue with a priority of 9, the selector query parameter would be as follows:

selector="Priority='9' and DeliveryMode like NON_PERSISTENT"

xreject

Denies access through the XML Firewall.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:xreject
  reason="rejectionText"
  override="true | false"/>
```

Attributes

reason="rejectionText"
(xs:string) Provides explanatory text.

override="true | false"
(xs:boolean) Specifies whether this rejection decision has precedence over previous rejections.

true Indicates that this rejection has precedence.

false (Default) Indicates that this rejection does not have precedence.

Guidelines

dp:xreject is an extended version of the dp:reject element that uses an XPath expression attribute to construct the rejection text that is sent back to the client in a SOAP fault message.

The override attribute (xs:boolean) and the message text (xs:string) are passed as XPath expressions.

Examples

```
⋮
<xsl:variable name="verify-result"
  select='dp:verify($sigmech,$signedInfoHash,$signValue,$certID)'/>
<xsl:if test='$verify-result != ""'>
  <dp:xreject reason="$verify-result"/>
</xsl:if>
⋮
```

xset-target

Specifies a server-side recipient of a client request.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:xset-target
  host="hostName"
  port="portNumber"
  ssl="true()" | "false()"
  sslid="sslProxyProfile"/>
```

Attributes

host="hostName"
(xs:string) Provides the IP address or host name of the target server.

port="*portNumber*"
 (xs:double) Provides the port number of the target server.

ssl="true()" | "false()"
 (xs:boolean) Indicates whether the connection to the target server is secure (SSL-enabled).
 "true()"
 Specifies a secure connection to the target server.
 "false()"
 Specifies a nonsecure connection to the target server.

sslid="*sslProxyProfile*"
 (xs:string) Specifies the SSL Proxy Profile to use to establish the secure connection.
 This attribute is required when the **ssl** attribute is true(); otherwise, it is not used.

Guidelines

The `dp:xset-target` element is an extended version of the `dp:set-target` element. The `dp:xset-target` element overrides the value of the target server that is specified with the `var://service/routing-url` variable. For Multi-Protocol Gateway and Web Service Proxy services, the honoring of the URI is based on the setting of the **Propagate URI** toggle (WebGUI) or **propagate-uri** command.

The **host**, **port**, and **ssl** attributes are passed as XPath expressions. The **sslid** attribute is passed as an AVT.

Note: Because the **ssl** attribute is passed as an XPath expression do not specify "true". An XPath expression of "true" corresponds to all child elements of the `dp:xset-target` element whose name is true. Because the `dp:xset-target` element does not contain child elements, the node set is empty. An empty node set that is cast to an XPath boolean returns false. Contrary to the obvious intent, a non-SSL connection is specified.

Examples

- Specifies a target server that uses a nonsecure connection.

```

:
:
<xsl:output method="xml" />
<xsl:template match="/">
  <xsl:choose>
    <xsl:when test="/*[local-name()='Envelope']/*[local-
      name()='Body']/*[local-name()='CheckRequestElement']">
      <dp:set-variable name="'var://context/mine/portno'"
        value="2068" />
    </xsl:when>
    <xsl:when test="/*[local-name()='Envelope']/*[local-
      name()='Body']/*[local-name()='request']">
      <dp:set-variable name="'var://context/mine/portno'"
        value="2064" />
    </xsl:when>
    <xsl:otherwise>
      <dp:set-variable name="'var://context/mine/portno'"
        value="8080" />
    </xsl:otherwise>
  </xsl:choose>
  <dp:xset-target host="dp:http-request-header('Target')"
    port="dp:variable('var://context/mine/portno')"
    ssl="false()" />

```

```

</xsl:template>
:
:
• Specifies a target server that uses an SSL-enabled connection.
:
:
<dp:xset-target host="'127.0.0.1'" port="9310" ssl='true()' />
  sslid='SSLserver2'>
:
:

```

Chapter 2. Metadata extension functions

This chapter provides documentation about extension functions that you can use for protocol headers and message manipulation. The documentation for each function contains the following sections:

- Function name
- Platform availability
- Declarations for required namespace and extension prefix
- Syntax
- Attributes with data type
- Guidelines
- Return values or results, if any
- Examples

accepting()

Specifies whether a style sheet is processing a client request or server response.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:accepting()`

Guidelines

The appliance may use a single style sheet to filter both the incoming client request and the outgoing server response.

`dp:accepting()` returns TRUE if processing a client request or returns FALSE if processing a server response.

Results

Returns a boolean value of TRUE or FALSE

Examples

```
⋮
<xsl:choose>
  <xsl:when test="dp:accepting()">
    <xsl:if test="$sla-compliant = 'on'">
      <xsl:message dp:priority="info">Message allowed</xsl:message>
    </xsl:if>
    <xsl:if test="string($processingdoc/Counter) != ''">
      <dp:increment-integer name="'/count-monitor/SLACounter-1'" />
    </xsl:if>
  </xsl:when>
</xsl:choose>
```

```
</xs1:when>
:
```

binary-decode()

Decodes Base64 encoded binary data.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:binary-decode(*string*)

Parameters

string (xs:string) Specifies the string that contains the Base64 encoded binary data.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:blob that contains the decoded binary data.

binary-encode()

Base64-encodes arbitrary binary data.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:binary-encode(*blob*)

Parameters

blob (xs:blob) Specifies the object that contains the binary data to Base64-encode.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string that contains the Base64 encoded binary data.

client-ip-addr()

Obtains the IP address of the requesting client.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:client-ip-address()`

Results

An `xs:string` that contains the IP address of the requesting client.

Examples

```
⋮  
<xsl:value-of select="dp:client-ip-addr()"/>  
⋮
```

client-ip-port()

Obtains the port number of the requesting client.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:client-ip-port()`

Results

An `xs:string` that contains the port number of the requesting client.

Examples

```
⋮  
<xsl:value-of select="dp:client-ip-port()"/>  
⋮
```

client-issuer-dn()

Extracts the distinguished name of the issuer (often, although not always a CA) from a certificate.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:client-issuer-dn(cert, format)
```

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.
- *name:cert*
name: Indicates the required literal prefix for a certificate that is identified by object name.
cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - *cert:base64Cert*
cert: Indicates the required literal prefix for a Base64 encoded certificate.
base64Cert Specifies that the target certificate is Base64 encoded.
 - *ski:certSKI*
ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).
certSKI Specifies that the target certificate is the Base64 encoding of the SKI.
 - *issuerserial:serial*
issuerserial: Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).
serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
 - *thumbprintsha1:sha1string*
thumbprintsha1: Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.
sha1string Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
 - *pkcs7:base64Cert*

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.

- **pkipath:***base64cert*

pkipath:

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

format (*xs:string*) Optionally specifies the order of the DN components. Takes one of the following values:

ldap Arranges the RDNs of the DNs from right to left separated by commas as shown in the following sample:

CN=John, C=us

x500 Arranges the RDNs of the DNs from left to right separated by commas as shown in the following sample:

C=us, CN=John

If not specified, the format is as shown in the following sample:

/C=us/CN=John

Guidelines

All arguments are passed as XPath expressions.

Results

An *xs:string* that contains the distinguished name of the certificate issuer.

If `dp:client-issuer-dn()`

/C=US/ST=MA/L=Cambridge/O=DataPower/CN=Alice

If `dp:client-issuer-dn('ldap')`

CN=Alice, O=DataPower, L=Cambridge, ST=MA, C=US

If `dp:client-issuer-dn('x500')`

C=US, ST=MA, L=Cambridge, O=DataPower, CN=Alice

Examples

```
⋮
<xsl:variable name="CA" select="dp:client-issuer-dn()"/>
⋮
```

client-subject-dn()

Extracts the distinguished name of the subject (the entity whose public key the certificate identifies) from a certificate.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:client-subject-dn(cert, format)`

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.
- `name:cert`

name: Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - `cert:base64Cert`

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert Specifies that the target certificate is Base64 encoded.
 - `ski:certSKI`

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI Specifies that the target certificate is the Base64 encoding of the SKI.
 - `issuerserial:serial`

issuerserial: Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
 - `thumbprintsha1:sha1string`

thumbprintsha1: Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

- `pkcs7:base64Cert`

`pkcs7:` Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

`base64Cert`

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.

- `pkipath:base64cert`

`pkipath:`

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

`base64cert`

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

format (`xs:string`) Optionally specifies the order of the DN components. Takes one of the following values:

`ldap` Arranges the RDNs of the DNs from right to left separated by commas as shown in the following sample:

CN=John, C=us

`x500` Arranges the RDNs of the DNs from left to right separated by commas as shown in the following sample:

C=us, CN=John

If not specified, the format is as shown in the following sample:

/C=us/CN=John

Guidelines

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the distinguished name of the client.

If `dp:client-subject-dn()`

/C=US/ST=MA/L=Cambridge/O=DataPower/CN=Alice

If `dp:client-subject-dn('ldap')`

CN=Alice, O=DataPower, L=Cambridge, ST=MA, C=US

If `dp:client-subject-dn('x500')`

C=US, ST=MA, L=Cambridge, O=DataPower, CN=Alice

Examples

```

:
<xsl:import href="store:///accessfile.xsl"/>
<xsl:call-template name="access-check">
  <xsl:with-param name="username" select="dp:client-subject-dn()"/>
  <xsl:with-param name="url" select="dp:http-url()"/>

```

```
    </xsl:call-template>
    :
```

decode()

Decodes a Base64 encoded or URL-encoded string.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:decode(*string*, *method*)

Parameters

string (xs:string) Identifies the encoded string to decode.

method

(xs:string) Specifies the decoding method and must take one of the following values:

base-64

Specifies that the string is Base64 encoded.

url

Specifies that the string is URL-encoded.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string contained the decoded input string.

Examples

```
    :
    <xsl:variable name="URL" select="dp:decode('$inputURL','url')"/>
    :
```

encode()

Encodes an input string using Base64 encoding or URL-encoding.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:encode(*string*, *method*)

Parameters

- string* (xs:string) Identifies the string to encode.
- method* (xs:string) Specifies the encoding method and must take one of the following values:
- base-64*
Specifies that the string is encoded using Base64-encoding.
 - url*
Specifies that the string is encoded using URL encoding.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string contained the encoded input string.

Examples

```
⋮  
<xsl:variable name="binFlow" select="dp:encode($fromCustomer,'base-64')"/>  
⋮
```

exter-correlator()

Calculates the next correlator ID for a request-response message sequence.

Availability

All products except XA35 and XS40

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:exter-correlator(*identifier*, *direction*)

Parameters

- identifier*
(xs:string) Specifies the correlator ID.
- direction*
(xs:string) Specifies the direction of the message. Specify 0 for a request, or specify 1 for a response.

Guidelines

The **dp:exter-correlator()** extension function calculates the next correlator ID in a sequence or the first correlator ID in a new sequence for a request or for a response. A correlator ID associates the response to the original request. The use of a correlator ID is useful for the tracking of messages and for the collection of message data.

If a correlator ID is in the message, the designer of the system that originates the message must identify the location. A correlator ID can reside in the following locations:

- A SOAP header in SOAP-formatted message
- An HTTP header in a message with binary payload
- A specific node in an XML (non-SOAP) message

If a correlator ID exists, use this identifier. If an empty string (the correlator ID does not exist), specify `NEW_CORRELATOR` as the correlator ID.

All arguments are passed as XPath expressions.

Results

An `xs:string` that indicates the correlator ID for a request-response message sequence.

Examples

The code from the custom style sheet searches the headers from a response message for a correlator ID. If found, the code passes the value for a correlator to the `dp:exter-correlator()` function, and the function generates the next sequential correlator ID. If not found or not valid, the code passes `NEW_CORRELATOR` to the `dp:exter-correlator()` function, and the function calculates and returns the first correlator in a new sequence.

```
...
<xsl:template match="soap:Envelope">

  <xsl:variable name="kd4h">
    <xsl:choose>
      <xsl:when test="//kd4:KD4SoapHeaderV2">
        <xsl:value-of select="//kd4:KD4SoapHeaderV2" />
      </xsl:when>
      <xsl:otherwise>
        <xsl:text>NEW_CORRELATOR</xsl:text>
      </xsl:otherwise>
    </xsl:choose>
  </xsl:variable>

  <xsl:copy>
    <soap:Header>
      <xsl:variable name="foo" select="dp:exter-correlator($kd4h, '1')" />
      <kd4:KD4SoapHeaderV2>
        <xsl:value-of select="$foo"/>
      </kd4:KD4SoapHeaderV2>
      <xsl:apply-templates mode="soap-header" select="soap:Header/*" />
    </soap:Header>
    <xsl:copy-of select="soap:Body" />
  </xsl:copy>
</xsl:template>
...
```

generate-uuid()

Generates a 128-bit UUID (Universal Unique Identifier).

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:generate-uuid()`

Results

An `xs:string` that contains a 128-bit UUID.

Examples

```
⋮  
<xsl:variable name="ID" select="dp:generate-uuid()"/>  
⋮
```

get-metadata()

Fetches metadata for the current transaction.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:get-metadata(object)`

Parameters

object (`xs:string`) Identifies the requested metadata object. In the absence of this argument, the function provides a default value (an empty string) which requests all the metadata for the current transaction.

Guidelines

This extension function supports both request and response traffic, if the current traffic is from client to server (request), it will return transactional metadata of the request message, if the traffic is from server to client, it will fetch the transactional response message metadata.

In case of any errors, such as a meta-item mapping is not defined in the manifest, or the header/variable is not available to read, or the value is NULL or empty string, the corresponding meta-item element will not be contained in the returned node set.

In case of the current protocol scheme is not supported by the metadata manifest, only the metadata items that can be customized will be attempted.

All arguments are passed as XPath expressions.

Results

A node set (an XML fragment) that contains the specified metadata name-value pair, or all metadata name-value pairs.

Examples

```
⋮  
<xsl:variable name="metadata" select="dp:get-metadata('my-short-list')"/>  
⋮
```

http-request-header()

Obtains the value of a specified HTTP header field from a client request.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:http-request-header(*field*)

Parameters

field (xs:string) Identifies the target HTTP header field.

Guidelines

http-request-header() returns the value of the target header field after any required rewriting has been completed; if the target header field is not found, it returns an empty string.

Compare with **dp:request-header()**, which is used with HTTP and additional protocol requests; in contrast, **dp:http-request-header()** supports only HTTP.

All arguments are passed as XPath expressions.

Results

An xs:string that contains the value of the specified HTTP header field.

Examples

```
⋮  
<xsl:variable name="SOAPAction" select="dp:http-request-header('SOAPAction')"/>  
⋮
```

http-request-method()

Extracts the HTTP method from the start line of an incoming request.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

`dp:http-request-method()`

Results

An `xs:string` that contains the HTTP method.

Examples

```
⋮  
<xsl:variable name="Method" select="dp:http-request-method()"/>  
⋮
```

http-response-header()

Obtains the value of a specified HTTP header field from a server response.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:http-response-header(field)`

Parameters

field (xs:string) Identifies the name of an HTTP header field or the `x-dp-response-code` special code.

Guidelines

The **http-response-header()** function returns the value for the specified target header field after the completion of any required rewriting. If the target header field is not found, the function returns an empty string.

The `x-dp-response-code` special code is a protocol response code that is returned to the DataPower server. This special code is not a field that is included in the response header. This special code contains the protocol-specific response code.

Compare with **dp:response-header()**, which is used with HTTP and additional protocol responses; in contrast, **dp:http-response-header()** supports only HTTP.

Are arguments are passed as XPath expressions.

Results

An `xs:string` that contains the value of the specified HTTP header field.

Examples

```
⋮  
<xsl:variable name="SOAPAction" select="dp:http-request-header('Content-Type')"/>  
⋮
```

http-url()

Extracts the HTTP URL from a client request.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:http-url()
```

Guidelines

http-url() returns the HTTP URL after all URL rewriting has been completed.

original-http-url() returns the HTTP URL prior to any rewriting.

Compare to **url()**, which functions with multiple protocols.

Results

An `xs:string` that contains the possibly rewritten request URL.

Examples

```
⋮  
<xsl:variable name="URLRewritten" select="dp:http-url()"/>  
⋮
```

index-of()

Specifies the 1-base offset of the initial occurrence of a substring within another target string.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:index-of(haystack, needle)
```

Parameters

haystack

(`xs:string`) provides the material to be searched through.

needle

(`xs:string`) provides the value to be searched for.

Guidelines

All arguments are passed as XPath expressions.

Results

An `xs:double` that specifies the 1-base offset of the first occurrence of *needle* in *haystack*. Returns 0 in the absence of the proverbial needle.

last-index-of()

Specifies the 1-base offset of the final occurrence of a substring within another target string.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:last-index-of(haystack, needle)`

Parameters

haystack

(`xs:string`) provides the material to be searched through.

needle

(`xs:string`) provides the value to be searched for.

Guidelines

All arguments are passed as XPath expressions.

Results

An `xs:double` that specifies the 1-base offset of the last occurrence of *needle* in *haystack*. Returns 0 in the absence of the proverbial needle.

local-variable()

Retrieves the value of a specified context variable.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:local-variable(variable)`

Parameters

variable

(`xs:string`) Identifies the target context variable.

Guidelines

Differs from **dp:variable()** in that the scope of **dp:local-variable()** is restricted to a single execution context, while **dp:variable()** operates in the global multistep scope.

All arguments are passed as XPath expressions.

Results

the variable value (any type)

Examples

```
⋮
<xsl:template name="set-counter">
  <xsl:param name="counter" select="''" />
  <xsl:param name="value" select="''" />
  <xsl:param name="inc" select="''" />
  <xsl:if test="not($counter = '')">
    <xsl:choose>
      <xsl:when test="not($value = '') and
        not(string(number($value)) = 'NaN')">
        <dp:set-local-variable name="$counter" value="$value" />
      </xsl:when>
      <xsl:when test="not($inc = '')
        and not(string(number($inc)) = 'NaN')">
        <xsl:variable name="counter-value"
          select="number(dp:local-variable($counter))"/>
        <dp:set-local-variable
          name="$counter"
          value="string(number($counter-value) + number($inc))" />
      </xsl:when>
    </xsl:choose>
  </xsl:if>
</xsl:template>
⋮
```

Note the use of **<dp:set-local-variable/>** and **dp:local-variable()**. You must access (set, get, check) the counter from within the same style sheet.

mime-header()

Retrieves the header value of the MIME root part.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:mime-header(*header*,*context*)

Parameters

header (xs:string) Identifies the target header field.

context (xs:string) Identifies the name of the multistep context.

Guidelines

The **http-mime-header()** function returns the value of a specific MIME header in a specific context.

Results

An `xs:string` that contains the value of the specified header.

Examples

```
...
<xsl:variable name="context-type"
  select="dp:mime-header('Context-Type')" />
...
```

mq-queue-depth()

Specifies the number of messages in a MQ queue.

Availability

All products with WebSphere MQ support

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:mq-queue-depth(*queue-manager*, *queue*)

Parameters

queue-manager

(`xs:string`) Identifies the name of an existing MQ Queue Manager object. The object provides the necessary information to access a remote MQ server.

queue (`xs:string`) Specifies the name of a MQ reply queue or MQ request queue.

Guidelines

Checking queue depth provides message count information that helps you to decide whether or not you wish to continue adding messages to a queue that has reached a certain threshold. Knowing the queue depth also enables you to use that value as a parameter in a style sheet that employs an XSLT loop function to locate a unique message in a queue as shown in the following example.

All arguments are passed as XPath expressions.

Results

A `xs:string` that indicates the number of messages in a MQ queue.

Examples

This custom style sheet locates message b3 in a MQ queue with a message depth value of 4.

```
⋮
<xsl:template match="/">
```

```

:
<!-- inquire queue depth of MQ096 and start looking for specified message-->
<xsl:call-template name="find-something-using-browse">
  <xsl:with-param name="num" select="dp:mq-queue-depth('queuemgr1','MQ096')"/>
  <xsl:with-param name="url" select="'dpmq://queuemgr1/?ReplyQueue=MQ096;
    TimeOut=500;Browse=next'"/>
</xsl:call-template>

</xsl:template>

<xsl:template name="find-something-using-browse">
  <xsl:param name="num" />
  <xsl:param name="url" />

  <xsl:if test="$num > 0">

    <xsl:variable name="reply">
      <dp:url-open target="{ $url }" response="xml"/>
    </xsl:variable>

    <xsl:choose>
      <xsl:when test="$reply//*[local-name() = 'b3']">
        <dp:url-open target="dpmq://queuemgr1/?ReplyQueue=MQ096;GMO=256"
          response="xml"/>
        <xsl:call-template name="find-something-using-browse">
          <xsl:with-param name="num" select="$num - 1"/>
          <xsl:with-param name="url" select="$url"/>
        </xsl:call-template>
      </xsl:when>
      <xsl:otherwise>
        <xsl:call-template name="find-something-using-browse">
          <xsl:with-param name="num" select="$num - 1"/>
          <xsl:with-param name="url" select="$url"/>
        </xsl:call-template>
      </xsl:otherwise>
    </xsl:choose>
  </xsl:if>
</xsl:template>
:

```

original-http-url()

Extracts the HTTP URL from a client request.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:original-http-url()

Guidelines

original-http-url() returns the URL prior to any rewriting.

http-url() returns the URL after all URL rewriting has been completed.

Results

An xs:string that contains the URL.

Examples

```
⋮  
<xsl:variable name="URLInput" select="dp:original-http-url()"/>  
⋮
```

original-url()

Extracts the protocol URL from a client request.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:original-url()

Guidelines

original-url() returns the protocol URL prior to any rewriting.

url() returns the protocol URL after all URL rewriting has been completed.

Results

An xs:string that contains the protocol URL.

Examples

```
⋮  
<xsl:variable name="URLInput" select="dp:original-url()"/>  
⋮
```

parse()

Takes a well-formed XML document, parses it and returns a node set.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:parse(*XML*, *encoding*)

Parameters

XML (xs:string) Identifies the XML to parse.

encoding

An optional `xs:string`) If present and assigned a value of base-64, specifies that the XML is treated as Base64 encoded, and will be decoded before being parsed.

Guidelines

The input XML must be well formed. **dp:parse()** issues an error message if the input is not well-formed.

External DTD and entity references are not currently supported.

All arguments are passed as XPath expressions.

Results

A node set

Examples

```
⋮
<xsl:copy-of select="dp:parse(dp:decrypt-data($algorithm,
    $derived-key, $ciphertext))"/>
⋮
```

request-header()

Obtains the value of a specified protocol header field from a client request.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

dp:request-header(*field*)

Parameters

field (xs:string) Identifies the target protocol header field.

Guidelines

dp:request-header() returns the value of the target header field after any required rewriting has been completed; if the target header field is not found, it returns an empty string.

Compare with **dp:http-request-header()**, which is used only with HTTP requests; in contrast, **dp:request-header()** supports HTTP and additional protocols.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the value of the specified protocol header field.

Examples

```
⋮
<!-- Capture the input content-type header value -->
<xsl:variable name="input-contenttype">
  <xsl:choose>
    <xsl:when test="dp:responding()">
      <xsl:value-of select="dp:response-header('Content-Type')"/>
    </xsl:when>
    <xsl:otherwise>
      <xsl:value-of select="dp:request-header('Content-Type')"/>
    </xsl:otherwise>
  </xsl:choose>
</xsl:variable>
⋮
```

responding()

Specifies whether the style sheet is processing a client request or server response.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:responding()

Guidelines

The appliance may use a single style sheet to filter both the incoming client request and the outgoing server response.

responding() returns TRUE if processing a server response, or FALSE if processing a client request.

Results

Returns a boolean value: TRUE or FALSE

Examples

```
⋮
<xsl:template match="/">
  <xsl:choose>
    <xsl:when test="dp:responding()=false()">
      arbitrary XSLT server response processing
    </xsl:when>
  </xsl:choose>
⋮
```

response-header()

Obtains the value of a specified protocol header field from a server response.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:response-header(field)
```

Parameters

field (xs:string) Identifies the name of a protocol-specific header field or the x-dp-response-code special code.

Guidelines

The **dp:response-header()** function returns the value of the target header field after the completion of any required rewriting. If the target header field is not found, the function returns an empty string.

The x-dp-response-code special code is a protocol response code that is returned to the DataPower server. This special code is not a field that is included in the response header. This special code contains the protocol-specific response code.

Compare with **dp:http-response-header()**, which is used only with HTTP responses; in contrast, **dp:response-header()** supports HTTP and additional protocols.

All arguments are passed as XPath expressions.

Results

An xs:string that contains the value of the specified protocol header field.

Examples

```
⋮
<!-- Capture the input content-type header value -->
<xsl:variable name="input-contenttype">
  <xsl:choose>
    <xsl:when test="dp:responding()">
      <xsl:value-of select="dp:response-header('Content-Type')"/>
    </xsl:when>
    <xsl:otherwise>
      <xsl:value-of select="dp:request-header('Content-Type')"/>
    </xsl:otherwise>
  </xsl:choose>
</xsl:variable>
⋮
```

schema-validate()

Performs a schema validation.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```


Syntax

dp:schema-validate(*schema*, *nodeset*)

Parameters

schema (xs:string) Identifies the XSD schema to perform the validation.

nodeset (xs:node-set) Identifies the node set that contains the XML content to validate.

Guidelines

All arguments are passed as XPath expressions.

Results

the validated node set.

Examples

```
⋮
<xsl:when test="$Ready">
  <xsl:copy-of select="dp:schema-validate('store:///headers.xsd',
    $headerOutput)" />
</xsl:when>
⋮
```

soap-call()

Posts an XML message to a server and receives the server response.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:soap-call(*URL*, *message*, *SSL-Proxy-Profile*, *flags*, *SOAP-action*, *HTTP-headers*, *process-faults*)

Parameters

URL (xs:string) Identifies the URL of the target server.

message
(node set) Contains the SOAP envelope to be transmitted.

SSL-Proxy-Profile
(xs:string) Optionally identifies the SSL Proxy Profile to establish a secure connection with the target URL. An empty string, the default value, specifies a non-SSL connection.

flags (xs:string) Retain the default value of 0.

SOAP-action
(xs:string) Optionally specifies the contents of the HTTP SOAPAction header. An empty string, the default value, suppresses the addition of this header.

HTTP-headers

(node set) Specifies the HTTP headers to add to the message.

This parameter contains a `<header>` element with a `name` attribute that defines the name of the header. The contents of the `<header>` element defines the value of the header. For example:

```
<xsl:variable name="httpHeaders">
  <header name="SOAPAction">test_soap_action</header>
  <header name="Content-Type">application/soap+xml</header>
</xsl:variable>
```

process-faults

(`xs:boolean`) Indicates whether to process SOAP faults. Specify `true()` to process SOAP faults, or specify `false()` to not process SOAP faults. The default is `false()`.

Guidelines

The **dp:soap-call** function builds a message from literal elements and from part of the incoming message body in a style sheet. The function then makes a server call, parses the results, and performs the specified action. For example, you can use this function to extract the certificate from a signed document and call an XKMS server to validate the certificate.

A `BasicAuth` header in the *HTTP-headers* parameter takes priority over a `BasicAuthPolicy` header from the User Agent.

- For SOAP 1.1, the *SOAP-action* parameter takes priority over a `SOAPAction` header in the *HTTP-headers* parameter.
- For SOAP 1.2, do not use the *SOAP-action* parameter to specify the contents of the `SOAPAction` header. Instead, use the *HTTP-headers* parameter to define the `Content-Type` header. You can also define the SOAP action with the `action` parameter. For example:

`Content-Type: application/soap+xml; charset=utf-8; action=http://foo/bar`

The function passes all arguments as XPath expressions.

Results

A node set that contains the server response.

Examples

Uses the **dp:soap-call** function to send a message and save the response in a `result` variable.

```
⋮
<xsl:variable name="call">
  <soap:Envelope xmlns:soap="http://www.w3.org/2003/05/soap-envelope">
    <soap:Header/>
    <soap:Body>
      <echoString>
        <inputString>foo bar</inputString>
      </echoString>
    </soap:Body>
  </soap:Envelope>
</xsl:variable>

<xsl:template match="/*">
  <xsl:variable name="httpHeaders">
    <header name="Content-Type">application/soap+xml</header>
    <header name="SOAPAction">test_soap_action</header>
```

```

        <header name="Authorization">Basic</header>
        <header name="RandomStuff">abcd</header>
    </xsl:variable>
    <xsl:variable name="result"
        select="dp:soap-call('http://x.xx.xx.xxx:nnnn/soapcalltest',
            $call/*,'',0,'',$httpHeaders/*)"/>
    <xsl:copy-of select="$result"/>
</xsl:template>
:

```

sql-execute()

Executes an SQL statement against a DB2, Oracle, or Sybase database.

Availability

All products with the SQL/ODBC support

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:sql-execute(*object*, *statement*)

Parameters

object (xs:string) Identifies the SQL Data Source Object, previously created with the WebGUI or command line. This object provides the data (for example, IP address, monitored port, database type) that is required to access a remote database.

statement (xs:string) Provides the SQL statement to run against the target database

Guidelines

The timeout value for the **dp:sql-execute** extension function is the timeout value of the HTTP user agent for the appropriate XML manager.

All arguments are passed as XPath expressions.

Results

A node set that contains the response from the SQL server.

Examples

```

:
<xsl:variable name="where-clause" select="..."/>
<!--specify location of WHERE clause, for example -->
<xsl:variable name="sqlString" select="SELECT ID,
COUNT(1) FROMtTable<xsl:value-of-select="$where-clause"/>GROUP
BY ID"/>
<xsl:variable name="sqlNodeSet">
  <xsl:copy-of select="dp:sql-execute('data-source-name',
    $sqlString)/>

```

```
</xsl:variable>
⋮
```

substring-base64()

Extracts a specified portion of a base string and Base64-encodes the extracted bytes.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:substring-base64(*string*, *offset*, *length*)

Parameters

string (xs:string) Specifies the string to be extracted from.

offset (xs:integer) Specifies the initial byte to be extracted. a value of 0 specifies the first byte of the string.

length (xs:integer) Specifies the length of the extracted string in bytes.

Guidelines

All arguments are passed as XPath expressions.

Results

a Base64 encoded xs:string

time-value()

Returns the current time as the number of milliseconds since January 1, 1970.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:time-value()

Results

a number (xs:double) that contains the current time expressed as milliseconds since January 1, 1970.

transform()

Initiates a XSLT transformation from a style sheet.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:transform()(stylesheet, nodeset)`

Parameters

stylesheet

(`xs:string`) Identifies the style sheet to perform the transform.

nodeset (node set) Contains the XML content to transform.

Guidelines

dp:transform() is intended for use with dynamic style sheets. If the style sheet is static, use the `<xsl:include>` element to the target style sheet and its templates.

All arguments are passed as XPath expressions.

Results

The transformed node set

Examples

```
⋮
<xsl:when test="$Ready">
  <xsl:copy-of select="dp:transform('store:///headers.xml',
    $headerOutput)" />
</xsl:when>
⋮
```

url()

Extracts the protocol URL from a client request.

Availability

All products

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:url()`

Guidelines

url() returns the protocol URL after all URL rewriting has been completed.

original-url() returns the protocol URL prior to any rewriting.

Compare with **http-url()** which processes only HTTP URLs.

Results

An xs:string that contains the protocol URL.

Examples

```
⋮  
<xsl:variable name="URLRewritten" select="dp:url()"/>  
⋮
```

variable()

Retrieves the value of a specified variable.

Availability

All products

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:variable(*variable*)

Parameters

variable

(xs:string) Identifies the target variable.

Guidelines

Refer to Appendix A, “Working with variables,” on page 195 for a list of system variables.

All arguments are passed as XPath expressions.

Results

Any

Examples

```
⋮  
<!-- build log message -->  
<xsl:variable name="log-message">  
  <env:Envelope>  
    <env:Body>  
      <log-entry>  
        <date>  
          <xsl:value-of select="date:date()"/>  
        </date>  
        <time>  
          <xsl:value-of select="date:time()"/>  
        </time>  
        <transaction>  
          <xsl:value-of select="dp:variable('var://service/transaction-id')"/>  
        </transaction>  
        <type>  
          <xsl:value-of select="$dpconfig:LogCategory"/>  
        </type>  
        <level>
```

```

        <xsl:value-of select="$dpconfig:LogPriority"/>
      </level>
    <message>
      <xsl:copy-of select="."/>
    </message>
  </log-entry>
</env:Body>
</env:Envelope>
</xsl:variable>
:

```

wsm-agent-append()

Adds a record to a Web Services Management Agent.

Availability

All products except XA35 and XS40

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:wsm-agent-append(*domain*, *record*)

Parameters

domain (xs:string) Identifies the name of the application domain.

record (xs:string) Identifies the record to add.

Guidelines

The **dp:wsm-agent-append()** adds a record for a request-response message sequence to a Web Services Management Agent. The record contains transaction data that was collected during a request-response message sequence. Each application domain can contain an instance of a configured Web Services Management Agent.

To obtain the name of the domain, use the `var://service/domain-name` variable.

To obtain the record, define a variable that creates a `dpwsm:wsa-record` node set. Refer to the `store:///schemas/dp-wsm-agent-append.xsd` schema for details about creating this node set.

Depending on the configuration, a record can include the following processing information about requests and responses:

- IP address
- Client identification
- Authenticated identity
- Target service or operation
- Message size
- Processing duration
- Fault messages
- SOAP headers
- Full message

For ITCAM to receive a data capture, enable the WS-Management Endpoint in the XML Management Interface. You can enable this endpoint from the WebGUI or from the command line.

WebGUI

Use the following procedure:

1. Select (**NETWORK** → **Management** → **XML Management Interface**).
2. Set the value of the **WS-Management Endpoint** toggle to **on**.
3. Click **Apply**.
4. Click **Save Config**.

Command line

Enter the following command sequence, where *keyword-string* is the existing value for the **mode** property.

```
# configure terminal
# show xml-mgmt
xml-mgmt [up]
-----
admin-state enabled
ip-address 0.0.0.0
port 5550
acl xml-mgmt [up]
slm-peering 10
mode any+soma+v2004+amp+slm+wsm
# xml-mgmt
# mode keyword-string+wsm
# exit
# write memory
```

All arguments are passed as XPath expressions.

Results

An `xs:string` that indicates that the record was added.

Examples

Adds a record to the Web Services Management Agent.

```
...
<!--Create a nodeset to be sent to ITCAM using (mostly) defaults-->
<xsl:variable name="record">
  <dpwsm:wsa-record xmlns:dpwsm="http://www.datapower.com/schemas/transactions">
    <!-- Default uses "var://service/soap-oneway-mep" -->
    <dpwsm:is-one-way default='yes'/>
    <!-- Default uses "var://service/URI" -->
    <dpwsm:request-uri default='yes'/>
    <!-- Default uses "var://service/URL-in" -->
    <dpwsm:final-front-url default='yes'/>
    <!-- Default uses "var://service/wsm/service" - set manually -->
    <dpwsm:webservice default='yes'/>
    <!-- Default uses "var://service/wsm/service-port" - set manually -->
    <dpwsm:service-port default='yes'/>
    <!-- Default uses "var://service/wsm/operation" - set manually -->
    <dpwsm:ws-operation default='yes'/>
    <!-- Default uses internal calculation -->
    <dpwsm:ws-client-id default='yes'/>
    <!-- Default uses internal calculation -->
    <dpwsm:ws-clientid-extmthd default='yes'/>
    <!-- Default uses internal calculation -->
    <dpwsm:ws-correlator-sfid default='yes'/>
    <!-- Default uses internal calculation -->
    <dpwsm:ws-client-socode default='yes'/>
    <!-- Default uses internal calculation -->
```



```

        <dpwsm:ws-dp-socode default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:ws-server-socode default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:ws-client-hopcount default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:ws-server-hopcount default='yes' />
<!-- Default uses var://service/transaction/client -->
        <dpwsm:client default='yes' />
<!-- Default uses var://context/WSM/identity/AAA-extracted-identity -->
        <dpwsm:username>
            <xsl:value-of select="dp:variable('var://context/oos/identity')"/>
        </dpwsm:username>
<!-- Default uses var://context/WSM/identity/AAA-mapped-credentials -->
        <dpwsm:credential />
<!-- Default uses internal calculation -->
        <dpwsm:start-time default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:duration-ms default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:front-latency-ms default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:back-latency-ms default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:request-size default='yes' />
<!-- Default uses internal calculation -->
        <dpwsm:response-size default='yes' />

        <dpwsm:backend-message>
            <dpwsm:backend-url>
                <xsl:value-of select="dp:variable('var://service/URL-out')"/>
            </dpwsm:backend-url>
        </dpwsm:backend-message>

<xsl:if test="$dpconfig:gw-error='true'"
    "xmlns:soap="http://schemas.xmlsoap.org/soap/envelope/">
    <dpwsm:error-code>
        <xsl:value-of select="dp:variable('var://service/error-code')"/>
    </dpwsm:error-code>
    <dpwsm:error-subcode>
        <xsl:value-of select="dp:variable('var://service/error-subcode')"/>
    </dpwsm:error-subcode>
    <dpwsm:fault-code>
        <xsl:value-of select="soap:Envelope/soap:Body/soap:Fault/faultcode"/>
    </dpwsm:fault-code>
    <dpwsm:fault-message>
        <xsl:value-of select="soap:Envelope/soap:Body/soap:Fault/faultstring"/>
    </dpwsm:fault-message>
</xsl:if>
</dpwsm:wsa-record>
</xsl:variable>

<!-- add this record to the wsm-agent queue -->
<xsl:variable name="domain" select="dp:variable('var://service/domain-name')"/>
<xsl:variable name="result" select="dp:wsm-agent-append($domain,$record)"/>
<dp:set-variable name="'var://context/oos/wsm-agent-result'" value="$result"/>
...

```

Chapter 3. Cryptographic extension functions

This chapter provides documentation about extension functions that you can use to perform standard cryptographic operations (encryption, decryption, document signature, signature verification, and so forth). The documentation for each function contains the following sections:

- Function name
- Platform availability
- Declarations for required namespace and extension prefix
- Syntax
- Attributes with data type
- Guidelines
- Return values or results, if any
- Examples

Cryptographic functions are available on XS40 and appliances only.

aaa-derive-context-key()

Generates new key material based on the existing context key and the supplied arguments.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:aaa-derive-context-key(context, nonce, label, length, algorithm)`

Parameters

context (xs:string) Identifies the security context.

nonce (xs:string) Contains the value of the <wsc:Nonce> element.

label (xs:string) Contains the value of the <wsc:Label> element. The default is WS-SecureConversationWS-SecureConversation.

length (xs:string) Contains the value of the <wsc:Length> element. The default is 32.

algorithm

(xs:string) Identifies the algorithm to generate the derived key from the initial session key and the supplied arguments.

Use the following value, which specifies the P_SHA1 algorithm as defined in RFC 2246, *The TLS Protocol, Version 1.0*:

`http://schemas.xmlsoap.org/ws/2004/04/security/sc/dk/p_sha1`

Guidelines

All arguments are passed as XPath expressions.

Results

If successful, returns a string that contains the key material. If unsuccessful, or if `newlen` is less than or equal to 0, returns an empty string.

Examples

```
⋮
<xsl:variable name="key-2">
  <xsl:value-of select="dp:aaa-derive-context-key($contextid,
    $nonce, $label, $keylen, $algo)" />
</xsl:variable>
⋮
```

aaa-get-context-info()

Obtains the value associated with a specified name.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:aaa-get-context-info(context, name)`

Parameters

context (xs:string) Identifies the security context associated with the name-value pair.

name (xs:string) Identifies the property whose value is sought.

Guidelines

Table 3 lists the well-known context names.

Table 3. Well known context names

Context name	Type	Description
transaction-id	read-only	The security context ID.
transaction-key	read-write	The key material associated with the context. The dp:aaa-new-security-context() function creates a random ephemeral key when called. Use the aaa-set-context-info() function to override this value.
transaction-created	read-only	The context start time.
transaction-expiry	read-write	The context expiration time.
transaction-renew	read-write	Specifies whether the context is renewable; a value of 1 indicates the context is renewable, any other value indicates that the context is not renewable.

Table 3. Well known context names (continued)

Context name	Type	Description
transaction-instance	read-only	The security context instance.

All arguments are passed as XPath expressions.

Results

If successful returns the associated value as an `xs:string`. If unsuccessful, returns an empty string.

Examples

```

:
<xsl:variable name="sc-key" select="dp:aaa-get-context-info($id,
'transaction-key')"/>
:

```

aaa-new-security-context()

Establishes a security context.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:aaa-new-security-context(*context, time, renew, key, entropy*)

Parameters

context (xs:string) Optionally identifies the security context to establish.

The Security Context must be unique to both the sender and the recipient. The WS-SecureConversation specification (Version 1.1, May 2004) recommends that the Security Context be globally unique in time and space.

This argument can take the form of the `<wsc:Identifier>` element or, more commonly, an empty string or NULL.

time (xs:string) Specified the start time of the context. This argument takes the form of a UTC (coordinated universal time) string in either Zulu or GMT with offset format.

renew (xs:string) Specifies whether the context is renewable with a WS-Trust renew request.

- 1 Specifies that the context is renewable.
- All other strings forbid context renewal.

key (xs:string) Identifies the symmetric key type to generate the context key (shared secret). The context key must take one of the following values:

`http://www.w3.org/2001/04/xmlenc#tripledes-cbc`
Specifies a 3DES key

`http://www.w3.org/2001/04/xmlenc#aes128-cbc`
Specifies a 128-bit AES key

`http://www.w3.org/2001/04/xmlenc#aes192-cbc`
Specifies a 192-bit AES key

`http://www.w3.org/2001/04/xmlenc#aes256-cbc`
Specifies a 256-bit AES key

entropy

(xs:string) Optionally provides client-generated material for use in the key generation process.

Contains either the value of the <wsc:Nonce> element or a blank string that indicates the lack of client-generated randomness material.

Guidelines

You determine the security context expiration time as follows:

Configure the `var://system/AAA/defaultexpiry` system variable value (interpreted as seconds) to set the context expiration timer. If you do not set this variable, the appliance configures a default value of 14,400 (4 hours) and sets the system variable to 4.

The expiry of a specific context can be changed with **aaa-set-context-info()**. This change is context-specific and does not change the value of the `var://system/AAA/defaultexpiry` system variable.

All arguments are passed as XPath expressions.

Results

If successful returns a string that contains a generated context-ID, either a random GUID, globally unique identifier (if the first argument is an empty string or none), or the value of the supplied argument (the contents of the <wsc:Identifier> element).

If unsuccessful, returns an empty string.

Examples

```
⋮
<xsl:variable name="id">
  <xsl:value-of select="dp:aaa-new-security-context('', $now,
    $flags, 'http://www.w3.org/2001/04/xmlenc#tripledes-cbc',
    $client-entropy)"/>
</xsl:variable>
⋮
```

aaa-set-context-info()

Associates a name-value pair with a specified context.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:aaa-set-context-info(*context*, *name*, *value*)

Parameters

context (xs:string) Identifies the security context associated with the name-value pair.

name (xs:string) Specifies the property name.

value (xs:string) Specifies the property value.

Guidelines

Table 4 lists the well-known context names.

Table 4. Well known context names

Context name	Type	Description
transaction-id	read-only	The security context ID.
transaction-key	read-write	The key material associated with the context. The dp:aaa-new-security-context() function creates a random ephemeral key when called. Use the aaa-set-context-info() function to override this value.
transaction-created	read-only	The context start time.
transaction-expiry	read-write	The context expiration time.
transaction-renew	read-write	Specifies whether the context is renewable; a value of 1 indicates the context is renewable, any other value indicates that the context is not renewable.
transaction-instance	read-only	The security context instance.

All arguments are passed as XPath expressions.

Results

If successful returns the supplied context-ID (a string). If unsuccessful, returns an empty string.

Examples

```
⋮
<xsl:variable name="PPdata" select="dp:aaa-set-context-info($id,
'transaction-credentials', $credentials/*)"/>
⋮
```

auth-info()

Returns client authentication information.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:auth-info(*method*, *format*)

Parameters

method (xs:string) Specifies the method used to authenticate a client. Takes one of the following values:

basic-auth-name

Used with HTTP BasicAuth and returns the name from the Authorization HTTP header

basic-auth-password

Used with HTTP BasicAuth and returns the password from the Authorization HTTP header

ssl-client-cert

Used with SSL-based client authentication and returns the entire Base64 encoded client certificate

ssl-client-issuer

Used with SSL-based client authentication and returns the issuer DN from the client's certificate

ssl-client-subject

Used with SSL-based client authentication and returns the subject DN from the client's certificate

format (xs:string) When *method* is **ssl-client-subject** or **ssl-client-issuer**, optionally specifies the order of the DN components. Takes one of the following values:

ldap Arranges the RDNs of the DNs from right to left separated by commas as shown in the following sample:

CN=John, C=us

x500 Arranges the RDNs of the DNs from left to right separated by commas as shown in the following sample:

C=us, CN=John

ldap-strict

Arranges the RDNs of the DNs in the same way as the **ldap** format, but strictly complies with the LDAP standard. The output does not include a space after the comma separator as shown in the following sample:

CN=John,C=us

x500-strict

Arranges the RDNs of the DNs in the same way as the **x500** format, but strictly complies with the LDAP standard. The output does not include a space after the comma separator as shown in the following sample:

C=us,CN=John

If not specified, the format is as shown in the following sample:

/C=us/CN=John

Guidelines

The argument is passed as an XPath expression.

Results

An xs:string that contains the authentication credentials.

```
If dp:auth-info('ssl-client-subject')
    /C=US/ST=MA/L=Cambridge/O=DataPower/CN=Alice

If dp:auth-info('ssl-client-subject', 'ldap')
    CN=Alice, O=DataPower, L=Cambridge, ST=MA, C=US

If dp:auth-info('ssl-client-subject', 'x500')
    C=US, ST=MA, L=Cambridge, O=DataPower, CN=Alice

If dp:auth-info('ssl-client-subject', 'ldap-strict')
    CN=Alice,O=DataPower,L=Cambridge,ST=MA,C=US

If dp:auth-info('ssl-client-subject', 'x500-strict')
    C=US,ST=MA,L=Cambridge,O=DataPower,CN=Alice
```

Examples

```
⋮
<!-- Retrieve the client's BasicAuth name -->
<xsl:value-of select="dp:auth-info('basic-auth-name')"/>
⋮
```

base64-cert()

Gets an X.509 certificate from the appliance flash.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:base64-cert(cert)
```

Parameters

cert (xs:string) Identifies the target certificate.

Use the form *name:certificate*; for example *name:bob*, where *name* is a constant, and *certificate* is the name of a Crypto Certificate object that was previously created with the **certificate** command or WebGUI and that references the target certificate file.

Guidelines

The argument is passed as an XPath expression.

Results

A string that contains the Base64 encoded target certificate.

Examples

```
⋮
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
```

```

<xsl:copy-of select="$signedinfo-subtree"/>
<SignatureValue>
  <xsl:value-of select="dp:sign($sigmech,$signedinfo-hash,$keyid)"/>
</SignatureValue>
<xsl:if test='$certid!=""'>
  <KeyInfo>
    <X509Data>
      <X509Certificate>
        <xsl:value-of select="dp:base64-cert($certid)"/>
      </X509Certificate>
      <X509IssuerSerial>
        <X509IssuerName>
          <xsl:value-of select="dp:get-cert-issuer($certid)"/>
        </X509IssuerName>
        <X509SerialNumber>
          <xsl:value-of select="dp:get-cert-serial($certid)"/>
        </X509SerialNumber>
      </X509IssuerSerial>
    </X509Data>
  </KeyInfo>
</xsl:if>
</Signature>
:

```

c14n-hash()

Canonicalizes and computes a hash value for a specified node set.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:c14n-hash(*nodeset*, *includeComments*, *algorithm*)

Parameters

nodeset (node set) Identifies the XML content to convert to its canonical form.

includeComments

(xs:boolean) Specifies the treatment of XML comments.

- true() specifies that comments are included.
- false() specifies that comments are excluded.

algorithm

(xs:string) Identifies the hashing algorithm. The firmware supports the following hash algorithms:

```

http://www.w3.org/2000/09/xmldsig#sha1
http://www.w3.org/2001/04/xmenc#sha256
http://www.w3.org/2001/04/xmenc#sha512
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5

```

The default is <http://www.w3.org/2000/09/xmldsig#sha1>.

Guidelines

c14n-hash() uses the canonicalization method defined in the W3C Recommendation 15 March 2001 version of *XML Canonicalization*.

c14n-hash() and **c14n-hash-set()** differ in that **c14n-hash-set()** converts data into its canonical form only those elements and attributes explicitly passed via the *nodeset* argument. In contrast, **c14n-hash()** performs a deep hash that includes all child elements of the *nodeset* argument.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the Base64-encoded hash of the canonicalized node set.

Examples

```
⋮
<xsl:variable name="digest">
  <xsl:value-of select="dp:c14n-hash($node, false())"/>
</xsl:variable>
⋮
```

c14n-hash-attachment()

Canonicalizes and computes a hash value for a specified SOAP attachment.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:c14n-hash-attachment(*URL*, *doHeaders*, *algorithm*)

Parameters

URL (`xs:string`) Identifies the location of the attachment to be canonicalized and hashed.

Attachment URLs take the form `attachment://context/URL`. For example:
`attachment://orange/cid:12345`

doHeaders

(`xs:boolean`) Optionally specifies whether certain message headers, described in the OASIS *Web Services Security SOAP Messages with Attachments (SwA) Profile 1.0* specification, are included in the canonicalized output.

- `true()` Specifies that headers are included.
- `false()` (Default) Specifies that headers are excluded.

algorithm

(`xs:string`) Identifies the hashing algorithm. The firmware supports the following hash algorithms:

```
http://www.w3.org/2000/09/xmldsig#sha1
http://www.w3.org/2001/04/xmenc#sha256
http://www.w3.org/2001/04/xmenc#sha512
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5
```

The default is `http://www.w3.org/2000/09/xmldsig#sha1`.

Guidelines

c14n-hash-attachment() uses the canonicalization method described in the OASIS specification *Web Services Security SOAP Messages with Attachments (SwA) Profile 1.0*.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the Base64-encoded hash value of the canonicalized SOAP attachment.

Examples

```
⋮
<xsl:variable name="digestNonXML">
  <xsl:value-of select="dp:c14n-hash-attachment($attachmentID,false(),
    $hashAlgorithm)"/>
</xsl:variable>
⋮
```

c14n-hash-set()

Canonicalizes and computes a hash value for an input node set.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:c14n-hash-set(*nodeset*, *includeComments*, *algorithm*)

Parameters

nodeset (node set) Identifies the XML content to be canonicalized.

includeComments

(`xs:boolean`) Specifies the treatment of XML comments.

- `true()` specifies that comments are included.
- `false()` specifies that comments are excluded.

algorithm

(`xs:string`) Identifies the hashing algorithm. The firmware supports the following hash algorithms:

```
http://www.w3.org/2000/09/xmldsig#sha1
http://www.w3.org/2001/04/xmenc#sha256
http://www.w3.org/2001/04/xmenc#sha512
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5
```

The default is `http://www.w3.org/2000/09/xmldsig#sha1`.

Guidelines

c14n-hash-set() uses the canonicalization method defined in the W3C Recommendation 15 March 2001 version of *XML Canonicalization*.

c14n-hash() and **c14n-hash-set()** differ in that **c14n-hash-set()** converts data into its canonical form only those elements and attributes explicitly passed via the *nodeset* argument. In contrast, **c14n-hash()** performs a deep hash that includes all child elements of the *nodeset* argument.

All arguments are passed as XPath expressions.

Results

A string that contains the Base64-encoded hash of the canonicalized node set.

Examples

```
:
<xsl:variable name="digest">
  <xsl:value-of select="dp:c14n-hash-set($node,false(),$hashAlgorithm)"/>
</xsl:variable>
:
```

canonicalize()

Canonicalizes a specified node set.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:canonicalize(*nodeset*, *algorithm*, *prefixes*, *restrictToNodeSet*)

Parameters

nodeset (node set) Contains the XML content to be canonicalized.

algorithm

(xs:string) Specifies the method used to canonicalize the target node set. Use one of the following string values:

`http://www.w3.org/TR/2001/REC-xml-c14n-20010315`

Identifies the c14n algorithm (comments are excluded in the canonicalized output)

<http://www.w3.org/TR/2001/REC-xml-c14n-20010315#WithComments>
Identifies the c14n algorithm (comments are included in the canonicalized output)

<http://www.w3.org/2001/10/xml-exc-c14n#>
Identifies the c14n exclusive canonicalization algorithm (comments are excluded in the canonicalized output)

<http://www.w3.org/2001/10/xml-exc-c14n#WithComments>
Identifies the c14n exclusive canonicalization algorithm (comments are included in the canonicalized output)

prefixes

(xs:string) Optionally provides a space-delimited list of the inclusive namespace prefixes. That is the namespace declarations that are emitted by either of the two exclusive canonicalization algorithms.

This parameter is meaningful only when an exclusive canonicalization method is used.

By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

This parameter overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string specifies an empty set of prefixes.

restrictToNodeSet

(xs:boolean) Specifies the treatment of descendants of the nodes in the target node set.

- If `true()`, the canonicalizer includes exactly those nodes in the target node set and no others.
- If `false()`, the canonicalizer includes all descendants of the nodes in the node set.

restrictToNodeSet is almost always **false()**, because a digital signature typically protects a subtree of a document.

Guidelines

Note: IBM strongly recommends that the XSL style sheet specify an output method of text when using **dp:canonicalize()**.

Because the resulting string is a text representation of XML, it will typically contain left and right angle brackets surrounding markup elements. If the output method is either HTML or XML, all left angle brackets in the output will be escaped as `<`; to avoid being confused with actual output markup.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mumblens"/>
```

Where the `x` attribute is interpreted as a QName, and the `mumble` prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the `mumble` prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix `mumble` in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for `mumble` to be emitted.

Often used for debugging purposes, for example to examine the intermediate canonicalized output produced when computing an SHA-1 hash of a node set.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the canonicalized target node set.

Examples

```
⋮
<xsl:stylesheet xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:SOAP="http://schemas.xmlsoap.org/soap/envelope/"
  exclude-result-prefixes="dp SOAP"
  version="1.0">
  <xsl:output method="text"/>
  <xsl:template match="/">
    <xsl:value-of select="dp:canonicalize(//SOAP:Body,
      'http://www.w3.org/TR/2001/REC-xml-c14n-20010315', '', false())"/>
  </xsl:template>
</xsl:stylesheet>
⋮
```

cert-from-issuer-serial()

Gets an X.509 certificate from the file system on the appliance.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:cert-from-issuer-serial(caDn, certSerialNumber)`

Parameters

caDn (xs:string) Specifies the distinguished name of the certificate issuer.

certSerialNumber
(xs:string) Specifies the serial number of the target certificate.

Guidelines

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the Base64 encoded target certificate.

Examples

```
⋮
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
  <xsl:copy-of select="$signedinfo-subtree"/>
  <SignatureValue>
    <xsl:value-of select="dp:sign($sigmech,$signedinfo-hash,$keyid)"/>
  </SignatureValue>
  <xsl:if test='$certid!=""'>
    <KeyInfo>
      <X509Data>
        <X509Certificate>
          <xsl:value-of select="dp:cert-from-serial-issuer(
            $issuingCA,$serialNo)"/>
        </X509Certificate>
        <X509IssuerSerial>
          <X509IssuerName>
            <xsl:value-of select="dp:get-cert-issuer($certid)"/>
          </X509IssuerName>
          <X509SerialNumber>
            <xsl:value-of select="dp:get-cert-serial($certid)"/>
          </X509SerialNumber>
        </X509IssuerSerial>
      </X509Data>
    </KeyInfo>
  </xsl:if>
</Signature>
⋮
```

concat-base64()

Decodes input strings, concatenates, and then returns a Base64 notation of the data.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:concat-base64(string1, string2)`

Parameters

string1 (xs:string) Identifies the first string to concatenate.

string2 (xs:string) Identifies the second string to concatenate.

Guidelines

The function passes all arguments as XPath expressions.

Results

A Base64 encoded string.

Examples

```
⋮  
  select="dp:concat-base64($msg64,$watermark64)"/>  
⋮
```

decrypt-attachment()

Decrypts an attachment using a shared secret key and symmetric cryptographic algorithm

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:decrypt-attachment(URI, doHeaders, algorithm, sessionKey, encoding, contentType)`

Parameters

URI (xs:string) Identifies the attachment to decrypt.

doHeaders

(xs:boolean) Indicates whether or not the attachment headers were encrypted.

- `true()` attachment headers were encrypted.
- `false()` attachment headers were not encrypted.

algorithm

(xs:string) Identifies the symmetric cryptographic algorithm used for decryption. Valid values are:

```
http://www.w3.org/2001/04/xmlenc#tripledes-cbc  
http://www.w3.org/2001/04/xmlenc#aes128-cbc  
http://www.w3.org/2001/04/xmlenc#aes192-cbc  
http://www.w3.org/2001/04/xmlenc#aes256-cbc
```

sessionKey

(xs:string) Identifies the session key the **encrypt-attachment()** function uses for encryption. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.
- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key:` prefix, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

encoding

(xs:string) Optionally specifies an encoding to be decoded after decrypting the attachment.

- To Base64 decode, use <http://www.w3.org/2000/09/xmldsig#base64>.
- To not decode, use '' or leave blank.

contentType

Optionally specifies a final header value for the decrypted attachment.

- If specified, it overrides the Content-Type header value from the decrypted attachment.
- If not specified and the decrypted attachment does not have a Content-Type value, the header value defaults to "text/plain; charset=us=ascii".

Guidelines

Use **decrypt-attachment()** to perform binary-to-binary decryption of an attachment. To construct the *URI*, use the format *cid:string* that points to the attachment to decrypt. The function uses the key and the specified cryptographic algorithm to decrypt a message attachment.

This function passes all arguments as XPath expressions.

Results

On success, the decrypt-attachment function returns an empty string and decrypts the attachment. If not successful, the function returns an error message and leaves the attachment unaltered.

Examples

```

:
:
<xsl:template match="/">
  <xsl:variable name="attachment" select="'cid:sheet'"/>
  <xsl:variable name="doHeaders" select="false()"/>
  <xsl:variable name="algorithm"
    select="'http://www.w3.org/2001/04/xmlenc#tripledes-cbc'"/>
  <xsl:variable name="sessionKey" select="//session_key"/>
  <xsl:value-of select="dp:decrypt-attachment($attachment,
    $doHeaders,$algorithm,$sessionKey)"/>
</xsl:template>
:
:

```

decrypt-data()

Decrypts input encrypted data using a specified session key and symmetric cryptographic algorithm.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:decrypt-data(*algorithm*, *key*, *text*)

Parameters

algorithm

(xs:string) Identifies the symmetric cryptographic algorithm used for decryption. Valid values are:

`http://www.w3.org/2001/04/xmlenc#tripledes-cbc`
`http://www.w3.org/2001/04/xmlenc#aes128-cbc`
`http://www.w3.org/2001/04/xmlenc#aes192-cbc`
`http://www.w3.org/2001/04/xmlenc#aes256-cbc`

key

(xs:string) Identifies the session key used by *algorithm* to decrypt *text*. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.
- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key:` prefix, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

key was previously generated with the **decrypt-key()** extension function.

text

(xs:string) Contains the data to be decrypted.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string that contains a plaintext version of the input *text*.

Examples

```
⋮  
<xsl:value-of select="dp:decrypt-data($algorithm,$session-key,$CipherData)"  
⋮
```

decrypt-key()

Decrypts a session (ephemeral) key using a specified private key and key transport algorithm.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:decrypt-key(*encryptedKey*, *recipient*, *keyTransportAlgorithm*, *OAEPParameters*, *OAEPDigestAlgorithm*)

Parameters

encryptedKey

(xs:string) Contains the encrypted session key.

recipient

(xs:string) Identifies the message recipient's private key. The private key can take the one of the following forms:

- *name:cert*

name: Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.

- *cert:base64Cert*

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert

Specifies that the target certificate is Base64 encoded.

- *ski:certSKI*

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI

Specifies that the target certificate is the Base64 encoding of the SKI.

- *issuerserial:serial*

issuerserial:

Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use the *serial* value to search the management store for a matching certificate.

- *thumbprintsha1:sha1string*

thumbprintsha1:

Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string

Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

keyTransportAlgorithm

(xs:string) Identifies the public key transport algorithm used to decrypt the enciphered session key.

Both key transport algorithms in the W3C Proposed Recommendation 03 October 2002 version of *XML Encryption Syntax and Processing* are supported.

- To specify RSA Version 1.5, *keyTransportAlgorithm* takes the value http://www.w3.org/2001/04/xmlenc#rsa-1_5.
- To specify RSA Version-OAEP, *keyTransportAlgorithm* takes the value <http://www.w3.org/2001/04/xmlenc#rsa-oaep-mgf1p>.

OAEPParameters

(xs:string) Is an optional argument used when *keyTransportAlgorithm* indicates RSA OAEP encryption (URI ending in *rsa-oaep-mgf1p*). You must specify this argument as a Base64-encoded. The default value for *OAEPParams* is an empty string.

OAEPDigestAlgorithm

(xs:string) Is an optional argument used when *keyTransportAlgorithm* indicates RSA OAEP encryption. The OAEP digest algorithm must be the URI of a supported algorithm.

The firmware supports the following digest algorithms:

<http://www.w3.org/2000/09/xmlsig#sha1> (Default)
<http://www.w3.org/2001/04/xmlenc#sha256>
<http://www.w3.org/2001/04/xmlenc#sha512>
<http://www.w3.org/2001/04/xmlsig-more#sha224>
<http://www.w3.org/2001/04/xmlsig-more#sha384>
<http://www.w3.org/2001/04/xmlenc#ripemd160>
<http://www.w3.org/2001/04/xmlsig-more#md5>

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string that contains the plaintext session key as a Base64 encoded string.

Examples

```
:  
<xsl:variable name="sess-key"  
  select="dp:decrypt-key($encrypted-key,$recipient,$keytransport)"/>  
:
```

deflate()

Compresses an input string and returns a Base64 encoded version of the compressed string.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:deflate(*text*)

Parameters

text (xs:string) Contains the data to compress.

Guidelines

deflate() uses GZIP to compress the input string.

The argument is passed as an XPath expression.

Results

An xs:string that contains the Base64 encoded compressed input.

Examples

```
⋮  
<xsl:variable name="shortVersion" select="dp:deflate($authInfo)"/>  
⋮
```

encrypt-attachment()

Encrypts an attachment using a shared secret key and symmetric cryptographic algorithm

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:encrypt-attachment(*URI*, *doHeaders*, *algorithm*, *sessionKey*, *encoding*)

Parameters

URI (xs:string) Identifies the attachment to encrypt.

doHeaders

(xs:boolean) Indicates whether or not to encrypt the attachment headers.

algorithm

(xs:string) Identifies the symmetric cryptographic algorithm used for encryption. Valid values are:

```
http://www.w3.org/2001/04/xmlenc#tripledes-cbc  
http://www.w3.org/2001/04/xmlenc#aes128-cbc  
http://www.w3.org/2001/04/xmlenc#aes192-cbc  
http://www.w3.org/2001/04/xmlenc#aes256-cbc
```

sessionKey

(xs:string) Identifies the session key *algorithm* used for encryption. Use one of the following prefixes to refer to a shared secret key:

- *name:key*, such as *name:alice*, that refers to an already configured shared secret key object named *alice*.
- *key:Base64* refers to a Base64-encoded literal that is the shared secret key. If you enter *Base64* without the *key:* prefix, the function uses *Base64* as the key.
- *hex:hexadecimal* refers to a Hexadecimal-encoded literal that is the shared secret key.

encoding

(xs:string) Optionally specifies an encoding that the function applies before encrypting the attachment.

Guidelines

Use **encrypt-attachment()** to perform binary-to-binary encryption of an attachment. To construct the *attachmentURI*, use the following format:

cid:string

Points to the attachment to encrypt.

doHeaders

Specifies whether or not to encrypt the attachment headers.

- `true()` encrypts attachment headers.
- `false()` does not encrypt attachment headers.

sessionKey

Use the *sessionKey* and the specified cryptographic algorithm to encrypt a message attachment.

encoding

To specify Base64 encoding, enter:

`http://www.w3.org/2000/09/xmldsig#base64`

To not encode the message attachment, enter `' '` for *encoding* or leave blank.

This function passes all arguments as XPath expressions.

Results

On success, the `encrypt-attachment` function returns an empty string and encrypts the attachment. If not successful, the function returns an error message and strips the attachment.

Examples

```
⋮
<xsl:template match="/">
  <xsl:variable name="attachment" select="'cid:sheet'"/>
  <xsl:variable name="doHeaders" select="false()"/>
  <xsl:variable name="algorithm"
    select="'http://www.w3.org/2001/04/xmlenc#tripledes-cbc'"/>
  <xsl:variable name="sessionKey"
    select="dp:generate-key($algorithm)"/>
  <xsl:value-of select="dp:encrypt-attachment($attachment,
    $doHeaders,$algorithm,$sessionKey)"/>
</xsl:template>
⋮
```

encrypt-data()

Encrypts an XML document using a specified session key and symmetric cryptographic algorithm.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:encrypt-data(*algorithm*, *key*, *text*)

Parameters

algorithm

(xs:string) Identifies the symmetric cryptographic algorithm used for encryption. Valid values are:

http://www.w3.org/2001/04/xmlenc#tripledes-cbc
http://www.w3.org/2001/04/xmlenc#aes128-cbc
http://www.w3.org/2001/04/xmlenc#aes192-cbc
http://www.w3.org/2001/04/xmlenc#aes256-cbc

key

(xs:string) Identifies the session key used by *algorithm* to encrypt *text*. Use one of the following prefixes to refer to a shared secret key:

- **name:key**, such as **name:alice**, that refers to an already configured shared secret key object named **alice**.
- **key:Base64** refers to a Base64-encoded literal that is the shared secret key. If you enter *Base64* without the **key:** prefix, the function uses *Base64* as the key.
- **hex:hexadecimal** refers to a Hexadecimal-encoded literal that is the shared secret key.

text

(node set) Contains the data to be encrypted.

Guidelines

encrypt-data() is used during the XML encryption process. It uses a session key and specified cryptographic algorithm (3DES or AES) to encrypt a plaintext document.

Depending on XSLT instructions in a style sheet, a document can be selectively encrypted. That is, any or all XML elements in the plaintext document can be encrypted. All children of an encrypted element are also encrypted.

The encryption process removes the encrypted subtree from the XML document and substitutes an <EncryptedData> element in its place.

All arguments are passed as XPath expressions.

Results

A Base64 encoded xs:string that contains the encrypted *text*.

Examples

```
⋮  
<xsl:variable name="ciphertext">  
  <xsl:value-of select="dp:encrypt-data($algorithm,$session-key,$node)"/>  
</xsl:variable>  
⋮
```

encrypt-key()

Encrypts a session (ephemeral) key using a specified public key and key transport algorithm.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:encrypt-key(*sessionKey*, *recipient*, *keyTransportAlgorithm*, *OAEPParameters*, *OAEPDigestAlgorithm*)

Parameters

sessionKey

(*xs:string*) Specifies the session key. The **encrypt-key()** function processes all legal length session key inputs; it rejects (not truncates) inputs that are too long.

recipient

(*xs:string*) Identifies the message recipient's public key, which can reside in a certificate. The *keyTransportAlgorithm* uses the recipient's public key to encrypt *sessionKey*. *recipient*, because it is a standard string-based representation for extension functions, can take many different forms like *name:*, *cert:*, *ski:*, or *pkipath:*. For example, *name:certificate* refers to a Crypto Certificate object, such as *name:alice*. In this example, *name* is a constant and *certificate* is a certificate object that was previously created with the **certificate** command or with the WebGUI. The certificate object references the public key in the target X.509 certificate.

keyTransportAlgorithm

(*xs:string*) Identifies the public key transport algorithm used to encrypt the session key.

Both of the key transport algorithms in the W3C Proposed Recommendation 03 October 2002 version of *XML Encryption Syntax and Processing* are supported.

- To specify RSA Version 1.5, *keyTransportAlgorithm* takes the following value:
`http://www.w3.org/2001/04/xmenc#rsa-1_5`
- To specify RSA Version OAEP, *keyTransportAlgorithm* takes the following value:
`http://www.w3.org/2001/04/xmenc#rsa-oaep-mgf1p`

OAEPParameters

(*xs:string*) Is an optional argument used when *keyTransportAlgorithm* indicates RSA OAEP encryption (URI ending in *rsa-oaep-mgf1p*). You must specify this argument as a Base64-encoded string. The default value for *OAEPParameters* is an empty string.

OAEPDigestAlgorithm

(*xs:string*) Is an optional argument used when *keyTransportAlgorithm* indicates RSA OAEP encryption. The OAEP digest algorithm must be the URI of a supported algorithm.

The firmware supports the following digest algorithms:

`http://www.w3.org/2000/09/xmldsig#sha1` (Default)
`http://www.w3.org/2001/04/xmenc#sha256`
`http://www.w3.org/2001/04/xmenc#sha512`

```
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmlenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5
```

Guidelines

encrypt-key() is used during the XML encryption process. The session key that was created by the **generate-key()** extension function is used to encrypt the plaintext XML document, and is subsequently encrypted with the **encrypt-key()** extension function.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the encrypted session key as a Base64 encoded string.

Examples

```
⋮
<xsl:variable name="recipient-key">
  <xsl:value-of select="dp:encrypt-key($session-key,
    $recipient,$KeyTransportAlgorithm)"/>
</xsl:variable>
<xsl:variable name="ciphertext">
  <xsl:value-of select="dp:encrypt-data($algorithm,$session-key,$node)"/>
</xsl:variable>
⋮
```

encrypt-string()

Encrypts a plaintext string using a specified session key and symmetric cryptographic algorithm.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

dp:encrypt-string(*algorithm*, *key*, *text*)

Parameters

algorithm

(`xs:string`) Identifies the symmetric cryptographic algorithm used for encryption. Valid values are:

```
http://www.w3.org/2001/04/xmlenc#tripledes-cbc
http://www.w3.org/2001/04/xmlenc#aes128-cbc
http://www.w3.org/2001/04/xmlenc#aes192-cbc
http://www.w3.org/2001/04/xmlenc#aes256-cbc
```

key

(`xs:string`) Specifies the session key used by *algorithm* to encrypt *text*. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.

- *key:Base64* refers to a Base64-encoded literal that is the shared secret key. If you enter *Base64* without the *key:* prefix, the function uses *Base64* as the key.
- *hex:hexadecimal* refers to a Hexadecimal-encoded literal that is the shared secret key.

text (xs:string) Identifies the string to be encrypted.

Guidelines

All arguments are passed as XPath expressions.

Results

an xs:string with the encrypted plaintext string as a Base64 encoded string.

Examples

```

:
:
<xsl:variable name="cipherstring">
  <xsl:value-of select="dp:encrypt-string($algorithm,$session-key,$plainText)"/>
</xsl:variable>
:
:

```

exc-c14n-hash()

Canonicalizes an input node set with the specified algorithm.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:exc-c14n-hash(*prefixes*, *nodeset*, *includeComments*, *algorithm*)

Parameters

prefixes

(xs:string) Identifies a space-delimited list of the inclusive namespace prefixes. That is the namespace declarations that are emitted by either of the two exclusive canonicalization algorithms.

By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

prefixes overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string specifies an empty set of prefixes.

nodeset (node set) Contains the XML content to be canonicalized.

includeComments

(xs:boolean) Specifies the treatment of XML comments.

- *true()* specifies that comments are included.

- `false()` specifies that comments are excluded.

algorithm

(`xs:string`) that Identifies the hashing algorithm. The firmware supports the following hash algorithms:

```
http://www.w3.org/2000/09/xmldsig#sha1
http://www.w3.org/2001/04/xmenc#sha256
http://www.w3.org/2001/04/xmenc#sha512
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5
```

The default is `http://www.w3.org/2000/09/xmldsig#sha1`.

Guidelines

Canonicalizes an input node set using the algorithm specified in the W3C Recommendation 18 July 2002 version of *Exclusive XML Canonicalization* and calculates a hash value for the canonical representation.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mublens"/>
```

Where the `x` attribute is interpreted as a QName, and the `mumble` prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the `mumble` prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix `mumble` in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for `mumble` to be emitted.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the Base64-encoded hash of the canonicalized node set.

Examples

```
:
:
<xsl:variable name="digest">
  <xsl:value-of select="dp:exc-c14n-hash('', $node, false(), $hashAlgorithm)"/>
</xsl:variable>
:
```

exc-c14n-hash-set()

Canonicalizes an input node set with the specified algorithm.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:exc-c14n-hash-set(prefixes, nodeset, includeComments, algorithm)`

Parameters

prefixes

(xs:string) Identifies a space-delimited list of the inclusive namespace prefixes. That is the namespace declarations that are emitted by either of the two exclusive canonicalization algorithms.

By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

This parameter overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string specifies an empty set of prefixes.

nodeset (node set) explicitly Identifies the XML context to be canonicalized.

includeComments

(xs:boolean) Specifies the treatment of XML comments.

- `true()` specifies that comments are included.
- `false()` specifies that comments are excluded.

algorithm

(xs:string) that Identifies the hashing algorithm. The firmware supports the following hash algorithms:

```
http://www.w3.org/2000/09/xmldsig#sha1
http://www.w3.org/2001/04/xmenc#sha256
http://www.w3.org/2001/04/xmenc#sha512
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5
```

The default is `http://www.w3.org/2000/09/xmldsig#sha1`.

Guidelines

Canonicalizes an input node set with the algorithm specified in the W3C Recommendation 18 July 2002 version *Exclusive XML Canonicalization* and calculates a hash value for the canonical representation.

`exc-c14n-hash()` and `exc-c14n-hash-set()` differ in that `exc-14n-hash-set()` converts data into its canonical form only those elements and attributes explicitly passed via the *nodeset* argument. In contrast, `exc-14n-hash()` performs a deep hash that includes all child elements of the *nodeset* argument.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mumblens"/>
```

Where the `x` attribute is interpreted as a `QName`, and the `mumble` prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the `mumble` prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix `mumble` in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for `mumble` to be emitted.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the Base64-encoded hash of the canonicalized node set.

Examples

```
⋮
<xsl:value-of select="dp:exc-c14n-hash-set('',$signed-node-set,false()),
$hashAlgorithm"/>
⋮
```

generate-key()

Generates a session (ephemeral) key in the format required by a specified cryptographic algorithm.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:generate-key(algorithm)
```

Parameters

algorithm

(`xs:string`) Identifies the symmetric cryptographic algorithm used for encryption. Valid values are:

```
http://www.w3.org/2001/04/xmlenc#tripledes-cbc
http://www.w3.org/2001/04/xmlenc#aes128-cbc
http://www.w3.org/2001/04/xmlenc#aes192-cbc
http://www.w3.org/2001/04/xmlenc#aes256-cbc
```

Guidelines

generate-key() is used during the encryption process. The generated key is used to encrypt a plaintext document, and is subsequently encrypted with **encrypt-key()**.

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the session key as a Base64 encoded string.

Examples

```
⋮
<xsl:variable name="session-key">
  <xsl:value-of select="dp:generate-key($algorithm)"/>
</xsl:variable>
⋮
```

generate-passticket()

Generates a PassTicket used to authenticate to the NSS server.

Availability

All products except XA35, XB60

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:generate-passticket(*user*, *application-ID*, *key*)

Parameters

user (xs:string) Specifies the name used to authenticate to the NSS server.

application-ID
(xs:string) Specifies the application ID as defined on the NSS server.

key (xs:string) Identifies an existing key on the NSS server.

Guidelines

The **generate-passticket** function generates a PassTicket. The PassTicket must be generated before using the **zosnss-passticket-authen** function with the same application ID. A PassTicket is generated using the current time on the system and can be used only within ten minutes of generation. To avoid a PassTicket authentication failure, ensure that the time on the DataPower appliance and the z/OS® NSS system are synchronized when the PassTicket is generated.

Results

On success, the function returns the PassTicket to be used for authentication. If not successful, the function returns an empty string.

Examples

This custom style sheet generates a PassTicket using the `generate-passticket` function and authenticates the user `USER1` using the PassTicket on the NSS server specified in the z/OS NSS Client object `zosnss1`.

```
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:dpconfig="http://www.datapower.com/param/config"
  extension-element-prefixes="dp"
  exclude-result-prefixes="dp dpconfig">

  <xsl:template match="/">
    <xsl:variable name="passticket"
      select="dp:generate-passticket('USER1', 'APP1',
        'E001193519561977')" />
    <xsl:variable name="auth"
      select="dp:zosnss-passticket-authen('USER1',
        $passticket, 'APP1', 'zos1')" />
    <passticketauthen>
      zosnss passticketauthen return:[
        <xsl:value-of select="$auth" />
      ]
    </passticketauthen>
  </xsl:template>

</xsl:stylesheet>
```

get-cert-details()

Extracts information from a specified X.509 certificate.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:get-cert-details(cert )
```

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.
- `name:cert`
 - `name:` Indicates the required literal prefix for a certificate that is identified by object name.
 - *cert*
 - cert* Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - `cert:base64Cert`
 - `cert:` Indicates the required literal prefix for a Base64 encoded certificate.

- base64Cert*
Specifies that the target certificate is Base64 encoded.
- *ski:certSKI*
 - ski:* Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).
 - certSKI*
Specifies that the target certificate is the Base64 encoding of the SKI.
- *issuerserial:serial*
 - issuerserial:*
Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).
 - serial* Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- *thumbprintsha1:sha1string*
 - thumbprintsha1:*
Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.
 - sha1string*
Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- *pkcs7:base64Cert*
 - pkcs7:* Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.
 - base64Cert*
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- *pkipath:base64cert*
 - pkipath:*
Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.
 - base64cert*
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

The argument is passed as an XPath expression.

Results

A node set (the contents of the certificate in XML format) that contains the following certificate-specific data:

Version

Specifies the version of the target certificate (usually 3)

Serial Number

the certificate serial number assigned by the CA

Signature Algorithm

Identifies the algorithm used by the issuing CA to sign this certificate

Issuer the DN of the CA that issued and signed the certificate

Not Before (Zulu time)

the certificate start time

Not After (Zulu time)

the certificate end time

Subject

the entity associated with the public key contained in the certificate

Subject Public Key Algorithm

public key data

Extensions

includes extension name, criticality, and OID

Examples

```

:
<xsl:variable name="cert-data">
  <xsl:value-of select="dp:get-cert-details($certAlice)"/>
</xsl:variable>
:

```

get-cert-issuer()

Extracts the issuing CA from a specified X.509 certificate.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:get-cert-issuer(*cert*)

Parameters

cert (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.

- name:*cert*

name: Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.

- *cert:base64Cert*
cert: Indicates the required literal prefix for a Base64 encoded certificate.
base64Cert
Specifies that the target certificate is Base64 encoded.
- *ski:certSKI*
ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).
certSKI
Specifies that the target certificate is the Base64 encoding of the SKI.
- *issuerserial:serial*
issuerserial:
Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).
serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- *thumbprintsha1:sha1string*
thumbprintsha1:
Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.
sha1string
Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- *pkcs7:base64Cert*
pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.
base64Cert
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- *pkipath:base64cert*
pkipath:
Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.
base64cert
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

The argument is passed as an XPath expression.

Results

An xs:string that contains the distinguished name (DN) of the issuing CA.

Examples

```
⋮
<xsl:variable name="certauth">
  <xsl:value-of select="dp:get-cert-issuer($certBob)"/>
</xsl:variable>
⋮
```

get-cert-serial()

Extracts the serial number from a specified X.509 certificate.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:get-cert-serial(*cert*)

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.
- **name:***cert*
name: Indicates the required literal prefix for a certificate that is identified by object name.
cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - **cert:***base64Cert*
cert: Indicates the required literal prefix for a Base64 encoded certificate.
base64Cert Specifies that the target certificate is Base64 encoded.
 - **ski:***certSKI*
ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).
certSKI Specifies that the target certificate is the Base64 encoding of the SKI.
 - **issuerserial:***serial*

- issuerserial:**
Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).
 - serial** Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- thumbprintsha1:*sha1string*
 - thumbprintsha1:**
Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.
 - sha1string**
Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- pkcs7:*base64Cert*
 - pkcs7:** Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.
 - base64Cert**
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- pkipath:*base64cert*
 - pkipath:**
Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.
 - base64cert**
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the serial number of the target certificate.

Examples

```

:
:
<xsl:variable name="certserial">
  <xsl:value-of select="dp:get-cert-serial($certAlice)"/>
</xsl:variable>
:
:

```

get-cert-ski()

Extracts the contents of the Subject Key Identifier extension from a specified X.509 certificate.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:get-cert-ski(cert)`

Parameters

- cert* (xs:string) Identifies the target certificate. The target certificate can be identified in any of the following ways.
- `name:cert`
`name:` Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - `cert:base64Cert`
`cert:` Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert
Specifies that the target certificate is Base64 encoded.
 - `ski:certSKI`
`ski:` Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI
Specifies that the target certificate is the Base64 encoding of the SKI.
 - `issuerserial:serial`
`issuerserial:`
Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
 - `thumbprintsha1:sha1string`
`thumbprintsha1:`
Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string
Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
 - `pkcs7:base64Cert`

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.

- **pkipath:***base64cert*

pkipath:

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the contents of the Subject Key Identifier extension from the target certificate.

Examples

```
⋮
<xsl:variable name="certskil">
  <xsl:value-of select="dp:get-cert-ski($certTrudy)"/>
</xsl:variable>
⋮
```

get-cert-subject()

Extracts subject information from a specified X.509 certificate.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:get-cert-subject(cert)`

Parameters

cert (`xs:string`) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.

- **name:***cert*

- name:** Indicates the required literal prefix for a certificate that is identified by object name.
- cert** Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
- **cert:base64Cert**

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert
Specifies that the target certificate is Base64 encoded.
- **ski:certSKI**

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI
Specifies that the target certificate is the Base64 encoding of the SKI.
- **issuerserial:serial**

issuerserial:
Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- **thumbprintsha1:sha1string**

thumbprintsha1:
Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string
Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- **pkcs7:base64Cert**

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- **pkipath:base64cert**

pkipath:
Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the subject information extracted from the certificate.

Examples

```
⋮  
<xsl:variable name="cert-subject" select="dp:get-cert-subject('cert:Bob')"/>  
⋮
```

get-cert-thumbprintsha1()

Returns the SHA-1 thumbprint from an X.509 certificate

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:get-cert-thumbprintsha1(cert)`

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.
- *name:cert*
name: Indicates the required literal prefix for a certificate that is identified by object name.
cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - *cert:base64Cert*
cert: Indicates the required literal prefix for a Base64 encoded certificate.
base64Cert Specifies that the target certificate is Base64 encoded.
 - *ski:certSKI*
ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI

Specifies that the target certificate is the Base64 encoding of the SKI.

- *issuerserial:serial*

issuerserial:

Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.

- *thumbprintsha1:sha1string*

thumbprintsha1:

Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string

Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

- *pkcs7:base64Cert*

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.

- *pkipath:base64cert*

pkipath:

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the SHA thumbprint.

Examples

```
⋮
<wsse:KeyIdentifier ValueType="http://docs.oasis-open.org/wss/
oasis-wss-soap-message-security-1.1#ThumbPrintSHA1">
  <xsl:value-of select="dp:get-cert-thumbprintsha1(
    concat('name:', $recipient))"/>
```

```
</wsse:KeyIdentifier>
:
```

get-kerberos-apreq()

Acting on behalf of a Kerberos client, obtains a Kerberos AP-REQ message from a KDC (Key Distribution Center).

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:get-kerberos-apreq(*client*, *keyInfo*, *server*)

Parameters

client (xs:string) Identifies the client principal

keyInfo (xs:string) Identifies the secret shared key used by the requesting client and KDC.

keyInfo consists of a literal prefix followed by a string and takes one of the following forms:

- **password:***string* where **password:** is the required literal and *string* is the client's Kerberos shared secret
- **keytab:***string* where **keytab:** is the required literal and *string* is the Base64-encoded contents of a Kerberos Keytab file, a Kerberos binary file that contains a list of principal names and corresponding secret shared keys

Note: The keytab method is not currently supported.

- **keytabname:***string* where **keytabname:** is the required literal and *string* is the DataPower object representation of a Kerberos Keytab file, a Kerberos binary file that contains a list of principal names and corresponding secret shared keys

server (xs:string) Identifies the server principal

Guidelines

A Kerberos AP-REQ message (the actual message that a requesting client sends to a server) consists of a Kerberos ticket and an authenticator, the proof that the requesting client is in fact the entity vouched for by the ticket.

If the keytabname method is used to identify a Kerberos Keytab, the keytab object must have been configured within the caller's domain.

All arguments are passed as XPath expressions.

Results

A node set that contains the Kerberos AP-REQ message obtained from the KDC.

Examples

```
⋮
<xsl:variable name="apreq"
  select="dp:get-kerberos-apreq($dpconfig:clientprinc,concat(
    'keytabname:', $dpconfig:keytab), $dpconfig:serverprinc)"/>
⋮
```

hash()

Calculates a hash of a text string.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:hash(algorithm, text)`

Parameters

algorithm

(`xs:string`) that Identifies the hashing algorithm. The firmware release supports the following hash algorithms:

```
http://www.w3.org/2000/09/xmldsig#sha1
http://www.w3.org/2001/04/xmenc#sha256
http://www.w3.org/2001/04/xmenc#sha512
http://www.w3.org/2001/04/xmldsig-more#sha224
http://www.w3.org/2001/04/xmldsig-more#sha384
http://www.w3.org/2001/04/xmenc#ripemd160
http://www.w3.org/2001/04/xmldsig-more#md5
```

text (`xs:string`) Contains the text to be hashed.

Guidelines

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains the Base64-encoded hash of the input string.

Examples

```
⋮
<xsl:variable name="sha-hash" select="dp:hash($SHA1, $plainText)"/>
⋮
```

hash-base64()

Calculates a hash of a Base64-encoded string.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:hash-base64(algorithm, textString)`

Parameters

algorithm

(*xs:string*) that identifies the hashing algorithm. The firmware supports the following hash algorithms:

`http://www.w3.org/2000/09/xmldsig#sha1`
`http://www.w3.org/2001/04/xmlenc#sha256`
`http://www.w3.org/2001/04/xmlenc#sha512`
`http://www.w3.org/2001/04/xmldsig-more#sha224`
`http://www.w3.org/2001/04/xmldsig-more#sha384`
`http://www.w3.org/2001/04/xmlenc#ripemd160`
`http://www.w3.org/2001/04/xmldsig-more#md5`

textString

(*xs:string*) Contains the Base64-encoded text to be hashed.

Guidelines

All arguments are passed as XPath expressions.

Results

An *xs:string* that contains the Base64-encoded hash of the Base64-decoded input string.

Examples

```
⋮
<xsl:when test="$use-encryptedkeysha1 = 'true'">
  <xsl:value-of select="dp:hash-base64(
    'http://www.w3.org/2000/09/xmldsig#sha1',$session-key)' />
</xsl:when>
⋮
```

inflate()

Decompresses a Base64-encoded string and returns a decoded version of the string.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:inflate(text)`

Parameters

text (*xs:string*) that is to be decompressed using the GZIP algorithm and Base64-encoded.

Guidelines

`inflate()` uses GZIP to decompress the input string.

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the non-compressed and decoded string.

Examples

```
⋮  
<xsl:variable name="longVersion" select="dp:inflate($authInfo)"/>  
⋮
```

Idap-authen()

Makes an LDAP authentication request.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:ldap-authen(*bindDN*, *bindPassword*, *serverAddress*, *sslProxyProfileName*,
ldapLBGroup, *sslCertificate*)

Parameters

bindDN

(`xs:string`) Specifies the distinguished name used to authenticate to the LDAP server.

bindPassword

(`xs:string`) Specifies the password used to authenticate to the LDAP server.

serverAddress

(`xs:string`) Optionally identifies an LDAP server, and may be supplied as a dotted-decimal IP address-port pair, or as a FQDN.

sslProxyProfileName

type `xs:string`) Optionally identifies an existing SSL Proxy Profile. If an SSL Proxy Profile is provided, the client (forward) SSL profile included in that proxy profile establishes a secure connection with the LDAP server.

ldapLBGroup

(`xs:string`) required in the absence of an explicit *serverAddress*, and otherwise optional, specifies the name of an LDAP load balancer group.

sslCertificate

(`xs:string`)

Guidelines

All arguments are passed as XPath expressions.

Results

A node set that contains the server response.

Examples

```
⋮
<xsl:choose>
  <xsl:when test="dp:ldap-authen($username, $password,
    '172.21.223.178:21389')">
    <dp:accept/>
  </xsl:when>
  <xsl:otherwise>
    <dp:send-error override="true">
      <xsl:copy-of select="$rejectMsg"/>
    </dp:send-error>
  </xsl:otherwise>
</xsl:choose>
⋮
```

ldap-search()

Queries an LDAP server for a general (nonspecific) search.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:ldap-search(*serverAddress*, *portNumber*, *bindDN*, *bindPassword*, *targetDN*,
attributeName, *filter*, *scope*, *sslProxyProfile*, *ldapLBGroup*)

Parameters

serverAddress

(xs:string) Provides the location of the target LDAP server, and may be supplied as a dotted-decimal IP address or as a FQDN. Required in the absence of a specified LDAP load balancer group. If an LDAP load balancer group is identified by the *ldapLBGroup* argument, use an empty string for this argument.

portNumber

(xs:string) Identifies the LDAP server port. The default LDAP port is 389.

bindDN

(xs:string) Specifies the distinguished name used to authenticate to the LDAP server. An empty string specifies anonymous access.

bindPassword

(xs:string) Specifies the password used to authenticate to the LDAP server. An empty string specifies no password.

targetDN

(xs:string) Specifies the base distinguished name for the search. All sub-trees rooted at this base will be queried.

attributeName

(xs:string) Specifies the target attribute whose value will be returned by the LDAP server.

filter (xs:string) Is an LDAP filter expression as defined in RFC 2254, *The String Representation of LDAP Filters*. The search will return the attribute values for every expression in the subtree satisfying the filter expression.

scope (xs:string) Specifies the depth of the LDAP search. Use one of the following values:

base Matches only the function input

one Matches the function input and any object one level below

sub Matches the function input and any descendents

sslProxyProfile

(xs:string) Optionally identifies an existing SSL Proxy Profile. If an SSL Proxy Profile is provided, the client (forward) SSL profile included in that proxy profile will be used to establish a secure connection with the LDAP server. In the absence of a specified SSL Proxy Profile, the function provides a default value of an empty string.

ldapLBGroup

(xs:string) required in the absence of an explicit *serverAddress*, and otherwise optional, specifies the name of an LDAP load balancer group.

- If an LDAP load balancer is specified, use an empty string for the *serverAddress* and *portNumber* parameters.
- If an LDAP load balancer is not specified, the function provides a default value of an empty string.

Guidelines

All arguments are passed as XPath expressions.

Results

A node set corresponding to an XML fragment that contains the search results.

Examples

```
⋮
dp:ldap-search('cryptoboy.datapower.com','','','ou=Tappet Brothers Staff,dc=datapower,dc=com','cn',
'', 'one', '', '')
⋮
```

Performs an anonymous query of the LDAP server at cryptoboy.datapower.com, retrieving the values of the cn attribute for every entity in the subtree rooted at ou=Tappet Brothers Staff,dc=datapower,dc=com.

The filter expression is the empty string; signifying that every entity satisfies the empty filter.

The function returns a node set similar to the following:

```
⋮
<LDAP-search-results xmlns="http://www.datapower.com/extensions">
  <result>
    <DN>cn=Paul Murky,ou=Tappet Brothers Staff,dc=datapower,dc=com</DN>
    <attribute-value name="cn">Paul Murky</attribute-value>
```



```

        <attribute-value name="cn">Murky Research</attribute-value>
    </result>
    <result>
        <DN>cn=Marge Murky,ou=Tappet Brothers Staff,dc=datapower,dc=com</DN>
        <attribute-value name="cn">Marge Murky</attribute-value>
    </result>
    <result>
        <DN>cn=Mike Easter,ou=Tappet Brothers Staff,dc=datapower,dc=com</DN>
        <attribute-value name="cn">Mike Easter</attribute-value>
    </result>
</LDAP-search-results>
:
:

```

The return contains a `<result>` element for each DN matching the filter, whether or not the requested attribute is defined for that DN. The text in the `<DN>` child element of the `<result>` element is the DN of the matching entity. For each the requested attribute, there is an `<attribute-value>` element whose text is the attribute's value.

An entity may have multiple values for an attribute, in which case there are multiple attribute-value elements. For example, Paul Murky's entry in the LDAP directory contains two values for the `cn` attribute, so there are two attribute-value child elements of the result element for Paul Murky.

ldap-simple-query()

Queries an LDAP server for a single attribute value for a specific entity (distinguished name).

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:ldap-simple-query(*serverAddress*, *portNumber*, *bindDN*, *bindPassword*, *targetDN*, *attributeName*, *scope*, *sslProxyProfile*, *ldapLBGroup*)

Parameters

serverAddress

(xs:string) Specifies the required address of the LDAP server, and may be expressed as a dotted-decimal IP address or as a FQDN. Use an empty string if LDAP access is accomplished via an LDAP load balancer group, and refer to *ldapLBGroup*.

portNumber

(xs:string) Specifies the required LDAP server port. Use an empty string if LDAP access is accomplished via an LDAP load balancer group, and refer to *ldapLBGroup*.

bindDN

(xs:string) Specifies the required distinguished name used to authenticate to the LDAP server. An empty string specifies anonymous access.

bindPassword

(xs:string) Specifies the required password used to authenticate to the LDAP server. An empty string specifies no password.

targetDN

(xs:string) Specifies the required distinguished name of the target entity that will be queried.

attributeName

(xs:string) Specifies the required target attribute whose value will be returned by the LDAP server.

scope (xs:string) Specifies the required depth of the LDAP search. Use one of the following values:

base Matches only the function input

one Matches the function input and any object one level below

sub Matches the function input and any descendents

sslProxyProfile

(xs:string) Optionally identifies an existing SSL Proxy Profile. If an SSL Proxy Profile is provided, the client (forward) SSL profile included in that proxy profile will be used to establish a secure connection with the LDAP server. In the absence of a specified SSL Proxy Profile, the function provides a default value of an empty string.

ldapLBGroup

(xs:string) required in the absence of an explicit *serverAddress*, and otherwise optional, specifies the name of an LDAP load balancer group.

- If an LDAP load balancer is specified, use an empty string for the *serverAddress* and *portNumber* parameters.
- If an LDAP load balancer is not specified, the function provides a default value of an empty string.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string that contains the requested attribute value.

Examples

```
⋮
dp:ldap-simple-query('krb.datapower.com','',',',
'cn=Mike East,ou=Tappet Brothers Staff,dc=cartalk,dc=com',
'title','base','',')
⋮
```

Logs on to default port 389 of LDAP server krb.datapower.com as anonymous and returns the value of the title attribute for Mike East.

```
⋮
dp:ldap-simple-query('krb.datapower.com','',
'cn=Manager,dc=datapower,dc=com','YetAnotherPassword',
'cn=Paul Murky,ou=Tappet Brothers Staff,dc=cartalk,dc=com',
```

```

    'userCertificate','base','','')
    :

```

Uses the distinguished name CN=Manager,dc=datapower,dc=com and the password YetAnotherPassword to authenticate via the default port to the LDAP server, krb.datapower.com. Retrieves the value of the userCertificate attribute for Paul Murky and returns the attribute value as a string. Because the LDAP server returns the certificate as binary data, the string is the Base64 encoding of the X.509 certificate. The LDAP server indicates that the returned data is in binary format by appending a ;binary string to the attribute name in its response.

ocsp-validate-certificate()

Makes an OCSF (Online Certificate Status Protocol) request to an OCSF server, validates the server response, and returns an XML representation of the response.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:ocsp-validate-certificate(*cert, issuer, valCred, ocspServerUrl, nonce, idCred, sslProxyProfile*)

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate from which data will be extracted. The target certificate can be identified in any of the following ways.
- **name:cert**

name: Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - **cert:base64Cert**

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert Specifies that the target certificate is Base64 encoded.
 - **ski:certSKI**

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI Specifies that the target certificate is the Base64 encoding of the SKI.
 - **issuerserial:serial**

- issuerserial:
 - Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).
 - serial
 - Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- thumbprintsha1:*sha1string*
 - thumbprintsha1:
 - Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.
 - sha1string*
 - Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- pkcs7:*base64Cert*
 - pkcs7:
 - Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.
 - base64Cert*
 - Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- pkipath:*base64cert*
 - pkipath:
 - Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.
 - base64cert*
 - Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.
- issuer* (xs:string) Identifies the issuer certificate, the certificate of the CA that issued the target certificate. The issuer certificate can be identified in any of the following ways.
 - name:*cert*
 - name:
 - Indicates the required literal prefix for a certificate that is identified by object name.
 - cert*
 - Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - cert:*base64Cert*
 - cert:
 - Indicates the required literal prefix for a Base64 encoded certificate.
 - base64Cert*
 - Specifies that the target certificate is Base64 encoded.
 - ski:*certSKI*

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI

Specifies that the target certificate is the Base64 encoding of the SKI.

- **issuerserial:serial**

issuerserial:

Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.

- **thumbprintsha1:sha1string**

thumbprintsha1:

Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string

Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

- **pkcs7:base64Cert**

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.

- **pkipath:base64cert**

pkipath:

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

valCred

(xs:string) Identifies the Validation Credentials Set that contains the OCSP Authorized Responder's public certificate. This Validation Credentials Set will be used to validate the signature on the received OCSP response. OCSP requires that all OCSP responses be digitally signed.

ocspServerUrl

(xs:string) Optionally identifies the target OCSP responder.

In the absence of this argument, the firmware provides a default value of %aia% that indicates that the identity of the OCSP responder is extracted from the target certificate's AIA (Authority Information Access) field.

nonce (xs:string) Optionally specifies the OCSF *nonce* (an arbitrary Base64-encoded string, used to bind OCSF requests and responses), and takes one of the following formats:

- %rand%* (Default) Specifies that the nonce extension (defined in Section 4.4.1 of RFC 2560, *X.509 Internet Public Key Infrastructure Online Certificate Status Protocol - OCSF*) is included in the OCSF request; the nonce value is randomly generated by this extension function.
- ' '* (empty string) Specifies that the nonce extension is excluded in the OCSF request.
- base64EncodedString* Specifies that the nonce extension is included in the OCSF request; the nonce value is set to this Base64-encoded string.

idCred (xs:string) Optionally specifies whether or not the OCSF request generated by this extension element is signed.

- ' '* (Default) Specifies that the OCSF request is not signed.
- idCred* Specifies the name of an Identification Credentials Set (a matched public-private key pair that contains the private key used to sign the OCSF response). Provision of an Identification Credentials set indicates that the OCSF request is to be signed. The named Identification Credentials Set is used for the signing operation.

sslProxyProfile (xs:string) Optionally identifies an existing SSL Proxy Profile. If an SSL Proxy Profile is provided, the client (forward) SSL profile included in that proxy profile will be used to establish a secure connection with the OCSF responder.

In the absence of a specified SSL Proxy Profile, the function provides a default value of an empty string.

Guidelines

All arguments are passed as XPath expressions.

Results

An XML-formatted report that takes the following form.

```
<ocsp-response>
  <ocsp-response-base64>
    MIIEEdAoBAKCCBG0w...
  </ocsp-response-base64>
  <ocsp-response-status>successful</ocsp-response-status>
  <ocsp-basic-response>
    <ocsp-produced-at format="zulu" generalized="20040806152739Z">
      2004-08-06T15:27:39Z
    </ocsp-produced-at>
    <ocsp-single-response>
      <ocsp-cert-status>good</ocsp-cert-status>
    </ocsp-single-response>
    <ocsp-nonce>yjGKfsleR+/ZiZeq29oZBg==</ocsp-nonce>
  </ocsp-basic-response>
</ocsp-response>
```

The return contains a formatted version of the response received from the OCSF Authorized Responder in addition to a Base64 encoding of the actual response, contained within the *ocsp-response-base64* element.

This element can be provided as an argument to the **ocsp-validate-response()** function at a later time.

If **ocsp-cert-status** is other than **successful**, the returned report does not contain an **ocsp-basic-response** element.

In certain cases, where the OCSF could not be contacted, the return takes the **<ocsp-error>error message</ocsp-error>** form.

ocsp-validate-response()

Processes an OCSF server response, previously obtained by **ocsp-validate-certificate()**, and enables a later audit of the OCSF server response.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:ocsp-validate-response(*cert, issuer, valCred, nonce, response*)

Parameters

- cert* (xs:string) Identifies the target certificate, the certificate whose revocation status is to be checked. The target certificate can be identified in any of the following ways.
- **name:cert**
name: Indicates the required literal prefix for a certificate that is identified by object name.
cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - **cert:base64Cert**
cert: Indicates the required literal prefix for a Base64 encoded certificate.
base64Cert Specifies that the target certificate is Base64 encoded.
 - **ski:certSKI**
ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).
certSKI Specifies that the target certificate is the Base64 encoding of the SKI.
 - **issuerserial:serial**
issuerserial: Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

- serial* Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- thumbprintsha1:*sha1string*
 - thumbprintsha1: Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.
 - sha1string* Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- pkcs7:*base64Cert*
 - pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.
 - base64Cert* Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- pkipath:*base64cert*
 - pkipath: Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.
 - base64cert* Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.
- issuer* (xs:string) Identifies the issuer certificate, the certificate of the CA that issued the target certificate. The issuer certificate can be identified in any of the following ways.
 - name:*cert*
 - name: Indicates the required literal prefix for a certificate that is identified by object name.
 - cert* Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - cert:*base64Cert*
 - cert: Indicates the required literal prefix for a Base64 encoded certificate.
 - base64Cert* Specifies that the target certificate is Base64 encoded.
 - ski:*certSKI*
 - ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI

Specifies that the target certificate is the Base64 encoding of the SKI.

- *issuerserial:serial*

issuerserial:

Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.

- *thumbprintsha1:sha1string*

thumbprintsha1:

Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string

Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

- *pkcs7:base64Cert*

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.

- *pkipath:base64cert*

pkipath:

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

valCred

(xs:string) Identifies the Validation Credentials Set that contains the OCSP Authorized Responder's public certificate. This Validation Credentials Set will be used to validate the signature on the received OCSP response. OCSP requires that all OCSP responses be digitally signed.

nonce (xs:string) Specifies the OCSP *nonce* (an arbitrary Base64-encoded string, used to bind OCSP requests and responses), and takes one of the following formats:

- ' ' Specifies that the nonce extension was excluded in the OCSP request.

base64EncodedString

Specifies that the nonce extension was included in the OCSF request; the nonce value was set to this Base64-encoded string.

response

(xs:string) Contains the Base64 encoding of the OCSF response (the contents of the <ocsp-response-base64> element contained in the XML returned by the **ocsp-validate-certificate()** function.

Guidelines

All arguments are passed as XPath expressions.

Results

An XML-formatted report that takes the following form.

```
<ocsp-response>
  <ocsp-response-base64>
    MIIEEdAoBAKCCBG0w...
  </ocsp-response-base64>
  <ocsp-response-status>successful</ocsp-response-status>
  <ocsp-basic-response>
    <ocsp-produced-at format="zulu" generalized="20040806152739Z">
      2004-08-06T15:27:39Z
    </ocsp-produced-at>
    <ocsp-single-response>
      <ocsp-cert-status>good</ocsp-cert-status>
    </ocsp-single-response>
    <ocsp-nonce>yjGKfsleR+/ZiZeq29oZBg==</ocsp-nonce>
  </ocsp-basic-response>
</ocsp-response>
```

The return contains a formatted version of the response received from the OCSF Authorized Responder in addition to a Base64 encoding of the actual response, contained within the ocsp-response-base64 element.

This element can be provided as an argument to the **ocsp-validate-response()** function at a later time.

If ocsp-cert-status is other than successful, the returned report does not contain an ocsp-basic-response element.

In certain cases, where the OCSF could not be contacted, the return takes the <ocsp-error>error message</ocsp-error> form.

parse-kerberos-apreq()

Acting on behalf of a Kerberos server, parses a Kerberos AP-REQ message presented by a requesting client.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:parse-kerberos-apreq(apreq, keyInfo, server)

Parameters

apreq (xs:string) Specifies the Base64-encoded Kerberos AP-REQ message.

keyInfo (xs:string) Identifies the secret shared key used by the server and KDC; this key is used to decrypt the AP-REQ message.

keyInfo consists of a literal prefix followed by a string and takes one of the following forms:

- *password:string* where *password:* Specifies the required literal and *string* is the server's Kerberos shared secret
- *keytab:string* where *keytab:* Specifies the required literal and *string* is the Base64-encoded contents of a Kerberos Keytab file, a Kerberos binary file that contains a list of principal names and corresponding secret shared keys

Note: The password and keytab methods are not currently supported.

- *keytabname:string* where *keytabname:* is the required literal, and *string* is the DataPower object representation of a Kerberos Keytab file, a Kerberos binary file that contains a list of principal names and corresponding secret shared keys

server (xs:string) Optionally identifies the server principal. If present used to constrain the keytab lookup

Guidelines

A Kerberos AP-REQ message (the actual message that a requesting client sends to a server) consists of a Kerberos ticket and an authenticator, the proof that the requesting client is in fact the entity vouched for by the ticket.

If the *keytabname* method is used to identify a Kerberos Keytab, the keytab object must have been configured within the caller's domain.

All arguments are passed as XPath expressions.

Results

A node set that contains the fields of the decrypted Kerberos ticket (to include client principal, server principal, session key, session key ID, and so forth).

This function also verifies the authenticator, and returns an error if verification fails.

Examples

```
⋮
<xsl:when test="$AU/AUMethod = 'kerberos'">
  <xsl:variable name="apreq" select="dp:parse-kerberos-apreq($first-apreq,
    concat('keytabname:', $AU/AUKerberosKeytab), $AU/AUKerberosPrincipal)"/>
  <entry type="kerberos">
    <xsl:if test="$apreq/apreq/ticket/client">
      <xsl:copy-of select="$apreq" />
    </xsl:if>
  </entry>
```

```
</xsl:when>
⋮
```

random-bytes()

Generates a random string of Base64-encoded bytes.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:random-bytes(length)`

Parameters

length The number of bytes of the generated string.

Guidelines

Can be used to generate a nonce value.

The argument is passed as an XPath expression.

Results

An `xs:string` that contains the generated Base64-encoded bytes

Examples

```
⋮
<xsl:variable name="nonce" select="dp:random-bytes(20)"/>
⋮
```

radix-convert()

Performs numeric conversions between decimal, hexadecimal, and base-64 values.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:radix-convert(data, input-radix, output-radix)`

Parameters

data (`xs:string`) Provides the numeric data to convert. The data can be a base-64 encoded strings with one or two padding characters represented by `=` characters; for example, `dGVzdA==` shows the encoded string with two padding characters.

input-radix

(xs:string) Identifies the radix from which to convert. Supported values are 0, 10, 16, and 64.

- To convert from a decimal number, specify 10
- To convert from a hexadecimal number with the 0x prefix, specify 0
- To convert from a hexadecimal number without the 0x prefix, specify 16
- To convert from a base-64 number, specify 64

output-radix

(xs:string) Identifies the radix to which to convert. Supported values are 0, 10, 16, and 64.

- To convert to a decimal number, specify 0 or 10
- To convert to a hexadecimal number, specify 16
- To convert to a base-64 number, specify 64

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string that contains the converted input.

Examples

- Converts the 792 decimal value to hexadecimal. The result is 318.
:
<xsl:variable name="decToHex"
 select="dp:radix-convert(792, 10, 16)" />
:
- Converts the 0x12 hexadecimal value to decimal. The result is 18.
:
<xsl:variable name="0xHexToDec"
 select="dp:radix-convert(x012, 0, 10)" />
:
- Converts the 12 hexadecimal value to decimal. The result is 18.
:
<xsl:variable name="HexToDec"
 select="dp:radix-convert(12, 16, 10)" />
:
- Converts the base-64 encoded string dGVzdA with two padding characters to hexadecimal. The result is 74657374.
:
<xsl:variable name="base64ToHex"
 select="dp:radix-convert("dGVzdA==", 64, 16)" />
:

same-dn()

Compares the distinguished names extracted from two specified X.509 certificates.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:same-dn(DN1,DN2)`

Parameters

DN1 and *DN2*

(*xs:string*) Identifies the two distinguished names to compare.

Guidelines

All arguments are passed as XPath expressions.

Results

A *xs:boolean*:

- `true()` if the certificates contain the same distinguished name.
- `false()` if otherwise.

Examples

- Compare `c=us,cn=foo` to `CN=foo,C=us`.
`dp:same-dn('c=us,cn=foo','CN=foo,C=us')`

sign()

Generates a digital signature.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:sign(signMechanism, hash, key)`

Parameters

signMechanism

(*xs:string*) Identifies the algorithm used to generate the digital signature. *signMechanism* must reference one of the following algorithms:

`http://www.w3.org/2000/09/xmldsig#dsa-sha1`
`http://www.w3.org/2000/09/xmldsig#rsa-sha1`
`http://www.w3.org/2001/04/xmldsig-more#rsa-sha256`
`http://www.w3.org/2001/04/xmldsig-more#rsa-sha512`
`http://www.w3.org/2001/04/xmldsig-more#rsa-sha384`
`http://www.w3.org/2001/04/xmldsig-more/rsa-ripemd160`
`http://www.w3.org/2001/04/xmldsig-more#rsa-md5`

hash (*xs:string*) Specifies the hash of the <SignedInfo> element.

- key* (xs:string) Identifies the private key used to encrypt the *hash* parameter to generate the digital signature. The private key can take the one of the following forms:
- *name:cert*

name: Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.
 - *cert:base64Cert*

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert Specifies that the target certificate is Base64 encoded.
 - *ski:certSKI*

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI Specifies that the target certificate is the Base64 encoding of the SKI.
 - *issuerserial:serial*

issuerserial: Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use the *serial* value to search the management store for a matching certificate.
 - *thumbprintsha1:sha1string*

thumbprintsha1: Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

Guidelines

All arguments are passed as XPath expressions.

Results

An xs:string that contains a digital signature

Examples

```

:
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
  <xsl:copy-of select="$signedinfo-subtree"/>
  <SignatureValue>

```

```

        <xsl:value-of select="dp:sign($sigmech,$signedinfo-hash,$keyid)"/>
    </SignatureValue>
    <xsl:if test='$certid!=""'>
        <KeyInfo><X509Data><X509Certificate>
            <xsl:value-of select="dp:base64-cert($certid)"/>
        </X509Certificate></X509Data></KeyInfo>
    </xsl:if>
</Signature>
:

```

sign-hmac()

Generates a HMAC signature.

Availability

All products except XA35

Namespace declaration

xmlns:dp="http://www.datapower.com/extensions"

Syntax

dp:sign-hmac(*signMechanism*, *outputLength*, *signedInfoSubtree*, *sharedSecretKey*, *includeComments*, *canonicalizationAlgorithm*, *prefixes*)

Parameters

signMechanism

(xs:string) Identifies the algorithm used to generate the HMAC signature. *signMechanism* must reference one of the following:

```

http://www.w3.org/2000/09/xmlsig#hmac-sha1
http://www.w3.org/2001/04/xmlsig-more#hmac-sha256
http://www.w3.org/2001/04/xmlsig-more#hmac-sha512
http://www.w3.org/2001/04/xmlsig-more#hmac-sha224
http://www.w3.org/2001/04/xmlsig-more#hmac-sha384
http://www.w3.org/2001/04/xmlsig-more#hmac-ripemd160
http://www.w3.org/2001/04/xmlsig-more#hmac-md5

```

outputLength

(xs:double) Specifies the value of the HMACOutputLength element in the SignatureMethod element.

- Must be no less than 80
- Must be at least half the number of bits the hash outputs
- Cannot be greater than the number of bits the hash outputs.

Zero uses the entire HMAC output. The HMACOutputLength element is only output if *outputLength* is nonzero.

signedInfoSubtree

(node set) Identifies the elements to be signed.

sharedSecretKey

(xs:string) Identifies the HMAC shared secret key. Use one of the following prefixes to refer to a shared secret key:

- name:*key*, such as name:alice, that refers to an already configured shared secret key object named alice.

- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key:` prefix, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

includeComments

(`xs:boolean`) Specifies the treatment of XML comments.

- `true()` specifies that comments are included.
- `false()` specifies that comments are excluded.

canonicalizationAlgorithm

(`xs:string`) Optionally specifies the method used to canonicalize the node set to be signed.

canonicalizationAlgorithm must take one of the following string values:

`http://www.w3.org/TR/2001/REC-xml-c14n-20010315`

(Default) Identifies the c14n algorithm (comments are excluded in the canonicalized output)

`http://www.w3.org/TR/2001/REC-xml-c14n-20010315#WithComments`

Identifies the c14n algorithm (comments are included in the canonicalized output)

`http://www.w3.org/2001/10/xml-exc-c14n#`

Identifies the c14n exclusive canonicalization algorithm (comments are excluded in the canonicalized output)

`http://www.w3.org/2001/10/xml-exc-c14n#WithComments`

Identifies the c14n exclusive canonicalization algorithm (comments are included in the canonicalized output)

prefixes

(`xs:string`) Identifies a space-delimited list of the inclusive namespace prefixes. That is the namespace declarations that are emitted by either of the two exclusive canonicalization algorithms.

prefixes is meaningful only when an exclusive canonicalization method is used.

By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

prefixes overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string specifies an empty set of prefixes.

Guidelines

The shared secret key used to generate the HMAC signature must be in the Firewall Credentials List assigned to the XML Firewall.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mumblens"/>
```

Where the `x` attribute is interpreted as a QName, and the `mumble` prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the `mumble` prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix `mumble` in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for `mumble` to be emitted.

sign-hmac() and **sign-hmac-set()** differ in that **sign-hmac-set()** converts data into its canonical form only those elements and attributes explicitly passed via the *signedInfoSubtree* argument. In contrast, **sign-hmac()** performs a deep hash that includes all child elements of the *signedInfoSubtree* argument.

All arguments are passed as XPath expressions.

Results

An `xs:string` that contains a HMAC digital signature.

Examples

```
:
:
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#"
  <xsl:copy-of select="$signedinfo-subtree"/>
  <SignatureValue>
    <xsl:value-of select="dp:sign-hmac($sigmech, $outputlen,
      $signedinfo-subtree/*,$keyid, false(), $excAlgo, ' ')" />
  </SignatureValue>
  <KeyInfo>
    <KeyName>
      <xsl:value-of select="$keyid"/>
    </KeyName>
  </KeyInfo>
</Signature>
:
```

sign-hmac-set()

Generates a HMAC signature.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:sign-hmac-set(*signMechanism*, *outputLength*, *signedInfoSubtree*, *sharedSecretKey*, *includeComments*, *canonicalizationAlgorithm*, *prefixes*)

Parameters

signMechanism

(xs:string) Identifies the algorithm to generate the HMAC signature. This value must reference one of the following:

<http://www.w3.org/2000/09/xmlsig#hmac-sha1>
<http://www.w3.org/2001/04/xmlsig-more#hmac-sha256>
<http://www.w3.org/2001/04/xmlsig-more#hmac-sha512>
<http://www.w3.org/2001/04/xmlsig-more#hmac-sha224>
<http://www.w3.org/2001/04/xmlsig-more#hmac-sha384>
<http://www.w3.org/2001/04/xmlsig-more#hmac-ripemd160>
<http://www.w3.org/2001/04/xmlsig-more#hmac-md5>

outputLength

(xs:double) Specifies the value of the HMACOutputLength element in the SignatureMethod element.

- Must be no less than 80
- Must be at least half the number of bits the hash outputs
- Cannot be greater than the number of bits the hash outputs.

A value of zero uses the entire HMAC output. The HMACOutputLength element is in the output only for nonzero values.

signedInfoSubtree

(node set) Identifies the elements to be signed.

sharedSecretKey

(xs:string) Identifies the HMAC shared secret key. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.
- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key:` prefix, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

includeComments

(xs:boolean) Specifies the treatment of XML comments.

- `true()` specifies that comments are included.
- `false()` specifies that comments are excluded.

canonicalizationAlgorithm

(xs:string) Optionally specifies the method used to canonicalize the node set to be signed. Use one of the following string values:

<http://www.w3.org/TR/2001/REC-xml-c14n-20010315>

(Default) Identifies the c14n algorithm (comments are excluded in the canonicalized output)

<http://www.w3.org/TR/2001/REC-xml-c14n-20010315#WithComments>

Identifies the c14n algorithm (comments are included in the canonicalized output)

<http://www.w3.org/2001/10/xml-exc-c14n#>

Identifies the c14n exclusive canonicalization algorithm (comments are excluded in the canonicalized output)

<http://www.w3.org/2001/10/xml-exc-c14n#WithComments>

Identifies the c14n exclusive canonicalization algorithm (comments are included in the canonicalized output)

prefixes

(xs:string) Optionally identifies a space-delimited list of the inclusive namespace prefixes. That is the namespace declarations that are emitted by either of the two exclusive canonicalization algorithms.

This parameter is meaningful only when an exclusive canonicalization method is used.

By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

This parameter overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string specifies an empty set of prefixes.

Guidelines

The shared secret key used to generate the HMAC signature must be in the Firewall Credentials List assigned to the XML Firewall.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mumlens"/>
```

Where the *x* attribute is interpreted as a QName, and the *mumble* prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the *mumble* prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix *mumble* in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for *mumble* to be emitted.

sign-hmac() and **sign-hmac-set()** differ in that **sign-hmac-set()** converts data into its canonical form only those elements and attributes explicitly passed via the *signedInfoSubtree* argument. In contrast, **sign-hmac()** performs a deep hash that includes all child elements of the *signedInfoSubtree* argument.

All arguments are passed as XPath expressions.

Results

An xs:string that contains a HMAC digital signature.

Examples

```
⋮
<Signature xmlns="http://www.w3.org/2000/09/xmldsig#">
  <xsl:copy-of select="$signedinfo-subtree"/>
  <SignatureValue>
    <xsl:value-of select="dp:sign-hmac($sigmech, $outputlen,
      $signedinfo-subtree/*,
      $keyid, false(), $excAlgo, '')" />
  </SignatureValue>
  <KeyInfo>
    <KeyName>
      <xsl:value-of select="$keyid"/>
    </KeyName>
  </KeyInfo>
</Signature>
⋮
```

substring-base64()

Decodes the input, extracts a specified portion of the base string, and Base64-encodes the extracted substring.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:substring-base64(baseString, stringOffset, stringLength)`

Parameters

baseString

(`xs:string`) the string to be extracted from

stringOffset

(`xs:integer`) Specifies the initial byte to be extracted. A value of 0 specifies the first byte of the *baseString*.

stringLength

(`xs:integer`) Specifies the length, in bytes, of the extracted string.

Guidelines

All arguments are passed as XPath expressions.

Results

an `xs:string` with a Base64-encoded string

unwrap-key()

Decrypts a wrapped key using a specified shared secret key and key wrapping algorithm.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:unwrap-key(encryptedKey, sharedSecretKey, keyWrapAlgorithm)`

Parameters

encryptedKey

(`xs:string`) the wrapped key to be decrypted.

sharedSecretKey

(`xs:string`) Specifies the shared secret key used to decrypt the session key. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.
- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key:` prefix, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

keyWrapAlgorithm

(`xs:string`) the key wrapping algorithm used to decrypt the enciphered session key.

Use one of the following supported algorithms:

- `http://www.w3.org/2001/04/xmlenc#kw-tripledes`
- `http://www.w3.org/2001/04/xmlenc#kw-aes128`
- `http://www.w3.org/2001/04/xmlenc#kw-aes192`
- `http://www.w3.org/2001/04/xmlenc#kw-aes256`

Guidelines

RFC 3217, *Triple-DES and RC2 Key Wrapping*, defines the key wrapping algorithm.

This function passes all arguments as XPath expressions.

Examples

```
⋮
<xsl:value-of select="dp:unwrap-key($encrypted-key,$sharedsecret,$keytransport)"/>
⋮
```

validate-certificate()

Validates a target certificate.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:validate-certificate(certNodes, valCred)`

Parameters

certNodes

(node set) Identifies the target certificate to be validated in the <subject> element. The function can pass untrusted CA certificates through one or more <ca> elements or through pkipath: and pkcs7: prefixes in the <subject> element. The validate-certificate function treats any certificates in the pkipath: and pkcs7: tokens, other than the target certificate, as untrusted CA certificates. The function uses untrusted certificates to construct a chain between the target certificate and one of the root CA certificates in the Validation Credentials only when the Validation Credentials object specifies PKIX validation. The following input is an example that shows how to specify a node set:

- A node set of size one that contains one <input> element with one <subject> subelement and zero or more <ca> subelements.

```
<input>
  <subject>certstring1</subject>
  <ca>certstring2</ca>
  ...
</input>
```

You can identify the certstring1 value in any of the following ways:

- *name:cert*

name: Indicates the required literal prefix for a certificate that is identified by object name.

cert Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.

- *cert:base64Cert*

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert

Specifies that the target certificate is Base64 encoded.

- *ski:certSKI*

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI

Specifies that the target certificate is the Base64 encoding of the SKI.

- *issuerserial:serial*

issuerserial:

Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.

- `thumbprintshal:sha1string`

`thumbprintshal:`

Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

`sha1string`

Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.

- `pkcs7:base64Cert`

`pkcs7:` Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

`base64Cert`

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string as the target certificate and treats any remaining certificates as untrusted CA certificates.

- `pkipath:base64cert`

`pkipath:`

Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

`base64cert`

Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string as the target certificate and treats any remaining certificates as untrusted CA certificates. For example, if the PKIPath token contains two X.509 certificates called vsign (the Certificate Authority) and alice (the subject), specify the certificate string as follows:

```
<input>
  <subject>name:alice</subject>
  <ca>name:vsign</ca>
</input>
```

`valCred`

(`xs:string`) Identifies the Validation Credentials used to validate the target certificate.

Guidelines

The extension function validates a target certificate using the parameters specified in the Validation Credentials.

This function passes all arguments as XPath expressions.

Results

returns an empty node set if certificate validation succeeds. Otherwise, returns a node set of size one containing an `<error>` element with the appropriate error message text. Because future firmware releases may return non-empty node sets on success, the most reliable indicator of a successful validation is the absence of an `<error>` element.

Examples

```
⋮
  <xsl:variable name="input">
    <input>
      <subject>name:Alice</subject>
    </input>
  </xsl:variable>
  <output>
    <xsl:copy-of select="dp:validate-certificate($input,'AliceValCred')"/>
  </output>
⋮
```

verify()

Verifies a digital signature.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:verify(signAlgorithm, signedInfoHash, signValue, cert)`

Parameters

signAlgorithm

(xs:string) Identifies the signature algorithm and must take one of the following values:

```
http://www.w3.org/2000/09/xmldsig#dsa-sha1
http://www.w3.org/2000/09/xmldsig#rsa-sha1
http://www.w3.org/2001/04/xmldsig-more#rsa-sha256
http://www.w3.org/2001/04/xmldsig-more#rsa-sha512
http://www.w3.org/2001/04/xmldsig-more#rsa-sha384
http://www.w3.org/2001/04/xmldsig-more/rsa-ripemd160
http://www.w3.org/2001/04/xmldsig-more#rsa-md5
```

(xs:string) the locally-calculated hash of the <SignedInfo> element of the XML signature.

signValue

(xs:string) Derived from the contents of the <Signature Value> element of the XML signature, contains the digital signature to be verified.

cert

(xs:string) Identifies the X.509 certificate that contains the public key of the XML signatory. The target certificate can be identified in any of the following ways:

- `name:cert`

`name:` Indicates the required literal prefix for a certificate that is identified by object name.

`cert` Specifies the name of an X.509 Crypto Certificate object that was previously created with the WebGUI or with the **certificate** command.

- *cert:base64Cert*

cert: Indicates the required literal prefix for a Base64 encoded certificate.

base64Cert
Specifies that the target certificate is Base64 encoded.
- *ski:certSKI*

ski: Indicates the required literal prefix for a certificate that is identified by Subject Key Identifier (SKI).

certSKI
Specifies that the target certificate is the Base64 encoding of the SKI.
- *issuerserial:serial*

issuerserial:
Indicates the required literal prefix for a certificate that is identified by issuer serial number and Distinguished Name (DN).

serial Specifies the issuer serial number as a decimal integer and the issuer DN; for example, 0,CN=Harold, O=Acme, L=Someplace, ST=MA, C=US. The function use this value to search the management store for a matching certificate.
- *thumbprintsha1:sha1string*

thumbprintsha1:
Indicates the required literal prefix for a certificate with a Base64 encoded SHA-1 hash.

sha1string
Specifies a Base64 encoded SHA-1 hash of a certificate. The function use this value to search the management store for the SHA-1 hash of a matching certificate.
- *pkcs7:base64Cert*

pkcs7: Indicates the required literal prefix for a certificate that is identified as the first certificate in an unordered collection of certificates.

base64Cert
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the first certificate it finds in the string.
- *pkipath:base64cert*

pkipath:
Indicates the required literal prefix for a certificate that is identified as the last certificate in an ordered collection of certificates.

base64cert
Specifies a string of Base64 encoded ASN.1 objects with multiple certificates. The function uses the last certificate it finds in the string.

Guidelines

Verifies a digital signature as specified in W3C Recommendation 12 February 2002, IETF RFC 3275 *XML - Signature Syntax and Processing*.

All arguments are passed as XPath expressions.

Results

an empty `xs:string` if signature verification succeeds; otherwise, returns an error string.

Examples

```
:
<xsl:variable name="verify-result"
  select='dp:verify($sigmech,$signedinfo-hash,$sigvalue,$certid)'/>
:
```

verify-hmac()

Verifies a HMAC signature.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:verify-hmac(*signAlgorithm*, *outputLength*, *verifiedRoot*, *digestValue*, *sharedSecretKey*, *includeComments*, *canonicalizationAlgorithm*, *prefixes*)

Parameters

signAlgorithm

(`xs:string`) Identifies the HMAC signature algorithm and must take one of the following values:

```
http://www.w3.org/2000/09/xmlsig#hmac-sha1
http://www.w3.org/2001/04/xmlsig-more#hmac-sha256
http://www.w3.org/2001/04/xmlsig-more#hmac-sha512
http://www.w3.org/2001/04/xmlsig-more#hmac-sha224
http://www.w3.org/2001/04/xmlsig-more#hmac-sha384
http://www.w3.org/2001/04/xmlsig-more#hmac-ripemd160
http://www.w3.org/2001/04/xmlsig-more#hmac-md5
```

outputLength

(`xs:double`) Specifies the length of the HMAC hash.

verifiedRoot

(node set) Identifies the topmost element of the subtree whose signature is to be verified

digestValue

(`xs:string`) Identifies the received HMAC signature.

sharedSecretKey

(`xs:string`) Identifies the HMAC shared secret. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.
- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key: prefix`, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

includeComments

(`xs:boolean`) Specifies the treatment of XML comments.

- `true()` specifies that comments are included.
- `false()` specifies that comments are excluded.

Specifies whether the canonicalizer should limit itself to emitting exactly those nodes in the node set passed as the third parameter. Usually, this value is `false`, meaning that the canonicalizer should recursively emit all children of the node.

This parameter's value must be `true()` when verifying an enveloped signature. Because the signature is contained within the signed data, the signature itself must be excluded from the verification process. Consequently you must carefully define the node set passed as the third parameter to ensure that it selects only the signed data, and that you pass `true()` as the last parameter.

canonicalizationAlgorithm

(`xs:string`) Optionally identifies the method used to canonicalize the node set to be verified.

canonicalizationAlgorithm must take one of the following values:

`http://www.w3.org/TR/2001/REC-xml-c14n-20010315`
(Default) Identifies the c14n algorithm

`http://www.w3.org/2001/10/xml-exc-c14n#`
Identifies the c14n exclusive canonicalization algorithm

prefixes

(`xs:string`) Optionally identifies a space-delimited list of the inclusive namespace prefixes. That is the namespace declarations that are emitted by the exclusive canonicalization algorithm.

prefixes is meaningful only when the exclusive canonicalization method is used.

By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

prefixes overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string (Default) specifies an empty set of prefixes.

Guidelines

The shared secret key used for verification must be in the Firewall Credentials List assigned to the XML Firewall.

The boolean value is `true()` when verifying an enveloped signature. Because the signature is contained within the signed data, the signature itself must be excluded from the verification process. Consequently, carefully define the node set passed as the third argument to ensure that it picks up only the signed data.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mumlens"/>
```

Where the `x` attribute is interpreted as a `QName`, and the `mumble` prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the `mumble` prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix `mumble` in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for `mumble` to be emitted.

`verify-hmac()` and **`verify-hmac-set()`** differ in that **`verify-hmac-set()`** converts data into its canonical form only those elements and attributes explicitly passed via the *verifiedRoot* argument. In contrast, **`verify-hmac()`** performs a deep hash that includes all child elements of the *verifiedRoot* argument.

All arguments are passed as XPath expressions.

Results

An empty `xs:string` if signature verification succeeds; otherwise, returns an error string.

Examples

```
⋮
<xsl:variable name="verify-result" select="dp:verify-hmac($sigmech,
$outputlen, ./dsig:SignedInfo, $sigvalue, $keyid, false())" />
⋮
```

`verify-hmac-set()`

Verifies a HMAC signature.

Availability

All products except XA35

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

dp:verify-hmac-set(*signAlgorithm*, *outputLength*, *verifiedRoot*, *digestValue*, *sharedSecret*, *includeComments*, *boolean*, *canonicalizationAlgorithm*, *prefixes*)

Parameters

signAlgorithm

(xs:string) Identifies the HMAC signature algorithm and must take one of the following values:

http://www.w3.org/2000/09/xmlsig#hmac-sha1
http://www.w3.org/2001/04/xmlsig-more#hmac-sha256
http://www.w3.org/2001/04/xmlsig-more#hmac-sha512
http://www.w3.org/2001/04/xmlsig-more#hmac-sha224
http://www.w3.org/2001/04/xmlsig-more#hmac-sha384
http://www.w3.org/2001/04/xmlsig-more#hmac-ripemd160
http://www.w3.org/2001/04/xmlsig-more#hmac-md5

outputLength

(xs:double) Specifies the length of the HMAC hash.

verifiedRoot

(node set) Identifies the topmost element of the subtree whose signature is to be verified.

digestValue

(xs:string) Identifies the received HMAC signature.

sharedSecret

(xs:string) Identifies the HMAC shared secret. Use one of the following prefixes to refer to a shared secret key:

- **name:key**, such as **name:alice**, that refers to an already configured shared secret key object named **alice**.
- **key:Base64** refers to a Base64-encoded literal that is the shared secret key. If you enter *Base64* without the **key:** prefix, the function uses *Base64* as the key.
- **hex:hexadecimal** refers to a Hexadecimal-encoded literal that is the shared secret key.

includeComments

(xs:boolean) Specifies the treatment of XML comments.

- **true()** specifies that comments are included.
- **false()** specifies that comments are excluded.

boolean

(boolean) Specifies whether the canonicalizer should limit itself to emitting exactly those nodes in the node set passed as the third parameter. Usually, this value is **false**, meaning that the canonicalizer should recursively emit all children of the node.

This value must be **true** to verify an enveloped signature. Because the signature is within the signed data, the signature itself must be excluded from the verification process. Consequently, carefully define the node set to pass as the third parameter to ensure that it selects only the signed data, and that you pass **true()** as the last parameter.

canonicalizationAlgorithm

(xs:string) Optionally identifies the method used to canonicalize the node set to be verified. Use one of the following values:

http://www.w3.org/TR/2001/REC-xml-c14n-20010315
(Default) Identifies the c14n algorithm

<http://www.w3.org/2001/10/xml-exc-c14n#>

Identifies the c14n exclusive canonicalization algorithm

prefixes

(xs:string) Optionally identifies a space-delimited list of the inclusive namespace prefixes. That is, the namespace declarations that are emitted by the exclusive canonicalization algorithm.

This parameter is meaningful only when the exclusive canonicalization method is used. By default, the exclusive canonicalization algorithm emits a namespace prefix declaration only if the prefix is used in an element in the node set being canonicalized. The exclusive algorithms will not declare a namespace prefix until it is actually required.

This parameter overrides this default behavior and specifies a set of namespace prefixes to be included in the namespace prefix declarations.

An empty string (Default) specifies an empty set of prefixes.

Guidelines

The shared secret key for verification must be in the Firewall Credentials List that is assigned to the XML Firewall.

The boolean value is true when verifying an enveloped signature. Because the signature is within the signed data, the signature itself must be excluded from the verification process. Consequently, carefully define the node set to pass as the third argument to ensure that it picks up the signed data only.

Usually, exclusive canonicalization emits a declaration for a namespace prefix only if it is required to parse the current element. However, sometimes the requirement for prefix definition is not intuitively obvious.

For example:

```
<foo:bar x="mumble:whatever"
  xmlns:foo="urn:foons"
  xmlns:mumble="urn:mumlens"/>
```

Where the *x* attribute is interpreted as a QName, and the *mumble* prefix declaration must be included.

While parsing this element, an exclusive canonicalization algorithm omits the *mumble* prefix declaration. While the element semantics are lost, the markup is valid.

In this instance, specify the prefix *mumble* in the inclusive namespace prefix list to override the exclusive canonicalization algorithm and force the declaration for *mumble* to be emitted.

verify-hmac() and **verify-hmac-set()** differ in that **verify-hmac-set()** converts data into its canonical form only those elements and attributes explicitly passed via the *verifiedRoot* argument. In contrast, **verify-hmac()** performs a deep hash that includes all child elements of the *verifiedRoot* argument.

All arguments are passed as XPath expressions.

Results

An empty `xs:string` if signature verification succeeds; otherwise, returns an error string.

Examples

```
⋮
<xsl:variable name="verify-result" select="dp:verify-hmac($sigmech,
$outputlen, ./dsig:SignedInfo, $sigvalue, $keyid, false())" />
⋮
```

wrap-key()

Encrypts (wraps) the input key using a specified shared secret key and key wrapping algorithm.

Availability

All products except XA35

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

dp:wrap-key(*inputKey*, *sharedSecretKey*, *keyWrapAlgorithm*)

Parameters

inputKey

(`xs:string`) Specifies the input key to be encrypted.

sharedSecretKey

(`xs:string`) Identifies the shared secret key used to encrypt the input key. Use one of the following prefixes to refer to a shared secret key:

- `name:key`, such as `name:alice`, that refers to an already configured shared secret key object named `alice`.
- `key:Base64` refers to a Base64-encoded literal that is the shared secret key. If you enter `Base64` without the `key:` prefix, the function uses `Base64` as the key.
- `hex:hexadecimal` refers to a Hexadecimal-encoded literal that is the shared secret key.

keyWrapAlgorithm

(`xs:string`) Identifies the key wrapping algorithm used to encrypt the input key.

Use one of the following supported algorithms:

- `http://www.w3.org/2001/04/xmlenc#kw-tripledes`
- `http://www.w3.org/2001/04/xmlenc#kw-aes128`
- `http://www.w3.org/2001/04/xmlenc#kw-aes192`
- `http://www.w3.org/2001/04/xmlenc#kw-aes256`

Guidelines

RFC 3217, *Triple-DES and RC2 Key Wrapping*, defines the key wrapping algorithm.

This function passes all arguments as XPath expressions.

Results

An `xs:string` that contains the wrapped key.

Examples

```
⋮
<xsl:when test="substring-after($keytransport,'#')='kw-tripledes'">
  <xsl:value-of select="dp:wrap-key($inputKey,$sharedsecret,$keytransport)"/>
</xsl:when>
⋮
```

zosnss-authen()

Makes an authentication request to an NSS server.

Availability

All products except XA35, XB60

Namespace declaration

`xmlns:dp="http://www.datapower.com/extensions"`

Syntax

`dp:zosnss-authen(user, password, client)`

Parameters

user (xs:string) Specifies the name used to authenticate to the NSS server.

password
(xs:string) Specifies the password used to authenticate to the NSS server.

client (xs:string) Identifies the name of an existing z/OS NSS Client object.

Guidelines

The specified *user* and *password* parameters are used with the function run time request and are independent of the User name and Password in the z/OS NSS Client object. The *client* object provides the necessary information to access a remote NSS server.

Results

On success, the function returns the user name as an `xs:string`. If not successful, the function returns an empty string.

Examples

This custom style sheet authenticates user USER1 with password pword1 on the NSS server specified in the zosnss1 z/OS NSS Client object.

```
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
```

```

xmlns:dpconfig="http://www.datapower.com/param/config"
extension-element-prefixes="dp"
exclude-result-prefixes="dp dpconfig">

<xsl:template match="/">
  <xsl:variable name="auth"
    select="dp:zosnss-authen('USER1','pword1','zosnss1')" />
  <authen>
    zosnss authen return:[
      <xsl:value-of select="$auth" />
    ]
  </authen>
</xsl:template>

</xsl:stylesheet>

```

zosnss-author()

Makes an authorization request to an NSS server.

Availability

All products except XA35, XB60

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:zosnss-author(user, operation, resource, client)
```

Parameters

user (xs:string) Specifies the name used to authenticate to the NSS server.

operation

(xs:string) Specifies the operation access to the resource.

resource

(xs:string) Specifies the resource as defined on the z/OS NSS server.

client

(xs:string) Identifies the name of an existing z/OS NSS Client object. The object provides the necessary information to access a remote NSS server.

Guidelines

The *operation* specifies the access level to the resource. Valid values include the following operations:

a (Alter)

r (Read)

c (Control)

u (Update)

The *resource* specifies a resource defined for the user in RACF. The NSS XMLAppliance SAF Access service allows an NSS XMLAppliance to check a user authorization to any profile in the RACF SERVAUTH class. SERVAUTH profile names are limited to 64 bytes.

Results

On success, the function returns ok. If not successful, the function returns an empty string.

Examples

This custom style sheet authorizes user USER1 for the read operation (r) for resource book1 on the NSS server specified in the zosnss1 z/OS NSS Client object.

```
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:dpconfig="http://www.datapower.com/param/config"
  extension-element-prefixes="dp"
  exclude-result-prefixes="dp dpconfig">

  <xsl:template match="/">
    <xsl:variable name="author"
      select="dp:zosnss-author('USER1','r','book1','zosnss1')" />
    <author>
      zosnss author return:[
        <xsl:value-of select="$author" />
      ]
    </author>
  </xsl:template>

</xsl:stylesheet>
```

zosnss-passticket-authen()

Makes an authentication request to an NSS server using a PassTicket.

Availability

All products except XA35, XB60

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
```

Syntax

```
dp:zosnss-passticket-authen(user, passticket, application-ID, client)
```

Parameters

user (xs:string) Specifies the name used to authenticate to the NSS server.

passticket
(xs:string) Specifies a PassTicket.

application-ID
(xs:string) Specifies the application ID as defined on the NSS server.

client (xs:string) Identifies the name of an existing z/OS NSS Client object. The object provides the necessary information to access a remote NSS server.

Guidelines

As an alternative to using a password, the **zosnss-passticket-authen** function makes an authentication request to the NSS server using a PassTicket. This allows the user to authenticate without sending a password.

Before using the **zosnss-passticket-authen** function, the PassTicket must be generated with the **generate-passticket** function using the same application ID. A PassTicket is generated using the current time on the system and can be used only

within ten minutes of generation. To avoid a PassTicket authentication failure, ensure that the time on the DataPower appliance and the z/OS NSS system are synchronized.

Results

On success, the function returns the user name as an `xs:string`. If not successful, the function returns an empty string.

Examples

This custom style sheet generates a PassTicket using the `generate-passticket` function and authenticates the user `USER1` using the PassTicket on the NSS server specified in the z/OS NSS Client object `zos1`.

```
<xsl:stylesheet version="1.0"
  xmlns:xsl="http://www.w3.org/1999/XSL/Transform"
  xmlns:dp="http://www.datapower.com/extensions"
  xmlns:dpconfig="http://www.datapower.com/param/config"
  extension-element-prefixes="dp"
  exclude-result-prefixes="dp dpconfig">

  <xsl:template match="/">
    <xsl:variable name="passticket"
      select="dp:generate-passticket('USER1', 'APP1',
        'E001193519561977')" />
    <xsl:variable name="auth"
      select="dp:zosnss-passticket-authen('USER1',
        $passticket, 'APP1', 'zos1')" />
    <passticketauthen>
      zosnss passticketauthen return:[
        <xsl:value-of select="$auth" />
      ]
    </passticketauthen>
  </xsl:template>

</xsl:stylesheet>
```

Chapter 4. XSLT and XPath extensions

This chapter provides documentation about the DataPower-specific changes to the supported XSLT and XPath extensions. These changes are as follows:

- Added the `dp:ignore-multiple` attribute to the `<xsl:import>` element and to the `<xsl:include>` element.
- Added the `dp:escaping` attribute and the `dp:expand-empty-elements` attribute to the `<xsl:output>` element.
- Added the `dp:type` attribute and the `dp:priority` attribute to the `<xsl:message>` element.

To use these changes in a style sheet, include the following namespace declaration:

```
xmlns:dp="http://www.datapower.com/extensions"
```

The DataPower compiler supports all extensions from the XSLT 1.0 and XPath 1.0 specifications. The support for XSLT 2.0 and XPath 2.0 is currently limited to the decimal data type. Specifically, numeric literals in the style sheet are interpreted as decimals (instead of double-precision floating point numbers as in 1.0), and the `xs:decimal` constructor function is supported for converting other data types to decimal.

For complete details the use of XSLT 1.0 and XPath 1.0 extensions, refer to the following Web sites:

XSLT 1.0

<http://www.w3.org/TR/xslt>

XPath 1.0

<http://www.w3.org/TR/xpath>

Note: The key difference is that XSLT specifies that the only possible operations on a result tree fragment are to copy it to output or to copy it to another result tree fragment. EXSLT, however, provides an extension to convert a result tree fragment to a node set. From XSLT, the DataPower compiler allows result tree fragments to be used as node sets:

```
<xsl:variable name="rtf">
  <a/><a/><a/>
</xsl:variable>
<xsl:value-of select="count($rtf)" />
<!-- the root node -->
<xsl:value-of select="count($rtf/a)" />
<!-- 3 children of the root node -->
```

xsl:import

Imports the contents of one style sheet into another.

Syntax

```
<xsl:import
  href="URI" />
  dp:ignore-multiple="yes|no"/>
```

Parameters

`dp:ignore-multiple="yes|no"`

Indicates whether to include only the first specified URL. If present and any value except no, only the first import for a given URL is processed.

xsl:include

Includes the contents of one style sheet into another.

Syntax

```
<xsl:include
  href="URI"
  dp:ignore-multiple="yes|no"/>
```

Parameters

`dp:ignore-multiple="yes|no"`

Indicates whether to include only the first specified URL. If present and any value except no, only the first include for a given URL is processed.

xsl:message

Writes a message to the log.

Syntax

```
<xsl:message
  terminate="yes|no"
  dp:type="category"
  dp:priority="alert|critic|error|warn|notice|info|debug"
  <!-- Content: Message text -->
</xsl:message>
```

Parameters

`dp:type="category"`

Specifies the category to assign to the message. Refer to `dmLogClass` in the `store:///xml-mgmt.xsd` schema.

`dp:priority="alert|critic|error|warn|notice|info|debug"`

Specifies the level to assign to the message.

xsl:output

Defines the format of the output document.

Syntax

```
<xsl:output
  method="xml|html|text|name"
  version="string"
  encoding="string"
  omit-xml-declaration="yes|no"
  standalone="yes|no"
  doctype-public="string"
  doctype-system="string"
  cdata-section-elements="namelist"
  indent="yes|no"
```

```
media-type="string"  
dp:escaping="minimum|maximum"  
dp:expand-empty-elements="qname-list"/>
```

Parameters

`dp:escaping="minimum|maximum"`

Overrides the optional minimum output escaping rule defined by the Compile Options Policy. A minimum output escaping rule is often used when processing non-English character sets.

`maximum`

Outputs XML numeric character entities for non-ASCII characters whenever possible.

`minimum`

Outputs native character-representation whenever possible.

`dp:expand-empty-elements="element-list"`

Specifies a list of whitespace-delimited elements that should not be converted to their collapsed form during processing. When the compiler serializes these named elements, the expanded form will be used.

This attribute is useful for controlling the structure of generated HTML and XHTML documents. Many browsers can encounter rendering problems while attempting to display these Web pages. In many cases, empty elements cause Web pages to be incorrectly rendered or to be incompletely rendered.

For example to retain the expanded form of the anchor and script elements, this attribute would have the following coding:

```
dp:expand-empty-elements="a script"
```

Then if the input document contains ``, serialization would not collapse the anchor element to `` but would retain the original, expanded structure. Alternatively if the input document contains ``, serialization would expand the anchor element to ``.

Chapter 5. EXSLT extensions

The chapter lists supported EXSLT extension elements and extension functions. These extensions support the EXSLT community effort to provide a standardized set of common extensions to enhance style sheet portability.

EXSLT provides the following modules that contain extension elements and extension functions:

- Common module, refer to “Common module.”
- Dates and Time module, refer to “Dates and Times module” on page 180.
- Dynamic module, refer to “Dynamic module” on page 184.
- Functions module, refer to “Functions module” on page 184.
- Math module, refer to “Math module” on page 185.
- Random module, refer to “Random module” on page 186.
- Regular Expressions module, refer to “Regular Expressions module” on page 186.
- Sets module, refer to “Sets module” on page 187.
- Strings module, refer to “Strings module” on page 188.

Refer to the tables in these sections to determine whether DataPower appliances supports a specific extension element or extension function

Although these modules define EXSLT elements and functions, DataPower appliances do not support all of these elements and functions. This document provides only the following information about elements and extension functions that you can use in DataPower custom style sheets:

- Abstract statement
- Syntax statement

For complete information about EXSLT elements and functions, refer to the following Web site or your favorite EXSLT reference:

<http://www.exslt.org/>

Common module

The Common module includes the elements and functions that are listed in Table 5.

Table 5. Supported elements and functions for the EXSLT Common module

Name	Element or function	Supported
exslt:document	Element	No
exslt:node-set()	Function	Yes
exslt:object-type()	Function	Yes

The supported extension functions require the following namespace declaration:

```
xmlns:exsl="http://exslt.org/common"
```

node-set()

Returns a node set that identifies the type of the object that is passed as the argument.

Syntax

exslt:node-set(*object*)

object-type()

Returns a string that identifies the type of the object that is passed as the argument.

Syntax

common:object-type(*object*)

Dates and Times module

The Dates and Times module includes the elements and functions that are listed in Table 6.

Table 6. Supported elements and functions for the EXSLT Dates and Times module

Name	Element or function	Supported
date:add()	Function	Yes
date:add-duration()	Function	Yes
date:date()	Function	Yes
date:date-format	Element	No
date:date-time()	Function	Yes
date:day-abbreviation()	Function	Yes
date:day-in-month()	Function	Yes
date:day-in-week()	Function	Yes
date:day-in-year()	Function	Yes
date:day-name()	Function	Yes
date:day-of-week-in-month()	Function	Yes
date:difference()	Function	Yes
date:duration()	Function	Yes
date:format-date()	Function	No
date:hour-in-day()	Function	Yes
date:leap-year()	Function	Yes
date:minute-in-hour()	Function	Yes
date:month-abbreviation()	Function	Yes
date:month-in-year()	Function	Yes
date:month-name()	Function	Yes
date:parse-date()	Function	No
date:second-in-minute()	Function	Yes
date:seconds()	Function	Yes
date:sum()	Function	No
date:time()	Function	Yes

Table 6. Supported elements and functions for the EXSLT Dates and Times module (continued)

Name	Element or function	Supported
date:week-in-month()	Function	Yes
date:week-in-year()	Function	Yes
date:year()	Function	Yes

The supported extension functions require the following namespace declaration:

```
xmlns:date="http://exslt.org/dates-and-times"
```

add()

Returns the date/time from adding a duration to a date/time.

Syntax

date:add(*dateTime*, *duration*)

add-duration()

returns the duration from adding two durations.

Syntax

date:add-duration(*duration1*, *duration-2*)

date()

Returns the date from the input date/time string.

Syntax

date:date(*dateTime*)

date-time()

Returns the current date and time as a date/time string.

Syntax

date:date-time()

day-abbreviation()

Returns the abbreviation of the day of the week from the input string.

Syntax

date:day-abbreviation(*dateTime*)

day-in-month()

Returns the day of the month from the input string.

Syntax

date:day-in-month(*dateTime*)

day-in-week()

Returns the day of the week from the input string.

Syntax

`date:day-in-week(dateTime)`

day-in-year()

Returns the day of the year from the input string.

Syntax

`date:day-in-year(dateTime)`

day-name()

Returns the full name of the day of the week from the input string.

Syntax

`date:day-name(dateTime)`

day-of-week-in-month()

Returns the day-of-the-week in a month as a number.

Syntax

`date:day-of-week-in-month(dateTime)`

difference()

Returns the duration between the first date and the second date.

Syntax

`date:difference(start-dateTime, end-dateTime)`

duration()

Converts an input number of seconds to a duration string.

Syntax

`date:duration(duration)`

hour-in-day()

Returns the hour of the day from the input string.

Syntax

`date:hour-in-day(dateTime)`

leap-year()

Tests an input year to determine if it is a leap year.

Syntax

`date:leap-year(dateTime)`

minute-in-hour()

Returns the minute of the hour from the input string.

Syntax

`date:minute-in-hour(dateTime)`

month-abbreviation()

Returns the abbreviation of the month of the year from the input string.

Syntax

date:month-abbreviation(*dateTime*)

month-in-year()

Returns the month of the year from the input string.

Syntax

date:month-in-year(*dateTime*)

month-name()

Returns the name of the month of the year from the input string.

Syntax

date:month-name(*dateTime*)

second-in-minute()

Returns the second of the minute from the input string.

Syntax

date:second-in-minute(*dateTime*)

seconds()

Converts an optional input string to seconds.

Syntax

date:seconds(*dateTime* | *duration*)

sum()

Adds a set of durations.

Syntax

sum(*nodeset*)

time()

Returns the time-of-day from the input string.

Syntax

date:time(*dateTime*)

week-in-month()

Returns the week of the month from the input string.

Syntax

date:week-in-month(*dateTime*)

week-in-year()

Returns the week of the year from the input string.

Syntax

date:week-in-year(*dateTime*)

year()

Extracts the year from the input string.

Syntax

date:year(*dateTime*)

Dynamic module

The Dynamic module includes the functions that are listed in Table 7.

Table 7. Supported functions for the EXSLT Dynamic module

Name	Element or function	Supported
dyn:closure()	Function	No
dyn:evaluate()	Function	Yes
dyn:map()	Function	No
dyn:max()	Function	No
dyn:min()	Function	No
dyn:sum()	Function	No

The supported extension functions require the following namespace declaration:

```
xmlns:dyn="http://exslt.org/dynamic"
```

evaluate()

Returns an object that identifies the evaluation of the input string.

Syntax

dyn:evaluate(*string*)

Functions module

The Functions module includes the elements that are listed in Table 8.

Table 8. Supported elements for the EXSLT Functions module

Name	Element or function	Supported
func:function	Element	Yes
func:result	Element	Yes
func:script	Element	No

The supported extension functions require the following namespace declaration:

```
xmlns:func="http://exslt.org/functions"
```

function

Declares an extension function that is visible everywhere.

Syntax

```
<func:function
  name = qname>
  <-- Contents: (xsl:param* | template) -->
</func:function>
```

result

When an `func:result` element is instantiated, during the instantiation of a `func:function` element, the function returns with its value.

Syntax

```
<func:result
  select = expression>
  <-- Contents: template -->
</func:result>
```

Math module

The Math module includes the functions that are listed in Table 9.

Table 9. Supported functions for the EXSLT Functions module

Name	Element or function	Supported
<code>math:abs()</code>	Function	No
<code>math:acos()</code>	Function	No
<code>math:asin()</code>	Function	No
<code>math:atan()</code>	Function	No
<code>math:atan2()</code>	Function	No
<code>math:constant</code>	Function	No
<code>math:cos()</code>	Function	No
<code>math:exp()</code>	Function	No
<code>math:highest()</code>	Function	No
<code>math:log()</code>	Function	No
<code>math:lowest()</code>	Function	No
<code>math:max()</code>	Function	Yes
<code>math:min()</code>	Function	Yes
<code>math:power()</code>	Function	No
<code>math:random()</code>	Function	No
<code>math:sin()</code>	Function	No
<code>math:sqrt()</code>	Function	No
<code>math:tan()</code>	Function	No

The supported extension functions require the following namespace declaration:

```
xmlns:math="http://exslt.org/math"
```

`max()`

Returns a number that identifies the maximum.

Syntax

math:max(*nodeset*)

min()

Returns a number that identifies the minimum.

Syntax

math:min(*nodeset*)

Random module

The Random module includes the function that are listed in Table 10.

Table 10. Supported function for the EXSLT Random module

Name	Element or function	Supported
random:random-sequence()	Function	No

Regular Expressions module

The Regular Expressions module includes the functions that are listed in Table 11.

Table 11. Supported functions for the EXSLT Regular Expressions module

Name	Element or function	Supported
regexp:match()	Function	Yes
regexp:replace()	Function	Yes
regexp:test()	Function	Yes

The supported extension functions require the following namespace declaration:

```
xmlns:regexp="http://exslt.org/regular-expressions"
```

match()

Uses a regular expression, which uses the Perl-compatible regular expression (PCRE) syntax, to capture parts of a target string and returns a node set of match elements, each of whose string values is equal to a portion of the first argument string that was captured by the regular expression.

Syntax

regexp:match(*input*, *expression*, *flags*)

replace()

Uses a regular expression, which follows the Perl-compatible regular expression (PCRE) syntax, to extract part or all of an input string and replace it with another string.

Syntax

regexp:replace(*input*, *expression*, *flags*, *replacementString*)

test()

Performs a string/regular expression match using Perl-compatible regular expression (PCRE) syntax.

Syntax

`regex:test(input, expression, flags)`

Sets module

The Sets module includes the functions that are listed in Table 12.

Table 12. Supported functions for the EXSLT Sets module

Name	Element or function	Supported
<code>set:difference()</code>	Function	Yes
<code>set:distinct()</code>	Function	Yes
<code>set:has-same-node()</code>	Function	Yes
<code>set:intersection()</code>	Function	Yes
<code>set:leading()</code>	Function	Yes
<code>set:trailing()</code>	Function	Yes

The supported extension functions require the following namespace declaration:

```
xmlns:set="http://exslt.org/sets"
```

difference()

Compares two node sets to identify nodes that are in the first node set but not in the second node set.

Syntax

`set:difference(nodeset1, nodeset2)`

distinct()

Extracts a list of all nodes in a target node set.

Syntax

`set:distinct(nodeset)`

has-same-node()

Compares two node sets, looking for common nodes.

Syntax

`set:has-same-node(nodeset1, nodeset2)`

intersection()

Returns a list of the nodes common to two input node sets.

Syntax

`set:intersection(nodeset1, nodeset2)`

leading()

Returns a list of the nodes in the node set passed as the first argument that precede, in document order, the first node in the node set passed as the second argument.

Syntax

set:leading(*nodeset1*, *nodeset2*)

trailing()

Returns a list of the nodes in the node set passed as the first argument that follow, in document order, the first node in the node set passed as the second argument.

Syntax

set:trailing(*nodeset1*, *nodeset2*)

Strings module

The Strings module includes the functions that are listed in Table 13.

Table 13. Supported functions for the EXSLT Strings module

Name	Element or function	Supported
str:align()	Function	No
str:concat()	Function	Yes
str:decode-uri()	Function	Yes
str:encode-uri()	Function	Yes
str:padding()	Function	Yes
str:replace()	Function	No
str:split()	Function	Yes
str:tokenize()	Function	Yes

The supported extension functions require the following namespace declaration:

```
xmlns:str="http://exslt.org/strings"
```

concat()

Returns the concatenation of the string values of all nodes in a target node set.

Syntax

str:concat(*nodeset*)

decode-uri()

Decodes a URI-encoded string.

Syntax

str:decode-uri(*URI*, *encoding*)

Parameters

URI Specifies an XPath expression that resolves to a string and specifies the string to escape.

encoding

Specifies an optional XPath expression that resolves to a string and specifies the character encoding of *URI*. If specified, use an encoding name that is listed in “Character Sets” (<http://www.iana.org/assignments/character-sets>). The default is UTF-8.

encode-uri()

Returns an encoded URI.

Syntax

str:encode-uri(*URI*, *escapeReserved*, *encoding*)

Parameters

URI Specifies an XPath expression that resolves to a string and specifies the string to escape.

escapeReserved

Indicates whether to escape reserved characters.

`true()` Escapes all characters that are referred to in Section 2.3 of RFC 2396 as “unreserved characters”. Use this value to escape a string that is to form a single part of a URI, URI reference, or IRI.

`false()`

Does not escape characters that are referred to in RFC 2396 and RFC 2732 as “reserved” characters. Use this value to escape an entire URI, URI reference, or IRI.

encoding

Specifies an optional XPath expression that resolves to a string and specifies the character encoding of *URI*. If specified, use an encoding name that is listed in “Character Sets” (<http://www.iana.org/assignments/character-sets>). The default is UTF-8.

Guidelines

Escaping rules are defined in Section 2 of RFC 2396, *Uniform Resource Identifiers (URI): Generic Syntax*, as amended by RFC 2732, *Format for Literal IPv6 Addresses in URL's*, to an input string, which typically represents all or part of a URI, URI reference, or Internationalized Resource Identifier (IRI).

The effect of the function is to replace any special character in the string by an escape sequence of the form `%xx%yy...`, where `xxyy...` is the hexadecimal representation of the octets that represent the character in ASCII for characters in the ASCII repertoire, and a different character encoding for non-ASCII characters.

RFC 2396 does not define whether escaped URIs should use lower case or uppercase for hexadecimal digits. To ensure that escaped URIs can be compared using string comparison functions, this function must always use the uppercase letters A through F.

UTF-8 is the only encoding that is required to be supported by an implementation of this function. If the given encoding is not supported, then returns an empty string. If the encoding is supported but a character in the string cannot be represented in that encoding, then the character is escaped as if it were a question mark (“%3F”).

Examples

- Returns `http://www.example.com/my%20r%E9sum%C3%A9.html`
`str:encode-uri('http://www.example.com/my résumé.html', false())`
- Returns `http%3A%2F%2Fwww.example.com%2Fmy%20r%C3%A9sum%C3%A9.html`
`str:encode-uri('http://www.example.com/my résumé.html', true())`
- Returns `http://www.example.com/my%20r%E9sum%E9.html` if the implementation supports ISO-8859-1, or an empty string otherwise.

```
str:encode-uri('http://www.example.com/my résumé.html', false(), 'iso-8859-1')
```

padding()

Creates a padding string of a specified length.

Syntax

str:padding(*length*, *string*)

split()

Splits up a string and returns a node set of token elements, each containing one token from the string.

Syntax

str:split(*string*, *pattern*?)

tokenize()

Splits up a string and returns a node set of token elements, each containing one token from the string.

Syntax

str:tokenize (*string*, *delimiter*?)

Chapter 6. WebGUI extensions

This chapter provides documentation about available DataPower XSLT extension elements. The documentation for each element contains the following sections:

- Element name
- Platform availability
- Declarations for required namespace and extension prefix
- Syntax
- Attributes with data type
- Child elements
- Guidelines
- Examples

param

Controls the presentation of parameters in transform processing actions.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"  
extension-element-prefixes="dp"
```

Syntax

```
<dp:param name="name" type="'dmString'" xmlns="">  
  <display>label</display>  
  <description>description</description>  
  <default>value</default>  
</dp:param>
```

Attributes

name="name"

(xs:string) Specifies the name of the parameter. The value must match that of the name attribute of the xsl:param element.

type="'dmString'"

(xs:string) Specifies the DataPower data type. The value must be dmString.

Child elements

<display>label</display>

The <display> element defines the text for the label.

<description>description</description>

(Optional) The <description> element defines the online help for the parameter. The help is available by double-clicking the label.

```
<default>value</default>
```

(Optional) The <default> element identifies the default value for the parameter. If required, the value must match that of the select attribute of the xsl:param element.

Guidelines

The dp:param element controls the presentation of global parameters in the processing policy editor. In other words, controls WebGUI the presentation of custom properties when configuring a transform xform action that uses a custom style sheet. The action is defined by the <operation> element within the dp:summary element.

Examples

```
<xsl:stylesheet ...>
...
<dp:summary xmlns="">
  <operation>xform</operation>
  <description>Test Transform</description>
</dp:summary>
...
<xsl:param name="enableIndent" select="'off'" />
<dp:param name="enableIndent" type="'dmString'" xmlns="">
  <display>Use Standard Indentations</display>
  <description>Indicates whether to use standard indentations. When enabled (on),
the format of the output pads child elements using five spaces. When disabled
(off), the outut is not formatted. The default is off.</description>
  <default>off</default>
</dp:param>
...
```

summary

Controls the presentation of icons in processing policy.

Availability

All products

Namespace declaration

```
xmlns:dp="http://www.datapower.com/extensions"
extension-element-prefixes="dp"
```

Syntax

```
<dp:summary xmlns="">
  <operation>xform</operation>
  <description>tooltip</description>
</dp:summary>
```

Attributes

None

Child elements

```
<operation>xform</operation>
```

The <operation> element identifies the type of processing action. the text for the label. The value must be xform.

```
<description>tooltip</description>
```

(Optional) The `<description>` element defines the text to display when the cursor is on the icon.

Guidelines

The `dp:summary` element controls the presentation of action icon in the processing policy editor. This element can be used with `xform` actions only.

Examples

```
<xsl:stylesheet ...>
...
<dp:summary xmlns="">
  <operation>xform</operation>
  <description>Test Transform</description>
</dp:summary>
...
<xsl:param name="enableIndent" select="'off'" />
<dp:param name="enableIndent" type="'dmString'" xmlns="">
  <display>Use Standard Indentations</display>
  <description>Indicates whether to use standard indentations. When enabled (on),
the format of the output pads child elements using five spaces. When disabled
(off), the output is not formatted. The default is off.</description>
  <default>off</default>
</dp:param>
...
```

Appendix A. Working with variables

Variables can be used in most context, except PIPE. To use a variable, you must create it with the `setvar` action. A `setvar` action creates a variable in a specified context and assigns it a value.

Note: You can view the value of variables for a transaction with the multistep probe. Edit the DataPower service to enable the multistep probe. After enabling the multistep probe and recording transactions, you can view variables and their values.

There are the following distinct variable types, each expressed in the `var://URL` format:

`var://local/variable`

A local context variable to addresses a variable called *variable* in the default (current) context. The following example transforms the document in the `tmp1` context with a style sheet that is referenced by the `stylesheet-1` variable (also in the `tmp1` context) and stores the transformed document in the `tmp2` context:

```
xform tmp1 var://local/stylesheet-1 tmp2
```

The local context does not persist beyond the scope of the multistep transaction. A multistep transaction can include both a request component and a response component. The local context cannot be accessed by any object outside of the scope of the multistep transaction. In other words, the service cannot read and use the variable.

A local context variables can be user-defined or based on an extension variable. For a complete list of the available extension variables, refer to “Extension variables” on page 210.

`var://context/context/variable`

Addresses a variable called *variable* in a context called *context*. The following example transforms the document in the `tmp1` context with a style sheet that is referenced by the `stylesheet-1` variable (in the `apple` context) and stores the transformed document in the `tmp2` context:

```
xform tmp1 var://context/apple/stylesheet-1 tmp2
```

A named context does not persist beyond the scope of the multistep transaction. A multistep transaction can include both a request component and a response component. The local context cannot be accessed by any object outside of the scope of the multistep transaction. In other words, the service cannot read and use the variable.

Note: Creating variables in a named context is the recommended approach. This form decouples the variable from the input and output contexts and allows the variable to be accessed from any step in a multistep scope.

A named context variables can be user-defined or based on an extension variable. For a complete list of the available extension variables, refer to “Extension variables” on page 210.

`var://service/variable`

Address a variable that is made available to a service (such as HTTP or XSL Co-Processor) that is attached to a multistep session. The majority of service variables are read-only and cannot be set.

For a complete list of the available service variables, refer to “Service variables.”

`var://system/variable`

Addresses a global variable that is available in all contexts. System variables persist beyond the multistep scope and can be read by other objects in the system. If the content of a variable needs to be read or set outside the scope of the multistep process, use a system variable.

For a complete list of the available global system variables, refer to “System variables” on page 212.

Note: Table 31 on page 213 lists all of the variables that are available when using a DataPower appliance.

Service variables

Service variables enable the setting and retrieval of pieces of state that usually reflect the state of the current transaction.

The available service variables are separated alphabetically into the following categories:

- General service variables that are available to all DataPower services
- Service variables that are available only to Multi-Protocol Gateway services and to Web Service Proxy services
- Configuration services
- Load balancer service
- MQ-specific services

General service variables

This section contains information about general variables in alphabetic order by permission category. General variables are available to all services. Table 14 lists the names and permission for these variables.

Table 14. Names and permissions for variables that are available to all DataPower services

Variable name	Permission
<code>var://service/soap-fault-response</code>	Read-write
<code>var://service/system/ident</code>	Read-only
<code>var://service/system/status/status-enumeration</code>	Read-only

Read-only variables

`var://service/system/ident`

Gets the system identification information. This information includes the product number, the model, the configured name of the DataPower appliance, and the serial number.

`var://service/system/status/status-enumeration`

Gets the contents of a specific status object. You must include the enumeration value of the status object. Refer to the StatusEnum type in the `store:///xml-mgmt.xsd` schema for the list of the available status objects.

Use the following variable to return the contents of the Load Balancer status object. This status object corresponds to the LoadBalancerStatus enumeration value.

`var://service/system/status/LoadBalancerStatus`

Read-write variables

`var://service/soap-fault-response`

Set when the response input rule is treated as a SOAP fault.

Multi-Protocol Gateway and Web Service Proxy service variables

This section contains information about general variables in alphabetic order by permission category. General variables are available to all services. Table 15 lists the names and permission for these variables.

Table 15. Names and permissions for variables that are available only to Multi-Protocol Gateway services and to Web Service services

Variable name	Permission
<code>var://service/mpgw/backend-timeout</code>	Read-write
<code>var://service/mpgw/request-size</code>	Read-only
<code>var://service/mpgw/response-size</code>	Read-only
<code>var://service/mpgw/skip-backside</code>	Write-only

Read-only variables

`var://service/mpgw/request-size`

For Multi-Protocol Gateway and Web Service Proxy services only, gets the size of a request message. The value 0 indicates that the size cannot be determined, perhaps temporarily, due to message streaming or some other processing issue.

`var://service/mpgw/response-size`

For Multi-Protocol Gateway and Web Service Proxy services only, gets the size of a response message. The value 0 indicates that the size cannot be determined, perhaps temporarily, due to message streaming or some other processing issue.

Write-only variables

`var://service/mpgw/skip-backside`

For Multi-Protocol Gateway and Web Service Proxy services only, indicates that the service skips backside processing.

Set this variable to 1 to prevent backside processing. Use this variable as a custom redirect implementation, not as the point of the service. Because the service is not aware of the processing flow, unusual messages might be written to the event log.

Read-write variables

`var://service/mpgw/backend-timeout`

For Multi-Protocol Gateway and Web Service Proxy services only, gets or sets the backend timeout, in seconds. Setting this variable overrides the default timeout. Use an integer in the range of 1 through 86400.

Configuration services service variables

This section contains information about configuration Services variables in alphabetic order by permission category. Table 16 lists the names and permission for these variables.

Table 16. Names and permissions for variables that are available for configuration services

Variable name	Permission
var://service/back-attachment-format	Read-only
var://service/config-param	Write-only
var://service/default-stylesheet	Read-only
var://service/domain-name	Read-only
var://service/front-attachment-format	Read-only
var://service/system/frontwsdl	Read-only
var://service/max-call-depth	Read-write
var://service/processor-name	Read-only
var://service/processor-type	Read-only
var://service/xmlmgr-name	Read-only

Read-only variables

var://service/back-attachment-format
Gets the format for the backside attachment.

var://service/default-stylesheet
Gets the name of the default processing policy.

var://service/domain-name
Gets domain of the service.

var://service/front-attachment-format
Gets the format for the frontend attachment.

var://service/system/frontwsdl
Gets the frontend WSDL URL of the service.

var://service/processor-name
Gets the name of the service (processor).

var://service/processor-type
Gets the service (processor) type.

var://service/xmlmgr-name
Gets the name of the XML manager service.

Write-only variables

var://service/config-param/parameterName value
Sets the specified stylesheet parameter to the specified value.

Read-write variables

var://service/max-call-depth
Gets or sets the maximum call depth for each transaction. This variable controls how many levels of called rules can be layered before an error is thrown. The default is 128.

Load balancer service variables

This section contains information about load balancer variables in alphabetic order by permission category. Table 17 lists the names and permission for these variables.

Table 17. Names and permissions for variables that are available for load balancers

Variable name	Permission
var://service/lb/group	Read-only
var://service/lb/member	Read-only
var://service/lbhealth/	Write-only

Read-only variables

var://service/lb/group

Gets the name of the load balancer group.

var://service/lb/member

Gets the group member for the current load balancer.

Write-only variables

var://service/lbhealth/

Sets the member and state of a load balancer group.

MQ-specific service variables

This section contains information about MQ-specific variables in alphabetic order by permission category. MQ-specific variables are available to MQ Host services and MQ Proxy services. Table 18 lists the names and permission for these variables.

Table 18. Names and permissions for variables that are available to MQ objects

Variable name	Permission
var://service/accounting-token	Read-only
var://service/backout-count	Read-only
var://service/correlation-identifier	Read-write
var://service/expiry	Read-write
var://service/format	Read-write
var://service/message-identifier	Read-write
var://service/message-type	Read-write
var://service/mq-ccsi	Write-only
var://service/mq-error-code	Read-only
var://service/mqmd-reply-to-q	Write-only
var://service/mqmd-reply-to-qm	Write-only
var://service/original-length	Read-only
var://service/persistence	Read-write
var://service/priority	Read-write
var://service/put-date	Read-only
var://service/put-time	Read-only
var://service/reply-to-q	Read-write
var://service/reply-to-qm	Read-write
var://service/report	Read-write

Table 18. Names and permissions for variables that are available to MQ objects (continued)

Variable name	Permission
var://service/user-identifier	Read-only

Read-only variables

var://service/accounting-token
Gets the MQ message descriptor AccountingToken.

var://service/backout-count
Gets the MQ Backout Count.

var://service/mq-error-code
Gets the MQ Reason Code for the last MQ API call.

var://service/original-length
Gets the MQ message descriptor OriginalLength.

var://service/put-date
Gets the MQ message descriptor PutDate.

var://service/put-time
Gets the MQ message descriptor PutTime.

var://service/user-identifier
MQ User Identifier - Gets the MQ message descriptor UserIdentifier.

Write-only variables

var://service/mq-ccsi
Sets the MQ message descriptor character set for an MQ Host or Proxy service.

var://service/mqmd-reply-to-q
Sets the output MQ message descriptor.ReplyToQ value for an MQ Host or Proxy service.

var://service/mqmd-reply-to-qm
Sets the output MQ message descriptor.ReplyToQM value for an MQ Host or Proxy service.

Read-write variables

var://service/correlation-identifier
Read and write the MQ value in the Correlation Identifier header for MQ Host and Proxy services.

var://service/expiry
Read and write the MQ value in the Expiry header for MQ Host and Proxy services.

var://service/format
Read and write the MQ value in the Format header for MQ Host and Proxy services.

var://service/message-identifier
Read and write the MQ value in the Message Identifier header for MQ Host and Proxy services.

var://service/message-type
Read and write the MQ value in the Message Type header for MQ Host and Proxy services.

var://service/persistence
Read and write the MQ value in the Persistence for MQ Host and Proxy services.

var://service/priority
Read and write the MQ value in the Priority header for MQ Host and Proxy services.

var://service/reply-to-q
Read and write the MQ value in the ReplyToQ (Reply to Queue) header for MQ Host and Proxy services. When read, shows the input message value. When write, changes the dynamic routing.

var://service/reply-to-qm
Read and write the MQ value in the ReplyToQM (Reply to Queue Manager) header for MQ Host and Proxy services. When read, shows the input message value. When write, changes the dynamic routing.

var://service/report
Read and write the MQ value in the Report header for MQ Host and Proxy services.

Multistep variables

This section contains information about system variables in alphabetic order by permission category. Multistep variables usually impact the behavior of specific actions in the context of a processing rule. Table 19 lists the names and permission for these variables.

Table 19. Names and permissions for variables that are available to all services

Variable name	Permission
var://multistep/loop-count	Read-only
var://multistep/loop-iterator	Read-only
var://service/log/soapversion	Read-write
var://service/multistep/contexts	Read-only

Read-only variables

var://multistep/loop-count
Gets the loop iterator for the innermost for-each action. If the for-each action is set to run with a fixed iteration count, returns the input context of the loop action. If the loop runs over a node set, returns the current element in the node set.

var://multistep/loop-iterator
Gets the current loop count for the innermost for-each action. For the first action in the loop, returns 1; for the second action, returns 2, and so forth.

var://service/multistep/contexts
Gets all existing contexts.

Read-write variables

var://service/log/soapversion
Gets or sets the version of SOAP for use by a SOAP log targets. Use a setvar action before a log action to change the version of SOAP to use when logging this message.

Supports the following values:

soap11 Uses SOAP 1.1.
soap12 (Default) Uses SOAP 1.2.

Transaction variables

The available transaction variables are separated alphabetically into the following categories:

- Asynchronous transactions
- Error handling
- Headers
- Information
- Persistent connections
- Routing
- Statistics
- URL
- Web Services Management (WSM)

Asynchronous transaction variables

This section contains information about asynchronous transaction variables in alphabetic order by permission category. Table 20 lists the names and permission for these variables.

Table 20. Names and permissions for variables that are available for asynchronous transactions

Variable name	Permission
var://service/soap-oneway-mep	Read-write
var://service/transaction-key	Write-only
var://service/transaction-name	Write-only
var://service/transaction-timeout	Write-only

Write-only variables

var://service/transaction-key
Sets the token for asynchronous transactions.

var://service/transaction-name
Sets the name for asynchronous transactions.

var://service/transaction-timeout
Sets the timeout for asynchronous transactions.

Read-write variables

var://service/soap-oneway-mep
Gets or sets the SOAP one-way Message Exchange Pattern (MEP) notification.

- When true, notifies the service layer that this transaction is performing a one-way MEP operation. This setting enables the service layer to optimize resource usage while preventing Web Services Addressing (WSA) from waiting for and faulting on a response that will never arrive.
- When false, no notification is sent. When using WSA and one-way MEPs, the service layer will time out waiting for a response.

When a DataPower service is configured for WSA-to-WSA and it receives a WSA annotated message without the `wsa:MessageId`, the DataPower service assumes that this is a one-way MEP and notifies the service layer by setting this value of this variable to true.

This variable is not needed for Web Service Proxy services, as one-way MEPs are identified by reviewing the specifics of the port operation.

Error handling transaction variables

This section contains information about error handling variables in alphabetic order by permission category. Table 21 lists the names and permission for these variables.

Table 21. Names and permissions for variables that are available for error handling

Variable name	Permission
<code>var://service/error-code</code>	Read-write
<code>var://service/error-headers</code>	Read-only
<code>var://service/error-ignore</code>	Read-write
<code>var://service/error-message</code>	Read-write
<code>var://service/error-protocol-reason-phrase</code>	Write-only
<code>var://service/error-protocol-response</code>	Write-only
<code>var://service/error-subcode</code>	Read-write
<code>var://service/formatted-error-message</code>	Read-only
<code>var://service/strict-error-mode</code>	Read-write

Read-only variables

`var://service/error-headers`

Gets the error headers. This variable contains the name of the HTTP header field that contains error information.

`var://service/formatted-error-message`

Gets the formatted error message. This variable contains the formatted version of the error text in the `var://service/error-message` variable. The formatted error message is the message that is written to the log file.

Write-only variables

`var://service/error-protocol-reason-phrase`

Sets the protocol-specific reason phrase for an error. This variable overwrites the reason phrase in the response to provide a short description that can be understood by people.

`var://service/error-protocol-response`

Sets the protocol-specific response for an error. This variable overwrites the protocol-specific response code in an error condition.

Read-write variables

`var://service/error-code`

Gets or sets the assigned error code from the Result Code table.

`var://service/error-ignore`

Gets or sets a flag that controls how the Front Side Handler processes error condition. If the value is set and greater than zero, it does not run any

error handling action and produces a regular response. The content of the message is produced by an error rule.

The default value is 0.

Currently, on the TIBCO EMS and WebSphere JMS Front Side Handler use this variable. If any error happens and the variable is set, the Front Side Handler acknowledges a request message and puts the response message in the PUT queue. This response message will be a SOAP-fault or any output that error rule generates.

`var://service/error-message`

Gets or sets the generic error message that is sent to the client. This variable contains the error condition that stopped multistep processing. Setting this variable overwrites the error response that is sent to the client in an error condition. To set the error message that is written to the log file, use the `var://service/formatted-error-message` variable.

`var://service/error-subcode`

Gets or sets the error sub-code. This variable can help to disambiguate the reason for which the error rule was invoked. Often, the sub-code is the same as the value of the `var://service/error-code` variable. Sometimes, the sub-code is a more specific result code.

`var://service/strict-error-mode`

Gets or sets the strict error mode. This variable controls the error mode for multistep processing.

- If the value is set, an invocation of the `dp:reject` extension element stops multistep processing.
- If the value is not set, an invocation of the `dp:reject` extension element logs a message but does not stop multistep processing.

Headers transaction variables

This section contains information about header variables in alphabetic order by permission category. Table 22 lists the names and permission for these variables.

Table 22. Names and permissions for variables that are available for headers

Variable name	Permission
<code>var://service/append-request-header/</code>	Write-only
<code>var://service/append-response-header/</code>	Write-only
<code>var://service/header-manifest</code>	Read-only
<code>var://service/set-request-header/</code>	Write-only
<code>var://service/set-response-header/</code>	Write-only

Read-only variables

`var://service/header-manifest`

Gets the transaction header manifest. The manifest lists all protocol headers of current transaction.

Write-only variables

`var://service/append-request-header/`

Appends to the protocol request header.

`var://service/append-response-header/`

Appends to the protocol response header.

`var://service/set-request-header/`
 Sets the protocol request header. This variable directly correlates to the **dp:set-request-header()** extension function. Setting the `var://service/set-request-header/F00` variable to the value BAR would set the request header F00 to BAR.

`var://service/set-response-header/`
 Sets the protocol response header. This variable directly correlates to the **dp:set-response-header()** extension function. Setting the `var://service/set-response-header/F00` variable to the value BAR would set the response header F00 to BAR.

Information transaction variables

This section contains information about information variables in alphabetic order by permission category. Table 23 lists the names and permission for these variables.

Table 23. Names and permissions for variables that are available for information

Variable name	Permission
<code>var://service/current-call-depth</code>	Read-only
<code>var://service/input-size</code>	Read-only
<code>var://service/transaction-audit-trail</code>	Read-only
<code>var://service/transaction-client</code>	Read-only
<code>var://service/transaction-id</code>	Read-only
<code>var://service/transaction-policy-name</code>	Read-only
<code>var://service/transaction-rule-name</code>	Read-only
<code>var://service/transaction-rule-type</code>	Read-only

Read-only variables

`var://service/current-call-depth`
 Gets the current call depth. This variable returns the current depth of called rules. The maximum call depth is set with the `var://service/max-call-depth` variable.

`var://service/input-size`
 Gets the size of the parsed input message (request or response). The value 0 indicates that the size cannot be determined, perhaps temporarily, due to message streaming or some other processing issue.

`var://service/transaction-client`
 Gets the IP Address of transaction client.

`var://service/transaction-id`
 Gets the identifier of transaction.

`var://service/transaction-audit-trail`
 Gets the transaction audit trail.

`var://service/transaction-policy-name`
 Gets the policy name of the transaction

`var://service/transaction-rule-name`
 Gets the rule name of the transaction.

`var://service/transaction-rule-type`
 Gets the rule type of the transaction.

Persistent connection transaction variables

This section contains information about persistent connection variables in alphabetic order by permission category. Table 24 lists the names and permission for these variables.

Table 24. Names and permissions for variables that are available for persistent connections

Variable name	Permission
var://service/connection/note	Read-write
var://service/persistent-connection-counter	Read-only

Read-only variables

var://service/persistent-connection-counter

Gets the persistent connection counter. This variable returns the number of transactions that were completed on the current protocol session.

Read-write variables

var://service/connection/note

Gets or sets the annotation for the current connection. This variable allows the user to annotate the current protocol session. The value could be an identifier that could be used to maintain the state based on an existing protocol session.

Routing transaction variables

This section contains information about routing variables in alphabetic order by permission category. Table 25 lists the names and permission for these variables.

Table 25. Names and permissions for variables that are available for routing

Variable name	Permission
var://service/routing-url	Write-only
var://service/routing-url-sslprofile	Write-only

Write-only variables

var://service/routing-url

For XML Firewall, Multi-Protocol Gateway, and Web Service Proxy services, sets the routing URL. This variable can be set one time only and takes the following format:

```
<dp:set-variable name="var://service/routing-url"
  value="'protocol://target/URI'" />
```

- For XML Firewall services:
 - The protocol must be HTTP or HTTPS. If any other protocol, the service generates an error.
 - The URI is stripped. To specify the URI, use the var://service/URI variable, as shown in the following excerpt:

```
<dp:set-variable name="'var://service/routing-url'"
  value="'http://10.10.36.11:2064'" />
<dp:set-variable name="'var://service/URI'"
  value="'/service'" />
```

- For Multi-Protocol Gateway and Web Service Proxy services:
 - The protocol can be any valid backend protocol.

- The URI is absolute and cannot be controlled with the **Propagate URI** toggle (WebGUI) or **propagate-uri** command.

The `var://service/routing-url` variable is an addition to the `dp:set-target` and `dp:xset-target` extension elements. These extension elements do not allow the specification of a protocol. These extension element, if provided, overrides the value of the target server that is specified in this variable.

`var://service/routing-url-sslprofile`

Sets the SSL proxy profile for the routing URL (dynamic route). Use this variable when the `ssl` property for the DataPower service is not sufficient for the route to be selected. Use this variable before using the `var://service/routing-url` variable.

Statistics variables

This section contains information about statistics variables in alphabetic order by permission category. Table 26 lists the names and permission for these variables.

Table 26. Names and permissions for variables that are available for statistics

Variable name	Permission
<code>var://service/time-elapsed</code>	Read-only
<code>var://service/time-forwarded</code>	Read-only
<code>var://service/time-response-complete</code>	Read-only
<code>var://service/time-started</code>	Read-only

Read-only variables

`var://service/time-elapsed`

Gets the duration of the transaction.

`var://service/time-forwarded`

Gets the timestamp for when the request messaged was forwarded.

`var://service/time-response-complete`

Gets the timestamp for when the transaction completes (ends).

`var://service/time-started`

Gets the timestamp for when the request was received (started).

URL-based transaction variables

This section contains information about URL-based transaction variables in alphabetic order by permission category. Table 27 lists the names and permission for these variables.

Table 27. Names and permissions for variables that are available for URL-based transactions

Variable name	Permission
<code>var://service/client-service-address</code>	Read-only
<code>var://service/local-service-address</code>	Read-only
<code>var://service/protocol</code>	Read-only
<code>var://service/URI</code>	Read-write
<code>var://service/URL-in</code>	Read-only
<code>var://service/URL-out</code>	Read-only

Read-only variables

`var://service/client-service-address`
Gets the address of the frontend client.

`var://service/local-service-address`
Gets the address of the frontend service.

`var://service/protocol`
Gets the frontend Protocol

`var://service/URL-in`
Gets the URL of the incoming request.

`var://service/URL-out`
Gets the outbound URL to the backend

Read-write variables

`var://service/URI`
Gets or sets the request URI of the transaction.

Web Services Management transaction variables

This section contains information about Web Services Management (WSM) variables in alphabetic order by permission category. Table 28 lists the names and permission for these variables.

Table 28. Names and permissions for variables that are available to WSM

Variable name	Permission
<code>var://service/wsa/timeout</code>	Read-write
<code>var://service/wsa/genpattern</code>	Read-write
<code>var://service/wsm/aaa-policy-name</code>	Read-only
<code>var://service/wsm/binding</code>	Read-only
<code>var://service/wsm/enabled</code>	Read-only
<code>var://service/wsm/validate-faults</code>	Read-only
<code>var://service/wsm/validate-headers</code>	Read-only
<code>var://service/wsm/validate-message</code>	Read-only
<code>var://service/wsm/wsd1</code>	Read-only
<code>var://service/wsm/wsd1-error</code>	Write-only
<code>var://service/wsm/wsd1-warning</code>	Write-only
<code>var://wsm/num-subschema</code>	Read-only
<code>var://wsm/operation</code>	Read-only
<code>var://wsm/schemalocation</code>	Read-only
<code>var://wsm/resolve-hrefs</code>	Read-only
<code>var://wsm/service</code>	Read-only
<code>var://wsm/service-port</code>	Read-only
<code>var://wsm/service-port-operation</code>	Read-only
<code>var://wsm/strict-fault-document-style</code>	Read-only

Read-only variables

`var://service/wsm/aaa-policy-name`
Gets the name of the WSM AAA policy.

`var://service/wsm/binding`
Gets the WSM service binding.

`var://service/wsm/enabled`
Gets the WSM enabled flag.

`var://service/wsm/validate-faults`
Gets the WSM fault validation.

`var://service/wsm/validate-headers`
Gets the WSM header validation.

`var://service/wsm/validate-message`
Gets the WSM validate message.

`var://service/wsm/wSDL`
Gets the WSM WSDL.

`var://wsm/num-subschema`
Gets the number of WSM subschema.

`var://wsm/operation`
Gets the WSM service operation.

`var://wsm/schemalocation`
Gets the WSM schema location.

`var://wsm/resolve-hrefs`
Gets the WSM resolve HREFs.

`var://wsm/service`
Gets the WSM service name.

`var://wsm/service-port`
Gets the WSM service port.

`var://wsm/service-port-operation`
Gets the WSM service port operation.

`var://wsm/strict-fault-document-style`
WSM strict fault document style. Do not expect RPC wrappers on RPC faults.

Write-only variables

`var://service/wsm/wSDL-error`
Sets the WSDL error.

`var://service/wsm/wSDL-warning`
Sets the WSDL warning.

Read-write variables

`var://service/wsa/timeout`
Gets or sets the timeout value for the WS-Addressing asynchronous reply.

`var://service/wsa/genpattern`
Gets or sets the pattern for the WS-Addressing asynchronous reply.

Extension variables

This section contains information about system variables in alphabetic order by permission category. Extension variables usually impact the behavior of specific actions, particularly `fetch`, `results`, and `results-async` actions. Table 29 lists the names and permission for these variables.

Table 29. Names and permissions for extension variables

Variable name	Permission
<code>var://local/_extension/allow-compression</code>	Write-only
<code>var://local/_extension/attachment-format</code>	Read-only
<code>var://local/_extension/attachment-manifest</code>	Read-only
<code>var://local/_extension/attachment-root-uri</code>	Read-only
<code>var://local/_extension/donot-follow-redirect</code>	Write-only
<code>var://local/_extension/error</code>	Read-only
<code>var://local/_extension/header/</code>	Write-only
<code>var://local/_extension/http-10-only</code>	Write-only
<code>var://local/_extension/messages</code>	Read-only
<code>var://local/_extension/prevent-persistent-connection</code>	Write-only
<code>var://local/_extension/response-headers</code>	Read-only
<code>var://local/_extension/response-header/<i>headerName</i></code>	Read-only
<code>var://local/_extension/responsecode</code>	Read-only
<code>var://local/_extension/sslprofile</code>	Write only
<code>var://local/_extension/variables</code>	Read-only

Read-only variables

`var://local/_extension/attachment-format`
Gets the output format of the attachment.

`var://local/_extension/attachment-manifest`
Gets the manifest for the attachment.

`var://local/_extension/attachment-root-uri`
Get the base URI for document attachments.

`var://local/_extension/error`
Gets the error manifest. This variable contains the error message, if any, from the last `dp:transform()`, `dp:parse()`, or `document()` invocation. If the variable is empty, no error occurred. If an error occurs in any subsequent calls to one of these functions, the existing error message, if any, will be overwritten.

`var://local/_extension/messages`
Gets the `xsl:message` manifest.

`var://local/_extension/response-headers`
Gets the manifest for the response header. This variable, on the output context of a `dp:url-open()` extension function or `results` action or `fetch` action, contains in the response header manifest.

`var://local/_extension/response-header/headerName`
Gets the contents of the specified response header. This variable, in the

output context of a **dp:url-open()** extension function or results action or fetch action, contains the contents of the specified response header.

`var://local/_extension/responsecode`

Gets the response code. This variable is set on an output context to indicate the protocol-level response code of a **dp:url-open()** extension function or results action or fetch action. For instance, if the following action is successful:

```
results tmpvar2 http://foo.bar.com/foome.asp tmpvar3
```

The value of 200 would be written to the `var://context/tmpvar3/_extension/responsecode` context variable.

`var://local/_extension/variables`

Gets the variable manifest.

Write-only variables

`var://local/_extension/allow-compression`

Enables compression of HTTP requests. Set this variable to allow compression of outgoing results content and negotiate the returned document to be compressed if the underlying protocol supports it. For HTTP, this means the content-encoding and accept-encoding headers.

`var://local/_extension/donot-follow-redirect`

Disables HTTP redirects. Set this variable to prevent the following of protocol-level redirect sequences on the outgoing results and fetch calls that are associated with this context. By default, redirects are followed.

`var://local/_extension/header/`

Appends the specified header field to the protocol connection. Variables of the following form can be set to append headers to the **dp:url-open()** extension function or results action or fetch action connection when a context that contains them is used as the input context:

`_extension/header/*`

The following example would add the HTTP header `X-foo: bar` to the HTTP request:

```
setvar tmpvar2 var://local/_extension/header/X-foo bar
results tmpvar2 http://foo.bar.com/foome.asp tmpvar3"
```

`var://local/_extension/http-10-only`

Restricts HTTP to version 1.0. Set this variable to prevent the use of HTTP/1.1 on the related context of a results action or fetch action.

`var://local/_extension/prevent-persistent-connection`

Disables HTTP persistent connection. Set this variable to prevent persistent connections of the outgoing a results action call or fetch action call that is associated with this context. Persistent connections are supported by default, where appropriate.

`var://local/_extension/sslprofile`

Sets the SSL proxy profile for the request. This variable can be set on the input context to a **dp:url-open()** extension function or to a results action or to a fetch action to override the selection of an SSL Proxy Profile. For instance:

```
results tmpvar2 https://foo.bar.com/foome.asp tmpvar3
```

would normally use the SSL Proxy Profile that is associated with any user-agent configuration for the URL
`https://foo.bar.com/foome.asp`

If the profile needed to be determined programmatically, perhaps based on AAA, it could be set up as follows to dynamically resolve the value of `*sslprofiletouse`:

```
setvar tmpvar2 var://local/_extension/sslprofile
var://context/notepad/sslprofiletouse
results tmpvar2 https://foo.bar.com/foome.asp tmpvar3
```

`var://local/_extension/timeout`

Sets the request timeout on an input context to override any previously set timeout parameter. Set the value in seconds.

System variables

This section contains information about system variables in alphabetic order by permission category. Table 30 lists the names and permission for these variables.

Table 30. Names and permissions for system variables

Variable name	Permission
<code>var://system/map/debug</code>	Read-write
<code>var://system/tasktemplates/debug</code>	Read-write

Read-write variables

`var://system/map/debug`

Gets or sets the debugging level for role-based management (RBM).

`var://system/tasktemplates/debug`

Gets or sets the debugging level for task templates.

List of available variables

Table 31 lists all of the variables that are available when using a DataPower appliance.

Table 31. All available variables

Short variable name	Full variable name	Category	Permission
aaa-policy-name	var://service/wsm/aaa-policy-name	Transaction, WSM	Read-only
accounting-token	var://service/accounting-token	Service, MQ	Read-only
allow-compression	var://local/_extension/allow-compression	Extension	Write-only
append-request-header	var://service/append-request-header	Transaction, headers	Write-only
append-response-header	var://service/append-response-header	Transaction, headers	Write-only
attachment-format	var://local/_extension/attachment-format	Extension	Read-only
attachment-manifest	var://local/_extension/attachment-manifest	Extension	Read-only
attachment-root-uri	var://local/_extension/attachment-root-uri	Extension	Read-only
back-attachment-format	var://service/back-attachment-format	Service, configuration	Read-only
backend-timeout	var://service/mpgw/backend-timeout	Service, general	Read-write
backout-count	var://service/backout-count	Service, MQ	Read-only
binding	var://service/wsm/binding	Transaction, WSM	Read-only
client-service-address	var://service/client-service-address	Transaction, URL	Read-only
config-param	var://service/config-param	Service, configuration	Write-only
contexts	var://service/multistep/contexts	Service, multistep	Read-only
correlation-identifier	var://service/correlation-identifier	Service, MQ	Read-write
current-call-depth	var://service/current-call-depth	Transaction, information	Read-only
debug	var://system/map/debug	System	Read-write
	var://system/tasktemplates/debug		
default-stylesheet	var://service/default-stylesheet	Service, configuration	Read-only
domain-name	var://service/domain-name	Service, configuration	Read-only
donot-follow-redirect	var://local/_extension/donot-follow-redirect	Extension	Write-only
enabled	var://service/wsm/enabled	Transaction, WSM	Read-only
error	var://local/_extension/error	Extension	Read-only
error-code	var://service/error-code	Transaction, error handling	Read-write
error-headers	var://service/error-headers	Transaction, error handling	Read-only

Table 31. All available variables (continued)

Short variable name	Full variable name	Category	Permission
error-ignore	var://service/error-ignore	Transaction, error handling	Read-write
error-message	var://service/error-message	Transaction, error handling	Read-write
error-protocol-reason-phrase	var://service/error-protocol-reason-phrase	Transaction, error handling	Write-only
error-protocol-response	var://service/error-protocol-response	Transaction, error handling	Write-only
error-subcode	var://service/error-subcode	Transaction, error handling	Read-write
expiry	var://service/expiry	Service, MQ	Read-write
format	var://service/format	Service, MQ	Read-write
formatted-error-message	var://service/formatted-error-message	Transaction, error handling	Read-only
front-attachment-format	var://service/front-attachment-format	Service, configuration	Read-only
frontwsdl	var://service/system/frontwsdl	Service, configuration	Read-only
genpattern	var://service/wsa/genpattern	Transaction, WSM	Read-write
group	var://service/lb/group	Service, load balancer	Read-only
header	var://local/_extension/header	Extension	Write-only
header-manifest	var://service/header-manifest	Transaction, headers	Read-only
http-10-only	var://local/_extension/http-10-only	Extension	Write-only
ident	var://service/system/ident	Service, general	Read-only
input-size	var://service/input-size	Transaction, information	Read-only
lbhealth	var://service/lbhealth	Service, load balancer	Write-only
local-service-address	var://service/local-service-address	Transaction, URL	Read-only
loop-count	var://multistep/loop-count	Service, multistep	Read-only
loop-iterator	var://multistep/loop-iterator	Service, multistep	Read-only
max-call-depth	var://service/max-call-depth	Service, configuration	Read-write
member	var://service/lb/member	Service, load balancer	Read-only
message-identifier	var://service/message-identifier	Service, MQ	Read-write
message-type	var://service/message-type	Service, MQ	Read-write
messages	var://local/_extension/messages	Extension	Read-only
mq-ccsi	var://service/mq-ccsi	Service, MQ	Write-only

Table 31. All available variables (continued)

Short variable name	Full variable name	Category	Permission
mq-error-code	var://service/mq-error-code	Service, MQ	Read-only
mqmd-reply-to-q	var://service/mqmd-reply-to-q	Service, MQ	Write-only
mqmd-reply-to-qm	var://service/mqmd-reply-to-qm	Service, MQ	Write-only
note	var://service/connection/note	Transaction, persistent connection	Read-write
num-subschema	var://wsm/num-subschema	Transaction, WSM	Read-only
operation	var://wsm/operation	Transaction, WSM	Read-only
original-length	var://service/original-length	Service, MQ	Read-only
persistence	var://service/persistence	Service, MQ	Read-write
persistent-connection-counter	var://service/persistent-connection-counter	Transaction, persistent connection	Read-only
prevent-persistent-connection	var://local/_extension/prevent-persistent-connection	Extension	Write-only
priority	var://service/priority	Service, MQ	Read-write
processor-name	var://service/processor-name	Service, configuration	Read-only
processor-type	var://service/processor-type	Service, configuration	Read-only
protocol	var://service/protocol	Transaction, URL	Read-only
put-date	var://service/put-date	Service, MQ	Read-only
put-time	var://service/put-time	Service, MQ	Read-only
request-size	var://service/mpgw/request-size	Service, general	Read-only
reply-to-q	var://service/reply-to-q	Service, MQ	Read-write
reply-to-qm	var://service/reply-to-qm	Service, MQ	Read-write
report	var://service/report	Service, MQ	Read-write
resolve-hrefs	var://wsm/resolve-hrefs	Transaction, WSM	Read-only
response-header	var://local/_extension/response-header	Extension	Read-only
response-headers	var://local/_extension/response-headers	Extension	Read-only
response-size	var://service/mpgw/response-size	Service, general	Read-only
responsecode	var://local/_extension/responsecode	Extension	Read-only
routing-url	var://service/routing-url	Transaction, routing	Write-only
routing-url-sslprofile	var://service/routing-url-sslprofile	Transaction, routing	Write-only
schemalocation	var://wsm/schemalocation	Transaction, WSM	Read-only
service	var://wsm/service	Transaction, WSM	Read-only

Table 31. All available variables (continued)

Short variable name	Full variable name	Category	Permission
service-port	var://wsm/service-port	Transaction, WSM	Read-only
service-port-operation	var://wsm/service-port-operation	Transaction, WSM	Read-only
set-request-header	var://service/set-request-header	Transaction, headers	Write-only
set-response-header	var://service/set-response-header	Transaction, headers	Write-only
skip-backside	var://service/mpgw/skip-backside	Service, general	Write-only
soap-fault-response	var://service/soap-fault-response	Service, general	Read-write
soap-oneway-mep	var://service/soap-oneway-mep	Transaction, asynchronous	Read-write
soapversion	var://service/log/soapversion	Service, multistep	Read-write
sslprofile	var://local/_extension/sslprofile	Extension	Write-only
status/	var://service/system/status/status-enumeration	Service, general	Read-only
strict-error-mode	var://service/strict-error-mode	Transaction, error handling	Read-write
strict-fault-document-style	var://wsm/strict-fault-document-style	Transaction, WSM	Read-only
time-elapsed	var://service/time-elapsed	Transaction, statistics	Read-only
time-forwarded	var://service/time-forwarded	Transaction, statistics	Read-only
time-response-complete	var://service/time-response-complete	Transaction, statistics	Read-only
time-started	var://service/time-started	Transaction, statistics	Read-only
timeout	var://service/wsa/timeout	Transaction, WSM	Read-write
transaction-audit-trail	var://service/transaction-audit-trail	Transaction, information	Read-only
transaction-client	var://service/transaction-client	Transaction, information	Read-only
transaction-id	var://service/transaction-id	Transaction, information	Read-only
transaction-key	var://service/transaction-key	Transaction, asynchronous	Write-only
transaction-name	var://service/transaction-name	Transaction, asynchronous	Write-only
transaction-policy-name	var://service/transaction-policy-name	Transaction, information	Read-only
transaction-rule-name	var://service/transaction-rule-name	Transaction, information	Read-only
transaction-rule-type	var://service/transaction-rule-type	Transaction, information	Read-only

Table 31. All available variables (continued)

Short variable name	Full variable name	Category	Permission
transaction-timeout	var://service/transaction-timeout	Transaction, asynchronous	Write-only
URI	var://service/URI	Transaction, URL	Read-write
URL-in	var://service/URL-in	Transaction, URL	Read-only
URL-out	var://service/URL-out	Transaction, URL	Read-only
user-identifier	var://service/user-identifier	Service, MQ	Read-only
validate-faults	var://service/wsm/validate-faults	Transaction, WSM	Read-only
validate-headers	var://service/wsm/validate-headers	Transaction, WSM	Read-only
validate-message	var://service/wsm/validate-message	Transaction, WSM	Read-only
variables	var://local/_extension/variables	Extension	Read-only
wsdl	var://service/wsm/wsdl	Transaction, WSM	Read-only
wsdl-error	var://service/wsm/wsdl-error	Transaction, WSM	Write-only
wsdl-warning	var://service/wsm/wsdl-warning	Transaction, WSM	Write-only
xmlmgr-name	var://service/xmlmgr-name	Service, configuration	Read-only

Appendix B. Getting help and technical assistance

This section describes the following options for obtaining support for IBM products:

- “Searching knowledge bases”
- “Getting a fix”
- “Contacting IBM Support” on page 220

Searching knowledge bases

If you encounter a problem, you want it resolved quickly. You can search the available knowledge bases to determine whether the resolution to your problem was already encountered and is already documented.

Documentation

The IBM WebSphere DataPower documentation library provides extensive documentation in Portable Document Format (PDF). You can use the search function of Adobe® Acrobat to query information. If you download and store the documents in a single location, you can use the search facility to find all references across the documentation set.

IBM Support

If you cannot find an answer in the documentation, use the *Search Support* feature from the product-specific support page.

From the **Search Support (this product)** area of the product-specific support page, you can search the following IBM resources:

- IBM technote database
- IBM downloads
- IBM Redbooks®
- IBM developerWorks®

Getting a fix

A product fix might be available to resolve your problem. To determine what fixes are available for your IBM product, check the product support site by performing the following steps:

1. Go to the IBM Support site at the following Web address:

<http://www.ibm.com/support>

2. Select **Support & Downloads** → **Download** to open the Support & downloads page.
3. From the **Category** list, select **WebSphere**.
4. From the **Sub-Category** list, select **WebSphere DataPower SOA Appliances**.
5. Click the **GO** icon to display the list of most recent updates.
6. Click the link for the firmware and documentation download that is specific to your WebSphere DataPower product.
7. Follow the instructions in the technote to download the fix.

Contacting IBM Support

IBM Support provides assistance with product defects. Before contacting IBM Support, the following criteria must be met:

- Your company has an active maintenance contract.
- You are authorized to submit problems.

To contact IBM Support with a problem, use the following procedure:

1. Define the problem, gather background information, and determine the severity of the problem. For help, refer to the *Software Support Handbook*. To access the online version of this handbook, use the following procedure:
 - a. Access the IBM Software Support Web page at the following Web address:

<http://www.ibm.com/software/support>

- b. Scroll down to the **Additional support links** section of the page.
- c. Under **Support tools**, click the **Software Support Handbook** link.
- d. Bookmark this page for future reference.

From this page, you can obtain a PDF copy of the handbook.

2. Gather diagnostic information.
 - a. Access the product support at the following Web address:

<http://www.ibm.com/software/integration/datapower/support>

- b. Locate the **Assistance** area of the product support page.
- c. Click **Information to include** to access that technote that lists the information that is required to report a problem.

3. Submit the problem in one of the following ways:

Online

From the IBM Support Web site (<http://www.ibm.com/support>), select **Support & Downloads** → **Open a service request**. Following the instructions.

By phone

For the phone number to call in your country, refer to “Contacts” in the *Software Support Handbook*. From the Software Support Handbook Web site, click **Contacts**. In the U.S. and Canada, call 1-800-IBM-SERV (1-800-426-7378) and select option 2 for software.

If the problem you should submit is for a software defect or for missing or inaccurate documentation, IBM Support creates an authorized program analysis report (APAR). The APAR describes the problem in detail. Whenever possible, IBM Support provides a workaround that you can implement until the APAR is resolved and a fix is delivered.

Notices and trademarks

This information was developed for products and services offered in the U.S.A.

IBM may not offer the products, services, or features discussed in this document in other countries. Consult your local IBM representative for information about the products and services currently available in your area. Any reference to an IBM product, program, or service is not intended to state or imply that only that IBM product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe any IBM intellectual property right may be used instead. However, it is the user's responsibility to evaluate and verify the operation of any non-IBM product, program, or service.

IBM may have patents or pending patent applications covering subject matter described in this document. The furnishing of this document does not grant you any license to these patents. You can send license inquiries, in writing, to:

IBM Director of Licensing
IBM Corporation
North Castle Drive
Armonk, NY 10504-1785
U.S.A.

The following paragraph does not apply to the United Kingdom or any other country where such provisions are inconsistent with local law: INTERNATIONAL BUSINESS MACHINES CORPORATION PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some states do not allow disclaimer of express or implied warranties in certain transactions, therefore, this statement may not apply to you.

This information could include technical inaccuracies or typographical errors. Changes are periodically made to the information herein; these changes will be incorporated in new editions of the publication. IBM may make improvements or changes in the product(s) or the program(s) described in this publication at any time without notice.

Trademarks

IBM, the IBM logo, developerWorks, DB2, DataPower, IMS, RACE, Redbooks, Tivoli, WebSphere, and z/OS are registered trademarks of the International Business Machines Corporation in the United States or other countries.

Adobe, the Adobe logo, PostScript, and the PostScript logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States, and/or other countries.

Microsoft and Windows are trademarks of Microsoft Corporation in the United States, other countries, or both.

Java and all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the United States and other countries.

Other company, product, and service names may be trademarks or service marks of others.

Index

Numerics

3DES
 decrypting key 159
 encrypting key 170

A

AAA Policy
 establishing security context 95
 generating key material 93
 obtaining context 94
 setting context 96
aaa-derive-context-key extension
 function 93
aaa-get-context-info extension
 function 94
aaa-new-security-context extension
 function 95
aaa-set-context-info extension
 function 96
abs()
 EXSLT extension function 185
accept extension element 1
accepting extension function 61
acos()
 EXSLT extension function 185
add-duration()
 EXSLT extension function 181
add()
 EXSLT extension function 181
align()
 EXSLT extension function 188
append-request-header extension
 element 2
append-response-header extension
 element 2
asin()
 EXSLT extension function 185
asynchronous transaction variables
 service/transaction-timeout 202
asynchronous transactions variables
 listing 202
 service/transaction-key 202
 service/transaction-name 202
asynchronous variables
 service/soap-oneway-mep 202
atan()
 EXSLT extension function 185
atan2()
 EXSLT extension function 185
attachment
 decrypting 107
 encrypting 112
attachments
 computing SHA-1 hash 101
auth-info extension function 97
authentication
 Kerberos 133
 LDAP 136
 obtaining information 97

B

backend-timeout variable 197
Base64 strings
 calculating SHA-1 hash 134
 compressing 111
 decompressing 135
 deflating 111
 inflating 135
base64-cert extension function 99
binary-decode extension function 62
binary-encode extension function 62
bold typeface xi

C

c14n
 See canonicalization
c14n-hash extension function 100
c14n-hash-attachment extension
 function 101
c14n-hash-set extension function 102
CA
 issuer
 extracting from X.509
 certificate 124
canonicalization
 node set 103
canonicalization, exclusive XML
 computing SHA-1 hash
 for node sets 118
 node sets
 computing deep SHA-1 hash 117
canonicalization, XML
 computing SHA-1 hash
 for node sets 102
 node sets
 computing deep SHA-1 hash 100
 SOAP attachments
 computing SHA-1 hash 101
canonicalize extension element 3
canonicalize extension function 103
cert-from-issuer-serial extension
 function 105
certificate authority
 See CA
certificate details
 extracting from X.509 certificate 122
certificates
 OCSP
 validating 141, 145
 validating 160
X.509
 comparing extracted DN's 151
 extracting certificate details 122
 extracting issuing CA 124
 extracting serial number 126
 extracting subject information 129
 extracting Subject Key
 Identifier 127
 obtaining 99

certificates (*continued*)
 X.509 (*continued*)
 obtaining from appliance 105
 obtaining SHA-1 thumbprint 131
client-ip-addr extension function 63
client-ip-port extension function 63
client-issuer-dn extension function 63
client-subject-dn extension function 65
closure()
 EXSLT extension function 184
Common module
 EXSLT extension elements
 document 179
 EXSLT extension functions
 node-set() 180
 object-type() 180
concat-base64 extension function 106
concat()
 EXSLT extension function 188
configuration service variables
 listing 198
 service/back-attachment-format 198
 service/config-param/ 198
 service/default-stylesheet 198
 service/domain-name 198
 service/front-attachment-format 198
 service/max-call-depth 198
 service/processor-name 198
 service/processor-type 198
 service/xmlmgr-name 198
 system/frontwsdl 198
constant()
 EXSLT extension function 185
cos()
 EXSLT extension function 185
cryptographic extension functions
 aaa-derive-context-key 93
 aaa-get-context-info 94
 aaa-new-security-context 95
 aaa-set-context-info 96
 auth-info 97
 base64-cert 99
 c14n-hash 100
 c14n-hash-attachment 101
 c14n-hash-set 102
 canonicalize 103
 cert-from-issuer-serial 105
 concat-base64 106
 decrypt-attachment 107
 decrypt-data 108
 decrypt-key 109
 deflate 111
 encrypt-attachment 112
 encrypt-data 113
 encrypt-key 114
 encrypt-string 116
 exc-c14n-hash 117
 exc-c14n-hash-set 118
 generate-key 120
 generate-passticket 121
 get-cert-details 122

cryptographic extension functions
(continued)

- get-cert-issuer 124
- get-cert-serial 126
- get-cert-ski 127
- get-cert-subject 129
- get-cert-thumbprintsha1 131
- get-kerberos-apreq 133
- hash 134
- hash-base64 134
- inflate 135
- ldap-authn 136
- ldap-search 137
- ldap-simple-query 139
- ocsp-validate-certificate 141
- ocsp-validate-response 145
- parse-kerberos-apreq 148
- radix-convert 150
- random-bytes 150
- same-dn 151
- sign 152
- sign-hmac 154
- sign-hmac-set 156
- substring-base64 159
- unwrap-key 159
- validate-certificate 160
- verify 163
- verify-hmac 165
- verify-hmac-set 167
- wrap-key 170
- zosnss-authn 171
- zosnss-author 172
- zosnss-passticket-authn 173

customer support

- contacting 220
- obtaining fixes 219
- searching knowledge bases 219

D

data

- decrypting 108
- encrypting 113

date-format

- EXSLT extension element 180

date-time()

- EXSLT extension function 181

date:add-duration() EXSLT extension
function 181

date:add() EXSLT extension function 181

date:date-format EXSLT extension
element 180

date:date-time() EXSLT extension
function 181

date:date() EXSLT extension
function 181

date:day-abbreviation() EXSLT extension
function 181

date:day-in-month() EXSLT extension
function 181

date:day-in-week() EXSLT extension
function 181

date:day-in-year() EXSLT extension
function 182

date:day-name() EXSLT extension
function 182

date:day-of-week-in-month() EXSLT
extension function 182

date:difference() EXSLT extension
function 182

date:duration() EXSLT extension
function 182

date:format-date() EXSLT extension
function 180

date:hour-in-day() EXSLT extension
function 182

date:leap-year() EXSLT extension
function 182

date:minute-in-hour() EXSLT extension
function 182

date:month-abbreviation() EXSLT
extension function 183

date:month-in-year() EXSLT extension
function 183

date:month-name() EXSLT extension
function 183

date:parse-date() EXSLT extension
function 180

date:second-in-minute() EXSLT extension
function 183

date:seconds() EXSLT extension
function 183

date:sum() EXSLT extension
function 183

date:time() EXSLT extension
function 183

date:week-in-month() EXSLT extension
function 183

date:week-in-year() EXSLT extension
function 183

date:year() EXSLT extension
function 184

date()

- EXSLT extension function 181

Dates and Times module

- EXSLT extension elements

- date-format 180

- EXSLT extension functions

- add-duration() 181

- add() 181

- date-time() 181

- date() 181

- day-abbreviation() 181

- day-in-month() 181

- day-in-week() 181

- day-in-year() 182

- day-name() 182

- day-of-week-in-month() 182

- difference() 182

- duration() 182

- format-date() 180

- hour-in-day() 182

- leap-year() 182

- minute-in-hour() 182

- month-abbreviation() 183

- month-in-year() 183

- month-name() 183

- parse-date() 180

- second-in-minute() 183

- seconds() 183

- sum() 183

- time() 183

- week-in-month() 183

Dates and Times module (continued)

- EXSLT extension functions (continued)

- week-in-year() 183

- year() 184

day-abbreviation()

- EXSLT extension function 181

day-in-month()

- EXSLT extension function 181

day-in-week()

- EXSLT extension function 181

day-in-year()

- EXSLT extension function 182

day-name()

- EXSLT extension function 182

day-of-week-in-month()

- EXSLT extension function 182

decimal numeric conversions 150

decimal XSLT constructor 175

decode extension function 68

decode-uri()

- EXSLT extension function 188

decrypt-attachment extension

- function 107

decrypt-data extension function 108

decrypt-key extension function 109

deflate extension function 111

difference()

- EXSLT extension function 182, 187

distinct()

- EXSLT extension function 187

distinguished names

- See DN

DN

- comparing 151

- querying LDAP 139

document

- EXSLT extension element 179

documentation conventions, typefaces xi

dp:escaping XSLT attribute 176

dp:expand-empty-elements XSLT
attribute 176

dp:ignore-multiple XSLT attribute

- xsl:import 175

- xsl:include 176

dp:priority XSLT attribute

- xsl:message 176

dp:type XSLT attribute

- xsl:message 176

dump-nodes extension element 5

duration()

- EXSLT extension function 182

dyn:closure() EXSLT extension

- function 184

dyn:evaluate() EXSLT extension

- function 184

dyn:map() EXSLT extension

- function 184

dyn:max() EXSLT extension function 184

dyn:min() EXSLT extension function 184

dyn:sum() EXSLT extension function 184

Dynamic module

- EXSLT extension functions

- closure() 184

- evaluate() 184

- map() 184

- max() 184

- min() 184

Dynamic module (*continued*)
EXSLT extension functions (*continued*)
 sum() 184

E

EMS URLs 53
encode extension function 68
encode-uri()
 EXSLT extension function 189
encrypt-attachment extension
 function 112
encrypt-data extension function 113
encrypt-key extension function 114
encrypt-string extension function 116
ephemeral keys
 decrypting 109
 encrypting 114
 generating 120
error handling variables
 listing 203
 service/error-code 203
 service/error-headers 203
 service/error-ignore 203
 service/error-message 204
 service/error-protocol-reason-
 phrase 203
 service/error-protocol-response 203
 service/error-subcode 204
 service/formatted-error-message 203
 service/strict-error-mode 204
escaping XSLT attribute 176
evaluate()
 EXSLT extension function 184
exc-c14n-hash extension function 117
exc-c14n-hash-set extension function 118
exclusive XML canonicalization
 See canonicalization, exclusive XML
exp()
 EXSLT extension function 185
expand-empty-elements XSLT
 attribute 176
EXSLT
 unsupported extension elements
 date:date-format 180
 exslt:document 179
 func:script 184
 unsupported extension functions
 date:format-date() 180
 date:parse-date() 180
 dyn:closure() 184
 dyn:map() 184
 dyn:max() 184
 dyn:min() 184
 dyn:sum() 184
 math:abs() 185
 math:acos() 185
 math:asin() 185
 math:atan() 185
 math:atan2() 185
 math:constant() 185
 math:cos() 185
 math:exp() 185
 math:highest() 185
 math:log() 185
 math:lowest() 185
 math:power() 185

EXSLT (*continued*)
 unsupported extension functions
 (*continued*)
 math:random() 185
 math:sin() 185
 math:sqrt() 185
 math:tan() 185
 random:random-sequence() 186
 str:align() 188
 str:replace() 188
EXSLT extension elements
 Common module
 document 179
 date:date-format 180
 Dates and Times module
 date-format 180
 exslt:document 179
 func:function 184
 func:result 185
 func:script 184
 Functions module
 function 184
 result 185
 script 184
EXSLT extension functions
 Common module
 node-set() 180
 object-type() 180
 date:add-duration() 181
 date:add() 181
 date:date-time() 181
 date:date() 181
 date:day-abbreviation() 181
 date:day-in-month() 181
 date:day-in-week() 181
 date:day-in-year() 182
 date:day-name() 182
 date:day-of-week-in-month() 182
 date:difference() 182
 date:duration() 182
 date:format-date() 180
 date:hour-in-day() 182
 date:leap-year() 182
 date:minute-in-hour() 182
 date:month-abbreviation() 183
 date:month-in-year() 183
 date:month-name() 183
 date:parse-date() 180
 date:second-in-minute() 183
 date:seconds() 183
 date:sum() 183
 date:time() 183
 date:week-in-month() 183
 date:week-in-year() 183
 date:year() 184
 Dates and Times module
 add-duration() 181
 add() 181
 date-time() 181
 date() 181
 day-abbreviation() 181
 day-in-month() 181
 day-in-week() 181
 day-in-year() 182
 day-name() 182
 day-of-week-in-month() 182
 difference() 182

EXSLT extension functions (*continued*)
 Dates and Times module (*continued*)
 duration() 182
 format-date() 180
 hour-in-day() 182
 leap-year() 182
 minute-in-hour() 182
 month-abbreviation() 183
 month-in-year() 183
 month-name() 183
 parse-date() 180
 second-in-minute() 183
 seconds() 183
 sum() 183
 time() 183
 week-in-month() 183
 week-in-year() 183
 year() 184
 dyn:closure() 184
 dyn:evaluate() 184
 dyn:map() 184
 dyn:max() 184
 dyn:min() 184
 dyn:sum() 184
 Dynamic module
 closure() 184
 evaluate() 184
 map() 184
 max() 184
 min() 184
 sum() 184
 exslt:node-set() 180
 exslt:object-type() 180
 Math module
 abs() 185
 acos() 185
 asin() 185
 atan() 185
 atan2() 185
 cos() 185
 exp() 185
 highest() 185
 log() 185
 lowest() 185
 max() 185
 min() 186
 power() 185
 random() 185
 sin() 185
 sqrt() 185
 tan() 185
 math:abs() 185
 math:acos() 185
 math:asin() 185
 math:atan() 185
 math:atan2() 185
 math:constant() 185
 math:cos() 185
 math:exp() 185
 math:highest() 185
 math:log() 185
 math:lowest() 185
 math:max() 185
 math:min() 186
 math:power() 185
 math:random-sequence() 186
 math:random() 185

EXSLT extension functions *(continued)*

- math:sin() 185
- math:sqrt() 185
- math:tan() 185
- Random module
 - random-sequence() 186
- regexp:match() 186
- regexp:replace() 186
- regexp:test() 186
- Regular Expressions module
 - match() 186
 - replace() 186
 - test() 186
- set:difference() 187
- set:distinct() 187
- set:has-same-node() 187
- set:intersection() 187
- set:leading() 187
- set:trailing() 188
- Sets module
 - difference() 187
 - distinct() 187
 - has-same-node() 187
 - intersection() 187
 - leading() 187
 - trailing() 188
- str:align() 188
- str:concat() 188
- str:decode-uri() 188
- str:encode-uri() 189
- str:padding() 190
- str:replace() 188
- str:split() 190
- str:tokenize() 190
- Strings module
 - align() 188
 - concat() 188
 - decode-uri() 188
 - encode-uri() 189
 - padding() 190
 - replace() 188
 - split() 190
 - tokenize() 190
- exslt:document 179
- exslt:document EXSLT extension
 - element 179
- exslt:node-set() EXSLT extension
 - function 180
- exslt:object-type() EXSLT extension
 - function 180
- extension elements
 - accept 1
 - append-request-header 2
 - append-response-header 2
 - canonicalize 3
 - dump-nodes 5
 - freeze-headers 5
 - increment-integer 6
 - param 191
 - parse 7
 - reject 8
 - remove-http-request-header 9
 - remove-http-response-header 9
 - remove-mime-header 10
 - send-error 10
 - serialize 11
 - set-http-request-header 12

extension elements *(continued)*

- set-http-response-header 13
- set-local-variable 14
- set-metadata 15
- set-mime-header 16
- set-request-header 16
- set-response-header 17
- set-target 18
- set-variable 20
- sql-execute 21
- strip-attachments 29
- url-open
 - FTP URLs 39
 - generic 30
 - ICAP URLs 41
 - IMS Connect URLs 42
 - MQ URLs 45
 - NFS URLs 48
 - SMTP URLs 49
 - SNMP URLs 50
 - SQL URLs 51
 - TCP URLs 52
 - TIBCO EMS URLs 53
 - WebSphere JMS URLs 55
- xreject 57
- xset-target 58
- extension function
 - metadata
 - accepting 61
 - binary-decode 62
 - binary-encode 62
 - client-ip-addr 63
 - client-ip-port 63
 - client-issuer-dn 63
 - client-subject-dn 65
 - decode 68
 - encode 68
 - generate-uuid 70
 - get-metadata 71
 - http-request-header 72
 - http-request-method 72
 - http-response-header 73
 - http-url 74
 - index-of 74
 - last-index-of 75
 - local-variable 75
 - mime-header 76
 - original-http-url 78
 - original-url 79
 - parse 79
 - request-header 80
 - responding 81
 - response-header 81
 - schema-validate 82
 - soap-call 83
 - sql-execute 85
 - substring-base64 86
 - time-value 86
 - transform 86
 - url 87
 - variable 88
- extension functions
 - cryptographic
 - aaa-derive-context-key 93
 - aaa-get-context-info 94
 - aaa-new-security-context 95
 - aaa-set-context-info 96

extension functions *(continued)*

- cryptographic *(continued)*
 - auth-info 97
 - base64-cert 99
 - c14n-hash 100
 - c14n-hash-attachment 101
 - c14n-hash-set 102
 - canonicalize 103
 - cert-from-issuer-serial 105
 - concat-base64 106
 - decrypt-attachment 107
 - decrypt-data 108
 - decrypt-key 109
 - deflate 111
 - encrypt-attachment 112
 - encrypt-data 113
 - encrypt-key 114
 - encrypt-string 116
 - exc-c14n-hash 117
 - exc-c14n-hash-set 118
 - generate-key 120
 - generate-passticket 121
 - get-cert-details 122
 - get-cert-issuer 124
 - get-cert-serial 126
 - get-cert-ski 127
 - get-cert-subject 129
 - get-cert-thumbprintsha1 131
 - get-kerberos-apreq 133
 - hash 134
 - hash-base64 134
 - inflate 135
 - ldap-authen 136
 - ldap-search 137
 - ldap-simple-query 139
 - ocsp-validate-certificate 141
 - ocsp-validate-response 145
 - parse-kerberos-apreq 148
 - radix-convert 150
 - random-bytes 150
 - same-dn 151
 - sign 152
 - sign-hmac 154
 - sign-hmac-set 156
 - substring-base64 159
 - unwrap-key 159
 - validate-certificate 160
 - verify 163
 - verify-hmac 165
 - verify-hmac-set 167
 - wrap-key 170
 - zosnss-authen 171
 - zosnss-author 172
 - zosnss-passticket-authen 173
- metadata
 - exter-correlator 69
 - mq-queue-depth 77
 - wsm-agent-append 89
- extension variables
 - listing 210
 - local/_extension/allow-compression 211
 - local/_extension/attachment-format 210
 - local/_extension/attachment-manifest 210

- extension variables (*continued*)
 - local/_extension/attachment-root-uri 210
 - local/_extension/donot-follow-redirect 211
 - local/_extension/error 210
 - local/_extension/header/ 211
 - local/_extension/http-10-only 211
 - local/_extension/messages 210
 - local/_extension/prevent-persistent-connection 211
 - local/_extension/response-header/ 210
 - local/_extension/response-headers 210
 - local/_extension/responsetcode 211
 - local/_extension/sslprofile 211
 - local/_extension/timeout 212
 - local/_extension/variables 211
- exter-correlator
 - metadata extension function 69

F

- Firewall Credentials
 - generating HMAC signatures 156
 - verifying HMAC signatures 167
- fixes, obtaining 219
- format-date()
 - EXSLT extension function 180
- freeze-headers extension element 5
- FTP URLs 39
- func:function EXSLT extension element 184
- func:result EXSLT extension element 185
- func:script 184
- func:script EXSLT extension element 184
- function
 - EXSLT extension element 184
- Functions module
 - EXSLT extension elements
 - function 184
 - result 185
 - script 184

G

- general variables
 - ident 196
 - listing 196
 - service/soap-fault-response 197
 - status/ 196
- generate-key extension function 120
- generate-passticket
 - cryptographic extension function 121
- generate-uuid extension function 70
- get-cert-details extension function 122
- get-cert-issuer extension function 124
- get-cert-serial extension function 126
- get-cert-ski extension function 127
- get-cert-subject extension function 129
- get-cert-thumbprintsha1 extension function 131
- get-kerberos-apreq extension function 133
- get-metadata extension function 71

H

- has-same-node()
 - EXSLT extension function 187
- hash extension function 134
- hash-base64 extension function 134
- hexadecimal numeric conversions 150
- highest()
 - EXSLT extension function 185
- HMAC
 - generating signatures 154, 156
 - verifying signatures 165, 167
- hour-in-day()
 - EXSLT extension function 182
- http-request-header extension function 72
- http-request-method extension function 72
- http-response-header extension function 73
- http-url extension function 74

I

- ICAP URLs 41
- ident variable 196
- ignore-multiple XSLT attribute
 - xsl:import 175
 - xsl:include 176
- import
 - XSLT extension function 175
- IMS Connect URLs 42
- include
 - XSLT extension function 176
- increment-integer extension element 6
- index-of extension function 74
- inflate extension function 135
- intellectual property 221
- intersection()
 - EXSLT extension function 187
- issuing CA
 - extracting from X.509 certificate 124
- italics typeface xi

J

- JMS URLs 55

K

- Kerberos
 - AP-REQ
 - obtaining 133
 - parsing 148
- keys
 - decrypting 109
 - encrypting 114
 - generating 120
- knowledge bases
 - searching 219

L

- last-index-of extension function 75
- LDAP
 - authentication 136

- LDAP (*continued*)

- searching 137
 - simple query 139
- ldap-authen extension function 136
- ldap-search extension function 137
- ldap-simple-query extension function 139
- leading()
 - EXSLT extension function 187
- leap-year()
 - EXSLT extension function 182
- licensing
 - sending inquiries 221
- load balancer service variables
 - listing 199
 - service/lb/group 199
 - service/lb/member 199
 - service/lbhealth/ 199
- local-variable extension function 75
- local/_extension/allow-compression variable 211
- local/_extension/attachment-format variable 210
- local/_extension/attachment-manifest variable 210
- local/_extension/attachment-root-uri variable 210
- local/_extension/donot-follow-redirect variable 211
- local/_extension/error variable 210
- local/_extension/header/ variable 211
- local/_extension/http-10-only variable 211
- local/_extension/messages variable 210
- local/_extension/prevent-persistent-connection variable 211
- local/_extension/response-header/ variable 210
- local/_extension/response-headers variable 210
- local/_extension/responsetcode variable 211
- local/_extension/sslprofile variable 211
- local/_extension/timeout variable 212
- local/_extension/variables variable 211
- log/soapversion variable 201
- log()
 - EXSLT extension function 185
- lowest()
 - EXSLT extension function 185

M

- map()
 - EXSLT extension function 184
- match()
 - EXSLT extension function 186
- Math module
 - EXSLT extension functions
 - abs() 185
 - acos() 185
 - asin() 185
 - atan() 185
 - atan2() 185
 - constant() 185
 - cos() 185
 - exp() 185

Math module (continued)

EXSLT extension functions (continued)

- highest() 185
- log() 185
- lowest() 185
- max() 185
- min() 186
- power() 185
- random() 185
- sin() 185
- sqrt() 185
- tan() 185
- math:abs() EXSLT extension function 185
- math:acos() EXSLT extension function 185
- math:asin() EXSLT extension function 185
- math:atan() EXSLT extension function 185
- math:atan2() EXSLT extension function 185
- math:constant() EXSLT extension function 185
- math:cos() EXSLT extension function 185
- math:exp() EXSLT extension function 185
- math:highest() EXSLT extension function 185
- math:log() EXSLT extension function 185
- math:lowest() EXSLT extension function 185
- math:max() EXSLT extension function 185
- math:min() EXSLT extension function 186
- math:power() EXSLT extension function 185
- math:random() EXSLT extension function 185
- math:sin() EXSLT extension function 185
- math:sqrt() EXSLT extension function 185
- math:tan() EXSLT extension function 185
- max() EXSLT extension function 184, 185
- message XSLT extension function 176
- metadata extension functions
 - accepting 61
 - binary-decode 62
 - binary-encode 62
 - client-ip-addr 63
 - client-ip-port 63
 - client-issuer-dn 63
 - client-subject-dn 65
 - decode 68
 - encode 68
 - exter-correlator 69
 - generate-uuid 70
 - get-metadata 71
 - http-request-header 72
 - http-request-method 72
 - http-response-header 73
 - http-url 74
 - index-of 74
 - last-index-of 75

metadata extension functions (continued)

- local-variable 75
- mime-header 76
- mq-queue-depth 77
- original-http-url 78
- original-url 79
- parse 79
- request-header 80
- responding 81
- response-header 81
- schema-validate 82
- soap-call 83
- sql-execute 85
- substring-base64 86
- time-value 86
- transform 86
- url 87
- variable 88
- wsm-agent-append 89
- mime-header extension function 76
- min() EXSLT extension function 184, 186
- minute-in-hour() EXSLT extension function 182
- monospaced typeface xi
- month-abbreviation() EXSLT extension function 183
- month-in-year() EXSLT extension function 183
- month-name() EXSLT extension function 183
- MQ functions
 - mq-queue-depth 77
- MQ services variables
 - listing 199
 - service/accounting-token 200
 - service/backout-count 200
 - service/correlation-identifier 200
 - service/expiry 200
 - service/format 200
 - service/message-identifier 200
 - service/message-type 200
 - service/mq-ccsi 200
 - service/mq-error-code 200
 - service/mqmd-reply-to-q 200
 - service/mqmd-reply-to-qm 200
 - service/original-length 200
 - service/persistence 200
 - service/priority 201
 - service/put-date 200
 - service/put-time 200
 - service/reply-to-q 201
 - service/reply-to-qm 201
 - service/report 201
 - service/user-identifier 200
- MQ URLs 45
- mq-queue-depth metadata extension function 77
- Multi-Protocol Gateway
 - service variables
 - backend-timeout 197
 - request-size 197
 - response-size 197
 - skip-backside 197
- multistep variables
 - log/soapversion 201
 - multistep/contexts 201

multistep variables (continued)

- multistep/loop-count 201
- multistep/loop-iterator 201
- multistep/contexts variable 201
- multistep/loop-count variable 201
- multistep/loop-iterator variable 201

N

- NFS URLs 48
- node-set() EXSLT extension function 180
- nonce
 - generating 150
- notices 221
- numeric conversions 150

O

- object-type() EXSLT extension function 180
- OCSP responses
 - processing 141, 145
 - validating 141, 145
- ocsp-validate-certificate extension function 141
- ocsp-validate-response extension function 145
- Online Certificate Status Protocol
 - See OCSP
- original-http-url extension function 78
- original-url extension function 79
- output XSLT extension function 176

P

- padding() EXSLT extension function 190
- param extension element 191
- parse extension element 7
- parse extension function 79
- parse-date() EXSLT extension function 180
- parse-kerberos-apreq extension function 148
- patents 221
- persistent connections variables
 - listing 206
 - service/connection/note 206
 - service/persistent-connection-counter 206
- power() EXSLT extension function 185
- priority XSLT attribute
 - xsl:message 176

R

- radix numeric conversions 150
- radix-convert extension function 150
- Random module
 - EXSLT extension functions
 - random-sequence() 186
- random-bytes extension function 150

- random-sequence()
 - EXSLT extension function 186
- random:random-sequence() 186
- random:random-sequence() EXSLT extension function 186
- random()
 - EXSLT extension function 185
- regexp:match() EXSLT extension function 186
- regexp:replace() EXSLT extension function 186
- regexp:test() EXSLT extension function 186
- Regular Expressions module
 - EXSLT extension functions
 - match() 186
 - replace() 186
 - test() 186
- reject extension element 8
- remove-http-request-header extension element 9
- remove-http-response-header extension element 9
- remove-mime-header element 10
- replace()
 - EXSLT extension function 186, 188
- request-header extension function 80
- request-size variable 197
- requests
 - Kerberos
 - obtaining 133
 - parsing 148
 - LDAP authentication 136
- responding extension function 81
- response-header extension function 81
- response-size variable 197
- responses
 - OCSP
 - processing 141, 145
 - validating 141, 145
- result
 - EXSLT extension element 185

S

- same-dn extension function 151
- schema-validate extension function 82
- script
 - EXSLT extension element 184
- second-in-minute()
 - EXSLT extension function 183
- seconds()
 - EXSLT extension function 183
- security context
 - AAA Policy
 - establishing 95
- Security Context
 - AAA Policy
 - generating key 93
 - obtaining 94
 - setting 96
- send-error extension element 10
- serial number
 - extracting from X.509 certificate 126
- serialize extension element 11
- service variables
 - listing 196

- service variables (*continued*)
 - types 196
- service/accounting-token variable 200
- service/append-request-header/ variable 204
- service/append-response-header/ variable 204
- service/back-attachment-format variable 198
- service/backout-count variable 200
- service/client-service-address variable 208
- service/config-param/ variable 198
- service/connection/note variable 206
- service/correlation-identifier variable 200
- service/current-call-depth variable 205
- service/default-stylesheet variable 198
- service/domain-name variable 198
- service/error-code variable 203
- service/error-headers variable 203
- service/error-ignore variable 203
- service/error-message variable 204
- service/error-protocol-reason-phrase variable 203
- service/error-protocol-response variable 203
- service/error-subcode variable 204
- service/expiry variable 200
- service/format variable 200
- service/formatted-error-message variable 203
- service/front-attachment-format variable 198
- service/header-manifest variable 204
- service/input-size variable 205
- service/lb/group variable 199
- service/lb/member variable 199
- service/lbhealth/ variable 199
- service/local-service-address variable 208
- service/max-call-depth variable 198
- service/message-identifier variable 200
- service/message-type variable 200
- service/mq-ccsi variable 200
- service/mq-error-code variable 200
- service/mqmd-reply-to-q variable 200
- service/mqmd-reply-to-qm variable 200
- service/original-length variable 200
- service/persistence variable 200
- service/persistent-connection-counter variable 206
- service/priority variable 201
- service/processor-name variable 198
- service/processor-type variable 198
- service/protocol variable 208
- service/put-date variable 200
- service/put-time variable 200
- service/reply-to-q variable 201
- service/reply-to-qm variable 201
- service/report variable 201
- service/routing-url variable 206
- service/routing-url-sslprofile variable 207
- service/set-request-header/ variable 204
- service/set-response-header/ variable 205

- service/soap-fault-response variable 197
- service/soap-oneway-mep variable 202
- service/strict-error-mode variable 204
- service/time-elapsed variable 207
- service/time-forwarded variable 207
- service/time-response-complete variable 207
- service/time-started variable 207
- service/transaction-audit-trail 205
- service/transaction-client variable 205
- service/transaction-key variable 202
- service/transaction-name variable 202
- service/transaction-policy-name variable 205
- service/transaction-rule-name variable 205
- service/transaction-rule-type variable 205
- service/transaction-timeout variable 202
- service/URI variable 208
- service/URI-in variable 208
- service/URI-out variable 208
- service/user-identifier variable 200
- service/wsa/genpattern variable 209
- service/wsa/timeout variable 209
- service/wsm/aaa-policy-name variable 209
- service/wsm/binding variable 209
- service/wsm/enabled variable 209
- service/wsm/validate-faults variable 209
- service/wsm/validate-headers variable 209
- service/wsm/validate-message variable 209
- service/wsm/wsdl variable 209
- service/wsm/wsdl-error variable 209
- service/wsm/wsdl-warning variable 209
- service/xmlmgr-name variable 198
- session keys
 - decrypting 109
 - encrypting 114
 - generating 120
- set-http-request-header extension element 12
- set-http-response-header extension element 13
- set-local-variable extension element 14
- set-metadata extension element 15
- set-mime-header element 16
- set-request-header extension element 16
- set-response-header extension element 17
- set-target extension element 18
- set-variable extension element 20
- set:difference() EXSLT extension function 187
- set:distinct() EXSLT extension function 187
- set:has-same-node() EXSLT extension function 187
- set:intersection() EXSLT extension function 187
- set:leading() EXSLT extension function 187

- set:trailing() EXSLT extension function 188
- Sets module
 - EXSLT extension functions
 - difference() 187
 - distinct() 187
 - has-same-node() 187
 - intersection() 187
 - leading() 187
 - trailing() 188
- SHA-1
 - calculating hash
 - Base64 strings 134
 - text strings 134
 - exclusive XML canonicalization
 - computing for node sets 117
 - computing hash for node sets 118
 - from X.509 certificate 131
 - generating signatures 152
 - thumbprint 131
 - verifying signatures 163
 - XML canonicalization
 - computing hash for node sets 100, 102
 - computing hash for SOAP attachments 101
- sign extension function 152
- sign-hmac extension function 154
- sign-hmac-set extension function 156
- sin()
 - EXSLT extension function 185
- skip-backside variable 197
- SMTP URLs 49
- SNMP URLs 50
- SOAP attachments
 - computing SHA-1 hash 101
- soap-call extension function 83
- split()
 - EXSLT extension function 190
- SQL URLs 51
- sql-execute extension element 21
- sql-execute extension function 85
- sqrt()
 - EXSLT extension function 185
- statistics variables
 - listing 207
 - service/time-elapsed 207
 - service/time-forwarded 207
 - service/time-response-complete 207
 - service/time-started 207
- status/ variable 196
- str:align() EXSLT extension function 188
- str:concat() EXSLT extension function 188
- str:decode-uri() EXSLT extension function 188
- str:encode-uri() EXSLT extension function 189
- str:padding() EXSLT extension function 190
- str:replace() EXSLT extension function 188
- str:split() EXSLT extension function 190
- str:tokenize() EXSLT extension function 190

- strings
 - Base64
 - calculating SHA-1 hash 134
 - compressing 111
 - decompressing 135
 - deflating 111
 - inflating 135
 - text
 - calculating SHA-1 hash 134
 - concatenating to Base64 106
 - encrypting 116
- Strings module
 - EXSLT extension functions
 - align() 188
 - concat() 188
 - decode-uri() 188
 - encode-uri() 189
 - padding() 190
 - replace() 188
 - split() 190
 - tokenize() 190
- strip-attachments extension element 29
- subject information
 - extracting from X.509 certificates 129
- Subject Key Identifier
 - extracting from X.509 certificate 127
- substring-base64 extension function 86, 159
- sum()
 - EXSLT extension function 183, 184
- summary Web GUI extension element 192
- support
 - See customer support
- syntax, reading xi
- system variables
 - listing 212
 - system/map/debug 212
 - system/tasktemplates/debug 212
- system/frontwsdl variable 198
- system/map/debug variable 212
- system/tasktemplates/debug variable 212

T

- tan()
 - EXSLT extension function 185
- TCP URLs 52
- test()
 - EXSLT extension function 186
- text strings
 - calculating SHA-1 hash 134
 - concatenating to Base64 106
 - encrypting 116
- thumbprint
 - from X.509 certificate 131
- TIBCO EMS URLs 53
- time-value extension function 86
- time()
 - EXSLT extension function 183
- tokenize()
 - EXSLT extension function 190
- trademarks 221
- trailing()
 - EXSLT extension function 188

- transaction headers variables
 - listing 204
 - service/append-request-header/ 204
 - service/append-response-header/ 204
 - service/header-manifest 204
 - service/set-request-header/ 204
 - service/set-response-header/ 205
- transaction information variables
 - listing 205
 - service/current-call-depth 205
 - service/input-size 205
 - service/transaction-audit-trail 205
 - service/transaction-client 205
 - service/transaction-policy-name 205
 - service/transaction-rule-name 205
 - service/transaction-rule-type 205
- transaction routing variables
 - listing 206
 - service/routing-url 206
 - service/routing-url-sslprofile 207
- transaction URL variables
 - listing 207
 - service/client-service-address 208
 - service/local-service-address 208
 - service/protocol 208
 - service/URI 208
 - service/URI-in 208
 - service/URI-out 208
- transaction variables
 - listing 202
 - types 202
- transform extension function 86
- triple DES
 - See 3DES
- type XSLT attribute
 - xsl:message 176
- typeface conventions xi

U

- unsupported extension elements 179, 184
 - date:date-format 180
- unsupported extension functions 186
 - atan2() 185
 - date:format-date() 180
 - date:parse-date() 180
 - dyn:closure() 184
 - dyn:map() 184
 - dyn:max() 184
 - dyn:min() 184
 - dyn:sum() 184
 - math:abs() 185
 - math:acos() 185
 - math:asin() 185
 - math:atan() 185
 - math:constant() 185
 - math:cos() 185
 - math:exp() 185
 - math:highest() 185
 - math:log() 185
 - math:lowest() 185
 - math:power() 185
 - math:random() 185
 - math:sin() 185
 - math:sqrt() 185

- unsupported extension functions
 - (*continued*)
 - math:tan() 185
 - str:align() 188
 - str:replace() 188
- unwrap-key extension function 159
- url extension function 87
- url-open extension element
 - FTP URLs 39
 - generic 30
 - ICAP URLs 41
 - IMS Connect URLs 42
 - MQ URLs 45
 - NFS URLs 48
 - SMTP URLs 49
 - SNMP URLs 50
 - SQL URLs 51
 - TCP URLs 52
 - TIBCO EMS URLs 53
 - WebSphere JMS URLs 55

V

- validate-certificate extension
 - function 160
- variable extension function 88
- variables
 - asynchronous
 - service/soap-oneway-mep 202
 - asynchronous transactions
 - listing 202
 - service/transaction-key 202
 - service/transaction-name 202
 - service/transaction-timeout 202
 - configuration service
 - listing 198
 - service/back-attachment-format 198
 - service/config-param/ 198
 - service/default-stylesheet 198
 - service/domain-name 198
 - service/front-attachment-format 198
 - service/max-call-depth 198
 - service/processor-name 198
 - service/processor-type 198
 - service/xmlmgr-name 198
 - system/frontwsdl 198
 - error handling
 - listing 203
 - service/error-code 203
 - service/error-headers 203
 - service/error-ignore 203
 - service/error-message 204
 - service/error-protocol-reason-phrase 203
 - service/error-protocol-response 203
 - service/error-subcode 204
 - service/formatted-error-message 203
 - service/strict-error-mode 204
 - extension
 - listing 210
 - local/_extension/allow-compression 211

- variables (*continued*)
 - extension (*continued*)
 - local/_extension/attachment-format 210
 - local/_extension/attachment-manifest 210
 - local/_extension/attachment-root-uri 210
 - local/_extension/donot-follow-redirect 211
 - local/_extension/error 210
 - local/_extension/header/ 211
 - local/_extension/http-10-only 211
 - local/_extension/messages 210
 - local/_extension/prevent-persistent-connection 211
 - local/_extension/response-header/ 210
 - local/_extension/response-headers 210
 - local/_extension/responsecode 211
 - local/_extension/sslprofile 211
 - local/_extension/timeout 212
 - local/_extension/variables 211
 - general
 - ident 196
 - listing 196
 - service/soap-fault-response 197
 - status/ 196
 - list, all available 213
 - load balancer service
 - listing 199
 - service/lb/group 199
 - service/lb/member 199
 - service/lbhealth/ 199
 - MQ Services
 - listing 199
 - service/accounting-token 200
 - service/backout-count 200
 - service/correlation-identifier 200
 - service/expiry 200
 - service/format 200
 - service/message-identifier 200
 - service/message-type 200
 - service/mq-ccsi 200
 - service/mq-error-code 200
 - service/mqmd-reply-to-q 200
 - service/mqmd-reply-to-qm 200
 - service/original-length 200
 - service/persistence 200
 - service/priority 201
 - service/put-date 200
 - service/put-time 200
 - service/reply-to-q 201
 - service/reply-to-qm 201
 - service/report 201
 - service/user-identifier 200
 - Multi-Protocol Gateway
 - backend-timeout 197
 - request-size 197
 - response-size 197
 - skip-backside 197
 - multistep
 - log/soapversion 201
 - multistep/contexts 201
 - multistep/loop-count 201

- variables (*continued*)
 - multistep (*continued*)
 - multistep/loop-iterator 201
 - persistent connections
 - listing 206
 - service/connection/note 206
 - service/persistent-connection-counter 206
 - service
 - listing 196
 - type 196
 - statistics
 - listing 207
 - service/time-elapsed 207
 - service/time-forwarded 207
 - service/time-response-complete 207
 - service/time-started 207
 - system
 - listing 212
 - system/map/debug 212
 - system/tasktemplates/debug 212
 - transaction
 - listing 202
 - type 202
 - transaction headers
 - listing 204
 - service/append-request-header/ 204
 - service/append-response-header/ 204
 - service/header-manifest 204
 - service/set-request-header/ 204
 - service/set-response-header/ 205
 - transaction information
 - listing 205
 - service/current-call-depth 205
 - service/input-size 205
 - service/transaction-audit-trail 205
 - service/transaction-client 205
 - service/transaction-policy-name 205
 - service/transaction-rule-name 205
 - service/transaction-rule-type 205
 - transaction routing
 - listing 206
 - service/routing-url 206
 - service/routing-url-sslprofile 207
 - transaction URL
 - listing 207
 - service/client-service-address 208
 - service/local-service-address 208
 - service/protocol 208
 - service/URI 208
 - service/URI-in 208
 - service/URI-out 208
 - types 195
 - using 195
 - Web Service Proxy
 - backend-timeout 197
 - request-size 197
 - response-size 197
 - skip-backside 197
 - WSM
 - listing 208
 - service/wsa/genpattern 209
 - service/wsa/timeout 209

- variables (*continued*)
 - WSM (*continued*)
 - service/wsm/aaa-policy-name 209
 - service/wsm/binding 209
 - service/wsm/enabled 209
 - service/wsm/validate-faults 209
 - service/wsm/validate-headers 209
 - service/wsm/validate-message 209
 - service/wsm/wsdl 209
 - service/wsm/wsdl-error 209
 - service/wsm/wsdl-warning 209
 - wsm/num-subschema 209
 - wsm/operation 209
 - wsm/resolve-hrefs 209
 - wsm/schemalocation 209
 - wsm/service 209
 - wsm/service-port 209
 - wsm/service-port-operation 209
 - wsm/strict-fault-document-style 209
- verify extension function 163
- verify-hmac extension function 165
- verify-hmac-set extension function 167

W

- Web GUI extension elements
 - summary 192
- Web Service Proxy
 - service variables
 - backend-timeout 197
 - request-size 197
 - response-size 197
 - skip-backside 197
- WebSphere JMS URLs 55
- week-in-month()
 - EXSLT extension function 183
- week-in-year()
 - EXSLT extension function 183
- wrap-key extension function 170
- WSM variables
 - listing 208
 - service/wsa/genpattern 209
 - service/wsa/timeout 209
 - service/wsm/aaa-policy-name 209
 - service/wsm/binding 209
 - service/wsm/enabled 209
 - service/wsm/validate-faults 209
 - service/wsm/validate-headers 209
 - service/wsm/validate-message 209
 - service/wsm/wsdl 209
 - service/wsm/wsdl-error 209
 - service/wsm/wsdl-warning 209
 - wsm/num-subschema 209
 - wsm/operation 209
 - wsm/resolve-hrefs 209
 - wsm/schemalocation 209
 - wsm/service 209
 - wsm/service-port 209
 - wsm/service-port-operation 209
 - wsm/strict-fault-document-style 209
- wsm-agent-append
 - metadata extension function 89
- wsm/num-subschema variable 209

- wsm/operation variable 209
- wsm/resolve-hrefs variable 209
- wsm/schemalocation variable 209
- wsm/service variable 209
- wsm/service-port variable 209
- wsm/service-port-operation variable 209
- wsm/strict-fault-document-style variable 209

X

- X.509 certificates
 - comparing extracted DNs 151
 - extracting certificate details 122
 - extracting issuing CA 124
 - extracting serial number 126
 - extracting subject information 129
 - extracting Subject Key Identifier 127
 - obtaining 99
 - obtaining from appliance 105
 - obtaining SHA-1 thumbprint 131
- XML canonicalization
 - See* canonicalization, XML
- XPath
 - supported versions 175
- xreject extension element 57
- xs:decimal XSLT constructor 175
- xset-target extension element 58
- xsl:import XSLT extension function 175
- xsl:include XSLT extension function 176
- xsl:message XSLT extension function 176
- xsl:output XSLT extension function 176
- XSLT
 - supported versions 175
- XSLT attributes
 - dp:escaping 176
 - dp:expand-empty-elements 176
 - dp:ignore-multiple XSLT attribute
 - xsl:import 175
 - xsl:include 176
 - dp:priority XSLT attribute
 - xsl:message 176
 - dp:type XSLT attribute
 - xsl:message 176
- XSLT constructors
 - xs:decimal 175
- XSLT extension function
 - xsl:import 175
 - xsl:include 176
 - xsl:message 176
 - xsl:output 176

Y

- year()
 - EXSLT extension function 184

Z

- z/OS NSS functions
 - generate-passticket 121
 - zosnss-authen 171
 - zosnss-author 172
 - zosnss-passticket-authen 173

- zosnss-authen
 - cryptographic extension functions 171
- zosnss-author
 - cryptographic extension function 172
- zosnss-passticket-authen
 - cryptographic extension function 173



Printed in USA