



## What are the core AO/DI/DL modules in LN-3000 architecture

The LN-3000 architecture is part of the **LN Series distributed control system** family built around **LONWORKS® industrial networking** from Johnson Controls. It uses modular AO (Analog Output), DI (Digital Input), and DL (Data or Digital Link) subsystems to extend distributed intelligence and interoperability across automation or HVAC networks.

### Core Module Overview

The system's hardware architecture defines three key remote I/O module types that collectively form the AO, DI, and DL layers of control.

Module	Inputs	Outputs	Output Type	Key Function	Source
LN-IO301-1	8 universal inputs	8 digital outputs	Triac 1.0 A @ 24 VAC (PWM configurable)	Local control with mixed AO/DI handling; supports 12-bit D/A conversion	<a href="#">[1]</a>
LN-IO401-1	12 universal inputs	12 digital outputs	Triac 1.0 A @ 24 VAC (PWM adjustable)	Expanded version for process loops or large HVAC zones	<a href="#">[1]</a>
LN-IO520-1	16 universal inputs	0 outputs	N/A	Dedicated input module for data acquisition or control coordination	<a href="#">[1]</a>

All three share consistent power, logic, and communication specifications, enabling interchangeable AO/DI functionality across the network.

### AO (Analog Output) Module Functions

- **12-bit digital-to-analog conversion** ensures smooth control over actuators and analog valves.
- Outputs may be configured as PWM or digital triac channels with adjustable duty cycles from 2 s–15 min.
- Supports **load shedding**, **flow calibration**, and **PID control loop adjustments** through software on the LN-Builder interface.
- Each channel features **status indicators** and **fuse protection** for 24 VAC power lines.[\[1\]](#)

## DI (Digital Input) Module Functions

- Fully **software-configurable universal inputs** that support:
  - **Digital dry contacts** (for switch or sensor triggers).
  - **Analog 0–10 VDC** and **current 4–20 mA** sensors with parallel 249  $\Omega$  resistors.
  - **Resistive sensors** such as thermistors (Type 2, 3), **Pt100/Pt1000 RTDs**, or **potentiometers** for variable measurement.
- **16-bit A/D converter** provides fine-grain digital resolution for analog measurement inputs.<sup>[1]</sup>

## DL (Data Link) and Communication Layer

- Built upon **LONWORKS® (LonTalk® protocol)** with **TP/FT-10 twisted-pair channels** running at 78 kbps.
- **Peer-to-peer communication** allows modules (I/O, supervisory, or controllers) to operate without a central intermediary.
- Network variables follow **LONMARK® standard SNVTs**, ensuring interoperability between controllers.
- Managed via **LNS plug-ins** such as **LN-Builder** or **LN-Configure**, which allow configuration of I/O parameters, PID sequences, calibration, and fault responses.
- DL firmware runs on a **Neuron 3150 10 MHz processor** with **64 KB nonvolatile flash** for program and storage memory.<sup>[1]</sup>

## Physical and Environmental Design

- 24 VAC/DC  $\pm 15\%$  power supply (6–15 VA typical).
- ABS UL94-5VA fire-retardant enclosure with CE, FCC, and UL916 compliance.
- Operating range: 0–50 °C, 0–90% RH non-condensing; designed for field or panel mounting.<sup>[1]</sup>

## Architectural Summary

In the LN-3000 distributed control system:

- The **AO subsystem** manages analog actuation via configurable PWM/triac or voltage outputs.
- The **DI subsystem** aggregates universal sensor inputs (digital or analog) with real-time sampling and high resolution.
- The **DL subsystem** provides deterministic, peer-level communication over LONWORKS®, supporting decentralized decision logic and diagnostics.

Together these modules form a scalable, interoperable automation layer suitable for HVAC, process, and building management applications.<sup>[1]</sup>

1. [https://docs.johnsoncontrols.com/bas/api/khub/documents/PqKgF0\\_xN6VxPaf~70FAkw/content](https://docs.johnsoncontrols.com/bas/api/khub/documents/PqKgF0_xN6VxPaf~70FAkw/content)
2. <https://cdn.automationdirect.com/static/catalog/images/product-pdf/P3-Productivity3000-Tech-Specs.pdf>
3. <https://docs.johnsoncontrols.com/bas/api/khub/documents/f3pM173QRRZxVr68sQEwrQ/content>
4. [https://www.bau.edu.jo/UserPortal/UserProfile/PostsAttach/43038\\_4306\\_1.pdf](https://www.bau.edu.jo/UserPortal/UserProfile/PostsAttach/43038_4306_1.pdf)
5. [https://ingenico.com/sites/default/files/resource-document/2022-10/LANE-3000\\_datasheet\\_EN\\_OCT22.pdf](https://ingenico.com/sites/default/files/resource-document/2022-10/LANE-3000_datasheet_EN_OCT22.pdf)
6. [https://www.mitsubishielectric.com/dl/fa/document/manual/cnc/bnp-b2183\(eng\)/bnp-b2183\(eng\)k.pdf](https://www.mitsubishielectric.com/dl/fa/document/manual/cnc/bnp-b2183(eng)/bnp-b2183(eng)k.pdf)
7. [https://ingenico.com/sites/default/files/resource-document/2022-11/USA-CAN\\_DATASHEET\\_LANE\\_3000\\_ING\\_221020.pdf](https://ingenico.com/sites/default/files/resource-document/2022-11/USA-CAN_DATASHEET_LANE_3000_ING_221020.pdf)
8. <https://cdn.automationdirect.com/static/manuals/p3userm/ch2.pdf>
9. <https://www.sciencedirect.com/science/article/pii/S1383762124001802>
10. <https://datacapsystems.com/wp-content/uploads/datasheet-lane3000-jan21.pdf>
11. <https://www.empire-cat.com/equipment/attachments/generator-set-control-panels/control-panels/catr-ecs-100-control-panel>
12. <https://apps.dtic.mil/sti/tr/pdf/AD0758977.pdf>
13. <https://www.usmodernist.org/AJUK/AJUK-1960-07-28.pdf>
14. <https://www.scribd.com/doc/30512209/DCSARCHITECTURE-TDC3000>
15. <https://dspace.mit.edu/bitstream/handle/1721.1/149427/MIT-LCS-TR-123.pdf?sequence=1&isAllowed=y>
16. [https://eprints.soton.ac.uk/478926/1/Thesis\\_FINAL\\_with\\_amendments\\_and\\_pdfA.pdf](https://eprints.soton.ac.uk/478926/1/Thesis_FINAL_with_amendments_and_pdfA.pdf)
17. <https://research.tue.nl/files/4397790/445094.pdf>
18. <https://paya-trade.com/ln-control-system/ln3000-distributed-control-system/>
19. <https://www.youtube.com/watch?v=LzA9HOMiZPU>
20. <https://www.eaton.com/content/dam/eaton/products/electrical-circuit-protection/circuit-breakers/xpole-rccb/eaton-xpole-accessories-ca019015en-en-us.pdf>