

### Assignment 3

1. Navigate to <https://souravganguly.co.in/records-accolades/>

2. Write Xpath for below :

a. To get the runs scored in ODI using parent and starts-with text 'Runs'

⇒ `//td[text()='Runs scored']/parent::tr/child::td[@class='column-odi']`

⇒ `//th[text()='Runs']/ancestor::div//child::th[text()='ODI']/ancestor::thead/following-sibling::tbody/child::tr/td[text()='Runs scored']/following-sibling::td[@class='column-odi']`

→ Correct, if attribute value has spaces, we can use contains

b. Batting average in first class Cricket using following sibling and text 'Batting average'

⇒ `//tr/child::th[@class='wdthead sort sorting_disabled column-fc']/ancestor::thead/following-sibling::tbody/child::tr/td[text()='Batting average']/following-sibling::td[@class='column-fc']`

→ Correct

c. Wickets taken in ODI using preceding sibling and text 'Wickets'

⇒ `//th[text()='ODI']/preceding-sibling::th[text()='Competition']/ancestor::thead/following-sibling::tbody//child::td[text()='Wickets']/following-sibling::td[@class='column-odi']`

→ Correct

d. Matches lost at Away from 2000-2005 using text 'At Away' and year(span) 2000-2005

⇒ `//table[@id='table_5']//th[text()='Lost']/ancestor::thead/following-sibling::tbody//child::td[text()='At Away']/following-sibling::td/following-sibling::td`

→ Condition 2000-2005 is missing

`//td[text()='At Away']/following-sibling::td[text()='2000-2005']/following-sibling::td[@class='column-lost']`

3. Xpath for the text - Records and achievements

← → ↻ [souravganguly.co.in/records-accolades/](http://souravganguly.co.in/records-accolades/)



⇒ `//span[text()='Records and achievements']`

MSQUARE Global