



OXIDIZED BITUMEN 60/70

Technical Specifications

Product: Blown Asphalt 60/70
Manufacturer: GLOBAL AGRO Co. Company for Oxidized Asphalt Production Ltd.
Manufactured in Iraq

Category	Test Property	Standard / Method	Result
Physical & Safety	Penetration @ 25°C	ASTM D5	64 mm/10
Physical & Safety	Ductility @ 25°C	ASTM D113	> 150 cm
Physical & Safety	Specific Gravity @ 25°C	ASTM D70	1.053
Physical & Safety	Solubility in T.C.E.	ASTM D2042	99.8%
Physical & Safety	Flash Point	ASTM D92	304°C
Thermal & Rheological	Softening Point	ASTM D36	48°C
Thermal & Rheological	Breaking Point (Fraass)	IP 80	-8°C
Thermal & Rheological	Viscosity @ 135°C	ASTM D4402	404 cP
Thermal & Rheological	Dynamic Viscosity @ 60°C	ASTM D2171	1779 cP
Purity & Composition	Ash Content	ASTM D3104	0.08%
Purity & Composition	Water Content	ASTM D95	Nil

Product Description

Specially oxidized bitumen designed for enhanced performance in demanding conditions. The website describes Blown Asphalt 60/70 as providing excellent adhesion, durability and resistance for industrial and commercial applications.

Primary Applications

Waterproofing & Roofing	Superior protection for industrial membranes.
Pipe-Wrap & Coatings	Anti-corrosion barriers for pipelines.
Paving Grade Applications	High-resistance asphalt for durable roads.

Source: Technical Specifications section published on www.global-agro.net. Values reproduced from the website as accessed on September 2, 2026.