

# TURQUOISE

## Technical Specification FIX 4.4 Specification

Version 1.9  
August 2010

## Contents

1.	About This Document .....	4
1.1	Introduction .....	4
2.	Message Types.....	5
2.1	FIX Message Structure.....	5
2.2	Supported Session Messages .....	5
2.3	Supported Application Messages.....	5
2.4	Data Types.....	6
3.	Session Handling.....	7
3.1	Resend Order Flow.....	7
3.2	Session Message Details .....	7
3.2.1	Message Header .....	7
3.2.2	Message Trailer.....	7
3.2.3	Logon .....	8
3.2.4	Heartbeat.....	8
3.2.5	Test Request .....	9
3.2.6	Resend Request .....	9
3.2.7	Reject .....	9
3.2.8	Sequence Reset.....	10
3.2.9	Logout .....	10
3.2.10	Lost Connections .....	10
3.2.11	Service Not Available.....	11
3.2.12	No Acknowledgment Returned .....	11
4.	Application Messages .....	12
4.1	Common Components .....	12
4.1.1	Instrument Identification.....	12
4.1.2	Peg Instructions .....	12
4.1.3	Parties .....	12
4.2	New Order Single .....	13
4.3	New Order Single (TQ-LENS) .....	13
4.4	Order Cancel Request .....	14
4.5	Order Cancel Replace Request.....	14
4.6	Order Mass Status Request.....	15
4.7	Order Mass Cancel Request .....	15
4.8	Order Mass Cancel Report .....	15
4.9	Order Cancel Reject.....	16
4.10	Mass Quote .....	16
4.11	Quote Cancel.....	17
4.12	Quote Acknowledgement .....	17

4.13	Execution Report .....	18
4.14	Security List Request .....	19
4.15	Security List .....	19
4.16	Security Definition Request.....	20
4.17	Security Definition.....	20
4.18	Don't Know Trade .....	20
4.19	News Message .....	21
5.	Field Definitions .....	22
6.	Order State Change Matrices .....	31
6.1	Limit Day Order .....	31
6.2	TQ-LENS Order Strategy 1 .....	31
6.3	TQ-LENS Order Strategy 2 .....	32
6.4	TQ-LENS Order Strategy 3 .....	32
6.5	Limit Dark Order.....	33
6.6	Market Order .....	33
6.7	Fill or Kill.....	34
6.8	Fill and Kill .....	34
6.9	Limit Good From Time Order .....	35
6.10	Limit Good Till Time Order .....	35
6.11	Pegged against TBBO .....	36
6.12	Dark Order Pegged against EBBO.....	36
6.13	Iceberg Order .....	37
6.14	Pegged TBBO Iceberg Order.....	37
6.15	Mass Cancel Request .....	38
6.16	Order Mass Status Request.....	38
6.17	Mass Quote .....	38
6.18	Security List Request .....	39
6.19	News (Unsolicited Broadcast) .....	39

## 1. About This Document

### 1.1 Introduction

The Financial Information Exchange (FIX) protocol enables access to the Turquoise Trading System (TTS), using a messaging standard developed for real-time electronic exchange of security transactions.

FIX enables access to the trading services and security information within Turquoise. This document describes a conceptual overview of the FIX 4.4 protocol as well as providing technical guidance on adopting FIX to connect to Turquoise.

Using the FIX protocol, participants are able to access the TQ-LENS and TQ-MTF services at Turquoise; this specification illustrates the requirements for routing to TQ-LENS via the FIX protocol and trading with the TQ-MTF.

Note: for Turquoise MTF functionality, the proprietary tags implemented within the FIX 4.4 Turquoise Specification are not mandatory and can be added or removed upon request. For further information, contact Technical Account Management at Turquoise.

<http://www.fixprotocol.org>

## 2. Message Types

### 2.1 FIX Message Structure

A FIX message consists of three elements, a Header, a Body and a Trailer.

- **Header:** Identifies the message type, length, routing & addressing information.
- **Body:** Defines the content of the actual business level message; the payload.
- **Trailer:** Defines the three digit character representation of a check sum value.

### 2.2 Supported Session Messages

FIX Message	FIX Message Type	Inbound (to TTS) / Outbound (from TTS)
Logon	A	Incoming/Outgoing
Heartbeat	0	Incoming/Outgoing
Test Request	1	Incoming/Outgoing
Resend Request	2	Incoming/Outgoing
Reject	3	Outgoing
Sequence Request	4	Incoming/Outgoing
Logout	5	Incoming/Outgoing

### 2.3 Supported Application Messages

FIX Message	FIX Message Type	Inbound (to TTS) / Outbound (from TTS)
New Order Single	D	Incoming
Order Cancel Request	F	Incoming
Order Cancel Replace Request	G	Incoming
Order Mass Status Request	AF	Incoming
Order Mass Cancel Request	q	Incoming
Order Mass Cancel Report	r	Outgoing
Mass Quote	l	Incoming
Quote Cancel	Z	Incoming
Quote Acknowledgment	b	Outgoing
Execution Report	8	Outgoing
Security Definition Request	c	Incoming
Security Definition	d	Outgoing
Security List Request	x	Incoming
Security List	y	Outgoing
News Message	B	Outgoing
Don't Know Trade	Q	Incoming
Order Cancel Reject	9	Outgoing

Note: Quoting functionality is for use by participants who are registered market makers only.

## 2.4 Data Types

Each field within a FIX message has an associated data type allowing for data validation. The table below defines the meaning of each data type described within this document.

Data Type	Description
Int	Sequence of digits without commas or decimals and optional sign character (ASCII characters "-" and "0" - "9"). The sign character utilizes one byte (i.e. positive int is "99999" while negative int is "-99999"). Note that int values may contain leading zeros (e.g. "00023" = "23").
Qty	Value capable of storing either a whole number (no decimal places) of "shares" (securities denominated in whole units) or a decimal value containing decimal places for non-share quantity asset classes (securities denominated in fractional units).
String	Alpha-numeric free format strings; can include any character or punctuation except the delimiter. All char fields are case sensitive (i.e. morstatt != Morstatt).
Boolean	char field containing one of two values: 'Y' = True/Yes 'N' = False/No
Currency	Representing a currency type using ISO 4217 Currency code (3 character) values.
UTC Timestamp	Representing Time/date combination represented in UTC (Universal Time Coordinated, also known as "GMT") only accepted in this format : YYYYMMDD-HH:MM:SS (whole seconds).
Char	Char value, can include any alphanumeric character or punctuation except the delimiter. All char fields are case sensitive (i.e. m != M).
Price	Value representing a price. Note the number of decimal places may vary.
Length	Representing the length in bytes. Value must be positive
SeqNum	Representing a message sequence number. Value must be positive
Float	Sequence of digits with optional decimal point and sign character (ASCII characters "-", "0" - "9" and "."); the absence of the decimal point within the string will be interpreted as the float representation of an integer value. All float fields must accommodate up to fifteen significant digits. The number of decimal places used should be a factor of business/market needs and mutual agreement between counterparties. Note that float values may contain leading zeros (e.g. "00023.23" = "23.23") and may contain or omit trailing zeros after the decimal point (e.g. "23.0" = "23.0000" = "23" = "23."). Note that fields which are derived from float may contain negative values unless explicitly specified otherwise
NumInGroup	Value that represents the number of repeating values in a group
MultipleValueString	Field Containing one or more space delimited values.

## 3. Session Handling

Session handling is according to the FIX 4.4 specification standard.

### 3.1 Resend Order Flow

Resend requests are accepted and processed by the Turquoise Trading System, the response will include all application messages, for more information please refer to section 3.2.6.

### 3.2 Session Message Details

#### 3.2.1 Message Header

All FIX messages for the Turquoise Trading System use the Standard Message Header, as specified by the FIX 4.4 specification, below describes the tags associated with the message header.

The tags BeginString, BodyLength, and MsgType must always be the first three tags of every FIX message in the correct sequence as below. Any message that does not have these tags in the correct order will be rejected.

Tag	Field Name	Data Type	Required
8	<a href="#">BeginString</a>	<a href="#">String</a>	Y
9	<a href="#">BodyLength</a>	<a href="#">Length</a>	Y
35	<a href="#">MsgType</a>	<a href="#">String</a>	Y
49	<a href="#">SenderCompID</a>	<a href="#">String</a>	Y
50	<a href="#">SenderSubID</a>	<a href="#">String</a>	N
56	<a href="#">TargetCompID</a>	<a href="#">String</a>	Y
57	<a href="#">TargetSubID</a>	<a href="#">String</a>	N
34	<a href="#">MsgSeqNum</a>	<a href="#">SeqNum</a>	Y
43	<a href="#">PossDupFlag</a>	<a href="#">Boolean</a>	N
97	<a href="#">PossResend</a>	<a href="#">Boolean</a>	N
115	<a href="#">OnBehalfOfCompID</a>	<a href="#">String</a>	N
116	<a href="#">OnBehalfOfSubID</a>	<a href="#">String</a>	N
128	<a href="#">DeliverToCompID</a>	<a href="#">String</a>	N
129	<a href="#">DeliverToSubID</a>	<a href="#">String</a>	N
52	<a href="#">SendingTime</a>	<a href="#">UTCTimestamp</a>	Y

Note: Messages from Turquoise to a client application has the value TTS set as tag 49 SenderCompID

#### 3.2.2 Message Trailer

Each message is terminated by a standard trailer. The trailer is used to segregate messages and contains the three digit character representation of a checksum value:

Tag	Field Name	Data Type	Required
10	<a href="#">Checksum</a>	<a href="#">String</a>	Y

## 3.2.3 Logon

The initial messages exchanged in a FIX session are the Logon Request and the Logon Response. The logon request is initiated from the client, which will then follow a response from Turquoise. The main purpose of the Logon request and response is:

- To authenticate the client
- To agree on the sequence numbers
- To decide on Heartbeat handling

<b>FIX Message</b>	Logon (Message Type = A)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
98	<a href="#">EncryptMethod</a>	<a href="#">Int</a>	Y
108	<a href="#">HeartBtInt</a>	<a href="#">Int</a>	Y
141	<a href="#">ResetSeqNumFlag</a>	<a href="#">Boolean</a>	N
789	<a href="#">NextExpectedMsgSeqNum</a>	<a href="#">SeqNum</a>	N
553	<a href="#">Username</a>	<a href="#">String</a>	N
554	<a href="#">Password</a>	<a href="#">String</a>	N

Note: Username and Password are not required tags. To validate a session the FIX gateway will authenticate the IP, Port and SenderCompID before a connection is established. If a participant requires to also use the Username and Password, Turquoise can implement this accordingly on a per request basis.

## 3.2.4 Heartbeat

Upon logon a request for a heartbeat interval can be set using the HeartBtInt (tag 108) to determine if the session is still active.

<b>FIX Message</b>	Heartbeat (Message Type = 0)
<b>Direction</b>	From client to Turquoise and from Turquoise to client.

Tag	Field Name	Data Type	Required
112	<a href="#">TestReqID</a>	<a href="#">String</a>	N

The FIX gateway at Turquoise will only send Heartbeat requests at the requested interval if no other activity has been sent before that time.

Once a session has been established Heartbeats must be sent from both sides, if HeartBtInt=0 no Heartbeat messages will be sent from Turquoise; Turquoise does not require Heartbeat messages from the opposing SenderCompID.



## 3.2.5 Test Request

This message is utilised when the heartbeat is a result of a Test Request message, useful for checking sequence numbers or verifying the communication line status.

The FIX gateway at Turquoise supports Test requests in both directions. The response message will always be a heartbeat message with the TestReqID which will verify the heartbeat is a result of a Test Request message and not a normal timeout.

<b>FIX Message</b>	Test Request (Message Type = 1)
<b>Direction</b>	From client to Turquoise and from Turquoise to client.

Tag	Field Name	Data Type	Required
112	<a href="#">TestReqID</a>	<a href="#">String</a>	Y

## 3.2.6 Resend Request

A Resend Request is sent to initiate the retransmission of messages, utilised for example if a sequence number gap is detected.

<b>FIX Message</b>	Resend Request (Message Type = 2)
<b>Direction</b>	From client to Turquoise and from Turquoise to client

Tag	Field Name	Data Type	Required
7	<a href="#">BeginSeqNo</a>	<a href="#">SeqNum</a>	Y
16	<a href="#">EndSeqNo</a>	<a href="#">SeqNum</a>	Y

- If the request is for a single message:  
BeginSeqNo = EndSeqNo
- If the request is for all messages subsequent to a particular message:  
EndSeqNo = 0 (representing infinity)

## 3.2.7 Reject

The FIX gateway at Turquoise may reject transactions at the session level in the following example cases:

- A logon request with ResetSeqNumFlag set to Y.
- A logon request using a user that is disabled or not authorized to access the system.
- A gateway fault.

<b>FIX Message</b>	Reject (Message Type = 3)
<b>Direction</b>	From client to Turquoise or from Turquoise to client.

Tag	Field Name	Data Type	Required
45	<a href="#">RefSeqNum</a>	<a href="#">SeqNum</a>	Y
371	<a href="#">RefTagID</a>	<a href="#">Int</a>	N
372	<a href="#">RefMsgType</a>	<a href="#">String</a>	N
373	<a href="#">SessionRejectReason</a>	<a href="#">Int</a>	N
58	<a href="#">Text</a>	<a href="#">String</a>	N

## 3.2.8 Sequence Reset

Sequence Reset is used to reset the incoming sequence number on the opposing side, this message can be used in the following scenarios:

- Gap Fill mode which will be used as the response to a Resend Request
- Reset mode which will be used to reset the sequence number after an unrecoverable application failure, a Sequence Reset can only ever increase the sequence number.

<b>FIX Message</b>	Sequence Reset (Message Type = 4)
<b>Direction</b>	From client to Turquoise or from Turquoise to client.

Tag	Field Name	Data Type	Required
123	<a href="#">GapFillFlag</a>	<a href="#">Boolean</a>	N
36	<a href="#">NewSeqNo</a>	<a href="#">SeqNum</a>	Y

## 3.2.9 Logout

FIX clients should terminate their session by logging out. It is not advisable to terminate a FIX session without sending a logout message first.

If a FIX user is disabled by Turquoise Market Operations while the user is logged in, a Logout message will be sent to the client communicating the reason for the logout and the FIX session will be disconnected.

<b>FIX Message</b>	Logout (Message Type = 5)
<b>Direction</b>	From client to Turquoise or from Turquoise to client.

Tag	Field Name	Data Type	Required
58	<a href="#">Text</a>	<a href="#">String</a>	N

## 3.2.10 Lost Connections

If the connection with the FIX gateway drops and the session has been lost it is advisable to perform the following actions:

1. Re-establish the connection (if needed to a secondary access point).
2. Resend any application or session messages that have not been acknowledged by the FIX gateway (35=2).

Note: Resent messages will need to have the PossResend flag set in case the instruction has already been received by the FIX gateway. If the message has already been processed it will not be processed again.

### 3.2.11 Service Not Available

If an outgoing FIX message from Turquoise is received with 'Service Not Available' it is recommended to progress with the following action:

1. Wait five seconds then retry the rejected transaction on the same session. When resending the transaction the PossResend flag should be set.
2. If the problem is persistently occurring contact Turquoise Market Operations to find out more information.

Note: If a certain transaction results in 'Service Not Available' being returned it does not necessarily mean other transactions of the same type will be rejected. This is due to the fact that the system is partitioned, i.e. different instruments are handled by different matching engines within Turquoise. This means that a client can send other transactions while waiting to resend rejected transactions.

### 3.2.12 No Acknowledgment Returned

If an acknowledgement is not returned in response to a transaction there may be a problem with the link between the application and the central matching system. It is advisable in this scenario to contact Turquoise Market Operations to find out the status of the transaction and determine why an acknowledgement was not received. It can then be decided if a logout and new session will need to be established.

## 4. Application Messages

Application messages conform to the FIX 4.4 specification.

### 4.1 Common Components

#### 4.1.1 Instrument Identification

Instruments are identified within Turquoise by:

- SecurityID (ISIN Code)
  - Currency
- Or
- Symbol

Tag	Field Name	Data Type	Required
22	<a href="#">SecurityIDSource</a>	<a href="#">String</a>	N
48	<a href="#">SecurityID</a>	<a href="#">String</a>	N
15	<a href="#">Currency</a>	<a href="#">Currency</a>	N
55	<a href="#">Symbol</a>	<a href="#">String</a>	N

Note: If the Turquoise symbol is supplied, then SecurityID, SecurityIDSource, and Currency are not required. Either the Symbol or ISIN/Currency combination must be supplied.

#### 4.1.2 Peg Instructions

Peg instructions using FIX are required to adopt the following tags:

Tag	Field Name	Data Type	Required
211	<a href="#">PegOffsetValue</a>	<a href="#">Float</a>	N
835	<a href="#">PegMoveType</a>	<a href="#">Int</a>	Y
836	<a href="#">PegOffsetType</a>	<a href="#">Int</a>	Y
840	<a href="#">PegScope</a>	<a href="#">Int</a>	Y

#### 4.1.3 Parties

Party information is used to specify the clearing firm and adopts the following tags:

Tag	Field Name	Data Type	Required
453	<a href="#">NoPartyIDs</a>	<a href="#">NumInGroup</a>	N
448	<a href="#">PartyID</a>	<a href="#">String</a>	N
452	<a href="#">PartyRole</a>	<a href="#">Int</a>	N

Note: If party information is not supplied, Turquoise applies the default clearing code.

## 4.2 New Order Single

A message type used to enter orders within Turquoise.

<b>FIX Message</b>	New Order Single (Message Type = D)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
1	<a href="#">Account</a>	<a href="#">String</a>	N
11	<a href="#">ClOrdId</a>	<a href="#">String</a>	Y
18	<a href="#">ExecInst</a>	<a href="#">Multiple Value String</a>	N
21	<a href="#">HandlInst</a>	<a href="#">Char</a>	N
38	<a href="#">OrderQty</a>	<a href="#">Qty</a>	Y
40	<a href="#">OrdType</a>	<a href="#">Char</a>	Y
44	<a href="#">Price</a>	<a href="#">Price</a>	N
54	<a href="#">Side</a>	<a href="#">Char</a>	Y
58	<a href="#">Text</a>	<a href="#">String</a>	N
59	<a href="#">TimeInForce</a>	<a href="#">Char</a>	N
60	<a href="#">TransactTime</a>	<a href="#">UTC Timestamp</a>	Y
100	<a href="#">ExDestination</a>	<a href="#">String</a>	N
110	<a href="#">MinQty</a>	<a href="#">Qty</a>	N
210	<a href="#">MaxShow</a>	<a href="#">Qty</a>	N
126	<a href="#">ExpireTime</a>	<a href="#">UTC Timestamp</a>	N
168	<a href="#">EffectiveTime</a>	<a href="#">UTC Timestamp</a>	N
111	<a href="#">MaxFloor</a>	<a href="#">Qty</a>	N
<a href="#">&lt;Instrument&gt;</a>			Y
<a href="#">&lt;Parties&gt;</a>			N
<a href="#">&lt;Peg Instruction&gt;</a>			N
528	<a href="#">OrderCapacity</a>		N

## 4.3 New Order Single (TQ-LENS)

A message type used to enter orders within Turquoise.

<b>FIX Message</b>	New Order Single (Message Type = D)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
1	<a href="#">Account</a>	<a href="#">String</a>	N
11	<a href="#">ClOrdId</a>	<a href="#">String</a>	Y
18	<a href="#">ExecInst</a>	<a href="#">Multiple Value String</a>	N
21	<a href="#">HandlInst</a>	<a href="#">Char</a>	N
38	<a href="#">OrderQty</a>	<a href="#">Qty</a>	Y
40	<a href="#">OrdType</a>	<a href="#">Char</a>	Y
44	<a href="#">Price</a>	<a href="#">Price</a>	N
54	<a href="#">Side</a>	<a href="#">Char</a>	Y
58	<a href="#">Text</a>	<a href="#">String</a>	N
59	<a href="#">TimeInForce</a>	<a href="#">Char</a>	N
60	<a href="#">TransactTime</a>	<a href="#">UTC Timestamp</a>	Y
100	<a href="#">ExDestination</a>	<a href="#">String</a>	N
110	<a href="#">MinQty</a>	<a href="#">Qty</a>	N
210	<a href="#">MaxShow</a>	<a href="#">Qty</a>	N
126	<a href="#">ExpireTime</a>	<a href="#">UTC Timestamp</a>	N
168	<a href="#">EffectiveTime</a>	<a href="#">UTC Timestamp</a>	N
111	<a href="#">MaxFloor</a>	<a href="#">Qty</a>	N
<a href="#">&lt;Instrument&gt;</a>			Y
<a href="#">&lt;Parties&gt;</a>			N
<a href="#">&lt;Peg Instruction&gt;</a>			N
528	<a href="#">OrderCapacity</a>	<a href="#">Char</a>	N
9007	<a href="#">TQLStrategy</a>	<a href="#">Int</a>	N
9008	<a href="#">TQLTimestamp</a>	<a href="#">UTC Timestamp</a>	N

9010	<a href="#">TOLCustomisedStrategy</a>	<a href="#">String</a>	N
9011	<a href="#">TOLGrouping</a>	<a href="#">Int</a>	N
9012	<a href="#">TOLExecMethod</a>	<a href="#">Price</a>	N
9014	<a href="#">DPMaxQty</a>	<a href="#">Qty</a>	N

## 4.4 Order Cancel Request

A message type used to request cancellation of all or part of the remaining quantity of an existing order.

<b>FIX Message</b>	Order Cancel Request (Message Type = F)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
11	<a href="#">ClOrdId</a>	<a href="#">String</a>	Y
37	<a href="#">OrderID</a>	<a href="#">String</a>	N
41	<a href="#">OrigClOrdId</a>	<a href="#">String</a>	Y
54	<a href="#">Side</a>	<a href="#">Char</a>	Y
38	<a href="#">OrderQty</a>	<a href="#">Qty</a>	Y
<a href="#">&lt;Instrument&gt;</a>			Y
<a href="#">&lt;Parties&gt;</a>			N
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	Y

## 4.5 Order Cancel Replace Request

A message type used to change the parameters of an existing order, this will then be acknowledged by means of an execution report.

<b>FIX Message</b>	New Cancel Replace Request (Message Type = G)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
1	<a href="#">Account</a>	<a href="#">String</a>	N
11	<a href="#">ClOrdId</a>	<a href="#">String</a>	Y
37	<a href="#">OrderID</a>	<a href="#">String</a>	N
38	<a href="#">OrderQty</a>	<a href="#">Qty</a>	Y
40	<a href="#">OrdType</a>	<a href="#">Char</a>	Y
41	<a href="#">OrigClOrdId</a>	<a href="#">String</a>	Y
44	<a href="#">Price</a>	<a href="#">Price</a>	N
54	<a href="#">Side</a>	<a href="#">Char</a>	Y
<a href="#">&lt;Instrument&gt;</a>			Y
59	<a href="#">TimeInForce</a>	<a href="#">Char</a>	N
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	Y
100	<a href="#">ExDestination</a>	<a href="#">String</a>	N
110	<a href="#">MinQty</a>	<a href="#">Qty</a>	N
126	<a href="#">ExpireTime</a>	<a href="#">UTCTimestamp</a>	N
168	<a href="#">EffectiveTime</a>	<a href="#">UTCTimestamp</a>	N
210	<a href="#">MaxShow</a>	<a href="#">Qty</a>	Y
<a href="#">&lt;Parties&gt;</a>			N
<a href="#">&lt;Peg Instruction&gt;</a>			N
9007	<a href="#">TOLStrategy</a>	<a href="#">Int</a>	N
9008	<a href="#">TOLTimestamp</a>	<a href="#">UTC Timestamp</a>	N
9010	<a href="#">TOLCustomisedStrategy</a>	<a href="#">String</a>	N
9011	<a href="#">TOLGrouping</a>	<a href="#">Int</a>	N
9012	<a href="#">TOLExecMethod</a>	<a href="#">Price</a>	N
9014	<a href="#">DPMaxQty</a>	<a href="#">Qty</a>	N
528	<a href="#">OrderCapacity</a>	<a href="#">Char</a>	N

Note: The tags populated as part of the Order Cancel Replace Request message must at a minimum match the tags populated as part of the New Order Single message as well as any additional fields needed for the amendment.

## 4.6 Order Mass Status Request

A mass status request is assigned an ID and is treated as a separate entity.

On entry of this request no acknowledgement is returned, instead execution Reports with ExecType = I (Order Status) are returned for all orders matching the criteria provided on the request.

If an instrument is supplied, execution reports will be generated for all open orders for the instrument specified.

<b>FIX Message</b>	Order Mass Status Request (Message Type = AF)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
584	<a href="#">MassStatusReqID</a>	<a href="#">String</a>	Y
585	<a href="#">MassStatusReqType</a>	<a href="#">Int</a>	Y
<a href="#">&lt;Instrument&gt;</a>			N

## 4.7 Order Mass Cancel Request

The Order Mass Cancel Request message requests the cancellation of all of the remaining quantity of a group of orders matching criteria specified within the request.

An Order Mass Cancel Request must be assigned a unique ClOrdID and be treated as a separate entity, the ClOrdID is then acknowledged within the Order Mass Cancel Report.

<b>FIX Message</b>	Order Mass Cancel Request (Message Type = q)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
11	<a href="#">ClOrdID</a>	<a href="#">String</a>	Y
530	<a href="#">MassCancelRequestType</a>	<a href="#">Char</a>	Y
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	Y
58	<a href="#">Text</a>	<a href="#">String</a>	N

If you would like to cancel all orders for a specific instrument this can be requested by contacting Turquoise Market Operations. An unsolicited cancel execution message is then returned for each cancelled order.

## 4.8 Order Mass Cancel Report

The Order Mass Cancel Report is used to acknowledge an Order Mass Cancel Request. Each affected order that is cancelled is acknowledged by an Execution Report or Order Cancel Reject message.

<b>FIX Message</b>	Order Mass Cancel Report (Message Type = r)
<b>Direction</b>	From Turquoise to client

Tag	Field Name	Data Type	Required
11	<a href="#">ClOrdID</a>	<a href="#">String</a>	Y
37	<a href="#">OrderID</a>	<a href="#">String</a>	Y
530	<a href="#">MassCancelRequestType</a>	<a href="#">Char</a>	Y
531	<a href="#">MassCancelResponse</a>	<a href="#">Char</a>	Y
532	<a href="#">MassCancelRejectReason</a>	<a href="#">Char</a>	N
54	<a href="#">Side</a>	<a href="#">Char</a>	N
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	Y
58	<a href="#">Text</a>	<a href="#">String</a>	N

## 4.9 Order Cancel Reject

An order cancel reject will specify the reason for a cancel request not being acted upon.

<b>FIX Message</b>	Order Cancel Reject (Message Type = 9)
<b>Direction</b>	From Turquoise to Client

Tag	Field Name	Data Type	Required
1	<a href="#">Account</a>	<a href="#">String</a>	N
11	<a href="#">ClOrdID</a>	<a href="#">String</a>	Y
37	<a href="#">OrderID</a>	<a href="#">String</a>	N
39	<a href="#">OrdStatus</a>	<a href="#">Char</a>	Y
41	<a href="#">OrigClOrdID</a>	<a href="#">String</a>	Y
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	N
434	<a href="#">CxlRejResponseTo</a>	<a href="#">Char</a>	Y
102	<a href="#">CxlRejReason</a>	<a href="#">Qty</a>	N
58	<a href="#">Text</a>	<a href="#">String</a>	N

## 4.10 Mass Quote

A Mass Quote is used to insert and update a Quote request to Turquoise. Each specific Quote entry within the Mass Quote is given a unique QuoteEntryID and is placed within a repeating group as specified in the table below.

To replace an existing Quote entry, a new Mass Quote message using the original QuoteID is required to be sent. It is important to note that amendments are performed on an instrument level, a new Quote entry will replace anything currently existing within the QuoteID for the same instrument.

For example, if within a Mass Quote four quote entries exist for a specific instrument and a Mass Quote is amended with only two quote entries for this instrument, then the other two quotes will be removed from Turquoise.

If this behaviour is not desirable it may be suggested that where more than one Quote entry is required for the same instrument, the Quote Entries can be split between Mass Quote messages.

<b>FIX Message</b>	Mass Quote (Message Type = i)
<b>Direction</b>	From Client to Turquoise

Tag		Field Name	Data Type	Required
117		<a href="#">QuoteID</a>	<a href="#">String</a>	Y
293		<a href="#">DefBidSize</a>	<a href="#">Qty</a>	N
294		<a href="#">DefOfferSize</a>	<a href="#">Qty</a>	N
60		<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	N
296		<a href="#">NoQuoteSets</a>	<a href="#">Qty</a>	Y
→	299	<a href="#">QuoteEntryID</a>	<a href="#">Qty</a>	Y
→	55	<a href="#">Symbol</a>	<a href="#">String</a>	N
→	48	<a href="#">SecurityID</a>	<a href="#">String</a>	N
→	132	<a href="#">BidPx</a>	<a href="#">Price</a>	N
→	133	<a href="#">OfferPx</a>	<a href="#">Price</a>	N
→	134	<a href="#">BidSize</a>	<a href="#">Qty</a>	N
→	135	<a href="#">OfferSize</a>	<a href="#">Qty</a>	N
→	15	<a href="#">Currency</a>	<a href="#">Price</a>	N
→	9010	<a href="#">IsPassive</a>	<a href="#">String</a>	N



## 4.11 Quote Cancel

Quote cancellations within Turquoise are performed on an instrument level using the QuoteID from the original Mass Quote request. To cancel all quotes for a specific QuoteID each instrument must be specified within the repeating group.

<b>FIX Message</b>	Quote Cancel (Message Type = Z)
<b>Direction</b>	From Client to Turquoise

Tag	Field Name	Data Type	Required
117	<a href="#">QuoteID</a>	<a href="#">String</a>	Y
298	<a href="#">QuoteCancelType</a>	<a href="#">Int</a>	N
295	<a href="#">NoQuoteEntries</a>	<a href="#">Qty</a>	Y
→ 55	<a href="#">Symbol</a>	<a href="#">String</a>	N
→ 48	<a href="#">SecurityID</a>	<a href="#">String</a>	N
→ 15	<a href="#">Currency</a>	<a href="#">Price</a>	N

## 4.12 Quote Acknowledgement

A quote acknowledgement is returned on receipt of a Mass Quote or a Quote Cancel message.

<b>FIX Message</b>	Quote Acknowledgement (Message Type = b)
<b>Direction</b>	From Turquoise to Client

Tag	Field Name	Data Type	Required
117	<a href="#">QuoteID</a>	<a href="#">String</a>	N
297	<a href="#">QuoteAckStatus</a>	<a href="#">Int</a>	Y
300	<a href="#">QuoteRejectReason</a>	<a href="#">Int</a>	N
58	<a href="#">Text</a>	<a href="#">String</a>	N
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	N
296	<a href="#">NoQuoteSets</a>	<a href="#">Qty</a>	Y
→ 299	<a href="#">QuoteEntryID</a>	<a href="#">String</a>	N
→ 55	<a href="#">Symbol</a>	<a href="#">String</a>	N
→ 48	<a href="#">SecurityID</a>	<a href="#">String</a>	N
→ 132	<a href="#">BidPx</a>	<a href="#">Price</a>	N
→ 133	<a href="#">OfferPx</a>	<a href="#">Price</a>	N
→ 134	<a href="#">BidSize</a>	<a href="#">Qty</a>	N
→ 135	<a href="#">OfferSize</a>	<a href="#">Qty</a>	N
→ 15	<a href="#">Currency</a>	<a href="#">Price</a>	N
→ 9010	<a href="#">IsPassive</a>	<a href="#">String</a>	N

## 4.13 Execution Report

An execution report sent to the client will :

- Confirm the receipt of an order.
- Confirm changes to an existing order.
- Relay Order Status Information.
- Relay fill information on working orders.
- Send Rejected orders.

<b>FIX Message</b>	Execution Report (Message Type = 8)
<b>Direction</b>	From Turquoise to client

Tag	Field Name	Data Type	Required
1	<a href="#">Account</a>	<a href="#">String</a>	N
6	<a href="#">AvgPx</a>	<a href="#">Price</a>	Y
11	<a href="#">ClOrdId</a>	<a href="#">String</a>	N
14	<a href="#">CumQty</a>	<a href="#">Qty</a>	Y
17	<a href="#">ExecId</a>	<a href="#">String</a>	Y
18	<a href="#">ExecInst</a>	<a href="#">MultipleValueString</a>	N
30	<a href="#">LastMkt</a>	<a href="#">String</a>	N
31	<a href="#">LastPx</a>	<a href="#">Price</a>	N
32	<a href="#">LastQty</a>	<a href="#">Qty</a>	N
37	<a href="#">OrderID</a>	<a href="#">String</a>	Y
38	<a href="#">OrderQty</a>	<a href="#">Qty</a>	N
39	<a href="#">OrderStatus</a>	<a href="#">Char</a>	Y
40	<a href="#">OrdType</a>	<a href="#">Char</a>	N
41	<a href="#">OrigClOrdId</a>	<a href="#">String</a>	N
44	<a href="#">Price</a>	<a href="#">Price</a>	N
54	<a href="#">Side</a>	<a href="#">Char</a>	Y
<a href="#">&lt;Instrument&gt;</a>			Y
58	<a href="#">Text</a>	<a href="#">String</a>	N
59	<a href="#">TimeInForce</a>	<a href="#">Char</a>	N
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	N
103	<a href="#">OrdRejReason</a>	<a href="#">Int</a>	N
100	<a href="#">ExDestination</a>	<a href="#">String</a>	N
110	<a href="#">MinQty</a>	<a href="#">Qty</a>	N
111	<a href="#">MaxFloor</a>	<a href="#">Qty</a>	N
126	<a href="#">ExpireTime</a>	<a href="#">UTCTimestamp</a>	N
150	<a href="#">ExecType</a>	<a href="#">Char</a>	Y
151	<a href="#">LeavesQty</a>	<a href="#">Qty</a>	Y
168	<a href="#">EffectiveTime</a>	<a href="#">UTCTimestamp</a>	N
839	<a href="#">PeggedPrice</a>	<a href="#">Price</a>	N
378	<a href="#">ExecRestatementReason</a>	<a href="#">Char</a>	N
<a href="#">&lt;Peg Instruction&gt;</a>			N
528	<a href="#">OrderCapacity</a>	<a href="#">Char</a>	N
851	<a href="#">LastLiquidityInd</a>	<a href="#">Int</a>	N
9002	<a href="#">TBBOBid</a>	<a href="#">Price</a>	N
9003	<a href="#">TBBOAsk</a>	<a href="#">Price</a>	N
9004	<a href="#">ABBOBid</a>	<a href="#">Price</a>	N
9005	<a href="#">ABBOAsk</a>	<a href="#">Price</a>	N
9006	<a href="#">TypeOfTrade</a>	<a href="#">String</a>	N
9009	<a href="#">TQLSelfCrossed</a>	<a href="#">Int</a>	N
9012	<a href="#">TQLExecMethod</a>	<a href="#">Price</a>	N
9013	<a href="#">TQLExecFee</a>	<a href="#">Price</a>	N
9014	<a href="#">DPMaxQty</a>	<a href="#">Qty</a>	N

Note: Tags 9002-9014 are proprietary tags to the Turquoise platform.

## 4.14 Security List Request

This message type will subscribe to all the tradable securities within the Turquoise environment.

- If SecurityExchange is supplied within the request only instruments for that exchange will be returned in the Security List.
- If the SecurityListRequestType is set to 5, there will be separate Security List messages for each security exchange.
- If SecurityListRequestType is set to 4, all of the instruments for all of the supported exchanges will be sent on one message.

<b>FIX Message</b>	Security List Request (Message Type = x)
<b>Direction</b>	From Client to Turquoise

Tag	Field Name	Data Type	Required
320	<a href="#">SecurityReqId</a>	<a href="#">String</a>	Y
559	<a href="#">SecurityListRequestType</a>	<a href="#">String</a>	Y
207	<a href="#">SecurityExchange</a>	<a href="#">String</a>	N

## 4.15 Security List

This message is the response to the security list request containing the list of tradable instruments.

<b>FIX Message</b>	Security List (Message Type = y)
<b>Direction</b>	From Turquoise to client

Tag	Field Name	Data Type	Required
320	<a href="#">SecurityReqId</a>	<a href="#">String</a>	Y
322	<a href="#">SecurityResponseId</a>	<a href="#">String</a>	Y
393	<a href="#">TotalNumSecurities</a>	<a href="#">Int</a>	N
560	<a href="#">SecurityRequestResult</a>	<a href="#">Int</a>	Y
146	<a href="#">NoRelatedSym</a>	<a href="#">NumInGroup</a>	Y
→55	<a href="#">Symbol</a>	<a href="#">String</a>	Y
→22	<a href="#">SecurityIDSource</a>	<a href="#">String</a>	Y
→48	<a href="#">SecurityID</a>	<a href="#">String</a>	Y
→207	<a href="#">SecurityExchange</a>	<a href="#">String</a>	Y
→15	<a href="#">Currency</a>	<a href="#">Currency</a>	Y
→210	<a href="#">MaxShow</a>	<a href="#">Qty</a>	N
→9000	<a href="#">TestInst</a>	<a href="#">Char</a>	Y
→9001	<a href="#">LisLimit</a>	<a href="#">Price</a>	N

Note: Tags 9000 and 9001 are proprietary tags to the Turquoise platform. If a participant does not prefer to receive these tags, Turquoise can prevent them from being disseminated.

## 4.16 Security Definition Request

This message type will subscribe to the tradable securities listed on Turquoise. If a SecurityExchange is supplied, only instruments for that exchange will be returned in the Security Definition. If it is not supplied, the Security Definition will contain all of the securities on the Turquoise environment.

<b>FIX Message</b>	Security Definition Request (Message Type = c)
<b>Direction</b>	From Client to Turquoise

Tag	Field Name	Data Type	Required
320	<a href="#">SecurityReqId</a>	<a href="#">String</a>	Y
207	<a href="#">SecurityExchange</a>	<a href="#">String</a>	N

## 4.17 Security Definition

This message is the response to the Security Definition Request containing the list of tradable instruments. If a security exchange is supplied there will be a separate Security Definition for each Security Exchange.

<b>FIX Message</b>	Security Definition (Message Type = d)
<b>Direction</b>	From Turquoise to client

Tag	Field Name	Data Type	Required
320	<a href="#">SecurityReqId</a>	<a href="#">String</a>	Y
322	<a href="#">SecurityResponseId</a>	<a href="#">String</a>	Y
393	<a href="#">TotalNumSecurities</a>	<a href="#">Int</a>	N
146	<a href="#">NoRelatedSym</a>	<a href="#">NumInGroup</a>	Y
→311	<a href="#">UnderlyingSymbol</a>	<a href="#">String</a>	Y
→305	<a href="#">UnderlyingIDSource</a>	<a href="#">String</a>	Y
→309	<a href="#">UnderlyingSecurityID</a>	<a href="#">String</a>	Y
→308	<a href="#">UnderlyingSecurityExchange</a>	<a href="#">String</a>	Y
→318	<a href="#">UnderlyingCurrency</a>	<a href="#">Currency</a>	Y
→210	<a href="#">MaxShow</a>	<a href="#">Qty</a>	N
→9000	<a href="#">TestInst</a>	<a href="#">Char</a>	Y
→9001	<a href="#">LisLimit</a>	<a href="#">Price</a>	N

Note: Tags 9000-9001 are proprietary tags to the Turquoise platform. If a participant does not prefer to receive these tags, Turquoise can prevent them from being disseminated.

## 4.18 Don't Know Trade

Don't Know Trade messages are sent from the client to Turquoise upon receipt of an erroneous Execution Report, i.e. when the client is unable to map/match an Execution Report.

The system will respond to a Don't Know Trade message by generating an internal alarm. Manual interventions will then be required to arrive at a resolution.

<b>FIX Message</b>	Don't Know Trade (Message Type = Q)
<b>Direction</b>	From client to Turquoise

Tag	Field Name	Data Type	Required
17	<a href="#">ExecID</a>	<a href="#">String</a>	Y
31	<a href="#">LastPx</a>	<a href="#">Price</a>	N
32	<a href="#">LastQty</a>	<a href="#">Qty</a>	N
37	<a href="#">OrderID</a>	<a href="#">String</a>	Y
38	<a href="#">OrderQty</a>	<a href="#">Qty</a>	Y
54	<a href="#">Side</a>	<a href="#">Char</a>	Y
< <a href="#">Instrument</a> >			Y

58	<a href="#">Text</a>	<a href="#">String</a>	N
127	<a href="#">DKReason</a>	<a href="#">Char</a>	Y

## 4.19 News Message

News messages are distributed by Market Operations at Turquoise to provide information related to the activities and operations of the trading platform. These are broadcast messages and are disabled as default, upon request Turquoise Market Operations will enable the News and disseminate the messages for a particular session.

<b>FIX Message</b>	News Message (Message Type = B)
<b>Direction</b>	From Client to Turquoise

Tag	Field Name	Data Type	Required
60	<a href="#">TransactTime</a>	<a href="#">UTCTimestamp</a>	Y
148	<a href="#">Headline</a>	<a href="#">String</a>	Y

## 5. Field Definitions

This table provides definitions of all the FIX tags adopted at Turquoise and the platform they are applicable to:

- Turquoise Trading System only (MTF)
- TQ-LENS only (TQL)
- Both the Turquoise Trading System and TQ-LENS (TQL/MTF)

Tag	Field Name	Definition	Platform															
1	Account	Account mnemonic as agreed between buy and sell sides	TQL/MTF															
6	AvgPx	Average price of fills on an order. This is always returned as 0.0.	TQL/MTF															
7	BeginSeqNo	Message sequence number of the first message in range to be resent.	TQL/MTF															
8	BeginString	This is the first field in a FIX message identifying the FIX version; within Turquoise this is always version FIX 4.4.	TQL/MTF															
9	BodyLength	The length of the message in bytes.	TQL/MTF															
10	Checksum	Three byte, simple checksum. Always the last field in a message; i.e. serves, with the trailing <SOH>, as the end-of-message delimiter.	TQL/MTF															
11	ClOrderID	Firms, particularly those which electronically submit multi-day orders, trade globally or throughout market close periods, should ensure uniqueness across days and user identity, for example by embedding a date within the ClOrdID field. Otherwise uniqueness throughout the day per user is required. An example format is as follows: 51756345624-31041408 If a fill occurs from a Quote this field will be returned on the execution report and contain the QuoteEntryID and either a 'B' or 'S' depending on the side of the order, i.e. 51756345625	TQL/MTF															
14	CumQty	Total quantity filled on an order.	TQL/MTF															
15	Currency	This field is mandatory if ISIN and currency is used to identify an Orderbook (Instrument). If instead a symbol is populated (tag 55) on order entry then currency will be returned on the execution report from Turquoise.	TQL/MTF															
16	EndSeqNo	Message sequence number of the last message in range to be resent.	TQL/MTF															
17	ExecID	Unique identifier for execution message. For an execution that is a partial fill or fill, this field will contain the Turquoise Trade ID plus the Side of the trade.	TQL/MTF															
18	ExecInst	Instructions for order handling at the exchange trading floor. If more than one instruction is applicable to an order, this field can contain multiple instructions separated by space. Valid values: <table><tr><td>2</td><td>Work</td><td>TQL/MTF</td></tr><tr><td>Q</td><td>Cancel on system failure</td><td>TQL/MTF</td></tr><tr><td>M</td><td>Mid Price Peg</td><td>MTF</td></tr><tr><td>X</td><td>Exclude Self. This value ensures that participants do not cross with themselves when the order is routed to the dark order pool</td><td>TQL</td></tr><tr><td>T</td><td>Fixed Peg to Local best bid or offer at time of order entry.</td><td>MTF</td></tr></table>	2	Work	TQL/MTF	Q	Cancel on system failure	TQL/MTF	M	Mid Price Peg	MTF	X	Exclude Self. This value ensures that participants do not cross with themselves when the order is routed to the dark order pool	TQL	T	Fixed Peg to Local best bid or offer at time of order entry.	MTF	TQL/MTF
2	Work	TQL/MTF																
Q	Cancel on system failure	TQL/MTF																
M	Mid Price Peg	MTF																
X	Exclude Self. This value ensures that participants do not cross with themselves when the order is routed to the dark order pool	TQL																
T	Fixed Peg to Local best bid or offer at time of order entry.	MTF																

# TURQUOISE

		<p>Note:</p> <ul style="list-style-type: none"><li>If tag ExDestination(100) is specified as TQL with tag ExecInst(18) set to 2, the order is pegged inside the spread at Turquoise partner liquidity venues. The order is pegged to the midpoint on the Turquoise MTF.</li><li>If tag ExDestination(100) is specified as MTF with tag ExecInst(18) set to M, the order is pegged to the midpoint on the Turquoise MTF.</li><li>If tag ExDestination(100) is specified as TQL with tag ExecInst(18) set to M, the order is rejected.</li><li>Visible Immediate or Cancel (IOC) / Fill and Kill to Integrated orderbook: TimeInForce(59)=3, OrderType(40)=P, ExecInst(18)=M</li><li>Dark Immediate or Cancel (IOC) / Fill and Kill to Dark orderbook: TimeInForce(59)=3, OrderType(40)=P, ExecInst(18)=M, MaxShow(210)=0</li></ul>																	
21	HandInst	Instructions for order handling on the broker trading floor. Valid values: 1 Automated execution order	TQL/MTF																
22	SecurityIDSource	Identifies the class or source of the security ID (tag 48). Valid Values: 4 ISIN	TQL/MTF																
30	LastMkt	Market of execution returned on the execution report from a fill or partial fill within TQ-LENS, when TQLStrategy is set to 1 or 2.  Valid Values: TQL TRQX	TQL																
31	LastPx	Price of last fill.	TQL/MTF																
32	LastQty	Quantity bought and sold on last fill.	TQL/MTF																
34	MsgSeqNum	The integer number (within the current FIX session) associated with the FIX message.	TQL/MTF																
35	MsgType	Defines the message type. Only message types specified in this document are valid values for this field.	TQL/MTF																
36	NewSeqNo	New sequence number	TQL/MTF																
37	OrderID	Unique identifier for the order as assigned by the sell side (Broker or exchange). Uniqueness for this field must be guaranteed within a single trading day.	TQL/MTF																
38	OrderQty	Quantity ordered.	TQL/MTF																
39	OrderStatus	Identifies the current status of the order. Valid values: <table><tr><td>0</td><td>New</td></tr><tr><td>1</td><td>Partially filled</td></tr><tr><td>2</td><td>Filled</td></tr><tr><td>4</td><td>Cancelled</td></tr><tr><td>6</td><td>Pending Cancel</td></tr><tr><td>C</td><td>Expired</td></tr><tr><td>E</td><td>Pending Replace</td></tr><tr><td>8</td><td>Rejected</td></tr></table>	0	New	1	Partially filled	2	Filled	4	Cancelled	6	Pending Cancel	C	Expired	E	Pending Replace	8	Rejected	TQL/MTF
0	New																		
1	Partially filled																		
2	Filled																		
4	Cancelled																		
6	Pending Cancel																		
C	Expired																		
E	Pending Replace																		
8	Rejected																		
40	OrdType	Type of order, valid values: <table><tr><td>1</td><td>Market</td><td>MTF</td></tr><tr><td>2</td><td>Limit</td><td>MTF</td></tr><tr><td>P</td><td>Pegged</td><td>MTF/TQL</td></tr></table>	1	Market	MTF	2	Limit	MTF	P	Pegged	MTF/TQL	TQL/MTF							
1	Market	MTF																	
2	Limit	MTF																	
P	Pegged	MTF/TQL																	
41	OrigClOrdID	Derived from ClOrdId from the previous order assigned by the institution.	TQL/MTF																
43	PossDupFlag	Indicates that the details within the FIX message may have been sent before, with the same sequence number, on the same FIX session. The Boolean values for this field can	TQL/MTF																

# TURQUOISE

		either be Y or N.																
44	Price	Price per unit of quantity. If OrdType = P then this field contains the peg cap price and is mandatory. Should the pegged price become more aggressive than the price stated here, then the order will cease to track the BBO and be assigned this price. Should the pegged price return to below the cap price, the pegged order will resume tracking the BBO. This field is also mandatory if OrdType = 2.	TQL/MTF															
45	RefSeqNum	Reference message sequence number.	TQL/MTF															
48	SecurityID	A valid ISIN	TQL/MTF															
49	SenderCompID	Identifies the originator of the message. Messages sent from a client to Turquoise use the user ID specified in the logon message to which the FIX session belongs or the CompID.	TQL/MTF															
50	SenderSubID	Assigned value used to identify specific message originator (desk, trader, etc). The value in this tag is returned on an execution in the TargetSubID field (tag 57).	TQL/MTF															
52	SendingTime	Time of message transmission specified using the UTC timestamp.	TQL/MTF															
54	Side of order	The side of the order. Valid values: 1 Buy 2 Sell	TQL/MTF															
55	Symbol	A valid Turquoise symbol. This field is not required if Currency and SecurityID are supplied. If used when Currency and SecurityID are supplied then it should be set to N/A.	TQL/MTF															
56	TargetCompID	Identifies the receiver of the message	TQL/MTF															
57	TargetSubID	Assigned value used to identify specific individual or unit intended to receive message. This tag is populated on execution messages with the value contained in the SenderSubID tag (50) of the order message.	TQL/MTF															
58	Text	Free format text string. If a fill is sent back from a Mass quote this value will contain 'From Quote' on the execution report returned.	TQL/MTF															
59	TimeInForce	Specifies how long the order remains in effect. Absence of this field is interpreted as a Day order. Valid Values: <table><tr><td>0</td><td>Day</td><td>TQL/MTF</td></tr><tr><td>2</td><td>At the opening</td><td>MTF</td></tr><tr><td>3</td><td>Immediate or cancel (IOC). TTS interprets this order type as fill and kill (FAK)</td><td>MTF</td></tr><tr><td>4</td><td>Fill or Kill (FOK)</td><td>MTF</td></tr><tr><td>8</td><td>Good From Next AutoMatch</td><td>MTF</td></tr></table>	0	Day	TQL/MTF	2	At the opening	MTF	3	Immediate or cancel (IOC). TTS interprets this order type as fill and kill (FAK)	MTF	4	Fill or Kill (FOK)	MTF	8	Good From Next AutoMatch	MTF	TQL/MTF
0	Day	TQL/MTF																
2	At the opening	MTF																
3	Immediate or cancel (IOC). TTS interprets this order type as fill and kill (FAK)	MTF																
4	Fill or Kill (FOK)	MTF																
8	Good From Next AutoMatch	MTF																
60	TransactTime	UTC Timestamp illustrating the time of execution/order creation.	TQL/MTF															
97	PossResend	Indicates that the details within the FIX message may have been sent before, with a <i>different</i> sequence number, on the same FIX session. The Boolean values for this field can either be Y or N.	TQL/MTF															
98	EncryptMethod	Method of encryption. 0 None	TQL/MTF															
100	ExDestination	As defined by the client when an order is entered to determine the destination of the order.  Valid values: MTF TQL  Note: If this tag is not populated the default value will be MTF.	TQL/MTF															



102	CxlRejReason	Identify the reason for cancel rejection. Valid Values:		TQL/MTF	
		0	Too late to cancel		TQL/MTF
		1	Unknown order		TQL/MTF
		2	Broker/exchange option		TQL/MTF
		3	Order already in pending cancel or pending replace status.		TQL/MTF
		4	Unable to process order mass cancel request.		MTF
		6	Duplicate ClOrdID received.	TQL/MTF	
103	OrdRejReason	Set if ExecType=8 (rejected). Valid Values:		TQL/MTF	
		0	Other		TQL/MTF
		1	Unknown symbol		TQL/MTF
		2	Exchange closed.		TQL/MTF
		6	Duplicate order		TQL/MTF
		11	Unsupported order characteristics.		TQL/MTF
		12	Time in Force outside Limits.		TQL/MTF
		13	Price outside limits.		MTF
		14	Quantity outside limits.	TQL/MTF	
107	SecurityDesc	Optional textual description for a financial instrument.		TQL/MTF	
108	HeartBtInt	Heartbeat interval specified in seconds, a value of 0 will turn off the heartbeat handling.		TQL/MTF	
110	MinQty	Minimum quantity of an order to be executed acting as an MAQ within Turquoise and used for TQ-LENS.  The value placed in tag 110 must be either null or set to a quantity that is equal or less than the total order quantity (tag 30).		TQL/MTF	
111	MaxFloor	The quantity to be displayed. This tag is used for iceberg orders to specify the minimum display volume.		MTF	
112	TestReqID	The string value that will be returned in the resulting Heartbeat.		TQL/MTF	
115	OnBehalfOfCompID	Assigned value used to identify a firm originating message if the message was delivered by a third party. The third party would then be displayed in the SenderCompID. The information in this field on the order is returned in the DeliverToCompID (tag 128) field on each execution related to that order.		TQL/MTF	
116	OnBehalfOfSubID	Assigned value used to identify specific message originator (i.e. trader) if the message was delivered by a third party. The information in this field on the order is returned in the DeliverToSubID (tag 129) field on each execution related to that order.		TQL/MTF	
117	QuoteID	Unique identifier for a mass quote message.		MTF	
122	OrigSendingTime	UTC/GMT timestamp expressed as YYYYMMDD-HH:MM:ss indicating the original sending time of an order on return from a Resend Request.		TQL/MTF	
123	GapFillFlag	Indicates that the sequence reset message is replacing administrative or application messages which will not be resent. Valid values:		TQL/MTF	
		Y	Gap fill message, MsgSeqNumber field valid.		
		N	Sequence reset, ignore MsgSeqNum.		
126	ExpireTime	Conditionally required if TimeInForce = 0. Used to place Good Till Time orders. Time expressed as YYYYMMDD-HH:MM:ss.  TQ-LENS has a minimum time an order can remain in the liquidity pools of nnn milliseconds, if expire time is less than nnn milliseconds the order will be rejected.  Note: Turquoise does not support overnight orders therefore YYYYMMDD must always be the current date.		TQL/MTF	

127	DKReason	Reason for execution rejection. Valid values: <table><tr><td>A</td><td>Unknown symbol</td></tr><tr><td>B</td><td>Wrong side</td></tr><tr><td>C</td><td>Quantity exceeds order</td></tr><tr><td>D</td><td>No matching order</td></tr><tr><td>E</td><td>Price exceeds limit.</td></tr><tr><td>F</td><td>Calculation difference</td></tr><tr><td>Z</td><td>Other</td></tr></table>	A	Unknown symbol	B	Wrong side	C	Quantity exceeds order	D	No matching order	E	Price exceeds limit.	F	Calculation difference	Z	Other	TQL/MTF								
A	Unknown symbol																								
B	Wrong side																								
C	Quantity exceeds order																								
D	No matching order																								
E	Price exceeds limit.																								
F	Calculation difference																								
Z	Other																								
128	DeliverToCompID	Assigned value used to identify the firm targeted to receive the message if the message is delivered by a third party. The third party firm identifier would be delivered in the TargetCompID (56) field. This tag is populated on execution messages with the information that was contained in the OnBehalfOfCompID tag (115) of the order message.	TQL/MTF																						
129	DeliverToSubID	Assigned value used to identify specific message recipient (i.e. trader) if the message is delivered by a third party. This tag is populated on execution messages with the information that was contained in the OnBehalfOfSubID tag (116) of the order message.	TQL/MTF																						
132	BidPx	The bid price for a single quote.	MTF																						
133	OfferPx	The offer price for a single quote.	MTF																						
134	BidSize	The quantity of the bid on a single quote.	MTF																						
135	OfferSize	The quantity of the offer on a single quote.	MTF																						
141	ResetSeqNumFlag	Indicates that both sides of the FIX session should reset sequence numbers. Valid Values: Y Sequence Reset N No Reset	TQL/MTF																						
146	NoRelatedSym	The number of repeating symbols specified.	TQL/MTF																						
148	Headline	Used for News Messages. This tag contains the information broadcast from Turquoise Market Operations. The template format of a message is: <ul style="list-style-type: none"><li>OrderbookID/TQsymbol WIDE @ hh:mm:ss</li><li>OrderbookID/TQsymbol OUT @ hh:mm:ss</li></ul>	MTF																						
150	ExecType	Describes type of Execution Report. Valid values: <table><tr><td>0</td><td>New</td></tr><tr><td>4</td><td>Cancel</td></tr><tr><td>5</td><td>Replace</td></tr><tr><td>6</td><td>Pending cancel</td></tr><tr><td>8</td><td>Rejected</td></tr><tr><td>C</td><td>Expired</td></tr><tr><td>D</td><td>Restated</td></tr><tr><td>E</td><td>Pending replace</td></tr><tr><td>F</td><td>Trade</td></tr><tr><td>I</td><td>Order status</td></tr><tr><td>H</td><td>Trade cancel</td></tr></table>	0	New	4	Cancel	5	Replace	6	Pending cancel	8	Rejected	C	Expired	D	Restated	E	Pending replace	F	Trade	I	Order status	H	Trade cancel	TQL/MTF
0	New																								
4	Cancel																								
5	Replace																								
6	Pending cancel																								
8	Rejected																								
C	Expired																								
D	Restated																								
E	Pending replace																								
F	Trade																								
I	Order status																								
H	Trade cancel																								
151	LeavesQty	Quantity open for further execution	TQL/MTF																						
168	EffectiveTime	Conditionally required if TimeInForce = 0. Used to place Good From Time orders; i.e. specify the time at which the order should be considered valid. UTC/GMT timestamp expressed as YYYYMMDD-HH:MM:ss  Effective Time can only be used with TQ-LENS if the TQL Strategy chosen is strategy one, this must also be less than the TQLTimestamp.  Note: Turquoise does not support overnight orders therefore YYYYMMDD must always be the current date.	TQL/MTF																						
207	SecurityExchange	Market used to help identify a security. This field is only found on the Security List and Security Definition messages. Valid values include: <table><tr><td>XMAD</td><td>Bolsa De Madrid</td></tr><tr><td>MTAA</td><td>Borsa Italiana</td></tr><tr><td>XETR</td><td>Deutsche Borse - Xetra</td></tr><tr><td>XDUB</td><td>Irish Stock Exchange</td></tr><tr><td>XLON</td><td>London Stock Exchange</td></tr><tr><td>XAMS</td><td>NYSE Euronext Amsterdam</td></tr></table>	XMAD	Bolsa De Madrid	MTAA	Borsa Italiana	XETR	Deutsche Borse - Xetra	XDUB	Irish Stock Exchange	XLON	London Stock Exchange	XAMS	NYSE Euronext Amsterdam	TQL/MTF										
XMAD	Bolsa De Madrid																								
MTAA	Borsa Italiana																								
XETR	Deutsche Borse - Xetra																								
XDUB	Irish Stock Exchange																								
XLON	London Stock Exchange																								
XAMS	NYSE Euronext Amsterdam																								

		<table><tr><td>XBRU</td><td>NYSE Euronext Brussels</td></tr><tr><td>XLIS</td><td>NYSE Euronext Lisbon</td></tr><tr><td>XPAR</td><td>NYSE Euronext Paris</td></tr><tr><td>XCSE</td><td>OMX Copenhagen</td></tr><tr><td>XHEL</td><td>OMX Helsinki</td></tr><tr><td>XSTO</td><td>OMX Stockholm</td></tr><tr><td>XOSL</td><td>Oslo Bors</td></tr><tr><td>XVTX</td><td>Swiss Stock Exchange</td></tr><tr><td>WBAH</td><td>Vienna Stock Exchange</td></tr></table>	XBRU	NYSE Euronext Brussels	XLIS	NYSE Euronext Lisbon	XPAR	NYSE Euronext Paris	XCSE	OMX Copenhagen	XHEL	OMX Helsinki	XSTO	OMX Stockholm	XOSL	Oslo Bors	XVTX	Swiss Stock Exchange	WBAH	Vienna Stock Exchange	
XBRU	NYSE Euronext Brussels																				
XLIS	NYSE Euronext Lisbon																				
XPAR	NYSE Euronext Paris																				
XCSE	OMX Copenhagen																				
XHEL	OMX Helsinki																				
XSTO	OMX Stockholm																				
XOSL	Oslo Bors																				
XVTX	Swiss Stock Exchange																				
WBAH	Vienna Stock Exchange																				
210	MaxShow	<p>This field illustrates the transparency of the order, valid fields should include:</p> <p>0: Dark Order &lt;INTEGER&gt;: Full order quantity.</p> <p>To enter a transparent order in the integrated environment MaxShow will need to be the full order quantity. If MaxShow tag is not included the order will default to transparent.</p> <p>Similarly if the instrument is in the dark only environment and the MaxShow tag is not included, (210=0) the order will default to dark.</p>	MTF																		
211	PegOffsetValue	<p>Mandatory if OrdType=P this tag contains the amount (signed) added to the peg for a pegged order in the context of the PegScope.</p> <p>Pegoffsetvalue &lt;0 if bid, else &gt; 0. The Peg Offset value may also be a fraction of a tick.</p>	MTF																		
293	DefBidSize	<p>This tag will provide a default bid size for all quotes contained within a mass quote message if BidSize (134) is not explicitly provided within the repeating group.</p>	MTF																		
294	DefOfferSize	<p>This tag will provide a default offer size for all quotes contained within a mass quote message if OfferSize (135) is not explicitly provided within the repeating group.</p>	MTF																		
295	NoQuoteEntries	<p>Cancelling quotes is done on an instrument level. This tag illustrates the number of instruments to be cancelled within the Mass Quote.</p>	MTF																		
296	NoQuoteSets	<p>The number of quote sets within a Mass Quote message.</p>	MTF																		
297	QuoteAckStatus	<p>Identifies the status of the quote returned on the quote acknowledgment. Valid Values:</p> <p>0 Accepted 1 Cancelled for Instrument(s) 4 Cancelled All 5 Rejected</p>	MTF																		
298	QuoteCancelType	<p>Identifies the type of quote cancel. Valid Values:</p> <p>1 Cancel for Symbol(s) 4 Cancel all quotes</p>	MTF																		
299	QuoteEntryID	<p>Uniquely identifies a single quote from part of a mass quote message.</p>	MTF																		
300	QuoteRejectReason	<p>This tag specifies the reason why a quote was rejected. Valid Values:</p> <p>1 Unknown instrument 2 Trading system not available 4 Too late to enter 5 Unknown Quote 7 Invalid bid/ask spread 8 Invalid price 9 Not authorised to quote</p>	MTF																		
305	UnderlyingIDSource	<p>Identifies the class or source of the security ID (tag 48) value. Valid Values:</p> <p>4 ISIN</p>	TQL/MTF																		
308	UnderlyingSecurityExchange	<p>Market used to help identify a security. This field is only found on the Security List and Security Definition messages.</p>	TQL/MTF																		

309	UnderlyingSecurityID	A valid ISIN	TQL/MTF																																				
311	UnderlyingSymbol	The Turquoise symbol for an instrument.	TQL/MTF																																				
318	UnderlyingCurrency	The currency of an instrument.	TQL/MTF																																				
320	SecurityReqID	Unique ID of security definition request.	TQL/MTF																																				
322	SecuritytResponseID	Unique ID of a Security Definition message.	TQL/MTF																																				
373	SessionRejectReason	<div>A code to identify the reason for the session level rejects. Valid values include:</div> <table><tr><td>0</td><td>Invalid tag number</td></tr><tr><td>1</td><td>Required tag missing.</td></tr><tr><td>2</td><td>Tag not defined for this message type.</td></tr><tr><td>3</td><td>Undefined tag</td></tr><tr><td>4</td><td>Tag specified without a value.</td></tr><tr><td>5</td><td>Value is incorrect (out of range) for this tag.</td></tr><tr><td>6</td><td>Incorrect data format for value.</td></tr><tr><td>7</td><td>Decryption problem.</td></tr><tr><td>9</td><td>CompID problem</td></tr><tr><td>10</td><td>Sending Time accuracy problem</td></tr><tr><td>11</td><td>Invalid MsgType</td></tr><tr><td>13</td><td>Tag Appears more than once.</td></tr><tr><td>14</td><td>Tag specified out of required order.</td></tr><tr><td>15</td><td>Repeating group field out of order.</td></tr><tr><td>16</td><td>Incorrect number in group count for repeating group.</td></tr><tr><td>17</td><td>Non data value includes field delimiter SOH character.</td></tr><tr><td>99</td><td>Other</td></tr><tr><td>101</td><td>Service not available at this time.</td></tr></table>	0	Invalid tag number	1	Required tag missing.	2	Tag not defined for this message type.	3	Undefined tag	4	Tag specified without a value.	5	Value is incorrect (out of range) for this tag.	6	Incorrect data format for value.	7	Decryption problem.	9	CompID problem	10	Sending Time accuracy problem	11	Invalid MsgType	13	Tag Appears more than once.	14	Tag specified out of required order.	15	Repeating group field out of order.	16	Incorrect number in group count for repeating group.	17	Non data value includes field delimiter SOH character.	99	Other	101	Service not available at this time.	TQL/MTF
0	Invalid tag number																																						
1	Required tag missing.																																						
2	Tag not defined for this message type.																																						
3	Undefined tag																																						
4	Tag specified without a value.																																						
5	Value is incorrect (out of range) for this tag.																																						
6	Incorrect data format for value.																																						
7	Decryption problem.																																						
9	CompID problem																																						
10	Sending Time accuracy problem																																						
11	Invalid MsgType																																						
13	Tag Appears more than once.																																						
14	Tag specified out of required order.																																						
15	Repeating group field out of order.																																						
16	Incorrect number in group count for repeating group.																																						
17	Non data value includes field delimiter SOH character.																																						
99	Other																																						
101	Service not available at this time.																																						
378	ExecRestatementReason	<div>If an order has been repriced i.e. a pegged order this fields informs the user of the change in price. Valid values:</div> <table><tr><td>3</td><td>Repricing of an order</td></tr></table>	3	Repricing of an order	MTF																																		
3	Repricing of an order																																						
393	TotalNumSecurities	Total number of securities.	TQL/MTF																																				
434	CxlRejectResponseTo	<div>Identifies the type of request that a Cancel Reject is in response to.</div> <table><tr><td>1</td><td>Order Cancel Request</td></tr><tr><td>2</td><td>Order Cancel replace request.</td></tr></table>	1	Order Cancel Request	2	Order Cancel replace request.	TQL/MTF																																
1	Order Cancel Request																																						
2	Order Cancel replace request.																																						
448	PartyID	The clearing member	TQL/MTF																																				
452	PartyRole	Identifies the type of role of the PartyID, valid values: 4 = clearing firm	TQL/MTF																																				
453	NoPartyIDs	Number of parties supplied. This should always be set to 1.	TQL/MTF																																				
528	OrderCapacity	<div>Designates the capacity of the firm placing the order. Valid values:</div> <table><tr><td>A</td><td>Agency</td></tr><tr><td>P</td><td>Principal</td></tr></table> <div>Default value is Agency (A).</div>	A	Agency	P	Principal	TQL/MTF																																
A	Agency																																						
P	Principal																																						
530	MassCancelRequestType	<div>Scope of order mass cancel request. valid values:</div> <table><tr><td>7</td><td>Cancel all orders for a current session.</td></tr></table>	7	Cancel all orders for a current session.	TQL/MTF																																		
7	Cancel all orders for a current session.																																						
531	MassCancelResponse	<div>Indicates the action taken by the counterparty order handling system as a result of the Cancel Request. Valid values:</div> <table><tr><td>0</td><td>Cancel request rejected.</td></tr><tr><td>7</td><td>Cancelled all orders</td></tr></table>	0	Cancel request rejected.	7	Cancelled all orders	TQL/MTF																																
0	Cancel request rejected.																																						
7	Cancelled all orders																																						
532	MassCancelRejectReason	<div>Required if MassCancelResponse = 0, specifying the reason for the order mass cancel request rejection. Valid Values:</div> <table><tr><td>0</td><td>Mass Cancel not supported.</td></tr><tr><td>2</td><td>Invalid or unknown underlying.</td></tr><tr><td>99</td><td>Other</td></tr></table>	0	Mass Cancel not supported.	2	Invalid or unknown underlying.	99	Other	TQL/MTF																														
0	Mass Cancel not supported.																																						
2	Invalid or unknown underlying.																																						
99	Other																																						
553	Username	An optional string provided on the message from the client to Turquoise.	TQL/MTF																																				

554	Password	A tag that must be populated if a username is provided on logon.	TQL/MTF						
559	SecurityListRequestType	Identifies the criteria of the security list request. Valid Values: <table><tr><td>4</td><td>All securities</td></tr><tr><td>5</td><td>Separate List Messages by Security Exchange</td></tr></table>	4	All securities	5	Separate List Messages by Security Exchange	TQL/MTF		
4	All securities								
5	Separate List Messages by Security Exchange								
560	SecurityRequestResult	Results returned from security request message. Valid values: <table><tr><td>0</td><td>Valid request</td></tr><tr><td>8</td><td>Invalid or unsupported request</td></tr><tr><td>3</td><td>No instruments found.</td></tr></table>	0	Valid request	8	Invalid or unsupported request	3	No instruments found.	TQL/MTF
0	Valid request								
8	Invalid or unsupported request								
3	No instruments found.								
561	RoundLot	The trading lot size of a security.	TQL/MTF						
562	MinTradeVol	The minimum trading volume for a security.	TQL/MTF						
584	MassStatusReqID	String value assigned by the issuer of Mass Status Request to uniquely identify the request.	TQL/MTF						
585	MassStatusReqType	The status request: valid values: <table><tr><td>1</td><td>Status of orders for an instrument.</td></tr><tr><td>7</td><td>Status for all orders</td></tr></table>	1	Status of orders for an instrument.	7	Status for all orders	TQL/MTF		
1	Status of orders for an instrument.								
7	Status for all orders								
789	NextExpectedMsgSeqNum	This field is mandatory and will contain the next expected MsgSeqNum from Turquoise.	TQL/MTF						
835	PegMoveType	Describes whether a peg is static or floats. Valid values: 1 FIXED	TQL/MTF						
836	PegOffsetType	Type of peg offset value. Valid values: 2 Ticks	TQL/MTF						
839	PeggedPrice	The current price the order is pegged at.	TQL/MTF						
840	PegScope	Required if OrdType = P and defines the scope of the peg Valid values: 1 Local (Exchange, TBB0) 3 Global (EBBO)	TQL/MTF						
851	LastLiquidityInd	This tag displays the Liquidity indicator for partially or filled executions, as well as providing an indication of whether an execution took place during auction. Valid values include: <table><tr><td>1</td><td>Passive</td></tr><tr><td>2</td><td>Aggressive</td></tr><tr><td>4</td><td>Auction</td></tr></table>	1	Passive	2	Aggressive	4	Auction	MTF
1	Passive								
2	Aggressive								
4	Auction								
9000	TestInst	Used on Security List and Security Definition messages to identify whether an instrument is a test instrument. Valid values: N Instrument is not a test instrument Y Instrument is a test instrument	TQL/MTF						
9001	LisLimit	Limit size for large in scale orders, i.e. the minimum size required for an order to be allowed to be Dark. The size of the order is calculated as the Reference price multiplied with the order quantity.	TQL/MTF						
9002	TBB0Bid	The Turquoise BBO bid price at the time when the matching engine received the order.	MTF						
9003	TBB0Ask	The Turquoise BBO ask price at the time when the matching engine received the order.	MTF						
9004	ABB0Bid	The away BBO bid price at the time when the matching engine received the order.	MTF						
9005	ABB0Ask	The away BBO ask price at the time when the matching engine received the order.	MTF						
9006	TypeOfTrade	A description of the type of trade that has occurred. This field is only displayed on execution reports with an OrdStatus of partial fill or filled. <table><tr><td>DARK_TO_DARK</td></tr><tr><td>DARK_TO_TRANSPARENT</td></tr><tr><td>TRANSPARENT_TO_TRANSPARENT</td></tr><tr><td>TRADE_REPORT</td></tr><tr><td>MANUAL_LAST_TRADE_PRICE</td></tr><tr><td>MANUAL_LAST_AUCTION_PRICE</td></tr></table>	DARK_TO_DARK	DARK_TO_TRANSPARENT	TRANSPARENT_TO_TRANSPARENT	TRADE_REPORT	MANUAL_LAST_TRADE_PRICE	MANUAL_LAST_AUCTION_PRICE	MTF
DARK_TO_DARK									
DARK_TO_TRANSPARENT									
TRANSPARENT_TO_TRANSPARENT									
TRADE_REPORT									
MANUAL_LAST_TRADE_PRICE									
MANUAL_LAST_AUCTION_PRICE									

		<div> <div>UPDATED_REFERENCE_PRICE</div> <div>TRADE_REPORT_AUCTION.</div> <div>DARK_TO_DARK_AUCTION</div> <div>DARK_TO_TRANSPARENT_AUCTION</div> <div>TRANSPARENT_TO_TRANSPARENT_AUCTION</div> </div>	
9007	TQLStrategy	<p>Indicates the dark pool aggregation strategy, when ExDestination=TQL.</p> <p>Valid Values:</p> <ol style="list-style-type: none"> <li>1 Post to Turquoise first then seek non displayed liquidity.</li> <li>2 IOC to Turquoise first then seek non displayed liquidity .</li> <li>3 Seek non displayed liquidity</li> <li>4 User Defined</li> </ol> <p>If the strategy is not defined and ExDestination(100) is set to TQL, the order is rejected.</p>	TQL
9008	TQLTimestamp	<p>Used to indicate the amount of time the order should reside at Turquoise before being routed to non-displayed liquidity pools.</p> <p>The TQLTimestamp is expressed using the UTC Timestamp. TQL Timestamp is mandatory when strategy 1 is selected, but not supported for strategy 2 or 3.</p> <p>TQLTimestamp should be less than the tag ExpireTime (126).</p>	TQL
9009	TQLSelfCrossed	<p>An indicator sent on an execution report to highlight whether an execution from a TQ-LENS order is a result of a self cross.</p> <p>Valid Values:</p> <p>0 FALSE 1 TRUE</p> <p>Note: If this tag is not present then value 0 will be the default.</p>	TQL
9010	TQLCustomisedStrategy	<p>This field is mandatory if strategy 4 is specified as tag 9007 and indicates a user specific strategy as agreed between TQ-LENS and the user.</p>	TQL
9011	TQLGrouping	<p>Optional and can be used only if strategy 1, 2, or 3 is chosen with tag 9007.</p> <p>TQLGrouping is used when TQ-LENS and one or many liquidity providers agree to group one or many liquidity providers into one distribution group.</p>	TQL
9012	TQLExecMethod	<p>With ExDestination(100) set to TQL, TQLExecMethod can be specified with the New Order Single message. TQLExecMethod indicates the type of the execution method a participant can specify for the order to be executed by TQ-LENS:</p> <p>100 Flow 200 Block</p> <p>If TQLExecMethod is not populated within the New Order Single message, the execution method defaults to the value specified by the participant FIX session. TQLExecMethod is returned as part of the acknowledgement of the order as part of an Execution Report message.</p>	TQL
9013	TQLExecFee	<p>If ExDestination 100=TQL, TQLExecFee is returned on each fill and partial fill to indicate the fee applied for each execution.</p>	TQL
9014	DPMMaxQty	<p>DPMMaxQty allows a user to specify a limit on the number of shares distributed to each dark pool liquidity provider on each sweep. DPMMaxQty can either be null or set to a value that is equal or less than the Order Quantity (tag 38).</p>	TQL
9015	IsPassive	<p>This tag is used to determine whether the quote is passive only. If set to Passive (Y) and a quote crosses an existing bid or offer (trades aggressively) then the quote will be rejected. Valid values:</p>	MTF

		Y Passive Only Quote N Passive Or Aggressive  If this tag is not populated then by default it will be N.	
--	--	---	--

## 6. Order State Change Matrices

Below are example FIX messages accepted by the Turquoise FIX gateway.

### 6.1 Limit Day Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	157	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
SenderSubID(50)	GH6781	
OnBehalfOfCompID(115)	ZXS234	
MsgSeqNum(34)	2	
SendingTime(52)	20080325-07:40:15	
ClOrdID (11)	123485624-31042208	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	2 (Work)	
Side (54)	1 (Buy)	
OrderQty (38)	1000	
OrdType (40)	2 (Limit)	
Price (44)	200 (Mandatory)	
TimeInForce (59)	8 (Good From next automatch)	
MaxShow (210)	1000	
ExDestination (100)	MTF	
OrderCapacity(528)	P	
TransactTime (60)	20080325-10:05:15	
NoPartyIDs (453)	1	
PartyID (448)	RTY	
PartyRole (452)	4	
Checksum(10)	088	

### 6.2 TQ-LENS Order Strategy 1

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	157	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
SenderSubID(50)	GH6781	
OnBehalfOfCompID(115)	ZXS234	
MsgSeqNum(34)	2	
SendingTime(52)	20080325-07:40:15	
ClOrdID (11)	123485624-31042208	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	<Valid Currency>	
ExecInst (18)	2 (Work) X (Exclude Self)	
Side (54)	1 (Buy)	
OrderQty (38)	1000	
OrdType (40)	P	
Price (44)	(Optional)	
TimeInForce (59)	0 (Day)	

Sequence	1	2
ExDestination (100)	TQL	
OrderCapacity(528)	P	
TransactTime (60)	20090325-10:05:15	
NoPartyIDs (453)	1	
PartyID (448)	RTY	
PartyRole (452)	4	
TQLStrategy (9007)	1	
TQLTimestamp (9008)	20090325-11:06:30	
TQLExecMethod (9012)	100 or 200	
Checksum(10)	088	

## 6.3 TQ-LENS Order Strategy 2

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	157	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
SenderSubID(50)	GH6781	
OnBehalfOfCompID(115)	ZXS234	
MsgSeqNum(34)	2	
SendingTime(52)	20080325-07:40:15	
ClOrdID (11)	123485624-31042208	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	<Valid Currency>	
ExecInst (18)	2 (Work) X (Exclude Self)	
Side (54)	1 (Buy)	
OrderQty (38)	1000	
OrdType (40)	P	
Price (44)	(Optional)	
TimeInForce (59)	0 (Day)	
ExDestination (100)	TQL	
OrderCapacity(528)	P	
TransactTime (60)	20090325-10:05:15	
NoPartyIDs (453)	1	
PartyID (448)	RTY	
PartyRole (452)	4	
TQLStrategy (9007)	2	
TQLExecMethod (9012)	100 or 200	
Checksum(10)	088	

## 6.4 TQ-LENS Order Strategy 3

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	157	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
SenderSubID(50)	GH6781	
OnBehalfOfCompID(115)	ZXS234	
MsgSeqNum(34)	2	
SendingTime(52)	20080325-07:40:15	
ClOrdID (11)	123485624-31042208	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	<Valid Currency>	
ExecInst (18)	2 (Work) X (Exclude Self)	
Side (54)	1 (Buy)	
OrderQty (38)	80000	
OrdType (40)	P	
Price (44)	(Optional)	



Sequence	1	2
TimeInForce (59)	0 (Day)	
ExDestination (100)	TQL	
OrderCapacity(528)	P	
TransactTime (60)	20090325-10:05:15	
NoPartyIDs (453)	1	
PartyID (448)	RTY	
PartyRole (452)	4	
TQLStrategy (9007)	3	
TQLExecMethod (9012)	100 or 200	
DPMMaxQty (9014)	15000	
Checksum(10)	088	

## 6.5 Limit Dark Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	156	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
OnBehalfOfCompID(115)	ASD987	
OnBehalfOfSubID (116)	A9838832834	
MsgSeqNum(34)	9	
SendingTime(52)	20080320-11:05:15	
ClOrdID (11)	545795999-31121408	
Symbol(55)	VODI	
ExecInst (18)	2 (Work)	
Side (54)	1 (Buy)	
OrderQty (38)	300000	
OrdType (40)	2 (Limit)	
Price (44)	500 (Mandatory)	
TimeInForce (59)	0 (Day)	
MaxShow (210)	0 (Dark)	
ExDestination (100)	MTF	
OrderCapacity(528)	A	
TransactTime (60)	20080320-11:05:15	
NoPartyIDs (453)	1	
PartyID (448)	DSEW	
PartyRole (452)	4	
Checksum(10)	088	

## 6.6 Market Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	166	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
SenderSubID(50)	SDF345	
OnBehalfOfCompID(115)	DFE4567	
OnBehalfOfSubID (116)	GHJU1243	
MsgSeqNum(34)	10	
SendingTime(52)	20080325-12:58:38	
ClOrdID (11)	54522224-31021408	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
Side (54)	1 (Buy)	
OrderQty (38)	600	
OrdType (40)	1 (Market)	
Price (44)	0 (No price)	
TimeInForce (59)	0	
MaxShow (210)	600	

# TURQUOISE

Sequence	1	2
OrderCapacity(528)	A	
TransactTime (60)	20080325-12:58:38	
NoPartyIDs (453)	1	
PartyID (448)	BGT	
PartyRole (452)	4	
Checksum(10)	255	

## 6.7 Fill or Kill

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	166	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	15	
SendingTime(52)	20080325-14:58:38	
ClOrdID (11)	56890135645-31083108	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	2 (Work)	
Side (54)	1 (Buy)	
OrderQty (38)	100	
OrdType (40)	2 (Limit)	
Price (44)	200	
TimeInForce (59)	4 (Fill or Kill)	
TransactTime (60)	20080325-14:58:38	
ExDestination (100)	MTF	
OrderCapacity(528)	P	
NoPartyIDs (453)	1	
PartyID (448)	REW	
PartyRole (452)	4	
Checksum(10)	097	

## 6.8 Fill and Kill

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	166	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	28	
SendingTime(52)	20080325-11:58:38	
ClOrdID (11)	67489217834937-12040308	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	2 (Work) Q (Cxl On Disconnect)	
Side (54)	1 (Buy)	
OrderQty (38)	10000	
OrdType (40)	2 (Limit)	
Price (44)	200	
TimeInForce (59)	3 (Fill and Kill)	
MaxShow (210)	10000	
ExDestination (100)	MTF	
TransactTime (60)	20080325-11:58:38	
OrderCapacity(528)	P	
NoPartyIDs (453)	1	
PartyID (448)	YER	
PartyRole (452)	4	
Checksum(10)	080	

## 6.9 Limit Good From Time Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	166	
MsgType(35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
OnBehalfOfCompID(115)	SD23546	
MsgSeqNum(34)	11	
SendingTime(52)	20080325-14:58:38	
ClOrdID (11)	823819364-12100108	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	2 (Work)	
Side (54)	1 (Buy)	
OrderQty (38)	4600	
OrdType (40)	2 (Limit)	
Price (44)	200 (Mandatory)	
TimeInForce (59)	0 (Day)	
TransactTime (60)	20080325-14:58:38	
EffectiveTime (168)	20080325-15:58:38	
OrderCapacity(528)	A	
NoPartyIDs (453)	1	
PartyID (448)	REW	
PartyRole (452)	4	
Checksum(10)	090	

## 6.10 Limit Good Till Time Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	300	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
SenderSubID(50)	KO9864	
OnBehalfOfCompID(115)	DF3445	
MsgSeqNum(34)	16	
SendingTime(52)	20080325-13:14:35	
ClOrdID (11)	658934758693-31120408	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	2 (Work) Q (Cxl On Disconnect)	
Side (54)	1 (Buy)	
OrderQty (38)	100	
OrdType (40)	6	
Price (44)	200 (Mandatory)	
TimeInForce (59)	0 (Day)	
TransactTime (60)	20080325-13:14:35	
ExpireTime (126)	20080325-16:14:35	
OrderCapacity(528)	P	
NoPartyIDs (453)	1	
PartyID (448)	WQE	
PartyRole (452)	4	
Checksum(10)	070	

## 6.11 Pegged against TBBO

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	196	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
OnBehalfOfCompID(115)	DER456	
MsgSeqNum(34)	18	
SendingTime(52)	20080325-14:58:38	
ClOrdID (11)	5648901478932-31043108	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	P (Market)	
Side (54)	1 (Buy)	
OrderQty (38)	100	
OrdType (40)	P (Pegged)	
Price (44)	200 (Mandatory)	
TimeInForce (59)	0 (Day)	
TransactTime (60)	20080325-14:58:38	
PegOffsetValue (211)	-10 (must be < 0)	
PegMoveType (835)	1 (Fixed)	
PegOffsetType (836)	2 (Ticks)	
PegScope (840)	1 (Local)	
OrderCapacity(528)	A	
NoPartyIDs (453)	1	
PartyID (448)	RQW	
PartyRole (452)	4	
Checksum(10)	211	

## 6.12 Dark Order Pegged against EBBO

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	196	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	9	
SendingTime(52)	689279874575467-31061208	
ClOrdID (11)	1	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	M (Mid price) Q (Cxl On Disconnect)	
Side (54)	1 (Buy)	
OrderQty (38)	1000000	
OrdType (40)	P (Pegged)	
Price (44)	200 (Mandatory)	
TimeInForce (59)	0 (Day)	
MaxShow (210)	0	
TransactTime (60)	20080325-11:58:01	
PegOffsetValue (211)	-10 (must be < 0)	
PegMoveType (835)	1 (Fixed)	
PegOffsetType (836)	2 (Ticks)	
PegScope (840)	3 (Global)	

Sequence	1	2
OrderCapacity(528)	P	
NoPartyIDs (453)	1	
PartyID (448)	WQA	
PartyRole (452)	4	
Checksum(10)	665	

## 6.13 Iceberg Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	173	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	32	
SendingTime(52)	20080320-08:58:05	
ClOrdID (11)	5784306789237-12051408	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
Side (54)	1 (Buy)	
OrderQty (38)	100000	
OrdType (40)	2 (Limit)	
Price (44)	200 (Mandatory)	
TimeInForce (59)	0 (Day)	
MaxFloor (111)	5000	
TransactTime (60)	20080320-08:58:05	
OrderCapacity(528)	P	
NoPartyIDs (453)	1	
PartyID (448)	XZA	
PartyRole (452)	4	
Checksum(10)	135	

## 6.14 Pegged TBBO Iceberg Order

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	190	
MsgType (35)	D	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	80	
SendingTime(52)	20080316-08:58:05	
ClOrdID (11)	6546756768-31041208	
Symbol(55)	[N/A]	
SecurityIDSource (22)	4	
SecurityID (48)	<valid ISIN>	
Currency (15)	GBX	
ExecInst (18)	P (Market) Q (Cxl On Disconnect)	
Side (54)	1 (Buy)	
OrderQty (38)	1000000	
OrdType (40)	P (Pegged)	
Price (44)	200 (Mandatory)	
TimeInForce (59)	0 (Day)	
MaxFloor(111)	6000	
TransactTime (60)	20080316-08:58:05	
PegOffsetValue (211)	-10 (must be < 0)	
PegMoveType (835)	1 (Fixed)	
PegOffsetType (836)	2 (Ticks)	
PegScope (840)	1 (Local)	
OrderCapacity(528)	P	
NoPartyIDs (453)	1	
PartyID (448)	QALS	
PartyRole (452)	4	
Checksum(10)	148	

## 6.15 Mass Cancel Request

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	100	
MsgType (35)	q	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	22	
SendingTime(52)	20080316-08:58:05	
ClOrdID (11)	156476586785- 311208	
MassCancelRequestType (530)	7	
TransactTime (60)	20080316-08:58:05	
Text (58)		
Checksum(10)	112	

## 6.16 Order Mass Status Request

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	200	
MsgType (35)	AF	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	34	
SendingTime(52)	20080322-08:58:05	
ClOrdID (11)	5313645689- 311208	
MassStatusReqID (584)	1246758	
MassStatusReqType (585)	7 (All Instruments)	
TransactTime (60)	20080316-08:58:05	
Text (58)		
Checksum(10)	120	

## 6.17 Mass Quote

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	157	
MsgType(35)	i	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	1	
SendingTime(52)	20080325-10:05:15	
QuoteID (117)	20090102-17:03:41-22189	
TransactTime (60)	20080325-10:05:15	
NoQuoteSets (296)	2	
QuoteEntryID (299)	464196CM406TqNzu8d	
Symbol(55)	VOD1	
BixPx (132)	15	
OfferPx (133)	15.5	
BidSize (134)	10000	
OfferSize (135)	20000	
IsPassive (9010)	N	
QuoteEntryID (299)	460146CA90A4vVTRUnw	
Symbol(55)	GSK1	
BixPx (132)	21	
OfferPx (133)	25	
BidSize (134)	35000	
OfferSize (135)	45000	
IsPassive (9010)	Y	
Checksum(10)	080	

## 6.18 Security List Request

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	62	
MsgType (35)	x	
SenderCompID (49)	Client	TTS
TargetCompID (56)	TTS	Client
MsgSeqNum(34)	12	
SendingTime(52)	20080316-12:58:05	
SecurityReqId (320)	1	
SecurityListRequestType (559)	4 (All)	
Checksum(10)	057	

## 6.19 News (Unsolicited Broadcast)

Sequence	1	2
BeginString(8)	4.4	
BodyLength(9)	20	
MsgType (35)	B	
SenderCompID (49)	TTS	Client
TargetCompID (56)	Client	TTS
MsgSeqNum(34)	12	
TransactTime (60)	20080316-08:58:05	
Headline(148)	1466/DPBGN_DE.TQ WIDE @ 15:52:28	
Checksum(10)	057	