

Introduction to Snowflake SQL

INTRODUCTION TO SNOWFLAKE SQL



George Boorman

Senior Curriculum Manager, DataCamp

Connecting to Snowflake

- Snowsight: Snowflake Web Interface

The screenshot displays the Snowflake Snowsight web interface. On the left, a sidebar shows the 'Databases' tab selected, with a tree view of the database structure. The 'PIZZA_SALES' database is expanded, showing the 'PUBLIC' schema and a list of tables: 'ORDERS', 'ORDERS_FILTERED', 'ORDER_DETAILS', 'PIZZAS', and 'PIZZA_TYPE'. The 'ORDERS_VIEW' is also visible under the 'Views' section. The main area shows a worksheet named 'test_worksheet' with a SQL query: `select :datebucket(created), count(1) from table group by 1`. Below the query, the 'Results' tab is active, displaying a table with 5 columns: 'C_CUSTOMER_SK', 'C_CUSTOMER_ID', 'C_CURRENT_CDEMO_SK', 'C_CURRENT_', and 'C_CURRENT_'. The table contains 4 rows of data.

	C_CUSTOMER_SK	C_CUSTOMER_ID	C_CURRENT_CDEMO_SK	C_CURRENT_	C_CURRENT_
1	68,459,673	AAAAAAAAAJJMJEBA	1,323,178		
2	68,459,674	AAAAAAAKJMJEBEA	1,828,933		
3	68,459,675	AAAAAAAALJMJEBEA	404,253		
4	68,459,676	AAAAAAAAMJMJEBEA	145,624		

INTRODUCTION TO SNOWFLAKE SQL

Notebooks

+

🏠

🔍

<

Notebooks

2025-02-13 11:37am ▾

Files

Databases

Connect Git Repository

2025-02-13 11:37am

🔍 Search

+

notebook_app.ipynb

...

Packages ▾

• Active ▾

▶ Run all

⋮

Python ▾ as cell1 •

1

Import python packages

2

import pandas as pd

3

4

We can also use Snowpark for our analyses!

5

from snowflake.snowpark.context import import get_active_session

6

session = get_active_session()

7

SQL ▾ as cell2

1.3s ▶ ☰ ⋮

1

-- Welcome to Snowflake Notebooks!

2

-- Try out a SQL cell to generate some data.

3

SELECT *

4

FROM course_read_33509_prod.pizza.pizzas

	PIZZA_ID	PIZZA_TYPE_ID	PIZZA_SIZE	PRICE
0	bbq_ckn_s	bbq_ckn	S	12.75
1	bbq_ckn_m	bbq_ckn	M	16.75
2	bbq_ckn_l	bbq_ckn	L	20.75
3	cali_ckn_s	cali_ckn	S	12.75
4	cali_ckn_m	cali_ckn	M	16.75
5	cali_ckn_l	cali_ckn	L	20.75

• cell1

cell2

Connecting to Snowflake: Drivers

Drivers & Connectors

- ODBC (Open Database Connectivity)
- JDBC (Java Database Connectivity)
- Connectors : Python, Spark, and more

¹ <https://docs.snowflake.com/en/developer-guide/drivers>

Connecting to Snowflake: Snowflake CLI

Snowflake CLI

- Command-line client
 - Installed on Linux, Windows, or Mac

¹ <https://docs.snowflake.com/en/user-guide/snowsql>

SQL flavors

- Snowflake uses Snowflake SQL
- Other popular SQL flavors:
 - PostgreSQL
 - T-SQL
 - MySQL
- Some differences in data types, functions, and general syntax

Common syntax

- `SELECT`
- `FROM`
- `WHERE`
- `GROUPBY`
- `ORDER BY`
- `AVG()` , `COUNT()` , `SUM()` (etc)
- `DISTINCT`
- `HAVING`
- `JOIN *`

*Some differences exist, more on this later!

Let's practice!

INTRODUCTION TO SNOWFLAKE SQL

Snowflake SQL data types

INTRODUCTION TO SNOWFLAKE SQL



George Boorman

Senior Curriculum Manager, DataCamp

Common data types

Category	Data types
Text/string	<code>VARCHAR</code> , <code>CHAR</code> , <code>TEXT</code>

Common data types

Category	Data types
Text/string	<code>VARCHAR</code> , <code>CHAR</code> , <code>TEXT</code>
Numeric	<code>INTEGER</code>

Common data types

Category	Data types
Text/string	<code>VARCHAR</code> , <code>CHAR</code> , <code>TEXT</code>
Numeric	<code>INTEGER</code>
Boolean	<code>BOOLEAN</code>

Common data types

Category	Data types
Text/string	<code>VARCHAR</code> , <code>CHAR</code> , <code>TEXT</code>
Numeric	<code>INTEGER</code>
Boolean	<code>BOOLEAN</code>
Date/time	<code>DATE</code> , <code>TIME</code> , <code>TIMESTAMP</code>

¹ <https://docs.snowflake.com/en/sql-reference/intro-summary-data-types>

Snowflake SQL data types - NUMBER

`NUMBER(p, s)`

- `NUMERIC` works in Snowflake as an alias for `NUMBER`
- `p` = precision; `s` = scale
- Max `p` and `s` values: 38
 - Exceeding will cause rounding!

Snowflake SQL data types - TIMESTAMP_LTZ


- `TIMESTAMP_LTZ`
 - Combines `DATE` and `TIME` with local time zone
 - Format: `YYYY-MM-DD HH:MI:SS`

```
CREATE TABLE orders (  
  -- Timestamp with local time zone  
  order_timestamp TIMESTAMP_LTZ  
)
```

	ORDER_TIMESTAMP
1	2015-01-01 11:38:36.000 -0800
2	2015-01-01 11:57:40.000 -0800
3	2015-01-01 12:12:28.000 -0800
4	2015-01-01 12:16:31.000 -0800
5	2015-01-01 12:21:30.000 -0800

Data type conversion - What?

- Converting data from one type to another



Data type conversion - Why?

- Improving performance
- Data accuracy and consistency
- Data quality

Data type conversion - How?

1. CAST Syntax:

- `CAST( <source_data/column> AS <target_data_type> )`
- `CAST('80' AS INT)`

2. :: Syntax:

- `<source_data/column>::<target_data_type>`
- `'80'::INT`

CAST

```
SELECT CAST(order_timestamp AS DATE)
       AS order_date
FROM orders
```

CAST results

	ORDER_TIMESTAMP
1	2015-01-01 11:38:36.000 -0800
2	2015-01-01 11:57:40.000 -0800
3	2015-01-01 12:12:28.000 -0800
4	2015-01-01 12:16:31.000 -0800
5	2015-01-01 12:21:30.000 -0800

	ORDER_DATE
1	2015-01-01
2	2015-01-02
3	2015-01-03
4	2015-01-04
5	2015-01-05

Conversion functions

- Examples: `TO_VARCHAR` , `TO_DATE` , etc.

`TO_VARCHAR`

- `TO_VARCHAR( <expr> )`
 - `expr` - numeric, timestamp, etc.
 - Result: `VARCHAR`

Example:

```
SELECT TO_VARCHAR(86)
```

Result:

```
86
```

Checking data types

```
DESC TABLE orders
```

name	type	kind	null?	default	primary key
ORDER_ID	NUMBER(38,0)	COLUMN	N	null	Y
ORDER_DATE	DATE	COLUMN	Y	null	N
ORDER_TIME	TIME(9)	COLUMN	Y	null	N

Let's practice!

INTRODUCTION TO SNOWFLAKE SQL

Functions, sorting, and grouping

INTRODUCTION TO SNOWFLAKE SQL



George Boorman

Senior Curriculum Manager, DataCamp

String functions - INITCAP

Syntax: `INITCAP( <expr> )`

- Capitalize each word in a string

```
SELECT INITCAP(category) AS capitalized_category
FROM pizza_type
```

<u>A</u> CAPITALIZED_NAMES
The Barbecue Chicken Pizza
The California Chicken Pizza
The Chicken Alfredo Pizza
The Chicken Pesto Pizza

String functions - CONCAT

- Combines the expressions

Syntax:

```
CONCAT( <expr1> [ , <exprN> ... ] )
```

Before Concat:

CATEGORY
Chicken
Classic
Supreme
Veggie

- Combining `category` with `' - Pizza'`

```
SELECT CONCAT(category, ' - Pizza')  
  AS pizza_category  
FROM pizza_type
```

After Concat:

PIZZA_CATEGORY
Chicken - Pizza
Classic - Pizza
Supreme - Pizza
Veggie - Pizza

DATE & TIME functions

- `CURRENT_DATE()` or `CURRENT_DATE`
- `CURRENT_TIME()` or `CURRENT_TIME`

```
SELECT CURRENT_DATE
```

```
SELECT CURRENT_TIME
```

CURRENT_DATE
2023-08-15

CURRENT_TIME
13:35:58

EXTRACT

Syntax

- `EXTRACT( <date_or_time_part> FROM <date_or_time_expr> )`
 - `<date_or_time_part>` - `year`, `month`, `day`, `weekday`, etc.

```
SELECT EXTRACT(MONTH FROM order_date) AS order_month,  
       COUNT(*) AS num_orders  
FROM orders  
GROUP BY order_month
```

# ORDER_MONTH	# NUM_ORDERS
1	1845
2	1685
3	1840

SORTING and GROUPING

- SORTING: ORDER BY
- GROUPING: GROUP BY
 - Snowflake: GROUP BY ALL

GROUP BY ALL

- GROUP BY column1, column2

SELECT

```
    pizza_type_id,  
    size,  
    AVG(price) AS average_price
```

FROM

```
    pizzas
```

GROUP BY

```
    pizza_type_id, -- explicit columns  
    size
```

ORDER BY

```
    pizza_type_id, average_price DESC
```

- GROUP BY ALL

SELECT

```
    pizza_type_id,  
    size,  
    AVG(price) AS average_price
```

FROM

```
    pizzas
```

GROUP BY ALL -- Don't specify columns

ORDER BY

```
    pizza_type_id, average_price DESC
```


Summary

Function/keyword	Use
<code>INITCAP()</code>	Capitalize each word in a string
<code>CONCAT()</code>	Combine multiple strings
<code>CURRENT_DATE</code>	Get the current date
<code>CURRENT_TIME</code>	Get the current time
<code>EXTRACT</code>	Pull a date/time element, e.g., <code>month</code> from a date
<code>ORDER BY</code>	Sort query results
<code>GROUP BY ALL</code>	Group query by all (non-aggregated) columns

Let's practice!

INTRODUCTION TO SNOWFLAKE SQL