



# Soft Touch Relay Bypass

version 1.4

[mas-effects.com/relay-bypass/](http://mas-effects.com/relay-bypass/)


Documentation for earlier versions: **V1.3**, **V1.2**

## Introduction

Typical 3PDT latching mechanical switches are noisy, hard to press, and prone to mechanical failure after repeated use. A controller board with a relay is a great alternative, and provides some other really great options you couldn't otherwise do.

This tiny and featureful relay bypass board can do a LOT.

- Soft touch, momentary switches can toggle your DIY guitar pedal, using a relay to provide true bypass.
- Quick tap to switch between engaged and bypass, or hold the foot switch to temporarily toggle until you release it
- Fits easily in a tiny 1590A enclosure
- Optional optocoupler muting can be enabled with a switch or jumper to mute any popping your circuit might exhibit while switching
- Hold when powering on to toggle auto-on/auto-off
- Passes signal when powered off



## Usage Instructions

**Engage / Bypass:** When bypassed, the sound signal will go directly from your input to your output jacks. Tap the foot switch to engage the effect and route the signal to your audio PCB. When engaged, tap the foot switch again to switch to bypass.





**Temporary Bypass/Engage:** Holding the foot switch while the effect is engaged will temporarily bypass it, and it will re-engage when you lift your foot. Similarly, holding the foot switch while bypassed will temporarily engage it.

**Auto-on:** When you supply power to your pedal, it will either engage or bypass. If you want to toggle which setting is enabled when powered up, hold the foot switch down while you plug in the power. The LED (if used) will blink to indicate the *auto-on* setting was changed. If you unplug then power up your pedal again, it should now start in your desired setting.

# Bill of Materials

Quantity	Name	Designator	Note
1	FTR-B4C	K1	FTR-B4CB4.5Z (latching)
1	TLP222G	U1	Optional
1	ATTINY13	U2	Requires programming. Pre-programmed if purchased
1	78L05	U4	
1	100u	C3	Electrolytic
2	100n	C2,C1	Pre-soldered, SMD
1	2.2K	R2	Pre-soldered, SMD
		J1	Connect J1 pads to enable pop-suppressing mute
1	Switch	SW	SPST normally open momentary switch

## Schematic



# Build Notes

Assembly should be straightforward, but contact me if you'd like a detailed build doc <[mark@mas-effects.com](mailto:mark@mas-effects.com)>.

## Hookup

- **BO** (*Board Output*): Connect this to the "Output" of your audio PCB
- **BI** (*Board Input*): Connect this to the "Input" of your PCB
- **JO** (*Jack Output*): Connect this to the tip of your Output jack
- **JI** (*Jack Input*): Connect this to the tip of your Input jack
- **LED**: Supplies 5V when effect is engaged. See "Adding an LED" below.
- **J1**: These two pads can be connected to enable Optocoupler Muting
- **AG**: See "Audio Ground / Digital Ground" below
- **GND**: Connect this with all the other ground points of your pedal
- **SW1, SW2**: Connect these to the two lugs of a SPST, normally open, momentary foot switch
- **9V**: Connect to your 9V power supply

## Optocoupler Muting

By default, no muting is done.

However, you may find you have a noisy audio circuit that tends to pop when engaged or disengaged. When this occurs you can add the optional U1 optocoupler and connect the J1 jumper pads to temporarily mute (~35ms) when engaging and bypassing.

You can either directly connect them with a wire or solder, or use a switch. If you use a switch please note that this setting is only checked when the board is first powered up.

## Adding an LED

The LED solder pad (*or pin 3 of v1 - see below*) supplies 5V when the effect is engaged. You can use this to control or directly power your LED.

Look at the schematic above to see 2 options for hooking up an LED.

For a single, low-to-moderate current LED you can simply connect an LED in series with a resistor to this pad, and run the other side to GND. This is illustrated in "Option 2" of the schematic.

Because the power from this is supplied by the 78L05 voltage regulator, it is not suitable if you need more than a small amount of current or if you want higher than 5V. In this scenario you can use a common transistor to switch one or more LEDs as shown in "Option 1" in the schematic.

## Audio Ground / Digital Ground

The *AG* and *GND* pads on the PCB are connected, and are all part of the ground. You can simply use the *AG* as an additional *GND* pad if you'd like.

If, however, you want to separate your audio and digital grounds, e.g. because you're joining them elsewhere in your pedal, then carefully cut the trace between the *AG* and *GND* pads. There is a small line drawn in the silk layer showing where to cut. Then solder wires between these pads and your other grounding points.

### v1.3 Considerations

Version 1.3 required the RESET pin of the ATtiny to be changed to an IO pin, requiring fuse bits to be set. After doing this the microcontroller cannot be reprogrammed.

### Non-latching version (v1.2)

Earlier versions use a non-latching relay, so if you'd prefer a non-latching relay or want to avoid using the RESET pin for GPIO (see below), then consider using the earlier versions.