
Teacher Reference - The SpriteGame Library

What's inside the toolbox, for the person teaching from it.



This part of the book is for teachers. The chapters treat SpriteGame as a magic toolbox, on purpose: Guiding Principle 5 says students *"call methods the way they push buttons on a machine,"* and the button works. This reference opens the box. It documents every class and every public member, it shows how `Sprite` works on the inside, and it explains why the course builds every student class on `Blob`, along with what that choice costs.

Every behavior this reference describes was run against the library as it is in this repository, `library/SpriteGame.jar`, with Processing 4.5.2. The checks are in `lessons/chapters/planning/verify_api.sh`, and the messages and numbers below are what they printed. The generated Javadoc is in the repository too, under `reference/`.

It does it in five parts.

Part	What it covers
One	**The shape of the library.** The family tree, and where the students' classes hang on it.
Two	**`Sprite`, the base.** Its fields, its movement, and the vectors it hands out.
Three	**`Blob`, and why the course builds on it.** What the choice buys, and what it costs.
Four	**The rest of the family.** `Block`, `ImageSprite`, `CompoundSprite`, `AnimatedSprite`, `Vector2D`, `ScreenBehavior`, `Event`.
Five	**Known issues.** Every rough edge found, with a suggested fix.

Part One - The shape of the library

R.1 The family tree

```
Sprite  (abstract:  pos, vel, move(), followMouse(), keyboardControl(),
distanceTo())
 |
 +-- Blob  (radius, myColor, collidesWith(Blob), a circle for drawSprite())
 |    |
 |    +-- Block  (w, h, a rectangle for drawSprite())
 |    |
 |    +-- the students' classes:  MyCharacter, Cloud, MyImageCharacter,
MyCharacterFrame
 |
 +-- ImageSprite  (a picture, with a size and a rotation)
 |
 +-- CompoundSprite  (a list of child sprites, moved together)
      |
      +-- AnimatedSprite  (shows one child at a time, as a flipbook)

Helpers:  Vector2D (a pair of floats), ScreenBehavior (an enum), Event
(callbacks)
```

Everything a student puts on the screen, from Chapter 1's first circle to Chapter 7's game, is a `Blob` or a subclass of one. `ImageSprite` and `AnimatedSprite` arrive only in Bonus A and Bonus C. `CompoundSprite`, `Vector2D` by name, and `Event` appear in this reference alone.

R.2 How a student class fits

A class in a Processing tab is compiled as a nested class inside the sketch. That explains three things students do without knowing why.

- **Why they pass `this`.** Library classes live in their own package, so they reach the sketch only through a reference to it. Every constructor takes the `PApplet` and keeps it in `parent`. The handshake in Chapter 2, `super(p, x, y, 30, color(...))`, passes it up.
- **Why `MyCharacter` can call `fill()` directly, and the library calls `parent.fill()`.** A nested class can call the sketch's methods as its own. `MyImageCharacter` in Bonus A uses `parent.image(...)`, which works too. Both styles appear in the course, and both are correct.
- **Why `pos.x` works in a student's `drawSprite()`.** `pos` is `protected` in `Sprite`, so any subclass, including a nested class in a tab, can use it.

Part Two - `Sprite`, the base

R.3 Fields

Field	Type	Notes
`parent`	`PApplet` (`protected`)	the sketch. Used for drawing, `width`, `height`, `mouseX`, `mouseY`, `keyCode`.
`pos`	`Vector2D` (`protected`)	the sprite's position. For a `Blob` it's the center; for a `Block` it's the top-left corner.
`vel`	`Vector2D` (`protected`)	pixels per frame. Every constructor without a velocity starts it at `(0, 0)`.
`screenBehavior`	`ScreenBehavior` (`public static`)	what `move()` does at the window's edges. One setting, shared by every sprite. See R.12.

R.4 Constructors

Constructor	Notes
`Sprite(PApplet parent, float x, float y)`	velocity `(0, 0)`
`Sprite(PApplet parent, float x, float y, float dx, float dy)`	with a velocity
`Sprite(PApplet parent, Vector2D s)`	stores `s` itself as the position, so the caller's vector and the sprite's position are the same object. See R.7.

`Sprite` is `abstract`, so these are only ever called through `super(...)`.

R.5 Moving

Method	What it does
`move()`	`pos = pos.add(vel)`, which builds a new vector every frame, and then applies `screenBehavior` to the center.
`moveTo(float x, float y)`	sets `pos.x` and `pos.y` **in place**.
`moveTo(Vector2D p)`	stores `p` itself as the position. See R.7.
`setVelocity(float dx, float dy)`	sets `vel.x` and `vel.y` **in place**.
`setVelocity(Vector2D v)`	stores `v` itself as the velocity. See R.7.
`getPosition()`, `getVelocity()`	hand back the sprite's own vectors, not copies. See R.7.
`distanceTo(Sprite other)`	center to center: `pos` to `pos`. For a `Block`, that's its corner.
`drawSprite()`	`abstract`. Every subclass supplies one.

`move()` is the only method that looks at the window's edges. `followMouse()` and `moveTo()` skip them entirely, so a character steered by the mouse can be parked anywhere, edges included, whatever `screenBehavior` says.

Wrapping is by the **center**. When the center crosses an edge, the position jumps by the window's width or height in one frame. So half a character hangs off the edge before it wraps, and then the whole character pops across. Chapter 3 shows the stripe this makes.

R.6 The two input methods

`keyboardControl()` is a `switch` on `parent.keyCode`:

Key	Velocity
UP	`(0, -5)`
DOWN	`(0, 5)`
LEFT	`(-5, 0)`
RIGHT	`(5, 0)`
any other key	`(0, 0)`

Three consequences, all verified, and all taught in Chapter 4. The speed is always 5, whatever `setVelocity()` said. Movement is locked to one axis: UP sets `x` to zero. And every key that isn't an arrow is a brake, including Shift and the space bar. It reads `keyCode`, so it belongs in

`keyPressed()`. Called from `draw()`, it reapplies the last key's velocity every frame, and before any key has been pressed `keyCode` is 0, the `default` case, so the sprite sits still.

`followMouse()` is the other kind of control:

```
float speed = vel.mag();
Vector2D mLoc = new Vector2D(parent.mouseX, parent.mouseY);
Vector2D mDir = mLoc.subtract(pos);
pos = pos.add(mDir.unitVector().scale(speed));
```

It steps the **size** of the velocity straight toward the mouse, every frame, and leaves `vel` alone. So the velocity's direction is ignored: `(5, 0)`, `(0, 5)`, `(3, 4)` and `(-3, -4)` give byte-identical frames. A zero velocity is a zero step, which is why Chapter 4's Watch out says to set one. Within one step of the mouse it overshoots, and jitters back and forth by up to the speed.

It has one real bug. When the sprite lands **exactly** on the mouse, `mDir` is `(0, 0)`, `unitVector()` divides by zero, and the position becomes `(NaN, NaN)`. Every later step adds to NaN and gets NaN, so the sprite is gone for good:

```
frame 49:  pos = (596.0, 300.0)
frame 50:  pos = (600.0, 300.0)
frame 51:  pos = (NaN, NaN)
```

In a classroom it's exceedingly rare. The sprite has to land on the mouse exactly: level with it, a whole number of steps away, with the mouse held perfectly still the whole way. A hand on a real mouse doesn't do that. A test script can, and this book's screenshots hit it once that way, in Chapter 5, with a scripted mouse parked 200 pixels straight right of a player moving at 4. It's here so that a vanished sprite has an explanation, if you ever see one. The fix is in Part Five.

Calling `followMouse()` and `move()` together doesn't jitter. `followMouse()` pulls the sprite 4 toward the mouse, and `move()` pushes it `vel`, which is still `(4, 0)`. The two cancel where *toward the mouse* points straight left, so the sprite parks on the mouse's row, just to its right, and stays perfectly still. Chapter 4 shows it, and the Lesson 4 Mouse Group page has students try it on purpose.

R.7 The vectors it hands out

`Vector2D`'s own documentation says *"Every method returns a new Vector2D rather than changing the original."* That's true of `Vector2D`'s methods. It isn't true of the sprites that have them. `x` and `y` are public, `Sprite` changes them in place, and it hands its own vectors out. So two names can end up meaning one vector, and changing it through one name changes it through the other. Verified:

You write	What happens
`Vector2D p = a.getPosition(); p.x = 500;`	`a` moves to `x = 500`
`b.setVelocity(v); c.setVelocity(v);`, then `b.keyboardControl()` with UP	`c`'s velocity is `(0, -5)` too
`d.moveTo(spot); e.moveTo(spot);`, then `d.moveTo(50, 60)`	`e` moves to `(50, 60)` as well
the same, then `d.move()` and `d.moveTo(70, 80)`	`e` stays at `(50, 60)`: `move()` built `d` a new vector, and the sharing ended

The chapters use only the `float` versions of `moveTo()` and `setVelocity()`, and leave the getters alone, so the course itself steers clear of all of this. A curious student can find it, though, and it's the C# course's Chapter 1, aliasing, living in this library. The suggested fix is in Part Five.

Part Three - Blob, and why the course builds on it

R.8 Blob

Member	Notes
`radius`	`float` (`protected`). The collision circle. It doesn't change the drawing of a student's class.
`myColor`	`int` (`protected`). Used only by `Blob`'s own `drawSprite()`.
`Blob(PApplet parent, float x, float y, float r, int c)`	Chapter 1's five things
`Blob(PApplet parent, float x, float y, float r, float dx, float dy, int c)`	with a velocity: Chapter 5's coin
`collidesWith(Blob other)`	`distanceTo(other) <= radius + other.radius`. Circles only, and touching counts: centers exactly 20 apart, with radii 10 and 10, is `true`, and 21 apart is `false`.
`drawSprite()`	`fill(myColor)`, then a circle of `2 * radius`. It sets no stroke, so it uses whatever stroke is current. See R.10.

R.9 Why Blob

The course's own guiding principles say it: *"`collidesWith()` is on `Blob`, not on the base `Sprite`. Students' custom characters should use `class MyCharacter extends Blob` (not `extends Sprite`) so that collision detection works automatically against other Blobs in the world."*

So every class a student writes extends `Blob`: the character, the cloud, a picture character, an animation frame. One rule, the same words every time. The rule has costs, and each one buys something. Each is a trade-off, and all six are worth knowing when you're the one in the room.

1. A misspelling fails silently. `Sprite.drawSprite()` is `abstract`, and `Blob.drawSprite()` isn't. So a student who writes `void drawsprite()` in a class that extends `Blob` gets no error. The sketch runs and draws Blob's own circle, in the handshake's backup color. The same misspelling in a class that extends `Sprite` stops the sketch:

```
The type SpriteMisspelled.Thing must implement the inherited abstract method
Sprite.drawSprite()
```

What it buys: a sketch that always runs, and a picture of what's underneath. Chapter 2 turns the silent fallback into its first discovery. If you'd rather have the error, `@Override` on the line above `drawSprite()` brings it back, and keeps `Blob`:

```
The method drawsprite() of type OverrideCatch.Thing must override or implement a
supertype method
```

No chapter uses `@Override`. Adding it would put one more copied line in every class a student writes.

2. Only Blobs can collide. `collidesWith()` lives on `Blob`, and it takes a `Blob`. So only Blobs can use it, from either side. A plain `Sprite` subclass has no `collidesWith()`, and a Blob can't collide with one either:

```
The function collidesWith(Blob) does not exist.
The method collidesWith(Blob) in the type Blob is not applicable for the
arguments (BlobVsSprite.Thing)
```

`ImageSprite` and `AnimatedSprite` hit the same wall, in Bonus A and Bonus C. The way around it is `distanceTo()`, which lives on `Sprite` and works between any two sprites. What it buys: one type for the whole world. The character, the clouds, the coins, and the hazards are all Blobs, so one kind of variable fits any of them, and Bonus D's `ArrayList<Blob>` takes every one.

3. Collisions are circles. `collidesWith()` compares two radii, so every hitbox is a circle, and a tall character or a long platform can only be approximated. The radius is also separate from the drawing, so a student's art can drift far from its hitbox, which is a pitfall the Lesson 6 Canvas page names. What it buys: one number as the design lever. Chapter 6 asks *"generous or precise?"*, and the answer is the radius. The rule fits in one sentence a sixth grader can check.

4. The handshake carries two things the student doesn't use. `super(p, x, y, 30, color(...))` passes the sketch, which students only ever meet as `this`, and a color, which is dead the moment `drawSprite()` is replaced. What it buys: they're the same five things Chapter 1's Blob took, so Chapter 2 can say *"you've seen these five before."* The color is also what shows up when a misspelling falls back to Blob's circle, which makes trade-off 1 easier to explain.

5. `Block` is a `Blob`. A rectangle isn't a circle, and `Block` inherits anyway, to reuse `myColor` and to fit wherever a Blob fits. So a `Block` inherits a collision circle of radius 0 at its top-left corner. Verified: a Blob sitting in the middle of a 200-by-100 `Block` is `false`, and a Blob near its corner is `true`. `distanceTo()` measures to the corner too. That's why Chapter 5 calls a `Block` scenery. What it buys: one more thing that goes anywhere a `Blob` goes, at no cost in new code.


6. `pos` and `vel` are open to students. Because they're `protected`, a student's class can change `pos` directly, skipping `moveTo()`, and the getters hand out the live objects (R.7). What it buys: the belly button. A sixth grader writes `ellipse(pos.x - 12, pos.y - 8, 16, 16)`, with no getter and no copy, and Chapter 2's whole Part Three rests on it.

R.10 Style leaks from one sprite to the next


Processing keeps one set of drawing settings, `fill`, `stroke`, `strokeWeight`, and the rest, and each one carries on until something changes it: from shape to shape, sprite to sprite, and frame

to frame. The library's `drawSprite()` methods mostly don't save and restore them. `ImageSprite` is the exception: it wraps its drawing in `pushStyle()` and `popStyle()`.

So settings leak. `Block.drawSprite()` calls `noStroke()`, and every shape drawn after it loses its outline, including, from the second frame on, the shapes drawn before it, because the setting carries into the next frame.



Frame 1: a Blob, a Block, and a Blob. The first Blob has its outline, and the one drawn after the Block doesn't.



Frame 3: neither Blob has an outline. The `noStroke()` from frame 1 is still on.

In the course this shows up quietly. Chapter 1's blob has an outline, and Chapter 5's coin doesn't, because the ground is drawn first. A student's character sets its own fill and stroke inside `drawSprite()`, so it looks the same wherever it's drawn, and that's the habit to teach: a `drawSprite()` sets everything it needs.

Part Four - The rest of the family

R.11 Block

Member	Notes
`w`, `h`	`float` (`protected`). Width and height, stored as absolute values.
`Block(PApplet parent, float x, float y, float w, float h, int c)`	`x, y` is the **top-left corner**. The radius is 0.
`drawSprite()`	`fill(myColor); noStroke(); rect(pos.x, pos.y, w, h)`. The `noStroke()` leaks (R.10).

A `Block` has `move()` and `setVelocity()`, and starts still. Its collision is R.9's trade-off 5: a point at its corner.

R.12 ScreenBehavior

An enum with four values, set through the static `Sprite.screenBehavior`, so one line changes every sprite in the sketch, immediately, mid-game included. It applies only inside `move()`, and only to each sprite's center.

Value	At an edge	Verified
`Wrapping`	jumps to the opposite edge. The default.	Chapter 3
`HardWalls`	stops at the edge, and zeroes the velocity on that axis	a Blob moving right at 5 from `x = 780`: at frame 10, `x = 800`, `vx = 0`
`BouncyWalls`	reverses the velocity on that axis	then `vx = -5` two frames later
`NoWalls`	nothing: the sprite leaves the window	`x = 830` after ten frames from 780

Chapter 7 offers `BouncyWalls` as a one-line extra. Because it's static, the clouds bounce too, and a student can't make the hazards bounce and the clouds wrap at the same time.

R.13 ImageSprite

`ImageSprite` extends `Sprite` directly. It isn't a `Blob`, so it has no radius and no `collidesWith()`.

Member	Notes
`ImageSprite(PApplet parent, float x, float y, String fileName)`	100 by 100
`ImageSprite(PApplet parent, float x, float y, String fileName, float size)`	square
`ImageSprite(PApplet parent, float x, float y, String fileName, float w, float h)`	`x, y` is the **center**
`setSize(float size)`, `setSize(float w, float h)`	absolute values
`setRotation(float rotation)`, `rotate(float amount)`, `getRotation()`	radians, around the center
`drawSprite()`	`pushMatrix`, `pushStyle`, `translate`, `rotate`, `imageMode(CENTER)`, `image`, and both pops. The one `drawSprite()` in the library that puts every setting back.

The image loads once, in the constructor, from the sketch's `data` folder. A missing file prints Processing's *"is missing or inaccessible"* message and leaves the image `null`. The constructor carries on, and the sketch stops with `NullPointerException` the first time `drawSprite()` passes `null` to `image()`. A name with the wrong capitals gets Processing's own clear message instead: *"This file is named tree.png not Tree.PNG. Rename the file or change your code."*

R.14 CompoundSprite

A sprite made of other sprites, its **children**. The compound's own `pos` is a reference point. It isn't drawn, and it needn't be anywhere near its children. Children keep their own absolute positions and velocities.

Member	Notes
`CompoundSprite(PApplet parent, float x, float y)`, and with `dx, dy`	
`addSprite(Sprite s)`	adds the compound's **current** velocity to the child's, then adds it. Returns the compound, so calls chain.
`removeSprite(Sprite s)`	takes the compound's velocity back off the child
`getSprites()`	the live list of children
`setVelocity(...)`	changes the compound's velocity, and adds the same **change** to every child
`move()`	moves the compound, then calls `move()` on each child
`moveTo(...)`, `followMouse()`	move the compound, then shift every child by the same amount
`keyboardControl()`	sets the compound's velocity, and passes the change to every child
`drawSprite()`	draws every child, in the order they were added

Two consequences. **Each child wraps by itself**, because `move()` reaches every child separately. Verified with two Blobs 50 pixels apart moving right: the right one wraps to `x = 2` while the left is at `752`, and the compound's own point wraps later still. A compound that crosses an edge splits for a few frames, and comes back together on the other side. And **the compound's `distanceTo()` measures from its own point**, which is wherever it was made, so for collisions measure from a child.

No chapter uses `CompoundSprite` directly. The library's `FractalExample` builds its branches from it, and `AnimatedSceneExample` builds its clouds and sun from its subclass, `AnimatedSprite`.

R.15 AnimatedSprite

A `CompoundSprite` that draws one child at a time: a flipbook. Bonus C.

Member	Notes
`AnimatedSprite(PApplet parent, float x, float y)`, and with `dx, dy`	starts on frame 0, at a rate of 8
`FromSprite(Sprite s)`, `fromSprite(Sprite s)`	`static`. A new `AnimatedSprite` at `s`'s position, with `s` as its first frame. `null` throws `IllegalArgumentException`.
`AddFrameSprite(Sprite s)`, `addFrameSprite(Sprite s)`	adds a frame, and returns the sprite, so calls chain
`setFrameRate(int n)`, `getFrameRate()`	game frames per animation frame, at least 1. Smaller is faster.
`setFrameNumber(int n)`, `getFrameNumber()`	jump to a frame. Wraps around, negatives included.
`nextFrame()`, `previousFrame()`	turn one page, by hand
`getFrameSprites()`, `getFrameCount()`	the frames, and how many
`drawSprite()`	draws the current frame, **then** advances the clock

Both spellings of the builder methods exist, `FromSprite` and `fromSprite`, so either capital letter works. The clock advances inside `drawSprite()`, so an `AnimatedSprite` that isn't drawn doesn't animate, and one drawn twice a frame animates twice as fast. Each frame is a full sprite with its own position, so frames made at different spots jump (Bonus C shows it), and every frame under the current one still carries its own unused radius and color.

R.16 Vector2D

A pair of floats, `x` and `y`, both public. Every method returns a new vector.

Member	Notes
`Vector2D(float x, float y)`, `FromXY(float x, float y)`	the same thing, two ways
`FromPolar(float r, float theta)`	`(r cos theta, r sin theta)`. With y pointing down, positive angles turn **clockwise on the screen**.
`add`, `subtract`, `scale`, `inverse`	the usual
`mag()`	length. For a velocity, the speed.
`dotProduct(Vector2D other)`	the usual
`unitVector()`	length 1. `(0, 0)` gives `(NaN, NaN)`, which the documentation warns about, and which is R.6's bug.
`perpendicular()`	`(y, -x)`. `(1, 0)`, right, becomes `(0, -1)`, which is **up** on the screen: a quarter turn counter-clockwise as you see it. The documentation says *clockwise*, which is true in math's y-up coordinates.
`rotate(float rads)`	the standard formula. `(1, 0)` rotated by `HALF_PI` is `(0, 1)`, **down** on the screen: positive angles turn clockwise as you see it. The documentation says *counter-clockwise*, true in y-up coordinates.
`angleTo(Vector2D other)`	wrong for any vector pointing left. See Part Five.
`theta()`	`protected`. `atan(y / x)`.

`angleTo()` is `other.theta() - this.theta()`, and `theta()` is `atan(y / x)`, which can't tell left from right. Verified:

```
right.angleTo(left) = -0.0   (PI is 3.1415927)
right.angleTo(upLeft) = 0.7853982   (the true angle is -2.3561945)
```

No chapter uses it.

R.17 Event

An observer: bind methods to an event by name, and `trigger()` calls every bound method. The original author is credited in the source as Stephcraft.

Member	Notes
`Event(Class<?>... args)`	the argument types, as classes: `new Event()`, or `new Event(Integer.class)`
`bind(Object listener, String name)`	finds the public method by name, with reflection, and adds it. A wrong name or wrong types prints `[Event] could not bind ...` and carries on.
`unbind(Object listener, String name)`, `bound(Object listener, String name)`	the reverse, and a check
`trigger(Object... arguments)`	calls every bound method. An exception inside one is printed, and the rest still run.

Two problems, both verified, mean `Event` is hard to use from a sketch.

- **The name collides.** Processing imports `processing.event.Event` into every sketch, so a bare `Event` stops the sketch with `The type Event is ambiguous`. It has to be written out: `coxprogramming.processing.sprites.Event`.
- **It can't call into the sketch's own classes.** Bound to a function on the sketch itself, `bind(this, "addPoint")`, it works. Bound to a method of a class in a tab, even a `public` one, every `trigger()` prints `IllegalAccessException: class coxprogramming.processing.sprites.Event$EventListener cannot access a member of class Events2$Counter with modifiers "public"`, and the method never runs. Classes in tabs are compiled as non-public nested classes, and reflection from another package can't call into them.

No chapter uses `Event`.

Part Five - Known issues

Everything this run found, with a suggested fix for each. The fixes are suggestions. Only the first was built and run, as an override in a sketch, and the library itself is unchanged.

Where	The issue	Suggested fix
`Sprite.followMouse()`	Landing exactly on the mouse divides by zero: the position becomes NaN, and the sprite vanishes for good. Within one step it jitters.	Land on the mouse when it's within one step (below).
`Sprite.getPosition()`, `getVelocity()`, `moveTo(Vector2D)`, `setVelocity(Vector2D)`, `Sprite(PApplet, Vector2D)`	Share vectors with the caller (R.7).	Hand out and store copies: `return new Vector2D(pos.x, pos.y);`, `pos = new Vector2D(p.x, p.y);`.
`ImageSprite`	A missing file stops the sketch later, at `drawSprite()`, with `NullPointerException`.	In `drawSprite()`, `if (img == null) return;`, or draw a placeholder rectangle.
`Block`	Inherits a collision circle of radius 0 at its corner.	Give `Block` a rectangle check of its own, or say plainly that it's scenery (the chapters do).
`Blob.drawSprite()`, `Block.drawSprite()`	Leave fill and stroke changed for everything after them (R.10).	Wrap each in `parent.pushStyle()` and `parent.popStyle()`, the way `ImageSprite` does. This would also give Chapter 1's blob and Chapter 5's coin the same outline.
`Event`	Ambiguous by name in a sketch, and can't call methods in a sketch's classes.	Rename it, `GameEvent`, and call `method.setAccessible(true)` in `bind()`.
`Vector2D.theta()`	`atan(y / x)` can't tell left from right, so `angleTo()` is wrong for left-pointing vectors.	`(float) Math.atan2(y, x)`.
`Vector2D` documentation	*Clockwise* and *counter-clockwise* are y-up words, and the screen is y-down.	Say which way it turns on the screen.

The `followMouse()` fix, as it was run: overridden in a `Blob` subclass, with the mouse at the spot that gave the library's version a NaN at frame 51. It landed on `(600.0, 300.0)` at frame 51 and stayed there through frame 60.

```
public void followMouse() {
  float speed = vel.mag();
  Vector2D toMouse = new Vector2D(parent.mouseX, parent.mouseY).subtract(pos);
  float d = toMouse.mag();
  if (d <= speed) {
    pos = new Vector2D(parent.mouseX, parent.mouseY);
  } else {
    pos = pos.add(toMouse.scale(speed / d));
  }
}
```

In `CompoundSprite`, the same fix belongs in its override, which shifts the children by however far the compound moved.