

CellStyle

A cell style.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [duplicate](#), [extractLabel](#), [getElements](#), [insertLabel](#), [move](#), [remove](#), [removeEventListener](#), [toSource](#), [toSpecifier](#)

Objects:

[Boolean](#), [CellStyle](#), [EventListeners](#), [Events](#), [FirstBaseline](#), [NothingEnum](#), [Number](#), [Object](#), [ParagraphStyle](#), [String](#), [StrokeStyle](#), [Swatch](#), [VerticalJustification](#)

Property Listing

Property	Type	Access	Description
<code>appliedParagraphStyle</code>	ParagraphStyle <code>NothingEnum</code> Canalsoaccept:String	read/write	The paragraph style applied to the text. Can return: ParagraphStyle or NothingEnum enumerator. Can also accept: String.
<code>basedOn</code>	CellStyle String	read/write	The style that this style is based on. Can return: CellStyle or String.
<code>bottomEdgeStrokeColor</code>	Swatch <code>NothingEnum.NOTHING</code>	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the bottom edge border stroke. Can return: Swatch or NothingEnum enumerator.
<code>bottomEdgeStrokeGapColor</code>	Swatch <code>NothingEnum.NOTHING</code>	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the gap of the bottom edge border stroke. Note: Not valid when bottom edge stroke type is solid. Can return: Swatch or NothingEnum enumerator.
<code>bottomEdgeStrokeGapOverprint</code>	Boolean <code>NothingEnum.NOTHING</code>	read/write	If true, the gap color of the bottom edge border stroke will overprint. Note: Not valid when bottom edge stroke type is solid. Can return: Boolean or NothingEnum enumerator.

Property	Type	Access	Description
bottomEdgeStrokeGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the bottom edge border stroke gap color. (Range: 0 to 100) Note: Not valid when bottom edge stroke type is solid. Can return: Real or NothingEnum enumerator.
bottomEdgeStrokeOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the bottom edge border stroke will overprint. Can return: Boolean or NothingEnum enumerator.
bottomEdgeStrokeTint	Real NothingEnum.NOTHING	read/write	The tint (as a percentage) of the bottom edge border stroke. Can return: Real or NothingEnum enumerator.
bottomEdgeStrokeType	StrokeStyle NothingEnumCanalsoaccept:String	read/write	The stroke type of the bottom edge. Can return: StrokeStyle or NothingEnum enumerator. Can also accept: String.
bottomEdgeStrokeWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the bottom edge border stroke. Can return: Unit or NothingEnum enumerator.
bottomInset	Unit NothingEnum.NOTHING	read/write	The bottom inset of the cell.The API has been deprecated. Use TextBottomInset or GraphicBottomInset. Can return: Unit or NothingEnum enumerator.
clipContentToCell	Boolean NothingEnum.NOTHING	read/write	If true, clips the cell's content to width and height of the cell. The API has been deprecated. Use ClipContentsToTextCell or ClipContentsToPageItemCell. Can return: Boolean or NothingEnum enumerator.
clipContentToGraphicCell	Boolean NothingEnum.NOTHING	read/write	If true, clips the graphic cell's content to width and height of the cell. Can return: Boolean or NothingEnum enumerator.
clipContentToTextCell	Boolean NothingEnum.NOTHING	read/write	If true, clips the text cell's content to width and height

Property	Type	Access	Description
			of the cell. Can return: Boolean or NothingEnum enumerator.
diagonalLineInFront	Boolean NothingEnum.NOTHING	read/write	If true, draws the diagonal line in front of cell contents. Can return: Boolean or NothingEnum enumerator.
diagonalLineStrokeColor	Swatch NothingEnum.NOTHING	read/write	The diagonal line color, specified as a swatch. Can return: Swatch or NothingEnum enumerator.
diagonalLineStrokeGapColor	Swatch NothingEnum.NOTHING	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the gap of the diagonal line stroke. Note: Not valid when diagonal line stroke type is solid. Can return: Swatch or NothingEnum enumerator.
diagonalLineStrokeGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the stroke gap of the diagonal line will overprint. Note: Not valid when diagonal line stroke type is solid. Can return: Boolean or NothingEnum enumerator.
diagonalLineStrokeGapTint	Real NothingEnum.NOTHING	read/write	The tint (as a percentage) of the diagonal line stroke gap color. Note: Not valid when diagonal line stroke type is solid. Can return: Real or NothingEnum enumerator.
diagonalLineStrokeOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the diagonal line stroke will overprint. Can return: Boolean or NothingEnum enumerator.
diagonalLineStrokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The diagonal line tint (as a percentage). (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
diagonalLineStrokeType	StrokeStyle NothingEnumCanalsoaccept:String	read/write	The stroke type of the diagonal line(s). Can return: StrokeStyle or NothingEnum enumerator. Can also accept: String.
diagonalLineStrokeWeight	Unit NothingEnum.NOTHING	read/write	The diagonal line stroke weight. Can return: Unit or NothingEnum enumerator.

Property	Type	Access	Description
eventListeners	<i>EventListeners</i> <i>EventListener</i>	readonly	A collection of event listeners.
events	<i>Events</i> <i>Event</i>	readonly	A collection of events.
fillColor	<i>Swatch</i> NothingEnum.CanAlsoAccept:String	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the fill of the object. Can return: Swatch or NothingEnum enumerator. Can also accept: String.
fillTint	Real NothingEnum.NOTHING	read/write	The tint (as a percentage) of the fill of the object. Can return: Real or NothingEnum enumerator.
firstBaselineOffset	<i>FirstBaseline</i> FirstBaseline.ASCENT_OFFSET FirstBaseline.CAP_HEIGHT FirstBaseline.EMBOX_HEIGHT FirstBaseline.FIXED_HEIGHT FirstBaseline.LEADING_OFFSET FirstBaseline.X_HEIGHT NothingEnum.NOTHING	read/write	The distance between the baseline of the text and the top inset of the cell. Can return: FirstBaseline enumerator or NothingEnum enumerator.
gradientFillAngle	Real NothingEnum.NOTHING	read/write	The angle of a linear gradient applied to the fill of the object. (Range: -180 to 180). Can return: Real or NothingEnum enumerator.
gradientFillLength	Real NothingEnum.NOTHING	read/write	The length (of a linear gradient) or radius (of a radial gradient) applied to the fill of the object. Can return: Real or NothingEnum enumerator.
gradientFillStart	<i>Array</i> of 2 Units NothingEnum.NOTHING	read/write	The starting point (in page coordinates) of a gradient applied to the fill of the CellStyle, in the format [x, y]. Can return: Array of 2 Units or NothingEnum enumerator.
graphicBottomInset	Unit NothingEnum.NOTHING	read/write	The bottom inset of the graphic cell. Can return: Unit or NothingEnum enumerator.
graphicLeftInset	Unit NothingEnum.NOTHING	read/write	The left inset of the graphic cell. Can return: Unit or NothingEnum enumerator.

Property	Type	Access	Description
graphicRightInset	Unit NothingEnum.NOTHING	read/write	The right inset of the graphic cell. Can return: Unit or NothingEnum enumerator.
graphicTopInset	Unit NothingEnum.NOTHING	read/write	The top inset of the graphic cell. Can return: Unit or NothingEnum enumerator.
id	Number	readonly	The unique ID of the CellStyle.
index	Number	readonly	The index of the CellStyle within its containing object.
isValid	Boolean	readonly	Returns true if the object specifier resolves to valid objects.
label	String	read/write	A property that can be set to any string.
leftEdgeStrokeColor	Swatch NothingEnum.NOTHING	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the left edge border stroke. Can return: Swatch or NothingEnum enumerator.
leftEdgeStrokeGapColor	Swatch NothingEnum.NOTHING	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the gap of the left edge border stroke. Note: Not valid when left edge stroke type is solid. Can return: Swatch or NothingEnum enumerator.
leftEdgeStrokeGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color of the left edge border stroke will overprint. Note: Not valid when left edge stroke type is solid. Can return: Boolean or NothingEnum enumerator.
leftEdgeStrokeGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the left edge border stroke gap color. (Range: 0 to 100) Note: Not valid when left edge stroke type is solid. Can return: Real or NothingEnum enumerator.
leftEdgeStrokeOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the left edge border stroke will overprint. Can

Property	Type	Access	Description
leftEdgeStrokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	return: Boolean or NothingEnum enumerator. The tint (as a percentage) of the left edge border stroke. (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
leftEdgeStrokeType	StrokeStyle NothingEnumCanalsoaccept:String	read/write	The stroke type of the left edge. Can return: StrokeStyle or NothingEnum enumerator. Can also accept: String.
leftEdgeStrokeWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the left edge border stroke. Can return: Unit or NothingEnum enumerator.
leftInset	Unit NothingEnum.NOTHING	read/write	The left inset of the cell.The API has been deprecated. Use TextLeftInset or GraphicLeftInset. Can return: Unit or NothingEnum enumerator.
minimumFirstBaselineOffset	Unit(0-8640points) NothingEnum.NOTHING	read/write	The space between the baseline of the text and the top inset of the frame or cell. Can return: Unit (0 - 8640 points) or NothingEnum enumerator.
name	String	read/write	The name of the style.
overprintFill	Boolean NothingEnum.NOTHING	read/write	If true, the fill of the object will overprint. Can return: Boolean or NothingEnum enumerator.
paragraphSpacingLimit	Unit NothingEnum.NOTHING	read/write	The maximum space that can be added between paragraphs in a cell. Note: Valid only when vertical justification is justified. Can return: Unit or NothingEnum enumerator.
parent	Application CellStyleGroup Document	readonly	The parent of the CellStyle (a Document, Application or CellStyleGroup).
properties	Object	read/write	A property that allows setting of several properties at the same time.
rightEdgeStrokeColor	Swatch NothingEnum.NOTHING	read/write	The color, specified as a swatch, of the right edge

Property	Type	Access	Description
			border stroke. Can return: Swatch or NothingEnum enumerator.
rightEdgeStrokeGapColor	Swatch NothingEnum.NOTHING	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the gap of the right edge border stroke. Note: Not valid when right edge stroke type is solid. Can return: Swatch or NothingEnum enumerator.
rightEdgeStrokeGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color of the right edge border stroke will overprint. Note: Not valid when right edge stroke type is solid. Can return: Boolean or NothingEnum enumerator.
rightEdgeStrokeGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the right edge border stroke gap color. (Range: 0 to 100) Note: Not valid when right edge stroke type is solid. Can return: Real or NothingEnum enumerator.
rightEdgeStrokeOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the right edge border stroke will overprint. Can return: Boolean or NothingEnum enumerator.
rightEdgeStrokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the right edge border stroke. (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
rightEdgeStrokeType	StrokeStyle NothingEnumCanalsoaccept:String	read/write	The stroke type of the right edge. Can return: StrokeStyle or NothingEnum enumerator. Can also accept: String.
rightEdgeStrokeWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the right edge border stroke. Can return: Unit or NothingEnum enumerator.
rightInset	Unit NothingEnum.NOTHING	read/write	The right inset of the cell.The API has been deprecated. Use TextLeftInset or GraphicRightInset. Can

Property	Type	Access	Description
			return: Unit or NothingEnum enumerator.
rotationAngle	Real NothingEnum.NOTHING	read/write	The rotation angle (in degrees) of the cell, specified as one of the following values: 0, 90, 180, or 270. Can return: Real or NothingEnum enumerator.
textBottomInset	Unit NothingEnum.NOTHING	read/write	The bottom inset of the text cell. Can return: Unit or NothingEnum enumerator.
textLeftInset	Unit NothingEnum.NOTHING	read/write	The left inset of the text cell. Can return: Unit or NothingEnum enumerator.
textRightInset	Unit NothingEnum.NOTHING	read/write	The right inset of the text cell. Can return: Unit or NothingEnum enumerator.
textTopInset	Unit NothingEnum.NOTHING	read/write	The top inset of the text cell. Can return: Unit or NothingEnum enumerator.
topEdgeStrokeColor	Swatch NothingEnum.NOTHING	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the top edge border stroke. Can return: Swatch or NothingEnum enumerator.
topEdgeStrokeGapColor	Swatch NothingEnum.NOTHING	read/write	The swatch (color, gradient, tint, or mixed ink) applied to the gap of the top edge border stroke. Note: Not valid when top edge stroke type is solid. Can return: Swatch or NothingEnum enumerator.
topEdgeStrokeGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color of the top edge border stroke will overprint. Note: Not valid when top edge stroke type is solid. . Can return: Boolean or NothingEnum enumerator.
topEdgeStrokeGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the top edge border stroke gap color. (Range: 0 to 100) Note: Not valid when top edge stroke type is solid. Can return: Real or NothingEnum enumerator.

Property	Type	Access	Description
topEdgeStrokeOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the top edge border stroke will overprint. Can return: Boolean or NothingEnum enumerator.
topEdgeStrokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the top edge border stroke. (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
topEdgeStrokeType	StrokeStyle NothingEnumCanalsoaccept:String	read/write	The stroke type of the top edge. Can return: StrokeStyle or NothingEnum enumerator. Can also accept: String.
topEdgeStrokeWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the top edge border stroke. Can return: Unit or NothingEnum enumerator.
topInset	Unit NothingEnum.NOTHING	read/write	The top inset of the cell. The API has been deprecated. Use TextTopInset or GraphicTopInset. Can return: Unit or NothingEnum enumerator.
topLeftDiagonalLine	Boolean NothingEnum.NOTHING	read/write	If true, draws a diagonal line starting from the top left. Can return: Boolean or NothingEnum enumerator.
topRightDiagonalLine	Boolean NothingEnum.NOTHING	read/write	If true, draws a diagonal line starting from the top right. Can return: Boolean or NothingEnum enumerator.
verticalJustification	VerticalJustification VerticalJustification.BOTTOM_ALIGN VerticalJustification.CENTER_ALIGN VerticalJustification.JUSTIFY_ALIGN VerticalJustification.TOP_ALIGN NothingEnum.NOTHING	read/write	The vertical alignment of cell. Can return: VerticalJustification enumerator or NothingEnum enumerator.

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

CellStyle **duplicate** ()

Duplicates the CellStyle.

String **extractLabel** (key:String)

Gets the label value associated with the specified key.

Parameter	Type	Description
key	String	The key.

CellStyle **getElements** ()

Resolves the object specifier, creating an array of object references.

undefined **insertLabel** (key:String, value:String)

Sets the label to the value associated with the specified key.

Parameter	Type	Description
key	String	The key.
value	String	The value.

CellStyle **move** (to:LocationOptions, reference:Varies CellStyle CellStyleGroup CharacterStyle CharacterStyleGroup Document ParagraphStyle ParagraphStyleGroup TableStyle TableStyleGroup Application)

Moves the style to the specified location.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The location relative to the reference object or within the containing object.
reference	CellStyle CellStyleGroup CharacterStyle CharacterStyleGroup Document ParagraphStyle ParagraphStyleGroup TableStyle TableStyleGroup	The reference object. Note: Required when the to parameter specifies before or after. Can accept: ParagraphStyle, ParagraphStyleGroup, CharacterStyle, CharacterStyleGroup, CellStyle, CellStyleGroup, TableStyle, TableStyleGroup, Document or Application. (Optional)

Parameter	Type	Description
	Application	

undefined **remove** (replacingWith:CellStyle)

Deletes the style.

Parameter	Type	Description
replacingWith	CellStyle	The style to apply in place of the deleted style. (Optional)

Boolean **removeEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

String **toSource** ()

Generates a string which, if executed, will return the CellStyle.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Application.allCellStyles
 Document.allCellStyles
 CellStyleGroup.allCellStyles
 Cell.appliedCellStyle
 TableStyle.bodyRegionCellStyle
 TableStyle.footerRegionCellStyle
 TableStyle.headerRegionCellStyle
 TableStyle.leftColumnRegionCellStyle
 TableStyle.rightColumnRegionCellStyle
 Event.parent
 EventListener.parent
 MutationEvent.parent
 CellStyle.basedOn

Return

CellStyles.add()
 CellStyle.duplicate()
 CellStyle.move()
 CellStyle.getElements()

CellStyles.anyItem()
CellStyles.everyItem()
CellStyles.nextItem()
CellStyles.previousItem()
CellStyles.itemByID()
CellStyles.item()
CellStyles.[]()
CellStyles.itemByName()
CellStyles.itemByRange()
CellStyles.firstItem()
CellStyles.lastItem()
CellStyles.middleItem()
