

ChangeGrepPreference

Change grep preferences.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [getElements](#), [isNthDesignAxisHidden](#), [removeEventListener](#), [setNthDesignAxis](#), [toSource](#), [toSpecifier](#)

Objects:

[AdornmentOverprint](#), [AlternateGlyphForms](#), [BalanceLinesStyle](#), [Boolean](#), [Bullet](#), [Capitalization](#), [ChangeConditionsModes](#), [ChangecaseMode](#), [CharacterAlignment](#), [CharacterDirectionOptions](#), [CharacterStyle](#), [DiacriticPositionOptions](#), [DigitsTypeOptions](#), [EventListeners](#), [Events](#), [Font](#), [GridAlignment](#), [Justification](#), [KashidasOptions](#), [KentenAlignment](#), [KentenCharacter](#), [KentenCharacterSet](#), [KinsokuHangTypes](#), [KinsokuSet](#), [KinsokuTable](#), [KinsokuType](#), [LanguageWithVendors](#), [Leading](#), [LeadingModel](#), [ListType](#), [MojikumiTable](#), [MojikumiTableDefaults](#), [NothingEnum](#), [NumberingList](#), [NumberingRestartPolicy](#), [NumberingStyle](#), [OTFFigureStyle](#), [Object](#), [OutlineJoin](#), [ParagraphDirectionOptions](#), [ParagraphJustificationOptions](#), [Position](#), [PositionalForms](#), [Preferences](#), [RubyAlignments](#), [RubyKentenPosition](#), [RubyOverhang](#), [RubyParentSpacing](#), [RubyTypes](#), [SingleWordJustification](#), [Spacing](#), [SpanColumnCountOptions](#), [SpanColumnTypeOptions](#), [StartParagraph](#), [String](#), [StrokeStyle](#), [Swatch](#), [TextStrokeAlign](#), [WarichuAlignment](#)

Preferences:

[Preferences](#)

Hierarchy:

Superclass: [Preference](#)

Class: [ChangeGrepPreference](#)

Property Listing

Property	Type	Access	Description
allowArbitraryHyphenation	Boolean NothingEnum .NOTHING	read/write	If true, words unas with a hyphenatio dictionary can bre: next line on any cl Can return: Boolean NothingEnum enu
appliedCharacterStyle	String NothingEnum Canalsoaccept: CharacterStyle	read/write	The character style for or change to. C String or NothingE enumerator. Can a CharacterStyle .
appliedConditions	Array of Strings NothingEnum enumerator. Can also accept: Conditions .	read/write	The conditions to : or change to. Spec "nothing" enum fo an empty list for " [Unconditional]". (Array of Strings or NothingEnum enu Can also accept: A Conditions .
appliedFont	Font String NothingEnum .NOTHING	read/write	The font applied to ChangeGrepPrefer specified as either object or the name family. Can return: String or NothingE enumerator.
appliedLanguage	String LanguageWithVendors NothingEnum Canalsoaccept: Language	read/write	The language to se change to. Can ret or NothingEnum e Can also accept: L: LanguageWithVen
appliedNumberingList	NumberingList String NothingEnum .NOTHING	read/write	The list to be part return: Numbering or NothingEnum e
appliedParagraphStyle	String NothingEnum Canalsoaccept: ParagraphStyle	read/write	The paragraph styl for or change to. C

Property	Type	Access	Description
			String or Nothing Enumerator. Can a
autoLeading	Real (range 0 - 500) NothingEnum.NOTHING	read/write	ParagraphStyle. The percent of the to use for auto lea (Range: 0 to 500). Real or NothingEn enumerator.
autoTcy	ShortInteger NothingEnum.NOTHING	read/write	The number of hal characters at or be the characters aut run horizontally in text. Can return: S Integer or Nothing enumerator.
autoTcyIncludeRoman	Boolean NothingEnum.NOTHING	read/write	If true, auto tcy inc Roman characters. return: Boolean or NothingEnum enu
balanceRaggedLines	BalanceLineStyle BalanceLineStyle.FULLY_BALANCED BalanceLineStyle.NO_BALANCING BalanceLineStyle.PYRAMID_SHAPE BalanceLineStyle.VEE_SHAPE Boolean NothingEnum.NOTHING	read/write	If true or set to an enumeration value ragged lines. Note with a single-line t composer. Can ret Boolean, BalanceL enumerator or No enumerator.
baselineShift	Unit NothingEnum.NOTHING	read/write	The baseline shift : the text. Can retur NothingEnum enu
bulletChar	Bullet NothingEnum.NOTHING	readonly	Bullet character. C Bullet or NothingE enumerator.
bulletsAndNumberingListType	ListType ListType.BULLET_LIST ListType.NO_LIST ListType.NUMBERED_LIST NothingEnum.NOTHING	read/write	List type for bullet: numbering. Can re ListType enumerat NothingEnum enu
bulletsCharacterStyle	CharacterStyle String NothingEnum.NOTHING	read/write	The character style used for the text a Can return: Charac String or NothingE enumerator.
bulletsTextAfter	String NothingEnum.NOTHING	read/write	The text after strin expression for bull return: String or NothingEnum enu
bunriKinshi	Boolean NothingEnum.NOTHING	read/write	If true, adds the de period (.), ellipse (. double hyphen (--) selected kinsoku s Valid only when a is in effect. Can ret Boolean or Nothin enumerator.
capitalization	Capitalization Capitalization.ALL_CAPS Capitalization.CAP_TO_SMALL_CAP Capitalization.LOWER_CASE Capitalization.NORMAL Capitalization.SMALL_CAPS NothingEnum.NOTHING	read/write	The capitalization : Can return: Capita enumerator or No enumerator.
changeCaseMode	ChangeCaseMode ChangeCaseMode.LOWERCASE ChangeCaseMode.SENTENCECASE ChangeCaseMode.TITLECASE ChangeCaseMode.UPPERCASE NothingEnum.NOTHING	read/write	The change case m changes the case o found text. Can ret ChangeCaseMode enumerator or No enumerator.

Property	Type	Access	Description
changeConditionsMode	ChangeConditionsModes ChangeConditionsModes.ADD_TO ChangeConditionsModes.REPLACE_WITH NothingEnum.NOTHING	read/write	The change conditions mode. Can return: ChangeConditionsModes enumerator or NothingEnum enumerator.
changeTo	String NothingEnum.NOTHING	read/write	The replacement text. Can return: String or NothingEnum enumerator.
characterAlignment	CharacterAlignment CharacterAlignment.ALIGN_BASELINE CharacterAlignment.ALIGN_EM_BOTTOM CharacterAlignment.ALIGN_EM_CENTER CharacterAlignment.ALIGN_EM_TOP CharacterAlignment.ALIGN_ICF_BOTTOM CharacterAlignment.ALIGN_ICF_TOP NothingEnum.NOTHING	read/write	The alignment of the character. Can return: CharacterAlignment enumerator or NothingEnum enumerator.
characterDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION NothingEnum.NOTHING	read/write	The direction of the character. Can return: CharacterDirectionOptions enumerator or NothingEnum enumerator.
characterRotation	Real NothingEnum.NOTHING	read/write	The rotation angle (in degrees) of individual characters. Note: 0 degrees is counter-clockwise. Can return: Real or NothingEnum enumerator.
CJKGridTracking	Boolean NothingEnum.NOTHING	read/write	If true, uses grid tracking for non-Roman characters in CJK grids. Can return: Boolean or NothingEnum enumerator.
composer	String NothingEnum.NOTHING	read/write	The text composer. Can return: String or NothingEnum enumerator.
designAxes	Array of Reals NothingEnum.NOTHING	read/write	Value of Design Axes. Can return: Array of Real or NothingEnum enumerator.
diacriticPosition	DiacriticPositionOptions DiacriticPositionOptions.DEFAULT_POSITION DiacriticPositionOptions.LOOSE_POSITION DiacriticPositionOptions.MEDIUM_POSITION DiacriticPositionOptions.OPENTYPE_POSITION DiacriticPositionOptions.OPENTYPE_POSITION_FROM_BASELINE DiacriticPositionOptions.TIGHT_POSITION NothingEnum.NOTHING	read/write	Position of diacritical characters. Can return: DiacriticPositionOptions enumerator or NothingEnum enumerator.
digitsType	DigitsTypeOptions DigitsTypeOptions.ARABIC_DIGITS DigitsTypeOptions.BENGALI_DIGITS DigitsTypeOptions.BURMESE_DIGITS DigitsTypeOptions.DEFAULT_DIGITS DigitsTypeOptions.DEVANAGARI_DIGITS DigitsTypeOptions.FARSI_DIGITS DigitsTypeOptions.FULL_FARSI_DIGITS DigitsTypeOptions.GUJARATI_DIGITS DigitsTypeOptions.GURMUKHI_DIGITS DigitsTypeOptions.HINDI_DIGITS DigitsTypeOptions.KANNADA_DIGITS DigitsTypeOptions.KHMER_DIGITS DigitsTypeOptions.LAO_DIGITS DigitsTypeOptions.MALAYALAM_DIGITS DigitsTypeOptions.NATIVE_DIGITS DigitsTypeOptions.ORIYA_DIGITS DigitsTypeOptions.TAMIL_DIGITS	read/write	The digits type. Can return: DigitsTypeOptions enumerator or NothingEnum enumerator.

Property	Type	Access	Description
	DigitsTypeOptions.TELUGU_DIGITS DigitsTypeOptions.THAI_DIGITS DigitsTypeOptions.TIBETAN_DIGITS NothingEnum.NOTHING		
dropCapCharacters	ShortInteger(0-150) NothingEnum.NOTHING	read/write	The number of characters to drop cap. Can return: Short Integer (0 - 150) or NothingEnum enumerator.
dropCapLines	ShortInteger(0-25) NothingEnum.NOTHING	read/write	The number of lines to drop cap. Can return: Short Integer (0 - 25) or NothingEnum enumerator.
dropcapDetail	LongInteger NothingEnum.NOTHING	read/write	Details about the drop cap based on the glyph. 1 = left side bearing descenders. 0x100,0x200,0x400 for Japanese frame. Can return: Long Integer or NothingEnum enumerator.
endJoin	OutlineJoin OutlineJoin.BEVEL_END_JOIN OutlineJoin.MITER_END_JOIN OutlineJoin.ROUND_END_JOIN NothingEnum.NOTHING	read/write	The stroke join type to the characters connected. Can return: OutlineJoin enumerator or NothingEnum enumerator.
eventListeners	EventListeners EventListener	readonly	A collection of event listeners.
events	Events Event	readonly	A collection of events.
fillColor	String NothingEnum.CanAlsoAccept:Swatch	read/write	The swatch (color, tint, or mixed ink), a fill color, to search for a fill color, to search for a change to. Can return: String or NothingEnum enumerator. Can also accept: Swatch.
fillTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the fill color of the text. Can return: Real or NothingEnum enumerator. To specify a tint percentage, specify a tint percentage number in the range 0 to 100; to use the inherited value, specify 0. Can return: Real or NothingEnum enumerator.
firstLineIndent	Unit NothingEnum.NOTHING	read/write	The amount to indent the first line. Can return: Unit or NothingEnum enumerator.
fontStyle	String NothingEnum.NOTHING	read/write	The name of the font style. Can return: String or NothingEnum enumerator.
glyphForm	AlternateGlyphForms AlternateGlyphForms.EXPERT_FORM AlternateGlyphForms.FULL_WIDTH_FORM AlternateGlyphForms.JIS04_FORM AlternateGlyphForms.JIS78_FORM AlternateGlyphForms.JIS83_FORM AlternateGlyphForms.JIS90_FORM AlternateGlyphForms.MONOSPACED_HALF_WIDTH_FORM AlternateGlyphForms.NLC_FORM AlternateGlyphForms.NONE AlternateGlyphForms.PROPORTIONAL_WIDTH_FORM AlternateGlyphForms.QUARTER_WIDTH_FORM AlternateGlyphForms.THIRD_WIDTH_FORM AlternateGlyphForms.TRADITIONAL_FORM NothingEnum.NOTHING	read/write	The glyph variant to substitute for standard glyphs. Can return: AlternateGlyphForms enumerator or NothingEnum enumerator.
gradientFillAngle	Real NothingEnum.NOTHING	read/write	The angle of a line applied to the fill color. (Range: -180 to 180 degrees)

Property	Type	Access	Description
gradientFillLength	Real NothingEnum.NOTHING	read/write	return: Real or No The length (for a li gradient) or radius radial gradient) ap fill of the text. Can Real or NothingEn enumerator.
gradientFillStart	Array of 2 Units NothingEnum.NOTHING	read/write	The starting point coordinates) of a g applied to the fill c in the format [x, y] return: Array of 2 l NothingEnum enu
gradientStrokeAngle	Real NothingEnum.NOTHING	read/write	The angle of a line applied to the stro text. (Range: -180 Can return: Real o NothingEnum enu
gradientStrokeLength	Real NothingEnum.NOTHING	read/write	The length (for a li gradient) or radius radial gradient) ap stroke of the text. Real or NothingEn enumerator.
gradientStrokeStart	Array of 2 Units NothingEnum.NOTHING	read/write	The starting point coordinates) of a g applied to the stro text, in the format return: Array of 2 l NothingEnum enu
gridAlignment	GridAlignment GridAlignment.ALIGN_BASELINE GridAlignment.ALIGN_EM_BOTTOM GridAlignment.ALIGN_EM_CENTER GridAlignment.ALIGN_EM_TOP GridAlignment.ALIGN_ICF_BOTTOM GridAlignment.ALIGN_ICF_TOP GridAlignment.NONE NothingEnum.NOTHING	read/write	The alignment to t grid or baseline gri return: GridAlignr enumerator or No enumerator.
gridGyoudori	ShortInteger NothingEnum.NOTHING	read/write	The manual gyoud Can return: Short l NothingEnum enu
horizontalScale	Real NothingEnum.NOTHING	read/write	The horizontal sca to the ChangeGrepPrefer return: Real or No enumerator.
hyphenateAcrossColumns	Boolean NothingEnum.NOTHING	read/write	If true, allows the a text column to b hyphenated. Can r Boolean or Nothin enumerator.
hyphenateLastWord	Boolean NothingEnum.NOTHING	read/write	If true, allows hyp the last word in a p Note: Valid only w hyphenation is tru return: Boolean or NothingEnum enu
ignoreEdgeAlignment	Boolean NothingEnum.NOTHING	read/write	If true, ignores opt alignment for the p Can return: Boolea NothingEnum enu
isValid	Boolean	readonly	Returns true if the specifier resolves t objects.
jidori	ShortInteger NothingEnum.NOTHING	read/write	The number of gri in which to arrang

Property	Type	Access	Description
justification	Justification Justification.AWAY_FROM_BINDING_SIDE Justification.CENTER_ALIGN Justification.CENTER_JUSTIFIED Justification.FULLY_JUSTIFIED Justification.LEFT_ALIGN Justification.LEFT_JUSTIFIED Justification.RIGHT_ALIGN Justification.RIGHT_JUSTIFIED Justification.TO_BINDING_SIDE NothingEnum.NOTHING	read/write	Can return: Short Integer(1-50) or NothingEnum enumerator. Can return: Justification enumerator or NothingEnum enumerator.
kashidas	KashidasOptions KashidasOptions.DEFAULT_KASHIDAS KashidasOptions.KASHIDAS_OFF NothingEnum.NOTHING	read/write	Use of Kashidas for justification. Can return: KashidasOptions enumerator or NothingEnum enumerator.
keepAllLinesTogether	Boolean NothingEnum.NOTHING	read/write	If true, keeps all lines of a paragraph together. Can return: Boolean or NothingEnum enumerator.
keepFirstLines	ShortInteger(1-50) NothingEnum.NOTHING	read/write	The minimum number of lines to keep together at the beginning of a paragraph before a page break. Can return: Short Integer (1 - 50) or NothingEnum enumerator.
keepLastLines	ShortInteger(1-50) NothingEnum.NOTHING	read/write	The minimum number of lines to keep together at the end of a paragraph after a page break. Can return: Short Integer (1 - 50) or NothingEnum enumerator.
keepLinesTogether	Boolean NothingEnum.NOTHING	read/write	If true, keeps a specified number of lines together when the paragraph crosses columns or frames. Can return: Boolean or NothingEnum enumerator.
keepRuleAboveInFrame	Boolean NothingEnum.NOTHING	read/write	If true, forces the top of the paragraph to remain above the frame bounds. Valid only when rule is true. Can return: Boolean or NothingEnum enumerator.
keepWithNext	ShortInteger(0-5) NothingEnum.NOTHING	read/write	The minimum number of lines to keep with the next paragraph. Can return: Short Integer (0 - 5) or NothingEnum enumerator.
keepWithPrevious	Boolean NothingEnum.NOTHING	read/write	If the first line in the paragraph should be kept with the last line of the previous paragraph. Can return: Boolean or NothingEnum enumerator.
kentenAlignment	KentenAlignment KentenAlignment.ALIGN_KENTEN_CENTER KentenAlignment.ALIGN_KENTEN_LEFT NothingEnum.NOTHING	read/write	The alignment of kenten characters relative to the parent characters. Can return: KentenAlignment enumerator or NothingEnum enumerator.
kentenCharacterSet	KentenCharacterSet KentenCharacterSet.CHARACTER_INPUT KentenCharacterSet.JIS KentenCharacterSet.KUTEN KentenCharacterSet.SHIFT_JIS	read/write	The character set used for the custom kenten. Note: Valid only when kind is custom. Can return: KentenCharacterSet enumerator.

Property	Type	Access	Description
	KentenCharacterSet.UNICODE		enumerator or No
kentenCustomCharacter	NothingEnum.NOTHING String NothingEnum.NOTHING	read/write	enumerator. The character used kenten. Note: Valid when kenten kind Can return: String NothingEnum enu
kentenFillColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the fill of kenten cl Can return: Swatch NothingEnum enu
kentenFont	Font String NothingEnum.NOTHING	read/write	The font to use for characters. Can rel String or NothingE enumerator.
kentenFontSize	Real NothingEnum.NOTHING	read/write	The size (in points) characters. Can rel or NothingEnum e
kentenFontStyle	String NothingEnum.NOTHING	read/write	The font style of k characters. Can rel or NothingEnum e
kentenKind	KentenCharacter KentenCharacter.CUSTOM KentenCharacter.KENTEN_BLACK_CIRCLE KentenCharacter.KENTEN_BLACK_TRIANGLE KentenCharacter.KENTEN_BULLSEYE KentenCharacter.KENTEN_FISHEYE KentenCharacter.KENTEN_SESAME_DOT KentenCharacter.KENTEN_SMALL_BLACK_CIRCLE KentenCharacter.KENTEN_SMALL_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_SESAME_DOT KentenCharacter.KENTEN_WHITE_TRIANGLE KentenCharacter.NONE NothingEnum.NOTHING	read/write	The style of kenter characters. Can rel KentenCharacter e or NothingEnum e
kentenOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of ove the kenten fill. Car AdornmentOverpr enumerator or No enumerator.
kentenOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of ove the kenten stroke. return: Adornmen enumerator or No enumerator.
kentenPlacement	Real NothingEnum.NOTHING	read/write	The distance betw characters and the characters. Can rel or NothingEnum e
kentenPosition	RubyKentenPosition RubyKentenPosition.ABOVE_RIGHT RubyKentenPosition.BELOW_LEFT NothingEnum.NOTHING	read/write	The kenten positio to the parent char return: RubyKente enumerator or No enumerator.
kentenStrokeColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the stroke of kente characters. Can rel Swatch, String or NothingEnum enu
kentenStrokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The stroke tint (as percentage) of ker characters. (Range Can return: Real o NothingEnum enu
kentenTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The fill tint (as a p of kenten characte

Property	Type	Access	Description
			0 to 100). Can return NothingEnum enumerator.
kentenWeight	Real NothingEnum.NOTHING	read/write	The stroke weight of kenten characters. Can return: Real or NothingEnum enumerator.
kentenXScale	Real NothingEnum.NOTHING	read/write	The horizontal size of characters as a percentage of the original size. Can return: Real or NothingEnum enumerator.
kentenYScale	Real NothingEnum.NOTHING	read/write	The vertical size of characters as a percentage of the original size. Can return: Real or NothingEnum enumerator.
kerningMethod	String NothingEnum.NOTHING	read/write	The type of pair kerning. Can return: String or NothingEnum enumerator.
kerningValue	Real NothingEnum.NOTHING	read/write	The amount of space to add or remove between characters, specified in thousands of an em. Can return: Real or NothingEnum enumerator.
keyboardDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION NothingEnum.NOTHING	read/write	The keyboard direction for the character. Can return: CharacterDirectionOptions enumerator or NothingEnum enumerator.
kinsokuHangType	KinsokuHangTypes KinsokuHangTypes.KINSOKU_HANG_FORCE KinsokuHangTypes.KINSOKU_HANG_REGULAR KinsokuHangTypes.NONE NothingEnum.NOTHING	read/write	The type of hanging punctuation to allow. Valid only when alignment is in effect. Can return: KinsokuHangTypes enumerator or NothingEnum enumerator.
kinsokuSet	KinsokuSet KinsokuSet.HARD_KINSOKU KinsokuSet.KOREAN_KINSOKU KinsokuSet.NOTHING KinsokuSet.SIMPLIFIED_CHINESE_KINSOKU KinsokuSet.SOFT_KINSOKU KinsokuSet.TRADITIONAL_CHINESE_KINSOKU KinsokuTable String NothingEnum.NOTHING	read/write	The kinsoku set that determines legitimate line breaks. Can return: KinsokuTable, KinsokuSet enumerator, String, or NothingEnum enumerator.
kinsokuType	KinsokuType KinsokuType.KINSOKU_PRIORITIZE_ADJUSTMENT_AMOUNT KinsokuType.KINSOKU_PUSH_IN_FIRST KinsokuType.KINSOKU_PUSH_OUT_FIRST KinsokuType.KINSOKU_PUSH_OUT_ONLY NothingEnum.NOTHING	read/write	The type of kinsoku processing for pre-kinsoku characters at the beginning or end of a line. Note: Valid only when kinsoku set is defined. Can return: KinsokuType enumerator or NothingEnum enumerator.
lastLineIndent	Unit NothingEnum.NOTHING	read/write	The amount to indent the last line in the paragraph. Can return: Unit or NothingEnum enumerator.
leading	Leading Leading.AUTO Unit NothingEnum.NOTHING	read/write	The leading applied to the text. Can return: Unit, Leading enumerator, or NothingEnum enumerator.
leadingAki	Real NothingEnum.NOTHING	read/write	The amount of space between each character. Can return: Real or NothingEnum enumerator.

Property	Type	Access	Description
leadingModel	LeadingModel LeadingModel.LEADING_MODEL_AKI_ABOVE LeadingModel.LEADING_MODEL_AKI_BELOW LeadingModel.LEADING_MODEL_CENTER LeadingModel.LEADING_MODEL_CENTER_DOWN LeadingModel.LEADING_MODEL_ROMAN NothingEnum.NOTHING	read/write	The point from wh is measured from l Can return: Leadin enumerator or No enumerator.
leftIndent	Unit NothingEnum.NOTHING	read/write	The width of the le Can return: Unit o NothingEnum enu
ligatures	Boolean NothingEnum.NOTHING	read/write	If true, replaces sp character combina fl, fi) with ligature Can return: Boolea NothingEnum enu
markupTag	String NothingEnumCanalsoaccept:XMLTag	read/write	The XML tag applic element. Can retur or NothingEnum e Can also accept: Xl
miterLimit	Real(0-1000) NothingEnum.NOTHING	read/write	The limit of the rat width to miter len a miter (pointed) j becomes a bevel (: off) join. Can retur 1000) or NothingE enumerator.
mojikumi	MojikumiTable MojikumiTableDefaults MojikumiTableDefaults.LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.NOTHING MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.SIMP_CHINESE_DEFAULT MojikumiTableDefaults.TRAD_CHINESE_DEFAULT String NothingEnum.NOTHING	read/write	The mojikumi tabl information, see r table defaults. Can MojikumiTable, Str MojikumiTableDef enumerator or No enumerator.
noBreak	Boolean NothingEnum.NOTHING	read/write	If true, keeps the t same line. . Can re Boolean or Nothin enumerator.
numberingApplyRestartPolicy	Boolean NothingEnum.NOTHING	read/write	If true, apply the n restart policy. Can Boolean or Nothin enumerator.
numberingCharacterStyle	CharacterStyle String NothingEnum.NOTHING	read/write	The character style used for the numb Can return: Charac String or NothingE enumerator.
numberingContinue	Boolean NothingEnum.NOTHING	read/write	Continue the num this level. Can retu Boolean or Nothin enumerator.
numberingExpression	String NothingEnum.NOTHING	read/write	The number string for numbering. Ca String or NothingE enumerator.

Property	Type	Access	Description
numberingFormat	NumberingStyle NumberingStyle.ARABIC NumberingStyle.ARABIC_ABJAD NumberingStyle.ARABIC_ALIF_BA_TAH NumberingStyle.DOUBLE_LEADING_ZEROS NumberingStyle.FORMAT_NONE NumberingStyle.HEBREW_BIBLICAL NumberingStyle.HEBREW_NON_STANDARD NumberingStyle.KANJI NumberingStyle.KATAKANA_MODERN NumberingStyle.KATAKANA_TRADITIONAL NumberingStyle.LOWER_LETTERS NumberingStyle.LOWER_ROMAN NumberingStyle.SINGLE_LEADING_ZEROS NumberingStyle.TRIPLE_LEADING_ZEROS NumberingStyle.UPPER_LETTERS NumberingStyle.UPPER_ROMAN String NothingEnum.NOTHING	read/write	Numbering format Can return: NumberingStyle enumerator, String or NothingEnum enumerator
numberingLevel	LongInteger NothingEnum.NOTHING	read/write	The level of the paragraph Can return: Long Integer or NothingEnum enumerator
numberingRestartPolicies	NumberingRestartPolicy NothingEnum.NOTHING	readonly	Numbering restart policy Can return: NumberingRestartPolicy enumerator or NothingEnum enumerator
numberingStartAt	LongInteger NothingEnum.NOTHING	read/write	Determines starting index in a numbered list. return: Long Integer or NothingEnum enumerator
otfContextualAlternate	Boolean NothingEnum.NOTHING	read/write	If true, uses contextual alternate forms in OpenType fonts. Can return: Boolean or NothingEnum enumerator
otfDiscretionaryLigature	Boolean NothingEnum.NOTHING	read/write	If true, uses discretionary ligatures in OpenType fonts. Can return: Boolean or NothingEnum enumerator
otfFigureStyle	OTFFigureStyle OTFFigureStyle.DEFAULT_VALUE OTFFigureStyle.PROPORTIONAL_LINING OTFFigureStyle.PROPORTIONAL_OLDSTYLE OTFFigureStyle.TABULAR_LINING OTFFigureStyle.TABULAR_OLDSTYLE NothingEnum.NOTHING	read/write	The figure style in OpenType fonts. Can return: OTFFigureStyle enumerator or NothingEnum enumerator
otfFraction	Boolean NothingEnum.NOTHING	read/write	If true, uses fractional forms in OpenType fonts. Can return: Boolean or NothingEnum enumerator
otfHVKana	Boolean NothingEnum.NOTHING	read/write	If true, switches horizontal and vertical glyphs for horizontal and vertical. Can return: Boolean or NothingEnum enumerator
otfHistorical	Boolean NothingEnum.NOTHING	read/write	If true, use historical forms in OpenType fonts. Can return: Boolean or NothingEnum enumerator
otfJustificationAlternate	Boolean NothingEnum.NOTHING	read/write	If true, use alternative justification forms in OpenType fonts. Can return: Boolean or NothingEnum enumerator
otfLocale	Boolean NothingEnum.NOTHING	read/write	If true, uses localized forms in OpenType fonts. Can return: Boolean or NothingEnum enumerator

Property	Type	Access	Description
otfMark	Boolean NothingEnum.NOTHING	read/write	If true, uses mark in OpenType fonts return: Boolean or NothingEnum enu
otfOrdinal	Boolean NothingEnum.NOTHING	read/write	If true, uses ordina OpenType fonts. C Boolean or Nothin enumerator.
otfOverlapSwash	Boolean NothingEnum.NOTHING	read/write	If true, use overlap swash forms in Op fonts. Can return: NothingEnum enu
otfProportionalMetrics	Boolean NothingEnum.NOTHING	read/write	If true, kerns accor proportional CJK n OpenType fonts. C Boolean or Nothin enumerator.
otfRomanItalics	Boolean NothingEnum.NOTHING	read/write	If true, applies itali width alphanumeric return: Boolean or NothingEnum enu
otfSlashedZero	Boolean NothingEnum.NOTHING	read/write	If true, use a slash in OpenType fonts return: Boolean or NothingEnum enu
otfStretchedAlternate	Boolean NothingEnum.NOTHING	read/write	If true, use stretch alternate forms in fonts. Can return: NothingEnum enu
otfStylisticAlternate	Boolean NothingEnum.NOTHING	read/write	If true, use stylistic forms in OpenType return: Boolean or NothingEnum enu
otfStylisticSets	LongInteger NothingEnum.NOTHING	read/write	The stylistic sets to OpenType fonts. C Long Integer or No enumerator.
otfSwash	Boolean NothingEnum.NOTHING	read/write	If true, uses swash OpenType fonts. C Boolean or Nothin enumerator.
otfTitling	Boolean NothingEnum.NOTHING	read/write	If true, uses titling OpenType fonts. C Boolean or Nothin enumerator.
overprintFill	Boolean NothingEnum.NOTHING	read/write	If true, the fill color characters will ove return: Boolean or NothingEnum enu
overprintStroke	Boolean NothingEnum.NOTHING	read/write	If true, the stroke c characters will ove return: Boolean or NothingEnum enu
paragraphDirection	ParagraphDirectionOptions ParagraphDirectionOptions.LEFT_TO_RIGHT_DIRECTION ParagraphDirectionOptions.RIGHT_TO_LEFT_DIRECTION NothingEnum.NOTHING	read/write	Paragraph direction return: ParagraphDirection enumerator or No enumerator.
paragraphGyoudori	Boolean NothingEnum.NOTHING	read/write	If true, the gyoudo applies to the entire paragraph. If false, gyoudori mode applies to each line in the paragraph. Can return: Boolean or NothingEnum enu

Property	Type	Access	Description
paragraphJustification	ParagraphJustificationOptions ParagraphJustificationOptions.ARABIC_JUSTIFICATION ParagraphJustificationOptions.DEFAULT_JUSTIFICATION ParagraphJustificationOptions.NASKH_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION_FRAC ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION_FRAC NothingEnum.NOTHING	read/write	Paragraph justification return: ParagraphJustificationOptions enumerator or NothingEnum enumerator.
paragraphKashidaWidth	Real NothingEnum.NOTHING	read/write	Paragraph kashida width. Can return: none, 1 is short, 2 is medium, 3 is long. Can return: NothingEnum enumerator.
parent	Application	readonly	The parent of the ChangeGrepPreferences (Application).
pointSize	Unit NothingEnum.NOTHING	read/write	The text size. Can return: Unit or NothingEnum enumerator.
position	Position Position.NORMAL Position.OT_DENOMINATOR Position.OT_NUMERATOR Position.OT_SUBSCRIPT Position.OT_SUPERSCRIPT Position.SUBSCRIPT Position.SUPERSCRIPT NothingEnum.NOTHING	read/write	The text position relative to the baseline. Can return: Position enumerator or NothingEnum enumerator.
positionalForm	PositionalForms PositionalForms.CALCULATE PositionalForms.FINAL PositionalForms.INITIAL PositionalForms.ISOLATED PositionalForms.MEDIAL PositionalForms.NONE NothingEnum.NOTHING	read/write	The OpenType positional form. Can return: PositionalForms enumerator or NothingEnum enumerator.
preferences	Preferences <i>Preference</i>	readonly	A collection of preference objects.
properties	Object	read/write	A property that all of several properties share the same time.
rensuuji	Boolean NothingEnum.NOTHING	read/write	If true, disallows line breaks in numbers. If false, allows a break between digits in multi-digit numbers. Can return: Boolean or NothingEnum enumerator.
rightIndent	Unit NothingEnum.NOTHING	read/write	The width of the right margin. Can return: Unit or NothingEnum enumerator.
rotateSingleByteCharacters	Boolean NothingEnum.NOTHING	read/write	If true, rotates ROR characters in vertical text. Can return: Boolean or NothingEnum enumerator.
rubyAlignment	RubyAlignments RubyAlignments.RUBY_1_AKI RubyAlignments.RUBY_CENTER RubyAlignments.RUBY_EQUAL_AKI RubyAlignments.RUBY_FULL_JUSTIFY RubyAlignments.RUBY_JIS RubyAlignments.RUBY_LEFT RubyAlignments.RUBY_RIGHT NothingEnum.NOTHING	read/write	The ruby alignment. Can return: RubyAlignments enumerator or NothingEnum enumerator.
rubyAutoAlign	Boolean NothingEnum.NOTHING	read/write	If true, auto aligns ruby text. Can return: Boolean or NothingEnum enumerator.
rubyAutoScaling	Boolean NothingEnum.NOTHING	read/write	If true, automatically scales ruby text to the specified size.

Property	Type	Access	Description
			of parent text size. information on spe percent, see ruby scaling percent. . C Boolean or Nothin enumerator.
rubyAutoTcyAutoScale	Boolean NothingEnum.NOTHING	read/write	If true, automatica glyphs in auto tcy yoko) in ruby to fit Can return: Boolea NothingEnum enu
rubyAutoTcyDigits	ShortInteger NothingEnum.NOTHING	read/write	The number of dig included in auto tc chuu-yoko) in ruby return: Short Integ NothingEnum enu
rubyAutoTcyIncludeRoman	Boolean NothingEnum.NOTHING	read/write	If true, includes Rc characters in auto chuu-yoko) in ruby return: Boolean or NothingEnum enu
rubyFill	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the fill of ruby cha Can return: Swatch NothingEnum enu
rubyFont	Font String NothingEnum.NOTHING	read/write	The font applied to characters. Can rel String or NothingE enumerator.
rubyFontSize	Real NothingEnum.NOTHING	read/write	The size (in points) characters. Can rel or NothingEnum e
rubyFontStyle	String NothingEnum.NOTHING	read/write	The font style of r characters. Can rel or NothingEnum e
rubyOpenTypePro	Boolean NothingEnum.NOTHING	read/write	If true, uses Open1 fonts for ruby. Can Boolean or Nothin enumerator.
rubyOverhang	Boolean NothingEnum.NOTHING	read/write	If true, constrains overhang to the sp amount. For inforr specifying an amo ruby parent overh amount. . Can rett Boolean or Nothin enumerator.
rubyOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of ove the ruby fill. Can r AdornmentOverpr enumerator or No enumerator.
rubyOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of ove the ruby stroke. Ca AdornmentOverpr enumerator or No enumerator.
rubyParentOverhangAmount	RubyOverhang RubyOverhang.NONE RubyOverhang.RUBY_OVERHANG_HALF_CHAR RubyOverhang.RUBY_OVERHANG_HALF_RUBY RubyOverhang.RUBY_OVERHANG_NO_LIMIT RubyOverhang.RUBY_OVERHANG_ONE_CHAR RubyOverhang.RUBY_OVERHANG_ONE_RUBY NothingEnum.NOTHING	read/write	The amount by wh characters can ove parent text. Can re RubyOverhang eni or NothingEnum e
rubyParentScalingPercent	Real NothingEnum.NOTHING	read/write	The amount (as a percentage) to sca

Property	Type	Access	Description
			parent text size to the ruby text size. Real or NothingEnum enumerator.
rubyParentSpacing	RubyParentSpacing RubyParentSpacing.RUBY_PARENT_121_AKI RubyParentSpacing.RUBY_PARENT_BOTH_SIDES RubyParentSpacing.RUBY_PARENT_EQUAL_AKI RubyParentSpacing.RUBY_PARENT_FULL_JUSTIFY RubyParentSpacing.RUBY_PARENT_NO_ADJUSTMENT NothingEnum.NOTHING	read/write	The ruby spacing relative to the parent text. Can return: RubyParentSpacing enumerator or NothingEnum enumerator.
rubyPosition	RubyKantenPosition RubyKantenPosition.ABOVE_RIGHT RubyKantenPosition.BELOW_LEFT NothingEnum.NOTHING	read/write	The position of ruby characters relative to the parent text. Can return: RubyKantenPosition enumerator or NothingEnum enumerator.
rubyStroke	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the stroke of ruby characters. Can return: Swatch or NothingEnum enumerator.
rubyStrokeTint	Real NothingEnum.NOTHING	read/write	The stroke tint (as percentage) of ruby characters. Can return: Real or NothingEnum enumerator.
rubyTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as percentage) of the ruby fill color. Can return: Real or NothingEnum enumerator.
rubyType	RubyTypes RubyTypes.GROUP_RUBY RubyTypes.PER_CHARACTER_RUBY NothingEnum.NOTHING	read/write	The ruby type. Can return: RubyTypes enumerator or NothingEnum enumerator.
rubyWeight	Real NothingEnum.NOTHING	read/write	The stroke weight of ruby characters. Can return: Real or NothingEnum enumerator.
rubyXOffset	Real NothingEnum.NOTHING	read/write	The amount of horizontal space between ruby and parent characters. Can return: Real or NothingEnum enumerator.
rubyXScale	Real NothingEnum.NOTHING	read/write	The horizontal size of ruby characters, specified as a percent of the original size. Can return: Real or NothingEnum enumerator.
rubyYOffset	Real NothingEnum.NOTHING	read/write	The amount of vertical space between ruby and parent characters. Can return: Real or NothingEnum enumerator.
rubyYScale	Real NothingEnum.NOTHING	read/write	The vertical size of ruby characters, specified as a percent of the original size. Can return: Real or NothingEnum enumerator.
sameParaStyleSpacing	Spacing Spacing.SETIGNORE Unit NothingEnum.NOTHING	read/write	The space between paragraphs using the same style. Can return: Unit, Spacing enumerator or NothingEnum enumerator.
scaleAffectsLineHeight	Boolean NothingEnum.NOTHING	read/write	If true, the line height is affected when characters are scaled. Can return: Boolean or NothingEnum enumerator.

Property	Type	Access	Description
shataiAdjustRotation	Boolean NothingEnum.NOTHING	read/write	If true, applies shatai rotation. Can return NothingEnum
shataiAdjustTsume	Boolean NothingEnum.NOTHING	read/write	If true, adjusts shatai tsume. Can return: Boolean or NothingEnum
shataiDegreeAngle	Real NothingEnum.NOTHING	read/write	The shatai lens angle (in degrees). Can return NothingEnum
shataiMagnification	Real NothingEnum.NOTHING	read/write	The amount (as a percentage) of shatai obliquing to apply. return: Real or NothingEnum
singleWordJustification	SingleWordJustification SingleWordJustification.CENTER_ALIGN SingleWordJustification.FULLY_JUSTIFIED SingleWordJustification.LEFT_ALIGN SingleWordJustification.RIGHT_ALIGN NothingEnum.NOTHING	read/write	The alignment to use for words that contain a single character. Can return: SingleWordJustification enumerator or NothingEnum
skew	Real NothingEnum.NOTHING	read/write	The skew angle of the text. Can return: Real or NothingEnum
spaceAfter	Unit NothingEnum.NOTHING	read/write	The height of the space below. Can return: Unit or NothingEnum
spaceBefore	Unit NothingEnum.NOTHING	read/write	The height of the space above. Can return: Unit or NothingEnum
spanColumnMinSpaceAfter	Unit NothingEnum.NOTHING	read/write	The minimum space after a span or a split column. return: Unit or NothingEnum
spanColumnMinSpaceBefore	Unit NothingEnum.NOTHING	read/write	The minimum space before a span or a split column. return: Unit or NothingEnum
spanColumnType	SpanColumnTypeOptions SpanColumnTypeOptions.SINGLE_COLUMN SpanColumnTypeOptions.SPAN_COLUMNS SpanColumnTypeOptions.SPLIT_COLUMNS NothingEnum.NOTHING	read/write	Whether a paragraph is a single column, spans multiple columns or split columns. Can return: SpanColumnTypeOptions enumerator or NothingEnum
spanSplitColumnCount	ShortInteger(1-40) SpanColumnCountOptions SpanColumnCountOptions.ALL NothingEnum.NOTHING	read/write	The number of columns a paragraph spans or the number of split columns. return: Short Integer or SpanColumnCount enumerator or NothingEnum
splitColumnInsideGutter	Unit NothingEnum.NOTHING	read/write	The inside gutter of a paragraph splits columns. Can return: Unit or NothingEnum
splitColumnOutsideGutter	Unit NothingEnum.NOTHING	read/write	The outside gutter of a paragraph splits columns. Can return: Unit or NothingEnum
startParagraph	StartParagraph StartParagraph.ANYWHERE StartParagraph.NEXT_COLUMN StartParagraph.NEXT_EVEN_PAGE StartParagraph.NEXT_FRAME StartParagraph.NEXT_ODD_PAGE StartParagraph.NEXT_PAGE	read/write	The location at which the paragraph starts. Can return: StartParagraph enumerator or NothingEnum

Property	Type	Access	Description
	NothingEnum.NOTHING		
strikeThroughColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the strikethrough stroke uses. Can return: Swatch, String or NothingEnum enumerator.
strikeThroughGapColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the gap of the strikethrough stroke uses. Can return: String or NothingEnum enumerator.
strikeThroughGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color will overprint the strikethrough stroke. Note: Valid when strike through type is not solid. Can return: Boolean or NothingEnum enumerator.
strikeThroughGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the strikethrough gap color. (Range: 0 to 100). Valid when strike through type is not solid. Can return: Real or NothingEnum enumerator.
strikeThroughOffset	Unit NothingEnum.NOTHING	read/write	The amount by which to offset the strikethrough stroke from the text. Can return: Unit or NothingEnum enumerator.
strikeThroughOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the strikethrough stroke will overprint the text. Can return: Boolean or NothingEnum enumerator.
strikeThroughTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the strikethrough stroke. (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
strikeThroughType	String StrokeStyle NothingEnum.NOTHING	read/write	The stroke type of the strikethrough stroke. Can return: StrokeStyle or NothingEnum enumerator.
strikeThroughWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the strikethrough stroke. Can return: Unit or NothingEnum enumerator.
strikeThru	Boolean NothingEnum.NOTHING	read/write	If true, draws a straight line through the text. Can return: Boolean or NothingEnum enumerator.
strokeAlignment	TextStrokeAlign TextStrokeAlign.CENTER_ALIGNMENT TextStrokeAlign.OUTSIDE_ALIGNMENT NothingEnum.NOTHING	read/write	The stroke alignment relative to the text. Can return: TextStrokeAlign enumerator or NothingEnum enumerator.
strokeColor	String NothingEnumCanalsoaccept:Swatch	read/write	The swatch (color, tint, or mixed ink), or a stroke color, to which the stroke will change to. Can return: Swatch, String or NothingEnum enumerator. Can also accept: Swatch.
strokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the stroke color of the text. Can return: Real or NothingEnum enumerator. Can also accept: ChangeGrepPreference, a tint percentage, or a number in the range 0 to 100; to use the ink color.

Property	Type	Access	Description
			overridden value, Can return: Real or NothingEnum enumerator.
strokeWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the characters of text. Can return: Unit or NothingEnum enumerator.
tatechuyoko	Boolean NothingEnum.NOTHING	read/write	If true, makes the horizontal in vertical text. Can return: Boolean or NothingEnum enumerator.
tatechuyokoXOffset	Real NothingEnum.NOTHING	read/write	The horizontal offset of horizontal characters in vertical text. Can return: Real or NothingEnum enumerator.
tatechuyokoYOffset	Real NothingEnum.NOTHING	read/write	The vertical offset of horizontal characters in vertical text. Can return: Real or NothingEnum enumerator.
tracking	Real NothingEnum.NOTHING	read/write	The amount by which to loosen or tighten a text, specified in terms of an em. Can return: Real or NothingEnum enumerator.
trailingAki	Real NothingEnum.NOTHING	read/write	The amount of space between each character. Can return: Real or NothingEnum enumerator.
treatIdeographicSpaceAsSpace	Boolean NothingEnum.NOTHING	read/write	If true, ideographic spaces will not wrap to the next line like text characters. Can return: Boolean or NothingEnum enumerator.
tsume	Real NothingEnum.NOTHING	read/write	The amount of horizontal space each character compresses. Can return: Real or NothingEnum enumerator.
underline	Boolean NothingEnum.NOTHING	read/write	If true, underlines the text. Can return: Boolean or NothingEnum enumerator.
underlineColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the underline stroke. Can return: Swatch, String, or NothingEnum enumerator.
underlineGapColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the gap of the underline stroke. Note: Valid when underline type is not solid. Can return: Swatch, String, or NothingEnum enumerator.
underlineGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color of the underline stroke will overprint. Can return: Boolean or NothingEnum enumerator.
underlineGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the gap color of the underline stroke. (Range: 0 to 100). Note: Valid when underline type is not solid. Can return: Real or NothingEnum enumerator.
underlineOffset	Unit NothingEnum.NOTHING	read/write	The amount by which to offset the underline text baseline. Can return: Unit or NothingEnum enumerator.

Property	Type	Access	Description
underlineOverprint	Boolean NothingEnum.NOTHING	read/write	Unit or NothingEnum enumerator. If true, the underline color will overprint the text color. Can return: Boolean or NothingEnum enumerator.
underlineTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The underline stroke as a percentage. (Range 0 to 100). Can return: Real or NothingEnum enumerator.
underlineType	String StrokeStyle NothingEnum.NOTHING	read/write	The stroke type of underline stroke. Can return: StrokeStyle, String or NothingEnum enumerator.
underlineWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of underline stroke. Can return: Unit or NothingEnum enumerator.
verticalScale	Real NothingEnum.NOTHING	read/write	The vertical scaling of the ChangeGrepProperty. Can return: Real or NothingEnum enumerator.
warichu	Boolean NothingEnum.NOTHING	read/write	If true, turns on warichu. Can return: Boolean or NothingEnum enumerator.
warichuAlignment	WarichuAlignment WarichuAlignment.AUTO WarichuAlignment.CENTER_ALIGN WarichuAlignment.CENTER_JUSTIFIED WarichuAlignment.FULLY_JUSTIFIED WarichuAlignment.LEFT_ALIGN WarichuAlignment.LEFT_JUSTIFIED WarichuAlignment.RIGHT_ALIGN WarichuAlignment.RIGHT_JUSTIFIED NothingEnum.NOTHING	read/write	The warichu alignment. Can return: WarichuAlignment enumerator or NothingEnum enumerator.
warichuCharsAfterBreak	ShortInteger NothingEnum.NOTHING	read/write	The minimum number of characters allowed after a line break. Can return: Integer or NothingEnum enumerator.
warichuCharsBeforeBreak	ShortInteger NothingEnum.NOTHING	read/write	The minimum number of characters allowed before a line break. Can return: Integer or NothingEnum enumerator.
warichuLineSpacing	Real NothingEnum.NOTHING	read/write	The gap between lines of warichu characters. Can return: Real or NothingEnum enumerator.
warichuLines	ShortInteger NothingEnum.NOTHING	read/write	The number of lines of warichu within a normal line. Can return: Short Integer or NothingEnum enumerator.
warichuSize	Real NothingEnum.NOTHING	read/write	The amount (as a percentage) to scale the text size to determine the warichu size. Can return: Real or NothingEnum enumerator.
xOffsetDiacritic	Real NothingEnum.NOTHING	read/write	The x (horizontal) offset of the diacritic adjustment. Can return: Real or NothingEnum enumerator.
yOffsetDiacritic	Real NothingEnum.NOTHING	read/write	The y (vertical) offset of the diacritic adjustment. Can return: Real or NothingEnum enumerator.

Method Listing

EventListener **addEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

ChangeGrepPreference **getElements** ()

Resolves the object specifier, creating an array of object references.

Boolean **isNthDesignAxisHidden** (nthAxisIndex:*Number*)

If true, Nth design axis of variable font is hidden.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **setNthDesignAxis** (nthAxisIndex:*Number*, nthAxisValue:*Number*)

Set Nth design axis of a variable font.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.
nthAxisValue	Number	Value of nth design axis.

String **toSource** ()

Generates a string which, if executed, will return the ChangeGrepPreference.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Application.changeGrepPreferences

Bullet.parent

Event.parent

EventListener.parent

MutationEvent.parent

NumberingRestartPolicy.parent

Preference.parent

Return

ChangeGrepPreference.getElements()