

# Character

A text character.

Go to [Property Listing](#) | [Method Listing](#)

## Methods:

[addEventListener](#), [applyCharacterStyle](#), [applyConditions](#), [applyParagraphStyle](#), [asynchronousExportFile](#), [autoTag](#), [changeGlyph](#), [changeGrep](#), [changeText](#), [changeTransliterate](#), [changepcase](#), [clearOverrides](#), [convertBulletsAndNumberingToText](#), [convertToNote](#), [convertToTable](#), [createEmailQRCode](#), [createHyperlinkQRCode](#), [createOutlines](#), [createPlainTextQRCode](#), [createStyleThumbnailWithProperties](#), [createTextMsgQRCode](#), [createThumbnailWithProperties](#), [createVCardQRCode](#), [duplicate](#), [exportFile](#), [findGlyph](#), [findGrep](#), [findHyperlinks](#), [findText](#), [findTransliterate](#), [getElements](#), [isNthDesignAxisHidden](#), [markup](#), [move](#), [place](#), [recompose](#), [remove](#), [removeEventListener](#), [select](#), [setNthDesignAxis](#), [showText](#), [textHasOverrides](#), [toSource](#), [toSpecifier](#)

## Objects:

[AdornmentOverprint](#), [AlternateGlyphForms](#), [BalanceLinesStyle](#), [Boolean](#), [Bullet](#), [Buttons](#), [Capitalization](#), [CharacterAlignment](#), [CharacterDirectionOptions](#), [CharacterStyle](#), [Characters](#), [CheckBoxes](#), [ComboBoxes](#), [Condition](#), [CornerOptions](#), [DiacriticPositionOptions](#), [DigitsTypeOptions](#), [EPSTexts](#), [EndCap](#), [EndJoin](#), [EndnoteRanges](#), [EndnoteTextFrames](#), [EventListeners](#), [Events](#), [Font](#), [Footnotes](#), [FormFields](#), [Graphic](#), [GraphicLines](#), [GridAlignment](#), [Groups](#), [HiddenTexts](#), [HyphenationStyleEnum](#), [InsertionPoints](#), [Justification](#), [KashidasOptions](#), [KentenAlignment](#), [KentenCharacter](#), [KentenCharacterSet](#), [KinsokuHangTypes](#), [KinsokuSet](#), [KinsokuTable](#), [KinsokuType](#), [LanguageWithVendors](#), [Leading](#), [LeadingModel](#), [Lines](#), [ListAlignment](#), [ListBoxes](#), [ListType](#), [MojikumiTable](#), [MojikumiTableDefaults](#), [MultiStateObjects](#), [NestedGrepStyles](#), [NestedLineStyles](#), [NestedStyles](#), [Notes](#), [NothingEnum](#), [Number](#), [NumberingList](#), [NumberingRestartPolicy](#), [NumberingStyle](#), [OTFFigureStyle](#), [Object](#), [OutlineJoin](#), [Ovals](#), [PageItem](#), [PageItems](#), [ParagraphBorderBottomOriginEnum](#), [ParagraphBorderEnum](#), [ParagraphBorderTopOriginEnum](#), [ParagraphDirectionOptions](#), [ParagraphJustificationOptions](#), [ParagraphShadingBottomOriginEnum](#), [ParagraphShadingTopOriginEnum](#), [ParagraphShadingWidthEnum](#), [ParagraphStyle](#), [Paragraphs](#), [Polygons](#), [Position](#), [PositionalForms](#), [Preferences](#), [RadioButtons](#), [Rectangles](#), [RubyAlignments](#), [RubyKentenPosition](#), [RubyOverhang](#), [RubyParentSpacing](#), [RubyTypes](#), [RuleWidth](#), [SignatureFields](#), [SingleWordJustification](#), [Spacing](#), [SpanColumnCountOptions](#), [SpanColumnTypeOptions](#), [SpecialCharacters](#), [SplineItems](#), [StartParagraph](#), [String](#), [StrokeStyle](#), [Swatch](#), [TabStops](#), [Tables](#), [TextBoxes](#), [TextColumns](#), [TextFrames](#), [TextPaths](#), [TextStrokeAlign](#), [TextStyleRanges](#), [TextVariableInstances](#), [Texts](#), [WarichuAlignment](#), [Words](#), [XMLItem](#),

## Preferences:

[Preferences](#)

## Hierarchy:

Superclass: [Text](#)

Class: [Character](#)

## Property Listing

| Property                                  | Type                                                                                | Access     | Desc                                                                                  |
|-------------------------------------------|-------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------------------------|
| <a href="#">alignToBaseline</a>           | <a href="#">Boolean</a>                                                             | read/write | If true, the character aligns to the baseline of the grid.                            |
| <a href="#">allGraphics</a>               | <a href="#">Array of Graphic</a>                                                    | readonly   | Lists all the graphics contained in the character.                                    |
| <a href="#">allPageItems</a>              | <a href="#">Array of PageItem</a>                                                   | readonly   | Lists all the page items contained in the character.                                  |
| <a href="#">allowArbitraryHyphenation</a> | <a href="#">Boolean</a>                                                             | read/write | If true, the character can be hyphenated at any point.                                |
| <a href="#">appliedCharacterStyle</a>     | <a href="#">CharacterStyle</a><br><a href="#">String</a>                            | read/write | The character style applied to the character. Also see <a href="#">appliedStyle</a> . |
| <a href="#">appliedConditions</a>         | <a href="#">Array of Condition</a>                                                  | read/write | The conditions applied to the character.                                              |
| <a href="#">appliedFont</a>               | <a href="#">Font</a><br><a href="#">String</a>                                      | read/write | The font applied to the character. Either a font name or a font object.               |
| <a href="#">appliedLanguage</a>           | <a href="#">LanguageWithVendors</a><br><a href="#">LanguageCanAlsoAccept:String</a> | read/write | The language applied to the character. Can be a language name or a language object.   |

| Property                    | Type                                                                                                                                                                                                                                                            | Access     | Description                                                                                                                                |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| appliedNestedStyles         | Array of <a href="#">CharacterStyle</a>                                                                                                                                                                                                                         | readonly   | The nested styles applied to the text.                                                                                                     |
| appliedNumberingList        | <a href="#">NumberingList</a><br>String                                                                                                                                                                                                                         | read/write | The numbering list applied to the text. Returns a string.                                                                                  |
| appliedParagraphStyle       | <a href="#">ParagraphStyle</a><br>String                                                                                                                                                                                                                        | read/write | The paragraph style applied to the text. Also applies to the first line of the paragraph.                                                  |
| ascent                      | Number<br>String                                                                                                                                                                                                                                                | readonly   | The ascent of the text. Returns a number or a string.                                                                                      |
| associatedXMLElements       | Array of <a href="#">XMLItem</a>                                                                                                                                                                                                                                | readonly   | The XML elements associated with the text.                                                                                                 |
| autoLeading                 | Number (range 0 - 500)                                                                                                                                                                                                                                          | read/write | The auto leading of the text. Returns a number.                                                                                            |
| autoTcy                     | Number                                                                                                                                                                                                                                                          | read/write | The auto text case of the text. Returns a number.                                                                                          |
| autoTcyIncludeRoman         | Boolean                                                                                                                                                                                                                                                         | read/write | If true, the text case includes Roman numerals.                                                                                            |
| balanceRaggedLines          | Boolean<br><a href="#">BalanceLinesStyle</a><br><a href="#">BalanceLinesStyle.FULLY_BALANCED</a><br><a href="#">BalanceLinesStyle.NO_BALANCING</a><br><a href="#">BalanceLinesStyle.PYRAMID_SHAPE</a><br><a href="#">BalanceLinesStyle.VEE_SHAPE</a>            | read/write | If true, the text is balanced. Returns a boolean or a <a href="#">BalanceLinesStyle</a> object. Note: single line text cannot be balanced. |
| baseline                    | Number<br>String                                                                                                                                                                                                                                                | readonly   | The baseline of the text. Returns a number or a string.                                                                                    |
| baselineShift               | Number<br>String                                                                                                                                                                                                                                                | read/write | The baseline shift of the text. Returns a number or a string.                                                                              |
| bulletChar                  | <a href="#">Bullet</a>                                                                                                                                                                                                                                          | readonly   | The bullet character of the text.                                                                                                          |
| bulletsAlignment            | <a href="#">ListAlignment</a><br><a href="#">ListAlignment.CENTER_ALIGN</a><br><a href="#">ListAlignment.LEFT_ALIGN</a><br><a href="#">ListAlignment.RIGHT_ALIGN</a>                                                                                            | read/write | The alignment of the bullets. Returns a <a href="#">ListAlignment</a> object.                                                              |
| bulletsAndNumberingListType | <a href="#">ListType</a><br><a href="#">ListType.BULLET_LIST</a><br><a href="#">ListType.NO_LIST</a><br><a href="#">ListType.NUMBERED_LIST</a>                                                                                                                  | read/write | The type of the bullets and numbering list. Returns a <a href="#">ListType</a> object.                                                     |
| bulletsCharacterStyle       | <a href="#">CharacterStyle</a><br>String                                                                                                                                                                                                                        | read/write | The character style of the bullets. Returns a <a href="#">CharacterStyle</a> object or a string.                                           |
| bulletsTextAfter            | String                                                                                                                                                                                                                                                          | read/write | The text after the bullets. Returns a string.                                                                                              |
| bunriKinshi                 | Boolean                                                                                                                                                                                                                                                         | read/write | If true, the text is periodic. Returns a boolean.                                                                                          |
| buttons                     | <a href="#">Buttons</a> <i>Button</i>                                                                                                                                                                                                                           | readonly   | A collection of buttons.                                                                                                                   |
| capitalization              | <a href="#">Capitalization</a><br><a href="#">Capitalization.ALL_CAPS</a><br><a href="#">Capitalization.CAP_TO_SMALL_CAP</a><br><a href="#">Capitalization.LOWER_CASE</a><br><a href="#">Capitalization.NORMAL</a><br><a href="#">Capitalization.SMALL_CAPS</a> | read/write | The capitalization of the text. Returns a <a href="#">Capitalization</a> object.                                                           |

| Property           | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Access     | Desc                                    |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------------------------------------|
| characterAlignment | <b>CharacterAlignment</b><br>CharacterAlignment.ALIGN_BASELINE<br>CharacterAlignment.ALIGN_EM_BOTTOM<br>CharacterAlignment.ALIGN_EM_CENTER<br>CharacterAlignment.ALIGN_EM_TOP<br>CharacterAlignment.ALIGN_ICF_BOTTOM<br>CharacterAlignment.ALIGN_ICF_TOP                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | read/write | The i<br>char:<br>char:                 |
| characterDirection | <b>CharacterDirectionOptions</b><br>CharacterDirectionOptions.DEFAULT_DIRECTION<br>CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION<br>CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | The i<br>char:                          |
| characterRotation  | <b>Number</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | The i<br>degr<br>char:<br>rotat<br>coun |
| characters         | <b>Characters</b> <i>Character</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | readonly   | A col                                   |
| checkboxes         | <b>CheckBoxes</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | readonly   | A col<br>chec                           |
| cjkGridTracking    | <b>Boolean</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | read/write | If tru<br>to tr<br>char:                |
| comboBoxes         | <b>ComboBoxes</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | readonly   | A col<br>coml                           |
| composer           | <b>String</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | The t<br>to cc                          |
| contents           | <b>String</b><br><b>SpecialCharacters</b><br>SpecialCharacters.ARABIC_COMMA<br>SpecialCharacters.ARABIC_KASHIDA<br>SpecialCharacters.ARABIC_QUESTION_MARK<br>SpecialCharacters.ARABIC_SEMICOLON<br>SpecialCharacters.AUTO_PAGE_NUMBER<br>SpecialCharacters.BULLET_CHARACTER<br>SpecialCharacters.COLUMN_BREAK<br>SpecialCharacters.COPYRIGHT_SYMBOL<br>SpecialCharacters.DEGREE_SYMBOL<br>SpecialCharacters.DISCRETIONARY_HYPHEN<br>SpecialCharacters.DISCRETIONARY_LINE_BREAK<br>SpecialCharacters.DOTTED_CIRCLE<br>SpecialCharacters.DOUBLE_LEFT_QUOTE<br>SpecialCharacters.DOUBLE_RIGHT_QUOTE<br>SpecialCharacters.DOUBLE_STRAIGHT_QUOTE<br>SpecialCharacters.ELLIPSIS_CHARACTER<br>SpecialCharacters.EM_DASH<br>SpecialCharacters.EM_SPACE<br>SpecialCharacters.END_NESTED_STYLE<br>SpecialCharacters.EN_DASH<br>SpecialCharacters.EN_SPACE<br>SpecialCharacters.EVEN_PAGE_BREAK<br>SpecialCharacters.FIGURE_SPACE<br>SpecialCharacters.FIXED_WIDTH_NONBREAKING_SPACE<br>SpecialCharacters.FLUSH_SPACE<br>SpecialCharacters.FOOTNOTE_SYMBOL<br>SpecialCharacters.FORCED_LINE_BREAK<br>SpecialCharacters.FRAME_BREAK<br>SpecialCharacters.HAIR_SPACE<br>SpecialCharacters.HEBREW_GERESH<br>SpecialCharacters.HEBREW_GERSHAYIM<br>SpecialCharacters.HEBREW_MAQAF<br>SpecialCharacters.HEBREW_SOF_PASUK<br>SpecialCharacters.INDENT_HERE_TAB<br>SpecialCharacters.LEFT_TO_RIGHT_EMBEDDING<br>SpecialCharacters.LEFT_TO_RIGHT_MARK<br>SpecialCharacters.LEFT_TO_RIGHT_OVERRIDE<br>SpecialCharacters.NEXT_PAGE_NUMBER<br>SpecialCharacters.NONBREAKING_HYPHEN<br>SpecialCharacters.NONBREAKING_SPACE<br>SpecialCharacters.ODD_PAGE_BREAK | read/write | The i<br>Can i<br>Spec<br>enur          |

| Property             | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Access     | Desc                                    |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-----------------------------------------|
|                      | SpecialCharacters.PAGE_BREAK<br>SpecialCharacters.PARAGRAPH_SYMBOL<br>SpecialCharacters.POP_DIRECTIONAL_FORMATTING<br>SpecialCharacters.PREVIOUS_PAGE_NUMBER<br>SpecialCharacters.PUNCTUATION_SPACE<br>SpecialCharacters.QUARTER_SPACE<br>SpecialCharacters.REGISTERED_TRADEMARK<br>SpecialCharacters.RIGHT_INDENT_TAB<br>SpecialCharacters.RIGHT_TO_LEFT_EMBEDDING<br>SpecialCharacters.RIGHT_TO_LEFT_MARK<br>SpecialCharacters.RIGHT_TO_LEFT_OVERRIDE<br>SpecialCharacters.SECTION_MARKER<br>SpecialCharacters.SECTION_SYMBOL<br>SpecialCharacters.SINGLE_LEFT_QUOTE<br>SpecialCharacters.SINGLE_RIGHT_QUOTE<br>SpecialCharacters.SINGLE_STRAIGHT_QUOTE<br>SpecialCharacters.SIXTH_SPACE<br>SpecialCharacters.TEXT_VARIABLE<br>SpecialCharacters.THIN_SPACE<br>SpecialCharacters.THIRD_SPACE<br>SpecialCharacters.TRADEMARK_SYMBOL<br>SpecialCharacters.ZERO_WIDTH_JOINER<br>SpecialCharacters.ZERO_WIDTH_NON_JOINER |            |                                         |
| descent              | <b>Number</b><br><b>String</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | readonly   | The i<br>any c                          |
| designAxes           | <b>Array of Number</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | read/write | Valu                                    |
| desiredGlyphScaling  | <b>Number</b> (range 50 - 200)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | read/write | The i<br>perc<br>char:<br>200)          |
| desiredLetterSpacing | <b>Number</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | read/write | The i<br>spec<br>of th<br>betw<br>font. |
| desiredWordSpacing   | <b>Number</b> (range 0 - 1000)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | read/write | The i<br>spec<br>of th<br>value         |
| diacriticPosition    | <b>DiacriticPositionOptions</b><br>DiacriticPositionOptions.DEFAULT_POSITION<br>DiacriticPositionOptions.LOOSE_POSITION<br>DiacriticPositionOptions.MEDIUM_POSITION<br>DiacriticPositionOptions.OPENTYPE_POSITION<br>DiacriticPositionOptions.OPENTYPE_POSITION_FROM_BASELINE<br>DiacriticPositionOptions.TIGHT_POSITION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | Posit<br>char:                          |
| digitsType           | <b>DigitsTypeOptions</b><br>DigitsTypeOptions.ARABIC_DIGITS<br>DigitsTypeOptions.BENGALI_DIGITS<br>DigitsTypeOptions.BURMESE_DIGITS<br>DigitsTypeOptions.DEFAULT_DIGITS<br>DigitsTypeOptions.DEVANAGARI_DIGITS<br>DigitsTypeOptions.FARSI_DIGITS<br>DigitsTypeOptions.FULL_FARSI_DIGITS<br>DigitsTypeOptions.GUJARATI_DIGITS<br>DigitsTypeOptions.GURMUKHI_DIGITS<br>DigitsTypeOptions.HINDI_DIGITS<br>DigitsTypeOptions.KANNADA_DIGITS<br>DigitsTypeOptions.KHMER_DIGITS<br>DigitsTypeOptions.LAO_DIGITS<br>DigitsTypeOptions.MALAYALAM_DIGITS<br>DigitsTypeOptions.NATIVE_DIGITS<br>DigitsTypeOptions.ORIYA_DIGITS<br>DigitsTypeOptions.TAMIL_DIGITS<br>DigitsTypeOptions.TELUGU_DIGITS<br>DigitsTypeOptions.THAI_DIGITS<br>DigitsTypeOptions.TIBETAN_DIGITS                                                                                                                                                         | read/write | The i                                   |
| dropCapCharacters    | <b>Number</b> (range 0 - 150)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | read/write | The i<br>to dr                          |

| Property            | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Access     | Desc                                                                                |
|---------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------------------------------------------|
| dropCapLines        | Number (range 0 - 25)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | read/write | The number of drop cap lines.                                                       |
| dropCapStyle        | CharacterStyle<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | read/write | The drop cap style, also.                                                           |
| dropcapDetail       | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | Detail base outline bear 0x10 used grid.                                            |
| endBaseline         | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | readonly   | Vertical of the                                                                     |
| endHorizontalOffset | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | readonly   | Horizontal end of                                                                   |
| endJoin             | OutlineJoin<br>OutlineJoin.BEVEL_END_JOIN<br>OutlineJoin.MITER_END_JOIN<br>OutlineJoin.ROUND_END_JOIN                                                                                                                                                                                                                                                                                                                                                                                                                        | read/write | The end of the applied                                                              |
| endnoteRanges       | EndnoteRanges <i>EndnoteRange</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | readonly   | A collection of text                                                                |
| endnoteTextFrames   | EndnoteTextFrames <i>EndnoteTextFrame</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | readonly   | A collection of text                                                                |
| epstexts            | EPSTexts <i>EPSText</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | readonly   | EPSTexts                                                                            |
| eventListeners      | EventListeners <i>EventListener</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | readonly   | A collection of listener                                                            |
| events              | Events <i>Event</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | readonly   | A collection of                                                                     |
| fillColor           | Swatch<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | read/write | The fill color (gradient, ink) of the object, accessible                            |
| fillTint            | Number (range 0 - 100)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | The fill tint of the Character, tint percentage from 0 to 100, in hexadecimal value |
| firstLineIndent     | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | read/write | The first line indent                                                               |
| fontStyle           | String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | The font style                                                                      |
| footnotes           | Footnotes <i>Footnote</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | readonly   | A collection of                                                                     |
| formFields          | FormFields <i>FormField</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | readonly   | A collection of                                                                     |
| glyphForm           | AlternateGlyphForms<br>AlternateGlyphForms.EXPERT_FORM<br>AlternateGlyphForms.FULL_WIDTH_FORM<br>AlternateGlyphForms.JIS04_FORM<br>AlternateGlyphForms.JIS78_FORM<br>AlternateGlyphForms.JIS83_FORM<br>AlternateGlyphForms.JIS90_FORM<br>AlternateGlyphForms.MONOSPACED_HALF_WIDTH_FORM<br>AlternateGlyphForms.NLC_FORM<br>AlternateGlyphForms.NONE<br>AlternateGlyphForms.PROPORTIONAL_WIDTH_FORM<br>AlternateGlyphForms.QUARTER_WIDTH_FORM<br>AlternateGlyphForms.THIRD_WIDTH_FORM<br>AlternateGlyphForms.TRADITIONAL_FORM | read/write | The glyph substitution glyph                                                        |
| gradientFillAngle   | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | The gradient fill angle of the                                                      |

| Property                  | Type                                                                                                                                                                                                                                 | Access     | Desc                                            |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------|
| gradientFillLength        | Number                                                                                                                                                                                                                               | read/write | The l<br>grad<br>radia<br>the f                 |
| gradientFillStart         | Array of Number<br>Array of String                                                                                                                                                                                                   | read/write | The :<br>coor<br>appli<br>text,                 |
| gradientStrokeAngle       | Number                                                                                                                                                                                                                               | read/write | The :<br>grad<br>strok<br>-180                  |
| gradientStrokeLength      | Number                                                                                                                                                                                                                               | read/write | The l<br>grad<br>radia<br>the s                 |
| gradientStrokeStart       | Array of Number<br>Array of String                                                                                                                                                                                                   | read/write | The :<br>coor<br>appli<br>the t<br>yl).         |
| graphicLines              | GraphicLines <i>GraphicLine</i>                                                                                                                                                                                                      | readonly   | A col<br>lines                                  |
| gridAlignFirstLineOnly    | Boolean                                                                                                                                                                                                                              | read/write | If tru<br>line t<br>base<br>align               |
| gridAlignment             | GridAlignment<br>GridAlignment.ALIGN_BASELINE<br>GridAlignment.ALIGN_EM_BOTTOM<br>GridAlignment.ALIGN_EM_CENTER<br>GridAlignment.ALIGN_EM_TOP<br>GridAlignment.ALIGN_ICF_BOTTOM<br>GridAlignment.ALIGN_ICF_TOP<br>GridAlignment.NONE | read/write | The :<br>fram<br>grid.                          |
| gridGyoudori              | Number                                                                                                                                                                                                                               | read/write | The i<br>setti                                  |
| groups                    | Groups <i>Group</i>                                                                                                                                                                                                                  | readonly   | A col                                           |
| hiddenTexts               | HiddenTexts <i>HiddenText</i>                                                                                                                                                                                                        | readonly   | A col<br>obje                                   |
| horizontalOffset          | Number<br>String                                                                                                                                                                                                                     | readonly   | The l<br>the t                                  |
| horizontalScale           | Number                                                                                                                                                                                                                               | read/write | The l<br>appli                                  |
| hyphenWeight              | Number (range 0 - 10)                                                                                                                                                                                                                | read/write | The i<br>bette<br>hyph<br>resul<br>hyph<br>100) |
| hyphenateAcrossColumns    | Boolean                                                                                                                                                                                                                              | read/write | If tru<br>worc<br>be h                          |
| hyphenateAfterFirst       | Number (range 1 - 15)                                                                                                                                                                                                                | read/write | The i<br>lette<br>a wo<br>by a                  |
| hyphenateBeforeLast       | Number (range 1 - 15)                                                                                                                                                                                                                | read/write | The i<br>lette<br>worc<br>by a                  |
| hyphenateCapitalizedWords | Boolean                                                                                                                                                                                                                              | read/write | If tru<br>hyph<br>worc                          |

| Property                 | Type                                                                                                                                                                                                                                                                                                              | Access     | Desc                                                  |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------------|
| hyphenateLadderLimit     | Number (range 0 - 25)                                                                                                                                                                                                                                                                                             | read/write | The i<br>hyph<br>on c<br>spec<br>cons<br>zero.        |
| hyphenateLastWord        | Boolean                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>hyph<br>worc<br>Note<br>hyph                |
| hyphenateWordsLongerThan | Number (range 3 - 25)                                                                                                                                                                                                                                                                                             | read/write | The i<br>lette<br>in or<br>hyph                       |
| hyphenation              | Boolean                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>hyph                                        |
| hyphenationZone          | Number<br>String                                                                                                                                                                                                                                                                                                  | read/write | The i<br>spac<br>of a l<br>text<br>begi<br>com<br>com |
| ignoreEdgeAlignment      | Boolean                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>edge<br>para                                |
| index                    | Number                                                                                                                                                                                                                                                                                                            | readonly   | The i<br>the c<br>obje                                |
| insertionPoints          | InsertionPoints <i>InsertionPoint</i>                                                                                                                                                                                                                                                                             | readonly   | A col<br>poin                                         |
| isValid                  | Boolean                                                                                                                                                                                                                                                                                                           | readonly   | Retu<br>spec<br>obje                                  |
| jidori                   | Number                                                                                                                                                                                                                                                                                                            | read/write | The i<br>squa<br>arrar                                |
| justification            | Justification<br>Justification.AWAY_FROM_BINDING_SIDE<br>Justification.CENTER_ALIGN<br>Justification.CENTER_JUSTIFIED<br>Justification.FULLY_JUSTIFIED<br>Justification.LEFT_ALIGN<br>Justification.LEFT_JUSTIFIED<br>Justification.RIGHT_ALIGN<br>Justification.RIGHT_JUSTIFIED<br>Justification.TO_BINDING_SIDE | read/write | The i                                                 |
| kashidas                 | KashidasOptions<br>KashidasOptions.DEFAULT_KASHIDAS<br>KashidasOptions.KASHIDAS_OFF                                                                                                                                                                                                                               | read/write | Use i<br>justil                                       |
| keepAllLinesTogether     | Boolean                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>the p<br>false<br>to br<br>colur            |
| keepFirstLines           | Number (range 1 - 50)                                                                                                                                                                                                                                                                                             | read/write | The i<br>lines<br>para<br>a pag                       |
| keepLastLines            | Number (range 1 - 50)                                                                                                                                                                                                                                                                                             | read/write | The i<br>lines<br>para<br>brea                        |
| keepLinesTogether        | Boolean                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>num                                         |

| Property              | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Access     | Desc                                                                |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------|
|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |            | when<br>break<br>text<br>If true<br>above<br>remain<br>bour<br>when |
| keepRuleAboveInFrame  | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | read/write |                                                                     |
| keepWithNext          | Number (range 0 - 5)                                                                                                                                                                                                                                                                                                                                                                                                                                                             | read/write | The i<br>lines<br>para                                              |
| keepWithPrevious      | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | read/write | If the<br>para<br>with<br>prev                                      |
| kentenAlignment       | KentenAlignment<br>KentenAlignment.ALIGN_KENTEN_CENTER<br>KentenAlignment.ALIGN_KENTEN_LEFT                                                                                                                                                                                                                                                                                                                                                                                      | read/write | The i<br>char<br>pare                                               |
| kentenCharacterSet    | KentenCharacterSet<br>KentenCharacterSet.CHARACTER_INPUT<br>KentenCharacterSet.JIS<br>KentenCharacterSet.KUTEN<br>KentenCharacterSet.SHIFT_JIS<br>KentenCharacterSet.UNICODE                                                                                                                                                                                                                                                                                                     | read/write | The i<br>the c<br>char<br>when<br>custo                             |
| kentenCustomCharacter | String                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | The i<br>kento<br>when<br>custo                                     |
| kentenFillColor       | Swatch<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | read/write | The i<br>grad<br>ink) i<br>kento<br>retur                           |
| kentenFont            | Font<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | read/write | The i<br>char<br>Font                                               |
| kentenFontSize        | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | The i<br>kento                                                      |
| kentenFontStyle       | String<br>NothingEnum.NOTHING                                                                                                                                                                                                                                                                                                                                                                                                                                                    | read/write | The i<br>char<br>Strin<br>enur                                      |
| kentenKind            | KentenCharacter<br>KentenCharacter.CUSTOM<br>KentenCharacter.KENTEN_BLACK_CIRCLE<br>KentenCharacter.KENTEN_BLACK_TRIANGLE<br>KentenCharacter.KENTEN_BULLSEYE<br>KentenCharacter.KENTEN_FISHEYE<br>KentenCharacter.KENTEN_SESAME_DOT<br>KentenCharacter.KENTEN_SMALL_BLACK_CIRCLE<br>KentenCharacter.KENTEN_SMALL_WHITE_CIRCLE<br>KentenCharacter.KENTEN_WHITE_CIRCLE<br>KentenCharacter.KENTEN_WHITE_SESAME_DOT<br>KentenCharacter.KENTEN_WHITE_TRIANGLE<br>KentenCharacter.NONE | read/write | The i<br>char                                                       |
| kentenOverprintFill   | AdornmentOverprint<br>AdornmentOverprint.AUTO<br>AdornmentOverprint.OVERPRINT_OFF<br>AdornmentOverprint.OVERPRINT_ON                                                                                                                                                                                                                                                                                                                                                             | read/write | The i<br>over<br>fill.                                              |
| kentenOverprintStroke | AdornmentOverprint<br>AdornmentOverprint.AUTO<br>AdornmentOverprint.OVERPRINT_OFF<br>AdornmentOverprint.OVERPRINT_ON                                                                                                                                                                                                                                                                                                                                                             | read/write | The i<br>over<br>stro                                               |
| kentenPlacement       | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | The i<br>kento<br>their                                             |

| Property          | Type                                                                                                                                                                                                                                                                             | Access     | Description                                                               |
|-------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------------|
| kentenPosition    | <a href="#">RubyKentenPosition</a><br>RubyKentenPosition.ABOVE_RIGHT<br>RubyKentenPosition.BELOW_LEFT                                                                                                                                                                            | read/write | The relative position of the kanten character.                            |
| kentenStrokeColor | <a href="#">Swatch</a><br><a href="#">String</a>                                                                                                                                                                                                                                 | read/write | The stroke color of the kanten character (in hexadecimal notation).       |
| kentenStrokeTint  | <a href="#">Number</a> (range 0 - 100)                                                                                                                                                                                                                                           | read/write | The stroke tint of the kanten character (percentage of the stroke color). |
| kentenTint        | <a href="#">Number</a> (range 0 - 100)                                                                                                                                                                                                                                           | read/write | The tint of the kanten character (percentage of the character color).     |
| kentenWeight      | <a href="#">Number</a>                                                                                                                                                                                                                                                           | read/write | The weight of the kanten character.                                       |
| kentenXScale      | <a href="#">Number</a>                                                                                                                                                                                                                                                           | read/write | The x-axis scale of the kanten character.                                 |
| kentenYScale      | <a href="#">Number</a>                                                                                                                                                                                                                                                           | read/write | The y-axis scale of the kanten character.                                 |
| kerningMethod     | <a href="#">String</a>                                                                                                                                                                                                                                                           | read/write | The kerning method used for the kanten character.                         |
| kerningValue      | <a href="#">Number</a>                                                                                                                                                                                                                                                           | read/write | The kerning value for the kanten character.                               |
| keyboardDirection | <a href="#">CharacterDirectionOptions</a><br>CharacterDirectionOptions.DEFAULT_DIRECTION<br>CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION<br>CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION                                                                               | read/write | The keyboard direction for the kanten character.                          |
| kinsokuHangType   | <a href="#">KinsokuHangTypes</a><br>KinsokuHangTypes.KINSOKU_HANG_FORCE<br>KinsokuHangTypes.KINSOKU_HANG_REGULAR<br>KinsokuHangTypes.NONE                                                                                                                                        | read/write | The kinsoku hang type for the kanten character.                           |
| kinsokuSet        | <a href="#">KinsokuSet</a><br>KinsokuSet.HARD_KINSOKU<br>KinsokuSet.KOREAN_KINSOKU<br>KinsokuSet.NOTHING<br>KinsokuSet.SIMPLIFIED_CHINESE_KINSOKU<br>KinsokuSet.SOFT_KINSOKU<br>KinsokuSet.TRADITIONAL_CHINESE_KINSOKU<br><a href="#">KinsokuTable</a><br><a href="#">String</a> | read/write | The kinsoku set for the kanten character.                                 |
| kinsokuType       | <a href="#">KinsokuType</a><br>KinsokuType.KINSOKU_PRIORITIZE_ADJUSTMENT_AMOUNT<br>KinsokuType.KINSOKU_PUSH_IN_FIRST<br>KinsokuType.KINSOKU_PUSH_OUT_FIRST<br>KinsokuType.KINSOKU_PUSH_OUT_ONLY                                                                                  | read/write | The kinsoku type for the kanten character.                                |
| lastLineIndent    | <a href="#">Number</a><br><a href="#">String</a>                                                                                                                                                                                                                                 | read/write | The last line indent for the kanten character.                            |
| leading           | <a href="#">Unit</a><br><a href="#">Leading</a><br>Leading.AUTO                                                                                                                                                                                                                  | read/write | The leading for the kanten character.                                     |
| leadingAki        | <a href="#">Number</a>                                                                                                                                                                                                                                                           | read/write | The leading aki for the kanten character.                                 |
| leadingModel      | <a href="#">LeadingModel</a><br>LeadingModel.LEADING_MODEL_AKI_ABOVE<br>LeadingModel.LEADING_MODEL_AKI_BELOW<br>LeadingModel.LEADING_MODEL_CENTER                                                                                                                                | read/write | The leading model for the kanten character.                               |

| Property                    | Type                                                                                                                                                                                                                                                                                                                                                                                                                                  | Access     | Desc                                                     |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------------------------------------------|
|                             | LeadingModel.LEADING_MODEL_CENTER_DOWN<br>LeadingModel.LEADING_MODEL_ROMAN                                                                                                                                                                                                                                                                                                                                                            |            |                                                          |
| leftIndent                  | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                      | read/write | The i<br>inde                                            |
| length                      | Number                                                                                                                                                                                                                                                                                                                                                                                                                                | readonly   | The i<br>the c                                           |
| ligatures                   | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | If tru<br>char:<br>(e.g.,<br>char:                       |
| lines                       | Lines <i>Line</i>                                                                                                                                                                                                                                                                                                                                                                                                                     | readonly   | A col                                                    |
| listBoxes                   | ListBoxes                                                                                                                                                                                                                                                                                                                                                                                                                             | readonly   | A col                                                    |
| maximumGlyphScaling         | Number (range 50 - 200)                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | The i<br>perc<br>char:<br>200)                           |
| maximumLetterSpacing        | Number                                                                                                                                                                                                                                                                                                                                                                                                                                | read/write | The i<br>spac<br>perc<br>spac<br>the f<br>500)<br>whei   |
| maximumWordSpacing          | Number (range 0 - 1000)                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | The i<br>spac<br>perc<br>worc<br>Valid<br>justif<br>100C |
| mergeConsecutiveParaBorders | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | If tru<br>bord<br>simil<br>merg                          |
| minimumGlyphScaling         | Number (range 50 - 200)                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | The i<br>perc<br>char:<br>200)                           |
| minimumLetterSpacing        | Number                                                                                                                                                                                                                                                                                                                                                                                                                                | read/write | The i<br>spac<br>perc<br>spac<br>the f<br>500)<br>whei   |
| minimumWordSpacing          | Number (range 0 - 1000)                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | The i<br>spac<br>perc<br>worc<br>Valid<br>justif<br>100C |
| miterLimit                  | Number (range 0 - 1000)                                                                                                                                                                                                                                                                                                                                                                                                               | read/write | The l<br>strok<br>lengt<br>(poir<br>beve                 |
| mojikumi                    | MojikumiTable<br>String<br>MojikumiTableDefaults<br>MojikumiTableDefaults.LINE_END_ALL_ONE_EM_ENUM<br>MojikumiTableDefaults.LINE_END_ALL_ONE_HALF_EM_ENUM<br>MojikumiTableDefaults.LINE_END_PERIOD_ONE_EM_ENUM<br>MojikumiTableDefaults.LINE_END_UKE_NO_FLOAT_ENUM<br>MojikumiTableDefaults.NOTHING<br>MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_NO_FLOAT_ENUM<br>MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM | read/write | The i<br>infor<br>table<br>Moji<br>Moji<br>enur          |

| Property                    | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Access     | Desc                           |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------------------|
|                             | MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_HALF_EM_ENUM<br>MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM<br>MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM<br>MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM<br>MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM<br>MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM<br>MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM<br>MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM<br>MojikumiTableDefaults.SIMP_CHINESE_DEFAULT<br>MojikumiTableDefaults.TRAD_CHINESE_DEFAULT |            |                                |
| multiStateObjects           | MultiStateObjects <i>MultiStateObject</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | readonly   | A col<br>obje                  |
| nestedGrepStyles            | NestedGrepStyles <i>NestedGrepStyle</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | readonly   | A col<br>GREP                  |
| nestedLineStyles            | NestedLineStyles <i>NestedLineStyle</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | readonly   | A col<br>style                 |
| nestedStyles                | NestedStyles <i>NestedStyle</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | readonly   | A col<br>style                 |
| noBreak                     | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>the s                |
| notes                       | Notes <i>Note</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | readonly   | A col                          |
| numberingAlignment          | ListAlignment<br>ListAlignment.CENTER_ALIGN<br>ListAlignment.LEFT_ALIGN<br>ListAlignment.RIGHT_ALIGN                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | read/write | The i<br>num                   |
| numberingApplyRestartPolicy | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>num                  |
| numberingCharacterStyle     | CharacterStyle<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | read/write | The i<br>used<br>strin<br>Char |
| numberingContinue           | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | Cont<br>at th                  |
| numberingExpression         | String                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | read/write | The i<br>expr                  |
| numberingFormat             | NumberingStyle<br>NumberingStyle.ARABIC<br>NumberingStyle.ARABIC_ABJAD<br>NumberingStyle.ARABIC_ALIF_BA_TAH<br>NumberingStyle.DOUBLE_LEADING_ZEROS<br>NumberingStyle.FORMAT_NONE<br>NumberingStyle.HEBREW_BIBLICAL<br>NumberingStyle.HEBREW_NON_STANDARD<br>NumberingStyle.KANJI<br>NumberingStyle.KATAKANA_MODERN<br>NumberingStyle.KATAKANA_TRADITIONAL<br>NumberingStyle.LOWER_LETTERS<br>NumberingStyle.LOWER_ROMAN<br>NumberingStyle.SINGLE_LEADING_ZEROS<br>NumberingStyle.TRIPLE_LEADING_ZEROS<br>NumberingStyle.UPPER_LETTERS<br>NumberingStyle.UPPER_ROMAN<br>String                                                                                                                     | read/write | Num<br>optic<br>Num<br>enur    |
| numberingLevel              | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | read/write | The l<br>para                  |
| numberingRestartPolicies    | NumberingRestartPolicy                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | readonly   | Num<br>polic                   |
| numberingStartAt            | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | read/write | Dete<br>num<br>list.           |
| opentypeFeatures            | Array of 2 Strings<br>Array of LongIntegers                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | Open<br>retur<br>Strin         |
| otfContextualAlternate      | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | read/write | If tru<br>alter<br>Open        |

| Property                              | Type                                                                                                                                                                                             | Access     | Desc                                                               |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------------------------------------------------------|
| otfDiscretionaryLigature              | Boolean                                                                                                                                                                                          | read/write | If true, ligatures are used in fonts.                              |
| otfFigureStyle                        | OTFFigureStyle<br>OTFFigureStyle.DEFAULT_VALUE<br>OTFFigureStyle.PROPORTIONAL_LINING<br>OTFFigureStyle.PROPORTIONAL_OLDSTYLE<br>OTFFigureStyle.TABULAR_LINING<br>OTFFigureStyle.TABULAR_OLDSTYLE | read/write | The figure style used in OpenType fonts.                           |
| otfFraction                           | Boolean                                                                                                                                                                                          | read/write | If true, fractions are used in OpenType fonts.                     |
| otfHVKana                             | Boolean                                                                                                                                                                                          | read/write | If true, horizontal kana are used in fonts.                        |
| otfHistorical                         | Boolean                                                                                                                                                                                          | read/write | If true, historical forms are used in fonts.                       |
| otfJustificationAlternate             | Boolean                                                                                                                                                                                          | read/write | If true, justification alternate forms are used in OpenType fonts. |
| otfLocale                             | Boolean                                                                                                                                                                                          | read/write | If true, locale forms are used in fonts.                           |
| otfMark                               | Boolean                                                                                                                                                                                          | read/write | If true, marks are used in fonts.                                  |
| otfOrdinal                            | Boolean                                                                                                                                                                                          | read/write | If true, ordinal forms are used in OpenType fonts.                 |
| otfOverlapSwash                       | Boolean                                                                                                                                                                                          | read/write | If true, overlapping swashes are used in fonts.                    |
| otfProportionalMetrics                | Boolean                                                                                                                                                                                          | read/write | If true, proportional metrics are used in OpenType fonts.          |
| otfRomanItalics                       | Boolean                                                                                                                                                                                          | read/write | If true, Roman italics are used in half-width fonts.               |
| otfSlashedZero                        | Boolean                                                                                                                                                                                          | read/write | If true, slashed zero is used in fonts.                            |
| otfStretchedAlternate                 | Boolean                                                                                                                                                                                          | read/write | If true, stretched alternate forms are used in OpenType fonts.     |
| otfStylisticAlternate                 | Boolean                                                                                                                                                                                          | read/write | If true, stylistic alternate forms are used in OpenType fonts.     |
| otfStylisticSets                      | Number                                                                                                                                                                                           | read/write | The stylistic set used in OpenType fonts.                          |
| otfSwash                              | Boolean                                                                                                                                                                                          | read/write | If true, swashes are used in OpenType fonts.                       |
| otfTitling                            | Boolean                                                                                                                                                                                          | read/write | If true, titling forms are used in OpenType fonts.                 |
| ovals                                 | Ovals <i>Oval</i>                                                                                                                                                                                | readonly   | A collection of ovals.                                             |
| overprintFill                         | Boolean                                                                                                                                                                                          | read/write | If true, overprint fill is used in characters.                     |
| overprintStroke                       | Boolean                                                                                                                                                                                          | read/write | If true, overprint stroke is used in characters.                   |
| pageItems                             | PageItems <i>PageItem</i>                                                                                                                                                                        | readonly   | The page items, which are processed in the document group.         |
| paragraphBorderBottomLeftCornerOption | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER                                                                                                                        | read/write | The bottom-left corner option for paragraphs.                      |

| Property                               | Type                                                                                                                                                                                                  | Access     | Desc                                                                                                                            |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------------------------------------------------------------------------------------------------------------|
|                                        | CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER                                                                              |            |                                                                                                                                 |
| paragraphBorderBottomLeftCornerRadius  | Number<br>String                                                                                                                                                                                      | read/write | The measurement of the bottom-left corner of the rectangle.                                                                     |
| paragraphBorderBottomLineWeight        | Number<br>String                                                                                                                                                                                      | read/write | The line weight of the bottom border.                                                                                           |
| paragraphBorderBottomOffset            | Number<br>String                                                                                                                                                                                      | read/write | The offset of the bottom border from the paragraph.                                                                             |
| paragraphBorderBottomOrigin            | ParagraphBorderBottomOriginEnum<br>ParagraphBorderBottomOriginEnum.BASELINE_BOTTOM_ORIGIN<br>ParagraphBorderBottomOriginEnum.DESCENT_BOTTOM_ORIGIN                                                    | read/write | The baseline of the bottom border of the paragraph.                                                                             |
| paragraphBorderBottomRightCornerOption | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER | read/write | The corner option of the bottom-right corner of the rectangle.                                                                  |
| paragraphBorderBottomRightCornerRadius | Number<br>String                                                                                                                                                                                      | read/write | The measurement of the bottom-right corner of the rectangle.                                                                    |
| paragraphBorderColor                   | Swatch<br>String                                                                                                                                                                                      | read/write | The color of the paragraph border (gradient or solid color).                                                                    |
| paragraphBorderDisplayIfSplits         | Boolean                                                                                                                                                                                               | read/write | If true, the paragraph border is displayed when the paragraph is split.                                                         |
| paragraphBorderGapColor                | Swatch<br>String                                                                                                                                                                                      | read/write | The color of the paragraph border gap (gradient or solid color). Note: The border gap is only visible when the border is split. |
| paragraphBorderGapOverprint            | Boolean                                                                                                                                                                                               | read/write | If true, the paragraph border gap is overprinted on the border.                                                                 |
| paragraphBorderGapTint                 | Number (range 0 - 100)                                                                                                                                                                                | read/write | The tint of the paragraph border gap. When the border is split, the gap is not visible if the tint is 0.                        |
| paragraphBorderLeftLineWeight          | Number<br>String                                                                                                                                                                                      | read/write | The line weight of the left border.                                                                                             |
| paragraphBorderLeftOffset              | Number<br>String                                                                                                                                                                                      | read/write | The offset of the left border from the paragraph.                                                                               |
| paragraphBorderOn                      | Boolean                                                                                                                                                                                               | read/write | If true, the paragraph border is displayed.                                                                                     |
| paragraphBorderOverprint               | Boolean                                                                                                                                                                                               | read/write | If true, the paragraph border is overprinted on the text.                                                                       |

| Property                            | Type                                                                                                                                                                                                  | Access     | Desc                                                                                                  |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------------------------------------------------------------|
| paragraphBorderRightLineWeight      | Number<br>String                                                                                                                                                                                      | read/write | The l<br>the b                                                                                        |
| paragraphBorderRightOffset          | Number<br>String                                                                                                                                                                                      | read/write | The o<br>right<br>para                                                                                |
| paragraphBorderStrokeEndCap         | EndCap<br>EndCap.BUTT_END_CAP<br>EndCap.PROJECTING_END_CAP<br>EndCap.ROUND_END_CAP                                                                                                                    | read/write | The o<br>path                                                                                         |
| paragraphBorderStrokeEndJoin        | EndJoin<br>EndJoin.BEVEL_END_JOIN<br>EndJoin.MITER_END_JOIN<br>EndJoin.ROUND_END_JOIN                                                                                                                 | read/write | The o<br>the C                                                                                        |
| paragraphBorderTint                 | Number (range 0 - 100)                                                                                                                                                                                | read/write | The t<br>of th<br>(Ran                                                                                |
| paragraphBorderTopLeftCornerOption  | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER | read/write | The s<br>to th<br>recta<br>corn<br>recta<br>corn<br>end j<br>set a<br>optic<br>roun<br>of ar<br>the s |
| paragraphBorderTopLeftCornerRadius  | Number<br>String                                                                                                                                                                                      | read/write | The i<br>mea:<br>corn<br>the t<br>recta<br>corn<br>recta                                              |
| paragraphBorderTopLineWeight        | Number<br>String                                                                                                                                                                                      | read/write | The t<br>bord                                                                                         |
| paragraphBorderTopOffset            | Number<br>String                                                                                                                                                                                      | read/write | The o<br>top e<br>bord                                                                                |
| paragraphBorderTopOrigin            | ParagraphBorderTopOriginEnum<br>ParagraphBorderTopOriginEnum.ASCENT_TOP_ORIGIN<br>ParagraphBorderTopOriginEnum.BASELINE_TOP_ORIGIN<br>ParagraphBorderTopOriginEnum.LEADING_TOP_ORIGIN                 | read/write | The l<br>asce<br>to ca<br>of th                                                                       |
| paragraphBorderTopRightCornerOption | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER | read/write | The s<br>top r<br>recta                                                                               |
| paragraphBorderTopRightCornerRadius | Number<br>String                                                                                                                                                                                      | read/write | The i<br>mea:<br>corn<br>the t<br>recta                                                               |
| paragraphBorderType                 | StrokeStyle<br>String                                                                                                                                                                                 | read/write | The t<br>the p<br>retur<br>Strin                                                                      |
| paragraphBorderWidth                | ParagraphBorderEnum<br>ParagraphBorderEnum.COLUMN_WIDTH<br>ParagraphBorderEnum.TEXT_WIDTH                                                                                                             | read/write | The l<br>colu<br>calcu<br>para                                                                        |

| Property                                | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Access     | Description                                                   |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|---------------------------------------------------------------|
| paragraphDirection                      | ParagraphDirectionOptions<br>ParagraphDirectionOptions.LEFT_TO_RIGHT_DIRECTION<br>ParagraphDirectionOptions.RIGHT_TO_LEFT_DIRECTION                                                                                                                                                                                                                                                                                                                           | read/write | Paragraph direction                                           |
| paragraphGyoudori                       | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | If true, applies gyoudori to each paragraph                   |
| paragraphJustification                  | ParagraphJustificationOptions<br>ParagraphJustificationOptions.ARABIC_JUSTIFICATION<br>ParagraphJustificationOptions.DEFAULT_JUSTIFICATION<br>ParagraphJustificationOptions.NASKH_JUSTIFICATION<br>ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION<br>ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION_FRAC<br>ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION<br>ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION_FRAC | read/write | Paragraph justification                                       |
| paragraphKashidaWidth                   | Number                                                                                                                                                                                                                                                                                                                                                                                                                                                        | read/write | Paragraph kashida width. 0 is recommended                     |
| paragraphShadingBottomLeftCornerOption  | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER                                                                                                                                                                                                                                                         | read/write | The shading bottom-left corner option                         |
| paragraphShadingBottomLeftCornerRadius  | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                              | read/write | The shading bottom-left corner radius. The kashida rectangle  |
| paragraphShadingBottomOffset            | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                              | read/write | The shading bottom offset. Paragraph                          |
| paragraphShadingBottomOrigin            | ParagraphShadingBottomOriginEnum<br>ParagraphShadingBottomOriginEnum.BASELINE_BOTTOM_ORIGIN<br>ParagraphShadingBottomOriginEnum.DESCENT_BOTTOM_ORIGIN                                                                                                                                                                                                                                                                                                         | read/write | The shading bottom origin. Paragraph                          |
| paragraphShadingBottomRightCornerOption | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER                                                                                                                                                                                                                                                         | read/write | The shading bottom-right corner option                        |
| paragraphShadingBottomRightCornerRadius | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                              | read/write | The shading bottom-right corner radius. The kashida rectangle |
| paragraphShadingClipToFrame             | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | If true, the shading is clipped to the frame                  |
| paragraphShadingColor                   | Swatch<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                              | read/write | The shading color (gradient or ink). Paragraph                |
| paragraphShadingLeftOffset              | Number<br>String                                                                                                                                                                                                                                                                                                                                                                                                                                              | read/write | The shading left offset. Paragraph                            |
| paragraphShadingOn                      | Boolean                                                                                                                                                                                                                                                                                                                                                                                                                                                       | read/write | If true, shading is on                                        |

| Property                             | Type                                                                                                                                                                                                  | Access     | Desc                                                                                |
|--------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------------------------------------------------------------------------------|
| paragraphShadingOverprint            | Boolean                                                                                                                                                                                               | read/write | If true, the shading is printed.                                                    |
| paragraphShadingRightOffset          | Number<br>String                                                                                                                                                                                      | read/write | The distance from the right edge of the paragraph to the right edge of the shading. |
| paragraphShadingSuppressPrinting     | Boolean                                                                                                                                                                                               | read/write | If true, the shading is not printed.                                                |
| paragraphShadingTint                 | Number (range 0 - 100)                                                                                                                                                                                | read/write | The tint of the shading (0 = black, 100 = white).                                   |
| paragraphShadingTopLeftCornerOption  | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER | read/write | The corner option for the top-left corner of the shading.                           |
| paragraphShadingTopLeftCornerRadius  | Number<br>String                                                                                                                                                                                      | read/write | The radius of the top-left corner of the shading.                                   |
| paragraphShadingTopOffset            | Number<br>String                                                                                                                                                                                      | read/write | The distance from the top edge of the paragraph to the top edge of the shading.     |
| paragraphShadingTopOrigin            | ParagraphShadingTopOriginEnum<br>ParagraphShadingTopOriginEnum.ASCENT_TOP_ORIGIN<br>ParagraphShadingTopOriginEnum.BASELINE_TOP_ORIGIN<br>ParagraphShadingTopOriginEnum.LEADING_TOP_ORIGIN             | read/write | The origin of the top edge of the shading.                                          |
| paragraphShadingTopRightCornerOption | CornerOptions<br>CornerOptions.BEVEL_CORNER<br>CornerOptions.FANCY_CORNER<br>CornerOptions.INSET_CORNER<br>CornerOptions.INVERSE_ROUNDED_CORNER<br>CornerOptions.NONE<br>CornerOptions.ROUNDED_CORNER | read/write | The corner option for the top-right corner of the shading.                          |
| paragraphShadingTopRightCornerRadius | Number<br>String                                                                                                                                                                                      | read/write | The radius of the top-right corner of the shading.                                  |
| paragraphShadingWidth                | ParagraphShadingWidthEnum<br>ParagraphShadingWidthEnum.COLUMN_WIDTH<br>ParagraphShadingWidthEnum.TEXT_WIDTH                                                                                           | read/write | The width of the shading.                                                           |
| paragraphs                           | Paragraphs <i>Paragraph</i>                                                                                                                                                                           | readonly   | A collection of paragraphs.                                                         |
| parent                               | Cell<br>Change<br>Character<br>Endnote<br>EndnoteTextFrame<br>Footnote<br>InsertionPoint<br>Line<br>Note<br>Paragraph<br>Story<br>Text<br>TextColumn                                                  | readonly   | The parent object of the paragraph.                                                 |

| Property                   | Type                                                                                                                                                                                                                               | Access     | Desc                                                                                                     |
|----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------------------------------------------------------------------------------------------|
|                            | TextFrame<br>TextPath<br>TextStyleRange<br>Word<br>XMLElement<br>HiddenText<br>XmlStory                                                                                                                                            |            |                                                                                                          |
| parentStory                | Story                                                                                                                                                                                                                              | readonly   | The story that contains the text frame.                                                                  |
| parentTextFrames           | Array of TextFrames<br>Array of TextPaths <i>TextPath</i>                                                                                                                                                                          | readonly   | An array of text frames that are part of the text frame's parent text frame.                             |
| pointSize                  | Number<br>String                                                                                                                                                                                                                   | read/write | The point size of the text.                                                                              |
| polygons                   | Polygons <i>Polygon</i>                                                                                                                                                                                                            | readonly   | A collection of polygons that define the shape of the text frame.                                        |
| position                   | Position<br>Position.NORMAL<br>Position.OT_DENOMINATOR<br>Position.OT_NUMERATOR<br>Position.OT_SUBSCRIPT<br>Position.OT_SUPERSCRIPT<br>Position.SUBSCRIPT<br>Position.SUPERSCRIPT                                                  | read/write | The position of the text frame relative to the text frame's parent text frame.                           |
| positionalForm             | PositionalForms<br>PositionalForms.CALCULATE<br>PositionalForms.FINAL<br>PositionalForms.INITIAL<br>PositionalForms.ISOLATED<br>PositionalForms.MEDIAL<br>PositionalForms.NONE                                                     | read/write | The positional form of the text frame.                                                                   |
| preferences                | Preferences <i>Preference</i>                                                                                                                                                                                                      | readonly   | A collection of preferences for the text frame.                                                          |
| properties                 | Object                                                                                                                                                                                                                             | read/write | A collection of properties for the text frame.                                                           |
| providerHyphenationStyle   | HyphenationStyleEnum<br>HyphenationStyleEnum.HYPH_AESTHETIC<br>HyphenationStyleEnum.HYPH_ALL<br>HyphenationStyleEnum.HYPH_ALL_BUT_UNAESTHETIC<br>HyphenationStyleEnum.HYPH_PREFERRED_AESTHETIC                                     | read/write | The hyphenation style of the text frame.                                                                 |
| radioButtons               | RadioButtons <i>RadioButton</i>                                                                                                                                                                                                    | readonly   | A collection of radio buttons that are part of the text frame.                                           |
| rectangles                 | Rectangles <i>Rectangle</i>                                                                                                                                                                                                        | readonly   | A collection of rectangles that define the shape of the text frame.                                      |
| rensuuji                   | Boolean                                                                                                                                                                                                                            | read/write | If true, the text frame is broken into two lines. If false, the text frame is not broken into two lines. |
| rightIndent                | Number<br>String                                                                                                                                                                                                                   | read/write | The right indent of the text frame.                                                                      |
| rotateSingleByteCharacters | Boolean                                                                                                                                                                                                                            | read/write | If true, the text frame rotates single byte characters.                                                  |
| rubyAlignment              | RubyAlignments<br>RubyAlignments.RUBY_1_AKI<br>RubyAlignments.RUBY_CENTER<br>RubyAlignments.RUBY_EQUAL_AKI<br>RubyAlignments.RUBY_FULL_JUSTIFY<br>RubyAlignments.RUBY_JIS<br>RubyAlignments.RUBY_LEFT<br>RubyAlignments.RUBY_RIGHT | read/write | The ruby alignment of the text frame.                                                                    |
| rubyAutoAlign              | Boolean                                                                                                                                                                                                                            | read/write | If true, the text frame automatically aligns the ruby text.                                              |
| rubyAutoScaling            | Boolean                                                                                                                                                                                                                            | read/write | If true, the text frame automatically scales the ruby text.                                              |

| Property                 | Type                                                                                                                                                                                                                                           | Access     | Desc                                           |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|------------------------------------------------|
|                          |                                                                                                                                                                                                                                                |            | pare<br>infor<br>a pei<br>scali                |
| rubyAutoTcyAutoScale     | Boolean                                                                                                                                                                                                                                        | read/write | If tru<br>scale<br>(tate<br>to fit             |
| rubyAutoTcyDigits        | Number                                                                                                                                                                                                                                         | read/write | The i<br>inclu<br>chuu                         |
| rubyAutoTcyIncludeRoman  | Boolean                                                                                                                                                                                                                                        | read/write | If tru<br>char:<br>(tate                       |
| rubyFill                 | Swatch<br>String                                                                                                                                                                                                                               | read/write | The :<br>grad<br>ink) ;<br>ruby<br>retur       |
| rubyFlag                 | Boolean                                                                                                                                                                                                                                        | read/write | If tru                                         |
| rubyFont                 | Font<br>String                                                                                                                                                                                                                                 | read/write | The f<br>char:<br>Font                         |
| rubyFontSize             | Number                                                                                                                                                                                                                                         | read/write | The :<br>char:                                 |
| rubyFontStyle            | String<br>NothingEnum.NOTHING                                                                                                                                                                                                                  | read/write | The f<br>char:<br>Strin<br>enur                |
| rubyOpenTypePro          | Boolean                                                                                                                                                                                                                                        | read/write | If tru<br>font:                                |
| rubyOverhang             | Boolean                                                                                                                                                                                                                                        | read/write | If tru<br>over<br>amo<br>on sp<br>see r<br>amo |
| rubyOverprintFill        | AdornmentOverprint<br>AdornmentOverprint.AUTO<br>AdornmentOverprint.OVERPRINT_OFF<br>AdornmentOverprint.OVERPRINT_ON                                                                                                                           | read/write | The i<br>over                                  |
| rubyOverprintStroke      | AdornmentOverprint<br>AdornmentOverprint.AUTO<br>AdornmentOverprint.OVERPRINT_OFF<br>AdornmentOverprint.OVERPRINT_ON                                                                                                                           | read/write | The i<br>over<br>stro                          |
| rubyParentOverhangAmount | RubyOverhang<br>RubyOverhang.NONE<br>RubyOverhang.RUBY_OVERHANG_HALF_CHAR<br>RubyOverhang.RUBY_OVERHANG_HALF_RUBY<br>RubyOverhang.RUBY_OVERHANG_NO_LIMIT<br>RubyOverhang.RUBY_OVERHANG_ONE_CHAR<br>RubyOverhang.RUBY_OVERHANG_ONE_RUBY         | read/write | The i<br>ruby<br>over                          |
| rubyParentScalingPercent | Number                                                                                                                                                                                                                                         | read/write | The i<br>perc<br>pare<br>dete<br>size.         |
| rubyParentSpacing        | RubyParentSpacing<br>RubyParentSpacing.RUBY_PARENT_121_AKI<br>RubyParentSpacing.RUBY_PARENT_BOTH_SIDES<br>RubyParentSpacing.RUBY_PARENT_EQUAL_AKI<br>RubyParentSpacing.RUBY_PARENT_FULL_JUSTIFY<br>RubyParentSpacing.RUBY_PARENT_NO_ADJUSTMENT | read/write | The i<br>to th                                 |
| rubyPosition             | RubyKentenPosition<br>RubyKentenPosition.ABOVE_RIGHT<br>RubyKentenPosition.BELOW_LEFT                                                                                                                                                          | read/write | The i<br>char:<br>pare                         |

| Property              | Type                                                              | Access     | Description                                                                                   |
|-----------------------|-------------------------------------------------------------------|------------|-----------------------------------------------------------------------------------------------|
| rubyString            | String                                                            | read/write | The ruby string.                                                                              |
| rubyStroke            | Swatch<br>String                                                  | read/write | The stroke color (as a gradient ink) ; if not set, the default color of the rule is returned. |
| rubyStrokeTint        | Number                                                            | read/write | The stroke tint (percentage) ; if not set, the default tint is 100.                           |
| rubyTint              | Number (range 0 - 100)                                            | read/write | The tint (percentage) of the color (Range 0 - 100). (Range 0 - 100)                           |
| rubyType              | RubyTypes<br>RubyTypes.GROUP_RUBY<br>RubyTypes.PER_CHARACTER_RUBY | read/write | The type of the ruby (Range 0 - 100).                                                         |
| rubyWeight            | Number                                                            | read/write | The weight of the rule (point size).                                                          |
| rubyXOffset           | Number                                                            | read/write | The x offset (space) of the rule (space).                                                     |
| rubyXScale            | Number                                                            | read/write | The x scale (character size) of the rule (percentage size).                                   |
| rubyYOffset           | Number                                                            | read/write | The y offset (space) of the rule (space).                                                     |
| rubyYScale            | Number                                                            | read/write | The y scale (character size) of the rule (percentage size).                                   |
| ruleAbove             | Boolean                                                           | read/write | If true, the rule is above the text.                                                          |
| ruleAboveColor        | Swatch<br>String                                                  | read/write | The color of the rule (as a gradient ink) ; if not set, the default color is returned.        |
| ruleAboveGapColor     | Swatch<br>String                                                  | read/write | The color of the gap (as a gradient ink) ; if not set, the default color is returned.         |
| ruleAboveGapOverprint | Boolean                                                           | read/write | If true, the gap will be overprinted (only if the rule is not set).                           |
| ruleAboveGapTint      | Number (range 0 - 100)                                            | read/write | The tint (percentage) of the gap (Range 0 - 100). (Valid range 0 - 100)                       |
| ruleAboveLeftIndent   | Number<br>String                                                  | read/write | The left indent (point size) of the rule (either the first or the last).                      |
| ruleAboveLineWeight   | Number<br>String                                                  | read/write | The line weight (point size) of the rule (above the text).                                    |

| Property              | Type                                                        | Access     | Desc                                                                         |
|-----------------------|-------------------------------------------------------------|------------|------------------------------------------------------------------------------|
| ruleAboveOffset       | Number<br>String                                            | read/write | The i<br>para<br>from<br>first                                               |
| ruleAboveOverprint    | Boolean                                                     | read/write | If tru<br>abov                                                               |
| ruleAboveRightIndent  | Number<br>String                                            | read/write | The i<br>right<br>para<br>(base<br>width<br>width<br>the p                   |
| ruleAboveTint         | Number (range 0 - 100)                                      | read/write | The t<br>of th<br>abov                                                       |
| ruleAboveType         | StrokeStyle<br>String                                       | read/write | The :<br>abov<br>retur<br>Strin                                              |
| ruleAboveWidth        | RuleWidth<br>RuleWidth.COLUMN_WIDTH<br>RuleWidth.TEXT_WIDTH | read/write | The l<br>colu<br>calcu<br>para                                               |
| ruleBelow             | Boolean                                                     | read/write | If tru<br>para                                                               |
| ruleBelowColor        | Swatch<br>String                                            | read/write | The :<br>grad<br>ink) ;<br>para<br>retur                                     |
| ruleBelowGapColor     | Swatch<br>String                                            | read/write | The :<br>grad<br>ink) ;<br>gap c<br>below<br>when<br>below<br>Can i<br>Strin |
| ruleBelowGapOverprint | Boolean                                                     | read/write | If tru<br>the r<br>over                                                      |
| ruleBelowGapTint      | Number (range 0 - 100)                                      | read/write | The t<br>of th<br>the p<br>(Ran<br>Valid<br>para<br>is no                    |
| ruleBelowLeftIndent   | Number<br>String                                            | read/write | The i<br>left e<br>rule<br>eithe<br>the c<br>last l                          |
| ruleBelowLineWeight   | Number<br>String                                            | read/write | The l<br>below                                                               |
| ruleBelowOffset       | Number<br>String                                            | read/write | The i<br>the p<br>from<br>last l                                             |
| ruleBelowOverprint    | Boolean                                                     | read/write | If tru<br>over                                                               |
| ruleBelowRightIndent  | Number<br>String                                            | read/write | The i<br>right                                                               |

| Property                 | Type                                                                                                                                                                                    | Access     | Desc                                   |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------------------------|
|                          |                                                                                                                                                                                         |            | para: (base width, width, the p        |
| ruleBelowTint            | Number (range 0 - 100)                                                                                                                                                                  | read/write | The i of th belo                       |
| ruleBelowType            | StrokeStyle<br>String                                                                                                                                                                   | read/write | The : belo retur Strin                 |
| ruleBelowWidth           | RuleWidth<br>RuleWidth.COLUMN_WIDTH<br>RuleWidth.TEXT_WIDTH                                                                                                                             | read/write | The l colu calcu para                  |
| sameParaStyleSpacing     | Unit<br>Spacing<br>Spacing.SETIGNORE                                                                                                                                                    | read/write | The : para style Spac                  |
| scaleAffectsLineHeight   | Boolean                                                                                                                                                                                 | read/write | If tru size \ scale                    |
| shataiAdjustRotation     | Boolean                                                                                                                                                                                 | read/write | If tru rotat                           |
| shataiAdjustTsume        | Boolean                                                                                                                                                                                 | read/write | If tru tsum                            |
| shataiDegreeAngle        | Number                                                                                                                                                                                  | read/write | The : degr                             |
| shataiMagnification      | Number                                                                                                                                                                                  | read/write | The : perc oblic                       |
| signatureFields          | SignatureFields <i>SignatureField</i>                                                                                                                                                   | readonly   | A col field:                           |
| singleWordJustification  | SingleWordJustification<br>SingleWordJustification.CENTER_ALIGN<br>SingleWordJustification.FULLY_JUSTIFIED<br>SingleWordJustification.LEFT_ALIGN<br>SingleWordJustification.RIGHT_ALIGN | read/write | The : lines worc                       |
| skew                     | Number                                                                                                                                                                                  | read/write | The : Char                             |
| spaceAfter               | Number<br>String                                                                                                                                                                        | read/write | The l para                             |
| spaceBefore              | Number<br>String                                                                                                                                                                        | read/write | The l para                             |
| spanColumnMinSpaceAfter  | Number<br>String                                                                                                                                                                        | read/write | The i a spa                            |
| spanColumnMinSpaceBefore | Number<br>String                                                                                                                                                                        | read/write | The i befo colu                        |
| spanColumnType           | SpanColumnTypeOptions<br>SpanColumnTypeOptions.SINGLE_COLUMN<br>SpanColumnTypeOptions.SPAN_COLUMNS<br>SpanColumnTypeOptions.SPLIT_COLUMNS                                               | read/write | Whe shou span colu                     |
| spanSplitColumnCount     | ShortInteger(1-40)<br>SpanColumnCountOptions<br>SpanColumnCountOptions.ALL                                                                                                              | read/write | The i para, num Can i (1 - 4 Span enur |
| splineItems              | SplineItems <i>SplineItem</i>                                                                                                                                                           | readonly   | The : colle                            |
| splitColumnInsideGutter  | Number<br>String                                                                                                                                                                        | read/write | The i para                             |

| Property                  | Type                                                                                                                                                                                              | Access     | Description                                                        |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------------------------------------------------------------------|
| splitColumnOutsideGutter  | Number<br>String                                                                                                                                                                                  | read/write | The column outside gutter                                          |
| startParagraph            | StartParagraph<br>StartParagraph.ANYWHERE<br>StartParagraph.NEXT_COLUMN<br>StartParagraph.NEXT_EVEN_PAGE<br>StartParagraph.NEXT_FRAME<br>StartParagraph.NEXT_ODD_PAGE<br>StartParagraph.NEXT_PAGE | read/write | The paragraph start                                                |
| strikeThroughColor        | Swatch<br>String                                                                                                                                                                                  | read/write | The color of the stroke (if the stroke is not solid)               |
| strikeThroughGapColor     | Swatch<br>String                                                                                                                                                                                  | read/write | The color of the gap (if the stroke is not solid)                  |
| strikeThroughGapOverprint | Boolean                                                                                                                                                                                           | read/write | If true, the gap will be overprinted when the stroke is not solid  |
| strikeThroughGapTint      | Number (range 0 - 100)                                                                                                                                                                            | read/write | The tint of the gap (if the stroke is not solid)                   |
| strikeThroughOffset       | Number<br>String                                                                                                                                                                                  | read/write | The offset of the stroke from the baseline                         |
| strikeThroughOverprint    | Boolean                                                                                                                                                                                           | read/write | If true, the stroke will be overprinted when the text is not solid |
| strikeThroughTint         | Number (range 0 - 100)                                                                                                                                                                            | read/write | The tint of the stroke (if the stroke is not solid)                |
| strikeThroughType         | StrokeStyle<br>String                                                                                                                                                                             | read/write | The stroke style (if the stroke is not solid)                      |
| strikeThroughWeight       | Number<br>String                                                                                                                                                                                  | read/write | The weight of the stroke (if the stroke is not solid)              |
| strikeThru                | Boolean                                                                                                                                                                                           | read/write | If true, the stroke will be overprinted when the text is not solid |
| strokeAlignment           | TextStrokeAlign<br>TextStrokeAlign.CENTER_ALIGNMENT<br>TextStrokeAlign.OUTSIDE_ALIGNMENT                                                                                                          | read/write | The alignment of the stroke                                        |
| strokeColor               | Swatch<br>String                                                                                                                                                                                  | read/write | The color of the stroke (if the stroke is not solid)               |
| strokeTint                | Number (range 0 - 100)                                                                                                                                                                            | read/write | The tint of the stroke (if the stroke is not solid)                |

| Property                     | Type                                              | Access     | Desc                                                               |
|------------------------------|---------------------------------------------------|------------|--------------------------------------------------------------------|
| strokeWeight                 | Number<br>String                                  | read/write | The :<br>to th<br>text.                                            |
| styleOverridden              | Boolean                                           | readonly   | If tru<br>has b<br>addi                                            |
| tabList                      | Array of Arrays of Property Name/Value Pairs.     | read/write | A list<br>the p<br>retur<br>Prop<br>Pairs                          |
| tabStops                     | TabStops <i>TabStop</i>                           | readonly   | A col                                                              |
| tables                       | Tables <i>Table</i>                               | readonly   | A col                                                              |
| tatechuyoko                  | Boolean                                           | read/write | If tru<br>char;<br>verti                                           |
| tatechuyokoXOffset           | Number                                            | read/write | The l<br>horiz<br>verti                                            |
| tatechuyokoYOffset           | Number                                            | read/write | The v<br>horiz<br>verti                                            |
| textBoxes                    | TextBoxes                                         | readonly   | A col                                                              |
| textColumns                  | TextColumns <i>TextColumn</i>                     | readonly   | A col<br>colur                                                     |
| textFrames                   | TextFrames <i>TextFrame</i>                       | readonly   | A col<br>fram                                                      |
| textStyleRanges              | TextStyleRanges <i>TextStyleRange</i>             | readonly   | A col<br>rang                                                      |
| textVariableInstances        | TextVariableInstances <i>TextVariableInstance</i> | readonly   | A col<br>varia                                                     |
| texts                        | Texts <i>Text</i>                                 | readonly   | A col<br>obje                                                      |
| tracking                     | Number                                            | read/write | The i<br>loose<br>of te<br>thou                                    |
| trailingAki                  | Number                                            | read/write | The i<br>each                                                      |
| treatIdeographicSpaceAsSpace | Boolean                                           | read/write | If tru<br>will r<br>line l                                         |
| tsume                        | Number                                            | read/write | The i<br>char;                                                     |
| underline                    | Boolean                                           | read/write | If tru<br>text.                                                    |
| underlineColor               | Swatch<br>String                                  | read/write | The :<br>grad<br>ink) ;<br>unde<br>retur                           |
| underlineGapColor            | Swatch<br>String                                  | read/write | The :<br>grad<br>ink) ;<br>the u<br>Note<br>unde<br>solid<br>or St |
| underlineGapOverprint        | Boolean                                           | read/write | If tru<br>the u<br>over                                            |

| Property                | Type                                                                                                                                                                                                                                                                                      | Access     | Desc                             |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|----------------------------------|
| underlineGapTint        | Number (range 0 - 100)                                                                                                                                                                                                                                                                    | read/write | The i of th unde 0 to whei not s |
| underlineOffset         | Number<br>String                                                                                                                                                                                                                                                                          | read/write | The i offse the t                |
| underlineOverprint      | Boolean                                                                                                                                                                                                                                                                                   | read/write | If tru strok                     |
| underlineTint           | Number (range 0 - 100)                                                                                                                                                                                                                                                                    | read/write | The i (as a 0 to                 |
| underlineType           | StrokeStyle<br>String                                                                                                                                                                                                                                                                     | read/write | The i unde retur Strin           |
| underlineWeight         | Number<br>String                                                                                                                                                                                                                                                                          | read/write | The i unde                       |
| verticalScale           | Number                                                                                                                                                                                                                                                                                    | read/write | The i appli                      |
| warichu                 | Boolean                                                                                                                                                                                                                                                                                   | read/write | If tru                           |
| warichuAlignment        | WarichuAlignment<br>WarichuAlignment.AUTO<br>WarichuAlignment.CENTER_ALIGN<br>WarichuAlignment.CENTER_JUSTIFIED<br>WarichuAlignment.FULLY_JUSTIFIED<br>WarichuAlignment.LEFT_ALIGN<br>WarichuAlignment.LEFT_JUSTIFIED<br>WarichuAlignment.RIGHT_ALIGN<br>WarichuAlignment.RIGHT_JUSTIFIED | read/write | The i                            |
| warichuCharsAfterBreak  | Number                                                                                                                                                                                                                                                                                    | read/write | The i char: line l               |
| warichuCharsBeforeBreak | Number                                                                                                                                                                                                                                                                                    | read/write | The i char: a line               |
| warichuLineSpacing      | Number                                                                                                                                                                                                                                                                                    | read/write | The i wari                       |
| warichuLines            | Number                                                                                                                                                                                                                                                                                    | read/write | The i wari norm                  |
| warichuSize             | Number                                                                                                                                                                                                                                                                                    | read/write | The i perc pare dete             |
| words                   | Words <i>Word</i>                                                                                                                                                                                                                                                                         | readonly   | A col                            |
| xOffsetDiacritic        | Number                                                                                                                                                                                                                                                                                    | read/write | The i for d                      |
| yOffsetDiacritic        | Number                                                                                                                                                                                                                                                                                    | read/write | The i diacr                      |

## Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

| Parameter | Type                       | Description                                                 |
|-----------|----------------------------|-------------------------------------------------------------|
| eventType | String                     | The event type.                                             |
| handler   | File<br>JavaScriptFunction | The event handler. Can accept: File or JavaScript Function. |
| captures  | Boolean                    | This parameter is obsolete. (Optional)                      |

| Parameter | Type | Description      |
|-----------|------|------------------|
|           |      | (default: false) |

undefined **applyCharacterStyle** (using:*CharacterStyle*)

Apply a character style.

| Parameter | Type                  | Description                   |
|-----------|-----------------------|-------------------------------|
| using     | <i>CharacterStyle</i> | The character style to apply. |

undefined **applyConditions** (using:*Array of Condition*, [removeExisting:*Boolean*=Boolean])

Apply one or more conditions.

| Parameter      | Type                      | Description                                                         |
|----------------|---------------------------|---------------------------------------------------------------------|
| using          | <i>Array of Condition</i> | The condition(s) to apply                                           |
| removeExisting | <i>Boolean</i>            | If true, remove existing conditions. (Optional)<br>(default: false) |

undefined **applyParagraphStyle** (using:*ParagraphStyle*, [clearingOverrides:*Boolean*=Boolean])

Apply a paragraph style.

| Parameter         | Type                  | Description                                                                                 |
|-------------------|-----------------------|---------------------------------------------------------------------------------------------|
| using             | <i>ParagraphStyle</i> | The paragraph style to apply.                                                               |
| clearingOverrides | <i>Boolean</i>        | If true, clear any text attributes before applying the style. (Optional)<br>(default: true) |

BackgroundTask **asynchronousExportFile** (format:*Varies ExportFormat String*, to:*File*, [showingOptions:*Boolean*=Boolean], using:*PDFExportPreset*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

asynchronously exports the object(s) to a file.

| Parameter       | Type                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Description                                                                                                                                                                                  |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| format          | <i>ExportFormat</i><br>ExportFormat.EPS_TYPE<br>ExportFormat.EPUB<br>ExportFormat.FIXED_LAYOUT_EPUB<br>ExportFormat.HTML<br>ExportFormat.HTMLFXL<br>ExportFormat.INCOPY_MARKUP<br>ExportFormat.INDESIGN_MARKUP<br>ExportFormat.INDESIGN_SNIPPET<br>ExportFormat.INTERACTIVE_PDF<br>ExportFormat.JPG<br>ExportFormat.PDF_TYPE<br>ExportFormat.PNG_FORMAT<br>ExportFormat.RTF<br>ExportFormat.TAGGED_TEXT<br>ExportFormat.TEXT_TYPE<br>ExportFormat.XML<br><i>String</i> | The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String. |
| to              | <i>File</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                            | The path to the export file.                                                                                                                                                                 |
| showingOptions  | <i>Boolean</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                         | If true, displays the export options dialog. (Optional)<br>(default: false)                                                                                                                  |
| using           | <i>PDFExportPreset</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                 | The export style. (Optional)                                                                                                                                                                 |
| versionComments | <i>String</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                          | The comment for this version. (Optional)                                                                                                                                                     |
| forceSave       | <i>Boolean</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                         | If true, forcibly saves a version. (Optional)<br>(default: false)                                                                                                                            |

undefined **autoTag** ()

Tag the object or the parent story using default tags defined in XML preference.

Text **changeGlyph** (reverseOrder:*Boolean*)

Finds glyphs that match the find what value and replaces the glyphs with the change to value.

| Parameter    | Type           | Description                                               |
|--------------|----------------|-----------------------------------------------------------|
| reverseOrder | <i>Boolean</i> | If true, returns the results in reverse order. (Optional) |

Text **changeGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

Text **changeText** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

Text **changeTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value and replaces the text with the change character type value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

undefined **changeCase** (using:*ChangeCaseMode*)

Sets the case of the text.

| Parameter | Type                                                                                                                                     | Description           |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| using     | <i>ChangeCaseMode</i><br>ChangeCaseMode.LOWERCASE<br>ChangeCaseMode.SENTENCECASE<br>ChangeCaseMode.TITLECASE<br>ChangeCaseMode.UPPERCASE | The text case option. |

undefined **clearOverrides** ([overridesToClear:*OverrideType*=OverrideType])

Clears the specified types of override.

| Parameter        | Type                                                                                                  | Description                                                               |
|------------------|-------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
| overridesToClear | <i>OverrideType</i><br>OverrideType.ALL<br>OverrideType.CHARACTER_ONLY<br>OverrideType.PARAGRAPH_ONLY | The types of override to clear. (Optional)<br>(default: OverrideType.ALL) |

undefined **convertBulletsAndNumberingToText** ()

Convert bullets and numbering to text.

Note **convertToNote** ()

Converts the text to a note.

Table **convertToTable** (columnSeparator:*String*, rowSeparator:*String*, [numberOfColumns:*Number*=Number])

Converts the text to a table.

| Parameter       | Type   | Description                                                                                                                                |
|-----------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------|
| columnSeparator | String | The character that starts a new column in the new table. (Optional)                                                                        |
| rowSeparator    | String | The character starts a new row in the new table. (Optional)                                                                                |
| numberOfColumns | Number | The number of columns in the table. Note: Valid only when the column and row separator characters are the same. (Optional)<br>(default: 1) |

undefined **createEmailQRCode** (emailAddress:*String*, subject:*String*, body:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Email QR Code on the page item or document

| Parameter      | Type             | Description                                                                                                      |
|----------------|------------------|------------------------------------------------------------------------------------------------------------------|
| emailAddress   | String           | QR code Email Address (Optional)                                                                                 |
| subject        | String           | QR code Email Subject (Optional)                                                                                 |
| body           | String           | QR code Email Body Message (Optional)                                                                            |
| qrCodeSwatch   | Swatch<br>String | Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)                     |
| withProperties | Array of String  | Initial values for properties of the new Character. Above parameters can also be passed as properties (Optional) |

undefined **createHyperlinkQRCode** (urlLink:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Hyperlink QR Code on the page item or document

| Parameter      | Type            | Description                                                                                                      |
|----------------|-----------------|------------------------------------------------------------------------------------------------------------------|
| urlLink        | String          | QR code Hyperlink URL (Optional)                                                                                 |
| qrCodeSwatch   | Swatch String   | Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)                     |
| withProperties | Array of String | Initial values for properties of the new Character. Above parameters can also be passed as properties (Optional) |

PageItem **createOutlines** ([deleteOriginal:Boolean=Boolean])

Converts text to outlines. Each line of text becomes a polygon object. When the converted text is a single letter that has no internal spaces or detached parts, the polygon contains only a single path. Note: To determine whether a font allows the creation of outlines, see allow outlines.

| Parameter      | Type    | Description                                                                                                                             |
|----------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------|
| deleteOriginal | Boolean | If true, deletes the original text. If false, creates the outlines as separate object(s) on top of the text. (Optional) (default: true) |

undefined **createPlainTextQRCode** (plainText:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Plain Text QR Code on the page item

| Parameter      | Type            | Description                                                                                                      |
|----------------|-----------------|------------------------------------------------------------------------------------------------------------------|
| plainText      | String          | QR code Plain Text (Optional)                                                                                    |
| qrCodeSwatch   | Swatch String   | Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)                     |
| withProperties | Array of String | Initial values for properties of the new Character. Above parameters can also be passed as properties (Optional) |

Boolean **createStyleThumbnailWithProperties** (previewText:String, pointSize:Number, space:ColorSpace, colorValue:Array of Number, to:File, charOrParaStyle:StyleType)

Create thumbnail for selected text using the applied style and overrides with the given properties.

| Parameter       | Type                                                                                                       | Description                    |
|-----------------|------------------------------------------------------------------------------------------------------------|--------------------------------|
| previewText     | String                                                                                                     | Text to use as sample          |
| pointSize       | Number                                                                                                     | Text font size (in points)     |
| space           | ColorSpace<br>ColorSpace.CMYK<br>ColorSpace.HSB<br>ColorSpace.LAB<br>ColorSpace.MIXEDINK<br>ColorSpace.RGB | Color space RGB, CMYK or LAB   |
| colorValue      | Array of Number                                                                                            | Color values                   |
| to              | File                                                                                                       | The path to the export file.   |
| charOrParaStyle | StyleType<br>StyleType.CHARACTER_STYLE_TYPE<br>StyleType.PARAGRAPH_STYLE_TYPE                              | The applied style type to use. |

undefined **createTextMsgQRCode** (cellNumber:String, textMessage:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Text Msg QR Code on the page item or document

| Parameter      | Type            | Description                                                                                                      |
|----------------|-----------------|------------------------------------------------------------------------------------------------------------------|
| cellNumber     | String          | QR code Text Phone Number (Optional)                                                                             |
| textMessage    | String          | QR code Text Message (Optional)                                                                                  |
| qrCodeSwatch   | Swatch String   | Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)                     |
| withProperties | Array of String | Initial values for properties of the new Character. Above parameters can also be passed as properties (Optional) |

Boolean **createThumbnailWithProperties** (previewText:String, pointSize:Number, space:ColorSpace, colorValue:Array of Number, to:File)

Create thumbnail for selected text with the given properties.

| Parameter   | Type   | Description           |
|-------------|--------|-----------------------|
| previewText | String | Text to use as sample |

| Parameter  | Type                                                                                                       | Description                  |
|------------|------------------------------------------------------------------------------------------------------------|------------------------------|
| pointSize  | Number                                                                                                     | Text font size (in points)   |
| space      | ColorSpace<br>ColorSpace.CMYK<br>ColorSpace.HSB<br>ColorSpace.LAB<br>ColorSpace.MIXEDINK<br>ColorSpace.RGB | Color space RGB, CMYK or LAB |
| colorValue | Array of Number                                                                                            | Color values                 |
| to         | File                                                                                                       | The path to the export file. |

undefined **createVCardQRCode** (firstName:*String*, lastName:*String*, jobTitle:*String*, cellPhone:*String*, phone:*String*, email:*String*, organisation:*String*, streetAddress:*String*, city:*String*, adrState:*String*, country:*String*, postalCode:*String*, website:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Business Card QR Code on the page item or load on document's placegun

| Parameter      | Type             | Description                                                                                                      |
|----------------|------------------|------------------------------------------------------------------------------------------------------------------|
| firstName      | String           | QR code Business Card First Name (Optional)                                                                      |
| lastName       | String           | QR code Business Card Last Name (Optional)                                                                       |
| jobTitle       | String           | QR code Business Card Title (Optional)                                                                           |
| cellPhone      | String           | QR code Business Card Cell Phone Number (Optional)                                                               |
| phone          | String           | QR code Business Card Phone Number (Optional)                                                                    |
| email          | String           | QR code Business Card Email Address (Optional)                                                                   |
| organisation   | String           | QR code Business Card Organisation (Optional)                                                                    |
| streetAddress  | String           | QR code Business Card Street Address (Optional)                                                                  |
| city           | String           | QR code Business Card City (Optional)                                                                            |
| adrState       | String           | QR code Business Card State (Optional)                                                                           |
| country        | String           | QR code Business Card Country (Optional)                                                                         |
| postalCode     | String           | QR code Business Card Postal Code (Optional)                                                                     |
| website        | String           | QR code Business Card URL (Optional)                                                                             |
| qrCodeSwatch   | Swatch<br>String | Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)                     |
| withProperties | Array of String  | Initial values for properties of the new Character. Above parameters can also be passed as properties (Optional) |

Text **duplicate** (to:*LocationOptions*, reference:*Varies Cell Column Row Story Table Text PageItem*)

Duplicates the text in the specified location.

| Parameter | Type                                                                                                                                                    | Description                                                                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| to        | LocationOptions<br>LocationOptions.AFTER<br>LocationOptions.AT_BEGINNING<br>LocationOptions.AT_END<br>LocationOptions.BEFORE<br>LocationOptions.UNKNOWN | The location relative to the reference object or within the containing object.                                                                                  |
| reference | Cell<br>Column<br>Row<br>Story<br>Table<br>Text<br>PageItem                                                                                             | The reference object. Note: Required when the to parameter specifies before or after. Can accept: Text, Story, Cell, Row, Column, Table or PageItem. (Optional) |

undefined **exportFile** (format:*Varies ExportFormat String*, to:*File*, [showingOptions:*Boolean*=Boolean], using:*PDFExportPreset*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

Exports the object(s) to a file.

| Parameter | Type                                                                                                              | Description                                                                                                                                                                                  |
|-----------|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| format    | ExportFormat<br>ExportFormat.EPS_TYPE<br>ExportFormat.EPUB<br>ExportFormat.FIXED_LAYOUT_EPUB<br>ExportFormat.HTML | The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String. |

| Parameter       | Type                                                                                                                                                                                                                                                                                                                      | Description                                                                 |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|
|                 | ExportFormat.HTMLFXL<br>ExportFormat.INCOPY_MARKUP<br>ExportFormat.INDESIGN_MARKUP<br>ExportFormat.INDESIGN_SNIPPET<br>ExportFormat.INTERACTIVE_PDF<br>ExportFormat.JPG<br>ExportFormat.PDF_TYPE<br>ExportFormat.PNG_FORMAT<br>ExportFormat.RTF<br>ExportFormat.TAGGED_TEXT<br>ExportFormat.TEXT_TYPE<br>ExportFormat.XML |                                                                             |
| to              | String<br>File                                                                                                                                                                                                                                                                                                            | The path to the export file.                                                |
| showingOptions  | Boolean                                                                                                                                                                                                                                                                                                                   | If true, displays the export options dialog. (Optional)<br>(default: false) |
| using           | PDFExportPreset                                                                                                                                                                                                                                                                                                           | The export style. (Optional)                                                |
| versionComments | String                                                                                                                                                                                                                                                                                                                    | The comment for this version. (Optional)                                    |
| forceSave       | Boolean                                                                                                                                                                                                                                                                                                                   | If true, forcibly saves a version. (Optional)<br>(default: false)           |

Text **findGlyph** (reverseOrder:*Boolean*)

Finds glyphs that match the find what value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

Text **findGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

HyperlinkTextSource **findHyperlinks** (sortOrder:*RangeSortOrder*)

Finds hyperlink sources that intersecting with specified text range.

| Parameter | Type                                                                                                       | Description                                |
|-----------|------------------------------------------------------------------------------------------------------------|--------------------------------------------|
| sortOrder | RangeSortOrder<br>RangeSortOrder.ASCENDING_SORT<br>RangeSortOrder.DECENDING_SORT<br>RangeSortOrder.NO_SORT | The sort order of found ranges. (Optional) |

Text **findText** (reverseOrder:*Boolean*)

Finds text that matches the find what value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

Text **findTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value.

| Parameter    | Type    | Description                                               |
|--------------|---------|-----------------------------------------------------------|
| reverseOrder | Boolean | If true, returns the results in reverse order. (Optional) |

Character **getElements** ()

Resolves the object specifier, creating an array of object references.

Boolean **isNthDesignAxisHidden** (nthAxisIndex:*Number*)

If true, Nth design axis of variable font is hidden.

| Parameter    | Type   | Description           |
|--------------|--------|-----------------------|
| nthAxisIndex | Number | Index of design axis. |

undefined **markup** (using:*XMLElement*)

Associates the page item with the specified XML element while preserving existing content.

| Parameter | Type       | Description      |
|-----------|------------|------------------|
| using     | XMLElement | The XML element. |

Text **move** (to:*LocationOptions*, reference:*Varies Cell Column Row Story Table Text PageItem*)

Moves the text to the specified location.

| Parameter | Type                                                                                                                                                    | Description                                                                                                                                                     |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| to        | LocationOptions<br>LocationOptions.AFTER<br>LocationOptions.AT_BEGINNING<br>LocationOptions.AT_END<br>LocationOptions.BEFORE<br>LocationOptions.UNKNOWN | The location relative to the reference object or within the containing object.                                                                                  |
| reference | Cell<br>Column<br>Row<br>Story<br>Table<br>Text<br>PageItem                                                                                             | The reference object. Note: Required when the to parameter specifies before or after. Can accept: Text, Story, Cell, Row, Column, Table or PageItem. (Optional) |

Varies **place** (fileName:*File*, [showingOptions:*Boolean*=Boolean], withProperties:*Object*)

Places the file.

| Parameter      | Type    | Description                                                              |
|----------------|---------|--------------------------------------------------------------------------|
| fileName       | File    | The file to place                                                        |
| showingOptions | Boolean | Whether to display the import options dialog (Optional) (default: false) |
| withProperties | Object  | Initial values for properties of the placed object(s) (Optional)         |

undefined **recompose** ()

Recomposes the text in the Character.

undefined **remove** ()

Deletes the Character.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

| Parameter | Type                       | Description                                                            |
|-----------|----------------------------|------------------------------------------------------------------------|
| eventType | String                     | The registered event type.                                             |
| handler   | File<br>JavaScriptFunction | The registered event handler. Can accept: File or JavaScript Function. |
| captures  | Boolean                    | This parameter is obsolete. (Optional) (default: false)                |

undefined **select** ([existingSelection:*SelectionOptions*=SelectionOptions])

Selects the object.

| Parameter         | Type                                                                                                                                     | Description                                                                                                                           |
|-------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| existingSelection | SelectionOptions<br>SelectionOptions.ADD_TO<br>SelectionOptions.REMOVE_FROM<br>SelectionOptions.REPLACE_WITH<br>SelectionOptions.SET_KEY | The selection status of the Character in relation to previously selected objects. (Optional) (default: SelectionOptions.REPLACE_WITH) |

undefined **setNthDesignAxis** (nthAxisIndex:*Number*, nthAxisValue:*Number*)

Set Nth design axis of a variable font.

| Parameter    | Type   | Description               |
|--------------|--------|---------------------------|
| nthAxisIndex | Number | Index of design axis.     |
| nthAxisValue | Number | Value of nth design axis. |

undefined **showText** ()

Jump to the text range.

Boolean **textHasOverrides** (charOrParaStyle: *StyleType*, [charStyleAsOverride: *Boolean*=Boolean])

If true, text has local overrides

| Parameter           | Type                                                                                 | Description                                                                            |
|---------------------|--------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| charOrParaStyle     | <i>StyleType</i><br>StyleType.CHARACTER_STYLE_TYPE<br>StyleType.PARAGRAPH_STYLE_TYPE | Style type to look at.                                                                 |
| charStyleAsOverride | <i>Boolean</i>                                                                       | Whether to consider character styles as overrides or not (Optional)<br>(default: true) |

String **toSource** ()

Generates a string which, if executed, will return the Character.

String **toSpecifier** ()

Retrieves the object specifier.

---

## Object of

- Bullet.parent
- Button.parent
- Character.parent
- CheckBox.parent
- ComboBox.parent
- EPSText.parent
- EndnoteRange.parent
- Event.parent
- EventListener.parent
- FormField.parent
- GraphicLine.parent
- Group.parent
- InsertionPoint.parent
- Line.parent
- ListBox.parent
- MultiStateObject.parent
- MutationEvent.parent
- NestedGrepStyle.parent
- NestedLineStyle.parent
- NestedStyle.parent
- NumberingRestartPolicy.parent
- Oval.parent
- PageItem.parent
- Paragraph.parent
- Polygon.parent
- Preference.parent
- RadioButton.parent
- Rectangle.parent
- SignatureField.parent
- SplineItem.parent
- TabStop.parent
- Table.parent
- Text.parent
- TextBox.parent
- TextColumn.parent
- TextFrame.parent
- TextStyleRange.parent
- Word.parent

---

## Return

- Character.getElements()
  - Characters.anyItem()
  - Characters.everyItem()
  - Characters.nextItem()
  - Characters.previousItem()
  - Characters.item()
  - Characters.[]()
  - Characters.itemByRange()
  - Characters.firstItem()
  - Characters.lastItem()
  - Characters.middleItem()
-