

Document

A document.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [adjustLayout](#), [align](#), [asynchronousExportFile](#), [changeColor](#), [changeComposer](#), [changeGlyph](#), [changeGrep](#), [changeObject](#), [changeText](#), [changeTransliterate](#), [checkIn](#), [clearFrameFittingOptions](#), [close](#), [colorTransform](#), [createAlternateLayout](#), [createEmailQRCode](#), [createFromMathML](#), [createHyperlinkQRCode](#), [createMissingFontObject](#), [createPlainTextQRCode](#), [createTOC](#), [createTextMsgQRCode](#), [createVCardQRCode](#), [deleteAlternateLayout](#), [deleteUnusedTags](#), [distribute](#), [embed](#), [exportFile](#), [exportForCloudLibrary](#), [exportPageItemsSelectionToSnippet](#), [exportPageItemsToSnippet](#), [exportStrokeStyles](#), [extractLabel](#), [findColor](#), [findGlyph](#), [findGrep](#), [findObject](#), [findText](#), [findTransliterate](#), [getAlternateLayoutsForFolio](#), [getElements](#), [getSelectedTextDirection](#), [getStyleConflictResolutionStrategy](#), [handleMathMLMessage](#), [importAdobeSwatchbookProcessColor](#), [importAdobeSwatchbookSpotColor](#), [importDtd](#), [importFormats](#), [importPdfComments](#), [importStyles](#), [importXML](#), [insertLabel](#), [internalMethod](#), [loadConditions](#), [loadMasters](#), [loadSwatches](#), [loadXMLTags](#), [mapStylesToXMLTags](#), [mapXMLTagsToStyles](#), [packageForPrint](#), [place](#), [placeAndLink](#), [placeCloudAsset](#), [print](#), [printBooklet](#), [recompose](#), [redo](#), [removeEventListener](#), [resetAllButtons](#), [resetAllMultiStateObjects](#), [revert](#), [revertToProject](#), [save](#), [saveACopy](#), [saveACopyCloud](#), [saveAsCloud](#), [saveSwatches](#), [saveXMLTags](#), [select](#), [synchronizeWithVersionCue](#), [toSource](#), [toSpecifier](#), [undo](#), [updateCrossReferences](#)

Objects:

[AdjustLayoutPreference](#), [AnchoredObjectDefault](#), [AnchoredObjectSetting](#), [Articles](#), [Assignments](#), [BaselineFrameGridOption](#), [Bookmarks](#), [Boolean](#), [ButtonPreference](#), [Buttons](#), [CellStyle](#), [CellStyleGroups](#), [CellStyleMappings](#), [CellStyles](#), [ChapterNumberPreference](#), [CharStyleMappings](#), [CharacterStyle](#), [CharacterStyleGroups](#), [CharacterStyles](#), [CheckBoxes](#), [CjkGridPreference](#), [ColorGroups](#), [ColorSettingsPolicy](#), [Colors](#), [ComboBoxes](#), [CompositeFonts](#), [ConditionSets](#), [ConditionalTextPreference](#), [Conditions](#), [CrossReferenceFormats](#), [CrossReferenceSources](#), [DTDs](#), [DashedStrokeStyles](#), [DataMerge](#), [DataMergeImagePlaceholders](#), [DataMergeOption](#), [DataMergeQrcodePlaceholders](#), [DataMergeTextPlaceholders](#), [DictionaryPreference](#), [DocumentPreference](#), [DottedStrokeStyles](#), [EPSTexts](#), [EPubExportPreference](#), [EPubFixedLayoutExportPreference](#), [EditingState](#), [EndnoteOption](#), [EndnoteTextFrames](#), [EventListeners](#), [Events](#), [ExportForWebPreference](#), [File](#), [FlexObjects](#), [Fonts](#), [FootnoteOption](#), [FormFields](#), [FrameFittingOption](#), [GalleyPreference](#), [Gradients](#), [Graphic](#), [GraphicLines](#), [GridPreference](#), [Groups](#), [GuidePreference](#), [Guides](#), [HTMLExportPreference](#), [HTMLFXLExportPreference](#), [HyperlinkExternalPageDestinations](#), [HyperlinkPageDestinations](#), [HyperlinkPageItemSources](#), [HyperlinkTextDestinations](#), [HyperlinkTextSources](#), [HyperlinkURLDestinations](#), [Hyperlinks](#), [HyphenationExceptions](#), [IndexOptions](#), [Indexes](#), [IndexingSortOptions](#), [Inks](#), [KinsokuTables](#), [Languages](#), [Layer](#), [Layers](#), [LayoutGridDataInformation](#), [LayoutWindows](#), [LinkedPageItemOption](#), [LinkedStoryOption](#), [Links](#), [ListBoxes](#), [MarginPreference](#), [MasterSpreads](#), [MathObjects](#), [MetadataPreference](#), [MixedInkGroups](#), [MixedInks](#), [MojikumiTables](#), [MojikumiUiPreference](#), [MotionPresets](#), [MultiStateObjects](#), [NamedGrids](#), [NothingEnum](#), [Number](#), [NumberingLists](#), [Object](#), [ObjectStyle](#), [ObjectStyleGroups](#), [ObjectStyles](#), [Ovals](#), [PDFComments](#), [PageItem](#), [PageItemDefault](#), [PageItems](#), [Pages](#), [ParaStyleMappings](#), [ParagraphDestinations](#), [ParagraphStyle](#), [ParagraphStyleGroups](#), [ParagraphStyles](#), [PasteboardPreference](#), [PlaceGun](#), [Polygons](#), [Preferences](#), [PreflightOption](#), [PreflightProcess](#), [PreflightProfiles](#), [PrintBookletOption](#), [PrintBookletPrintPreference](#), [PrintPreference](#), [PublishExportPreference](#), [RadioButtons](#), [Rectangles](#), [RenderingIntent](#), [Sections](#), [SignatureFields](#), [SplineItems](#), [Spreads](#), [Stories](#), [StoryGridDataInformation](#), [StoryPreference](#), [StoryWindows](#), [String](#), [StripedStrokeStyles](#), [StrokeStyles](#), [Swatch](#), [Swatches](#), [TOCStyles](#), [TableStyle](#), [TableStyleGroups](#), [TableStyleMappings](#), [TableStyles](#), [TaggedPDFPreference](#), [TextBoxes](#), [TextDefault](#), [TextFramePreference](#), [TextFrames](#), [TextPreference](#), [TextVariables](#), [TextWrapPreference](#), [Tints](#), [TransparencyPreference](#), [TrapPresets](#), [ValidationErrors](#), [VersionState](#), [ViewPreference](#), [WatermarkPreference](#), [Windows](#), [XMLComments](#), [XMLElements](#), [XMLExportMaps](#), [XMLExportPreference](#), [XMLImportMaps](#), [XMLImportPreference](#), [XMLInstructions](#), [XMLItem](#), [XMLItems](#), [XMLPreference](#), [XMLTags](#), [XMLViewPreference](#), [XmlStories](#)

Preferences:

[AdjustLayoutPreference](#), [BaselineFrameGridOption](#), [ButtonPreference](#), [ChapterNumberPreference](#), [CjkGridPreference](#), [ConditionalTextPreference](#), [DataMergeOption](#), [DictionaryPreference](#), [DocumentPreference](#), [EPubExportPreference](#), [EPubFixedLayoutExportPreference](#), [EndnoteOption](#), [ExportForWebPreference](#), [FootnoteOption](#), [FrameFittingOption](#), [GalleyPreference](#), [GridPreference](#), [GuidePreference](#), [HTMLExportPreference](#), [HTMLFXLExportPreference](#), [HyphenationExceptions](#), [IndexOptions](#), [IndexingSortOptions](#), [LinkedPageItemOption](#), [LinkedStoryOption](#), [MarginPreference](#), [MetadataPreference](#), [MojikumiUiPreference](#), [PasteboardPreference](#), [Preferences](#), [PreflightOption](#), [PrintBookletOption](#), [PrintBookletPrintPreference](#), [PrintPreference](#), [PublishExportPreference](#), [StoryPreference](#), [TaggedPDFPreference](#), [TextFramePreference](#), [TextPreference](#), [TextWrapPreference](#), [TransparencyPreference](#), [ViewPreference](#), [WatermarkPreference](#), [XMLExportPreference](#), [XMLImportPreference](#), [XMLPreference](#), [XMLViewPreference](#)

Property Listing

Property	Type	Access	Description
accurateLABSpots	Boolean	read/write	If true, uses LAB alternates for spot colors when available.
activeLayer	Layer String	read/write	The active layer. Can also accept: String .
activeProcess	PreflightProcess	readonly	The active preflight process for this document.
adjustLayoutPreferences	AdjustLayoutPreference	readonly	Adjust layout preference settings.
afterBlendingIntent	RenderingIntent RenderingIntent.ABSOLUTE_COLORIMETRIC RenderingIntent.PERCEPTUAL RenderingIntent.RELATIVE_COLORIMETRIC RenderingIntent.SATURATION RenderingIntent.USE_COLOR_SETTINGS	read/write	The rendering intent for colors that result from transparency interactions on the page after blending.
allCellStyles	Array of CellStyle	readonly	All Cell styles

Property	Type	Access	Description
allCharacterStyles	Array of CharacterStyle	readonly	Lists all character styles (regardless of their group).
allGraphics	Array of Graphic	readonly	Lists all graphics contained by the Document.
allObjectStyles	Array of ObjectStyle	readonly	All object styles contained by the Document.
allPageItems	Array of PageItem	readonly	Lists all page items contained by the Document.
allParagraphStyles	Array of ParagraphStyle	readonly	Lists all paragraph styles (regardless of their group).
allTableStyles	Array of TableStyle	readonly	All Table styles
anchoredObjectDefaults	AnchoredObjectDefault	readonly	Anchored object default settings.
anchoredObjectSettings	AnchoredObjectSetting	readonly	Anchored object settings.
appliedMathMLFontSize	Number	read/write	The font size (in points) for Math objects
appliedMathMLRGBColor	Array of Number	read/write	RGB Color applied on the math object specified in 0-255 range.
appliedMathMLSwatch	Swatch NothingEnumCanalsoaccept:String	read/write	The swatch used for math object color. Also accepts swatch name.(RGB, CMYK, LAB and HSB swatches supported.). Can return: Swatch or NothingEnum enumerator. Can also accept: String.
articles	Articles Article	readonly	A collection of articles.
assignments	Assignments Assignment	readonly	A collection of assignments.
associatedXMLElement	XMLItem	readonly	The XML element associated with the Document.
baselineFrameGridOptions	BaselineFrameGridOption	readonly	Baseline frame grid option settings.
bookmarks	Bookmarks Bookmark	readonly	A collection of bookmarks.
buttonPreferences	ButtonPreference	readonly	Button preference settings.
buttons	Buttons Button	readonly	A collection of buttons.
cellStyleGroups	CellStyleGroups CellStyleGroup	readonly	A collection of cell style groups.
cellStyleMappings	CellStyleMappings CellStyleMapping	readonly	A collection of cell style mappings.
cellStyles	CellStyles CellStyle	readonly	A collection of cell styles.
chapterNumberPreferences	ChapterNumberPreference	readonly	Chapter numbering preferences.
charStyleMappings	CharStyleMappings CharStyleMapping	readonly	A collection of char style mappings.
characterStyleGroups	CharacterStyleGroups CharacterStyleGroup	readonly	A collection of character style groups.
characterStyles	CharacterStyles CharacterStyle	readonly	A collection of character styles.
checkboxes	CheckBoxes	readonly	A collection of checkboxes.
cjkGridPreferences	CjkGridPreference	readonly	CJK grid preference settings.
cloudPath	String	readonly	The cloud path in case of a cloud document. Otherwise it throws error.
cmykPolicy	ColorSettingsPolicy ColorSettingsPolicy.COLOR_POLICY_OFF ColorSettingsPolicy.COMBINATION_OF_PRESERVE_AND_SAFE_CMYK ColorSettingsPolicy.CONVERT_TO_WORKING_SPACE ColorSettingsPolicy.PRESERVE_EMBEDDED_PROFILES	read/write	The policy for handling colors in a CMYK color model, including reading and embedding color profiles, mismatches between embedded color profiles and the working space, and moving colors from one document to another.
cmykProfile	String	read/write	The current CMYK profile.
cmykProfileList	Array of String	readonly	A list of valid CMYK profiles.
colorGroups	ColorGroups ColorGroup	readonly	A collection of color groups.
colors	Colors Color	readonly	A collection of colors.
comboBoxes	ComboBoxes	readonly	A collection of comboboxes.
compositeFonts	CompositeFonts CompositeFont	readonly	A collection of composite fonts.
conditionSets	ConditionSets ConditionSet	readonly	A collection of condition sets for conditional text.
conditionalTextPreferences	ConditionalTextPreference	readonly	Conditional text preferences.

Property	Type	Access	Description
conditions	Conditions <i>Condition</i>	readonly	A collection of conditions for conditional text.
converted	Boolean	readonly	If true, the Document was converted.
crossReferenceFormats	CrossReferenceFormats <i>CrossReferenceFormat</i>	readonly	A collection of cross reference formats.
crossReferenceSources	CrossReferenceSources <i>CrossReferenceSource</i>	readonly	A collection of cross reference text sources.
dashedStrokeStyles	DashedStrokeStyles <i>DashedStrokeStyle</i>	readonly	A collection of dashed stroke styles.
dataMergeImagePlaceholders	DataMergeImagePlaceholders <i>DataMergeImagePlaceholder</i>	readonly	A collection of data merge image placeholders.
dataMergeOptions	DataMergeOption	readonly	The data merge option properties that define the data merge.
dataMergeProperties	DataMerge	readonly	Data merge properties that define data merge fields and preferences.
dataMergeQrcodePlaceholders	DataMergeQrcodePlaceholders <i>DataMergeQrcodePlaceholder</i>	readonly	A collection of data merge QR code placeholders.
dataMergeTextPlaceholders	DataMergeTextPlaceholders <i>DataMergeTextPlaceholder</i>	readonly	A collection of data merge text placeholders.
defaultImageIntent	RenderingIntent RenderingIntent.ABSOLUTE_COLORIMETRIC RenderingIntent.PERCEPTUAL RenderingIntent.RELATIVE_COLORIMETRIC RenderingIntent.SATURATION RenderingIntent.USE_COLOR_SETTINGS	read/write	The rendering intent for bitmap images.
dictionaryPreferences	DictionaryPreference	readonly	User dictionary preference settings.
documentPreferences	DocumentPreference	readonly	Document preference settings.
dottedStrokeStyles	DottedStrokeStyles <i>DottedStrokeStyle</i>	readonly	A collection of dotted stroke styles.
dtDs	DTDs <i>DTD</i>	readonly	A collection of DTDs.
editingState	EditingState EditingState.EDITING_CONFLICT EditingState.EDITING_LOCALLY EditingState.EDITING_LOCALLY_LOCKED EditingState.EDITING_NOWHERE EditingState.EDITING_REMOTELY EditingState.EDITING_UNKNOWN	readonly	The Version Cue editing state of the file.
endnoteOptions	EndnoteOption	readonly	Endnote option settings.
endnoteTextFrames	EndnoteTextFrames <i>EndnoteTextFrame</i>	readonly	A collection of endnote text frames.
epstexts	EPSTexts <i>EPSText</i>	readonly	EPSTexts
epubExportPreferences	EPubExportPreference	readonly	EPub export preference settings.
epubFixedLayoutExportPreferences	EPubFixedLayoutExportPreference	readonly	EPub fixed layout export preference settings.
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
exportForWebPreferences	ExportForWebPreference	readonly	The default export for web preferences.
filePath	File	readonly	The full path to the file.
flexObjects	FlexObjects <i>FlexObject</i>	readonly	A collection of flex objects.
fonts	Fonts <i>Font</i>	readonly	A collection of fonts.
footnoteOptions	FootnoteOption	readonly	Footnote option settings.
formFields	FormFields <i>FormField</i>	readonly	A collection of form fields.
frameFittingOptions	FrameFittingOption	readonly	The frame fitting option to apply to placed or pasted content. Can be applied to a frame, object style, or document or to the application.
fullName	File	readonly	The full path to the Document, including the name of the Document.
galleyPreferences	GalleyPreference	readonly	Galley preference settings.
gradients	Gradients <i>Gradient</i>	readonly	A collection of gradients.
graphicLines	GraphicLines <i>GraphicLine</i>	readonly	A collection of graphic lines.
gridPreferences	GridPreference	readonly	Grid preference settings.

Property	Type	Access	Description
groups	Groups <i>Group</i>	readonly	A collection of groups.
guidePreferences	GuidePreference	readonly	Guide preference settings.
guides	Guides <i>Guide</i>	readonly	A collection of guides.
htmlExportPreferences	HTMLExportPreference	readonly	HTML export preference settings.
htmlFXLEExportPreferences	HTMLFXLEExportPreference	readonly	HTML FXL export preference settings.
hyperlinkExternalPageDestinations	HyperlinkExternalPageDestinations <i>HyperlinkExternalPageDestination</i>	readonly	A collection of hyperlink external page destinations.
hyperlinkPageDestinations	HyperlinkPageDestinations <i>HyperlinkPageDestination</i>	readonly	A collection of hyperlink page destinations.
hyperlinkPageItemSources	HyperlinkPageItemSources <i>HyperlinkPageItemSource</i>	readonly	A collection of hyperlink page item sources.
hyperlinkTextDestinations	HyperlinkTextDestinations <i>HyperlinkTextDestination</i>	readonly	A collection of hyperlink text destinations.
hyperlinkTextSources	HyperlinkTextSources <i>HyperlinkTextSource</i>	readonly	A collection of hyperlink text sources.
hyperlinkURLDestinations	HyperlinkURLDestinations <i>HyperlinkURLDestination</i>	readonly	A collection of hyperlink URL destinations.
hyperlinks	Hyperlinks <i>Hyperlink</i>	readonly	A collection of hyperlinks.
hyphenationExceptions	HyphenationExceptions <i>HyphenationException</i>	readonly	A collection of hyphenation exceptions lists.
id	Number	readonly	The unique ID of the Document.
index	Number	readonly	The index of the Document within its containing object.
indexGenerationOptions	IndexOptions	readonly	The index options properties that define how an index is formatted.
indexes	Indexes	readonly	A collection of indexes.
indexingSortOptions	IndexingSortOptions <i>IndexingSortOption</i>	readonly	A collection of indexing sort options.
inks	Inks <i>Ink</i>	readonly	A collection of inks.
isCloudDocument	Boolean	readonly	If true, the document is a cloud document.
isValid	Boolean	readonly	Returns true if the object specifier resolves to valid objects.
kinsokuTables	KinsokuTables <i>KinsokuTable</i>	readonly	A collection of kinsoku tables.
label	String	read/write	A property that can be set to any string.
languages	Languages <i>Language</i>	readonly	A collection of languages.
layers	Layers <i>Layer</i>	readonly	A collection of layers.
layoutGridData	LayoutGridDataInformation	readonly	Default properties specific to layout grids.
layoutWindows	LayoutWindows <i>LayoutWindow</i>	readonly	A collection of layout windows.
linkedPageItemOptions	LinkedPageItemOption	readonly	Linked Page Item options
linkedStoryOptions	LinkedStoryOption	readonly	Linked story options
links	Links <i>Link</i>	readonly	A collection of links.
listBoxes	ListBoxes	readonly	A collection of listboxes.
marginPreferences	MarginPreference	readonly	Margin preference settings.
masterSpreads	MasterSpreads <i>MasterSpread</i>	readonly	A collection of master spreads.
mathObjects	MathObjects <i>MathObject</i>	readonly	A collection of math objects.
metadataPreferences	MetadataPreference	readonly	Metadata preference settings.
mixedInkGroups	MixedInkGroups <i>MixedInkGroup</i>	readonly	A collection of mixed ink groups.
mixedInks	MixedInks <i>MixedInk</i>	readonly	A collection of mixed inks.
modified	Boolean	readonly	If true, the Document has been modified since it was last saved.
mojikumiTables	MojikumiTables <i>MojikumiTable</i>	readonly	A collection of mojikumi tables.
mojikumiUIPreferences	MojikumiUiPreference	readonly	Mojikumi user interface preference settings.
motionPresets	MotionPresets <i>MotionPreset</i>	readonly	A collection of Motion presets.
multiStateObjects	MultiStateObjects <i>MultiStateObject</i>	readonly	A collection of multi-state objects.

Property	Type	Access	Description
name	String	read/write	The name of the Document.
namedGrids	NamedGrids <i>NamedGrid</i>	readonly	A collection of named grids.
numberingLists	NumberingLists <i>NumberingList</i>	readonly	A collection of numbered lists.
objectStyleGroups	ObjectStyleGroups <i>ObjectStyleGroup</i>	readonly	A collection of object style groups.
objectStyles	ObjectStyles <i>ObjectStyle</i>	readonly	A collection of object styles.
ovals	Ovals <i>Oval</i>	readonly	A collection of ellipses.
pageItemDefaults	PageItemDefault	readonly	The default page item formatting for the Document.
pageItems	PageItems <i>PageItem</i>	readonly	The page items collection, which can be used to process all page items in a container (such as a document, page, or group), regardless of type.
pages	Pages <i>Page</i>	readonly	A collection of pages.
paraStyleMappings	ParaStyleMappings <i>ParaStyleMapping</i>	readonly	A collection of para style mappings.
paragraphDestinations	ParagraphDestinations <i>ParagraphDestination</i>	readonly	A collection of paragraph destinations.
paragraphStyleGroups	ParagraphStyleGroups <i>ParagraphStyleGroup</i>	readonly	A collection of paragraph style groups.
paragraphStyles	ParagraphStyles <i>ParagraphStyle</i>	readonly	A collection of paragraph styles.
parent	Application	readonly	The parent of the Document (a Application).
pasteboardPreferences	PasteboardPreference	readonly	Pasteboard preference settings.
pdfComments	PDFComments <i>PDFComment</i>	readonly	A collection of PDF comment objects
placeGuns	PlaceGun	readonly	The place gun.
polygons	Polygons <i>Polygon</i>	readonly	A collection of polygons.
preferMathMLInEpubExport	Boolean	read/write	Preference to export math objects as MathML or SVG in EPUB export.
preferences	Preferences <i>Preference</i>	readonly	A collection of preferences objects.
preflightOptions	PreflightOption	readonly	Preflight option settings.
preflightProfiles	PreflightProfiles <i>PreflightProfile</i>	readonly	A collection of preflight profiles.
printBookletOptions	PrintBookletOption	readonly	Booklet printing options.
printBookletPrintPreferences	PrintBookletPrintPreference	readonly	Print booklet preferences.
printPreferences	PrintPreference	readonly	Print preference settings.
properties	Object	read/write	A property that allows setting of several properties at the same time.
publishExportPreferences	PublishExportPreference	readonly	Publish export preference settings.
radioButtons	RadioButtons <i>RadioButton</i>	readonly	A collection of radio buttons.
readOnly	Boolean	readonly	If true, the Document is read-only.
recovered	Boolean	readonly	If true, the Document was recovered.
rectangles	Rectangles <i>Rectangle</i>	readonly	A collection of rectangles.
redoHistory	Array of String	readonly	The names of the items in the redo stack.
redoName	String	readonly	The name of the action on the top of the redo stack.
rgbPolicy	ColorSettingsPolicy ColorSettingsPolicy.COLOR_POLICY_OFF ColorSettingsPolicy.COMBINATION_OF_PRESERVE_AND_SAFE_CMYK ColorSettingsPolicy.CONVERT_TO_WORKING_SPACE ColorSettingsPolicy.PRESERVE_EMBEDDED_PROFILES	read/write	The policy for handling colors in an RGB color model, including reading and embedding color profiles, handling mismatches between embedded color profiles and the working space, and moving colors from one document to another.
rgbProfile	String	read/write	The current RGB profile.
rgbProfileList	Array of String	readonly	A list of valid RGB profiles.
saved	Boolean	readonly	If true, the Document has been saved since it was created.
sections	Sections <i>Section</i>	readonly	A collection of sections.
selectedPageItems	Array of Object NothingEnum.NOTHING	readonly	The selected page item(s). Can also accept: Object or NothingEnum

Property	Type	Access	Description
selection	Array of Object NothingEnum.NOTHING	read/write	enumerator. The selected object(s). Can also accept: Object or NothingEnum enumerator.
selectionKeyObject	PageItem NothingEnum.NOTHING	read/write	The key object of the selection. Can also accept: NothingEnum enumerator.
signatureFields	SignatureFields <i>SignatureField</i>	readonly	A collection of signature fields.
solidColorIntent	RenderingIntent RenderingIntent.ABSOLUTE_COLORIMETRIC RenderingIntent.PERCEPTUAL RenderingIntent.RELATIVE_COLORIMETRIC RenderingIntent.SATURATION RenderingIntent.USE_COLOR_SETTINGS	read/write	The rendering intent for all vector art (areas of solid color) in native objects.
splineItems	SplineItems <i>SplineItem</i>	readonly	The spline items collection.
spreads	Spreads <i>Spread</i>	readonly	A collection of spreads.
stories	Stories <i>Story</i>	readonly	A collection of stories.
storyGridData	StoryGridDataInformation	readonly	Default properties specific to frame grids.
storyPreferences	StoryPreference	readonly	Story preference settings.
storyWindows	StoryWindows <i>StoryWindow</i>	readonly	A collection of story windows.
stripedStrokeStyles	StripedStrokeStyles <i>StripedStrokeStyle</i>	readonly	A collection of striped stroke styles.
strokeStyles	StrokeStyles <i>StrokeStyle</i>	readonly	A collection of stroke styles.
swatches	Swatches	readonly	A collection of swatches.
tableStyleGroups	TableStyleGroups <i>TableStyleGroup</i>	readonly	A collection of table style groups.
tableStyleMappings	TableStyleMappings <i>TableStyleMapping</i>	readonly	A collection of table style mappings.
tableStyles	TableStyles <i>TableStyle</i>	readonly	A collection of table styles.
taggedPDFPreferences	TaggedPDFPreference	readonly	Tagged PDF preferences.
textBoxes	TextBoxes	readonly	A collection of text boxes.
textDefaults	TextDefault	readonly	Text default settings.
textFramePreferences	TextFramePreference	readonly	Text frame preference settings.
textFrames	TextFrames <i>TextFrame</i>	readonly	A collection of text frames.
textPreferences	TextPreference	readonly	Text preference settings.
textVariables	TextVariables <i>TextVariable</i>	readonly	A collection of text variables.
textWrapPreferences	TextWrapPreference	readonly	The text wrap preference properties that define the default formatting for wrapping text around objects.
tintValue	Number (range 0 - 100)	read/write	The percent of the base color. (Range: 0 to 100)
tints	Tints <i>Tint</i>	readonly	A collection of tints.
tocStyles	TOCStyles <i>TOCStyle</i>	readonly	A collection of TOC styles.
transparencyPreferences	TransparencyPreference	readonly	Transparency preference settings.
trapPresets	TrapPresets <i>TrapPreset</i>	readonly	A collection of trap presets.
undoHistory	Array of String	readonly	The names of the items in the undo stack.
undoName	String	readonly	The name of the action on the top of the undo stack.
unusedSwatches	Array of Swatch	readonly	The swatches that are not being used.
validationErrors	ValidationErrors <i>ValidationError</i>	readonly	A collection of XML validation errors.
versionState	VersionState VersionState.LOCAL_NEWER VersionState.LOCAL_PROJECT_MATCH VersionState.NO_RESOURCE VersionState.PROJECT_FILE_NEWER VersionState.VERSION_CONFLICT VersionState.VERSION_UNKNOWN	readonly	The Version Cue version state of the file.
viewPreferences	ViewPreference	readonly	View preference settings.
visible	Boolean	readonly	If true, the Document is visible.
watermarkPreferences	WatermarkPreference	readonly	Watermark preferences

Property	Type	Access	Description
windows	Windows <i>Window</i>	readonly	A collection of windows.
xmlComments	XMLComments <i>XMLComment</i>	readonly	A collection of XML comments.
xmlElements	XMLElements <i>XMLElement</i>	readonly	A collection of XML elements.
xmlExportMaps	XMLExportMaps <i>XMLExportMap</i>	readonly	A collection of XML export maps.
xmlExportPreferences	XMLExportPreference	readonly	XML export preference settings.
xmlImportMaps	XMLImportMaps <i>XMLImportMap</i>	readonly	A collection of XML import maps.
xmlImportPreferences	XMLImportPreference	readonly	XML import preference settings.
xmlInstructions	XMLInstructions <i>XMLInstruction</i>	readonly	A collection of XML instructions.
xmlItems	XMLItems <i>XMLItem</i>	readonly	A collection of XML items.
xmlPreferences	XMLPreference	readonly	The XML preference settings.
xmlStories	XmlStories <i>XmlStory</i>	readonly	A collection of xml stories.
xmlTags	XMLTags <i>XMLTag</i>	readonly	A collection of XML tags.
xmlViewPreferences	XMLViewPreference	readonly	XML view preference settings.
zeroPoint	Array of Number Array of String	read/write	The ruler origin, specified as page coordinates in the format [x, y].

Constants/Events

Name	Type	Access	Description
AFTER_ACTIVATE	String	readonly	Dispatched after the Document becomes active. This event bubbles. This event is not cancelable.
AFTER_EXPORT	String	readonly	Dispatched after a Document is exported. This event bubbles. This event is not cancelable.
AFTER_IMPORT	String	readonly	Dispatched after importing a file into a Document. This event bubbles. This event is not cancelable.
AFTER_LINKS_CHANGED	String	readonly	Dispatched after one or more links in the Document have been added, deleted, or modified. This event bubbles. This event is not cancelable.
AFTER_NEW	String	readonly	Dispatched after a Document is created. This event bubbles. This event is not cancelable.
AFTER_OPEN	String	readonly	Dispatched after a Document is opened. This event bubbles. This event is not cancelable.
AFTER_PRINT	String	readonly	Dispatched after a Document is printed. This event bubbles. This event is not cancelable.
AFTER_REVERT	String	readonly	Dispatched after a Document is reverted. This event bubbles. This event is not cancelable.
AFTER_SAVE	String	readonly	Dispatched after a Document is saved. This event bubbles. This event is not cancelable.
AFTER_SAVE_AS	String	readonly	Dispatched after a Document is saved under a new name. This event bubbles. This event is not cancelable.
AFTER_SAVE_A_COPY	String	readonly	Dispatched after a copy of a Document is saved. This event bubbles. This event is not cancelable.
BEFORE_CLOSE	String	readonly	Dispatched before a Document is closed. This event bubbles. This event is not cancelable.
BEFORE_DEACTIVATE	String	readonly	Dispatched before the Document becomes inactive. This event bubbles. This event is not cancelable.
BEFORE_EXPORT	String	readonly	Dispatched before a Document is exported. This event bubbles. This event is cancelable.
BEFORE_IMPORT	String	readonly	Dispatched before importing a file into a Document. This event bubbles. This event is cancelable.
BEFORE_PRINT	String	readonly	Dispatched before a Document is printed. This event bubbles. This event is cancelable.
BEFORE_REVERT	String	readonly	Dispatched before a Document is reverted. This event bubbles. This event is cancelable.
BEFORE_SAVE	String	readonly	Dispatched before a Document is saved. This event bubbles. This event is cancelable.
BEFORE_SAVE_AS	String	readonly	Dispatched before a Document is saved under a new name. This event bubbles. This event is cancelable.

Name	Type	Access	Description
BEFORE_SAVE_A_COPY	String	readonly	Dispatched before a copy of a Document is saved. This event bubbles. This event is cancelable.
FAILED_EXPORT	String	readonly	Dispatched after a Document export is canceled or fails. This event bubbles. This event is not cancelable.

Method Listing

EventListener **addEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **adjustLayout** (adoptTo:*Object*, affectedPages:*Array of Page*)

Adjust the existing layout according to new page size, bleed and margin values. The first parameter is a plain object with key value pairs for properties affected. Permissible keys are width, height, bleedInside, bleedTop, bleedOutside, bleedBottom, leftMargin, topMargin, rightMargin, bottomMargin. The values can be specified as decimal numbers in units of Pt or as a string having a measurement value such as '1 in'. Not all properties need to be specified, only the values that need update. Notice that when dealing with individual pages rather than the whole document, bleed changes has no effect. E.g. -
app.activeDocument.adjustLayout({width:'600px', leftMargin: '1in'}), app.activeDocument.adjustLayout({rightMargin:'1in'},
app.activeDocument.spreads[0].pages), app.activeDocument.spreads[0].pages[0].adjustLayout({width:'400px', leftMargin: '10px'})

Parameter	Type	Description
adoptTo	Object	Change values - see functin definition for details
affectedPages	Array of Page	The collection of Page objects to affect (optional). Has no effect if function is called from Page (Optional)

undefined **align** (alignDistributeItems:*Array of PageItem*, alignOption:*AlignOptions*, alignDistributeBounds:*AlignDistributeBounds*, reference:*PageItem*)

Align page items.

Parameter	Type	Description
alignDistributeItems	Array of PageItem	The page items to align or distribute.
alignOption	AlignOptions AlignOptions.BOTTOM_EDGES AlignOptions.HORIZONTAL_CENTERS AlignOptions.LEFT_EDGES AlignOptions.RIGHT_EDGES AlignOptions.TOP_EDGES AlignOptions.VERTICAL_CENTERS	The type of alignment to apply.
alignDistributeBounds	AlignDistributeBounds AlignDistributeBounds.BLEED_BOUNDS AlignDistributeBounds.ITEM_BOUNDS AlignDistributeBounds.KEY_OBJECT AlignDistributeBounds.MARGIN_BOUNDS AlignDistributeBounds.PAGE_BOUNDS AlignDistributeBounds.SPREAD_BOUNDS	The bounds within which to align or distribute the page items. (Optional)
reference	PageItem	The reference or key object to align to distribute relative to. Required when 'align distribute bounds' specifies 'key object'. (Optional)

BackgroundTask **asynchronousExportFile** (format:*Varies ExportFormat String*, to:*File*, [showingOptions:*Boolean*=Boolean], using:*PDFExportPreset*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

asynchronously exports the object(s) to a file.

Parameter	Type	Description
format	ExportFormat ExportFormat.EPS_TYPE ExportFormat.EPUB ExportFormat.FIXED_LAYOUT_EPUB ExportFormat.HTML ExportFormat.HTMLFXL ExportFormat.INCOPY_MARKUP ExportFormat.INDESIGN_MARKUP ExportFormat.INDESIGN_SNIPPET	The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String.

Parameter	Type	Description
	ExportFormat.INTERACTIVE_PDF ExportFormat.JPG ExportFormat.PDF_TYPE ExportFormat.PNG_FORMAT ExportFormat.RTF ExportFormat.TAGGED_TEXT ExportFormat.TEXT_TYPE ExportFormat.XML String	
to	File	The path to the export file.
showingOptions	Boolean	If true, displays the export options dialog. (Optional) (default: false)
using	PDFExportPreset	The export style. (Optional)
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

Number **changeColor** ()

Finds color that matches the find what value and replaces the color with the change to value.

undefined **changeComposer** ()

Change comoser to optyca

Text **changeGlyph** (reverseOrder: Boolean)

Finds glyphs that match the find what value and replaces the glyphs with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeGrep** (reverseOrder: Boolean)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

PageItem **changeObject** (reverseOrder: Boolean)

Finds objects that match the find what value and replace the objects with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeText** (reverseOrder: Boolean)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeTransliterate** (reverseOrder: Boolean)

Finds text that matches the find character type value and replaces the text with the change character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

undefined **checkIn** (versionComments: String, [forceSave: Boolean=Boolean])

Check in to Version Cue.

Parameter	Type	Description
versionComments	String	The comment for this version (Optional)
forceSave	Boolean	Forcibly save a version (Optional) (default: false)

undefined **clearFrameFittingOptions** ()

Removes the frame fittings options and resets it to the initial state.

undefined **close** ([saving:*SaveOptions*=SaveOptions], savingIn:*File*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

Close the Document

Parameter	Type	Description
saving	<i>SaveOptions</i> SaveOptions.ASK SaveOptions.NO SaveOptions.YES	Whether to save changes before closing the Document (Optional) (default: SaveOptions.ASK)
savingIn	<i>File</i>	The file in which to save the Document (Optional)
versionComments	<i>String</i>	The comment for this version (Optional)
forceSave	<i>Boolean</i>	Forcibly save a version (Optional) (default: false)

Number **colorTransform** (colorValue:*Array of Number*, sourceColorSpace:*ColorSpace*, destinationColorSpace:*ColorSpace*)

Transforms color values

Parameter	Type	Description
colorValue	<i>Array of Number</i>	source color value
sourceColorSpace	<i>ColorSpace</i> ColorSpace.CMYK ColorSpace.HSB ColorSpace.LAB ColorSpace.MIXEDINK ColorSpace.RGB	source color space
destinationColorSpace	<i>ColorSpace</i> ColorSpace.CMYK ColorSpace.HSB ColorSpace.LAB ColorSpace.MIXEDINK ColorSpace.RGB	destination color space

undefined **createAlternateLayout** (spreadItems:*Array of Spread*, name:*String*, width:*Number String*, height:*Number String*, createTextStyles:*Boolean*, linkTextStories:*Boolean*, layoutRule:*LayoutRuleOptions*)

Creates an alternate layout for a given list of spreads.

Parameter	Type	Description
spreadItems	<i>Array of Spread</i>	The spreads to create an alternate layout for.
name	<i>String</i>	The name of the alternate layout. Note: This is used for the named layout for the new section for the duplicated spreads.
width	<i>Number String</i>	The width of the pages created.
height	<i>Number String</i>	The height of the pages created.
createTextStyles	<i>Boolean</i>	Whether to create new text styles.
linkTextStories	<i>Boolean</i>	Whether to create linked text for duplicated text stories.
layoutRule	<i>LayoutRuleOptions</i> LayoutRuleOptions.GUIDE_BASED LayoutRuleOptions.OBJECT_BASED LayoutRuleOptions.OFF LayoutRuleOptions.PRESERVE_EXISTING LayoutRuleOptions.RECENTER LayoutRuleOptions.SCALE LayoutRuleOptions.USE_MASTER	What layout rule to set on the pages.

undefined **createEmailQRCode** (emailAddress:*String*, subject:*String*, body:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Email QR Code on the page item or document

Parameter	Type	Description
emailAddress	<i>String</i>	QR code Email Address (Optional)
subject	<i>String</i>	QR code Email Subject (Optional)
body	<i>String</i>	QR code Email Body Message (Optional)
qrCodeSwatch	<i>Swatch String</i>	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	<i>Array of String</i>	Initial values for properties of the new Document. Above parameters can also be passed as properties (Optional)

SVG createFromMathML (mathmlDescription:*String*, destinationPage:*Page*, destinationLayer:*Layer*, placePoint:*Array of Number String*)

Creates a new object from MathML description.

Parameter	Type	Description
mathmlDescription	String	The MathML description to create the SVG from.
destinationPage	Page	The page on which to create the object.
destinationLayer	Layer	The layer on which to create the Object.
placePoint	Array of Number Array of String	The point where to place the object (only applicable if you are telling a page or spread to place)

undefined **createHyperlinkQRCode** (urlLink:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Hyperlink QR Code on the page item or document

Parameter	Type	Description
urlLink	String	QR code Hyperlink URL (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Document. Above parameters can also be passed as properties (Optional)

Font **createMissingFontObject** (fontFamily:*String*, fontStyleName:*String*, postscriptName:*String*)

Create a missing font object.

Parameter	Type	Description
fontFamily	String	The name of the font family
fontStyleName	String	The name of the font style.
postscriptName	String	The PostScript name of the font.

undefined **createPlainTextQRCode** (plainText:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Plain Text QR Code on the page item

Parameter	Type	Description
plainText	String	QR code Plain Text (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Document. Above parameters can also be passed as properties (Optional)

Story **createTOC** (using:*TOCStyle*, [replacing:*Boolean*=Boolean], fromBook:*Book*, placePoint:*Array of Number String*, [includeOverset:*Boolean*=Boolean], destinationLayer:*Layer*)

Creates a table of contents.

Parameter	Type	Description
using	TOCStyle	The TOC style to use to define the content, title, and format of the table of contents.
replacing	Boolean	If true, replaces the existing TOC. (Optional) (default: false)
fromBook	Book	The book whose documents to include in the TOC. (Optional)
placePoint	Array of Number Array of String	The point at which to place the TOC story, specified as page coordinates in the format [x, y]. (Optional)
includeOverset	Boolean	If true, includes overset text TOC entries in the TOC. (Optional) (default: false)
destinationLayer	Layer	The layer on which to place the TOC. (Optional)

undefined **createTextMsgQRCode** (cellNumber:*String*, textMessage:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Text Msg QR Code on the page item or document

Parameter	Type	Description
cellNumber	String	QR code Text Phone Number (Optional)
textMessage	String	QR code Text Message (Optional)

Parameter	Type	Description
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Document. Above parameters can also be passed as properties (Optional)

undefined **createVCardQRCode** (firstName:String, lastName:String, jobTitle:String, cellPhone:String, phone:String, email:String, organisation:String, streetAddress:String, city:String, adrState:String, country:String, postalCode:String, website:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Business Card QR Code on the page item or load on document's placegun

Parameter	Type	Description
firstName	String	QR code Business Card First Name (Optional)
lastName	String	QR code Business Card Last Name (Optional)
jobTitle	String	QR code Business Card Title (Optional)
cellPhone	String	QR code Business Card Cell Phone Number (Optional)
phone	String	QR code Business Card Phone Number (Optional)
email	String	QR code Business Card Email Address (Optional)
organisation	String	QR code Business Card Organisation (Optional)
streetAddress	String	QR code Business Card Street Address (Optional)
city	String	QR code Business Card City (Optional)
adrState	String	QR code Business Card State (Optional)
country	String	QR code Business Card Country (Optional)
postalCode	String	QR code Business Card Postal Code (Optional)
website	String	QR code Business Card URL (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Document. Above parameters can also be passed as properties (Optional)

undefined **deleteAlternateLayout** (name:String)

Deletes an alternate layout.

Parameter	Type	Description
name	String	The name of the alternate layout to delete.

undefined **deleteUnusedTags** ()

Deletes unused XML markup tags.

undefined **distribute** (alignDistributeItems:Array of PageItem, distributeOption:DistributeOptions, alignDistributeBounds:AlignDistributeBounds, useDistributeMeasurement:Boolean, absoluteDistributeMeasurement:Number String, reference:PageItem)

Distribute page items.

Parameter	Type	Description
alignDistributeItems	Array of PageItem	The page items to align or distribute
distributeOption	DistributeOptions DistributeOptions.BOTTOM_EDGES DistributeOptions.HORIZONTAL_CENTERS DistributeOptions.HORIZONTAL_SPACE DistributeOptions.LEFT_EDGES DistributeOptions.RIGHT_EDGES DistributeOptions.TOP_EDGES DistributeOptions.VERTICAL_CENTERS DistributeOptions.VERTICAL_SPACE	The type of distribution to apply.
alignDistributeBounds	AlignDistributeBounds AlignDistributeBounds.BLEED_BOUNDS AlignDistributeBounds.ITEM_BOUNDS AlignDistributeBounds.KEY_OBJECT AlignDistributeBounds.MARGIN_BOUNDS AlignDistributeBounds.PAGE_BOUNDS AlignDistributeBounds.SPREAD_BOUNDS	The bounds within which to align or distribute the page items. (Optional)
useDistributeMeasurement	Boolean	If true, distribute space between page items. When this property is true, the bounds setting is ignored. (Optional)

Parameter	Type	Description
absoluteDistributeMeasurement	Number String	The distance to use when distributing page items. Required when 'align distribute bounds' specifies 'key object'. (Optional)
reference	PageItem	The reference or key object to align to distribute relative to. Required when 'align distribute bounds' specifies 'key object'. (Optional)

PreflightProfile **embed** (using:Varies String PreflightProfile)

Embed this profile to the document.

Parameter	Type	Description
using	String PreflightProfile	The preflight profile to embed. Can accept: String or PreflightProfile.

undefined **exportFile** (format:Varies ExportFormat String, to:File, [showingOptions:Boolean=Boolean], using:PDFExportPreset, versionComments:String, [forceSave:Boolean=Boolean])

Exports the object(s) to a file.

Parameter	Type	Description
format	ExportFormat ExportFormat.EPS_TYPE ExportFormat.EPUB ExportFormat.FIXED_LAYOUT_EPUB ExportFormat.HTML ExportFormat.HTMLFXL ExportFormat.INCOPY_MARKUP ExportFormat.INDESIGN_MARKUP ExportFormat.INDESIGN_SNIPPET ExportFormat.INTERACTIVE_PDF ExportFormat.JPG ExportFormat.PDF_TYPE ExportFormat.PNG_FORMAT ExportFormat.RTF ExportFormat.TAGGED_TEXT ExportFormat.TEXT_TYPE ExportFormat.XML String	The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String.
to	File	The path to the export file.
showingOptions	Boolean	If true, displays the export options dialog. (Optional) (default: false)
using	PDFExportPreset	The export style. (Optional)
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

Boolean **exportForCloudLibrary** (jsonData:String)

Exports as assets required for cloud library.

Parameter	Type	Description
jsonData	String	JSON encoded information about the export.

undefined **exportPageItemsSelectionToSnippet** (to:File)

Exports selected page items to snippet on the destination file path.

Parameter	Type	Description
to	File	The path to the export file.

undefined **exportPageItemsToSnippet** (to:File, pageItemIds:Array of Number)

Exports input page item ids to snippet on the destination file path.

Parameter	Type	Description
to	File	The path to the export file.
pageItemIds	Array of Number	The array of the page item ids.

undefined **exportStrokeStyles** (to:File, strokeStyleList:Array of StrokeStyle, versionComments:String, [forceSave:Boolean=Boolean])

Exports stroke styles or presets.

Parameter	Type	Description
to	File	The file to save to
strokeStyleList	Array of StrokeStyle	The list of stroke styles to save
versionComments	String	The comment for this version (Optional)
forceSave	Boolean	Forcibly save a version (Optional) (default: false)

String **extractLabel** (key:String)

Gets the label value associated with the specified key.

Parameter	Type	Description
key	String	The key.

Number **findColor** ()

Finds color that matches the find what value.

Text **findGlyph** (reverseOrder:Boolean)

Finds glyphs that match the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findGrep** (reverseOrder:Boolean)

Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

PageItem **findObject** (reverseOrder:Boolean)

Finds objects that match the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findText** (reverseOrder:Boolean)

Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findTransliterate** (reverseOrder:Boolean)

Finds text that matches the find character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Varies **getAlternateLayoutsForFolio** (resolveMaster:Boolean)

This will return an array of structs containing information about the alternate layouts.

Parameter	Type	Description
resolveMaster	Boolean	Resolves layout policy if setting is "use master" - default is true. (Optional)

Document **getElements** ()

Resolves the object specifier, creating an array of object references.

TextDirection **getSelectedTextDirection** ()

Selected text direction

Varies **getStyleConflictResolutionStrategy** (charOrParaStyle:StyleType)

Get the resolution strategy for style conflict, false if the user cancels

Parameter	Type	Description
charOrParaStyle	StyleType	Style type to look at. (Optional)

Parameter	Type	Description
	StyleType.CHARACTER_STYLE_TYPE StyleType.PARAGRAPH_STYLE_TYPE	

undefined **handleMathMLMessage** (resyncData:String)

Internal Use Only

Parameter	Type	Description
resyncData	String	Internal Use Only

Color **importAdobeSwatchbookProcessColor** (name:String)

Imports a process color swatch from a preloaded Adobe color book.

Parameter	Type	Description
name	String	The process color to load.

Color **importAdobeSwatchbookSpotColor** (name:String)

Imports a spot color swatch from an Adobe color book.

Parameter	Type	Description
name	String	The spot color to load.

undefined **importDtd** (from:File)

Imports a DTD to use for validation.

Parameter	Type	Description
from	File	The path to the DTD file.

undefined **importFormats** (from:File)

Imports the cross reference formats from specified file.

Parameter	Type	Description
from	File	The file whose formats to import.

undefined **importPdfComments** (from:File, withProperties:Object)

Import Commemnts from PDF

Parameter	Type	Description
from	File	The PDF File from which you want to import comments.
withProperties	Object	Initial values for properties of the new Document (Optional)

undefined **importStyles** (format:ImportFormat, from:File, [globalStrategy:GlobalClashResolutionStrategy=GlobalClashResolutionStrategy])

Imports the specified styles.

Parameter	Type	Description
format	ImportFormat ImportFormat.CELL_STYLES_FORMAT ImportFormat.CHARACTER_STYLES_FORMAT ImportFormat.OBJECT_STYLES_FORMAT ImportFormat.PARAGRAPH_STYLES_FORMAT ImportFormat.STROKE_STYLES_FORMAT ImportFormat.TABLE_AND_CELL_STYLES_FORMAT ImportFormat.TABLE_STYLES_FORMAT ImportFormat.TEXT_STYLES_FORMAT ImportFormat.TOC_STYLES_FORMAT	The types of styles to import.
from	File	The file containing the styles you want to import.
globalStrategy	GlobalClashResolutionStrategy GlobalClashResolutionStrategy.DO_NOT_LOAD_THE_STYLE GlobalClashResolutionStrategy.LOAD_ALL_WITH_OVERWRITE GlobalClashResolutionStrategy.LOAD_ALL_WITH_RENAME	The resolution strategy to employ for imported styles that have the same names as existing styles. (Optional) (default: GlobalClashResolutionStrategy.LOAD_ALL_WITH_OVERWRITE)

undefined **importXML** (from:File)

Imports the specified XML file into an InDesign document.

Parameter	Type	Description
from	File	The XML file.

undefined **insertLabel** (key:String, value:String)

Sets the label to the value associated with the specified key.

Parameter	Type	Description
key	String	The key.
value	String	The value.

String **internalMethod** (internalParameter1:String, internalParameter2:String)

Internal use only: a black box method for use by InDesign Engineering team only.

Parameter	Type	Description
internalParameter1	String	The first internal parameter
internalParameter2	String	The second internal parameter

undefined **loadConditions** (from:File, loadConditionSets:Boolean)

Load conditions from the specified file.

Parameter	Type	Description
from	File	The path to the file that contains the conditions.
loadConditionSets	Boolean	If true, load the condition sets as well. (Optional)

undefined **loadMasters** (from:File,

[globalStrategyForMasterPage:GlobalClashResolutionStrategyForMasterPage=GlobalClashResolutionStrategyForMasterPage])

Load masterpages from an InDesign file.

Parameter	Type	Description
from	File	The InDesign file to load the masters from.
globalStrategyForMasterPage	GlobalClashResolutionStrategyForMasterPage GlobalClashResolutionStrategyForMasterPage.LOAD_ALL_WITH_OVERWRITE GlobalClashResolutionStrategyForMasterPage.LOAD_ALL_WITH_RENAME	the global clash resolution strategy for load master pa (default: GlobalClashResolutionStrategyForMasterPage.LOAD_

undefined **loadSwatches** (from:File)

Load swatches from the specified file.

Parameter	Type	Description
from	File	The swatch file or InDesign document.

undefined **loadXMLTags** (from:File)

Loads a set of XML markup tags from the specified file.

Parameter	Type	Description
from	File	The path to the file that contains the tags.

undefined **mapStylesToXMLTags** ()

Auto tag the document based on the style to tag mappings

undefined **mapXMLTagsToStyles** ()

Auto style the document based on the tag to style mappings

Boolean **packageForPrint** (to:File, copyingFonts:Boolean, copyingLinkedGraphics:Boolean, copyingProfiles:Boolean, updatingGraphics:Boolean, includingHiddenLayers:Boolean, ignorePreflightErrors:Boolean, creatingReport:Boolean, includeldml:Boolean, includePdf:Boolean, pdfStyle:String, useDocumentHyphenationExceptionsOnly:Boolean, versionComments:String, [forceSave:Boolean=Boolean])

Packages the document.

Parameter	Type	Description
to	File	The folder, alias, or path in which to place the packaged files.
copyingFonts	Boolean	If true, copies fonts used in the document to the package folder.
copyingLinkedGraphics	Boolean	If true, copies linked graphics files to the package folder.
copyingProfiles	Boolean	If true, copies color profiles to the package folder.
updatingGraphics	Boolean	If true, updates graphics links to the package folder.
includingHiddenLayers	Boolean	If true, copies fonts and links from hidden layers to the package.
ignorePreflightErrors	Boolean	If true, ignores preflight errors and proceeds with the packaging. If false, cancels the packaging when errors exist.

Parameter	Type	Description
creatingReport	Boolean	If true, creates a package report that includes printing instructions, print settings, lists of fonts, links and required inks, and other information.
includeIdml	Boolean	If true, generates and includes IDML in the package folder. (Optional)
includePdf	Boolean	If true, generates and includes PDF in the package folder. (Optional)
pdfStyle	String	If specified and PDF is to be included, use this style for PDF export if it is valid, otherwise use the last used PDF preset. (Optional)
useDocumentHyphenationExceptionsOnly	Boolean	If this option is selected, InDesign flags this document so that it does not reflow when someone else opens or edits it on a computer that has different hyphenation and dictionary settings. (Optional)
versionComments	String	The comments for the version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

undefined **place** (fileName: *Array of Varies File Files.*, [showingOptions: *Boolean*=Boolean], withProperties: *Object*)

Place one or more files following the behavior of the place menu item. This may load the place gun or replace the selected object, depending on current preferences.

Parameter	Type	Description
fileName	File Array of Files.	One or more files to place. Can accept: File or Array of Files.
showingOptions	Boolean	Whether to display the import options dialog (Optional) (default: false)
withProperties	Object	Initial values for properties of the placed object(s) (Optional)

undefined **placeAndLink** (parentStory: *Story*, [showingOptions: *Boolean*=Boolean])

Deprecated: Use ContentPlacerObject load method. Original Description: Place following the behavior of the place and link story menu item. This will load the place gun.

Parameter	Type	Description
parentStory	Story	The story to place and link from.
showingOptions	Boolean	Whether to display the link options dialog (Optional) (default: false)

undefined **placeCloudAsset** (jsonData: *String*)

place a cloud asset on the document

Parameter	Type	Description
jsonData	String	JSON data containing metadata about the cloud asset

undefined **print** (printDialog: *Boolean*, using: *Varies PrinterPresetTypes PrinterPreset*)

Prints the Document(s).

Parameter	Type	Description
printDialog	Boolean	Whether to invoke the print dialog (Optional)
using	PrinterPresetTypes PrinterPresetTypes.CUSTOM PrinterPresetTypes.DEFAULT_VALUE PrinterPreset	Printer preset to use. Can accept: PrinterPresetTypes enumerator or PrinterPreset. (Optional)

undefined **printBooklet** ([printBookletDialog: *Boolean*=Boolean], using: *Varies PrinterPresetTypes PrinterPreset*)

Print the Booklet using current document and Booklet and Print settings in the document

Parameter	Type	Description
printBookletDialog	Boolean	Whether to invoke the print booklet dialog (Optional) (default: false)
using	PrinterPresetTypes PrinterPresetTypes.CUSTOM PrinterPresetTypes.DEFAULT_VALUE PrinterPreset	Printer preset to use. Can accept: PrinterPresetTypes enumerator or PrinterPreset. (Optional)

undefined **recompose** ()

Recomposes the text in the Document.

undefined **redo** ()

Redoes the last action.

Boolean **removeEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **resetAllButtons** ()

Resets all the buttons to their Normal state.

undefined **resetAllMultiStateObjects** ()

Resets all the multi-state objects to their first state.

Boolean **revert** ()

Reverts the document to its state at the last save operation.

undefined **revertToProject** ([forceRevert:Boolean=Boolean])

Reverts to the version of the document in Version Cue.

Parameter	Type	Description
forceRevert	Boolean	Forcibly reverts to the project version. (Optional) (default: false)

Document **save** (to:File, [stationery:Boolean=Boolean], versionComments:String, [forceSave:Boolean=Boolean])

Save the document

Parameter	Type	Description
to	File	Where to save the document. If the document is already saved, a copy is saved at this path, the original file is closed the new copy is opened (Optional)
stationery	Boolean	Whether to save the file as stationery (Optional) (default: false)
versionComments	String	The comment for this version (Optional)
forceSave	Boolean	Forcibly save a version (Optional) (default: false)

undefined **saveACopy** (to:File, [stationery:Boolean=Boolean])

Saves a copy of the document.

Parameter	Type	Description
to	File	The file path for the copy. Note: Leaves the original document open and does not open the copy. (Optional)
stationery	Boolean	If true, saves the file as stationery (Mac OS) or as a template (Windows). Note: The file extension for stationery and templates is different than the extension for regular files. (Optional) (default: false)

Document **saveACopyCloud** (cloudPath:String)

Save a copy as cloud document

Parameter	Type	Description
cloudPath	String	The cloud path in case of a cloud document

Document **saveAsCloud** (cloudPath:String)

Save as a cloud document

Parameter	Type	Description
cloudPath	String	The cloud path in case of a cloud document

undefined **saveSwatches** (to:*File*, swatchList:*Array of Swatch*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

Saves the specified swatch(es) to a swatchbook file.

Parameter	Type	Description
to	File	The swatchbook file to save to.
swatchList	Array of Swatch	The swatch(es) to save.
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

undefined **saveXMLTags** (to:*File*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

Saves a set of tags to an external file.

Parameter	Type	Description
to	File	The full path to the file in which to save the tags.
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

undefined **select** (selectableItems:*Array of Varies Objects NothingEnum Object SelectAll*, [existingSelection:*SelectionOptions*=SelectionOptions])

Selects the specified object(s).

Parameter	Type	Description
selectableItems	Array of Objects NothingEnum.NOTHING Object SelectAll SelectAll.ALL	The objects to select. Can accept: Object, Array of Objects, NothingEnum enumerator or SelectAll enumerator.
existingSelection	SelectionOptions SelectionOptions.ADD_TO SelectionOptions.REMOVE_FROM SelectionOptions.REPLACE_WITH SelectionOptions.SET_KEY	The selection status of the Document in relation to previously selected objects. (Optional) (default: SelectionOptions.REPLACE_WITH)

VersionCueSyncStatus **synchronizeWithVersionCue** ([syncConflictResolution:*SyncConflictResolution*=SyncConflictResolution], versionComments:*String*)

Synchronizes the file with the Version Cue project.

Parameter	Type	Description
syncConflictResolution	SyncConflictResolution SyncConflictResolution.ASK_ABOUT_CONFLICTS SyncConflictResolution.PREFER_LOCAL SyncConflictResolution.PREFER_PROJECT SyncConflictResolution.SKIP_CONFLICTS	The conflict resolution method to use during synchronization. (Optional) (default: SyncConflictResolution.SKIP_CONFLICTS)
versionComments	String	The comments that describe the version. (Optional)

String **toSource** ()

Generates a string which, if executed, will return the Document.

String **toSpecifier** ()

Retrieves the object specifier.

undefined **undo** ()

Undoes the last action.

undefined **updateCrossReferences** ()

Updates cross references' text source content in the document.

Object of

- Book.styleSourceDocument
- Application.activeDocument
- AdjustLayoutPreference.parent
- AnchoredObjectDefault.parent
- AnchoredObjectSetting.parent
- Article.parent

Assignment.parent
BaselineFrameGridOption.parent
Bookmark.parent
ButtonPreference.parent
CellStyle.parent
CellStyleGroup.parent
CellStyleMapping.parent
ChapterNumberPreference.parent
CharStyleMapping.parent
CharacterStyle.parent
CharacterStyleGroup.parent
CJKGridPreference.parent
Color.parent
ColorGroup.parent
CompositeFont.parent
Condition.parent
ConditionSet.parent
ConditionalTextPreference.parent
CrossReferenceFormat.parent
CrossReferenceSource.parent
DTD.parent
DashedStrokeStyle.parent
DataMerge.parent
DataMergeImagePlaceholder.parent
DataMergeOption.parent
DataMergeQrcodePlaceholder.parent
DataMergeTextPlaceholder.parent
DictionaryPreference.parent
DocumentEvent.parent
DocumentPreference.parent
DottedStrokeStyle.parent
EPubExportPreference.parent
EPubFixedLayoutExportPreference.parent
EndnoteOption.parent
Event.parent
EventListener.parent
ExportForWebPreference.parent
Font.parent
FootnoteOption.parent
FrameFittingOption.parent
GalleyPreference.parent
Gradient.parent
GridPreference.parent
GuidePreference.parent
HTMLExportPreference.parent
HTMLFXLExportPreference.parent
Hyperlink.parent
HyperlinkExternalPageDestination.parent
HyperlinkPageDestination.parent
HyperlinkPageItemSource.parent
HyperlinkTextDestination.parent
HyperlinkTextSource.parent
HyperlinkURLDestination.parent
HyphenationException.parent
ImportExportEvent.parent
Index.parent
IndexOptions.parent
IndexingSortOption.parent
Ink.parent
KinsokuTable.parent
Language.parent
Layer.parent
LayoutGridDataInformation.parent
LayoutWindow.parent
LinkedPageItemOption.parent
LinkedStoryOption.parent
MarginPreference.parent
MasterSpread.parent
MetadataPreference.parent
MixedInk.parent
MixedInkGroup.parent
MojikumiTable.parent
MojikumiUiPreference.parent
MotionPreset.parent

MutationEvent.parent
NamedGrid.parent
NumberingList.parent
ObjectStyle.parent
ObjectStyleGroup.parent
PDFComment.parent
PageItemDefault.parent
ParaStyleMapping.parent
ParagraphDestination.parent
ParagraphStyle.parent
ParagraphStyleGroup.parent
PasteboardPreference.parent
PlaceGun.parent
Preference.parent
PreflightOption.parent
PreflightProfile.parent
PrintBookletOption.parent
PrintBookletPrintPreference.parent
PrintEvent.parent
PrintPreference.parent
PublishExportPreference.parent
Section.parent
Spread.parent
Story.parent
StoryGridDataInformation.parent
StoryPreference.parent
StoryWindow.parent
StripedStrokeStyle.parent
StrokeStyle.parent
Swatch.parent
TOCStyle.parent
TableStyle.parent
TableStyleGroup.parent
TableStyleMapping.parent
TaggedPDFPreference.parent
TextDefault.parent
TextFramePreference.parent
TextPreference.parent
TextVariable.parent
TextWrapPreference.parent
Tint.parent
TransparencyPreference.parent
TrapPreset.parent
ValidationError.parent
ViewPreference.parent
WatermarkPreference.parent
Window.parent
XMLComment.parent
XMLElement.parent
XMLExportMap.parent
XMLExportPreference.parent
XMLImportMap.parent
XMLImportPreference.parent
XMLInstruction.parent
XMLItem.parent
XMLPreference.parent
XMLTag.parent
XMLViewPreference.parent
XmlStory.parent
PreflightProcess.targetObject

Return

Documents.add()
Application.openCloudDocument()
Document.getElements()
Documents.anyItem()
Documents.everyItem()
Documents.nextItem()
Documents.previousItem()
Documents.itemByID()
Documents.item()
Documents.[]()
Documents.itemByName()

```
Documents.itemByRange()  
Documents.firstItem()  
Documents.lastItem()  
Documents.middleItem()  
Document.saveACopyCloud()  
Document.saveAsCloud()  
Document.save()
```
