

FindGrepPreference

Find grep preferences.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [getElements](#), [isNthDesignAxisHidden](#), [removeEventListener](#), [setNthDesignAxis](#), [toSource](#), [toSpecifier](#)

Objects:

[AdornmentOverprint](#), [AlternateGlyphForms](#), [BalanceLinesStyle](#), [Boolean](#), [Bullet](#), [Capitalization](#), [CharacterAlignment](#), [CharacterDirectionOptions](#), [CharacterStyle](#), [DiacriticPositionOptions](#), [DigitsTypeOptions](#), [EventListeners](#), [Events](#), [Font](#), [GridAlignment](#), [Justification](#), [KashidasOptions](#), [KentenAlignment](#), [KentenCharacter](#), [KentenCharacterSet](#), [KinsokuHangTypes](#), [KinsokuSet](#), [KinsokuTable](#), [KinsokuType](#), [LanguageWithVendors](#), [Leading](#), [LeadingModel](#), [ListType](#), [MojikumiTable](#), [MojikumiTableDefaults](#), [NothingEnum](#), [NumberingList](#), [NumberingRestartPolicy](#), [NumberingStyle](#), [OTFFigureStyle](#), [Object](#), [OutlineJoin](#), [ParagraphDirectionOptions](#), [ParagraphJustificationOptions](#), [Position](#), [PositionalForms](#), [Preferences](#), [RubyAlignments](#), [RubyKentenPosition](#), [RubyOverhang](#), [RubyParentSpacing](#), [RubyTypes](#), [SingleWordJustification](#), [Spacing](#), [SpanColumnCountOptions](#), [SpanColumnTypeOptions](#), [StartParagraph](#), [String](#), [StrokeStyle](#), [Swatch](#), [TextStrokeAlign](#), [WarichuAlignment](#)

Preferences:

[Preferences](#)

Hierarchy:

Superclass: [Preference](#)

Class: [FindGrepPreference](#)

Property Listing

Property	Type	Access	Description
allowArbitraryHyphenation	Boolean NothingEnum .NOTHING	read/write	If true, words unas with a hyphenatio dictionary can bre: next line on any cl Can return: Boolean NothingEnum enu
appliedCharacterStyle	String NothingEnum Canalsoaccept: CharacterStyle	read/write	The character style for or change to. C String or NothingE enumerator. Can a CharacterStyle .
appliedConditions	Array of Strings NothingEnum enumerator. Can also accept: Conditions .	read/write	The conditions to : or change to. Spec "nothing" enum fo an empty list for " [Unconditional]". (Array of Strings or NothingEnum enu Can also accept: A Conditions .
appliedFont	Font String NothingEnum .NOTHING	read/write	The font applied to FindGrepPreferenc specified as either object or the name family. Can return: String or NothingE enumerator.
appliedLanguage	String LanguageWithVendors NothingEnum Canalsoaccept: Language	read/write	The language to se change to. Can ret or NothingEnum e Can also accept: L: LanguageWithVen
appliedNumberingList	NumberingList String NothingEnum .NOTHING	read/write	The list to be part return: Numbering or NothingEnum e
appliedParagraphStyle	String NothingEnum Canalsoaccept: ParagraphStyle	read/write	The paragraph styl for or change to. C

Property	Type	Access	Description
			String or Nothing Enumerator. Can a
autoLeading	Real (range 0 - 500) NothingEnum.NOTHING	read/write	ParagraphStyle The percent of the to use for auto lea (Range: 0 to 500). Real or NothingEn enumerator.
autoTcy	ShortInteger NothingEnum.NOTHING	read/write	The number of hal characters at or be the characters aut run horizontally in text. Can return: S Integer or Nothing enumerator.
autoTcyIncludeRoman	Boolean NothingEnum.NOTHING	read/write	If true, auto tcy inc Roman characters. return: Boolean or NothingEnum enu
balanceRaggedLines	BalanceLineStyle BalanceLineStyle.FULLY_BALANCED BalanceLineStyle.NO_BALANCING BalanceLineStyle.PYRAMID_SHAPE BalanceLineStyle.VEE_SHAPE Boolean NothingEnum.NOTHING	read/write	If true or set to an enumeration value ragged lines. Note with a single-line t composer. Can ret Boolean, BalanceL enumerator or No enumerator.
baselineShift	Unit NothingEnum.NOTHING	read/write	The baseline shift : the text. Can retur NothingEnum enu
bulletChar	Bullet NothingEnum.NOTHING	readonly	Bullet character. C Bullet or NothingE enumerator.
bulletsAndNumberingListType	ListType ListType.BULLET_LIST ListType.NO_LIST ListType.NUMBERED_LIST NothingEnum.NOTHING	read/write	List type for bullet numbering. Can re ListType enumerat NothingEnum enu
bulletsCharacterStyle	CharacterStyle String NothingEnum.NOTHING	read/write	The character style used for the text a Can return: Charac String or NothingE enumerator.
bulletsTextAfter	String NothingEnum.NOTHING	read/write	The text after strin expression for bull return: String or NothingEnum enu
bunriKinshi	Boolean NothingEnum.NOTHING	read/write	If true, adds the do period (..), ellipse (. double hyphen (--) selected kinsoku s Valid only when a is in effect. Can ret Boolean or Nothin enumerator.
capitalization	Capitalization Capitalization.ALL_CAPS Capitalization.CAP_TO_SMALL_CAP Capitalization.LOWER_CASE Capitalization.NORMAL Capitalization.SMALL_CAPS NothingEnum.NOTHING	read/write	The capitalization : Can return: Capita enumerator or No enumerator.
characterAlignment	CharacterAlignment CharacterAlignment.ALIGN_BASELINE CharacterAlignment.ALIGN_EM_BOTTOM CharacterAlignment.ALIGN_EM_CENTER CharacterAlignment.ALIGN_EM_TOP CharacterAlignment.ALIGN_ICF_BOTTOM CharacterAlignment.ALIGN_ICF_TOP	read/write	The alignment of s characters to the li character in the lir return: CharacterA enumerator or No enumerator.

Property	Type	Access	Description
	NothingEnum.NOTHING		
characterDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION NothingEnum.NOTHING	read/write	The direction of the character. Can return: CharacterDirectionOptions enumerator or NothingEnum enumerator.
characterRotation	Real NothingEnum.NOTHING	read/write	The rotation angle (in degrees) of individual characters. Note: 1 rotation is counter-clockwise. Can return: Real or NothingEnum enumerator.
cjkGridTracking	Boolean NothingEnum.NOTHING	read/write	If true, uses grid tracking for non-Roman characters in CJK grids. Can return: Boolean or NothingEnum enumerator.
composer	String NothingEnum.NOTHING	read/write	The text composer used to compose the text. Can return: String or NothingEnum enumerator.
designAxes	Array of Reals NothingEnum.NOTHING	read/write	Value of Design Axes. Can return: Array of Real or NothingEnum enumerator.
diacriticPosition	DiacriticPositionOptions DiacriticPositionOptions.DEFAULT_POSITION DiacriticPositionOptions.LOOSE_POSITION DiacriticPositionOptions.MEDIUM_POSITION DiacriticPositionOptions.OPENTYPE_POSITION DiacriticPositionOptions.OPENTYPE_POSITION_FROM_BASELINE DiacriticPositionOptions.TIGHT_POSITION NothingEnum.NOTHING	read/write	Position of diacritics on characters. Can return: DiacriticPositionOptions enumerator or NothingEnum enumerator.
digitsType	DigitsTypeOptions DigitsTypeOptions.ARABIC_DIGITS DigitsTypeOptions.BENGALI_DIGITS DigitsTypeOptions.BURMESE_DIGITS DigitsTypeOptions.DEFAULT_DIGITS DigitsTypeOptions.DEVANAGARI_DIGITS DigitsTypeOptions.FARSI_DIGITS DigitsTypeOptions.FULL_FARSI_DIGITS DigitsTypeOptions.GUJARATI_DIGITS DigitsTypeOptions.GURMUKHI_DIGITS DigitsTypeOptions.HINDI_DIGITS DigitsTypeOptions.KANNADA_DIGITS DigitsTypeOptions.KHMER_DIGITS DigitsTypeOptions.LAO_DIGITS DigitsTypeOptions.MALAYALAM_DIGITS DigitsTypeOptions.NATIVE_DIGITS DigitsTypeOptions.ORIYA_DIGITS DigitsTypeOptions.TAMIL_DIGITS DigitsTypeOptions.TELUGU_DIGITS DigitsTypeOptions.THAI_DIGITS DigitsTypeOptions.TIBETAN_DIGITS NothingEnum.NOTHING	read/write	The digits type. Can return: DigitsTypeOptions enumerator or NothingEnum enumerator.
dropCapCharacters	ShortInteger(0-150) NothingEnum.NOTHING	read/write	The number of characters for drop cap. Can return: ShortInteger (0 - 150) or NothingEnum enumerator.
dropCapLines	ShortInteger(0-25) NothingEnum.NOTHING	read/write	The number of lines for drop cap. Can return: ShortInteger (0 - 25) or NothingEnum enumerator.
dropcapDetail	LongInteger NothingEnum.NOTHING	read/write	Details about the drop cap based on the glyph. 1 = left side bearing descenders. 0x100, 0x200, 0x400 for Japanese frame.

Property	Type	Access	Description
			return: Long Integer NothingEnum enumerator.
endJoin	OutlineJoin OutlineJoin.BEVEL_END_JOIN OutlineJoin.MITER_END_JOIN OutlineJoin.ROUND_END_JOIN NothingEnum.NOTHING	read/write	The stroke join type to the characters. Can return: OutlineJoin enumerator or NothingEnum enumerator.
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
fillColor	String NothingEnumCanalsoaccept:Swatch	read/write	The swatch (color, tint, or mixed ink), a fill color, to search for or change to. Can return: String or NothingEnum enumerator. Can also accept: Swatch
fillTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the fill color of the text. Can return: Real or NothingEnum enumerator. Can specify a tint percentage by a number in the range 0 to 100; to use the inherited value, use NothingEnum.NOTHING.
findWhat	String NothingEnum.NOTHING	read/write	The FindGrepPreference value to find. Can return: String or NothingEnum enumerator.
firstLineIndent	Unit NothingEnum.NOTHING	read/write	The amount to indent the first line. Can return: Unit or NothingEnum enumerator.
fontStyle	String NothingEnum.NOTHING	read/write	The name of the font style. Can return: String or NothingEnum enumerator.
glyphForm	AlternateGlyphForms AlternateGlyphForms.EXPERT_FORM AlternateGlyphForms.FULL_WIDTH_FORM AlternateGlyphForms.JIS04_FORM AlternateGlyphForms.JIS78_FORM AlternateGlyphForms.JIS83_FORM AlternateGlyphForms.JIS90_FORM AlternateGlyphForms.MONOSPACED_HALF_WIDTH_FORM AlternateGlyphForms.NLC_FORM AlternateGlyphForms.NONE AlternateGlyphForms.PROPORTIONAL_WIDTH_FORM AlternateGlyphForms.QUARTER_WIDTH_FORM AlternateGlyphForms.THIRD_WIDTH_FORM AlternateGlyphForms.TRADITIONAL_FORM NothingEnum.NOTHING	read/write	The glyph variant to use to substitute for standard glyphs. Can return: AlternateGlyphForms enumerator or NothingEnum enumerator.
gradientFillAngle	Real NothingEnum.NOTHING	read/write	The angle of a line applied to the fill color. (Range: -180 to 180 degrees). Can return: Real or NothingEnum enumerator.
gradientFillLength	Real NothingEnum.NOTHING	read/write	The length (for a linear gradient) or radius (for a radial gradient) applied to the fill color of the text. Can return: Real or NothingEnum enumerator.
gradientFillStart	Array of 2 Units NothingEnum.NOTHING	read/write	The starting point (x, y coordinates) of a gradient applied to the fill color of the text. Can return: Array of 2 Units in the format [x, y]. Can also accept: Array of 2 Units. Can return: Array of 2 Units or NothingEnum enumerator.
gradientStrokeAngle	Real NothingEnum.NOTHING	read/write	The angle of a line applied to the stroke color.

Property	Type	Access	Description
			text. (Range: -180 to 180 degrees) Can return: Real or NothingEnum enumerator.
gradientStrokeLength	Real NothingEnum.NOTHING	read/write	The length (for a linear gradient) or radius (for a radial gradient) of the stroke of the text. Can return: Real or NothingEnum enumerator.
gradientStrokeStart	Array of 2 Units NothingEnum.NOTHING	read/write	The starting point (x, y) of a gradient applied to the stroke of the text, in the format (x, y). return: Array of 2 Units NothingEnum enumerator.
gridAlignment	GridAlignment GridAlignment.ALIGN_BASELINE GridAlignment.ALIGN_EM_BOTTOM GridAlignment.ALIGN_EM_CENTER GridAlignment.ALIGN_EM_TOP GridAlignment.ALIGN_ICF_BOTTOM GridAlignment.ALIGN_ICF_TOP GridAlignment.NONE NothingEnum.NOTHING	read/write	The alignment to the grid or baseline grid. return: GridAlignment enumerator or NothingEnum enumerator.
gridGyoudori	ShortInteger NothingEnum.NOTHING	read/write	The manual gyoudori (manual line spacing). Can return: Short Integer or NothingEnum enumerator.
horizontalScale	Real NothingEnum.NOTHING	read/write	The horizontal scale factor applied to the FindGrepProcess. Can return: Real or NothingEnum enumerator.
hyphenateAcrossColumns	Boolean NothingEnum.NOTHING	read/write	If true, allows the text column to be hyphenated. Can return: Boolean or NothingEnum enumerator.
hyphenateLastWord	Boolean NothingEnum.NOTHING	read/write	If true, allows hyphenation of the last word in a paragraph. Note: Valid only when hyphenation is true. return: Boolean or NothingEnum enumerator.
ignoreEdgeAlignment	Boolean NothingEnum.NOTHING	read/write	If true, ignores optimal alignment for the paragraph. Can return: Boolean or NothingEnum enumerator.
isValid	Boolean	readonly	Returns true if the specifier resolves to objects.
jidori	ShortInteger NothingEnum.NOTHING	read/write	The number of jidori (line spacing) in which to arrange the text. Can return: Short Integer or NothingEnum enumerator.
justification	Justification Justification.AWAY_FROM_BINDING_SIDE Justification.CENTER_ALIGN Justification.CENTER_JUSTIFIED Justification.FULLY_JUSTIFIED Justification.LEFT_ALIGN Justification.LEFT_JUSTIFIED Justification.RIGHT_ALIGN Justification.RIGHT_JUSTIFIED Justification.TO_BINDING_SIDE NothingEnum.NOTHING	read/write	The paragraph alignment. Can return: Justification enumerator or NothingEnum enumerator.
kashidas	KashidasOptions KashidasOptions.DEFAULT_KASHIDAS KashidasOptions.KASHIDAS_OFF NothingEnum.NOTHING	read/write	Use of Kashidas for justification. Can return: KashidasOptions enumerator or NothingEnum enumerator.

Property	Type	Access	Description
keepAllLinesTogether	Boolean NothingEnum.NOTHING	read/write	If true, keeps all lines of a paragraph together. This allows paragraphs to span across pages or columns. Can return: Boolean or NothingEnum enumerator.
keepFirstLines	ShortInteger(1-50) NothingEnum.NOTHING	read/write	The minimum number of lines to keep together at the beginning of a paragraph before a page break. Can return: ShortInteger (1 - 50) or NothingEnum enumerator.
keepLastLines	ShortInteger(1-50) NothingEnum.NOTHING	read/write	The minimum number of lines to keep together at the end of a paragraph after a page break. Can return: ShortInteger (1 - 50) or NothingEnum enumerator.
keepLinesTogether	Boolean NothingEnum.NOTHING	read/write	If true, keeps a specified number of lines together when the paragraph wraps across columns or frames. Can return: Boolean or NothingEnum enumerator.
keepRuleAboveInFrame	Boolean NothingEnum.NOTHING	read/write	If true, forces the top of the paragraph to remain within the frame bounds. Valid only when rule is true. Can return: Boolean or NothingEnum enumerator.
keepWithNext	ShortInteger(0-5) NothingEnum.NOTHING	read/write	The minimum number of lines to keep with the following paragraph. Can return: ShortInteger (0 - 5) or NothingEnum enumerator.
keepWithPrevious	Boolean NothingEnum.NOTHING	read/write	If the first line in the paragraph should be kept with the last line of the previous paragraph. Can return: Boolean or NothingEnum enumerator.
kentenAlignment	KentenAlignment KentenAlignment.ALIGN_KENTEN_CENTER KentenAlignment.ALIGN_KENTEN_LEFT NothingEnum.NOTHING	read/write	The alignment of kenten characters relative to the parent characters. Can return: KentenAlignment enumerator or NothingEnum enumerator.
kentenCharacterSet	KentenCharacterSet KentenCharacterSet.CHARACTER_INPUT KentenCharacterSet.JIS KentenCharacterSet.KUTEN KentenCharacterSet.SHIFT_JIS KentenCharacterSet.UNICODE NothingEnum.NOTHING	read/write	The character set used for the custom kenten. Note: Valid only when kenten kind is custom. Can return: KentenCharacterSet enumerator or NothingEnum enumerator.
kentenCustomCharacter	String NothingEnum.NOTHING	read/write	The character used for kenten. Note: Valid only when kenten kind is custom. Can return: String or NothingEnum enumerator.
kentenFillColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) used for the fill of kenten characters. Can return: Swatch or NothingEnum enumerator.
kentenFont	Font String NothingEnum.NOTHING	read/write	The font to use for kenten characters. Can return: String or NothingEnum enumerator.

Property	Type	Access	Description
kentenFontSize	Real NothingEnum.NOTHING	read/write	The size (in points) of the kenten characters. Can return NothingEnum.NOTHING.
kentenFontStyle	String NothingEnum.NOTHING	read/write	The font style of the kenten characters. Can return NothingEnum.NOTHING.
kentenKind	KentenCharacter KentenCharacter.CUSTOM KentenCharacter.KENTEN_BLACK_CIRCLE KentenCharacter.KENTEN_BLACK_TRIANGLE KentenCharacter.KENTEN_BULLSEYE KentenCharacter.KENTEN_FISHEYE KentenCharacter.KENTEN_SESAME_DOT KentenCharacter.KENTEN_SMALL_BLACK_CIRCLE KentenCharacter.KENTEN_SMALL_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_SESAME_DOT KentenCharacter.KENTEN_WHITE_TRIANGLE KentenCharacter.NONE NothingEnum.NOTHING	read/write	The style of the kenten characters. Can return KentenCharacter.CUSTOM or NothingEnum.NOTHING.
kentenOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of overprinting the kenten fill. Can return AdornmentOverprint.OVERPRINT_ON enumerator or NothingEnum.NOTHING.
kentenOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of overprinting the kenten stroke. Can return AdornmentOverprint.OVERPRINT_ON enumerator or NothingEnum.NOTHING.
kentenPlacement	Real NothingEnum.NOTHING	read/write	The distance between the kenten characters and the parent characters. Can return NothingEnum.NOTHING.
kentenPosition	RubyKentenPosition RubyKentenPosition.ABOVE_RIGHT RubyKentenPosition.BELOW_LEFT NothingEnum.NOTHING	read/write	The kenten position relative to the parent characters. Can return RubyKentenPosition.ABOVE_RIGHT enumerator or NothingEnum.NOTHING.
kentenStrokeColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the stroke of the kenten characters. Can return Swatch, String or NothingEnum.NOTHING.
kentenStrokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The stroke tint (as a percentage) of the kenten characters. (Range 0 to 100). Can return Real or NothingEnum.NOTHING.
kentenTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The fill tint (as a percentage) of the kenten characters. (Range 0 to 100). Can return Real or NothingEnum.NOTHING.
kentenWeight	Real NothingEnum.NOTHING	read/write	The stroke weight of the kenten characters. Can return Real or NothingEnum.NOTHING.
kentenXScale	Real NothingEnum.NOTHING	read/write	The horizontal size of the kenten characters as a percentage of the original size. Can return Real or NothingEnum.NOTHING.
kentenYScale	Real NothingEnum.NOTHING	read/write	The vertical size of the kenten characters as a percentage of the original size. Can return Real or NothingEnum.NOTHING.

Property	Type	Access	Description
kernelingMethod	String NothingEnum.NOTHING	read/write	The type of pair ke return: String or NothingEnum enu
kernelingValue	Real NothingEnum.NOTHING	read/write	The amount of spa or remove between characters, specific thousands of an ei return: Real or No enumerator.
keyboardDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION NothingEnum.NOTHING	read/write	The keyboard dire character. Can rett CharacterDirector enumerator or No enumerator.
kinsokuHangType	KinsokuHangTypes KinsokuHangTypes.KINSOKU_HANG_FORCE KinsokuHangTypes.KINSOKU_HANG_REGULAR KinsokuHangTypes.NONE NothingEnum.NOTHING	read/write	The type of hangir punctuation to all Valid only when a is in effect. Can ret KinsokuHangTypes enumerator or No enumerator.
kinsokuSet	KinsokuSet KinsokuSet.HARD_KINSOKU KinsokuSet.KOREAN_KINSOKU KinsokuSet.NOTHING KinsokuSet.SIMPLIFIED_CHINESE_KINSOKU KinsokuSet.SOFT_KINSOKU KinsokuSet.TRADITIONAL_CHINESE_KINSOKU KinsokuTable String NothingEnum.NOTHING	read/write	The kinsoku set th determines legitir breaks. Can return KinsokuTable, Kins enumerator, String NothingEnum enu
kinsokuType	KinsokuType KinsokuType.KINSOKU_PRIORITIZE_ADJUSTMENT_AMOUNT KinsokuType.KINSOKU_PUSH_IN_FIRST KinsokuType.KINSOKU_PUSH_OUT_FIRST KinsokuType.KINSOKU_PUSH_OUT_ONLY NothingEnum.NOTHING	read/write	The type of kinsok processing for pre kinsoku characters beginning or endir Note: Valid only w kinsoku set is defir return: KinsokuTyp enumerator or No enumerator.
lastLineIndent	Unit NothingEnum.NOTHING	read/write	The amount to ind line in the paragra return: Unit or No enumerator.
leading	Leading Leading.AUTO Unit NothingEnum.NOTHING	read/write	The leading applie text. Can return: U Leading enumerat NothingEnum enu
leadingAki	Real NothingEnum.NOTHING	read/write	The amount of spa each character. Ca Real or NothingEn enumerator.
leadingModel	LeadingModel LeadingModel.LEADING_MODEL_AKI_ABOVE LeadingModel.LEADING_MODEL_AKI_BELOW LeadingModel.LEADING_MODEL_CENTER LeadingModel.LEADING_MODEL_CENTER_DOWN LeadingModel.LEADING_MODEL_ROMAN NothingEnum.NOTHING	read/write	The point from wh is measured from l Can return: Leadin enumerator or No enumerator.
leftIndent	Unit NothingEnum.NOTHING	read/write	The width of the le Can return: Unit o NothingEnum enu
ligatures	Boolean NothingEnum.NOTHING	read/write	If true, replaces sp character combina fi, fi) with ligatur Can return: Boolea NothingEnum enu

Property	Type	Access	Description
miterLimit	Real(0-1000) NothingEnum.NOTHING	read/write	The limit of the ratio of the width to miter length. If a miter (pointed) join becomes a bevel (sloped off) join. Can return 1000) or NothingEnum enumerator.
mojikumi	MojikumiTable MojikumiTableDefaults MojikumiTableDefaults.LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.NOTHING MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.SIMP_CHINESE_DEFAULT MojikumiTableDefaults.TRAD_CHINESE_DEFAULT String NothingEnum.NOTHING	read/write	The mojikumi table information, see the table defaults. Can return MojikumiTable, String MojikumiTableDefaults enumerator or NothingEnum enumerator.
noBreak	Boolean NothingEnum.NOTHING	read/write	If true, keeps the text on the same line. . Can return Boolean or NothingEnum enumerator.
numberingApplyRestartPolicy	Boolean NothingEnum.NOTHING	read/write	If true, apply the numbering restart policy. Can return Boolean or NothingEnum enumerator.
numberingCharacterStyle	CharacterStyle String NothingEnum.NOTHING	read/write	The character style used for the numbering. Can return: CharacterStyle, String or NothingEnum enumerator.
numberingContinue	Boolean NothingEnum.NOTHING	read/write	Continue the numbering at this level. Can return Boolean or NothingEnum enumerator.
numberingExpression	String NothingEnum.NOTHING	read/write	The number string for numbering. Can return String or NothingEnum enumerator.
numberingFormat	NumberingStyle NumberingStyle.ARABIC NumberingStyle.ARABIC_ABJAD NumberingStyle.ARABIC_ALIF_BA_TAH NumberingStyle.DOUBLE_LEADING_ZEROS NumberingStyle.FORMAT_NONE NumberingStyle.HEBREW_BIBLICAL NumberingStyle.HEBREW_NON_STANDARD NumberingStyle.KANJI NumberingStyle.KATAKANA_MODERN NumberingStyle.KATAKANA_TRADITIONAL NumberingStyle.LOWER_LETTERS NumberingStyle.LOWER_ROMAN NumberingStyle.SINGLE_LEADING_ZEROS NumberingStyle.TRIPLE_LEADING_ZEROS NumberingStyle.UPPER_LETTERS NumberingStyle.UPPER_ROMAN String NothingEnum.NOTHING	read/write	Numbering format. Can return: NumberingStyle enumerator, String or NothingEnum enumerator.

Property	Type	Access	Description
numberingLevel	LongInteger NothingEnum.NOTHING	read/write	The level of the pa Can return: Long I NothingEnum enu
numberingRestartPolicies	NumberingRestartPolicy NothingEnum.NOTHING	readonly	Numbering restart Can return: NumberingRestart NothingEnum enu
numberingStartAt	LongInteger NothingEnum.NOTHING	read/write	Determines startin in a numbered list. return: Long Integ NothingEnum enu
otfContextualAlternate	Boolean NothingEnum.NOTHING	read/write	If true, uses conte alternate forms in fonts. Can return: NothingEnum enu
otfDiscretionaryLigature	Boolean NothingEnum.NOTHING	read/write	If true, uses discre ligatures in OpenT Can return: Boolea NothingEnum enu
otfFigureStyle	OTFFigureStyle OTFFigureStyle.DEFAULT_VALUE OTFFigureStyle.PROPORTIONAL_LINING OTFFigureStyle.PROPORTIONAL_OLDSTYLE OTFFigureStyle.TABULAR_LINING OTFFigureStyle.TABULAR_OLDSTYLE NothingEnum.NOTHING	read/write	The figure style in fonts. Can return: OTFFigureStyle en or NothingEnum e
otfFraction	Boolean NothingEnum.NOTHING	read/write	If true, uses fracti OpenType fonts. C Boolean or Nothin enumerator.
otfHVKana	Boolean NothingEnum.NOTHING	read/write	If true, switches hi fonts, which have glyphs for horizont vertical. . Can retu or NothingEnum e
otfHistorical	Boolean NothingEnum.NOTHING	read/write	If true, use historic OpenType fonts. C Boolean or Nothin enumerator.
otfJustificationAlternate	Boolean NothingEnum.NOTHING	read/write	If true, use alterna justification forms OpenType fonts. C Boolean or Nothin enumerator.
otfLocale	Boolean NothingEnum.NOTHING	read/write	If true, uses localiz OpenType fonts. C Boolean or Nothin enumerator.
otfMark	Boolean NothingEnum.NOTHING	read/write	If true, uses mark in OpenType fonts return: Boolean or NothingEnum enu
otfOrdinal	Boolean NothingEnum.NOTHING	read/write	If true, uses ordin OpenType fonts. C Boolean or Nothin enumerator.
otfOverlapSwash	Boolean NothingEnum.NOTHING	read/write	If true, use overlap swash forms in Op fonts. Can return: NothingEnum enu
otfProportionalMetrics	Boolean NothingEnum.NOTHING	read/write	If true, kerns accor proportional CJK n OpenType fonts. C Boolean or Nothin enumerator.

Property	Type	Access	Description
otfRomanItalics	Boolean NothingEnum.NOTHING	read/write	If true, applies italic width alphanumeric return: Boolean or NothingEnum enumerator.
otfSlashedZero	Boolean NothingEnum.NOTHING	read/write	If true, use a slash in OpenType fonts return: Boolean or NothingEnum enumerator.
otfStretchedAlternate	Boolean NothingEnum.NOTHING	read/write	If true, use stretch alternate forms in fonts. Can return: NothingEnum enumerator.
otfStylisticAlternate	Boolean NothingEnum.NOTHING	read/write	If true, use stylistic forms in OpenType fonts return: Boolean or NothingEnum enumerator.
otfStylisticSets	LongInteger NothingEnum.NOTHING	read/write	The stylistic sets to OpenType fonts. Can return: Long Integer or NothingEnum enumerator.
otfSwash	Boolean NothingEnum.NOTHING	read/write	If true, uses swash OpenType fonts. Can return: Boolean or NothingEnum enumerator.
otfTitling	Boolean NothingEnum.NOTHING	read/write	If true, uses titling OpenType fonts. Can return: Boolean or NothingEnum enumerator.
overprintFill	Boolean NothingEnum.NOTHING	read/write	If true, the fill color characters will overprint return: Boolean or NothingEnum enumerator.
overprintStroke	Boolean NothingEnum.NOTHING	read/write	If true, the stroke color characters will overprint return: Boolean or NothingEnum enumerator.
paragraphDirection	ParagraphDirectionOptions ParagraphDirectionOptions.LEFT_TO_RIGHT_DIRECTION ParagraphDirectionOptions.RIGHT_TO_LEFT_DIRECTION NothingEnum.NOTHING	read/write	Paragraph direction return: ParagraphDirectionOptions enumerator or NothingEnum enumerator.
paragraphGyoudori	Boolean NothingEnum.NOTHING	read/write	If true, the gyoudori applies to the entire paragraph. If false, gyoudori mode applies to each line in the paragraph. Can return: Boolean or NothingEnum enumerator.
paragraphJustification	ParagraphJustificationOptions ParagraphJustificationOptions.ARABIC_JUSTIFICATION ParagraphJustificationOptions.DEFAULT_JUSTIFICATION ParagraphJustificationOptions.NASKH_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION_FRAC ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION_FRAC NothingEnum.NOTHING	read/write	Paragraph justification return: ParagraphJustificationOptions enumerator or NothingEnum enumerator.
paragraphKashidaWidth	Real NothingEnum.NOTHING	read/write	Paragraph kashida width. 0 is none, 1 is short, 2 is medium, 3 is long. Can return: Real or NothingEnum enumerator.
parent	Application	readonly	The parent of the FindGrepPreferences (Application).
pointSize	Unit NothingEnum.NOTHING	read/write	The text size. Can return: Unit or NothingEnum enumerator.

Property	Type	Access	Description
position	Position Position.NORMAL Position.OT_DENOMINATOR Position.OT_NUMERATOR Position.OT_SUBSCRIPT Position.OT_SUPERSCRIPT Position.SUBSCRIPT Position.SUPERSCRIPT NothingEnum.NOTHING	read/write	The text position relative to the baseline. Can return: Position enumerator or NothingEnum enumerator.
positionalForm	PositionalForms PositionalForms.CALCULATE PositionalForms.FINAL PositionalForms.INITIAL PositionalForms.ISOLATED PositionalForms.MEDIAL PositionalForms.NONE NothingEnum.NOTHING	read/write	The OpenType positional form. Can return: PositionalForms enumerator or NothingEnum enumerator.
preferences	Preferences <i>Preference</i>	readonly	A collection of preference objects.
properties	Object	read/write	A property that allows setting all of several properties at the same time.
rensuuji	Boolean NothingEnum.NOTHING	read/write	If true, disallows line breaks in numbers. If false, allows a break between digits in multi-digit numbers. Can return: Boolean or NothingEnum enumerator.
rightIndent	Unit NothingEnum.NOTHING	read/write	The width of the right margin. Can return: Unit or NothingEnum enumerator.
rotateSingleByteCharacters	Boolean NothingEnum.NOTHING	read/write	If true, rotates Roman characters in vertical text. Can return: Boolean or NothingEnum enumerator.
rubyAlignment	RubyAlignments RubyAlignments.RUBY_1_AKI RubyAlignments.RUBY_CENTER RubyAlignments.RUBY_EQUAL_AKI RubyAlignments.RUBY_FULL_JUSTIFY RubyAlignments.RUBY_JIS RubyAlignments.RUBY_LEFT RubyAlignments.RUBY_RIGHT NothingEnum.NOTHING	read/write	The ruby alignment. Can return: RubyAlignments enumerator or NothingEnum enumerator.
rubyAutoAlign	Boolean NothingEnum.NOTHING	read/write	If true, auto-aligns ruby text. Can return: Boolean or NothingEnum enumerator.
rubyAutoScaling	Boolean NothingEnum.NOTHING	read/write	If true, automatically scales ruby text to the specified percentage of parent text size. Can return: Boolean or NothingEnum enumerator.
rubyAutoTcyAutoScale	Boolean NothingEnum.NOTHING	read/write	If true, automatically scales glyphs in auto tcy (auto yoko) in ruby to fit. Can return: Boolean or NothingEnum enumerator.
rubyAutoTcyDigits	ShortInteger NothingEnum.NOTHING	read/write	The number of digits included in auto tcy (auto chuu-yoko) in ruby. Can return: Short Integer or NothingEnum enumerator.
rubyAutoTcyIncludeRoman	Boolean NothingEnum.NOTHING	read/write	If true, includes Roman characters in auto tcy (auto chuu-yoko) in ruby.

Property	Type	Access	Description
			return: Boolean or NothingEnum enumerator.
rubyFill	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the fill of ruby characters. Can return: Swatch or NothingEnum enumerator.
rubyFont	Font String NothingEnum.NOTHING	read/write	The font applied to ruby characters. Can return: String or NothingEnum enumerator.
rubyFontSize	Real NothingEnum.NOTHING	read/write	The size (in points) of ruby characters. Can return: Real or NothingEnum enumerator.
rubyFontStyle	String NothingEnum.NOTHING	read/write	The font style of ruby characters. Can return: String or NothingEnum enumerator.
rubyOpenTypePro	Boolean NothingEnum.NOTHING	read/write	If true, uses OpenType fonts for ruby. Can return: Boolean or NothingEnum enumerator.
rubyOverhang	Boolean NothingEnum.NOTHING	read/write	If true, constrains ruby overhang to the specified amount. For information on specifying an amount, see the ruby parent overhang property. Can return: Boolean or NothingEnum enumerator.
rubyOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of overprinting the ruby fill. Can return: AdornmentOverprint enumerator or NothingEnum enumerator.
rubyOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON NothingEnum.NOTHING	read/write	The method of overprinting the ruby stroke. Can return: AdornmentOverprint enumerator or NothingEnum enumerator.
rubyParentOverhangAmount	RubyOverhang RubyOverhang.NONE RubyOverhang.RUBY_OVERHANG_HALF_CHAR RubyOverhang.RUBY_OVERHANG_HALF_RUBY RubyOverhang.RUBY_OVERHANG_NO_LIMIT RubyOverhang.RUBY_OVERHANG_ONE_CHAR RubyOverhang.RUBY_OVERHANG_ONE_RUBY NothingEnum.NOTHING	read/write	The amount by which ruby characters can overhang parent text. Can return: RubyOverhang enumerator or NothingEnum enumerator.
rubyParentScalingPercent	Real NothingEnum.NOTHING	read/write	The amount (as a percentage) to scale parent text size to the ruby text size. Can return: Real or NothingEnum enumerator.
rubyParentSpacing	RubyParentSpacing RubyParentSpacing.RUBY_PARENT_121_AKI RubyParentSpacing.RUBY_PARENT_BOTH_SIDES RubyParentSpacing.RUBY_PARENT_EQUAL_AKI RubyParentSpacing.RUBY_PARENT_FULL_JUSTIFY RubyParentSpacing.RUBY_PARENT_NO_ADJUSTMENT NothingEnum.NOTHING	read/write	The ruby spacing relative to the parent text. Can return: RubyParentSpacing enumerator or NothingEnum enumerator.
rubyPosition	RubyKantenPosition RubyKantenPosition.ABOVE_RIGHT RubyKantenPosition.BELOW_LEFT NothingEnum.NOTHING	read/write	The position of ruby characters relative to parent text. Can return: RubyKantenPosition enumerator or NothingEnum enumerator.

Property	Type	Access	Description
rubyStroke	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) the stroke of ruby Can return: Swatch NothingEnum enu
rubyStrokeTint	Real NothingEnum.NOTHING	read/write	The stroke tint (as percentage) of rub characters. Can rel or NothingEnum e
rubyTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a perce the ruby fill color. to 100). Can return NothingEnum enu
rubyType	RubyTypes RubyTypes.GROUP_RUBY RubyTypes.PER_CHARACTER_RUBY NothingEnum.NOTHING	read/write	The ruby type. Can RubyTypes enum NothingEnum enu
rubyWeight	Real NothingEnum.NOTHING	read/write	The stroke weight of ruby characters return: Real or No enumerator.
rubyXOffset	Real NothingEnum.NOTHING	read/write	The amount of hor space between rub parent characters. return: Real or No enumerator.
rubyXScale	Real NothingEnum.NOTHING	read/write	The horizontal size characters, specific percent of the orig Can return: Real or NothingEnum enu
rubyYOffset	Real NothingEnum.NOTHING	read/write	The amount of ver between ruby and characters. Can rel or NothingEnum e
rubyYScale	Real NothingEnum.NOTHING	read/write	The vertical size of characters, specific percent of the orig Can return: Real or NothingEnum enu
sameParaStyleSpacing	Spacing Spacing.SETIGNORE Unit NothingEnum.NOTHING	read/write	The space between paragraphs using s Can return: Unit, S enumerator or No enumerator.
scaleAffectsLineHeight	Boolean NothingEnum.NOTHING	read/write	If true, the line cha when characters a Can return: Boole NothingEnum enu
shataiAdjustRotation	Boolean NothingEnum.NOTHING	read/write	If true, applies sha rotation. Can retur or NothingEnum e
shataiAdjustTsume	Boolean NothingEnum.NOTHING	read/write	If true, adjusts sha Can return: Boole NothingEnum enu
shataiDegreeAngle	Real NothingEnum.NOTHING	read/write	The shatai lens ang degrees). Can retu NothingEnum enu
shataiMagnification	Real NothingEnum.NOTHING	read/write	The amount (as a percentage) of sha obliquing to apply. return: Real or No enumerator.
singleWordJustification	SingleWordJustification SingleWordJustification.CENTER_ALIGN SingleWordJustification.FULLY_JUSTIFIED	read/write	The alignment to u that contain a sing Can return:

Property	Type	Access	Description
	SingleWordJustification.LEFT_ALIGN SingleWordJustification.RIGHT_ALIGN		SingleWordJustification enumerator or NothingEnum enumerator.
skew	NothingEnum.NOTHING Real NothingEnum.NOTHING	read/write	The skew angle of the paragraph. Can return: Real or NothingEnum enumerator.
spaceAfter	Unit NothingEnum.NOTHING	read/write	The height of the space below. Can return: Unit or NothingEnum enumerator.
spaceBefore	Unit NothingEnum.NOTHING	read/write	The height of the space above. Can return: Unit or NothingEnum enumerator.
spanColumnMinSpaceAfter	Unit NothingEnum.NOTHING	read/write	The minimum space between spans or a split column. Can return: Unit or NothingEnum enumerator.
spanColumnMinSpaceBefore	Unit NothingEnum.NOTHING	read/write	The minimum space between spans or a split column. Can return: Unit or NothingEnum enumerator.
spanColumnType	SpanColumnTypeOptions SpanColumnTypeOptions.SINGLE_COLUMN SpanColumnTypeOptions.SPAN_COLUMNS SpanColumnTypeOptions.SPLIT_COLUMNS NothingEnum.NOTHING	read/write	Whether a paragraph should be a single column, span columns or split columns. Can return: SpanColumnTypeOptions enumerator or NothingEnum enumerator.
spanSplitColumnCount	ShortInteger(1-40) SpanColumnCountOptions SpanColumnCountOptions.ALL NothingEnum.NOTHING	read/write	The number of columns a paragraph spans or the number of split columns. Can return: Short Integer or SpanColumnCountOptions enumerator or NothingEnum enumerator.
splitColumnInsideGutter	Unit NothingEnum.NOTHING	read/write	The inside gutter if the paragraph splits columns. Can return: Unit or NothingEnum enumerator.
splitColumnOutsideGutter	Unit NothingEnum.NOTHING	read/write	The outside gutter if the paragraph splits columns. Can return: Unit or NothingEnum enumerator.
startParagraph	StartParagraph StartParagraph.ANYWHERE StartParagraph.NEXT_COLUMN StartParagraph.NEXT_EVEN_PAGE StartParagraph.NEXT_FRAME StartParagraph.NEXT_ODD_PAGE StartParagraph.NEXT_PAGE NothingEnum.NOTHING	read/write	The location at which the paragraph starts. Can return: StartParagraph enumerator or NothingEnum enumerator.
strikeThroughColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the strikethrough stroke. Can return: Swatch, String or NothingEnum enumerator.
strikeThroughGapColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the gap of the strikethrough stroke. Can return: String or NothingEnum enumerator.
strikeThroughGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color of the strikethrough stroke overprints the background. Note: Vector graphics do not support strike through type. Can return: Boolean or NothingEnum enumerator.

Property	Type	Access	Description
strikeThroughGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the strikethrough stroke color. (Range: 0 to 100). Valid when strike through type is not solid. Can return: Real or NothingEnum enumerator.
strikeThroughOffset	Unit NothingEnum.NOTHING	read/write	The amount by which to offset the strikethrough stroke from the text. Can return: Unit or NothingEnum enumerator.
strikeThroughOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the strikethrough stroke will overprint the text. Can return: Boolean or NothingEnum enumerator.
strikeThroughTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the strikethrough stroke color. (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
strikeThroughType	String StrokeStyle NothingEnum.NOTHING	read/write	The stroke type of the strikethrough stroke. Can return: StrokeStyle or NothingEnum enumerator.
strikeThroughWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the strikethrough stroke. Can return: Unit or NothingEnum enumerator.
strikeThrough	Boolean NothingEnum.NOTHING	read/write	If true, draws a strikethrough line through the text. Can return: Boolean or NothingEnum enumerator.
strokeAlignment	TextStrokeAlign TextStrokeAlign.CENTER_ALIGNMENT TextStrokeAlign.OUTSIDE_ALIGNMENT NothingEnum.NOTHING	read/write	The stroke alignment of the text. Can return: TextStrokeAlign enumerator or NothingEnum enumerator.
strokeColor	String NothingEnum.CanAlsoAccept:Swatch	read/write	The swatch (color, tint, or mixed ink), a stroke color, to which the text can change to. Can return: String or NothingEnum enumerator. Can also accept: Swatch.
strokeTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the stroke color of the text. Can return: Real or NothingEnum enumerator. FindGrepPreferences specify a tint percentage; a number in the range 0 to 100; to use the inherited value, 100; to use the overridden value, 0. Can return: Real or NothingEnum enumerator.
strokeWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the text. Can return: Unit or NothingEnum enumerator.
tatechuyoko	Boolean NothingEnum.NOTHING	read/write	If true, makes the text horizontal in vertical writing. Can return: Boolean or NothingEnum enumerator.
tatechuyokoXOffset	Real NothingEnum.NOTHING	read/write	The horizontal offset of the text. Can return: Real or NothingEnum enumerator.
tatechuyokoYOffset	Real NothingEnum.NOTHING	read/write	The vertical offset of the text. Can return: Real or NothingEnum enumerator.

Property	Type	Access	Description
tracking	Real NothingEnum.NOTHING	read/write	vertical text. Can return: Real or NothingEnum enumerator.
trailingAki	Real NothingEnum.NOTHING	read/write	The amount by which each character is loosened or tightened, specified in terms of an em. Can return: Real or NothingEnum enumerator.
treatIdeographicSpaceAsSpace	Boolean NothingEnum.NOTHING	read/write	If true, ideographic spaces will not wrap to the next line like text characters. Can return: Boolean or NothingEnum enumerator.
tsume	Real NothingEnum.NOTHING	read/write	The amount of horizontal space each character compresses. Can return: Real or NothingEnum enumerator.
underline	Boolean NothingEnum.NOTHING	read/write	If true, underlines the text. Can return: Boolean or NothingEnum enumerator.
underlineColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the underline stroke. Can return: Swatch, String, or NothingEnum enumerator.
underlineGapColor	String Swatch NothingEnum.NOTHING	read/write	The swatch (color, tint, or mixed ink) of the gap of the underline stroke. Note: Valid only when underline type is not solid. Can return: Swatch, String, or NothingEnum enumerator.
underlineGapOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the gap color of the underline stroke will overprint the text. Can return: Boolean or NothingEnum enumerator.
underlineGapTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The tint (as a percentage) of the gap color of the underline stroke. (Range: 0 to 100). Note: Valid when underline type is not solid. Can return: Real or NothingEnum enumerator.
underlineOffset	Unit NothingEnum.NOTHING	read/write	The amount by which the underline text is offset from the baseline. Can return: Unit or NothingEnum enumerator.
underlineOverprint	Boolean NothingEnum.NOTHING	read/write	If true, the underline color will overprint the text. Can return: Boolean or NothingEnum enumerator.
underlineTint	Real (range 0 - 100) NothingEnum.NOTHING	read/write	The underline stroke tint (as a percentage). (Range: 0 to 100). Can return: Real or NothingEnum enumerator.
underlineType	String StrokeStyle NothingEnum.NOTHING	read/write	The stroke type of the underline stroke. Can return: StrokeStyle, String, or NothingEnum enumerator.
underlineWeight	Unit NothingEnum.NOTHING	read/write	The stroke weight of the underline stroke. Can return: Unit or NothingEnum enumerator.

Property	Type	Access	Description
verticalScale	Real NothingEnum.NOTHING	read/write	The vertical scaling of the FindGrepPreference return: Real or NothingEnum enumerator.
warichu	Boolean NothingEnum.NOTHING	read/write	If true, turns on warichu return: Boolean or NothingEnum enumerator.
warichuAlignment	WarichuAlignment WarichuAlignment.AUTO WarichuAlignment.CENTER_ALIGN WarichuAlignment.CENTER_JUSTIFIED WarichuAlignment.FULLY_JUSTIFIED WarichuAlignment.LEFT_ALIGN WarichuAlignment.LEFT_JUSTIFIED WarichuAlignment.RIGHT_ALIGN WarichuAlignment.RIGHT_JUSTIFIED NothingEnum.NOTHING	read/write	The warichu alignment return: WarichuAlignment enumerator or NothingEnum enumerator.
warichuCharsAfterBreak	ShortInteger NothingEnum.NOTHING	read/write	The minimum number of characters allowed before a line break. Can return: Short Integer or NothingEnum enumerator.
warichuCharsBeforeBreak	ShortInteger NothingEnum.NOTHING	read/write	The minimum number of characters allowed after a line break. Can return: Short Integer or NothingEnum enumerator.
warichuLineSpacing	Real NothingEnum.NOTHING	read/write	The gap between lines of warichu characters return: Real or NothingEnum enumerator.
warichuLines	ShortInteger NothingEnum.NOTHING	read/write	The number of lines of warichu within a standard normal line. Can return: Short Integer or NothingEnum enumerator.
warichuSize	Real NothingEnum.NOTHING	read/write	The amount (as a percentage) to scale the text size to determine the warichu size. Can return: Real or NothingEnum enumerator.
xOffsetDiacritic	Real NothingEnum.NOTHING	read/write	The x (horizontal) offset of the diacritic adjustment return: Real or NothingEnum enumerator.
yOffsetDiacritic	Real NothingEnum.NOTHING	read/write	The y (vertical) offset of the diacritic adjustment return: Real or NothingEnum enumerator.

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

FindGrepPreference **getElements** ()

Resolves the object specifier, creating an array of object references.

Boolean **isNthDesignAxisHidden** (nthAxisIndex:*Number*)

If true, Nth design axis of variable font is hidden.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **setNthDesignAxis** (nthAxisIndex:*Number*, nthAxisValue:*Number*)

Set Nth design axis of a variable font.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.
nthAxisValue	Number	Value of nth design axis.

String **toSource** ()

Generates a string which, if executed, will return the FindGrepPreference.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Application.findGrepPreferences

Bullet.parent

Event.parent

EventListener.parent

MutationEvent.parent

NumberingRestartPolicy.parent

Preference.parent

Return

FindGrepPreference.getElements()
