

Font

A font.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [checkOpenTypeFeature](#), [createSubsetFont](#), [getElements](#), [removeEventListener](#), [toSource](#), [toSpecifier](#)

Objects:

[Boolean](#), [EventListeners](#), [Events](#), [FontStatus](#), [FontTypes](#), [Number](#), [Object](#), [String](#),

Property Listing

Property	Type	Access	Description
allowEditableEmbedding	Boolean	readonly	If true, the font can be embedded.
allowOutlines	Boolean	readonly	If true, the font can be converted to outlines.
allowPDFEmbedding	Boolean	readonly	If true, the font can be embedded in a PDF document.
allowPrinting	Boolean	readonly	If true, the can font be printed.
designAxesName	Array of String	readonly	The name of design axes in variable font.
designAxesRange	Array of Arrays of 2 Reals.	readonly	Range of design axes in variable font. Can return: Array of Arrays of 2 Reals.
designAxesValues	Array of Number	readonly	Value of design axes in variable font.
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
fontFamily	String	readonly	The name of the font family
fontStyleName	String	readonly	The name of the font style.
fontStyleNameNative	String	readonly	The native name of the font style.
fontType	FontTypes FontTypes.ATC FontTypes.BITMAP FontTypes.CID FontTypes.OCF FontTypes.OPENTYPE_CFF FontTypes.OPENTYPE_CID FontTypes.OPENTYPE_TT	readonly	The type of font.

Property	Type	Access	Description
	FontTypes.TRUETYPE FontTypes.TYPE_1 FontTypes.UNKNOWN		
fullName	String	readonly	The full font name.
fullNameNative	String	readonly	The full native name of the font.
index	Number	readonly	The index of the Font within its containing object.
isValid	Boolean	readonly	Returns true if the object specifier resolves to valid objects.
location	String	readonly	The full path to the Font.
name	String	readonly	The name of the Font.
numDesignAxes	Number	readonly	Number of design axes in variable font.
ordering	String	readonly	The ordering of a CID font.
parent	Application Document	readonly	The parent of the Font (a Document or Application).
platformName	String	readonly	The platform font name.
postscriptName	String	readonly	The PostScript name of the font.
properties	Object	read/write	A property that allows setting of several properties at the same time.
registry	String	readonly	The registry of a CID font.
restrictedPrinting	Boolean	readonly	If true, the font allows only restricted printing.
status	FontStatus FontStatus.FAUXED FontStatus.INSTALLED FontStatus.NOT_AVAILABLE FontStatus.SUBSTITUTED FontStatus.UNKNOWN	readonly	The status of the font.
version	String	readonly	The font version.
writingScript	Number	readonly	The writing script.

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

Boolean **checkOpenTypeFeature** (using: *Varies OpenTypeFeature String*)

Checks whether the font supports the specified OpenType feature.

Parameter	Type	Description
using	OpenTypeFeature OpenTypeFeature.ALL_SMALL_CAPS_FEATURE OpenTypeFeature.CONTEXTUAL_ALTERNATES_FEATURE OpenTypeFeature.DEFAULT_FIGURE_STYLE_FEATURE OpenTypeFeature.DENOMINATOR_FEATURE OpenTypeFeature.DISCRETIONARY_LIGATURES_FEATURE OpenTypeFeature.FRACTIONS_FEATURE OpenTypeFeature.JUSTIFICATION_ALTERNATE OpenTypeFeature.LOW OpenTypeFeature.NUMERATOR_FEATURE OpenTypeFeature.ORDINAL_FEATURE OpenTypeFeature.OVERLAP_SWASH OpenTypeFeature.PROPORTIONAL_LINING_FEATURE OpenTypeFeature.PROPORTIONAL_OLDSTYLE_FEATURE OpenTypeFeature.STRETCHED_ALTERNATE OpenTypeFeature.STYLISTIC_ALTERNATE OpenTypeFeature.SUBSCRIPT_FEATURE OpenTypeFeature.SUPERSCRIPT_FEATURE OpenTypeFeature.SWASH_FEATURE OpenTypeFeature.TABULAR_LINING_FEATURE OpenTypeFeature.TABULAR_OLDSTYLE_FEATURE OpenTypeFeature.TITLING_FEATURE String	The OpenType feature to check for, specified either as an OpenType feature or a string. Can accept: OpenTypeFeature enumerator or String.

undefined **createSubsetFont** (charactersForSubset: *String*, fontDestination: *File*)

Create a copy of the font with just enough information to render the list of characters given.

Parameter	Type	Description
charactersForSubset	String	String with all the characters used in the resulting font.
fontDestination	File	File location for the new font.

Font **getElements** ()

Resolves the object specifier, creating an array of object references.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

String **toSource** ()

Generates a string which, if executed, will return the Font.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Bullet.bulletsFont

TextDefault.rubyFont

Text.rubyFont

Character.rubyFont

Word.rubyFont

Line.rubyFont

TextColumn.rubyFont

Paragraph.rubyFont

TextStyleRange.rubyFont

InsertionPoint.rubyFont

Story.rubyFont

ParagraphStyle.rubyFont

XmlStory.rubyFont

FindTextPreference.rubyFont

FindGrepPreference.rubyFont

FindTransliteratePreference.rubyFont

ChangeTextPreference.rubyFont

ChangeGrepPreference.rubyFont

ChangeTransliteratePreference.rubyFont

CharacterStyle.rubyFont

ChangeGlyphPreference.appliedFont

ChangeGrepPreference.appliedFont

ChangeTextPreference.appliedFont

ChangeTransliteratePreference.appliedFont

Character.appliedFont

CharacterStyle.appliedFont

CompositeFontEntry.appliedFont

FindGlyphPreference.appliedFont

FindGrepPreference.appliedFont
FindTextPreference.appliedFont
FindTransliteratePreference.appliedFont
GridDataInformation.appliedFont
InsertionPoint.appliedFont
LayoutGridDataInformation.appliedFont
Line.appliedFont
Paragraph.appliedFont
ParagraphStyle.appliedFont
Story.appliedFont
StoryGridDataInformation.appliedFont
Text.appliedFont
TextColumn.appliedFont
TextDefault.appliedFont
TextStyleRange.appliedFont
Word.appliedFont
XmlStory.appliedFont
TextDefault.kentenFont
Text.kentenFont
Character.kentenFont
Word.kentenFont
Line.kentenFont
TextColumn.kentenFont
Paragraph.kentenFont
TextStyleRange.kentenFont
InsertionPoint.kentenFont
Story.kentenFont
ParagraphStyle.kentenFont
XmlStory.kentenFont
FindTextPreference.kentenFont
FindGrepPreference.kentenFont
FindTransliteratePreference.kentenFont
ChangeTextPreference.kentenFont
ChangeGrepPreference.kentenFont
ChangeTransliteratePreference.kentenFont
CharacterStyle.kentenFont
Event.parent
EventListener.parent
MutationEvent.parent

Return

Document.createMissingFontObject()
Font.getElements()
Fonts.anyItem()
Fonts.everyItem()
Fonts.nextItem()
Fonts.previousItem()
Fonts.item()

Fonts.[]()
Fonts.itemByName()
Fonts.itemByRange()
Fonts.firstItem()
Fonts.lastItem()
Fonts.middleItem()
