

LayoutWindow

A layout window.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [bringToFront](#), [close](#), [getElements](#), [maximize](#), [minimize](#), [removeEventListener](#), [restore](#), [select](#), [toSource](#), [toSpecifier](#), [zoom](#)

Objects:

[AnchorPoint](#), [Boolean](#), [EventListeners](#), [Events](#), [Layer](#), [MasterSpread](#), [NothingEnum](#), [Number](#), [Object](#), [Page](#), [PageItem](#), [ProofingType](#), [ScreenModeOptions](#), [Spread](#), [String](#), [ViewDisplaySettings](#)

Hierarchy:

Superclass: [Window](#)

Class: [LayoutWindow](#)

Property Listing

Property	Type	Access	Description
activeLayer	Layer String	read/write	The active layer. Can also accept: String .
activePage	Page	read/write	The front-most page.
activeSpread	Spread MasterSpread	read/write	The front-most spread. Can return: Spread or MasterSpread .
bounds	Array of Number	read/write	The bounds of the window (specified in pixels) in the form [top, left, bottom, right].
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
index	Number	readonly	The index of the LayoutWindow

Property	Type	Access	Description
			within its
isValid	Boolean	readonly	containing object. Returns true if the object specifier resolves to valid objects.
name	String	readonly	The name of the LayoutWindow.
overprintPreview	Boolean	read/write	If true, display a simulation of overprinting.
parent	Document	readonly	The parent of the LayoutWindow (a Document).
preserveColorNumbers	Boolean	read/write	If true, leaves color values unchanged for CMYK objects without embedded profiles and native objects such as line art or type. Note: Converts images whose profiles differ from the profile of the simulated device. Valid only when proofing type is custom.
proofingProfile	String	read/write	The profile used for proofing colors.
proofingType	ProofingType ProofingType.CUSTOM ProofingType.DOCUMENT_CMYK ProofingType.PROOF_OFF ProofingType.WORKING_CMYK	read/write	The method of proofing colors.
properties	Object	read/write	A property that allows setting of several properties at the same time.
screenMode	ScreenModeOptions ScreenModeOptions.PRESENTATION_PREVIEW	read/write	The screen mode for layout view.

Property	Type	Access	Description
	ScreenModeOptions.PREVIEW_OFF ScreenModeOptions.PREVIEW_TO_BLEED ScreenModeOptions.PREVIEW_TO_PAGE ScreenModeOptions.PREVIEW_TO_SLUG		
selection	Array of Object NothingEnum.NOTHING	read/write	The selected object(s). Can also accept: Object or NothingEnum enumerator.
selectionKeyObject	PageItem NothingEnum.NOTHING	read/write	The key object of the selection. Can also accept: NothingEnum enumerator.
simulateInkBlack	Boolean	read/write	If true, simulates the dark gray produced by many printers in place of solid black, according to the proofing profile. Note: Valid only when proofing type is custom.
simulatePaperWhite	Boolean	read/write	If true, simulates the dingy white of real paper, according to the proofing profile. Note: Valid only when proofing type is custom.
transformReferencePoint	AnchorPoint AnchorPoint.BOTTOM_CENTER_ANCHOR AnchorPoint.BOTTOM_LEFT_ANCHOR AnchorPoint.BOTTOM_RIGHT_ANCHOR AnchorPoint.CENTER_ANCHOR AnchorPoint.LEFT_CENTER_ANCHOR AnchorPoint.RIGHT_CENTER_ANCHOR AnchorPoint.TOP_CENTER_ANCHOR AnchorPoint.TOP_LEFT_ANCHOR AnchorPoint.TOP_RIGHT_ANCHOR Array of 2 Units.	read/write	The default anchor point around which to transform objects. Can return: AnchorPoint enumerator or Array of 2 Units.
viewDisplaySetting	ViewDisplaySettings ViewDisplaySettings.HIGH_QUALITY ViewDisplaySettings.OPTIMIZED	read/write	The display performance preferences

Property	Type	Access	Description
	ViewDisplaySettings.TYPICAL		override for the view.
zoomPercentage	Number (range 5 - 4000)	read/write	The size (as a percentage) to which to enlarge or reduce the view of the document. (Range: 5 to 4000)

Constants/Events

Name	Type	Access	Description
AFTER_ACTIVATE	String	readonly	Dispatched after the LayoutWindow becomes active. This event bubbles. This event is not cancelable.
AFTER_ATTRIBUTE_CHANGED	String	readonly	Dispatched when the value of a property changes on this LayoutWindow. This event bubbles. This event is not cancelable.
AFTER_CLOSE	String	readonly	Dispatched when a LayoutWindow is closing. Since the close has been committed, it can no longer be canceled. This event bubbles. This event is not cancelable.
AFTER_OPEN	String	readonly	Dispatched after a LayoutWindow is opened. This event bubbles. This event is not cancelable.
AFTER_SELECTION_ATTRIBUTE_CHANGED	String	readonly	Dispatched after an attribute on the active selection changes. This event bubbles. This event is not cancelable.
AFTER_SELECTION_CHANGED	String	readonly	Dispatched after the active selection changes. This event bubbles. This event is not cancelable.
BEFORE_CLOSE	String	readonly	Dispatched before a LayoutWindow is closed. This event bubbles. This event is cancelable.
BEFORE_DEACTIVATE	String	readonly	Dispatched before the LayoutWindow becomes inactive. This event bubbles. This event is not cancelable.

Method Listing

EventListener **addEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	<i>String</i>	The event type.
handler	<i>File JavaScriptFunction</i>	The event handler. Can accept: File or JavaScript Function.
captures	<i>Boolean</i>	This parameter is obsolete. (Optional) (default: false)

undefined **bringToFront** ()

Brings the object to the front.

undefined **close** ()

Closes the LayoutWindow.

LayoutWindow **getElements** ()

Resolves the object specifier, creating an array of object references.

undefined **maximize** ()

Maximizes the window.

undefined **minimize** ()

Minimizes the window.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	<i>String</i>	The registered event type.
handler	<i>File JavaScriptFunction</i>	The registered event handler. Can accept: File or JavaScript Function.
captures	<i>Boolean</i>	This parameter is obsolete. (Optional) (default: false)

undefined **restore** ()

Restores the window.

undefined **select** (selectableItems:*Array of Varies Objects NothingEnum Object SelectAll*, [existingSelection:*SelectionOptions*=SelectionOptions])

Selects the specified object(s).

Parameter	Type	Description
selectableItems	Array of Objects NothingEnum.NOTHING Object SelectAll SelectAll.ALL	The objects to select. Can accept: Object, Array of Objects, NothingEnum enumerator or SelectAll enumerator.
existingSelection	SelectionOptions SelectionOptions.ADD_TO SelectionOptions.REMOVE_FROM SelectionOptions.REPLACE_WITH SelectionOptions.SET_KEY	The selection status of the LayoutWindow in relation to previously selected objects. (Optional) (default: SelectionOptions.REPLACE_WITH)

String **toSource** ()

Generates a string which, if executed, will return the LayoutWindow.

String **toSpecifier** ()

Retrieves the object specifier.

undefined **zoom** (given:*ZoomOptions*)

Magnifies or reduces the window to the specified display size.

Parameter	Type	Description
given	ZoomOptions ZoomOptions.ACTUAL_SIZE ZoomOptions.FIT_PAGE ZoomOptions.FIT_SPREAD ZoomOptions.SHOW_PASTEBOARD ZoomOptions.ZOOM_IN ZoomOptions.ZOOM_OUT	The display size.

Object of

Application.activeWindow

Event.parent

EventListener.parent

MutationEvent.parent

Return

LayoutWindow.getElements()

LayoutWindows.anyItem()

LayoutWindows.everyItem()

LayoutWindows.nextItem()

LayoutWindows.previousItem()

LayoutWindows.item()
LayoutWindows.[]()
LayoutWindows.itemByName()
LayoutWindows.itemByRange()
LayoutWindows.firstItem()
LayoutWindows.lastItem()
LayoutWindows.middleItem()
