

Object

The base class of all JavaScript objects.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

[Object](#), [hasOwnProperty](#), [isPrototypeOf](#), [isValid](#), [propertyIsEnumerable](#), [toLocaleString](#), [toSource](#), [toString](#), [unwatch](#), [valueOf](#), [watch](#)

Objects:

[Function](#), [Object](#), [Reflection](#)

Property Listing

Property	Type	Access	Description
constructor	Function	readonly	Points to the constructor function that created this object. Note that this property is treated as an XML element in the XML class.
prototype	Object	readonly	Points to the prototype object for this object. Note that this property is treated as an XML element in the XML class.
reflect	Reflection	readonly	Retrieves and returns the Reflection object associated with this method or a property. Note that this property is treated as an XML element in the XML class.

Method Listing

Constructor

Object [Object](#) (what:*Varies*)

Creates and returns a new object of a given type.

Parameter	Type	Description
what	Varies	The object type.

Boolean [hasOwnProperty](#) (name:*String*)

Reports whether a given property is defined with an instance or within the prototype chain.

Parameter	Type	Description
name	String	The name of the property to check.

Boolean [isPrototypeOf](#) (what:*Object*)

Checks whether the given object is a prototype of this object.

Parameter	Type	Description
what	Object	The object to check.

Boolean **isValid** (what:*Object*)

Reports whether an object is still valid.

Parameter	Type	Description
what	Object	The object to check.

Boolean **propertyIsEnumerable** (name:*String*)

Reports whether a given property is enumerable.

Parameter	Type	Description
name	String	The name of the property to check.

String **toLocaleString** ()

Creates and returns a string representing this object, localized for the current locale. See `toString()`.

String **toSource** ()

Creates and returns a string representation of this object.

This function serializes the object, so that it can, for example, be passed between engines. Pass the returned string back to `eval()` to recreate the object. Works only with built-in classes.

String **toString** ()

Creates and returns a string representing this object.

Many objects (such as `Date`) override this method in favor of their own implementation. If an object has no string value and no user-defined `toString()` method, the default method returns `[object type]`, where type is the object type or the name of the constructor function that created the object.

undefined **unwatch** (name:*String*)

Removes the watch function of a property.

Parameter	Type	Description
name	String	The name of the property to unwatch.

Object **valueOf** ()

Retrieves and returns the primitive value of this object.

If the object has no primitive value, returns the object itself. Note that you rarely need to call this method yourself. The JavaScript interpreter automatically invokes it when encountering an object where a primitive value is expected.

undefined **watch** (name:*String*, func:*Function*)

Adds a watch function to a property, which is called when the value changes.

This function can accept, modify, or reject a new value that the user, application, or a script has attempted to place in a property.

Parameter	Type	Description
name	String	The name of the property to watch.
func	Function	The function to be called when the value of this property changes. This function must three arguments, and return as its result the value to be stored in the property. The arguments are: name: the name of the property that changes. oldValue: The old property value. newValue: The new property value that was specified.