

Page

A page.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [adjustLayout](#), [contentPlace](#), [deleteAllLayoutSnapshots](#), [deleteLayoutSnapshot](#), [detach](#), [duplicate](#), [extractLabel](#), [getElements](#), [insertLabel](#), [move](#), [place](#), [placeAndLink](#), [placeXML](#), [reframe](#), [remove](#), [removeEventListener](#), [removeOverride](#), [resize](#), [resolve](#), [select](#), [setContent](#), [snapshotCurrentLayout](#), [toSource](#), [toSpecifier](#), [transform](#), [transformValuesOf](#)

Objects:

[Boolean](#), [Buttons](#), [CheckBoxes](#), [ComboBoxes](#), [EPSTexts](#), [EventListeners](#), [Events](#), [FlexObjects](#), [FormFields](#), [Graphic](#), [GraphicLines](#), [Graphics](#), [GridDataInformation](#), [Groups](#), [Guides](#), [LayoutRuleOptions](#), [ListBoxes](#), [MarginPreference](#), [MasterSpread](#), [Movies](#), [MultiStateObjects](#), [NothingEnum](#), [Number](#), [Object](#), [Ovals](#), [PageColorOptions](#), [PageItem](#), [PageItems](#), [PageSideOptions](#), [Polygons](#), [Preferences](#), [RadioButtons](#), [Rectangles](#), [Section](#), [SignatureFields](#), [SnapshotBlendingModes](#), [Sounds](#), [SplineItems](#), [String](#), [TextBoxes](#), [TextFrames](#), [TransformationMatrix](#), [TrapPreset](#), [UIColors](#),

Preferences:

[MarginPreference](#), [Preferences](#)

Property Listing

Property	Type	Access	Description
allGraphics	Array of Graphic	readonly	Lists all graphics contained by the Page.
allPageItems	Array of PageItem	readonly	Lists all page items contained by the Page.
appliedAlternateLayout	Section	readonly	The alternate layout section to which the page belongs.
appliedMaster	MasterSpread NothingEnum .NOTHING	read/write	The master spread applied to the Page. Can also accept: NothingEnum enumerator.
appliedSection	Section	readonly	The section to which the page belongs.
appliedTrapPreset	TrapPreset String	read/write	The trap preset applied to the page. Can also accept: String .

Property	Type	Access	Description
bounds	Array of Number Array of String	readonly	The bounds of the Page, in the format [y1, x1, y2, x2].
buttons	Buttons <i>Button</i>	readonly	A collection of buttons.
checkboxes	CheckBoxes	readonly	A collection of checkboxes.
comboBoxes	ComboBoxes	readonly	A collection of comboboxes.
documentOffset	Number	readonly	The sequential number of the page within the document.
epstexts	EPSTexts <i>EPSText</i>	readonly	EPSTexts
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
flexObjects	FlexObjects <i>FlexObject</i>	readonly	A collection of flex objects.
formFields	FormFields <i>FormField</i>	readonly	A collection of form fields.
graphicLines	GraphicLines <i>GraphicLine</i>	readonly	A collection of graphic lines.
gridData	GridDataInformation	readonly	Default grid properties. Note: Applies to named, layout, and frame (story) grids.
groups	Groups <i>Group</i>	readonly	A collection of groups.
guides	Guides <i>Guide</i>	readonly	A collection of guides.
id	Number	readonly	The unique ID of the Page.
index	Number	readonly	The index of the Page within its containing object.
isValid	Boolean	readonly	Returns true if the object specifier resolves to valid objects.
label	String	read/write	A property that can be set to any string.
layoutRule	LayoutRuleOptions LayoutRuleOptions.GUIDE_BASED	read/write	layout rule

Property	Type	Access	Description
	LayoutRuleOptions.OBJECT_BASED LayoutRuleOptions.OFF LayoutRuleOptions.PRESERVE_EXISTING LayoutRuleOptions.RECENTER LayoutRuleOptions.SCALE LayoutRuleOptions.USE_MASTER		
listBoxes	ListBoxes	readonly	A collection of listboxes.
marginPreferences	MarginPreference	readonly	Margin preference settings.
masterPageItems	Array of PageItems Array of Graphics <i>Graphic</i> Array of Guides <i>Guide</i> Array of Movies Array of Sounds <i>Sound</i>	readonly	The items on a specified document page that originated on the applied master page and have not been overridden or detached. Can return: Array of PageItems, Guides, Graphics, Movies or Sounds.
masterPageTransform	TransformationMatrix	read/write	The transform applied to the master page before it is applied to Page.
multiStateObjects	MultiStateObjects <i>MultiStateObject</i>	readonly	A collection of multi-state objects.
name	String	readonly	The name of the Page.
optionalPage	Boolean	read/write	optional page for HTML5 pagination. Obsolete after CS6
ovals	Ovals <i>Oval</i>	readonly	A collection of ellipses.
pageColor	Array of 3 Reals (0 - 255) PageColorOptions PageColorOptions.NOTHING PageColorOptions.USE_MASTER_COLOR UIColors	read/write	The color label of the Page, specified either as an array of three doubles, each in the range 0 to 255 and representing R, G, and B values, or as a UI color. Can return: Array of 3 Reals (0 - 255) or UIColors enumerator or PageColorOptions enumerator.
pageItems	PageItems <i>PageItem</i>	readonly	The page items collection, which can

Property	Type	Access	Description
			be used to process all page items in a container (such as a document, page, or group), regardless of type.
parent	MasterSpread Spread	readonly	The parent of the Page (a Spread or MasterSpread).
polygons	Polygons <i>Polygon</i>	readonly	A collection of polygons.
preferences	Preferences <i>Preference</i>	readonly	A collection of preferences objects.
properties	Object	read/write	A property that allows setting of several properties at the same time.
radioButtons	RadioButtons <i>RadioButton</i>	readonly	A collection of radio buttons.
rectangles	Rectangles <i>Rectangle</i>	readonly	A collection of rectangles.
side	PageSideOptions PageSideOptions.LEFT_HAND PageSideOptions.RIGHT_HAND PageSideOptions.SINGLE_SIDED	readonly	The side of the binding spine on which to place the page within the spread.
signatureFields	SignatureFields <i>SignatureField</i>	readonly	A collection of signature fields.
snapshotBlendingMode	SnapshotBlendingModes SnapshotBlendingModes.FULL_SNAPSHOT_BLENDING SnapshotBlendingModes.IGNORE_LAYOUT_SNAPSHOTS SnapshotBlendingModes.LIMITED_SNAPSHOT_BLENDING SnapshotBlendingModes.USE_NEAREST_SNAPSHOT	read/write	snapshot blending mode
splineItems	SplineItems <i>SplineItem</i>	readonly	The spline items collection.
tabOrder	Array of Buttons Array of CheckBoxes Array of ComboBoxes Array of ListBoxes Array of RadioButtons <i>RadioButton</i> Array of TextBoxes Array of SignatureFields <i>SignatureField</i>	read/write	The order in which the focus moves to different form fields in the PDF when the tab key is pressed. Can return: Array of Buttons, CheckBoxes, ComboBoxes, ListBoxes, RadioButtons, TextBoxes or SignatureFields.

Property	Type	Access	Description
textBoxes	TextBoxes	readonly	A collection of text boxes.
textFrames	TextFrames <i>TextFrame</i>	readonly	A collection of text frames.

Method Listing

EventListener **addEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **adjustLayout** (adoptTo:*Object*, affectedPages:*Array of Page*)

Adjust the existing layout according to new page size, bleed and margin values. The first parameter is a plain object with key value pairs for properties affected. Permissible keys are width, height, bleedInside, bleedTop, bleedOutside, bleedBottom, leftMargin, topMargin, rightMargin, bottomMargin. The values can be specified as decimal numbers in units of Pt or as a string having a measurement value such as '1 in'. Not all properties need to be specified, only the values that need updation. Notice that when dealing with individual pages rather than the whole document, bleed changes has no effect. E.g. - app.activeDocument.adjustLayout({width:'600px', leftMargin: '1in'}), app.activeDocument.adjustLayout({rightMargin:'1in'}, app.activeDocument.spreads[0].pages), app.activeDocument.spreads[0].pages[0].adjustLayout({width:'400px', leftMargin: '10px'})

Parameter	Type	Description
adoptTo	Object	Change values - see functin definition for details
affectedPages	Array of Page	The collection of Page objects to affect (optional). Has no effect if function is called from Page (Optional)

Varies **contentPlace** (pageItems:*Array of PageItem*, [linkPageItems:*Boolean*=Boolean], [linkStories:*Boolean*=Boolean], [mapStyles:*Boolean*=Boolean], placePoint:*Array of Number String*, destinationLayer:*Layer*, [showingOptions:*Boolean*=Boolean])

Duplicate an object and place it into the target.

Parameter	Type	Description
pageItems	Array of PageItem	One or more page items to place or load
linkPageItems	Boolean	Whether to link pageItems in content placer (if true it will override link stories value) (Optional) (default: false)

Parameter	Type	Description
linkStories	Boolean	Whether to link stories in content placer (only applicable for single story, pageltem links will also be created in case of more than one item) (Optional) (default: false)
mapStyles	Boolean	Whether to map styles in content placer (Optional) (default: false)
placePoint	Array of Number Array of String	The point at which to place (Optional)
destinationLayer	Layer	The layer on which to place (Optional)
showingOptions	Boolean	Whether to display the link options dialog (Optional) (default: false)

undefined **deleteAllLayoutSnapshots** ()

Delete all layout snapshots for this Page.

undefined **deleteLayoutSnapshot** ()

Delete the snapshot of the layout for the current Page size and shape.

undefined **detach** ()

Detaches an overridden master page item from the master page.

Page **duplicate** ([to:LocationOptions=LocationOptions], reference:Varies Page Spread)

Duplicates the page.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The location at which to place the duplicate page relative to the reference object or within the document or spread. (Optional) (default: LocationOptions.AT_END)
reference	Page Spread	The reference object. Note: Required when the to value specifies before or after. Can accept: Page or Spread. (Optional)

String **extractLabel** (key:String)

Gets the label value associated with the specified key.

Parameter	Type	Description
key	String	The key.

Page **getElements** ()

Resolves the object specifier, creating an array of object references.

undefined **insertLabel** (key:String, value:String)

Sets the label to the value associated with the specified key.

Parameter	Type	Description
key	String	The key.
value	String	The value.

Page **move** ([to:*LocationOptions*=LocationOptions], reference:*Varies Page Spread*, [binding:*BindingOptions*=BindingOptions])

Moves the page.

Parameter	Type	Description
to	<i>LocationOptions</i> LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The new location of the page relative to the reference object or within the document or spread. (Optional) (default: LocationOptions.AT_END)
reference	<i>Page Spread</i>	The reference object. Note: Required when the to parameter value specifies before or after. Can accept: Page or Spread. (Optional)
binding	<i>BindingOptions</i> BindingOptions.DEFAULT_VALUE BindingOptions.LEFT_ALIGN BindingOptions.RIGHT_ALIGN	The location of the binding spine in spreads. (Optional) (default: BindingOptions.DEFAULT_VALUE)

Varies **place** (fileName:*File*, placePoint:*Array of Number String*, destinationLayer:*Layer*, [showingOptions:*Boolean*=Boolean], [autoflowing:*Boolean*=Boolean], withProperties:*Object*)

Places the file.

Parameter	Type	Description
fileName	<i>File</i>	The file to place
placePoint	<i>Array of Number</i> <i>Array of String</i>	The point at which to place (Optional)
destinationLayer	<i>Layer</i>	The layer on which to place (Optional)
showingOptions	<i>Boolean</i>	Whether to display the import options dialog (Optional) (default: false)
autoflowing	<i>Boolean</i>	Whether to autoflow placed text (Optional) (default: false)
withProperties	<i>Object</i>	Initial values for properties of the placed object(s) (Optional)

Story **placeAndLink** (parentStory:*Story*, placePoint:*Array of Number String*, destinationLayer:*Layer*, [showingOptions:*Boolean*=Boolean])

Deprecated: Use contentPlace method. Original Description: Create a linked story and place it into the target.

Parameter	Type	Description
parentStory	<i>Story</i>	The story to place and link from.

Parameter	Type	Description
placePoint	Array of Number Array of String	The point at which to place (Optional)
destinationLayer	Layer	The layer on which to place (Optional)
showingOptions	Boolean	Whether to display the link options dialog (Optional) (default: false)

PageItem **placeXML** (using:XMLElement, placePoint:Array of Number String, [autoflowing:Boolean=Boolean])

Places the XML element onto a page. If the place point is above an existing page item, place the XML element into the page item.

Parameter	Type	Description
using	XMLElement	The XML element to place.
placePoint	Array of Number Array of String	The point at which to place the object, specified in the format [x, y].
autoflowing	Boolean	If true, autoflows placed text. (Optional) (default: false)

undefined **reframe** (in:Varies CoordinateSpaces BoundsKind:BoundingBoxLimits OrderedarraycontainingcoordinateSpace:CoordinateSpaces, opposingCorners:Array of Varies)

Move the bounding box of the page item

Parameter	Type	Description
in	CoordinateSpaces CoordinateSpaces.INNER_COORDINATES CoordinateSpaces.PAGE_COORDINATES CoordinateSpaces.PARENT_COORDINATES CoordinateSpaces.PASTEBOARD_COORDINATES CoordinateSpaces.SPREAD_COORDINATES BoundsKind:BoundingBoxLimits OrderedarraycontainingcoordinateSpace:CoordinateSpaces	The bounding box to resize. Can accept: CoordinateSpaces enumerator or Ordered array containing coordinateSpace:CoordinateSpaces enumerator, boundsKind:BoundingBoxLimits enumerator.
opposingCorners	Array of Varies	Opposing corners of new bounding box in the given coordinate space

undefined **remove** ()

Deletes the Page.

Boolean **removeEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.

Parameter	Type	Description
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **removeOverride** ()

Removes the override from a previously overridden master page item.

undefined **resize** (in:Varies *BoundingBoxLimits* *CoordinateSpaces* *BoundsKind:BoundingBoxLimits* *OrderedarraycontainingcoordinateSpace:CoordinateSpaces*, from:Array of *Varies* *AnchorPoint* *AnchorPoints* *2 Reals* *BoundingBoxLimitss* *CoordinateSpacess* *Arrays of 2 Reals* *LongIntegers*, by:ResizeMethods, values:Array of *Varies* *Reals* *ResizeConstraintss* *CoordinateSpacess*, [resizeIndividually:Boolean=Boolean], [consideringRulerUnits:Boolean=Boolean])

Resize the page item.

Parameter	Type	Description
in	<i>BoundingBoxLimits</i> BoundingBoxLimits.GEOMETRIC_PATH_BOUNDS BoundingBoxLimits.OUTER_STROKE_BOUNDS <i>CoordinateSpaces</i> CoordinateSpaces.INNER_COORDINATES CoordinateSpaces.PAGE_COORDINATES CoordinateSpaces.PARENT_COORDINATES CoordinateSpaces.PASTEBOARD_COORDINATES CoordinateSpaces.SPREAD_COORDINATES BoundsKind:BoundingBoxLimits OrderedarraycontainingcoordinateSpace:CoordinateSpaces	The bounding box to resize. Can accept: <i>CoordinateSpaces</i> enumerator, <i>BoundingBoxLimits</i> enumerator or Ordered array containing <i>coordinateSpace:CoordinateSpaces</i> enumerator, <i>boundsKind:BoundingBoxLimits</i> enumerator.
from	<i>AnchorPoint</i> AnchorPoint.BOTTOM_CENTER_ANCHOR AnchorPoint.BOTTOM_LEFT_ANCHOR AnchorPoint.BOTTOM_RIGHT_ANCHOR AnchorPoint.CENTER_ANCHOR AnchorPoint.LEFT_CENTER_ANCHOR AnchorPoint.RIGHT_CENTER_ANCHOR AnchorPoint.TOP_CENTER_ANCHOR AnchorPoint.TOP_LEFT_ANCHOR AnchorPoint.TOP_RIGHT_ANCHOR AnchorPoints <i>AnchorPoint</i> <i>Array</i> of 2 Reals BoundingBoxLimitss <i>BoundingBoxLimits</i> CoordinateSpacess <i>CoordinateSpaces</i> <i>Array</i> of Arrays of 2 Reals LongIntegers	The transform origin. Legal specifications: relative to bounding box: anchor {anchor {x,y}, bounds kind [, coordinate space]}; relative to coordinate space: {x,y} {{x,y}[, coordinate space]}; relative to layout window ruler: {{x,y}, page index bounds kind}. Can accept: <i>Array</i> of 2 Reals, <i>AnchorPoint</i> enumerator or <i>Array</i> of <i>Arrays</i> of 2 Reals, <i>CoordinateSpaces</i> enumerators, <i>AnchorPoint</i> enumerators, <i>BoundingBoxLimits</i> enumerators or Long Integers.
by	<i>ResizeMethods</i> ResizeMethods.ADDING_CURRENT_DIMENSIONS_TO ResizeMethods.MULTIPLYING_CURRENT_DIMENSIONS_BY ResizeMethods.REPLACING_CURRENT_DIMENSIONS_WITH ResizeMethods.RESHAPING_AREA_TO_RATIO ResizeMethods.RESHAPING_BORDER_TO_RATIO	How the current dimensions are affected by the given values
values	<i>Array</i> of Reals <i>Array</i> of <i>ResizeConstraintss</i> <i>ResizeConstraints</i> <i>Array</i> of <i>CoordinateSpacess</i> <i>CoordinateSpaces</i>	The width and height values. Legal dimensions specifications: {x, y [, coordinate space]}, {x, resize constraint [, coordinate space]}, or

Parameter	Type	Description
		{resize constraint, y [, coordinate space]}; where x and y are real numbers and coordinate space is used to determine _only_ the unit of length for x and y; coordinate space is ignored for the 'current dimensions times' resize method). Can accept: Array of Reals, ResizeConstraints enumerators or CoordinateSpaces enumerators.
resizeIndividually	Boolean	If false and multiple page items are targeted, the new dimensions are attained only by moving the individual items rather than resizing them. (Optional) (default: true)
consideringRulerUnits	Boolean	If true then a ruler location is interpreted using ruler units rather than points. The default value is false. This parameter has no effect unless the reference point is specified relative to a page. (Optional) (default: false)

Varies **resolve** (location: *Array of Varies AnchorPoint AnchorPoints 2 Reals BoundingBoxLimitss CoordinateSpacess Arrays of 2 Reals LongIntegers*, in: *CoordinateSpaces*, [consideringRulerUnits: *Boolean*=Boolean])

Get the coordinates of the given location in the specified coordinate system.

Parameter	Type	Description
location	AnchorPoint AnchorPoint.BOTTOM_CENTER_ANCHOR AnchorPoint.BOTTOM_LEFT_ANCHOR AnchorPoint.BOTTOM_RIGHT_ANCHOR AnchorPoint.CENTER_ANCHOR AnchorPoint.LEFT_CENTER_ANCHOR AnchorPoint.RIGHT_CENTER_ANCHOR AnchorPoint.TOP_CENTER_ANCHOR AnchorPoint.TOP_LEFT_ANCHOR AnchorPoint.TOP_RIGHT_ANCHOR AnchorPoints <i>AnchorPoint</i> <i>Array</i> of 2 Reals BoundingBoxLimitss <i>BoundingBoxLimits</i> CoordinateSpacess <i>CoordinateSpaces</i> <i>Array</i> of Arrays of 2 Reals LongIntegers	The location requested. Can accept: Array of 2 Reals, AnchorPoint enumerator or Array of Arrays of 2 Reals, CoordinateSpaces enumerators, AnchorPoint enumerators, BoundingBoxLimits enumerators or Long Integers.
in	CoordinateSpaces CoordinateSpaces.INNER_COORDINATES CoordinateSpaces.PAGE_COORDINATES CoordinateSpaces.PARENT_COORDINATES CoordinateSpaces.PASTEBOARD_COORDINATES CoordinateSpaces.SPREAD_COORDINATES	The coordinate space to use.

Parameter	Type	Description
consideringRulerUnits	Boolean	If true then a ruler location is interpreted using ruler units rather than points. The default value is false. This parameter has no effect unless the reference point is specified relative to a page. (Optional) (default: false)

undefined **select** ([existingSelection:*SelectionOptions*=SelectionOptions])

Selects the object.

Parameter	Type	Description
existingSelection	<i>SelectionOptions</i> SelectionOptions.ADD_TO SelectionOptions.REMOVE_FROM SelectionOptions.REPLACE_WITH SelectionOptions.SET_KEY	The selection status of the Page in relation to previously selected objects. (Optional) (default: SelectionOptions.REPLACE_WITH)

PageItem **setContent** (using:String, relativeBasePath:String)

Replaces the content of XML element with content imported from a file.

Parameter	Type	Description
using	String	The file path to the import file.
relativeBasePath	String	Base path used to resolve relative paths. (Optional)

undefined **snapshotCurrentLayout** ()

Create a snapshot of the layout for the current Page size and shape.

String **toSource** ()

Generates a string which, if executed, will return the Page.

String **toSpecifier** ()

Retrieves the object specifier.

undefined **transform** (in:CoordinateSpaces, from:Array of *Varies AnchorPoint AnchorPoints 2 Reals BoundingBoxLimitss CoordinateSpacess Arrays of 2 Reals LongIntegers*, withMatrix:Array of *Varies 6 Reals TransformationMatrix*, replacingCurrent:Array of *Varies MatrixContent enumerators MatrixContent LongInteger*, [consideringRulerUnits:Boolean=Boolean])

Transform the page item.

Parameter	Type	Description
in	<i>CoordinateSpaces</i> CoordinateSpaces.INNER_COORDINATES CoordinateSpaces.PAGE_COORDINATES CoordinateSpaces.PARENT_COORDINATES CoordinateSpaces.PASTEBOARD_COORDINATES CoordinateSpaces.SPREAD_COORDINATES	The coordinate space to use

Parameter	Type	Description
from	AnchorPoint AnchorPoint.BOTTOM_CENTER_ANCHOR AnchorPoint.BOTTOM_LEFT_ANCHOR AnchorPoint.BOTTOM_RIGHT_ANCHOR AnchorPoint.CENTER_ANCHOR AnchorPoint.LEFT_CENTER_ANCHOR AnchorPoint.RIGHT_CENTER_ANCHOR AnchorPoint.TOP_CENTER_ANCHOR AnchorPoint.TOP_LEFT_ANCHOR AnchorPoint.TOP_RIGHT_ANCHOR AnchorPoints AnchorPoint Array of 2 Reals BoundingBoxLimitss BoundingBoxLimits CoordinateSpaces CoordinateSpaces Array of Arrays of 2 Reals LongIntegers	The temporary origin during the transformation. Can accept: Array of 2 Reals, AnchorPoint enumerator or Array of Arrays of 2 Reals, CoordinateSpaces enumerators, AnchorPoint enumerators, BoundingBoxLimits enumerators or Long Integers.
withMatrix	Array of 6 Reals TransformationMatrix	Transform matrix. Can accept: Array of 6 Reals or TransformationMatrix.
replacingCurrent	Array of MatrixContent enumerators MatrixContent MatrixContent.ROTATION_VALUE MatrixContent.SCALE_VALUES MatrixContent.SHEAR_VALUE MatrixContent.TRANSLATION_VALUES LongInteger	Transform components to consider; providing this optional parameter causes the target's existing transform components to be replaced with new values. Without this parameter, the given matrix is concatenated onto the target's existing transform combining the effect of the two. Can accept: MatrixContent enumerator, Array of MatrixContent enumerators or Long Integer. (Optional)
consideringRulerUnits	Boolean	If true then a ruler based origin is interpreted using ruler units rather than points. The default value is false. This parameter has no effect unless the reference point is specified relative to a page. (Optional) (default: false)

TransformationMatrix **transformValuesOf** (in:*CoordinateSpaces*)

Get the transformation values of the page item.

Parameter	Type	Description
in	CoordinateSpaces CoordinateSpaces.INNER_COORDINATES CoordinateSpaces.PAGE_COORDINATES CoordinateSpaces.PARENT_COORDINATES CoordinateSpaces.PASTEBOARD_COORDINATES CoordinateSpaces.SPREAD_COORDINATES	The coordinate space to use

Object of

Bookmark.destination

LayoutWindow.activePage
FormField.parentPage
Button.parentPage
MultiStateObject.parentPage
CheckBox.parentPage
ComboBox.parentPage
ListBox.parentPage
RadioButton.parentPage
TextBox.parentPage
SignatureField.parentPage
Movie.parentPage
Sound.parentPage
PageItem.parentPage
Oval.parentPage
Rectangle.parentPage
GraphicLine.parentPage
Polygon.parentPage
Group.parentPage
Image.parentPage
EPS.parentPage
PDF.parentPage
WMF.parentPage
PICT.parentPage
Graphic.parentPage
Guide.parentPage
SplineItem.parentPage
EPSText.parentPage
ImportedPage.parentPage
SVG.parentPage
MediaItem.parentPage
FlexObject.parentPage
HtmlItem.parentPage
TextFrame.parentPage
EndnoteTextFrame.parentPage
HyperlinkPageDestination.destinationPage
Event.parent
EventListener.parent
GridDataInformation.parent
MarginPreference.parent
MutationEvent.parent
Preference.parent
Section.pageStart

Return

Pages.add()
Page.duplicate()
Page.move()
Page.getElements()
Pages.anyItem()
Pages.everyItem()
Pages.nextItem()
Pages.previousItem()
Pages.itemByID()
Pages.item()

Pages.[]()
Pages.itemByName()
Pages.itemByRange()
Pages.firstItem()
Pages.lastItem()
Pages.middleItem()
