

Paragraph

A paragraph.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

addEventListener, applyCharacterStyle, applyConditions, applyParagraphStyle, asynchronousExportFile, autoTag, changeGlyph, changeGrep, changeText, changeTransliterate, changecase, clearOverrides, convertBulletsAndNumberingToText, convertToNote, convertToTable, createEmailQRCode, createHyperlinkQRCode, createOutlines, createPlainTextQRCode, createStyleThumbnailWithProperties, createTextMsgQRCode, createThumbnailWithProperties, createVCardQRCode, duplicate, exportFile, findGlyph, findGrep, findHyperlinks, findText, findTransliterate, getElements, isNthDesignAxisHidden, markup, move, place, recompose, remove, removeEventListener, select, setNthDesignAxis, showText, textHasOverrides, toSource, toSpecifier

Objects:

AdornmentOverprint, AlternateGlyphForms, BalanceLinesStyle, Boolean, Bullet, Buttons, Capitalization, CharacterAlignment, CharacterDirectionOptions, CharacterStyle, Characters, CheckBoxes, ComboBoxes, Condition, CornerOptions, DiacriticPositionOptions, DigitsTypeOptions, EPSTexts, EndCap, EndJoin, EndnoteRanges, EndnoteTextFrames, EventListeners, Events, Font, Footnotes, FormFields, Graphic, GraphicLines, GridAlignment, Groups, HiddenTexts, HyphenationStyleEnum, InsertionPoints, Justification, KashidasOptions, KentenAlignment, KentenCharacter, KentenCharacterSet, KinsokuHangTypes, KinsokuSet, KinsokuTable, KinsokuType, LanguageWithVendors, Leading, LeadingModel, Lines, ListAlignment, ListBoxes, ListType, MojikumiTable, MojikumiTableDefaults, MultiStateObjects, NestedGrepStyles, NestedLineStyles, NestedStyles, Notes, NothingEnum, Number, NumberingList, NumberingRestartPolicy, NumberingStyle, OTFFigureStyle, Object, OutlineJoin, Ovals, PageItem, PageItems, ParagraphBorderBottomOriginEnum, ParagraphBorderEnum, ParagraphBorderTopOriginEnum, ParagraphDirectionOptions, ParagraphJustificationOptions, ParagraphShadingBottomOriginEnum, ParagraphShadingTopOriginEnum, ParagraphShadingWidthEnum, ParagraphStyle, Paragraphs, Polygons, Position, PositionalForms, Preferences, RadioButtons, Rectangles, RubyAlignments, RubyKentenPosition, RubyOverhang, RubyParentSpacing, RubyTypes, RuleWidth, SignatureFields, SingleWordJustification, Spacing, SpanColumnCountOptions, SpanColumnTypeOptions, SpecialCharacters, SplineItems, StartParagraph, String, StrokeStyle, Swatch, TabStops, Tables, TextBoxes, TextColumns, TextFrames, TextPaths, TextStrokeAlign, TextStyleRanges, TextVariableInstances, Texts, WarichuAlignment, Words, XMLItem,

Preferences:

Preferences

Hierarchy:

Superclass: [Text](#)

Class: [Paragraph](#)

Property Listing

Property	Type	Access	Desc
alignToBaseline	Boolean	read/write	If true, the paragraph aligns to the baseline of the grid.
allGraphics	Array of Graphic	readonly	Lists all the graphics contained in the paragraph.
allPageItems	Array of PageItem	readonly	Lists all the page items contained in the paragraph.
allowArbitraryHyphenation	Boolean	read/write	If true, the paragraph can be hyphenated at any point.
appliedCharacterStyle	CharacterStyle String	read/write	The character style applied to the paragraph. Also returns the name of the style.
appliedConditions	Array of Condition	read/write	The conditions applied to the paragraph.
appliedFont	Font String	read/write	The font applied to the paragraph. Also returns the name of the font.
appliedLanguage	LanguageWithVendors LanguageCanAlsoAccept:String	read/write	The language applied to the paragraph. Can also return a list of languages accepted by the paragraph.

Property	Type	Access	Description
appliedNestedStyles	Array of CharacterStyle	readonly	The nested styles applied to the text.
appliedNumberingList	NumberingList String	read/write	The numbering list applied to the text. Returns a string representing the list.
appliedParagraphStyle	ParagraphStyle String	read/write	The paragraph style applied to the text. Also returns a string representing the style.
ascent	Number String	readonly	The ascent of the text.
associatedXMLElements	Array of XMLItem	readonly	The XML elements associated with the text.
autoLeading	Number (range 0 - 500)	read/write	The auto leading of the text.
autoTcy	Number	read/write	The auto text case, which auto horizontal text.
autoTcyIncludeRoman	Boolean	read/write	If true, Roman numerals are used for auto text case.
balanceRaggedLines	Boolean BalanceLinesStyle BalanceLinesStyle.FULLY_BALANCED BalanceLinesStyle.NO_BALANCING BalanceLinesStyle.PYRAMID_SHAPE BalanceLinesStyle.VEE_SHAPE	read/write	If true, ragged lines are balanced. Note: single line balancing is not supported. Can be used for balancing.
baseline	Number String	readonly	The baseline of the text.
baselineShift	Number String	read/write	The baseline shift of the text.
bulletChar	Bullet	readonly	The bullet character used for the list.
bulletsAlignment	ListAlignment ListAlignment.CENTER_ALIGN ListAlignment.LEFT_ALIGN ListAlignment.RIGHT_ALIGN	read/write	The alignment of the bullets.
bulletsAndNumberingListType	ListType ListType.BULLET_LIST ListType.NO_LIST ListType.NUMBERED_LIST	read/write	The type of the bullets and numbering list.
bulletsAndNumberingResultText	String	readonly	The result text of the bullets and numbering list.
bulletsCharacterStyle	CharacterStyle String	read/write	The character style used for the bullets. Character style.
bulletsTextAfter	String	read/write	The text after the bullets.
bunriKinshi	Boolean	read/write	If true, the text is separated by a line. Note: kinshi is not supported.
buttons	Buttons <i>Button</i>	readonly	A collection of buttons.
capitalization	Capitalization Capitalization.ALL_CAPS Capitalization.CAP_TO_SMALL_CAP Capitalization.LOWER_CASE	read/write	The capitalization of the text.

Property	Type	Access	Desc
	Capitalization.NORMAL Capitalization.SMALL_CAPS		
characterAlignment	CharacterAlignment CharacterAlignment.ALIGN_BASELINE CharacterAlignment.ALIGN_EM_BOTTOM CharacterAlignment.ALIGN_EM_CENTER CharacterAlignment.ALIGN_EM_TOP CharacterAlignment.ALIGN_ICF_BOTTOM CharacterAlignment.ALIGN_ICF_TOP	read/write	The i char: char:
characterDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The i char:
characterRotation	Number	read/write	The i degr char: rotat coun
characters	Characters <i>Character</i>	readonly	A col
checkboxes	CheckBoxes	readonly	A col chec
cjkGridTracking	Boolean	read/write	If tru to tr: char:
comboBoxes	ComboBoxes	readonly	A col coml
composer	String	read/write	The f to cc
contents	String SpecialCharacters SpecialCharacters.ARABIC_COMMA SpecialCharacters.ARABIC_KASHIDA SpecialCharacters.ARABIC_QUESTION_MARK SpecialCharacters.ARABIC_SEMICOLON SpecialCharacters.AUTO_PAGE_NUMBER SpecialCharacters.BULLET_CHARACTER SpecialCharacters.COLUMN_BREAK SpecialCharacters.COPYRIGHT_SYMBOL SpecialCharacters.DEGREE_SYMBOL SpecialCharacters.DISCRETIONARY_HYPHEN SpecialCharacters.DISCRETIONARY_LINE_BREAK SpecialCharacters.DOTTED_CIRCLE SpecialCharacters.DOUBLE_LEFT_QUOTE SpecialCharacters.DOUBLE_RIGHT_QUOTE SpecialCharacters.DOUBLE_STRAIGHT_QUOTE SpecialCharacters.ELLIPSIS_CHARACTER SpecialCharacters.EM_DASH SpecialCharacters.EM_SPACE SpecialCharacters.END_NESTED_STYLE SpecialCharacters.EN_DASH SpecialCharacters.EN_SPACE SpecialCharacters.EVEN_PAGE_BREAK SpecialCharacters.FIGURE_SPACE SpecialCharacters.FIXED_WIDTH_NONBREAKING_SPACE SpecialCharacters.FLUSH_SPACE SpecialCharacters.FOOTNOTE_SYMBOL SpecialCharacters.FORCED_LINE_BREAK SpecialCharacters.FRAME_BREAK SpecialCharacters.HAIR_SPACE SpecialCharacters.HEBREW_GERESH SpecialCharacters.HEBREW_GERSHAYIM SpecialCharacters.HEBREW_MAQAF SpecialCharacters.HEBREW_SOF_PASUK SpecialCharacters.INDENT_HERE_TAB SpecialCharacters.LEFT_TO_RIGHT_EMBEDDING SpecialCharacters.LEFT_TO_RIGHT_MARK SpecialCharacters.LEFT_TO_RIGHT_OVERRIDE SpecialCharacters.NEXT_PAGE_NUMBER SpecialCharacters.NONBREAKING_HYPHEN	read/write	The i Can i Spec enur

Property	Type	Access	Desc
	SpecialCharacters.NONBREAKING_SPACE SpecialCharacters.ODD_PAGE_BREAK SpecialCharacters.PAGE_BREAK SpecialCharacters.PARAGRAPH_SYMBOL SpecialCharacters.POP_DIRECTIONAL_FORMATTING SpecialCharacters.PREVIOUS_PAGE_NUMBER SpecialCharacters.PUNCTUATION_SPACE SpecialCharacters.QUARTER_SPACE SpecialCharacters.REGISTERED_TRADEMARK SpecialCharacters.RIGHT_INDENT_TAB SpecialCharacters.RIGHT_TO_LEFT_EMBEDDING SpecialCharacters.RIGHT_TO_LEFT_MARK SpecialCharacters.RIGHT_TO_LEFT_OVERRIDE SpecialCharacters.SECTION_MARKER SpecialCharacters.SECTION_SYMBOL SpecialCharacters.SINGLE_LEFT_QUOTE SpecialCharacters.SINGLE_RIGHT_QUOTE SpecialCharacters.SINGLE_STRAIGHT_QUOTE SpecialCharacters.SIXTH_SPACE SpecialCharacters.TEXT_VARIABLE SpecialCharacters.THIN_SPACE SpecialCharacters.THIRD_SPACE SpecialCharacters.TRADEMARK_SYMBOL SpecialCharacters.ZERO_WIDTH_JOINER SpecialCharacters.ZERO_WIDTH_NONJOINER		
descent	Number String	readonly	The i any c
designAxes	Array of Number	read/write	Value
desiredGlyphScaling	Number (range 50 - 200)	read/write	The i per c char: 200)
desiredLetterSpacing	Number	read/write	The i spec of th betw font.
desiredWordSpacing	Number (range 0 - 1000)	read/write	The i spec of th value
diacriticPosition	DiacriticPositionOptions DiacriticPositionOptions.DEFAULT_POSITION DiacriticPositionOptions.LOOSE_POSITION DiacriticPositionOptions.MEDIUM_POSITION DiacriticPositionOptions.OPENTYPE_POSITION DiacriticPositionOptions.OPENTYPE_POSITION_FROM_BASELINE DiacriticPositionOptions.TIGHT_POSITION	read/write	Posit char:
digitsType	DigitsTypeOptions DigitsTypeOptions.ARABIC_DIGITS DigitsTypeOptions.BENGALI_DIGITS DigitsTypeOptions.BURMESE_DIGITS DigitsTypeOptions.DEFAULT_DIGITS DigitsTypeOptions.DEVANAGARI_DIGITS DigitsTypeOptions.FARSI_DIGITS DigitsTypeOptions.FULL_FARSI_DIGITS DigitsTypeOptions.GUJARATI_DIGITS DigitsTypeOptions.GURMUKHI_DIGITS DigitsTypeOptions.HINDI_DIGITS DigitsTypeOptions.KANNADA_DIGITS DigitsTypeOptions.KHMER_DIGITS DigitsTypeOptions.LAO_DIGITS DigitsTypeOptions.MALAYALAM_DIGITS DigitsTypeOptions.NATIVE_DIGITS DigitsTypeOptions.ORIYA_DIGITS DigitsTypeOptions.TAMIL_DIGITS DigitsTypeOptions.TELUGU_DIGITS DigitsTypeOptions.THAI_DIGITS DigitsTypeOptions.TIBETAN_DIGITS	read/write	The i

Property	Type	Access	Desc
dropCapCharacters	Number (range 0 - 150)	read/write	The number of characters to drop
dropCapLines	Number (range 0 - 25)	read/write	The number of lines to drop
dropCapStyle	CharacterStyle String	read/write	The character style to apply also
dropcapDetail	Number	read/write	Detail of the drop cap bearing 0x10 used grid.
endBaseline	Number String	readonly	Vertical position of the
endHorizontalOffset	Number String	readonly	Horizontal offset of the
endJoin	OutlineJoin OutlineJoin.BEVEL_END_JOIN OutlineJoin.MITER_END_JOIN OutlineJoin.ROUND_END_JOIN	read/write	The end join style applied to the
endnoteRanges	EndnoteRanges <i>EndnoteRange</i>	readonly	A collection of endnote text
endnoteTextFrames	EndnoteTextFrames <i>EndnoteTextFrame</i>	readonly	A collection of endnote text frames
epstexts	EPSTexts <i>EPSText</i>	readonly	EPSTexts
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners
events	Events <i>Event</i>	readonly	A collection of events
fillColor	Swatch String	read/write	The fill color (gradient or ink) of the fill area
fillTint	Number (range 0 - 100)	read/write	The fill tint percentage of the Paragraph fill tint percentage (0 to 100) in hexadecimal
firstLineIndent	Number String	read/write	The first line indent
fontStyle	String	read/write	The font style
footnotes	Footnotes <i>Footnote</i>	readonly	A collection of footnotes
formFields	FormFields <i>FormField</i>	readonly	A collection of form fields
glyphForm	AlternateGlyphForms AlternateGlyphForms.EXPERT_FORM AlternateGlyphForms.FULL_WIDTH_FORM AlternateGlyphForms.JIS04_FORM AlternateGlyphForms.JIS78_FORM AlternateGlyphForms.JIS83_FORM AlternateGlyphForms.JIS90_FORM AlternateGlyphForms.MONOSPACED_HALF_WIDTH_FORM AlternateGlyphForms.NLC_FORM AlternateGlyphForms.NONE AlternateGlyphForms.PROPORTIONAL_WIDTH_FORM AlternateGlyphForms.QUARTER_WIDTH_FORM AlternateGlyphForms.THIRD_WIDTH_FORM AlternateGlyphForms.TRADITIONAL_FORM	read/write	The glyph substitution
gradientFillAngle	Number	read/write	The gradient fill angle

Property	Type	Access	Description
			of the text to 180 degrees.
gradientFillLength	Number	read/write	The length of the gradient fill in units.
gradientFillStart	Array of Number Array of String	read/write	The start coordinates and color of the gradient fill.
gradientStrokeAngle	Number	read/write	The angle of the gradient stroke in degrees (-180 to 180).
gradientStrokeLength	Number	read/write	The length of the gradient stroke in units.
gradientStrokeStart	Array of Number Array of String	read/write	The start coordinates and color of the gradient stroke.
graphicLines	GraphicLines <i>GraphicLine</i>	readonly	A collection of graphic lines.
gridAlignFirstLineOnly	Boolean	read/write	If true, the first line of the grid is aligned with the baseline.
gridAlignment	GridAlignment GridAlignment.ALIGN_BASELINE GridAlignment.ALIGN_EM_BOTTOM GridAlignment.ALIGN_EM_CENTER GridAlignment.ALIGN_EM_TOP GridAlignment.ALIGN_ICF_BOTTOM GridAlignment.ALIGN_ICF_TOP GridAlignment.NONE	read/write	The alignment of the grid relative to the frame.
gridGyoudori	Number	read/write	The grid gyoudori (vertical offset) in units.
groups	Groups <i>Group</i>	readonly	A collection of groups.
hiddenTexts	HiddenTexts <i>HiddenText</i>	readonly	A collection of hidden texts.
horizontalOffset	Number String	readonly	The horizontal offset in units or as a string.
horizontalScale	Number	read/write	The horizontal scale factor.
hyphenWeight	Number (range 0 - 10)	read/write	The weight of the hyphenation marks (0 to 100).
hyphenateAcrossColumns	Boolean	read/write	If true, words are hyphenated across columns.
hyphenateAfterFirst	Number (range 1 - 15)	read/write	The number of letters after the first hyphenation point.
hyphenateBeforeLast	Number (range 1 - 15)	read/write	The number of letters before the last hyphenation point.
hyphenateCapitalizedWords	Boolean	read/write	If true, capitalized words are hyphenated.

Property	Type	Access	Description
hyphenateLadderLimit	Number (range 0 - 25)	read/write	word. The i hyph on co spec cons zero.
hyphenateLastWord	Boolean	read/write	If true hyph word Note hyph
hyphenateWordsLongerThan	Number (range 3 - 25)	read/write	The i lette in or hyph
hyphenation	Boolean	read/write	If true hyph
hyphenationZone	Number String	read/write	The i spac of a l text begi com com
ignoreEdgeAlignment	Boolean	read/write	If true edge para
index	Number	readonly	The i the c obje
insertionPoints	InsertionPoints <i>InsertionPoint</i>	readonly	A col poin
isValid	Boolean	readonly	Retu spec obje
jidori	Number	read/write	The i squa arrar
justification	Justification Justification.AWAY_FROM_BINDING_SIDE Justification.CENTER_ALIGN Justification.CENTER_JUSTIFIED Justification.FULLY_JUSTIFIED Justification.LEFT_ALIGN Justification.LEFT_JUSTIFIED Justification.RIGHT_ALIGN Justification.RIGHT_JUSTIFIED Justification.TO_BINDING_SIDE	read/write	The i
kashidas	KashidasOptions KashidasOptions.DEFAULT_KASHIDAS KashidasOptions.KASHIDAS_OFF	read/write	Use i justil
keepAllLinesTogether	Boolean	read/write	If true the p false to br colur
keepFirstLines	Number (range 1 - 50)	read/write	The i lines para, a pag
keepLastLines	Number (range 1 - 50)	read/write	The i lines para, brea
keepLinesTogether	Boolean	read/write	If true num

Property	Type	Access	Description
			when a break occurs in the text.
keepRuleAboveInFrame	Boolean	read/write	If true, the rule above remains above the frame when the frame is moved.
keepWithNext	Number (range 0 - 5)	read/write	The number of lines the paragraph is kept with the next paragraph.
keepWithPrevious	Boolean	read/write	If true, the paragraph is kept with the previous paragraph.
kentenAlignment	KentenAlignment KentenAlignment.ALIGN_KENTEN_CENTER KentenAlignment.ALIGN_KENTEN_LEFT	read/write	The alignment of the character set.
kentenCharacterSet	KentenCharacterSet KentenCharacterSet.CHARACTER_INPUT KentenCharacterSet.JIS KentenCharacterSet.KUTEN KentenCharacterSet.SHIFT_JIS KentenCharacterSet.UNICODE	read/write	The character set used for the character set.
kentenCustomCharacter	String	read/write	The custom character used for the character set.
kentenFillColor	Swatch String	read/write	The fill color (gradient or solid) used for the character set.
kentenFont	Font String	read/write	The font used for the character set.
kentenFontSize	Number	read/write	The font size used for the character set.
kentenFontStyle	String NothingEnum.NOTHING	read/write	The font style used for the character set.
kentenKind	KentenCharacter KentenCharacter.CUSTOM KentenCharacter.KENTEN_BLACK_CIRCLE KentenCharacter.KENTEN_BLACK_TRIANGLE KentenCharacter.KENTEN_BULLSEYE KentenCharacter.KENTEN_FISHEYE KentenCharacter.KENTEN_SESAME_DOT KentenCharacter.KENTEN_SMALL_BLACK_CIRCLE KentenCharacter.KENTEN_SMALL_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_SESAME_DOT KentenCharacter.KENTEN_WHITE_TRIANGLE KentenCharacter.NONE	read/write	The kind of character set used for the character set.
kentenOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The overprint fill used for the character set.
kentenOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The overprint stroke used for the character set.
kentenPlacement	Number	read/write	The placement of the character set.

Property	Type	Access	Description
kentenPosition	RubyKentenPosition RubyKentenPosition.ABOVE_RIGHT RubyKentenPosition.BELOW_LEFT	read/write	The relative position of the kanten character.
kentenStrokeColor	Swatch String	read/write	The stroke color of the kanten character (in hexadecimal notation).
kentenStrokeTint	Number (range 0 - 100)	read/write	The stroke tint of the kanten character (percentage of the stroke color).
kentenTint	Number (range 0 - 100)	read/write	The tint of the kanten character (percentage of the character color).
kentenWeight	Number	read/write	The weight of the kanten character.
kentenXScale	Number	read/write	The x-axis scale of the kanten character.
kentenYScale	Number	read/write	The y-axis scale of the kanten character.
kerningMethod	String	read/write	The kerning method used for the kanten character.
kerningValue	Number	read/write	The kerning value for the kanten character.
keyboardDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The keyboard direction for the kanten character.
kinsokuHangType	KinsokuHangTypes KinsokuHangTypes.KINSOKU_HANG_FORCE KinsokuHangTypes.KINSOKU_HANG_REGULAR KinsokuHangTypes.NONE	read/write	The kinsoku hang type for the kanten character.
kinsokuSet	KinsokuSet KinsokuSet.HARD_KINSOKU KinsokuSet.KOREAN_KINSOKU KinsokuSet.NOTHING KinsokuSet.SIMPLIFIED_CHINESE_KINSOKU KinsokuSet.SOFT_KINSOKU KinsokuSet.TRADITIONAL_CHINESE_KINSOKU KinsokuTable String	read/write	The kinsoku set for the kanten character.
kinsokuType	KinsokuType KinsokuType.KINSOKU_PRIORITIZE_ADJUSTMENT_AMOUNT KinsokuType.KINSOKU_PUSH_IN_FIRST KinsokuType.KINSOKU_PUSH_OUT_FIRST KinsokuType.KINSOKU_PUSH_OUT_ONLY	read/write	The kinsoku type for the kanten character.
lastLineIndent	Number String	read/write	The last line indent for the kanten character.
leading	Unit Leading Leading.AUTO	read/write	The leading for the kanten character.
leadingAki	Number	read/write	The leading aki for the kanten character.
leadingModel	LeadingModel LeadingModel.LEADING_MODEL_AKI_ABOVE LeadingModel.LEADING_MODEL_AKI_BELOW LeadingModel.LEADING_MODEL_CENTER	read/write	The leading model for the kanten character.

Property	Type	Access	Desc
	LeadingModel.LEADING_MODEL_CENTER_DOWN LeadingModel.LEADING_MODEL_ROMAN		
leftIndent	Number String	read/write	The i inde
length	Number	readonly	The i the c
ligatures	Boolean	read/write	If tru char: (e.g., char:
lines	Lines <i>Line</i>	readonly	A col
listBoxes	ListBoxes	readonly	A col
maximumGlyphScaling	Number (range 50 - 200)	read/write	The i perc char: 200)
maximumLetterSpacing	Number	read/write	The i spac perc spac the f 500) whei
maximumWordSpacing	Number (range 0 - 1000)	read/write	The i spac perc worc Valid justif 100C
mergeConsecutiveParaBorders	Boolean	read/write	If tru bord simil merg
minimumGlyphScaling	Number (range 50 - 200)	read/write	The i perc char: 200)
minimumLetterSpacing	Number	read/write	The i spac perc spac the f 500) whei
minimumWordSpacing	Number (range 0 - 1000)	read/write	The i spac perc worc Valid justif 100C
miterLimit	Number (range 0 - 1000)	read/write	The l strok lengt (poir beve
mojikumi	MojikumiTable String MojikumiTableDefaults MojikumiTableDefaults.LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.NOTHING MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM	read/write	The i infor table Moji Moji enur

Property	Type	Access	Desc
	MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.SIMP_CHINESE_DEFAULT MojikumiTableDefaults.TRAD_CHINESE_DEFAULT		
multiStateObjects	MultiStateObjects <i>MultiStateObject</i>	readonly	A col obje
nestedGrepStyles	NestedGrepStyles <i>NestedGrepStyle</i>	readonly	A col GREP
nestedLineStyles	NestedLineStyles <i>NestedLineStyle</i>	readonly	A col style
nestedStyles	NestedStyles <i>NestedStyle</i>	readonly	A col style
noBreak	Boolean	read/write	If tru the s
notes	Notes <i>Note</i>	readonly	A col
numberingAlignment	ListAlignment ListAlignment.CENTER_ALIGN ListAlignment.LEFT_ALIGN ListAlignment.RIGHT_ALIGN	read/write	The i num
numberingApplyRestartPolicy	Boolean	read/write	If tru num
numberingCharacterStyle	CharacterStyle String	read/write	The i used strin Char
numberingContinue	Boolean	read/write	Cont at th
numberingExpression	String	read/write	The i expr
numberingFormat	NumberingStyle NumberingStyle.ARABIC NumberingStyle.ARABIC_ABJAD NumberingStyle.ARABIC_ALIF_BA_TAH NumberingStyle.DOUBLE_LEADING_ZEROS NumberingStyle.FORMAT_NONE NumberingStyle.HEBREW_BIBLICAL NumberingStyle.HEBREW_NON_STANDARD NumberingStyle.KANJI NumberingStyle.KATAKANA_MODERN NumberingStyle.KATAKANA_TRADITIONAL NumberingStyle.LOWER_LETTERS NumberingStyle.LOWER_ROMAN NumberingStyle.SINGLE_LEADING_ZEROS NumberingStyle.TRIPLE_LEADING_ZEROS NumberingStyle.UPPER_LETTERS NumberingStyle.UPPER_ROMAN String	read/write	Num optic Num enur
numberingLevel	Number	read/write	The l para
numberingRestartPolicies	NumberingRestartPolicy	readonly	Num polic
numberingResultNumber	Number	readonly	The i value
numberingStartAt	Number	read/write	Dete num list.
opentypeFeatures	Array of 2 Strings Array of LongIntegers	read/write	Ope retur Strin

Property	Type	Access	Desc
otfContextualAlternate	Boolean	read/write	If true, alter OpenType
otfDiscretionaryLigature	Boolean	read/write	If true, ligature fonts
otfFigureStyle	OTFFigureStyle OTFFigureStyle.DEFAULT_VALUE OTFFigureStyle.PROPORTIONAL_LINING OTFFigureStyle.PROPORTIONAL_OLDSTYLE OTFFigureStyle.TABULAR_LINING OTFFigureStyle.TABULAR_OLDSTYLE	read/write	The 1 Open
otfFraction	Boolean	read/write	If true, Oper
otfHVKana	Boolean	read/write	If true, fonts diffe horiz
otfHistorical	Boolean	read/write	If true, form
otfJustificationAlternate	Boolean	read/write	If true, justif Open
otfLocale	Boolean	read/write	If true, form
otfMark	Boolean	read/write	If true, posit font
otfOrdinal	Boolean	read/write	If true, Oper
otfOverlapSwash	Boolean	read/write	If true, swas font
otfProportionalMetrics	Boolean	read/write	If true, prop in Op
otfRomanItalics	Boolean	read/write	If true, half-
otfSlashedZero	Boolean	read/write	If true, zero
otfStretchedAlternate	Boolean	read/write	If true, alter Open
otfStylisticAlternate	Boolean	read/write	If true, alter Open
otfStylisticSets	Number	read/write	The : Open
otfSwash	Boolean	read/write	If true, in Op
otfTitling	Boolean	read/write	If true, in Op
ovals	Ovals <i>Oval</i>	readonly	A col
overprintFill	Boolean	read/write	If true, char
overprintStroke	Boolean	read/write	If true, char
pageItems	PageItems <i>PageItem</i>	readonly	The whic proc cont docu grou

Property	Type	Access	Description
paragraphBorderBottomLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The : bott recta
paragraphBorderBottomLeftCornerRadius	Number String	read/write	The : mea: corn the b recta
paragraphBorderBottomLineWeight	Number String	read/write	The l the b
paragraphBorderBottomOffset	Number String	read/write	The : bott para,
paragraphBorderBottomOrigin	ParagraphBorderBottomOriginEnum ParagraphBorderBottomOriginEnum.BASELINE_BOTTOM_ORIGIN ParagraphBorderBottomOriginEnum.DESCENT_BOTTOM_ORIGIN	read/write	The l base the b para,
paragraphBorderBottomRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The : bott recta
paragraphBorderBottomRightCornerRadius	Number String	read/write	The : mea: corn the b recta
paragraphBorderColor	Swatch String	read/write	The : grad ink) ; para, retur
paragraphBorderDisplayIfSplits	Boolean	read/write	If tru bord the p para, fram
paragraphBorderGapColor	Swatch String	read/write	The : grad ink) ; para, Note bord Can i Strin
paragraphBorderGapOverprint	Boolean	read/write	If tru bord Note bord
paragraphBorderGapTint	Number (range 0 - 100)	read/write	The i of th gap. wher not s 100)
paragraphBorderLeftLineWeight	Number String	read/write	The l bord
paragraphBorderLeftOffset	Number String	read/write	The : left e bord

Property	Type	Access	Desc
paragraphBorderOn	Boolean	read/write	If true, the border is visible.
paragraphBorderOverprint	Boolean	read/write	If true, the border is overprinted.
paragraphBorderRightLineWeight	Number String	read/write	The line weight of the right border.
paragraphBorderRightOffset	Number String	read/write	The offset of the right border from the paragraph.
paragraphBorderStrokeEndCap	EndCap EndCap.BUTT_END_CAP EndCap.PROJECTING_END_CAP EndCap.ROUND_END_CAP	read/write	The end cap of the paragraph border stroke.
paragraphBorderStrokeEndJoin	EndJoin EndJoin.BEVEL_END_JOIN EndJoin.MITER_END_JOIN EndJoin.ROUND_END_JOIN	read/write	The end join of the paragraph border stroke.
paragraphBorderTint	Number (range 0 - 100)	read/write	The tint of the border color.
paragraphBorderTopLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-left corner of the paragraph border.
paragraphBorderTopLeftCornerRadius	Number String	read/write	The radius of the top-left corner of the paragraph border.
paragraphBorderTopLineWeight	Number String	read/write	The line weight of the top border.
paragraphBorderTopOffset	Number String	read/write	The offset of the top border from the paragraph.
paragraphBorderTopOrigin	ParagraphBorderTopOriginEnum ParagraphBorderTopOriginEnum.ASCENT_TOP_ORIGIN ParagraphBorderTopOriginEnum.BASELINE_TOP_ORIGIN ParagraphBorderTopOriginEnum.LEADING_TOP_ORIGIN	read/write	The origin of the top border.
paragraphBorderTopRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-right corner of the paragraph border.
paragraphBorderTopRightCornerRadius	Number String	read/write	The radius of the top-right corner of the paragraph border.
paragraphBorderType	StrokeStyle String	read/write	The stroke style of the paragraph border.
paragraphBorderWidth	ParagraphBorderEnum ParagraphBorderEnum.COLUMN_WIDTH	read/write	The width of the paragraph border.

Property	Type	Access	Description
	ParagraphBorderEnum.TEXT_WIDTH		calculates the width of the paragraph border
paragraphDirection	ParagraphDirectionOptions ParagraphDirectionOptions.LEFT_TO_RIGHT_DIRECTION ParagraphDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	Paragraph direction
paragraphGyoudori	Boolean	read/write	If true, gyoudori is applied to the paragraph. Gyoudori is a Japanese text alignment method where each line of text is aligned to the right margin.
paragraphJustification	ParagraphJustificationOptions ParagraphJustificationOptions.ARABIC_JUSTIFICATION ParagraphJustificationOptions.DEFAULT_JUSTIFICATION ParagraphJustificationOptions.NASKH_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION_FRAC ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION_FRAC	read/write	Paragraph justification
paragraphKashidaWidth	Number	read/write	Paragraph kashida width. 0 is recommended.
paragraphShadingBottomLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The shading bottom-left corner option.
paragraphShadingBottomLeftCornerRadius	Number String	read/write	The shading bottom-left corner radius. The measurement is in units of the bounding rectangle.
paragraphShadingBottomOffset	Number String	read/write	The shading bottom offset. The measurement is in units of the bounding rectangle.
paragraphShadingBottomOrigin	ParagraphShadingBottomOriginEnum ParagraphShadingBottomOriginEnum.BASELINE_BOTTOM_ORIGIN ParagraphShadingBottomOriginEnum.DESCENT_BOTTOM_ORIGIN	read/write	The shading bottom origin. The baseline is the top of the paragraph.
paragraphShadingBottomRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The shading bottom-right corner option.
paragraphShadingBottomRightCornerRadius	Number String	read/write	The shading bottom-right corner radius. The measurement is in units of the bounding rectangle.
paragraphShadingClipToFrame	Boolean	read/write	If true, the shading is clipped to the frame of the paragraph.
paragraphShadingColor	Swatch String	read/write	The shading color. The color is a gradient (ink) of the paragraph color.
paragraphShadingLeftOffset	Number String	read/write	The shading left offset. The measurement is in units of the bounding rectangle.
paragraphShadingOn	Boolean	read/write	If true, the shading is applied to the paragraph.

Property	Type	Access	Description
paragraphShadingOverprint	Boolean	read/write	If true, the shading is printed.
paragraphShadingRightOffset	Number String	read/write	The offset of the right shading from the right edge of the paragraph.
paragraphShadingSuppressPrinting	Boolean	read/write	If true, the shading is not printed.
paragraphShadingTint	Number (range 0 - 100)	read/write	The tint of the shading (0 = black, 100 = white).
paragraphShadingTopLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-left corner of the shading rectangle.
paragraphShadingTopLeftCornerRadius	Number String	read/write	The radius of the top-left corner of the shading rectangle.
paragraphShadingTopOffset	Number String	read/write	The offset of the top shading from the top edge of the paragraph.
paragraphShadingTopOrigin	ParagraphShadingTopOriginEnum ParagraphShadingTopOriginEnum.ASCENT_TOP_ORIGIN ParagraphShadingTopOriginEnum.BASELINE_TOP_ORIGIN ParagraphShadingTopOriginEnum.LEADING_TOP_ORIGIN	read/write	The origin of the top shading (ascender, baseline, or leading).
paragraphShadingTopRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-right corner of the shading rectangle.
paragraphShadingTopRightCornerRadius	Number String	read/write	The radius of the top-right corner of the shading rectangle.
paragraphShadingWidth	ParagraphShadingWidthEnum ParagraphShadingWidthEnum.COLUMN_WIDTH ParagraphShadingWidthEnum.TEXT_WIDTH	read/write	The width of the shading (column width or text width).
paragraphs	Paragraphs <i>Paragraph</i>	readonly	A collection of paragraphs.
parent	Cell Change Character EndnoteTextFrame Footnote InsertionPoint Line Note Paragraph Story Text TextColumn TextFrame	readonly	The parent object of the paragraph.

Property	Type	Access	Desc
	TextPath TextStyleRange Word XMLElement HiddenText XmlStory		
parentStory	Story	readonly	The : the t
parentTextFrames	Array of TextFrames Array of TextPaths <i>TextPath</i>	readonly	An a fram text. Textf
pointSize	Number String	read/write	The 1
polygons	Polygons <i>Polygon</i>	readonly	A col
position	Position Position.NORMAL Position.OT_DENOMINATOR Position.OT_NUMERATOR Position.OT_SUBSCRIPT Position.OT_SUPERSCRIPT Position.SUBSCRIPT Position.SUPERSCRIPT	read/write	The 1 to th
positionalForm	PositionalForms PositionalForms.CALCULATE PositionalForms.FINAL PositionalForms.INITIAL PositionalForms.ISOLATED PositionalForms.MEDIAL PositionalForms.NONE	read/write	The 1 form
preferences	Preferences <i>Preference</i>	readonly	A col prefe
properties	Object	read/write	A pro setti prop time
providerHyphenationStyle	HyphenationStyleEnum HyphenationStyleEnum.HYPH_AESTHETIC HyphenationStyleEnum.HYPH_ALL HyphenationStyleEnum.HYPH_ALL_BUT_UNAESTHETIC HyphenationStyleEnum.HYPH_PREFERRED_AESTHETIC	read/write	The 1 chos
radioButtons	RadioButtons <i>RadioButton</i>	readonly	A col buttc
rectangles	Rectangles <i>Rectangle</i>	readonly	A col
rensuuji	Boolean	read/write	If tru brea false betw digit
rightIndent	Number String	read/write	The 1 inde
rotateSingleByteCharacters	Boolean	read/write	If tru char:
rubyAlignment	RubyAlignments RubyAlignments.RUBY_1_AKI RubyAlignments.RUBY_CENTER RubyAlignments.RUBY_EQUAL_AKI RubyAlignments.RUBY_FULL_JUSTIFY RubyAlignments.RUBY_JIS RubyAlignments.RUBY_LEFT RubyAlignments.RUBY_RIGHT	read/write	The 1
rubyAutoAlign	Boolean	read/write	If tru
rubyAutoScaling	Boolean	read/write	If tru scale spec pare

Property	Type	Access	Desc
			infor a per scali
rubyAutoTcyAutoScale	Boolean	read/write	If tru scale (tate to fit
rubyAutoTcyDigits	Number	read/write	The i inclu chuu
rubyAutoTcyIncludeRoman	Boolean	read/write	If tru char: (tate
rubyFill	Swatch String	read/write	The : grad ink) ; ruby retur
rubyFlag	Boolean	read/write	If tru
rubyFont	Font String	read/write	The i char: Font
rubyFontSize	Number	read/write	The : char:
rubyFontStyle	String NothingEnum.NOTHING	read/write	The i char: Strin enur
rubyOpenTypePro	Boolean	read/write	If tru font:
rubyOverhang	Boolean	read/write	If tru over amo on sp see r amo
rubyOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The i over
rubyOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The i over strok
rubyParentOverhangAmount	RubyOverhang RubyOverhang.NONE RubyOverhang.RUBY_OVERHANG_HALF_CHAR RubyOverhang.RUBY_OVERHANG_HALF_RUBY RubyOverhang.RUBY_OVERHANG_NO_LIMIT RubyOverhang.RUBY_OVERHANG_ONE_CHAR RubyOverhang.RUBY_OVERHANG_ONE_RUBY	read/write	The i ruby over
rubyParentScalingPercent	Number	read/write	The i perc pare dete size.
rubyParentSpacing	RubyParentSpacing RubyParentSpacing.RUBY_PARENT_121_AKI RubyParentSpacing.RUBY_PARENT_BOTH_SIDES RubyParentSpacing.RUBY_PARENT_EQUAL_AKI RubyParentSpacing.RUBY_PARENT_FULL_JUSTIFY RubyParentSpacing.RUBY_PARENT_NO_ADJUSTMENT	read/write	The i to th
rubyPosition	RubyKantenPosition RubyKantenPosition.ABOVE_RIGHT RubyKantenPosition.BELOW_LEFT	read/write	The i char: pare

Property	Type	Access	Description
rubyString	String	read/write	The ruby string.
rubyStroke	Swatch String	read/write	The stroke color (in hex or name) of the ruby stroke. Returns the stroke color if the stroke is not set.
rubyStrokeTint	Number	read/write	The stroke tint (percentage) of the ruby stroke.
rubyTint	Number (range 0 - 100)	read/write	The tint (percentage) of the ruby text. (Range 0-100)
rubyType	RubyTypes RubyTypes.GROUP_RUBY RubyTypes.PER_CHARACTER_RUBY	read/write	The ruby type.
rubyWeight	Number	read/write	The weight of the ruby text.
rubyXOffset	Number	read/write	The x offset of the ruby text.
rubyXScale	Number	read/write	The x scale of the ruby text.
rubyYOffset	Number	read/write	The y offset of the ruby text.
rubyYScale	Number	read/write	The y scale of the ruby text.
ruleAbove	Boolean	read/write	If true, the rule is above the text.
ruleAboveColor	Swatch String	read/write	The color of the rule above the text. Returns the color if the rule is not set.
ruleAboveGapColor	Swatch String	read/write	The color of the gap above the rule. Returns the color if the gap is not set.
ruleAboveGapOverprint	Boolean	read/write	If true, the gap will be overprinted. Only valid if the gap is not set.
ruleAboveGapTint	Number (range 0 - 100)	read/write	The tint (percentage) of the gap above the rule. (Range 0-100) Valid only if the gap is not set.
ruleAboveLeftIndent	Number String	read/write	The left indent of the rule. Returns the left indent if the rule is not set.
ruleAboveLineWeight	Number String	read/write	The line weight of the rule above the text.

Property	Type	Access	Desc
ruleAboveOffset	Number String	read/write	The i para from first
ruleAboveOverprint	Boolean	read/write	If tru abov
ruleAboveRightIndent	Number String	read/write	The i right para (base width width the p
ruleAboveTint	Number (range 0 - 100)	read/write	The t of th abov
ruleAboveType	StrokeStyle String	read/write	The : abov retur Strin
ruleAboveWidth	RuleWidth RuleWidth.COLUMN_WIDTH RuleWidth.TEXT_WIDTH	read/write	The l colu calcu para
ruleBelow	Boolean	read/write	If tru para
ruleBelowColor	Swatch String	read/write	The : grad ink) ; para retur
ruleBelowGapColor	Swatch String	read/write	The : grad ink) ; gap c below when below Can i Strin
ruleBelowGapOverprint	Boolean	read/write	If tru the r over
ruleBelowGapTint	Number (range 0 - 100)	read/write	The t of th the p (Ran Valid para is no
ruleBelowLeftIndent	Number String	read/write	The i left e rule eithe the c last l
ruleBelowLineWeight	Number String	read/write	The l below
ruleBelowOffset	Number String	read/write	The i the p from last l
ruleBelowOverprint	Boolean	read/write	If tru over
ruleBelowRightIndent	Number String	read/write	The i right

Property	Type	Access	Desc
			para: (base width) width of the p
ruleBelowTint	Number (range 0 - 100)	read/write	The t of th below
ruleBelowType	StrokeStyle String	read/write	The : below retur Strin
ruleBelowWidth	RuleWidth RuleWidth.COLUMN_WIDTH RuleWidth.TEXT_WIDTH	read/write	The l colu calcu para:
sameParaStyleSpacing	Unit Spacing Spacing.SETIGNORE	read/write	The : para: style Spac
scaleAffectsLineHeight	Boolean	read/write	If tru size \ scale
shataiAdjustRotation	Boolean	read/write	If tru rotat
shataiAdjustTsume	Boolean	read/write	If tru tsum
shataiDegreeAngle	Number	read/write	The : degr
shataiMagnification	Number	read/write	The : perc oblic
signatureFields	SignatureFields <i>SignatureField</i>	readonly	A col field:
singleWordJustification	SingleWordJustification SingleWordJustification.CENTER_ALIGN SingleWordJustification.FULLY_JUSTIFIED SingleWordJustification.LEFT_ALIGN SingleWordJustification.RIGHT_ALIGN	read/write	The : lines worc
skew	Number	read/write	The : Para:
spaceAfter	Number String	read/write	The l para:
spaceBefore	Number String	read/write	The l para:
spanColumnMinSpaceAfter	Number String	read/write	The l a spa
spanColumnMinSpaceBefore	Number String	read/write	The l befo colu
spanColumnType	SpanColumnTypeOptions SpanColumnTypeOptions.SINGLE_COLUMN SpanColumnTypeOptions.SPAN_COLUMNS SpanColumnTypeOptions.SPLIT_COLUMNS	read/write	Whe shou span colu
spanSplitColumnCount	ShortInteger(1-40) SpanColumnCountOptions SpanColumnCountOptions.ALL	read/write	The l para: num Can (1 - 4 Span enur
splineItems	SplineItems <i>SplineItem</i>	readonly	The : colle
splitColumnInsideGutter	Number String	read/write	The i para:

Property	Type	Access	Desc
splitColumnOutsideGutter	Number String	read/write	The c para
startParagraph	StartParagraph StartParagraph.ANYWHERE StartParagraph.NEXT_COLUMN StartParagraph.NEXT_EVEN_PAGE StartParagraph.NEXT_FRAME StartParagraph.NEXT_ODD_PAGE StartParagraph.NEXT_PAGE	read/write	The l start
strikeThroughColor	Swatch String	read/write	The : grad ink) ; strike retur
strikeThroughGapColor	Swatch String	read/write	The : grad ink) ; the s Can i Strin
strikeThroughGapOverprint	Boolean	read/write	If tru the s will c when is no
strikeThroughGapTint	Number (range 0 - 100)	read/write	The t of th strok to 10 strike solid
strikeThroughOffset	Number String	read/write	The : offse strok base
strikeThroughOverprint	Boolean	read/write	If tru strok
strikeThroughTint	Number (range 0 - 100)	read/write	The t of th strok
strikeThroughType	StrokeStyle String	read/write	The : strike retur Strin
strikeThroughWeight	Number String	read/write	The : strike
strikeThru	Boolean	read/write	If tru strike the t
strokeAlignment	TextStrokeAlign TextStrokeAlign.CENTER_ALIGNMENT TextStrokeAlign.OUTSIDE_ALIGNMENT	read/write	The : appli
strokeColor	Swatch String	read/write	The : grad ink) ; of th acce
strokeTint	Number (range 0 - 100)	read/write	The t of th Para tint p num to 10 inhe valu

Property	Type	Access	Desc
strokeWeight	Number String	read/write	The : to th text.
styleOverridden	Boolean	readonly	If tru has b addi
tabList	Array of Arrays of Property Name/Value Pairs.	read/write	A list the p retur Prop Pairs
tabStops	TabStops <i>TabStop</i>	readonly	A col
tables	Tables <i>Table</i>	readonly	A col
tatechuyoko	Boolean	read/write	If tru char: verti
tatechuyokoXOffset	Number	read/write	The l horiz verti
tatechuyokoYOffset	Number	read/write	The v horiz verti
textBoxes	TextBoxes	readonly	A col
textColumns	TextColumns <i>TextColumn</i>	readonly	A col colur
textFrames	TextFrames <i>TextFrame</i>	readonly	A col fram
textStyleRanges	TextStyleRanges <i>TextStyleRange</i>	readonly	A col rang
textVariableInstances	TextVariableInstances <i>TextVariableInstance</i>	readonly	A col varia
texts	Texts <i>Text</i>	readonly	A col obje
tracking	Number	read/write	The : loose of te thou
trailingAki	Number	read/write	The : each
treatIdeographicSpaceAsSpace	Boolean	read/write	If tru will r line l
tsume	Number	read/write	The : char:
underline	Boolean	read/write	If tru text.
underlineColor	Swatch String	read/write	The : grad ink) ; unde retur
underlineGapColor	Swatch String	read/write	The : grad ink) ; the u Note unde solid or St
underlineGapOverprint	Boolean	read/write	If tru the u over

Property	Type	Access	Desc
underlineGapTint	Number (range 0 - 100)	read/write	The i of th unde 0 to whei not s
underlineOffset	Number String	read/write	The i offse the t
underlineOverprint	Boolean	read/write	If tru strok
underlineTint	Number (range 0 - 100)	read/write	The i (as a 0 to
underlineType	StrokeStyle String	read/write	The i unde retur Strin
underlineWeight	Number String	read/write	The i unde
verticalScale	Number	read/write	The i appli
warichu	Boolean	read/write	If tru
warichuAlignment	WarichuAlignment WarichuAlignment.AUTO WarichuAlignment.CENTER_ALIGN WarichuAlignment.CENTER_JUSTIFIED WarichuAlignment.FULLY_JUSTIFIED WarichuAlignment.LEFT_ALIGN WarichuAlignment.LEFT_JUSTIFIED WarichuAlignment.RIGHT_ALIGN WarichuAlignment.RIGHT_JUSTIFIED	read/write	The i
warichuCharsAfterBreak	Number	read/write	The i char: line l
warichuCharsBeforeBreak	Number	read/write	The i char: a line
warichuLineSpacing	Number	read/write	The i wari
warichuLines	Number	read/write	The i wari norm
warichuSize	Number	read/write	The i perc pare dete
words	Words <i>Word</i>	readonly	A col
xOffsetDiacritic	Number	read/write	The i for d
yOffsetDiacritic	Number	read/write	The i diacr

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional)

Parameter	Type	Description
		(default: false)

undefined **applyCharacterStyle** (using:*CharacterStyle*)

Apply a character style.

Parameter	Type	Description
using	<i>CharacterStyle</i>	The character style to apply.

undefined **applyConditions** (using:*Array of Condition*, [removeExisting:*Boolean*=Boolean])

Apply one or more conditions.

Parameter	Type	Description
using	<i>Array of Condition</i>	The condition(s) to apply
removeExisting	<i>Boolean</i>	If true, remove existing conditions. (Optional) (default: false)

undefined **applyParagraphStyle** (using:*ParagraphStyle*, [clearingOverrides:*Boolean*=Boolean])

Apply a paragraph style.

Parameter	Type	Description
using	<i>ParagraphStyle</i>	The paragraph style to apply.
clearingOverrides	<i>Boolean</i>	If true, clear any text attributes before applying the style. (Optional) (default: true)

BackgroundTask **asynchronousExportFile** (format:*Varies ExportFormat String*, to:*File*, [showingOptions:*Boolean*=Boolean], using:*PDFExportPreset*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

asynchronously exports the object(s) to a file.

Parameter	Type	Description
format	<i>ExportFormat</i> ExportFormat.EPS_TYPE ExportFormat.EPUB ExportFormat.FIXED_LAYOUT_EPUB ExportFormat.HTML ExportFormat.HTMLFXL ExportFormat.INCOPY_MARKUP ExportFormat.INDESIGN_MARKUP ExportFormat.INDESIGN_SNIPPET ExportFormat.INTERACTIVE_PDF ExportFormat.JPG ExportFormat.PDF_TYPE ExportFormat.PNG_FORMAT ExportFormat.RTF ExportFormat.TAGGED_TEXT ExportFormat.TEXT_TYPE ExportFormat.XML <i>String</i>	The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String.
to	<i>File</i>	The path to the export file.
showingOptions	<i>Boolean</i>	If true, displays the export options dialog. (Optional) (default: false)
using	<i>PDFExportPreset</i>	The export style. (Optional)
versionComments	<i>String</i>	The comment for this version. (Optional)
forceSave	<i>Boolean</i>	If true, forcibly saves a version. (Optional) (default: false)

undefined **autoTag** ()

Tag the object or the parent story using default tags defined in XML preference.

Text **changeGlyph** (reverseOrder:*Boolean*)

Finds glyphs that match the find what value and replaces the glyphs with the change to value.

Parameter	Type	Description
reverseOrder	<i>Boolean</i>	If true, returns the results in reverse order. (Optional)

Text **changeGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeText** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value and replaces the text with the change character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

undefined **changeCase** (using:*ChangeCaseMode*)

Sets the case of the text.

Parameter	Type	Description
using	<i>ChangeCaseMode</i> ChangeCaseMode.LOWERCASE ChangeCaseMode.SENTENCECASE ChangeCaseMode.TITLECASE ChangeCaseMode.UPPERCASE	The text case option.

undefined **clearOverrides** ([overridesToClear:*OverrideType*=OverrideType])

Clears the specified types of override.

Parameter	Type	Description
overridesToClear	<i>OverrideType</i> OverrideType.ALL OverrideType.CHARACTER_ONLY OverrideType.PARAGRAPH_ONLY	The types of override to clear. (Optional) (default: OverrideType.ALL)

undefined **convertBulletsAndNumberingToText** ()

Convert bullets and numbering to text.

Note **convertToNote** ()

Converts the text to a note.

Table **convertToTable** (columnSeparator:*String*, rowSeparator:*String*, [numberOfColumns:*Number*=Number])

Converts the text to a table.

Parameter	Type	Description
columnSeparator	String	The character that starts a new column in the new table. (Optional)
rowSeparator	String	The character starts a new row in the new table. (Optional)
numberOfColumns	Number	The number of columns in the table. Note: Valid only when the column and row separator characters are the same. (Optional) (default: 1)

undefined **createEmailQRCode** (emailAddress:*String*, subject:*String*, body:*String*, qrCodeSwatch:*Varies Swatch String*, withProperties:*Array of String*)

Create Email QR Code on the page item or document

Parameter	Type	Description
emailAddress	String	QR code Email Address (Optional)
subject	String	QR code Email Subject (Optional)
body	String	QR code Email Body Message (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Paragraph. Above parameters can also be passed as properties (Optional)

undefined **createHyperlinkQRCode** (urlLink:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Hyperlink QR Code on the page item or document

Parameter	Type	Description
urlLink	String	QR code Hyperlink URL (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Paragraph. Above parameters can also be passed as properties (Optional)

PageItem **createOutlines** ([deleteOriginal:Boolean=Boolean])

Converts text to outlines. Each line of text becomes a polygon object. When the converted text is a single letter that has no internal spaces or detached parts, the polygon contains only a single path. Note: To determine whether a font allows the creation of outlines, see allow outlines.

Parameter	Type	Description
deleteOriginal	Boolean	If true, deletes the original text. If false, creates the outlines as separate object(s) on top of the text. (Optional) (default: true)

undefined **createPlainTextQRCode** (plainText:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Plain Text QR Code on the page item

Parameter	Type	Description
plainText	String	QR code Plain Text (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Paragraph. Above parameters can also be passed as properties (Optional)

Boolean **createStyleThumbnailWithProperties** (previewText:String, pointSize:Number, space:ColorSpace, colorValue:Array of Number, to:File, charOrParaStyle:StyleType)

Create thumbnail for selected text using the applied style and overrides with the given properties.

Parameter	Type	Description
previewText	String	Text to use as sample
pointSize	Number	Text font size (in points)
space	ColorSpace ColorSpace.CMYK ColorSpace.HSB ColorSpace.LAB ColorSpace.MIXEDINK ColorSpace.RGB	Color space RGB, CMYK or LAB
colorValue	Array of Number	Color values
to	File	The path to the export file.
charOrParaStyle	StyleType StyleType.CHARACTER_STYLE_TYPE StyleType.PARAGRAPH_STYLE_TYPE	The applied style type to use.

undefined **createTextMsgQRCode** (cellNumber:String, textMessage:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Text Msg QR Code on the page item or document

Parameter	Type	Description
cellNumber	String	QR code Text Phone Number (Optional)
textMessage	String	QR code Text Message (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Paragraph. Above parameters can also be passed as properties (Optional)

Boolean **createThumbnailWithProperties** (previewText:String, pointSize:Number, space:ColorSpace, colorValue:Array of Number, to:File)

Create thumbnail for selected text with the given properties.

Parameter	Type	Description
previewText	String	Text to use as sample

Parameter	Type	Description
pointSize	Number	Text font size (in points)
space	ColorSpace ColorSpace.CMYK ColorSpace.HSB ColorSpace.LAB ColorSpace.MIXEDINK ColorSpace.RGB	Color space RGB, CMYK or LAB
colorValue	Array of Number	Color values
to	File	The path to the export file.

undefined **createVCardQRCode** (firstName:String, lastName:String, jobTitle:String, cellPhone:String, phone:String, email:String, organisation:String, streetAddress:String, city:String, adrState:String, country:String, postalCode:String, website:String, qrCodeSwatch:Varies Swatch String, withProperties:Array of String)

Create Business Card QR Code on the page item or load on document's placegun

Parameter	Type	Description
firstName	String	QR code Business Card First Name (Optional)
lastName	String	QR code Business Card Last Name (Optional)
jobTitle	String	QR code Business Card Title (Optional)
cellPhone	String	QR code Business Card Cell Phone Number (Optional)
phone	String	QR code Business Card Phone Number (Optional)
email	String	QR code Business Card Email Address (Optional)
organisation	String	QR code Business Card Organisation (Optional)
streetAddress	String	QR code Business Card Street Address (Optional)
city	String	QR code Business Card City (Optional)
adrState	String	QR code Business Card State (Optional)
country	String	QR code Business Card Country (Optional)
postalCode	String	QR code Business Card Postal Code (Optional)
website	String	QR code Business Card URL (Optional)
qrCodeSwatch	Swatch String	Swatch to be applied on generated QR Code Graphic . Can accept: Swatch or String. (Optional)
withProperties	Array of String	Initial values for properties of the new Paragraph. Above parameters can also be passed as properties (Optional)

Text **duplicate** (to:LocationOptions, reference:Varies Cell Column Row Story Table Text PageItem)

Duplicates the text in the specified location.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The location relative to the reference object or within the containing object.
reference	Cell Column Row Story Table Text PageItem	The reference object. Note: Required when the to parameter specifies before or after. Can accept: Text, Story, Cell, Row, Column, Table or PageItem. (Optional)

undefined **exportFile** (format:Varies ExportFormat String, to:File, [showingOptions:Boolean=Boolean], using:PDFExportPreset, versionComments:String, [forceSave:Boolean=Boolean])

Exports the object(s) to a file.

Parameter	Type	Description
format	ExportFormat ExportFormat.EPS_TYPE ExportFormat.EPUB ExportFormat.FIXED_LAYOUT_EPUB ExportFormat.HTML	The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String.

Parameter	Type	Description
	ExportFormat.HTMLFXL ExportFormat.INCOPY_MARKUP ExportFormat.INDESIGN_MARKUP ExportFormat.INDESIGN_SNIPPET ExportFormat.INTERACTIVE_PDF ExportFormat.JPG ExportFormat.PDF_TYPE ExportFormat.PNG_FORMAT ExportFormat.RTF ExportFormat.TAGGED_TEXT ExportFormat.TEXT_TYPE ExportFormat.XML	
to	String File	The path to the export file.
showingOptions	Boolean	If true, displays the export options dialog. (Optional) (default: false)
using	PDFExportPreset	The export style. (Optional)
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

Text **findGlyph** (reverseOrder:*Boolean*)
 Finds glyphs that match the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findGrep** (reverseOrder:*Boolean*)
 Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

HyperlinkTextSource **findHyperlinks** (sortOrder:*RangeSortOrder*)
 Finds hyperlink sources that intersecting with specified text range.

Parameter	Type	Description
sortOrder	RangeSortOrder RangeSortOrder.ASCENDING_SORT RangeSortOrder.DECENDING_SORT RangeSortOrder.NO_SORT	The sort order of found ranges. (Optional)

Text **findText** (reverseOrder:*Boolean*)
 Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findTransliterate** (reverseOrder:*Boolean*)
 Finds text that matches the find character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Paragraph **getElements** ()
 Resolves the object specifier, creating an array of object references.

Boolean **isNthDesignAxisHidden** (nthAxisIndex:*Number*)
 If true, Nth design axis of variable font is hidden.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.

undefined **markup** (using:*XMLElement*)
 Associates the page item with the specified XML element while preserving existing content.

Parameter	Type	Description
using	XMLElement	The XML element.

Text **move** (to:*LocationOptions*, reference:*Varies Cell Column Row Story Table Text PageItem*)

Moves the text to the specified location.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The location relative to the reference object or within the containing object.
reference	Cell Column Row Story Table Text PageItem	The reference object. Note: Required when the to parameter specifies before or after. Can accept: Text, Story, Cell, Row, Column, Table or PageItem. (Optional)

Varies **place** (fileName:*File*, [showingOptions:*Boolean*=Boolean], withProperties:*Object*)

Places the file.

Parameter	Type	Description
fileName	File	The file to place
showingOptions	Boolean	Whether to display the import options dialog (Optional) (default: false)
withProperties	Object	Initial values for properties of the placed object(s) (Optional)

undefined **recompose** ()

Recomposes the text in the Paragraph.

undefined **remove** ()

Deletes the Paragraph.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **select** ([existingSelection:*SelectionOptions*=SelectionOptions])

Selects the object.

Parameter	Type	Description
existingSelection	SelectionOptions SelectionOptions.ADD_TO SelectionOptions.REMOVE_FROM SelectionOptions.REPLACE_WITH SelectionOptions.SET_KEY	The selection status of the Paragraph in relation to previously selected objects. (Optional) (default: SelectionOptions.REPLACE_WITH)

undefined **setNthDesignAxis** (nthAxisIndex:*Number*, nthAxisValue:*Number*)

Set Nth design axis of a variable font.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.
nthAxisValue	Number	Value of nth design axis.

undefined **showText** ()

Jump to the text range.

Boolean **textHasOverrides** (charOrParaStyle:*StyleType*, [charStyleAsOverride:*Boolean*=Boolean])

If true, text has local overrides

Parameter	Type	Description
charOrParaStyle	<i>StyleType</i> StyleType.CHARACTER_STYLE_TYPE StyleType.PARAGRAPH_STYLE_TYPE	Style type to look at.
charStyleAsOverride	<i>Boolean</i>	Whether to consider character styles as overrides or not (Optional) (default: true)

String **toSource** ()

Generates a string which, if executed, will return the Paragraph.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Bullet.parent
Character.parent
EndnoteRange.parent
Event.parent
EventListener.parent
InsertionPoint.parent
Line.parent
MutationEvent.parent
NestedGrepStyle.parent
NestedLineStyle.parent
NestedStyle.parent
NumberingRestartPolicy.parent
Paragraph.parent
Preference.parent
TabStop.parent
Table.parent
Text.parent
TextColumn.parent
TextStyleRange.parent
Word.parent

Return

Paragraph.getElements()
Paragraphs.anyItem()
Paragraphs.everyItem()
Paragraphs.nextItem()
Paragraphs.previousItem()
Paragraphs.item()
Paragraphs.[]()
Paragraphs.itemByRange()
Paragraphs.firstItem()
Paragraphs.lastItem()
Paragraphs.middleItem()
