

ParagraphStyle

A paragraph style.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [convertBulletsAndNumberingToText](#), [createThumbnailWithProperties](#), [duplicate](#), [extractLabel](#), [forceDelete](#), [getElements](#), [insertLabel](#), [isNthDesignAxisHidden](#), [move](#), [remove](#), [removeEventListener](#), [setNthDesignAxis](#), [toSource](#), [toSpecifier](#)

Objects:

[AdornmentOverprint](#), [AlternateGlyphForms](#), [BalanceLinesStyle](#), [Boolean](#), [Bullet](#), [Capitalization](#), [CharacterAlignment](#), [CharacterDirectionOptions](#), [CharacterStyle](#), [CornerOptions](#), [DiacriticPositionOptions](#), [DigitsTypeOptions](#), [EndCap](#), [EndJoin](#), [EventListeners](#), [Events](#), [Font](#), [GridAlignment](#), [HyphenationStyleEnum](#), [Justification](#), [KashidasOptions](#), [KentenAlignment](#), [KentenCharacter](#), [KentenCharacterSet](#), [KinsokuHangTypes](#), [KinsokuSet](#), [KinsokuTable](#), [KinsokuType](#), [LanguageWithVendors](#), [Leading](#), [LeadingModel](#), [ListAlignment](#), [ListType](#), [MojikumiTable](#), [MojikumiTableDefaults](#), [NestedGrepStyles](#), [NestedLineStyle](#), [NestedStyles](#), [NothingEnum](#), [Number](#), [NumberingList](#), [NumberingRestartPolicy](#), [NumberingStyle](#), [OTFFigureStyle](#), [Object](#), [OutlineJoin](#), [ParagraphBorderBottomOriginEnum](#), [ParagraphBorderEnum](#), [ParagraphBorderTopOriginEnum](#), [ParagraphDirectionOptions](#), [ParagraphJustificationOptions](#), [ParagraphShadingBottomOriginEnum](#), [ParagraphShadingTopOriginEnum](#), [ParagraphShadingWidthEnum](#), [ParagraphStyle](#), [Position](#), [PositionalForms](#), [Preferences](#), [RubyAlignments](#), [RubyKentenPosition](#), [RubyOverhang](#), [RubyParentSpacing](#), [RubyTypes](#), [RuleWidth](#), [SingleWordJustification](#), [Spacing](#), [SpanColumnCountOptions](#), [SpanColumnTypeOptions](#), [StartParagraph](#), [String](#), [StrokeStyle](#), [StyleExportTagMaps](#), [Swatch](#), [TabStops](#), [TextStrokeAlign](#), [UIColors](#), [WarichuAlignment](#)

Preferences:

[Preferences](#)

Property Listing

Property	Type	Access	Desc
alignToBaseline	Boolean	read/write	If true, the text is aligned to the baseline of the grid.
allowArbitraryHyphenation	Boolean	read/write	If true, the text can be hyphenated at any point.
appliedFont	Font String	read/write	The font used for the paragraph. Can be a string or a font object.
appliedLanguage	LanguageWithVendors LanguageCanAlsoAccept:String	read/write	The language used for the paragraph. Can be a string or a language object.
appliedNumberingList	NumberingList String	read/write	The numbering list used for the paragraph. Can be a string or a numbering list object.
autoLeading	Number (range 0 - 500)	read/write	The auto leading value for the paragraph.
autoTcy	Number	read/write	The auto tracking value for the paragraph.
autoTcyIncludeRoman	Boolean	read/write	If true, the auto tracking value is applied to Roman numerals.
balanceRaggedLines	Boolean BalanceLinesStyle BalanceLinesStyle.FULLY_BALANCED BalanceLinesStyle.NO_BALANCING BalanceLinesStyle.PYRAMID_SHAPE BalanceLinesStyle.VEE_SHAPE	read/write	If true, the lines are balanced. Can be a boolean or a balance lines style object.

Property	Type	Access	Description
basedOn	ParagraphStyle String	read/write	The base ParagraphStyle
baselineShift	Number String	read/write	The distance from the baseline to the top of the text
bulletChar	Bullet	readonly	The character used for bullets
bulletsAlignment	ListAlignment ListAlignment.CENTER_ALIGN ListAlignment.LEFT_ALIGN ListAlignment.RIGHT_ALIGN	read/write	The alignment of the bullets
bulletsAndNumberingListType	ListType ListType.BULLET_LIST ListType.NO_LIST ListType.NUMBERED_LIST	read/write	The type of the list
bulletsCharacterStyle	CharacterStyle String	read/write	The character style used for bullets
bulletsTextAfter	String	read/write	The text after the bullets
bunriKinshi	Boolean	read/write	If true, the document is a Note kinshi
capitalization	Capitalization Capitalization.ALL_CAPS Capitalization.CAP_TO_SMALL_CAP Capitalization.LOWER_CASE Capitalization.NORMAL Capitalization.SMALL_CAPS	read/write	The capitalization of the text
characterAlignment	CharacterAlignment CharacterAlignment.ALIGN_BASELINE CharacterAlignment.ALIGN_EM_BOTTOM CharacterAlignment.ALIGN_EM_CENTER CharacterAlignment.ALIGN_EM_TOP CharacterAlignment.ALIGN_ICF_BOTTOM CharacterAlignment.ALIGN_ICF_TOP	read/write	The alignment of the character
characterDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The direction of the character
characterRotation	Number	read/write	The rotation of the character
cjkGridTracking	Boolean	read/write	If true, the character is tracked
composer	String	read/write	The composer of the text
designAxes	Array of Number	read/write	The design axes of the text
desiredGlyphScaling	Number (range 50 - 200)	read/write	The desired glyph scaling of the text
desiredLetterSpacing	Number	read/write	The desired letter spacing of the text
desiredWordSpacing	Number (range 0 - 1000)	read/write	The desired word spacing of the text

Property	Type	Access	Description
			of the value
diacriticPosition	DiacriticPositionOptions DiacriticPositionOptions.DEFAULT_POSITION DiacriticPositionOptions.LOOSE_POSITION DiacriticPositionOptions.MEDIUM_POSITION DiacriticPositionOptions.OPENTYPE_POSITION DiacriticPositionOptions.OPENTYPE_POSITION_FROM_BASELINE DiacriticPositionOptions.TIGHT_POSITION	read/write	Position of the character
digitsType	DigitsTypeOptions DigitsTypeOptions.ARABIC_DIGITS DigitsTypeOptions.BENGALI_DIGITS DigitsTypeOptions.BURMESE_DIGITS DigitsTypeOptions.DEFAULT_DIGITS DigitsTypeOptions.DEVANAGARI_DIGITS DigitsTypeOptions.FARSI_DIGITS DigitsTypeOptions.FULL_FARSI_DIGITS DigitsTypeOptions.GUJARATI_DIGITS DigitsTypeOptions.GURMUKHI_DIGITS DigitsTypeOptions.HINDI_DIGITS DigitsTypeOptions.KANNADA_DIGITS DigitsTypeOptions.KHMER_DIGITS DigitsTypeOptions.LAO_DIGITS DigitsTypeOptions.MALAYALAM_DIGITS DigitsTypeOptions.NATIVE_DIGITS DigitsTypeOptions.ORIYA_DIGITS DigitsTypeOptions.TAMIL_DIGITS DigitsTypeOptions.TELUGU_DIGITS DigitsTypeOptions.THAI_DIGITS DigitsTypeOptions.TIBETAN_DIGITS	read/write	The type of digits
dropCapCharacters	Number (range 0 - 150)	read/write	The number of characters to drop
dropCapLines	Number (range 0 - 25)	read/write	The number of lines to drop
dropCapStyle	CharacterStyle String	read/write	The style of the drop cap, also
dropcapDetail	Number	read/write	Detail of the drop cap, base outline, bearing, 0x10 used grid.
emitCss	Boolean	read/write	Emit CSS
endJoin	OutlineJoin OutlineJoin.BEVEL_END_JOIN OutlineJoin.MITER_END_JOIN OutlineJoin.ROUND_END_JOIN	read/write	The style of the end join, applied to the
epubAriaRole	String	read/write	The role of the element, recorded
eventListeners	EventListeners EventListener	readonly	A collection of event listeners
events	Events Event	readonly	A collection of events
fillColor	Swatch String	read/write	The fill color of the gradient (ink) or the fill color
fillTint	Number (range 0 - 100)	read/write	The tint of the fill color, Parameter specification of 0 is in the value

Property	Type	Access	Desc
firstLineIndent	Number String	read/write	The i first
fontStyle	String	read/write	The i style
glyphForm	AlternateGlyphForms AlternateGlyphForms.EXPERT_FORM AlternateGlyphForms.FULL_WIDTH_FORM AlternateGlyphForms.JIS04_FORM AlternateGlyphForms.JIS78_FORM AlternateGlyphForms.JIS83_FORM AlternateGlyphForms.JIS90_FORM AlternateGlyphForms.MONOSPACED_HALF_WIDTH_FORM AlternateGlyphForms.NLC_FORM AlternateGlyphForms.NONE AlternateGlyphForms.PROPORTIONAL_WIDTH_FORM AlternateGlyphForms.QUARTER_WIDTH_FORM AlternateGlyphForms.THIRD_WIDTH_FORM AlternateGlyphForms.TRADITIONAL_FORM	read/write	The i subs glyph
gradientFillAngle	Number	read/write	The i grad of th to 18
gradientFillLength	Number	read/write	The l grad radia the f
gradientFillStart	Array of Number Array of String	read/write	The i coor appli text,
gradientStrokeAngle	Number	read/write	The i grad strok -180
gradientStrokeLength	Number	read/write	The l grad radia the s
gradientStrokeStart	Array of Number Array of String	read/write	The i coor appli the t y].
gridAlignFirstLineOnly	Boolean	read/write	If tru line t base align
gridAlignment	GridAlignment GridAlignment.ALIGN_BASELINE GridAlignment.ALIGN_EM_BOTTOM GridAlignment.ALIGN_EM_CENTER GridAlignment.ALIGN_EM_TOP GridAlignment.ALIGN_ICF_BOTTOM GridAlignment.ALIGN_ICF_TOP GridAlignment.NONE	read/write	The i fram grid.
gridGyoudori	Number	read/write	The i settti
horizontalScale	Number	read/write	The l appli Para
hyphenWeight	Number (range 0 - 10)	read/write	The i bette hyph resul hyph 100)

Property	Type	Access	Desc
hyphenateAcrossColumns	Boolean	read/write	If true, words will be hyphenated across columns.
hyphenateAfterFirst	Number (range 1 - 15)	read/write	The number of letters after the first letter of a word before a hyphen is placed.
hyphenateBeforeLast	Number (range 1 - 15)	read/write	The number of letters before the last letter of a word before a hyphen is placed.
hyphenateCapitalizedWords	Boolean	read/write	If true, capitalized words will be hyphenated.
hyphenateLadderLimit	Number (range 0 - 25)	read/write	The number of hyphens on a ladder of specified words. Consists of zero or more hyphens.
hyphenateLastWord	Boolean	read/write	If true, the last word of a paragraph will be hyphenated. Note: This property is not supported in all versions of the software.
hyphenateWordsLongerThan	Number (range 3 - 25)	read/write	The number of letters in a word before it is hyphenated.
hyphenation	Boolean	read/write	If true, hyphenation is enabled.
hyphenationZone	Number String	read/write	The number of spaces of a line of text before the hyphenation zone begins. The number of spaces of a line of text before the hyphenation zone begins.
id	Number	readonly	The ID of the paragraph.
ignoreEdgeAlignment	Boolean	read/write	If true, edge alignment is ignored for the paragraph.
imported	Boolean	readonly	If true, the paragraph is imported from a document.
includeClass	Boolean	read/write	If true, the paragraph is included in the global class.
index	Number	readonly	The index of the paragraph in the content.
isValid	Boolean	readonly	Return true if the paragraph is a valid object.
jidori	Number	read/write	The number of squares in the array.
justification	Justification Justification.AWAY_FROM_BINDING_SIDE Justification.CENTER_ALIGN Justification.CENTER_JUSTIFIED Justification.FULLY_JUSTIFIED Justification.LEFT_ALIGN Justification.LEFT_JUSTIFIED Justification.RIGHT_ALIGN Justification.RIGHT_JUSTIFIED	read/write	The justification of the paragraph.

Property	Type	Access	Desc
	Justification.TO_BINDING_SIDE		
kashidas	KashidasOptions KashidasOptions.DEFAULT_KASHIDAS KashidasOptions.KASHIDAS_OFF	read/write	Use i justil
keepAllLinesTogether	Boolean	read/write	If tru the p false to br colou
keepFirstLines	Number (range 1 - 50)	read/write	The i lines para, a pag
keepLastLines	Number (range 1 - 50)	read/write	The i lines para, brea
keepLinesTogether	Boolean	read/write	If tru num wher brea text
keepRuleAboveInFrame	Boolean	read/write	If tru abov rema bour wher
keepWithNext	Number (range 0 - 5)	read/write	The i lines para,
keepWithPrevious	Boolean	read/write	If the para, with prev
kentenAlignment	KentenAlignment KentenAlignment.ALIGN_KENTEN_CENTER KentenAlignment.ALIGN_KENTEN_LEFT	read/write	The i char; pare
kentenCharacterSet	KentenCharacterSet KentenCharacterSet.CHARACTER_INPUT KentenCharacterSet.JIS KentenCharacterSet.KUTEN KentenCharacterSet.SHIFT_JIS KentenCharacterSet.UNICODE	read/write	The i the c char; wher custo
kentenCustomCharacter	String	read/write	The i kent; wher custo
kentenFillColor	Swatch String	read/write	The i grad ink); kent; retur
kentenFont	Font String	read/write	The i char; Font
kentenFontSize	Number	read/write	The i kent;
kentenFontStyle	String NothingEnum.NOTHING	read/write	The i char; Strin enur
kentenKind	KentenCharacter KentenCharacter.CUSTOM KentenCharacter.KENTEN_BLACK_CIRCLE KentenCharacter.KENTEN_BLACK_TRIANGLE KentenCharacter.KENTEN_BULLSEYE	read/write	The i char;

Property	Type	Access	Desc
	KentenCharacter.KENTEN_FISHEYE KentenCharacter.KENTEN_SESAME_DOT KentenCharacter.KENTEN_SMALL_BLACK_CIRCLE KentenCharacter.KENTEN_SMALL_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_SESAME_DOT KentenCharacter.KENTEN_WHITE_TRIANGLE		
kentenOverprintFill	KentenCharacter.NONE AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The i over fill.
kentenOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The i over stro
kentenPlacement	Number	read/write	The i kent their
kentenPosition	RubyKentenPosition RubyKentenPosition.ABOVE_RIGHT RubyKentenPosition.BELOW_LEFT	read/write	The l relat char.
kentenStrokeColor	Swatch String	read/write	The i grad ink) ; of ke retur
kentenStrokeTint	Number (range 0 - 100)	read/write	The i perc char; 100)
kentenTint	Number (range 0 - 100)	read/write	The i perc char; 100)
kentenWeight	Number	read/write	The i poin char.
kentenXScale	Number	read/write	The l kent perc size.
kentenYScale	Number	read/write	The i char; the c
kerningMethod	String	read/write	The i
keyboardDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The l the c
kinsokuHangType	KinsokuHangTypes KinsokuHangTypes.KINSOKU_HANG_FORCE KinsokuHangTypes.KINSOKU_HANG_REGULAR KinsokuHangTypes.NONE	read/write	The i punc Note kinsc
kinsokuSet	KinsokuSet KinsokuSet.HARD_KINSOKU KinsokuSet.KOREAN_KINSOKU KinsokuSet.NOTHING KinsokuSet.SIMPLIFIED_CHINESE_KINSOKU KinsokuSet.SOFT_KINSOKU KinsokuSet.TRADITIONAL_CHINESE_KINSOKU KinsokuTable String	read/write	The l dete brea Kinsc enur
kinsokuType	KinsokuType KinsokuType.KINSOKU_PRIORITIZE_ADJUSTMENT_AMOUNT KinsokuType.KINSOKU_PUSH_IN_FIRST KinsokuType.KINSOKU_PUSH_OUT_FIRST	read/write	The i proc kinsc begi

Property	Type	Access	Desc
	KinsokuType.KINSOKU_PUSH_OUT_ONLY		line. when
label	String	read/write	define A pro to ar
lastLineIndent	Number String	read/write	The i last l
leading	Unit Leading Leading.AUTO	read/write	The l text. Lead
leadingAki	Number	read/write	The i befo
leadingModel	LeadingModel LeadingModel.LEADING_MODEL_AKI_ABOVE LeadingModel.LEADING_MODEL_AKI_BELOW LeadingModel.LEADING_MODEL_CENTER LeadingModel.LEADING_MODEL_CENTER_DOWN LeadingModel.LEADING_MODEL_ROMAN	read/write	The i leadi line t
leftIndent	Number String	read/write	The i inde
ligatures	Boolean	read/write	If tru char; (e.g. char;
maximumGlyphScaling	Number (range 50 - 200)	read/write	The i per; char; 200)
maximumLetterSpacing	Number	read/write	The i spac per; spac the f 500) whei
maximumWordSpacing	Number (range 0 - 1000)	read/write	The i spac per; worc Valid justil 1000
mergeConsecutiveParaBorders	Boolean	read/write	If tru bord simil merg
minimumGlyphScaling	Number (range 50 - 200)	read/write	The i per; char; 200)
minimumLetterSpacing	Number	read/write	The i spac per; spac the f 500) whei
minimumWordSpacing	Number (range 0 - 1000)	read/write	The i spac per; worc Valid justil 1000
miterLimit	Number (range 0 - 1000)	read/write	The l strok lengt

Property	Type	Access	Desc
			(poir beve The i infor table Mojik Mojik enur
mojikumi	MojikumiTable String MojikumiTableDefaults MojikumiTableDefaults.LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.NOTHING MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.SIMP_CHINESE_DEFAULT MojikumiTableDefaults.TRAD_CHINESE_DEFAULT	read/write	
name	String	read/write	The i Para
nestedGrepStyles	NestedGrepStyles <i>NestedGrepStyle</i>	readonly	A col GREP
nestedLineStyles	NestedLineStyles <i>NestedLineStyle</i>	readonly	A col style
nestedStyles	NestedStyles <i>NestedStyle</i>	readonly	A col style
nextStyle	ParagraphStyle	read/write	The s para para this s
noBreak	Boolean	read/write	If tru the s
numberingAlignment	ListAlignment ListAlignment.CENTER_ALIGN ListAlignment.LEFT_ALIGN ListAlignment.RIGHT_ALIGN	read/write	The i num
numberingApplyRestartPolicy	Boolean	read/write	If tru num
numberingCharacterStyle	CharacterStyle String	read/write	The i used strin Char
numberingContinue	Boolean	read/write	Cont at th
numberingExpression	String	read/write	The i expr
numberingFormat	NumberingStyle NumberingStyle.ARABIC NumberingStyle.ARABIC_ABJAD NumberingStyle.ARABIC_ALIF_BA_TAH NumberingStyle.DOUBLE_LEADING_ZEROS NumberingStyle.FORMAT_NONE NumberingStyle.HEBREW_BIBLICAL NumberingStyle.HEBREW_NON_STANDARD NumberingStyle.KANJI NumberingStyle.KATAKANA_MODERN NumberingStyle.KATAKANA_TRADITIONAL NumberingStyle.LOWER_LETTERS NumberingStyle.LOWER_ROMAN NumberingStyle.SINGLE_LEADING_ZEROS NumberingStyle.TRIPLE_LEADING_ZEROS NumberingStyle.UPPER_LETTERS NumberingStyle.UPPER_ROMAN String	read/write	Num opti Num enur

Property	Type	Access	Desc
numberingLevel	Number	read/write	The l para
numberingRestartPolicies	NumberingRestartPolicy	readonly	Num polic
numberingStartAt	Number	read/write	Dete num list.
otfContextualAlternate	Boolean	read/write	If tru alter Oper
otfDiscretionaryLigature	Boolean	read/write	If tru ligatu font
otfFigureStyle	OTFFigureStyle OTFFigureStyle.DEFAULT_VALUE OTFFigureStyle.PROPORTIONAL_LINING OTFFigureStyle.PROPORTIONAL_OLDSTYLE OTFFigureStyle.TABULAR_LINING OTFFigureStyle.TABULAR_OLDSTYLE	read/write	The f Oper
otfFraction	Boolean	read/write	If tru Oper
otfHVKana	Boolean	read/write	If tru font diffe horiz
otfHistorical	Boolean	read/write	If tru form
otfJustificationAlternate	Boolean	read/write	If tru justif Oper
otfLocale	Boolean	read/write	If tru form
otfMark	Boolean	read/write	If tru posit font
otfOrdinal	Boolean	read/write	If tru Oper
otfOverlapSwash	Boolean	read/write	If tru swas font
otfProportionalMetrics	Boolean	read/write	If tru prop in O
otfRomanItalics	Boolean	read/write	If tru half-
otfSlashedZero	Boolean	read/write	If tru zero
otfStretchedAlternate	Boolean	read/write	If tru alter Oper
otfStylisticAlternate	Boolean	read/write	If tru alter Oper
otfStylisticSets	Number	read/write	The : Oper
otfSwash	Boolean	read/write	If tru in O
otfTitling	Boolean	read/write	If tru in O
overprintFill	Boolean	read/write	If tru char
overprintStroke	Boolean	read/write	If tru char

Property	Type	Access	Description
paragraphBorderBottomLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The : bott recta
paragraphBorderBottomLeftCornerRadius	Number String	read/write	The : mea: corn the b recta
paragraphBorderBottomLineWeight	Number String	read/write	The l the b
paragraphBorderBottomOffset	Number String	read/write	The : bott para,
paragraphBorderBottomOrigin	ParagraphBorderBottomOriginEnum ParagraphBorderBottomOriginEnum.BASELINE_BOTTOM_ORIGIN ParagraphBorderBottomOriginEnum.DESCENT_BOTTOM_ORIGIN	read/write	The l base the b para,
paragraphBorderBottomRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The : bott recta
paragraphBorderBottomRightCornerRadius	Number String	read/write	The : mea: corn the b recta
paragraphBorderColor	Swatch String	read/write	The : grad ink) ; para, retur
paragraphBorderDisplayIfSplits	Boolean	read/write	If tru bord the p para, fram
paragraphBorderGapColor	Swatch String	read/write	The : grad ink) ; para, Note bord Can i Strin
paragraphBorderGapOverprint	Boolean	read/write	If tru bord Note bord
paragraphBorderGapTint	Number (range 0 - 100)	read/write	The i of th gap. wher not s 100)
paragraphBorderLeftLineWeight	Number String	read/write	The l bord
paragraphBorderLeftOffset	Number String	read/write	The : left e bord

Property	Type	Access	Desc
paragraphBorderOn	Boolean	read/write	If true, the border is visible.
paragraphBorderOverprint	Boolean	read/write	If true, the border is overprinted.
paragraphBorderRightLineWeight	Number String	read/write	The line weight of the right border.
paragraphBorderRightOffset	Number String	read/write	The offset of the right border from the paragraph.
paragraphBorderStrokeEndCap	EndCap EndCap.BUTT_END_CAP EndCap.PROJECTING_END_CAP EndCap.ROUND_END_CAP	read/write	The end cap of the paragraph border stroke.
paragraphBorderStrokeEndJoin	EndJoin EndJoin.BEVEL_END_JOIN EndJoin.MITER_END_JOIN EndJoin.ROUND_END_JOIN	read/write	The end join of the paragraph border stroke.
paragraphBorderTint	Number (range 0 - 100)	read/write	The tint of the border color.
paragraphBorderTopLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-left corner of the paragraph border.
paragraphBorderTopLeftCornerRadius	Number String	read/write	The radius of the top-left corner of the paragraph border.
paragraphBorderTopLineWeight	Number String	read/write	The line weight of the top border.
paragraphBorderTopOffset	Number String	read/write	The offset of the top border from the paragraph.
paragraphBorderTopOrigin	ParagraphBorderTopOriginEnum ParagraphBorderTopOriginEnum.ASCENT_TOP_ORIGIN ParagraphBorderTopOriginEnum.BASELINE_TOP_ORIGIN ParagraphBorderTopOriginEnum.LEADING_TOP_ORIGIN	read/write	The origin of the top border.
paragraphBorderTopRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-right corner of the paragraph border.
paragraphBorderTopRightCornerRadius	Number String	read/write	The radius of the top-right corner of the paragraph border.
paragraphBorderType	StrokeStyle String	read/write	The stroke style of the paragraph border.
paragraphBorderWidth	ParagraphBorderEnum ParagraphBorderEnum.COLUMN_WIDTH	read/write	The width of the paragraph border.

Property	Type	Access	Description
	ParagraphBorderEnum.TEXT_WIDTH		calculates the width of the paragraph border
paragraphDirection	ParagraphDirectionOptions ParagraphDirectionOptions.LEFT_TO_RIGHT_DIRECTION ParagraphDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	Paragraph direction
paragraphGyoudori	Boolean	read/write	If true, gyoudori is applied to the paragraph. If false, gyoudori is not applied to the paragraph.
paragraphJustification	ParagraphJustificationOptions ParagraphJustificationOptions.ARABIC_JUSTIFICATION ParagraphJustificationOptions.DEFAULT_JUSTIFICATION ParagraphJustificationOptions.NASKH_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION_FRAC ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION_FRAC	read/write	Paragraph justification
paragraphKashidaWidth	Number	read/write	Paragraph kashida width. 0 is recommended.
paragraphShadingBottomLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The shading bottom-left corner option.
paragraphShadingBottomLeftCornerRadius	Number String	read/write	The shading bottom-left corner radius. The measurement is in units of the bounding rectangle.
paragraphShadingBottomOffset	Number String	read/write	The shading bottom offset. The measurement is in units of the bounding rectangle.
paragraphShadingBottomOrigin	ParagraphShadingBottomOriginEnum ParagraphShadingBottomOriginEnum.BASELINE_BOTTOM_ORIGIN ParagraphShadingBottomOriginEnum.DESCENT_BOTTOM_ORIGIN	read/write	The shading bottom origin. The baseline is the bottom of the paragraph.
paragraphShadingBottomRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The shading bottom-right corner option.
paragraphShadingBottomRightCornerRadius	Number String	read/write	The shading bottom-right corner radius. The measurement is in units of the bounding rectangle.
paragraphShadingClipToFrame	Boolean	read/write	If true, the shading is clipped to the frame. If false, the shading is not clipped to the frame.
paragraphShadingColor	Swatch String	read/write	The shading color. The color is a gradient (ink) or a solid color (para). The return value is a Swatch object.
paragraphShadingLeftOffset	Number String	read/write	The shading left offset. The measurement is in units of the bounding rectangle.
paragraphShadingOn	Boolean	read/write	If true, the shading is on. If false, the shading is not on.

Property	Type	Access	Description
paragraphShadingOverprint	Boolean	read/write	If true, the shading is overprinted on the text.
paragraphShadingRightOffset	Number String	read/write	The distance from the right edge of the paragraph to the right edge of the shading.
paragraphShadingSuppressPrinting	Boolean	read/write	If true, the shading is not printed.
paragraphShadingTint	Number (range 0 - 100)	read/write	The tint of the shading (0 is black, 100 is white).
paragraphShadingTopLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-left corner of the shading.
paragraphShadingTopLeftCornerRadius	Number String	read/write	The radius of the top-left corner of the shading.
paragraphShadingTopOffset	Number String	read/write	The distance from the top edge of the paragraph to the top edge of the shading.
paragraphShadingTopOrigin	ParagraphShadingTopOriginEnum ParagraphShadingTopOriginEnum.ASCENT_TOP_ORIGIN ParagraphShadingTopOriginEnum.BASELINE_TOP_ORIGIN ParagraphShadingTopOriginEnum.LEADING_TOP_ORIGIN	read/write	The origin of the top edge of the shading.
paragraphShadingTopRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top-right corner of the shading.
paragraphShadingTopRightCornerRadius	Number String	read/write	The radius of the top-right corner of the shading.
paragraphShadingWidth	ParagraphShadingWidthEnum ParagraphShadingWidthEnum.COLUMN_WIDTH ParagraphShadingWidthEnum.TEXT_WIDTH	read/write	The width of the shading.
parent	Application Document ParagraphStyleGroup	readonly	The parent object of the paragraph style.
pointSize	Number String	read/write	The point size of the text.
position	Position Position.NORMAL Position.OT_DENOMINATOR Position.OT_NUMERATOR Position.OT_SUBSCRIPT Position.OT_SUPERSCRIPT Position.SUBSCRIPT Position.SUPERSCRIPT	read/write	The position of the text.

Property	Type	Access	Description
positionalForm	PositionalForms PositionalForms.CALCULATE PositionalForms.FINAL PositionalForms.INITIAL PositionalForms.ISOLATED PositionalForms.MEDIAL PositionalForms.NONE	read/write	The positionalForm property is used to specify the format of the text. The default value is PositionalForms.CALCULATE.
preferences	Preferences <i>Preference</i>	readonly	A collection of preferences for the text. The default value is Preferences.
previewColor	Array of 3 Reals (0 - 255) NothingEnum.NOTHING UIColors	read/write	The previewColor property is used to specify the color of the text preview. The default value is UIColors.
properties	Object	read/write	A collection of properties for the text. The default value is Object.
providerHyphenationStyle	HyphenationStyleEnum HyphenationStyleEnum.HYPH_AESTHETIC HyphenationStyleEnum.HYPH_ALL HyphenationStyleEnum.HYPH_ALL_BUT_UNAESTHETIC HyphenationStyleEnum.HYPH_PREFERRED_AESTHETIC	read/write	The providerHyphenationStyle property is used to specify the hyphenation style. The default value is HyphenationStyleEnum.HYPH_AESTHETIC.
rensuuji	Boolean	read/write	If true, the text is right-aligned. The default value is false.
rightIndent	Number String	read/write	The rightIndent property is used to specify the right indent of the text. The default value is 0.
rotateSingleByteCharacters	Boolean	read/write	If true, single-byte characters are rotated. The default value is false.
rubyAlignment	RubyAlignments RubyAlignments.RUBY_1_AKI RubyAlignments.RUBY_CENTER RubyAlignments.RUBY_EQUAL_AKI RubyAlignments.RUBY_FULL_JUSTIFY RubyAlignments.RUBY_JIS RubyAlignments.RUBY_LEFT RubyAlignments.RUBY_RIGHT	read/write	The rubyAlignment property is used to specify the alignment of the ruby text. The default value is RubyAlignments.RUBY_1_AKI.
rubyAutoAlign	Boolean	read/write	If true, the ruby text is auto-aligned. The default value is false.
rubyAutoScaling	Boolean	read/write	If true, the ruby text is auto-scaled. The default value is false.
rubyAutoTcyAutoScale	Boolean	read/write	If true, the ruby text is auto-scaled. The default value is false.
rubyAutoTcyDigits	Number	read/write	The rubyAutoTcyDigits property is used to specify the number of digits for the ruby text. The default value is 0.
rubyAutoTcyIncludeRoman	Boolean	read/write	If true, the ruby text includes Roman numerals. The default value is false.
rubyFill	Swatch String	read/write	The rubyFill property is used to specify the fill color of the ruby text. The default value is Swatch.

Property	Type	Access	Description
			ruby return value
rubyFont	Font String	read/write	The font character set.
rubyFontSize	Number	read/write	The font size.
rubyFontStyle	String NothingEnum.NOTHING	read/write	The font style. String enum.
rubyOpenTypePro	Boolean	read/write	If true, fonts are OpenType Pro.
rubyOverhang	Boolean	read/write	If true, overhang amount is set. See rubyOverprintFill and rubyOverprintStroke.
rubyOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The fill overprint.
rubyOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The stroke overprint.
rubyParentOverhangAmount	RubyOverhang RubyOverhang.NONE RubyOverhang.RUBY_OVERHANG_HALF_CHAR RubyOverhang.RUBY_OVERHANG_HALF_RUBY RubyOverhang.RUBY_OVERHANG_NO_LIMIT RubyOverhang.RUBY_OVERHANG_ONE_CHAR RubyOverhang.RUBY_OVERHANG_ONE_RUBY	read/write	The ruby overhang amount.
rubyParentScalingPercent	Number	read/write	The parent scaling percent. Determine the size.
rubyParentSpacing	RubyParentSpacing RubyParentSpacing.RUBY_PARENT_121_AKI RubyParentSpacing.RUBY_PARENT_BOTH_SIDES RubyParentSpacing.RUBY_PARENT_EQUAL_AKI RubyParentSpacing.RUBY_PARENT_FULL_JUSTIFY RubyParentSpacing.RUBY_PARENT_NO_ADJUSTMENT	read/write	The parent spacing. To the right.
rubyPosition	RubyKantenPosition RubyKantenPosition.ABOVE_RIGHT RubyKantenPosition.BELOW_LEFT	read/write	The position. Character position.
rubyStroke	Swatch String	read/write	The stroke gradient (ink) and color. Return value.
rubyStrokeTint	Number	read/write	The stroke percent character.
rubyTint	Number (range 0 - 100)	read/write	The tint of the character. (Range 0 - 100)
rubyType	RubyTypes RubyTypes.GROUP_RUBY RubyTypes.PER_CHARACTER_RUBY	read/write	The ruby type.
rubyWeight	Number	read/write	The weight point.
rubyXOffset	Number	read/write	The x offset. Space.

Property	Type	Access	Desc
			pare
rubyXScale	Number	read/write	The l char; perc size.
rubyYOffset	Number	read/write	The ; spac pare
rubyYScale	Number	read/write	The ; char; perc size.
ruleAbove	Boolean	read/write	If tru the p
ruleAboveColor	Swatch String	read/write	The ; grad ink) ; para; retur
ruleAboveGapColor	Swatch String	read/write	The ; grad ink) ; gap c abov whe abov Can Strin
ruleAboveGapOverprint	Boolean	read/write	If tru the p will c only not s
ruleAboveGapTint	Number (range 0 - 100)	read/write	The t of th the p (Ran Valid abov
ruleAboveLeftIndent	Number String	read/write	The ; left e rule eithe the c first
ruleAboveLineWeight	Number String	read/write	The l abov
ruleAboveOffset	Number String	read/write	The ; para; from first
ruleAboveOverprint	Boolean	read/write	If tru abov
ruleAboveRightIndent	Number String	read/write	The ; right para; (base width width the p
ruleAboveTint	Number (range 0 - 100)	read/write	The t of th abov

Property	Type	Access	Desc
ruleAboveType	StrokeStyle String	read/write	The : above return String
ruleAboveWidth	RuleWidth RuleWidth.COLUMN_WIDTH RuleWidth.TEXT_WIDTH	read/write	The l column calcul para,
ruleBelow	Boolean	read/write	If tru para,
ruleBelowColor	Swatch String	read/write	The : grad ink) ; para, return
ruleBelowGapColor	Swatch String	read/write	The : grad ink) ; gap c below when below Can i String
ruleBelowGapOverprint	Boolean	read/write	If tru the r over
ruleBelowGapTint	Number (range 0 - 100)	read/write	The t of th the p (Ran Valid para, is no
ruleBelowLeftIndent	Number String	read/write	The c left e rule eithe the c last l
ruleBelowLineWeight	Number String	read/write	The l below
ruleBelowOffset	Number String	read/write	The : the p from last l
ruleBelowOverprint	Boolean	read/write	If tru over
ruleBelowRightIndent	Number String	read/write	The c right para, (base width width the p
ruleBelowTint	Number (range 0 - 100)	read/write	The t of th below
ruleBelowType	StrokeStyle String	read/write	The : below return String
ruleBelowWidth	RuleWidth RuleWidth.COLUMN_WIDTH RuleWidth.TEXT_WIDTH	read/write	The l column calcul para,

Property	Type	Access	Desc
sameParaStyleSpacing	Unit Spacing Spacing.SETIGNORE	read/write	The : para, style spac
scaleAffectsLineHeight	Boolean	read/write	If tru size v scale
shataiAdjustRotation	Boolean	read/write	If tru rotat
shataiAdjustTsume	Boolean	read/write	If tru tsum
shataiDegreeAngle	Number	read/write	The : degr
shataiMagnification	Number	read/write	The : perc oblic
singleWordJustification	SingleWordJustification SingleWordJustification.CENTER_ALIGN SingleWordJustification.FULLY_JUSTIFIED SingleWordJustification.LEFT_ALIGN SingleWordJustification.RIGHT_ALIGN	read/write	The : lines worc
skew	Number	read/write	The : Para
spaceAfter	Number String	read/write	The l para,
spaceBefore	Number String	read/write	The l para,
spanColumnMinSpaceAfter	Number String	read/write	The i a spa
spanColumnMinSpaceBefore	Number String	read/write	The i befo colui
spanColumnType	SpanColumnTypeOptions SpanColumnTypeOptions.SINGLE_COLUMN SpanColumnTypeOptions.SPAN_COLUMNS SpanColumnTypeOptions.SPLIT_COLUMNS	read/write	Whe shou span colui
spanSplitColumnCount	ShortInteger(1-40) SpanColumnCountOptions SpanColumnCountOptions.ALL	read/write	The i para, num Can i (1 - 4 Span enur
splitColumnInsideGutter	Number String	read/write	The i para,
splitColumnOutsideGutter	Number String	read/write	The i para,
splitDocument	Boolean	read/write	Split only,
startParagraph	StartParagraph StartParagraph.ANYWHERE StartParagraph.NEXT_COLUMN StartParagraph.NEXT_EVEN_PAGE StartParagraph.NEXT_FRAME StartParagraph.NEXT_ODD_PAGE StartParagraph.NEXT_PAGE	read/write	The l start
strikeThroughColor	Swatch String	read/write	The : grad ink) ; strik retur
strikeThroughGapColor	Swatch String	read/write	The : grad ink) ; the s

Property	Type	Access	Desc
			Can i Strin
strikeThroughGapOverprint	Boolean	read/write	If tru the s will c wher is no
strikeThroughGapTint	Number (range 0 - 100)	read/write	The i of th strok to 10 strike solid
strikeThroughOffset	Number String	read/write	The i offse strok base
strikeThroughOverprint	Boolean	read/write	If tru strok
strikeThroughTint	Number (range 0 - 100)	read/write	The i of th strok
strikeThroughType	StrokeStyle String	read/write	The : strike retur Strin
strikeThroughWeight	Number String	read/write	The : strike
strikeThru	Boolean	read/write	If tru strike the t
strokeAlignment	TextStrokeAlign TextStrokeAlign.CENTER_ALIGNMENT TextStrokeAlign.OUTSIDE_ALIGNMENT	read/write	The : appli
strokeColor	Swatch String	read/write	The : grad ink) ; of th also
strokeTint	Number (range 0 - 100)	read/write	The i of th Para spec use a of 0 inhe value
strokeWeight	Number String	read/write	The : to th text.
styleExportTagMaps	StyleExportTagMaps <i>StyleExportTagMap</i>	readonly	A col expo
styleUniqueld	String	read/write	A un assign can b diffe style
tabList	Array of Arrays of Property Name/Value Pairs.	read/write	A list the p retur Prop Pairs
tabStops	TabStops <i>TabStop</i>	readonly	A col

Property	Type	Access	Desc
tatechuyoko	Boolean	read/write	If true, character is vertical.
tatechuyokoXOffset	Number	read/write	The horizontal offset.
tatechuyokoYOffset	Number	read/write	The vertical offset.
tracking	Number	read/write	The distance between characters.
trailingAki	Number	read/write	The distance between characters.
treatIdeographicSpaceAsSpace	Boolean	read/write	If true, ideographic space will be treated as a space character.
tsume	Number	read/write	The distance between characters.
underline	Boolean	read/write	If true, text is underlined.
underlineColor	Swatch String	read/write	The color of the underline (as a string or a Swatch).
underlineGapColor	Swatch String	read/write	The color of the underline gap (as a string or a Swatch). Note: underlineGapColor and underlineColor cannot both be solid colors.
underlineGapOverprint	Boolean	read/write	If true, the underline gap overprints the underline.
underlineGapTint	Number (range 0 - 100)	read/write	The tint of the underline gap (0 to 100, where 0 is no tint).
underlineOffset	Number String	read/write	The offset of the underline (as a number or a string).
underlineOverprint	Boolean	read/write	If true, the underline overprints the text.
underlineTint	Number (range 0 - 100)	read/write	The tint of the underline (0 to 100, where 0 is no tint).
underlineType	StrokeStyle String	read/write	The style of the underline (as a string or a StrokeStyle).
underlineWeight	Number String	read/write	The weight of the underline (as a number or a string).
verticalScale	Number	read/write	The vertical scale of the text.
warichu	Boolean	read/write	If true, text is justified.
warichuAlignment	WarichuAlignment WarichuAlignment.AUTO WarichuAlignment.CENTER_ALIGN	read/write	The alignment of the justified text.

Property	Type	Access	Desc
	WarichuAlignment.CENTER_JUSTIFIED WarichuAlignment.FULLY_JUSTIFIED WarichuAlignment.LEFT_ALIGN WarichuAlignment.LEFT_JUSTIFIED WarichuAlignment.RIGHT_ALIGN WarichuAlignment.RIGHT_JUSTIFIED		
warichuCharsAfterBreak	Number	read/write	The i char: line l
warichuCharsBeforeBreak	Number	read/write	The i char: a line
warichuLineSpacing	Number	read/write	The i waric
warichuLines	Number	read/write	The i waric norm
warichuSize	Number	read/write	The i perc pare dete
xOffsetDiacritic	Number	read/write	The i for d
yOffsetDiacritic	Number	read/write	The i diacr

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **convertBulletsAndNumberingToText** ()

Convert bullets and numbering to text.

Boolean **createThumbnailWithProperties** (previewText:String, pointSize:Number, space:ColorSpace, colorValue:Array of Number, to:File)

Create thumbnail for selected text with the given properties.

Parameter	Type	Description
previewText	String	Text to use as sample
pointSize	Number	Text font size (in points)
space	ColorSpace ColorSpace.CMYK ColorSpace.HSB ColorSpace.LAB ColorSpace.MIXEDINK ColorSpace.RGB	Color space RGB, CMYK or LAB
colorValue	Array of Number	Color values
to	File	The path to the export file.

ParagraphStyle **duplicate** ()

Duplicates the ParagraphStyle.

String **extractLabel** (key:String)

Gets the label value associated with the specified key.

Parameter	Type	Description
key	String	The key.

undefined **forceDelete** (replacingWith:*ParagraphStyle*)

Deletes the paragraph style forcefully. For internal use only.

Parameter	Type	Description
replacingWith	ParagraphStyle	The style to apply in place of the deleted style. (Optional)

ParagraphStyle **getElements** ()

Resolves the object specifier, creating an array of object references.

undefined **insertLabel** (key:*String*, value:*String*)

Sets the label to the value associated with the specified key.

Parameter	Type	Description
key	String	The key.
value	String	The value.

Boolean **isNthDesignAxisHidden** (nthAxisIndex:*Number*)

If true, Nth design axis of variable font is hidden.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.

ParagraphStyle **move** (to:*LocationOptions*, reference:*Varies CellStyle CellStyleGroup CharacterStyle CharacterStyleGroup Document ParagraphStyle ParagraphStyleGroup TableStyle TableStyleGroup Application*)

Moves the style to the specified location.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The location relative to the reference object or within the containing object.
reference	CellStyle CellStyleGroup CharacterStyle CharacterStyleGroup Document ParagraphStyle ParagraphStyleGroup TableStyle TableStyleGroup Application	The reference object. Note: Required when the to parameter specifies before or after. Can accept: ParagraphStyle, ParagraphStyleGroup, CharacterStyle, CharacterStyleGroup, CellStyle, CellStyleGroup, TableStyle, TableStyleGroup, Document or Application. (Optional)

undefined **remove** (replacingWith:*ParagraphStyle*)

Deletes the style.

Parameter	Type	Description
replacingWith	ParagraphStyle	The style to apply in place of the deleted style. (Optional)

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **setNthDesignAxis** (nthAxisIndex:*Number*, nthAxisValue:*Number*)

Set Nth design axis of a variable font.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.
nthAxisValue	Number	Value of nth design axis.

String **toSource** ()

Generates a string which, if executed, will return the ParagraphStyle.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Application.allParagraphStyles
Document.allParagraphStyles
ParagraphStyleGroup.allParagraphStyles
AnchoredObjectDefault.anchoredParagraphStyle
IndexOptions.sectionHeadingStyle
IndexOptions.level1Style
IndexOptions.level2Style
IndexOptions.level3Style
IndexOptions.level4Style
TOCStyleEntry.formatStyle
TOCStyle.titleStyle
ObjectStyle.appliedParagraphStyle
TextDefault.appliedParagraphStyle
MatchParagraphStylePreference.appliedParagraphStyle
Text.appliedParagraphStyle
Character.appliedParagraphStyle
Word.appliedParagraphStyle
Line.appliedParagraphStyle
TextColumn.appliedParagraphStyle
Paragraph.appliedParagraphStyle
TextStyleRange.appliedParagraphStyle
InsertionPoint.appliedParagraphStyle
Story.appliedParagraphStyle
XmlStory.appliedParagraphStyle
CellStyle.appliedParagraphStyle
IndexOptions.titleStyle
PageReference.pageReferenceLimit
EndnoteOption.endnoteTextStyle
EndnoteOption.endnoteTitleStyle
FootnoteOption.footnoteTextStyle
Bullet.parent
Event.parent
EventListener.parent
MutationEvent.parent
NestedGrepStyle.parent
NestedLineStyle.parent
NestedStyle.parent
NumberingRestartPolicy.parent
Preference.parent
StyleExportTagMap.parent
TabStop.parent
XMLImportMap.mappedStyle
XMLExportMap.mappedStyle
ParagraphStyle.basedOn
ParagraphStyle.nextStyle

Return

ParagraphStyles.add()
ParagraphStyle.duplicate()
ParagraphStyle.move()
ParagraphStyle.getElements()
ParagraphStyles.anyItem()
ParagraphStyles.everyItem()
ParagraphStyles.nextItem()
ParagraphStyles.previousItem()
ParagraphStyles.itemById()
ParagraphStyles.item()
ParagraphStyles.[]()
ParagraphStyles.itemByName()

ParagraphStyles.itemByRange()
ParagraphStyles.firstItem()
ParagraphStyles.lastItem()
ParagraphStyles.middleItem()
