

ScriptPreference

Scripting environment preferences.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [getElements](#), [removeEventListener](#), [toSource](#), [toSpecifier](#)

Objects:

[AutoEnum](#), [Boolean](#), [EventListeners](#), [Events](#), [File](#), [MeasurementUnits](#), [Object](#), [String](#), [UserInteractionLevels](#),

Hierarchy:

Superclass: [Preference](#)

Class: [ScriptPreference](#)

Property Listing

Property	Type	Access	Description
enableRedraw	Boolean	read/write	If true, enables redraw during script execution.
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
isValid	Boolean	readonly	Returns true if the object specifier resolves to valid objects.
measurementUnit	AutoEnum AutoEnum.AUTO_VALUE MeasurementUnits MeasurementUnits.AGATES MeasurementUnits.AMERICAN_POINTS MeasurementUnits.BAI MeasurementUnits.CENTIMETERS MeasurementUnits.CICEROS MeasurementUnits.CUSTOM MeasurementUnits.HA MeasurementUnits.INCHES MeasurementUnits.INCHES_DECIMAL MeasurementUnits.MILLIMETERS	read/write	The measurement unit used during script processing. Can return: AutoEnum enumerator or MeasurementUnits enumerator.

Property	Type	Access	Description
	MeasurementUnits.MILS MeasurementUnits.PICAS MeasurementUnits.PIXELS MeasurementUnits.POINTS MeasurementUnits.Q		
parent	MeasurementUnits.U Application	readonly	The parent of the ScriptPreference (a Application).
properties	Object	read/write	A property that allows setting of several properties at the same time.
scriptsFolder	File	readonly	The path to the Scripts folder for the application.
scriptsList	Array of 2 Strings Array of Files <i>File</i>	readonly	A list of the scripts in the Scripts folder. Can return: Array of Array of 2 Strings or Files.
userInteractionLevel	UserInteractionLevels UserInteractionLevels.INTERACT_WITH_ALERTS UserInteractionLevels.INTERACT_WITH_ALL UserInteractionLevels.NEVER_INTERACT	read/write	Controls the display of dialogs and alerts during script processing.
version	String Real	read/write	The version of the scripting environment. Can also accept: Real.

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

ScriptPreference **getElements** ()

Resolves the object specifier, creating an array of object references.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

String **toSource** ()

Generates a string which, if executed, will return the ScriptPreference.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

Application.scriptPreferences

Event.parent

EventListener.parent

MutationEvent.parent

Return

ScriptPreference.getElements()
