

Socket

Creates a TCP/IP connection, or establishes a TCP/IP server.

Go to [Property Listing](#) | [Method Listing](#)

Methods:

[Socket](#), [close](#), [listen](#), [open](#), [poll](#), [read](#), [readln](#), [write](#), [writeln](#)

Objects:

[Boolean](#), [Number](#), [String](#)

Property Listing

Property	Type	Access	Description
connected	Boolean	readonly	When true, the connection is active.
encoding	String	read/write	Sets or retrieves the name of the encoding used to transmit data. Typical values are "ASCII", "BINARY", or "UTF-8".
eof	Boolean	readonly	When true, the receive buffer is empty.
error	String	read/write	A message describing the most recent error. Setting this value clears any error message.
host	String	readonly	The name of the remote computer when a connection is established. If the connection is shut down or does not exist, the property contains the empty string.
timeout	Number	read/write	The timeout in seconds to be applied to read or write operations.

Method Listing

Constructor

[Socket](#) [Socket](#) ()

Creates a new [Socket](#) object.

[Boolean](#) [close](#) ()

Terminates the open connection.

Returns true if the connection was closed, false on I/O errors. Deleting the object also closes the connection, but not until JavaScript garbage-collects the object. The connection might stay open longer than you wish if you do not close it explicitly.

[Boolean](#) [listen](#) (port:[Number](#), [encoding:[String](#)=[String](#)])

Instructs the object to start listening for an incoming connection.

The call to open() and the call to listen() are mutually exclusive. Call one function or the other, not both.

Parameter	Type	Description
port	Number (range 1 - 65535)	The TCP/IP port number to listen on. Valid port numbers are 1 to 65535. Typical values are 80 for a Web server, 23 for a Telnet server and so on.
encoding	String	The encoding to be used for the connection Typical values are "ASCII", "BINARY", or "UTF-8". (default: ASCII)

Boolean **open** (host:String, [encoding:String=String])

Opens the connection for subsequent read/write operations.

The call to open() and the call to listen() are mutually exclusive. Call one function or the other, not both.

Parameter	Type	Description
host	String	The server to connect to. This can be a DNS name, an IPv4 address, or an IPv6 address, followed by a colon and a port number.
encoding	String	The encoding to be used for the connection Typical values are "ASCII", "binary", or "UTF-8". (default: ASCII)

Socket **poll** ()

Checks a listening object for a new incoming connection.

If a connection request was detected, the method returns a new Socket object that wraps the new connection. Use this connection object to communicate with the remote computer. After use, close the connection and delete the JavaScript object. If no new connection request was detected, the method returns null.

String **read** ([count:Number])

Reads up to the specified number of characters from the connection. CR characters are ignored unless the encoding is set to "BINARY".

Returns a string that contains up to the number of characters that were supposed to be read, or the number of characters read before the connection closed or timed out.

Parameter	Type	Description
count	Number	The number of characters to read. If not supplied, the connection attempts to read as many characters it can get and returns immediately.

String **readln** ()

Reads one line of text up to the next line feed.

Line feeds are recognized as LF or CRLF pairs. CR characters are ignored. Returns a string containing the characters.

Boolean **write** (text:*String*)

Concatenates all arguments into a single string and writes that string to the connection.

Parameter	Type	Description
text	<i>String</i>	Any number of string values. All arguments are concatenated to form the string to be written. CRLF sequences are converted to LFs unless the encoding is set to "BINARY".

Boolean **writeln** (text:*String*)

Concatenates all arguments into a single string, appends a LF character, and writes that string to the connection.

Parameter	Type	Description
text	<i>String</i>	Any number of string values. All arguments are concatenated to form the string to be written. CRLF sequences are converted to LFs unless the encoding is set to "BINARY".

Return

Socket.poll()

Socket.Socket()
