

Story

A story.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [asynchronousExportFile](#), [autoTag](#), [changeGlyph](#), [changeGrep](#), [changeText](#), [changeTransliterate](#), [changepcase](#), [checkIn](#), [checkOut](#), [clearOverrides](#), [convertBulletsAndNumberingToText](#), [createOutlines](#), [duplicate](#), [exportFile](#), [extractLabel](#), [findGlyph](#), [findGrep](#), [findText](#), [findTransliterate](#), [getElements](#), [insertLabel](#), [isNthDesignAxisHidden](#), [markup](#), [move](#), [placeXML](#), [recompose](#), [remove](#), [removeEventListener](#), [revert](#), [setNthDesignAxis](#), [storyEdit](#), [toSource](#), [toSpecifier](#)

Objects:

[AdornmentOverprint](#), [AlternateGlyphForms](#), [BalanceLinesStyle](#), [Boolean](#), [Bullet](#), [Buttons](#), [Capitalization](#), [CellStyleMappings](#), [Changes](#), [CharStyleMappings](#), [CharacterAlignment](#), [CharacterDirectionOptions](#), [CharacterStyle](#), [Characters](#), [CheckBoxes](#), [ComboBoxes](#), [CornerOptions](#), [DiacriticPositionOptions](#), [DigitsTypeOptions](#), [EPSTexts](#), [EndCap](#), [EndJoin](#), [EndnoteRanges](#), [EndnoteTextFrames](#), [Endnotes](#), [EventListeners](#), [Events](#), [Font](#), [Footnotes](#), [FormFields](#), [Graphic](#), [GraphicLines](#), [GridAlignment](#), [GridDataInformation](#), [Groups](#), [HiddenTexts](#), [HyphenationStyleEnum](#), [InCopyExportOption](#), [InsertionPoints](#), [Justification](#), [KashidasOptions](#), [KentenAlignment](#), [KentenCharacter](#), [KentenCharacterSet](#), [KinsokuHangTypes](#), [KinsokuSet](#), [KinsokuTable](#), [KinsokuType](#), [LanguageWithVendors](#), [Leading](#), [LeadingModel](#), [Lines](#), [Link](#), [LinkedStoryOption](#), [ListAlignment](#), [ListBoxes](#), [ListType](#), [LockStateValues](#), [MojikumiTable](#), [MojikumiTableDefaults](#), [MultiStateObjects](#), [NamedGrid](#), [NestedGrepStyles](#), [NestedLineStyle](#)s, [NestedStyles](#), [Notes](#), [NothingEnum](#), [Number](#), [NumberingList](#), [NumberingRestartPolicy](#), [NumberingStyle](#), [OTFFigureStyle](#), [Object](#), [OutlineJoin](#), [Ovals](#), [PageItem](#), [PageItems](#), [ParaStyleMappings](#), [ParagraphBorderBottomOriginEnum](#), [ParagraphBorderEnum](#), [ParagraphBorderTopOriginEnum](#), [ParagraphDirectionOptions](#), [ParagraphJustificationOptions](#), [ParagraphShadingBottomOriginEnum](#), [ParagraphShadingTopOriginEnum](#), [ParagraphShadingWidthEnum](#), [ParagraphStyle](#), [Paragraphs](#), [Polygons](#), [Position](#), [PositionalForms](#), [Preferences](#), [RadioButtons](#), [Rectangles](#), [RubyAlignments](#), [RubyKentenPosition](#), [RubyOverhang](#), [RubyParentSpacing](#), [RubyTypes](#), [RuleWidth](#), [SignatureFields](#), [SingleWordJustification](#), [Spacing](#), [SpanColumnCountOptions](#), [SpanColumnTypeOptions](#), [SpecialCharacters](#), [SplineItems](#), [StartParagraph](#), [StoryPreference](#), [StoryTypes](#), [String](#), [StrokeStyle](#), [Swatch](#), [TabStops](#), [TableStyleMappings](#), [Tables](#), [TextBoxes](#), [TextColumns](#), [TextFrames](#), [TextPaths](#), [TextStrokeAlign](#), [TextStyleRanges](#), [TextVariableInstances](#), [Texts](#), [WarichuAlignment](#), [Words](#), [XMLItem](#)

Preferences:

[InCopyExportOption](#), [LinkedStoryOption](#), [Preferences](#), [StoryPreference](#)

Hierarchy:

Class: [Story](#)

Subclasses: [XmlStory](#)

Property Listing

Property	Type	Access	Description
alignToBaseline	Boolean	read/write	If true, the text aligns to the baseline of the grid.
allGraphics	Array of Graphic	readonly	Lists all the graphics in the story.
allPageItems	Array of PageItem	readonly	Lists all the page items in the story.
allowArbitraryHyphenation	Boolean	read/write	If true, hyphenation is allowed on all lines of text.
appliedCharacterStyle	CharacterStyle String	read/write	The character style applied to the text. Can also be a string name.
appliedFont	Font String	read/write	The font applied to the text. Can be a font object or a string name.
appliedLanguage	LanguageWithVendors LanguageCanAlsoAccept : String	read/write	The language applied to the text. Can be a language object or a string name.
appliedNamedGrid	NamedGrid	read/write	The named grid applied to the text.

Property	Type	Access	Desc
appliedNestedStyles	Array of CharacterStyle	readonly	The i style style
appliedNumberingList	NumberingList String	read/write	The l retur Strin
appliedParagraphStyle	ParagraphStyle String	read/write	The p appli also
associatedXMLElement	XMLItem	readonly	The d asso
autoLeading	Number (range 0 - 500)	read/write	The p size t leadi
autoTcy	Number	read/write	The i char: whic auto horiz text.
autoTcyIncludeRoman	Boolean	read/write	If tru Rom
balanceRaggedLines	Boolean BalanceLinesStyle BalanceLinesStyle.FULLY_BALANCED BalanceLinesStyle.NO_BALANCING BalanceLinesStyle.PYRAMID_SHAPE BalanceLinesStyle.VEE_SHAPE	read/write	If tru enur balai Note singl Can i Balai enur
baselineShift	Number String	read/write	The l to th
bulletChar	Bullet	readonly	Bulle
bulletsAlignment	ListAlignment ListAlignment.CENTER_ALIGN ListAlignment.LEFT_ALIGN ListAlignment.RIGHT_ALIGN	read/write	The i bulle
bulletsAndNumberingListType	ListType ListType.BULLET_LIST ListType.NO_LIST ListType.NUMBERED_LIST	read/write	List t num
bulletsCharacterStyle	CharacterStyle String	read/write	The c used strin, Char
bulletsTextAfter	String	read/write	The t expr
bunriKinshi	Boolean	read/write	If tru peric dout selec Note kinc
buttons	Buttons <i>Button</i>	readonly	A col
capitalization	Capitalization Capitalization.ALL_CAPS Capitalization.CAP_TO_SMALL_CAP Capitalization.LOWER_CASE Capitalization.NORMAL Capitalization.SMALL_CAPS	read/write	The c
cellStyleMappings	CellStyleMappings <i>CellStyleMapping</i>	readonly	A col map
changes	Changes <i>Change</i>	readonly	A col

Property	Type	Access	Desc
charStyleMappings	CharStyleMappings CharStyleMapping	readonly	A col map
characterAlignment	CharacterAlignment CharacterAlignment.ALIGN_BASELINE CharacterAlignment.ALIGN_EM_BOTTOM CharacterAlignment.ALIGN_EM_CENTER CharacterAlignment.ALIGN_EM_TOP CharacterAlignment.ALIGN_ICF_BOTTOM CharacterAlignment.ALIGN_ICF_TOP	read/write	The i char: char:
characterDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The i char:
characterRotation	Number	read/write	The i degr char: rotat coun
characters	Characters Character	readonly	A col
checkboxes	CheckBoxes	readonly	A col chec
cjkGridTracking	Boolean	read/write	If tru to tr: char:
comboBoxes	ComboBoxes	readonly	A col coml
composer	String	read/write	The t to cc
contents	String SpecialCharacters SpecialCharacters.ARABIC_COMMA SpecialCharacters.ARABIC_KASHIDA SpecialCharacters.ARABIC_QUESTION_MARK SpecialCharacters.ARABIC_SEMICOLON SpecialCharacters.AUTO_PAGE_NUMBER SpecialCharacters.BULLET_CHARACTER SpecialCharacters.COLUMN_BREAK SpecialCharacters.COPYRIGHT_SYMBOL SpecialCharacters.DEGREE_SYMBOL SpecialCharacters.DISCRETIONARY_HYPHEN SpecialCharacters.DISCRETIONARY_LINE_BREAK SpecialCharacters.DOTTED_CIRCLE SpecialCharacters.DOUBLE_LEFT_QUOTE SpecialCharacters.DOUBLE_RIGHT_QUOTE SpecialCharacters.DOUBLE_STRAIGHT_QUOTE SpecialCharacters.ELLIPSIS_CHARACTER SpecialCharacters.EM_DASH SpecialCharacters.EM_SPACE SpecialCharacters.END_NESTED_STYLE SpecialCharacters.EN_DASH SpecialCharacters.EN_SPACE SpecialCharacters.EVEN_PAGE_BREAK SpecialCharacters.FIGURE_SPACE SpecialCharacters.FIXED_WIDTH_NONBREAKING_SPACE SpecialCharacters.FLUSH_SPACE SpecialCharacters.FOOTNOTE_SYMBOL SpecialCharacters.FORCED_LINE_BREAK SpecialCharacters.FRAME_BREAK SpecialCharacters.HAIR_SPACE SpecialCharacters.HEBREW_GERESH SpecialCharacters.HEBREW_GERSHAYIM SpecialCharacters.HEBREW_MAQAF SpecialCharacters.HEBREW_SOF_PASUK SpecialCharacters.INDENT_HERE_TAB SpecialCharacters.LEFT_TO_RIGHT_EMBEDDING SpecialCharacters.LEFT_TO_RIGHT_MARK SpecialCharacters.LEFT_TO_RIGHT_OVERRIDE SpecialCharacters.NEXT_PAGE_NUMBER SpecialCharacters.NONBREAKING_HYPHEN	read/write	The i Can i Spec enur

Property	Type	Access	Desc
	SpecialCharacters.NONBREAKING_SPACE SpecialCharacters.ODD_PAGE_BREAK SpecialCharacters.PAGE_BREAK SpecialCharacters.PARAGRAPH_SYMBOL SpecialCharacters.POP_DIRECTIONAL_FORMATTING SpecialCharacters.PREVIOUS_PAGE_NUMBER SpecialCharacters.PUNCTUATION_SPACE SpecialCharacters.QUARTER_SPACE SpecialCharacters.REGISTERED_TRADEMARK SpecialCharacters.RIGHT_INDENT_TAB SpecialCharacters.RIGHT_TO_LEFT_EMBEDDING SpecialCharacters.RIGHT_TO_LEFT_MARK SpecialCharacters.RIGHT_TO_LEFT_OVERRIDE SpecialCharacters.SECTION_MARKER SpecialCharacters.SECTION_SYMBOL SpecialCharacters.SINGLE_LEFT_QUOTE SpecialCharacters.SINGLE_RIGHT_QUOTE SpecialCharacters.SINGLE_STRAIGHT_QUOTE SpecialCharacters.SIXTH_SPACE SpecialCharacters.TEXT_VARIABLE SpecialCharacters.THIN_SPACE SpecialCharacters.THIRD_SPACE SpecialCharacters.TRADEMARK_SYMBOL SpecialCharacters.ZERO_WIDTH_JOINER SpecialCharacters.ZERO_WIDTH_NONJOINER		
designAxes	Array of Number	read/write	Value
desiredGlyphScaling	Number (range 50 - 200)	read/write	The (per cent of original glyph size) (range 50 - 200)
desiredLetterSpacing	Number	read/write	The (spec of the letter spacing between characters in the font)
desiredWordSpacing	Number (range 0 - 1000)	read/write	The (spec of the word spacing between words in the font)
diacriticPosition	DiacriticPositionOptions DiacriticPositionOptions.DEFAULT_POSITION DiacriticPositionOptions.LOOSE_POSITION DiacriticPositionOptions.MEDIUM_POSITION DiacriticPositionOptions.OPENTYPE_POSITION DiacriticPositionOptions.OPENTYPE_POSITION_FROM_BASELINE DiacriticPositionOptions.TIGHT_POSITION	read/write	Position of the diacritic character
digitsType	DigitsTypeOptions DigitsTypeOptions.ARABIC_DIGITS DigitsTypeOptions.BENGALI_DIGITS DigitsTypeOptions.BURMESE_DIGITS DigitsTypeOptions.DEFAULT_DIGITS DigitsTypeOptions.DEVANAGARI_DIGITS DigitsTypeOptions.FARSI_DIGITS DigitsTypeOptions.FULL_FARSI_DIGITS DigitsTypeOptions.GUJARATI_DIGITS DigitsTypeOptions.GURMUKHI_DIGITS DigitsTypeOptions.HINDI_DIGITS DigitsTypeOptions.KANNADA_DIGITS DigitsTypeOptions.KHMER_DIGITS DigitsTypeOptions.LAO_DIGITS DigitsTypeOptions.MALAYALAM_DIGITS DigitsTypeOptions.NATIVE_DIGITS DigitsTypeOptions.ORIYA_DIGITS DigitsTypeOptions.TAMIL_DIGITS DigitsTypeOptions.TELUGU_DIGITS DigitsTypeOptions.THAI_DIGITS DigitsTypeOptions.TIBETAN_DIGITS	read/write	The (type of the digits character)
dropCapCharacters	Number (range 0 - 150)	read/write	The (number of characters to drop)

Property	Type	Access	Desc
dropCapLines	Number (range 0 - 25)	read/write	The number of drop cap lines.
dropCapStyle	CharacterStyle String	read/write	The drop cap style applied to the first letter of the first line of the paragraph.
dropcapDetail	Number	read/write	Detail of the drop cap. 0 = no drop cap, 1 = drop cap, 2 = drop cap with outline, 3 = drop cap with outline and bear, 4 = drop cap with outline and bear and 0x10 used grid.
endJoin	OutlineJoin OutlineJoin.BEVEL_END_JOIN OutlineJoin.MITER_END_JOIN OutlineJoin.ROUND_END_JOIN	read/write	The end join style applied to the end of the paragraph.
endnoteRanges	EndnoteRanges <i>EndnoteRange</i>	readonly	A collection of endnote ranges.
endnoteTextFrames	EndnoteTextFrames <i>EndnoteTextFrame</i>	readonly	A collection of endnote text frames.
endnotes	Endnotes <i>Endnote</i>	readonly	A collection of endnotes.
epstexts	EPSTexts <i>EPSText</i>	readonly	EPSTexts.
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
fillColor	Swatch String	read/write	The fill color (gradient or solid) of the paragraph.
fillTint	Number (range 0 - 100)	read/write	The fill tint of the paragraph.
firstLineIndent	Number String	read/write	The first line indent of the paragraph.
fontStyle	String	read/write	The font style of the paragraph.
footnotes	Footnotes <i>Footnote</i>	readonly	A collection of footnotes.
formFields	FormFields <i>FormField</i>	readonly	A collection of form fields.
glyphForm	AlternateGlyphForms AlternateGlyphForms.EXPERT_FORM AlternateGlyphForms.FULL_WIDTH_FORM AlternateGlyphForms.JIS04_FORM AlternateGlyphForms.JIS78_FORM AlternateGlyphForms.JIS83_FORM AlternateGlyphForms.JIS90_FORM AlternateGlyphForms.MONOSPACED_HALF_WIDTH_FORM AlternateGlyphForms.NLC_FORM AlternateGlyphForms.NONE AlternateGlyphForms.PROPORTIONAL_WIDTH_FORM AlternateGlyphForms.QUARTER_WIDTH_FORM AlternateGlyphForms.THIRD_WIDTH_FORM AlternateGlyphForms.TRADITIONAL_FORM	read/write	The glyph form of the paragraph.
gradientFillAngle	Number	read/write	The gradient fill angle of the paragraph.
gradientFillLength	Number	read/write	The gradient fill length of the paragraph.

Property	Type	Access	Desc
gradientFillStart	Array of Number Array of String	read/write	The : coord appli text,
gradientStrokeAngle	Number	read/write	The : grad strok -180
gradientStrokeLength	Number	read/write	The l grad radia the s
gradientStrokeStart	Array of Number Array of String	read/write	The : coord appli the t y].
graphicLines	GraphicLines <i>GraphicLine</i>	readonly	A col lines
gridAlignFirstLineOnly	Boolean	read/write	If tru line t base align
gridAlignment	GridAlignment GridAlignment.ALIGN_BASELINE GridAlignment.ALIGN_EM_BOTTOM GridAlignment.ALIGN_EM_CENTER GridAlignment.ALIGN_EM_TOP GridAlignment.ALIGN_ICF_BOTTOM GridAlignment.ALIGN_ICF_TOP GridAlignment.NONE	read/write	The : fram grid.
gridData	GridDataInformation	readonly	Defa Note layot grids
gridGyoudori	Number	read/write	The : setti
groups	Groups <i>Group</i>	readonly	A col
hiddenTexts	HiddenTexts <i>HiddenText</i>	readonly	A col obje
horizontalScale	Number	read/write	The l appli
hyphenWeight	Number (range 0 - 10)	read/write	The : bette hyph resul hyph 100)
hyphenateAcrossColumns	Boolean	read/write	If tru worc be h'
hyphenateAfterFirst	Number (range 1 - 15)	read/write	The : lette a wo by a
hyphenateBeforeLast	Number (range 1 - 15)	read/write	The : lette worc by a
hyphenateCapitalizedWords	Boolean	read/write	If tru hyph worc
hyphenateLadderLimit	Number (range 0 - 25)	read/write	The : hyph on co

Property	Type	Access	Desc
			spec cons
hyphenateLastWord	Boolean	read/write	zero. If true, hyphenate words. Note: hyphenateWordsLongerThan must be greater than zero.
hyphenateWordsLongerThan	Number (range 3 - 25)	read/write	The number of letters in or more letters in a word before hyphenating.
hyphenation	Boolean	read/write	If true, hyphenate words.
hyphenationZone	Number String	read/write	The number of spaces of a line of text before beginning a column of text.
id	Number	readonly	The ID of the story.
idmlComponentName	String	read/write	The IDML component name.
ignoreEdgeAlignment	Boolean	read/write	If true, ignore edge alignment.
incopyExportOptions	InCopyExportOption	readonly	Export options for InCopy.
index	Number	readonly	The index of the object.
insertionPoints	InsertionPoints <i>InsertionPoint</i>	readonly	A collection of insertion points.
isEndnoteStory	Boolean	readonly	Return true if the story is an endnote.
isValid	Boolean	readonly	Return true if the object is valid.
itemLink	Link	readonly	The item link.
jidori	Number	read/write	The JIDORI value.
justification	Justification Justification.AWAY_FROM_BINDING_SIDE Justification.CENTER_ALIGN Justification.CENTER_JUSTIFIED Justification.FULLY_JUSTIFIED Justification.LEFT_ALIGN Justification.LEFT_JUSTIFIED Justification.RIGHT_ALIGN Justification.RIGHT_JUSTIFIED Justification.TO_BINDING_SIDE	read/write	The justification of the text.
kashidas	KashidasOptions KashidasOptions.DEFAULT_KASHIDAS KashidasOptions.KASHIDAS_OFF	read/write	Use the kashidas value.
keepAllLinesTogether	Boolean	read/write	If true, the paragraph is kept together. If false, the paragraph is broken into columns.
keepFirstLines	Number (range 1 - 50)	read/write	The number of lines to keep at the beginning of the story.

Property	Type	Access	Description
keepLastLines	Number (range 1 - 50)	read/write	The number of lines to keep at the end of the paragraph.
keepLinesTogether	Boolean	read/write	If true, lines in the paragraph are kept together when wrapped.
keepRuleAboveInFrame	Boolean	read/write	If true, the paragraph's border is kept above the text when wrapped.
keepWithNext	Number (range 0 - 5)	read/write	The number of lines to keep with the next paragraph.
keepWithPrevious	Boolean	read/write	If true, the paragraph is kept with the previous paragraph.
kentenAlignment	KentenAlignment KentenAlignment.ALIGN_KENTEN_CENTER KentenAlignment.ALIGN_KENTEN_LEFT	read/write	The alignment of the paragraph's text.
kentenCharacterSet	KentenCharacterSet KentenCharacterSet.CHARACTER_INPUT KentenCharacterSet.JIS KentenCharacterSet.KUTEN KentenCharacterSet.SHIFT_JIS KentenCharacterSet.UNICODE	read/write	The character set used for the paragraph's text.
kentenCustomCharacter	String	read/write	The custom character used for the paragraph's text.
kentenFillColor	Swatch String	read/write	The fill color of the paragraph's text.
kentenFont	Font String	read/write	The font used for the paragraph's text.
kentenFontSize	Number	read/write	The font size of the paragraph's text.
kentenFontStyle	String NothingEnum.NOTHING	read/write	The font style of the paragraph's text.
kentenKind	KentenCharacter KentenCharacter.CUSTOM KentenCharacter.KENTEN_BLACK_CIRCLE KentenCharacter.KENTEN_BLACK_TRIANGLE KentenCharacter.KENTEN_BULLSEYE KentenCharacter.KENTEN_FISHEYE KentenCharacter.KENTEN_SESAME_DOT KentenCharacter.KENTEN_SMALL_BLACK_CIRCLE KentenCharacter.KENTEN_SMALL_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_CIRCLE KentenCharacter.KENTEN_WHITE_SESAME_DOT KentenCharacter.KENTEN_WHITE_TRIANGLE KentenCharacter.NONE	read/write	The kind of character used for the paragraph's text.
kentenOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The overprint fill of the paragraph's text.

Property	Type	Access	Description
kentenOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The overprint stroke
kentenPlacement	Number	read/write	The kenten placement of their
kentenPosition	RubyKentenPosition RubyKentenPosition.ABOVE_RIGHT RubyKentenPosition.BELOW_LEFT	read/write	The kenten position relat to the character
kentenStrokeColor	Swatch String	read/write	The stroke color (gradient ink) of kenten return
kentenStrokeTint	Number (range 0 - 100)	read/write	The stroke tint percentage character (100)
kentenTint	Number (range 0 - 100)	read/write	The kenten tint percentage character (100)
kentenWeight	Number	read/write	The kenten weight point character
kentenXScale	Number	read/write	The kenten x scale percentage size
kentenYScale	Number	read/write	The kenten y scale character the character
kerningMethod	String	read/write	The kerning method
keyboardDirection	CharacterDirectionOptions CharacterDirectionOptions.DEFAULT_DIRECTION CharacterDirectionOptions.LEFT_TO_RIGHT_DIRECTION CharacterDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The keyboard direction the character
kinsokuHangType	KinsokuHangTypes KinsokuHangTypes.KINSOKU_HANG_FORCE KinsokuHangTypes.KINSOKU_HANG_REGULAR KinsokuHangTypes.NONE	read/write	The kinsoku hang type punct Note kinsoku
kinsokuSet	KinsokuSet KinsokuSet.HARD_KINSOKU KinsokuSet.KOREAN_KINSOKU KinsokuSet.NOTHING KinsokuSet.SIMPLIFIED_CHINESE_KINSOKU KinsokuSet.SOFT_KINSOKU KinsokuSet.TRADITIONAL_CHINESE_KINSOKU KinsokuTable String	read/write	The kinsoku set delete break kinsoku enur
kinsokuType	KinsokuType KinsokuType.KINSOKU_PRIORITIZE_ADJUSTMENT_AMOUNT KinsokuType.KINSOKU_PUSH_IN_FIRST KinsokuType.KINSOKU_PUSH_OUT_FIRST KinsokuType.KINSOKU_PUSH_OUT_ONLY	read/write	The kinsoku type process kinsoku begin line when defir
label	String	read/write	A label to ar
lastLineIndent	Number String	read/write	The last line indent
leading	Unit Leading Leading.AUTO	read/write	The leading text. Leading

Property	Type	Access	Desc
leadingAki	Number	read/write	The i befo
leadingModel	LeadingModel LeadingModel.LEADING_MODEL_AKI_ABOVE LeadingModel.LEADING_MODEL_AKI_BELOW LeadingModel.LEADING_MODEL_CENTER LeadingModel.LEADING_MODEL_CENTER_DOWN LeadingModel.LEADING_MODEL_ROMAN	read/write	The leadi line t
leftIndent	Number String	read/write	The v inde
length	Number	readonly	The i the c
ligatures	Boolean	read/write	If tru char: (e.g., char:
lines	Lines <i>Line</i>	readonly	A col
linkedStoryOptions	LinkedStoryOption	readonly	Link
listBoxes	ListBoxes	readonly	A col
lockState	LockStateValues LockStateValues.CHECKED_IN_STORY LockStateValues.CHECKED_OUT_STORY LockStateValues.EMBEDDED_STORY LockStateValues.LOCKED_STORY LockStateValues.MISSING_LOCK_STATE LockStateValues.MIXED_LOCK_STATE LockStateValues.NONE LockStateValues.UNMANAGED_STORY	readonly	The l
maximumGlyphScaling	Number (range 50 - 200)	read/write	The i perc char: 200)
maximumLetterSpacing	Number	read/write	The i spac perc spac the f 500) whei
maximumWordSpacing	Number (range 0 - 1000)	read/write	The i spac perc worc Valid justif 1000
mergeConsecutiveParaBorders	Boolean	read/write	If tru bord simil merg
minimumGlyphScaling	Number (range 50 - 200)	read/write	The i perc char: 200)
minimumLetterSpacing	Number	read/write	The i spac perc spac the f 500) whei
minimumWordSpacing	Number (range 0 - 1000)	read/write	The i spac perc worc Valid

Property	Type	Access	Desc
			justified
miterLimit	Number (range 0 - 1000)	read/write	The length of the stroke (points)
mojikumi	MojikumiTable String MojikumiTableDefaults MojikumiTableDefaults.LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.NOTHING MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_ALL_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_ALL_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_PERIOD_ONE_EM_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_NO_FLOAT_ENUM MojikumiTableDefaults.ONE_OR_ONE_HALF_EM_INDENT_LINE_END_UKE_ONE_HALF_EM_ENUM MojikumiTableDefaults.SIMP_CHINESE_DEFAULT MojikumiTableDefaults.TRAD_CHINESE_DEFAULT	read/write	The information table Moji enur
multiStateObjects	MultiStateObjects <i>MultiStateObject</i>	readonly	A collection of objects
name	String	read/write	The name of this story
nestedGrepStyles	NestedGrepStyles <i>NestedGrepStyle</i>	readonly	A collection of GREP styles
nestedLineStyles	NestedLineStyles <i>NestedLineStyle</i>	readonly	A collection of line styles
nestedStyles	NestedStyles <i>NestedStyle</i>	readonly	A collection of styles
noBreak	Boolean	read/write	If true, the story does not break
notes	Notes <i>Note</i>	readonly	A collection of notes
numberingAlignment	ListAlignment ListAlignment.CENTER_ALIGN ListAlignment.LEFT_ALIGN ListAlignment.RIGHT_ALIGN	read/write	The alignment of the numbering
numberingApplyRestartPolicy	Boolean	read/write	If true, the numbering restarts at the beginning of the paragraph
numberingCharacterStyle	CharacterStyle String	read/write	The character style used for the numbering
numberingContinue	Boolean	read/write	Continue the numbering from the previous paragraph
numberingExpression	String	read/write	The regular expression used for the numbering
numberingFormat	NumberingStyle NumberingStyle.ARABIC NumberingStyle.ARABIC_ABJAD NumberingStyle.ARABIC_ALIF_BA_TAH NumberingStyle.DOUBLE_LEADING_ZEROS NumberingStyle.FORMAT_NONE NumberingStyle.HEBREW_BIBLICAL NumberingStyle.HEBREW_NON_STANDARD NumberingStyle.KANJI NumberingStyle.KATAKANA_MODERN NumberingStyle.KATAKANA_TRADITIONAL NumberingStyle.LOWER_LETTERS	read/write	Numbering options: Numbering style

Property	Type	Access	Desc
	NumberingStyle.LOWER_ROMAN NumberingStyle.SINGLE_LEADING_ZEROS NumberingStyle.TRIPLE_LEADING_ZEROS NumberingStyle.UPPER_LETTERS NumberingStyle.UPPER_ROMAN String		
numberingLevel	Number	read/write	The l para
numberingRestartPolicies	NumberingRestartPolicy	readonly	Num polic
numberingStartAt	Number	read/write	Dete num list.
opentypeFeatures	Array of 2 Strings Array of LongIntegers	read/write	Oper retur Strin
otfContextualAlternate	Boolean	read/write	If tru alter Oper
otfDiscretionaryLigature	Boolean	read/write	If tru ligatu fonts
otfFigureStyle	OTFFigureStyle OTFFigureStyle.DEFAULT_VALUE OTFFigureStyle.PROPORTIONAL_LINING OTFFigureStyle.PROPORTIONAL_OLDSTYLE OTFFigureStyle.TABULAR_LINING OTFFigureStyle.TABULAR_OLDSTYLE	read/write	The f Oper
otfFraction	Boolean	read/write	If tru Oper
otfHVKana	Boolean	read/write	If tru font: diffe horiz
otfHistorical	Boolean	read/write	If tru form
otfJustificationAlternate	Boolean	read/write	If tru justif Oper
otfLocale	Boolean	read/write	If tru form
otfMark	Boolean	read/write	If tru posit font:
otfOrdinal	Boolean	read/write	If tru Oper
otfOverlapSwash	Boolean	read/write	If tru swas font:
otfProportionalMetrics	Boolean	read/write	If tru prop in Op
otfRomanItalics	Boolean	read/write	If tru half-
otfSlashedZero	Boolean	read/write	If tru zero
otfStretchedAlternate	Boolean	read/write	If tru alter Oper
otfStylisticAlternate	Boolean	read/write	If tru alter Oper
otfStylisticSets	Number	read/write	The : Oper

Property	Type	Access	Desc
otfSwash	Boolean	read/write	If true in OpenType font
otfTitling	Boolean	read/write	If true in OpenType font
ovals	Ovals <i>Oval</i>	readonly	A collection of ovals
overflows	Boolean	readonly	If true overflows the page
overprintFill	Boolean	read/write	If true characters are overprinted with fill
overprintStroke	Boolean	read/write	If true characters are overprinted with stroke
pageItems	PageItems <i>PageItem</i>	readonly	The page items which are part of the document group
paraStyleMappings	ParaStyleMappings <i>ParaStyleMapping</i>	readonly	A collection of paragraph style mappings
paragraphBorderBottomLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The bottom-left corner option of the rectangle
paragraphBorderBottomLeftCornerRadius	Number String	read/write	The bottom-left corner radius of the rectangle
paragraphBorderBottomLineWeight	Number String	read/write	The bottom line weight of the text
paragraphBorderBottomOffset	Number String	read/write	The bottom offset of the paragraph
paragraphBorderBottomOrigin	ParagraphBorderBottomOriginEnum ParagraphBorderBottomOriginEnum.BASELINE_BOTTOM_ORIGIN ParagraphBorderBottomOriginEnum.DESCENT_BOTTOM_ORIGIN	read/write	The bottom origin of the paragraph
paragraphBorderBottomRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The bottom-right corner option of the rectangle
paragraphBorderBottomRightCornerRadius	Number String	read/write	The bottom-right corner radius of the rectangle
paragraphBorderColor	Swatch String	read/write	The color of the paragraph border (gradient or solid color)
paragraphBorderDisplayIfSplits	Boolean	read/write	If true the paragraph border is displayed if the paragraph is split
paragraphBorderGapColor	Swatch String	read/write	The color of the paragraph border gap (gradient or solid color)

Property	Type	Access	Desc
			para: Note bord Can i
paragraphBorderGapOverprint	Boolean	read/write	Strin If tru bord Note bord
paragraphBorderGapTint	Number (range 0 - 100)	read/write	The i of th gap. when not s 100)
paragraphBorderLeftLineWeight	Number String	read/write	The l bord
paragraphBorderLeftOffset	Number String	read/write	The i left e bord
paragraphBorderOn	Boolean	read/write	If tru bord
paragraphBorderOverprint	Boolean	read/write	If tru bord
paragraphBorderRightLineWeight	Number String	read/write	The i the b
paragraphBorderRightOffset	Number String	read/write	The i right para
paragraphBorderStrokeEndCap	EndCap EndCap.BUTT_END_CAP EndCap.PROJECTING_END_CAP EndCap.ROUND_END_CAP	read/write	The i path
paragraphBorderStrokeEndJoin	EndJoin EndJoin.BEVEL_END_JOIN EndJoin.MITER_END_JOIN EndJoin.ROUND_END_JOIN	read/write	The i the S
paragraphBorderTint	Number (range 0 - 100)	read/write	The i of th (Ran
paragraphBorderTopLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The i to th recta corn recta corn end j set a optic roun of ar the s
paragraphBorderTopLeftCornerRadius	Number String	read/write	The i mea: corn the t recta corn recta
paragraphBorderTopLineWeight	Number String	read/write	The i bord
paragraphBorderTopOffset	Number String	read/write	The i top e bord
paragraphBorderTopOrigin	ParagraphBorderTopOriginEnum ParagraphBorderTopOriginEnum.ASCENT_TOP_ORIGIN ParagraphBorderTopOriginEnum.BASELINE_TOP_ORIGIN	read/write	The l asce

Property	Type	Access	Description
	ParagraphBorderTopOriginEnum .LEADING_TOP_ORIGIN		to calculate the top right corner of the rectangle
paragraphBorderTopRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	
paragraphBorderTopRightCornerRadius	Number String	read/write	The measurement of the corner of the rectangle
paragraphBorderType	StrokeStyle String	read/write	The type of the border returned as a string
paragraphBorderWidth	ParagraphBorderEnum ParagraphBorderEnum.COLUMN_WIDTH ParagraphBorderEnum.TEXT_WIDTH	read/write	The border width calculated for the paragraph
paragraphDirection	ParagraphDirectionOptions ParagraphDirectionOptions.LEFT_TO_RIGHT_DIRECTION ParagraphDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	Paragraph direction
paragraphGyoudori	Boolean	read/write	If true, apply paragraph gyoudori to each paragraph
paragraphJustification	ParagraphJustificationOptions ParagraphJustificationOptions.ARABIC_JUSTIFICATION ParagraphJustificationOptions.DEFAULT_JUSTIFICATION ParagraphJustificationOptions.NASKH_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION ParagraphJustificationOptions.NASKH_KASHIDA_JUSTIFICATION_FRAC ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION ParagraphJustificationOptions.NASKH_TATWEEL_JUSTIFICATION_FRAC	read/write	Paragraph justification
paragraphKashidaWidth	Number	read/write	Paragraph kashida width. 0 is recommended
paragraphShadingBottomLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The shading bottom left corner of the rectangle
paragraphShadingBottomLeftCornerRadius	Number String	read/write	The measurement of the corner of the rectangle
paragraphShadingBottomOffset	Number String	read/write	The shading bottom offset of the paragraph
paragraphShadingBottomOrigin	ParagraphShadingBottomOriginEnum ParagraphShadingBottomOriginEnum.BASELINE_BOTTOM_ORIGIN ParagraphShadingBottomOriginEnum.DESCENT_BOTTOM_ORIGIN	read/write	The shading bottom origin of the paragraph
paragraphShadingBottomRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The shading bottom right corner of the rectangle

Property	Type	Access	Description
paragraphShadingBottomRightCornerRadius	Number String	read/write	The measurement of the bottom right corner of the rectangle.
paragraphShadingClipToFrame	Boolean	read/write	If true, the shading is clipped to the frame of the paragraph.
paragraphShadingColor	Swatch String	read/write	The color of the shading (as a swatch or a hex color string).
paragraphShadingLeftOffset	Number String	read/write	The offset of the shading from the left edge of the paragraph.
paragraphShadingOn	Boolean	read/write	If true, the shading is applied to the paragraph.
paragraphShadingOverprint	Boolean	read/write	If true, the shading is overprinted on top of other content.
paragraphShadingRightOffset	Number String	read/write	The offset of the shading from the right edge of the paragraph.
paragraphShadingSuppressPrinting	Boolean	read/write	If true, the shading is suppressed from printing.
paragraphShadingTint	Number (range 0 - 100)	read/write	The tint of the shading, expressed as a percentage of the original color.
paragraphShadingTopLeftCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top left corner of the rectangle.
paragraphShadingTopLeftCornerRadius	Number String	read/write	The measurement of the top left corner of the rectangle.
paragraphShadingTopOffset	Number String	read/write	The offset of the shading from the top edge of the paragraph.
paragraphShadingTopOrigin	ParagraphShadingTopOriginEnum ParagraphShadingTopOriginEnum.ASCENT_TOP_ORIGIN ParagraphShadingTopOriginEnum.BASELINE_TOP_ORIGIN ParagraphShadingTopOriginEnum.LEADING_TOP_ORIGIN	read/write	The origin of the shading at the top of the paragraph.
paragraphShadingTopRightCornerOption	CornerOptions CornerOptions.BEVEL_CORNER CornerOptions.FANCY_CORNER CornerOptions.INSET_CORNER CornerOptions.INVERSE_ROUNDED_CORNER CornerOptions.NONE CornerOptions.ROUNDED_CORNER	read/write	The corner option for the top right corner of the rectangle.
paragraphShadingTopRightCornerRadius	Number String	read/write	The measurement of the top right corner of the rectangle.

Property	Type	Access	Desc
			the t
paragraphShadingWidth	ParagraphShadingWidthEnum ParagraphShadingWidthEnum.COLUMN_WIDTH ParagraphShadingWidthEnum.TEXT_WIDTH	read/write	recta the colu calcu para
paragraphs	Paragraphs <i>Paragraph</i>	readonly	A col para
parent	Document XMLElement	readonly	The XML Docu
pointSize	Number String	read/write	The t
polygons	Polygons <i>Polygon</i>	readonly	A col
position	Position Position.NORMAL Position.OT_DENOMINATOR Position.OT_NUMERATOR Position.OT_SUBSCRIPT Position.OT_SUPERSCRIPT Position.SUBSCRIPT Position.SUPERSCRIPT	read/write	The t to th
positionalForm	PositionalForms PositionalForms.CALCULATE PositionalForms.FINAL PositionalForms.INITIAL PositionalForms.ISOLATED PositionalForms.MEDIAL PositionalForms.NONE	read/write	The form
preferences	Preferences <i>Preference</i>	readonly	A col prefe
properties	Object	read/write	A pro setti prop time
providerHyphenationStyle	HyphenationStyleEnum HyphenationStyleEnum.HYPH_AESTHETIC HyphenationStyleEnum.HYPH_ALL HyphenationStyleEnum.HYPH_ALL_BUT_UNAESTHETIC HyphenationStyleEnum.HYPH_PREFERRED_AESTHETIC	read/write	The l chos
radioButtons	RadioButtons <i>RadioButton</i>	readonly	A col buttc
rectangles	Rectangles <i>Rectangle</i>	readonly	A col
rensuuji	Boolean	read/write	If tru brea false betw digit
rightIndent	Number String	read/write	The inde
rotateSingleByteCharacters	Boolean	read/write	If tru char:
rubyAlignment	RubyAlignments RubyAlignments.RUBY_1_AKI RubyAlignments.RUBY_CENTER RubyAlignments.RUBY_EQUAL_AKI RubyAlignments.RUBY_FULL_JUSTIFY RubyAlignments.RUBY_JIS RubyAlignments.RUBY_LEFT RubyAlignments.RUBY_RIGHT	read/write	The
rubyAutoAlign	Boolean	read/write	If tru
rubyAutoScaling	Boolean	read/write	If tru scale spec pare infor

Property	Type	Access	Desc
			a per
rubyAutoTcyAutoScale	Boolean	read/write	scalh If tru scale (tate to fit
rubyAutoTcyDigits	Number	read/write	The i inclu chuu
rubyAutoTcyIncludeRoman	Boolean	read/write	If tru char: (tate
rubyFill	Swatch String	read/write	The : grad ink) ; ruby retur
rubyFlag	Boolean	read/write	If tru
rubyFont	Font String	read/write	The f char: Font
rubyFontSize	Number	read/write	The : char:
rubyFontStyle	String NothingEnum.NOTHING	read/write	The f char: Strin enur
rubyOpenTypePro	Boolean	read/write	If tru font:
rubyOverhang	Boolean	read/write	If tru over amo on sp see r amo
rubyOverprintFill	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The i over
rubyOverprintStroke	AdornmentOverprint AdornmentOverprint.AUTO AdornmentOverprint.OVERPRINT_OFF AdornmentOverprint.OVERPRINT_ON	read/write	The i over stro
rubyParentOverhangAmount	RubyOverhang RubyOverhang.NONE RubyOverhang.RUBY_OVERHANG_HALF_CHAR RubyOverhang.RUBY_OVERHANG_HALF_RUBY RubyOverhang.RUBY_OVERHANG_NO_LIMIT RubyOverhang.RUBY_OVERHANG_ONE_CHAR RubyOverhang.RUBY_OVERHANG_ONE_RUBY	read/write	The i ruby over
rubyParentScalingPercent	Number	read/write	The i perc pare dete size.
rubyParentSpacing	RubyParentSpacing RubyParentSpacing.RUBY_PARENT_121_AKI RubyParentSpacing.RUBY_PARENT_BOTH_SIDES RubyParentSpacing.RUBY_PARENT_EQUAL_AKI RubyParentSpacing.RUBY_PARENT_FULL_JUSTIFY RubyParentSpacing.RUBY_PARENT_NO_ADJUSTMENT	read/write	The i to th
rubyPosition	RubyKentenPosition RubyKentenPosition.ABOVE_RIGHT RubyKentenPosition.BELOW_LEFT	read/write	The i char: pare
rubyString	String	read/write	The i

Property	Type	Access	Description
rubyStroke	Swatch String	read/write	The stroke color (in hexadecimal) of the ruby text.
rubyStrokeTint	Number	read/write	The stroke tint (percentage) of the ruby text.
rubyTint	Number (range 0 - 100)	read/write	The tint (percentage) of the ruby text. (Range: 0 - 100)
rubyType	RubyTypes RubyTypes.GROUP_RUBY RubyTypes.PER_CHARACTER_RUBY	read/write	The ruby type.
rubyWeight	Number	read/write	The weight of the ruby text.
rubyXOffset	Number	read/write	The x offset of the ruby text.
rubyXScale	Number	read/write	The x scale of the ruby text.
rubyYOffset	Number	read/write	The y offset of the ruby text.
rubyYScale	Number	read/write	The y scale of the ruby text.
ruleAbove	Boolean	read/write	If true, the rule is above the text.
ruleAboveColor	Swatch String	read/write	The stroke color (in hexadecimal) of the rule above the text.
ruleAboveGapColor	Swatch String	read/write	The stroke color (in hexadecimal) of the gap above the text.
ruleAboveGapOverprint	Boolean	read/write	If true, the gap above the text will be overprinted.
ruleAboveGapTint	Number (range 0 - 100)	read/write	The tint (percentage) of the gap above the text. (Range: 0 - 100)
ruleAboveLeftIndent	Number String	read/write	The left indent of the rule above the text.
ruleAboveLineWeight	Number String	read/write	The line weight of the rule above the text.

Property	Type	Access	Desc
ruleAboveOffset	Number String	read/write	The i para from first
ruleAboveOverprint	Boolean	read/write	If tru abov
ruleAboveRightIndent	Number String	read/write	The i right para (base width width the p
ruleAboveTint	Number (range 0 - 100)	read/write	The t of th abov
ruleAboveType	StrokeStyle String	read/write	The : abov retur Strin
ruleAboveWidth	RuleWidth RuleWidth.COLUMN_WIDTH RuleWidth.TEXT_WIDTH	read/write	The l colu calcu para
ruleBelow	Boolean	read/write	If tru para
ruleBelowColor	Swatch String	read/write	The : grad ink) ; para retur
ruleBelowGapColor	Swatch String	read/write	The : grad ink) ; gap c below when below Can i Strin
ruleBelowGapOverprint	Boolean	read/write	If tru the r over
ruleBelowGapTint	Number (range 0 - 100)	read/write	The t of th the p (Ran Valid para is no
ruleBelowLeftIndent	Number String	read/write	The i left e rule eithe the c last l
ruleBelowLineWeight	Number String	read/write	The l below
ruleBelowOffset	Number String	read/write	The i the p from last l
ruleBelowOverprint	Boolean	read/write	If tru over
ruleBelowRightIndent	Number String	read/write	The i right

Property	Type	Access	Desc
			para: (base width, width of the p
ruleBelowTint	Number (range 0 - 100)	read/write	The t of th below
ruleBelowType	StrokeStyle String	read/write	The : below retur String
ruleBelowWidth	RuleWidth RuleWidth.COLUMN_WIDTH RuleWidth.TEXT_WIDTH	read/write	The l colu calcu para:
sameParaStyleSpacing	Unit Spacing Spacing.SETIGNORE	read/write	The : para: style Spac
scaleAffectsLineHeight	Boolean	read/write	If tru size \ scale
shataiAdjustRotation	Boolean	read/write	If tru rotat
shataiAdjustTsume	Boolean	read/write	If tru tsum
shataiDegreeAngle	Number	read/write	The : degr
shataiMagnification	Number	read/write	The : perc oblic
signatureFields	SignatureFields <i>SignatureField</i>	readonly	A col field:
singleWordJustification	SingleWordJustification SingleWordJustification.CENTER_ALIGN SingleWordJustification.FULLY_JUSTIFIED SingleWordJustification.LEFT_ALIGN SingleWordJustification.RIGHT_ALIGN	read/write	The : lines worc
skew	Number	read/write	The : Story
spaceAfter	Number String	read/write	The l para:
spaceBefore	Number String	read/write	The l para:
spanColumnMinSpaceAfter	Number String	read/write	The l a spa
spanColumnMinSpaceBefore	Number String	read/write	The l befo colu
spanColumnType	SpanColumnTypeOptions SpanColumnTypeOptions.SINGLE_COLUMN SpanColumnTypeOptions.SPAN_COLUMNS SpanColumnTypeOptions.SPLIT_COLUMNS	read/write	Whe shou span colu
spanSplitColumnCount	ShortInteger(1-40) SpanColumnCountOptions SpanColumnCountOptions.ALL	read/write	The l para: num Can (1 - 4 Span enur
splineItems	SplineItems <i>SplineItem</i>	readonly	The : colle
splitColumnInsideGutter	Number String	read/write	The i para:

Property	Type	Access	Description
splitColumnOutsideGutter	Number String	read/write	The column split position outside the gutter.
startParagraph	StartParagraph StartParagraph.ANYWHERE StartParagraph.NEXT_COLUMN StartParagraph.NEXT_EVEN_PAGE StartParagraph.NEXT_FRAME StartParagraph.NEXT_ODD_PAGE StartParagraph.NEXT_PAGE	read/write	The paragraph start position.
storyPreferences	StoryPreference	readonly	Story preferences.
storyTitle	String	read/write	Story title.
storyType	StoryTypes StoryTypes.ENDNOTE_STORY StoryTypes.INDEXING_STORY StoryTypes.REGULAR_STORY StoryTypes.TOC_STORY	readonly	Story type.
strikeThroughColor	Swatch String	read/write	The color of the strike-through line.
strikeThroughGapColor	Swatch String	read/write	The color of the gap between the strike-through lines.
strikeThroughGapOverprint	Boolean	read/write	If true, the gap between the strike-through lines will be overprinted.
strikeThroughGapTint	Number (range 0 - 100)	read/write	The tint of the gap between the strike-through lines.
strikeThroughOffset	Number String	read/write	The offset of the strike-through line from the baseline.
strikeThroughOverprint	Boolean	read/write	If true, the strike-through line will be overprinted.
strikeThroughTint	Number (range 0 - 100)	read/write	The tint of the strike-through line.
strikeThroughType	StrokeStyle String	read/write	The stroke style of the strike-through line.
strikeThroughWeight	Number String	read/write	The weight of the strike-through line.
strikeThru	Boolean	read/write	If true, the strike-through line is applied to the text.
strokeAlignment	TextStrokeAlign TextStrokeAlign.CENTER_ALIGNMENT TextStrokeAlign.OUTSIDE_ALIGNMENT	read/write	The alignment of the stroke.
strokeColor	Swatch String	read/write	The color of the stroke.

Property	Type	Access	Description
strokeTint	Number (range 0 - 100)	read/write	The tint of the stroke, as a percentage of the story's color, in the range 0 to 100.
strokeWeight	Number String	read/write	The weight of the stroke, in points.
styleOverridden	Boolean	readonly	If true, the style is overridden by the text's style.
tabList	Array of Arrays of Property Name/Value Pairs.	read/write	A list of the text's tabs, each represented by a Property Name/Value Pairs object.
tabStops	TabStops <i>TabStop</i>	readonly	A collection of the text's tab stops.
tableStyleMappings	TableStyleMappings <i>TableStyleMapping</i>	readonly	A collection of the text's table style mappings.
tables	Tables <i>Table</i>	readonly	A collection of the text's tables.
tatechuyoko	Boolean	read/write	If true, the text is rotated vertically.
tatechuyokoXOffset	Number	read/write	The horizontal offset of the text, in points.
tatechuyokoYOffset	Number	read/write	The vertical offset of the text, in points.
textBoxes	TextBoxes	readonly	A collection of the text's text boxes.
textColumns	TextColumns <i>TextColumn</i>	readonly	A collection of the text's text columns.
textContainers	Array of TextFrames Array of TextPaths <i>TextPath</i>	readonly	An array of the text's text containers.
textFrames	TextFrames <i>TextFrame</i>	readonly	A collection of the text's text frames.
textStyleRanges	TextStyleRanges <i>TextStyleRange</i>	readonly	A collection of the text's text style ranges.
textVariableInstances	TextVariableInstances <i>TextVariableInstance</i>	readonly	A collection of the text's text variable instances.
texts	Texts <i>Text</i>	readonly	A collection of the text's text objects.
trackChanges	Boolean	read/write	If true, the text's changes are tracked.
tracking	Number	read/write	The tracking of the text, in points.
trailingAki	Number	read/write	The trailing aki of the text, in points.
treatIdeographicSpaceAsSpace	Boolean	read/write	If true, ideographic space will be treated as space.
tsume	Number	read/write	The tsume of the text, in points.
underline	Boolean	read/write	If true, the text is underlined.
underlineColor	Swatch String	read/write	The color of the underline, as a percentage of the story's color, in the range 0 to 100.

Property	Type	Access	Description
			ink) ; under retur
underlineGapColor	Swatch String	read/write	The : grad ink) ; the u Note unde solid or St
underlineGapOverprint	Boolean	read/write	If tru the u over
underlineGapTint	Number (range 0 - 100)	read/write	The f of th unde 0 to when not s
underlineOffset	Number String	read/write	The : offse the t
underlineOverprint	Boolean	read/write	If tru strok
underlineTint	Number (range 0 - 100)	read/write	The : (as a 0 to
underlineType	StrokeStyle String	read/write	The : unde retur Strin
underlineWeight	Number String	read/write	The : unde
userText	Boolean	read/write	Indic is us text.
verticalScale	Number	read/write	The v appli
warichu	Boolean	read/write	If tru
warichuAlignment	WarichuAlignment WarichuAlignment.AUTO WarichuAlignment.CENTER_ALIGN WarichuAlignment.CENTER_JUSTIFIED WarichuAlignment.FULLY_JUSTIFIED WarichuAlignment.LEFT_ALIGN WarichuAlignment.LEFT_JUSTIFIED WarichuAlignment.RIGHT_ALIGN WarichuAlignment.RIGHT_JUSTIFIED	read/write	The v
warichuCharsAfterBreak	Number	read/write	The : char; line l
warichuCharsBeforeBreak	Number	read/write	The : char; a line
warichuLineSpacing	Number	read/write	The g wari
warichuLines	Number	read/write	The : wari norm
warichuSize	Number	read/write	The : perc pare dete
words	Words <i>Word</i>	readonly	A col

Property	Type	Access	Description
xOffsetDiacritic	Number	read/write	The x offset for the diacritic.
yOffsetDiacritic	Number	read/write	The y offset for the diacritic.

Constants/Events

Name	Type	Access	Description
AFTER_PLACE	String	readonly	Dispatched after a Story is placed. This event bubbles. This event is not cancelable.
BEFORE_PLACE	String	readonly	Dispatched before a Story is placed. This event bubbles. This event is cancelable.

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

BackgroundTask **asynchronousExportFile** (format:Varies ExportFormat String, to:File, [showingOptions:Boolean=Boolean], using:PDFExportPreset, versionComments:String, [forceSave:Boolean=Boolean])

asynchronously exports the object(s) to a file.

Parameter	Type	Description
format	ExportFormat ExportFormat.EPS_TYPE ExportFormat.EPUB ExportFormat.FIXED_LAYOUT_EPUB ExportFormat.HTML ExportFormat.HTMLFXL ExportFormat.INCOPY_MARKUP ExportFormat.INDESIGN_MARKUP ExportFormat.INDESIGN_SNIPPET ExportFormat.INTERACTIVE_PDF ExportFormat.JPG ExportFormat.PDF_TYPE ExportFormat.PNG_FORMAT ExportFormat.RTF ExportFormat.TAGGED_TEXT ExportFormat.TEXT_TYPE ExportFormat.XML String	The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String.
to	File	The path to the export file.
showingOptions	Boolean	If true, displays the export options dialog. (Optional) (default: false)
using	PDFExportPreset	The export style. (Optional)
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

undefined **autoTag** ()

Tag the object or the parent story using default tags defined in XML preference.

Text **changeGlyph** (reverseOrder:Boolean)

Finds glyphs that match the find what value and replaces the glyphs with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeText** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value and replaces the text with the change character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

undefined **changeCase** (using:*ChangeCaseMode*)

Sets the case of the text.

Parameter	Type	Description
using	ChangeCaseMode ChangeCaseMode.LOWERCASE ChangeCaseMode.SENTENCECASE ChangeCaseMode.TITLECASE ChangeCaseMode.UPPERCASE	The text case option.

Boolean **checkIn** (versionComments:*String*, [forceSave:*Boolean*=Boolean])

Checks in the story or stories.

Parameter	Type	Description
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

Boolean **checkOut** ()

Checks out the story.

undefined **clearOverrides** ([overridesToClear:*OverrideType*=OverrideType])

Clears the specified types of override.

Parameter	Type	Description
overridesToClear	OverrideType OverrideType.ALL OverrideType.CHARACTER_ONLY OverrideType.PARAGRAPH_ONLY	The types of override to clear. (Optional) (default: OverrideType.ALL)

undefined **convertBulletsAndNumberingToText** ()

Convert bullets and numbering to text.

PageItem **createOutlines** ([deleteOriginal:*Boolean*=Boolean])

Converts text to outlines. Each line of text becomes a polygon object. When the converted text is a single letter that has no internal spaces or detached parts, the polygon contains only a single path. Note: To determine whether a font allows the creation of outlines, see allow outlines.

Parameter	Type	Description
deleteOriginal	Boolean	If true, deletes the original text. If false, creates the outlines as separate object(s) on top of the text. (Optional) (default: true)

Text **duplicate** (to:*LocationOptions*, reference:*Varies Cell Column Row Story Table Text PageItem*)

Duplicates the text in the specified location.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER	The location relative to the reference object or within the containing object.

Parameter	Type	Description
	LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE	
reference	LocationOptions.UNKNOWN Cell Column Row Story Table Text PageItem	The reference object. Note: Required when the to parameter specifies before or after. Can accept: Text, Story, Cell, Row, Column, Table or PageItem. (Optional)

undefined **exportFile** (format:*Varies ExportFormat String*, to:*File*, [showingOptions:*Boolean*=Boolean], using:*PDFExportPreset*, versionComments:*String*, [forceSave:*Boolean*=Boolean])

Exports the object(s) to a file.

Parameter	Type	Description
format	ExportFormat ExportFormat.EPS_TYPE ExportFormat.EPUB ExportFormat.FIXED_LAYOUT_EPUB ExportFormat.HTML ExportFormat.HTMLFXL ExportFormat.INCOPY_MARKUP ExportFormat.INDESIGN_MARKUP ExportFormat.INDESIGN_SNIPPET ExportFormat.INTERACTIVE_PDF ExportFormat.JPG ExportFormat.PDF_TYPE ExportFormat.PNG_FORMAT ExportFormat.RTF ExportFormat.TAGGED_TEXT ExportFormat.TEXT_TYPE ExportFormat.XML String	The export format, specified as an enumeration value or as an extension that appears in the Save as type or Format menu in the Export dialog. Can accept: ExportFormat enumerator or String.
to	File	The path to the export file.
showingOptions	Boolean	If true, displays the export options dialog. (Optional) (default: false)
using	PDFExportPreset	The export style. (Optional)
versionComments	String	The comment for this version. (Optional)
forceSave	Boolean	If true, forcibly saves a version. (Optional) (default: false)

String **extractLabel** (key:*String*)

Gets the label value associated with the specified key.

Parameter	Type	Description
key	String	The key.

Text **findGlyph** (reverseOrder:*Boolean*)

Finds glyphs that match the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findText** (reverseOrder:*Boolean*)

Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Story **getElements** ()

Resolves the object specifier, creating an array of object references.

undefined **insertLabel** (key:*String*, value:*String*)

Sets the label to the value associated with the specified key.

Parameter	Type	Description
key	String	The key.
value	String	The value.

Boolean **isNthDesignAxisHidden** (nthAxisIndex:*Number*)

If true, Nth design axis of variable font is hidden.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.

undefined **markup** (using:*XMLElement*)

Associates the page item with the specified XML element while preserving existing content.

Parameter	Type	Description
using	XMLElement	The XML element.

Text **move** (to:*LocationOptions*, reference:*Varies Cell Column Row Story Table Text PageItem*)

Moves the text to the specified location.

Parameter	Type	Description
to	LocationOptions LocationOptions.AFTER LocationOptions.AT_BEGINNING LocationOptions.AT_END LocationOptions.BEFORE LocationOptions.UNKNOWN	The location relative to the reference object or within the containing object.
reference	Cell Column Row Story Table Text PageItem	The reference object. Note: Required when the to parameter specifies before or after. Can accept: Text, Story, Cell, Row, Column, Table or PageItem. (Optional)

undefined **placeXML** (using:*XMLElement*)

Places XML content into the specified object. Note: Replaces any existing content.

Parameter	Type	Description
using	XMLElement	The XML element whose content you want to place.

undefined **recompose** ()

Recomposes the text in the Story.

undefined **remove** ()

Deletes the Story.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=Boolean])

Removes the event listener.

Parameter	Type	Description
eventType	String	The registered event type.
handler	File JavaScriptFunction	The registered event handler. Can accept: File or JavaScript Function.

Parameter	Type	Description
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

Boolean **revert** ()

Reverts the document to its state at the last save operation.

undefined **setNthDesignAxis** (nthAxisIndex:*Number*, nthAxisValue:*Number*)

Set Nth design axis of a variable font.

Parameter	Type	Description
nthAxisIndex	Number	Index of design axis.
nthAxisValue	Number	Value of nth design axis.

StoryWindow **storyEdit** ()

Opens the story in a story editor window.

String **toSource** ()

Generates a string which, if executed, will return the Story.

String **toSpecifier** ()

Retrieves the object specifier.

Object of

- AssignedStory.storyReference
- Bullet.parent
- CellStyleMapping.parent
- Change.parent
- CharStyleMapping.parent
- Character.parent
- Endnote.parent
- EndnoteRange.parent
- Event.parent
- EventListener.parent
- Footnote.parent
- GridDataInformation.parent
- HiddenText.parent
- InCopyExportOption.parent
- InsertionPoint.parent
- Line.parent
- LinkedStoryOption.parent
- MutationEvent.parent
- NestedGrepStyle.parent
- NestedLineStyle.parent
- NestedStyle.parent
- Note.parent
- NumberingRestartPolicy.parent
- ParaStyleMapping.parent
- Paragraph.parent
- Preference.parent
- StoryPreference.parent
- TabStop.parent
- Table.parent
- TableStyleMapping.parent
- Text.parent
- TextColumn.parent
- TextStyleRange.parent
- TextVariableInstance.parent
- Word.parent
- DataMergeTextPlaceholder.parentStory
- Text.parentStory
- Character.parentStory
- Word.parentStory
- Line.parentStory
- TextColumn.parentStory
- Paragraph.parentStory
- TextStyleRange.parentStory
- InsertionPoint.parentStory
- TextFrame.parentStory

[EndnoteTextFrame.parentStory](#)
[TextPath.parentStory](#)
[XMLElement.parentStory](#)
[XMLElement.xmlContent](#)

Return

[Document.createTOC\(\)](#)
[TextFrame.placeAndLink\(\)](#)
[EndnoteTextFrame.placeAndLink\(\)](#)
[Spread.placeAndLink\(\)](#)
[Page.placeAndLink\(\)](#)
[MasterSpread.placeAndLink\(\)](#)
[Index.generate\(\)](#)
[Story.getElements\(\)](#)
[Stories.anyItem\(\)](#)
[Stories.everyItem\(\)](#)
[Stories.itemByRange\(\)](#)
[Stories.nextItem\(\)](#)
[Stories.previousItem\(\)](#)
[Stories.itemByID\(\)](#)
[Stories.item\(\)](#)
[Stories.\[\]\(\)](#)
[Stories.itemByName\(\)](#)
[Stories.firstItem\(\)](#)
[Stories.lastItem\(\)](#)
[Stories.middleItem\(\)](#)
