

Table

A table.

[Go to Property Listing](#) | [Method Listing](#)

Methods:

[addEventListener](#), [autoTag](#), [changeGlyph](#), [changeGrep](#), [changeText](#), [changeTransliterate](#), [clearTableStyleOverrides](#), [convertBulletsAndNumberingToText](#), [convertToText](#), [createOutlines](#), [extractLabel](#), [findGlyph](#), [findGrep](#), [findText](#), [findTransliterate](#), [getElements](#), [insertLabel](#), [markup](#), [recompose](#), [remove](#), [removeEventListener](#), [select](#), [toSource](#), [toSpecifier](#), [unmerge](#)

Objects:

[AlternatingFillsTypes](#), [Boolean](#), [Buttons](#), [Cells](#), [Changes](#), [CheckBoxes](#), [Columns](#), [ComboBoxes](#), [DisplayOrderOptions](#), [EPSTexts](#), [EndnoteTextFrames](#), [Endnotes](#), [EventListeners](#), [Events](#), [Footnotes](#), [FormFields](#), [Graphic](#), [GraphicLines](#), [Groups](#), [HeaderFooterBreakTypes](#), [HiddenTexts](#), [ListBoxes](#), [MultiStateObjects](#), [Notes](#), [Number](#), [Object](#), [Ovals](#), [PageItem](#), [PageItems](#), [Polygons](#), [RadioButtons](#), [Rectangles](#), [Rows](#), [SignatureFields](#), [SpecialCharacters](#), [SplinelItems](#), [String](#), [StrokeOrderTypes](#), [StrokeStyle](#), [Swatch](#), [TableDirectionOptions](#), [TableStyle](#), [TextBoxes](#), [TextFrames](#), [TextVariableInstances](#), [XMLItem](#),

Property Listing

Property	Type	Access	Description
allGraphics	Array of Graphic	readonly	Lists all graphics contained by the Table.
allPageItems	Array of PageItem	readonly	Lists all page items contained by the Table.
alternatingFills	AlternatingFillsTypes AlternatingFillsTypes.ALTERNATING_COLUMNS AlternatingFillsTypes.ALTERNATING_ROWS AlternatingFillsTypes.NO_ALTERNATING_PATTERN	read/write	The pattern for alternating fills.
appliedTableStyle	TableStyle String	read/write	The table style applied to the table. Can also accept: String.
associatedXMLElement	XMLItem	readonly	The XML element associated with the Table.
bodyRowCount	Number (range 1 - 10000)	read/write	The number of body rows.
bottomBorderStrokeColor	Swatch	read/write	The color, specified as a swatch (color, gradient, tint, or mixed ink), of the bottom border stroke.
bottomBorderStrokeGapColor	Swatch	read/write	The gap color, specified as a swatch (color, gradient, tint, or

Property	Type	Access	Description
			mixed ink), of the bottom border stroke. Note: Valid only when bottom border stroke type is not solid.
bottomBorderStrokeGapOverprint	Boolean	read/write	If true, the gap of the bottom border stroke will overprint. Note: Valid only when bottom border stroke type is not solid.
bottomBorderStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of the bottom border stroke. (Range: 0 to 100) Note: Valid only when bottom border stroke type is not solid.
bottomBorderStrokeOverprint	Boolean	read/write	If true, the bottom border stroke will overprint.
bottomBorderStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the bottom border stroke. (Range: 0 to 100)
bottomBorderStrokeType	StrokeStyle String	read/write	The stroke type of the bottom border. Can also accept: String.
bottomBorderStrokeWeight	Number String	read/write	The stroke weight of the bottom border stroke.
breakFooters	HeaderFooterBreakTypes HeaderFooterBreakTypes.IN_ALL_TEXT_COLUMNS HeaderFooterBreakTypes.ONCE_PER_PAGE HeaderFooterBreakTypes.ONCE_PER_TEXT_FRAME	read/write	The footer placement.
breakHeaders	HeaderFooterBreakTypes HeaderFooterBreakTypes.IN_ALL_TEXT_COLUMNS HeaderFooterBreakTypes.ONCE_PER_PAGE HeaderFooterBreakTypes.ONCE_PER_TEXT_FRAME	read/write	The header placement.
buttons	Buttons <i>Button</i>	readonly	A collection of buttons.
cells	Cells <i>Cell</i>	readonly	A collection of table cells.
changes	Changes <i>Change</i>	readonly	A collection of changes.

Property	Type	Access	Description
checkboxes	CheckBoxes	readonly	A collection of checkboxes.
clipContentToGraphicCell	Boolean	read/write	If true, clips the graphic cell's content to width and height of the cell.
clipContentToTextCell	Boolean	read/write	If true, clips the text cell's content to width and height of the cell.
columnCount	Number (range 1 - 200)	read/write	The number of columns.
columnFillsPriority	Boolean	read/write	If true, hides alternating row fills. If false, hides alternating column fills.
columns	Columns <i>Column</i>	readonly	A collection of table columns.
comboBoxes	ComboBoxes	readonly	A collection of comboboxes.
contents	Array of Strings Array of SpecialCharacters SpecialCharacters.ARABIC_COMMA SpecialCharacters.ARABIC_KASHIDA SpecialCharacters.ARABIC_QUESTION_MARK SpecialCharacters.ARABIC_SEMICOLON SpecialCharacters.AUTO_PAGE_NUMBER SpecialCharacters.BULLET_CHARACTER SpecialCharacters.COLUMN_BREAK SpecialCharacters.COPYRIGHT_SYMBOL SpecialCharacters.DEGREE_SYMBOL SpecialCharacters.DISCRETIONARY_HYPHEN SpecialCharacters.DISCRETIONARY_LINE_BREAK SpecialCharacters.DOTTED_CIRCLE SpecialCharacters.DOUBLE_LEFT_QUOTE SpecialCharacters.DOUBLE_RIGHT_QUOTE SpecialCharacters.DOUBLE_STRAIGHT_QUOTE SpecialCharacters.ELLIPSIS_CHARACTER SpecialCharacters.EM_DASH SpecialCharacters.EM_SPACE SpecialCharacters.END_NESTED_STYLE SpecialCharacters.EN_DASH SpecialCharacters.EN_SPACE SpecialCharacters.EVEN_PAGE_BREAK SpecialCharacters.FIGURE_SPACE SpecialCharacters.FIXED_WIDTH_NONBREAKING_SPACE SpecialCharacters.FLUSH_SPACE SpecialCharacters.FOOTNOTE_SYMBOL SpecialCharacters.FORCED_LINE_BREAK SpecialCharacters.FRAME_BREAK SpecialCharacters.HAIR_SPACE	read/write	The contents to place in cells, specified as an array whose first item populates the top left cell and whose second item populates the next cell to the right, and so on until each cell in the top row is populated, at which point the next item populates the left-most cell in the second row, and so on. Note: If the array contains fewer strings than the table contains cells, the remaining cells are left blank. Can return: Array of Strings or SpecialCharacters enumerators. Can also accept: Array of Strings, SpecialCharacters

Property	Type	Access	Description
	SpecialCharacters.HEBREW_GERESH SpecialCharacters.HEBREW_GERSHAYIM SpecialCharacters.HEBREW_MAQAF SpecialCharacters.HEBREW_SOF_PASUK SpecialCharacters.INDENT_HERE_TAB SpecialCharacters.LEFT_TO_RIGHT_EMBEDDING SpecialCharacters.LEFT_TO_RIGHT_MARK SpecialCharacters.LEFT_TO_RIGHT_OVERRIDE SpecialCharacters.NEXT_PAGE_NUMBER SpecialCharacters.NONBREAKING_HYPHEN SpecialCharacters.NONBREAKING_SPACE SpecialCharacters.ODD_PAGE_BREAK SpecialCharacters.PAGE_BREAK SpecialCharacters.PARAGRAPH_SYMBOL SpecialCharacters.POP_DIRECTIONAL_FORMATTING SpecialCharacters.PREVIOUS_PAGE_NUMBER SpecialCharacters.PUNCTUATION_SPACE SpecialCharacters.QUARTER_SPACE SpecialCharacters.REGISTERED_TRADEMARK SpecialCharacters.RIGHT_INDENT_TAB SpecialCharacters.RIGHT_TO_LEFT_EMBEDDING SpecialCharacters.RIGHT_TO_LEFT_MARK SpecialCharacters.RIGHT_TO_LEFT_OVERRIDE SpecialCharacters.SECTION_MARKER SpecialCharacters.SECTION_SYMBOL SpecialCharacters.SINGLE_LEFT_QUOTE SpecialCharacters.SINGLE_RIGHT_QUOTE SpecialCharacters.SINGLE_STRAIGHT_QUOTE SpecialCharacters.SIXTH_SPACE SpecialCharacters.TEXT_VARIABLE SpecialCharacters.THIN_SPACE SpecialCharacters.THIRD_SPACE SpecialCharacters.TRADEMARK_SYMBOL SpecialCharacters.ZERO_WIDTH_JOINER SpecialCharacters.ZERO_WIDTH_NONJOINER NothingEnums <i>NothingEnum</i> Array of SpecialCharacters enumerators. Can also accept: Strings		enumerators or NothingEnum enumerators.
displayCollapsed	Boolean	read/write	If true, then the table will show collapsed in story and galley views.
displayOrder	DisplayOrderOptions DisplayOrderOptions.ORDER_BY_COLUMNS DisplayOrderOptions.ORDER_BY_ROWS	read/write	Specifies the order the table cells will display in when viewing in story and galley views.
endColumnFillColor	Swatch	read/write	The fill color, specified as a swatch (color, gradient, tint, or mixed ink), of columns in the second alternating fill group. Note:

Property	Type	Access	Description
			Valid when alternating fills are defined for table columns.
endColumnFillCount	Number	read/write	The number of columns in the second alternating fills group. Note: Valid when alternating fills are defined for table columns.
endColumnFillOverprint	Boolean	read/write	If true, the columns in the second alternating fills group will overprint. Note: Valid when alternating fills are defined for table columns.
endColumnFillTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the columns in the second alternating fills group. (Range: 0 to 100) Note: Valid when alternating fills are defined for table columns.
endColumnLineStyle	StrokeStyle String	read/write	The stroke type of columns in the second alternating strokes group. Can also accept: String.
endColumnStrokeColor	Swatch	read/write	The stroke color, specified as a swatch (color, gradient, tint, or mixed ink), of column borders in the second alternating column strokes group. Note: Valid when end column stroke count is 1 or greater.
endColumnStrokeCount	Number	read/write	The number of columns in the second alternating column strokes group.

Property	Type	Access	Description
endColumnStrokeGapColor	Swatch	read/write	The stroke gap color, specified as a swatch (color, gradient, tint, or mixed ink), of column borders in the second alternating column strokes group. Note: Valid when end column stroke count is 1 or greater.
endColumnStrokeGapOverprint	Boolean	read/write	If true, the gap of the column border stroke in the second alternating column strokes group will overprint. Note: Valid when end column stroke count is 1 or greater.
endColumnStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of column borders in the second alternating column strokes group. (Range: 0 to 100) Note: Valid when end column stroke count is 1 or greater.
endColumnStrokeOverprint	Boolean	read/write	If true, the column borders in the second alternating column strokes group will overprint. Note: Valid when end column stroke count is 1 or greater.
endColumnStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of column borders in the second alternating column strokes group. (Range: 0 to 100) Note: Valid when

Property	Type	Access	Description
			end column stroke count is 1 or greater.
endColumnStrokeWeight	Number String	read/write	The stroke weight of column borders in the second alternating column strokes group. Note: Valid when end column stroke count is 1 or greater.
endRowFillColor	Swatch	read/write	The fill color, specified as a swatch (color, gradient, tint, or mixed ink), of rows in the second alternating fills group. Note: Valid when alternating fills are defined for table rows.
endRowFillCount	Number	read/write	The number of rows in the second alternating fills group. Note: Valid when alternating fills are defined for table rows.
endRowFillOverprint	Boolean	read/write	If true, the rows in the second alternating fills group will overprint. Note: Valid when alternating fills are defined for table rows.
endRowFillTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the rows in the second alternating fills group. (Range: 0 to 100) Note: Valid when alternating fills are defined for table rows.
endRowStrokeColor	Swatch	read/write	The stroke color, specified as a swatch (color, gradient, tint, or mixed ink), of row borders in the

Property	Type	Access	Description
			second alternating row strokes group. Note: Valid when end row stroke count is 1 or greater.
endRowStrokeCount	Number	read/write	The number of rows in the second alternating row strokes group.
endRowStrokeGapColor	Swatch	read/write	The gap color, specified as a swatch (color, gradient, tint, or mixed ink), of row borders in the second alternating rows group. Note: Valid when end row stroke count is 1 or greater.
endRowStrokeGapOverprint	Boolean	read/write	If true, the gap of the row borders in the second alternating rows group will overprint. Note: Valid when end row stroke count is 1 or greater.
endRowStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of rows in the second alternating strokes group. (Range: 0 to 100) Note: Valid when end row stroke count is 1 or greater and end row stroke type is not solid.
endRowStrokeOverprint	Boolean	read/write	If true, the rows in the second alternating rows group will overprint. Note: Valid when end row stroke count is 1 or greater.
endRowStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the row borders in the second alternating

Property	Type	Access	Description
			strokes group. (Range: 0 to 100) Note: Valid when end row stroke count is 1 or greater.
endRowStrokeType	StrokeStyle String	read/write	The stroke type of rows in the second alternating strokes group. Can also accept: String.
endRowStrokeWeight	Number String	read/write	The stroke weight of row borders in the second alternating row strokes group. Note: Valid when end row stroke count is 1 or greater.
endnoteTextFrames	EndnoteTextFrames <i>EndnoteTextFrame</i>	readonly	A collection of endnote text frames.
endnotes	Endnotes <i>Endnote</i>	readonly	A collection of endnotes.
epstexts	EPSTexts <i>EPSText</i>	readonly	EPSTexts
eventListeners	EventListeners <i>EventListener</i>	readonly	A collection of event listeners.
events	Events <i>Event</i>	readonly	A collection of events.
footerRowCount	Number (range 0 - 25)	read/write	The number of footer rows.
footnotes	Footnotes <i>Footnote</i>	readonly	A collection of footnotes.
formFields	FormFields <i>FormField</i>	readonly	A collection of form fields.
graphicBottomInset	Number String	read/write	The bottom inset of the graphic cell.
graphicLeftInset	Number String	read/write	The left inset of the graphic cell.
graphicLines	GraphicLines <i>GraphicLine</i>	readonly	A collection of graphic lines.
graphicRightInset	Number String	read/write	The right inset of the graphic cell.
graphicTopInset	Number String	read/write	The top inset of the graphic cell.
groups	Groups <i>Group</i>	readonly	A collection of groups.
headerRowCount	Number (range 0 - 25)	read/write	The number of header rows.

Property	Type	Access	Description
height	Number String	read/write	The height of the Table. For a table or column, specifies the sum of the row heights.
hiddenTexts	HiddenTexts <i>HiddenText</i>	readonly	A collection of hidden text objects.
id	Number	readonly	The unique ID of the Table.
index	Number	readonly	The index of the Table within its containing object.
isValid	Boolean	readonly	Returns true if the object specifier resolves to valid objects.
label	String	read/write	A property that can be set to any string.
leftBorderStrokeColor	Swatch	read/write	The color, specified as a swatch (color, gradient, tint, or mixed ink), of the left border stroke.
leftBorderStrokeGapColor	Swatch	read/write	The gap color, specified as a swatch (color, gradient, tint, or mixed ink), of the left border stroke. Note: Valid only when left border stroke type is not solid.
leftBorderStrokeGapOverprint	Boolean	read/write	If true, the gap of the left border stroke will overprint. Note: Valid only when left border stroke type is not solid.
leftBorderStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of the left border stroke. (Range: 0 to 100) Note: Valid only when left border stroke type is not solid.

Property	Type	Access	Description
leftBorderStrokeOverprint	Boolean	read/write	If true, the left border stroke will overprint.
leftBorderStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the left border stroke. (Range: 0 to 100)
leftBorderStrokeType	StrokeStyle String	read/write	The stroke type of the left border. Can also accept: String.
leftBorderStrokeWeight	Number String	read/write	The stroke weight of the left border stroke.
listBoxes	ListBoxes	readonly	A collection of listboxes.
multiStateObjects	MultiStateObjects <i>MultiStateObject</i>	readonly	A collection of multi-state objects.
name	String	read/write	The name of the Table; this is an alias to the Table's label property.
notes	Notes <i>Note</i>	readonly	A collection of notes.
ovals	Ovals <i>Oval</i>	readonly	A collection of ellipses.
pageItems	PageItems <i>PageItem</i>	readonly	The page items collection, which can be used to process all page items in a container (such as a document, page, or group), regardless of type.
parent	Character EndnoteTextFrame InsertionPoint Line Paragraph Story Text TextColumn TextFrame TextStyleRange Word XmlStory Cell XMLElement	readonly	The parent of the Table (a XElement, XmlStory, TextFrame, EndnoteTextFrame, Text, InsertionPoint, TextStyleRange, Paragraph, TextColumn, Line, Word, Character, Story or Cell).
polygons	Polygons <i>Polygon</i>	readonly	A collection of polygons.

Property	Type	Access	Description
properties	Object	read/write	A property that allows setting of several properties at the same time.
radioButtons	RadioButtons <i>RadioButton</i>	readonly	A collection of radio buttons.
rectangles	Rectangles <i>Rectangle</i>	readonly	A collection of rectangles.
rightBorderStrokeColor	Swatch	read/write	The color, specified as a swatch (color, gradient, tint, or mixed ink), of the right border stroke.
rightBorderStrokeGapColor	Swatch	read/write	The gap color, specified as a swatch (color, gradient, tint, or mixed ink), of the right border stroke. Note: Valid only when right border stroke type is not solid.
rightBorderStrokeGapOverprint	Boolean	read/write	If true, the gap color of the right border stroke will overprint. Note: Valid only when right border stroke type is not solid.
rightBorderStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of the right border stroke. (Range: 0 to 100) Note: Valid only when right border stroke type is not solid.
rightBorderStrokeOverprint	Boolean	read/write	If true, the right border stroke will overprint.
rightBorderStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the right border stroke. (Range: 0 to 100)
rightBorderStrokeType	StrokeStyle String	read/write	The stroke type of the right border. Can also accept: String.

Property	Type	Access	Description
rightBorderStrokeWeight	Number String	read/write	The stroke weight of the right border stroke.
rows	Rows <i>Row</i>	readonly	A collection of table rows.
signatureFields	SignatureFields <i>SignatureField</i>	readonly	A collection of signature fields.
skipFirstAlternatingFillColumns	Number	read/write	The number of columns on the left side of the table to skip before applying the column fill color. Note: Valid when alternating fills are defined for table columns.
skipFirstAlternatingFillRows	Number	read/write	The number of body rows at the beginning of the table to skip before applying the row fill color. Note: Valid when alternating fills are defined for table rows.
skipFirstAlternatingStrokeColumns	Number	read/write	The number of columns on the left of the table in which to skip border stroke formatting. Note: Valid when start column stroke count is 1 or greater and/or end column stroke count is 1 or greater.
skipFirstAlternatingStrokeRows	Number	read/write	The number of body rows at the beginning of the table in which to skip border stroke formatting. Note: Valid when start row stroke count is 1 or greater and/or end row stroke count is 1 or greater.

Property	Type	Access	Description
skipFirstHeader	Boolean	read/write	If true, skips the first occurrence of header rows.
skipLastAlternatingFillColumns	Number	read/write	The number columns on the right side of the table in which to not apply the column fill color. Note: Valid when alternating fills are defined for table columns.
skipLastAlternatingFillRows	Number	read/write	The number of body rows at the end of the table in which to not apply the row fill color. Note: Valid when alternating fills are defined for table rows.
skipLastAlternatingStrokeColumns	Number	read/write	The number of columns on the right side of the table in which to skip border stroke formatting. Note: Valid when start column stroke count is 1 or greater and/or end column stroke count is 1 or greater.
skipLastAlternatingStrokeRows	Number	read/write	The number of body rows at the end of the table in which to skip border stroke formatting. Note: Valid when start row stroke count is 1 or greater and/or end row stroke count is 1 or greater.
skipLastFooter	Boolean	read/write	If true, skips the last occurrence of footer rows.
spaceAfter	Number String	read/write	The space below the table.

Property	Type	Access	Description
spaceBefore	Number String	read/write	The space above the table.
splineItems	SplineItems <i>SplineItem</i>	readonly	The spline items collection.
startColumnFillColor	Swatch	read/write	The fill color, specified as a swatch (color, gradient, tint, or mixed ink), of columns in the first alternating fills group. Note: Valid when alternating fills are defined for table columns.
startColumnFillCount	Number	read/write	The number of columns in the first alternating fills group. Note: Valid when alternating fills are defined for table columns.
startColumnFillOverprint	Boolean	read/write	If true, the columns in the first alternating fills group will overprint. Note: Valid when alternating fills are defined for table columns.
startColumnFillTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the columns in the first alternating fills group. (Range: 0 to 100) Note: Valid when alternating fills are defined for table columns.
startColumnStrokeColor	Swatch	read/write	The stroke color, specified as a swatch (color, gradient, tint, or mixed ink), of column borders in the first alternating column strokes group.
startColumnStrokeCount	Number	read/write	The number of columns in the first alternating column strokes group.

Property	Type	Access	Description
startColumnStrokeGapColor	Swatch	read/write	The stroke gap color, specified as a swatch (color, gradient, tint, or mixed ink), of column borders in the first alternating column strokes group. Note: Valid when start column stroke count is 1 or greater.
startColumnStrokeGapOverprint	Boolean	read/write	If true, the gap of the column borders in the first alternating column strokes group will overprint. Note: Valid when start column stroke count is 1 or greater.
startColumnStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of column borders in the first alternating column strokes group. (Range: 0 to 100) Note: Valid when start column stroke count is 1 or greater.
startColumnStrokeOverprint	Boolean	read/write	If true, the column borders in the first alternating column strokes group will overprint. Note: Valid when start column stroke count is 1 or greater.
startColumnStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of column borders in the first alternating column strokes group. (Range: 0 to 100) Note: Valid when start column stroke count is 1 or greater.
startColumnStrokeType	StrokeStyle String	read/write	The stroke type of columns in the first

Property	Type	Access	Description
			alternating strokes group. Can also accept: String.
startColumnStrokeWeight	Number String	read/write	The stroke weight of column borders in the first alternating column strokes group. Note: Valid when start column stroke count is 1 or greater.
startRowFillColor	Swatch	read/write	The fill color, specified as a swatch (color, gradient, tint, or mixed ink), of rows in the first alternating fills group. Note: Valid when alternating fills are defined for table rows.
startRowFillCount	Number	read/write	The number of rows in the first alternating fills group. Note: Valid when alternating fills are defined for table rows.
startRowFillOverprint	Boolean	read/write	If true, the rows in the first alternating fills group will overprint. Note: Valid when alternating fills are defined for table rows.
startRowFillTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the rows in the first alternating fills group. (Range: 0 to 100) Note: Valid when alternating fills are defined for table rows.
startRowStrokeColor	Swatch	read/write	The color, specified as a swatch (color, gradient, tint, or mixed ink), of row borders in the first alternating row strokes group.

Property	Type	Access	Description
			Note: Valid when start row stroke count is 1 or greater.
startRowStrokeCount	Number	read/write	The number of rows in the first alternating row strokes group.
startRowStrokeGapColor	Swatch	read/write	The stroke gap color of row borders in the first alternating row strokes group, specified as a swatch (color, gradient, tint, or mixed ink). Note: Valid when start row stroke count is 1 or greater.
startRowStrokeGapOverprint	Boolean	read/write	If true, the gap color of the row border stroke in the first alternating row strokes group will overprint. Note: Valid when start row stroke count is 1 or greater.
startRowStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of row borders in the first alternating rows group. (Range: 0 to 100) Note: Valid when start row stroke count is 1 or greater.
startRowStrokeOverprint	Boolean	read/write	If true, the row borders in the first alternating row strokes group will overprint. Note: Valid when start row stroke count is 1 or greater.
startRowStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the borders in the first alternating row strokes group. (Range: 0 to 100)

Property	Type	Access	Description
			Note: Valid when start row stroke count is 1 or greater.
startRowStrokeType	StrokeStyle String	read/write	The stroke type of rows in the first alternating strokes group. Can also accept: String.
startRowStrokeWeight	Number String	read/write	The stroke weight of row borders in the first alternating row strokes group. Note: Valid when start row stroke count is 1 or greater.
storyOffset	InsertionPoint	readonly	The insertion point before the table in the story containing the table.
strokeOrder	StrokeOrderTypes StrokeOrderTypes.BEST_JOINS StrokeOrderTypes.COLUMN_ON_TOP StrokeOrderTypes.INDESIGN_2_COMPATIBILITY StrokeOrderTypes.ROW_ON_TOP	read/write	The order in which to display row and column strokes at corners.
tableDirection	TableDirectionOptions TableDirectionOptions.LEFT_TO_RIGHT_DIRECTION TableDirectionOptions.RIGHT_TO_LEFT_DIRECTION	read/write	The direction of the the table
textBottomInset	Number String	read/write	The bottom inset of the text cell.
textBoxes	TextBoxes	readonly	A collection of text boxes.
textFrames	TextFrames <i>TextFrame</i>	readonly	A collection of text frames.
textLeftInset	Number String	read/write	The left inset of the text cell.
textRightInset	Number String	read/write	The right inset of the text cell.
textTopInset	Number String	read/write	The top inset of the text cell.
textVariableInstances	TextVariableInstances <i>TextVariableInstance</i>	readonly	A collection of text variable instances.
topBorderStrokeColor	Swatch	read/write	The color, specified as a swatch (color, gradient, tint, or mixed ink), of the table's top border stroke.

Property	Type	Access	Description
topBorderStrokeGapColor	Swatch	read/write	The gap color, specified as a swatch (color, gradient, tint, or mixed ink), of the table's top border stroke. Note: Valid only when top border stroke type is not solid.
topBorderStrokeGapOverprint	Boolean	read/write	If true, the gap of the top border stroke will overprint. Note: Valid only when top border stroke type is not solid.
topBorderStrokeGapTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the gap color of the table's top border stroke. (Range: 0 to 100) Note: Valid only when top border stroke type is not solid.
topBorderStrokeOverprint	Boolean	read/write	If true, the top border strokes will overprint.
topBorderStrokeTint	Number (range 0 - 100)	read/write	The tint (as a percentage) of the table's top border stroke. (Range: 0 to 100)
topBorderStrokeType	StrokeStyle String	read/write	The stroke type of the top border. Can also accept: String.
topBorderStrokeWeight	Number String	read/write	The stroke weight of the table's top border stroke.
width	Number String	read/write	The width of the Table. For a table or row, specifies the sum of the column widths.

Method Listing

EventListener **addEventListener** (eventType:String, handler:Varies File JavaScriptFunction, [captures:Boolean=Boolean])

Adds an event listener.

Parameter	Type	Description
eventType	String	The event type.
handler	File JavaScriptFunction	The event handler. Can accept: File or JavaScript Function.
captures	Boolean	This parameter is obsolete. (Optional) (default: false)

undefined **autoTag** ()

Tag the object or the parent story using default tags defined in XML preference.

Text **changeGlyph** (reverseOrder:*Boolean*)

Finds glyphs that match the find what value and replaces the glyphs with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeText** (reverseOrder:*Boolean*)

Finds text that matches the find what value and replaces the text with the change to value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **changeTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value and replaces the text with the change character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

undefined **clearTableStyleOverrides** ()

Clear Table Style Overrides

undefined **convertBulletsAndNumberingToText** ()

Convert bullets and numbering to text.

Text **convertToText** (columnSeparator:*String*, rowSeparator:*String*)

Converts the table to text.

Parameter	Type	Description
columnSeparator	String	The character to insert between the each column's content in the converted text. Note: Can be defined as any single character, such as a letter, number, or punctuation mark, or by typing a space or tab. Use the actual character rather than its name, such as ',' rather than 'Comma'. Precede double or single quotes or a backslash with an extra backslash as an escape character. For paragraphs, use ^p. (Optional)

Parameter	Type	Description
rowSeparator	String	The character to use to separate each row's content in the converted text. Note: Can be defined as any single character, such as a letter, number, or punctuation mark, or by typing a space or tab. Use the actual character rather than its name, such as , rather than Comma. Precede double or single quotes or a backslash with an extra backslash as an escape character. For paragraphs, use ^p. (Optional)

PageItem **createOutlines** ([deleteOriginal:*Boolean*=Boolean])

Converts text to outlines. Each line of text becomes a polygon object. When the converted text is a single letter that has no internal spaces or detached parts, the polygon contains only a single path. Note: To determine whether a font allows the creation of outlines, see allow outlines.

Parameter	Type	Description
deleteOriginal	Boolean	If true, deletes the original text. If false, creates the outlines as separate object(s) on top of the text. (Optional) (default: true)

String **extractLabel** (key:*String*)

Gets the label value associated with the specified key.

Parameter	Type	Description
key	String	The key.

Text **findGlyph** (reverseOrder:*Boolean*)

Finds glyphs that match the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findGrep** (reverseOrder:*Boolean*)

Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findText** (reverseOrder:*Boolean*)

Finds text that matches the find what value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Text **findTransliterate** (reverseOrder:*Boolean*)

Finds text that matches the find character type value.

Parameter	Type	Description
reverseOrder	Boolean	If true, returns the results in reverse order. (Optional)

Table **getElements** ()

Resolves the object specifier, creating an array of object references.

undefined **insertLabel** (key:*String*, value:*String*)

Sets the label to the value associated with the specified key.

Parameter	Type	Description
key	<i>String</i>	The key.
value	<i>String</i>	The value.

undefined **markup** (using:*XMLElement*)

Associates the page item with the specified XML element while preserving existing content.

Parameter	Type	Description
using	<i>XMLElement</i>	The XML element.

undefined **recompose** ()

Recomposes the text in the Table.

undefined **remove** ()

Deletes the Table.

Boolean **removeEventListener** (eventType:*String*, handler:*Varies File JavaScriptFunction*, [captures:*Boolean*=*Boolean*])

Removes the event listener.

Parameter	Type	Description
eventType	<i>String</i>	The registered event type.
handler	<i>File JavaScriptFunction</i>	The registered event handler. Can accept: File or JavaScript Function.
captures	<i>Boolean</i>	This parameter is obsolete. (Optional) (default: false)

undefined **select** ([existingSelection:*SelectionOptions*=*SelectionOptions*])

Selects the object.

Parameter	Type	Description
existingSelection	<i>SelectionOptions</i> <i>SelectionOptions.ADD_TO</i> <i>SelectionOptions.REMOVE_FROM</i> <i>SelectionOptions.REPLACE_WITH</i> <i>SelectionOptions.SET_KEY</i>	The selection status of the Table in relation to previously selected objects. (Optional) (default: <i>SelectionOptions.REPLACE_WITH</i>)

String **toSource** ()

Generates a string which, if executed, will return the Table.

String **toSpecifier** ()

Retrieves the object specifier.

Cell **unmerge** ()

Unmerges all merged cells in the Table.

Object of

[Cell.parent](#)
[Column.parent](#)
[Endnote.parent](#)
[Event.parent](#)
[EventListener.parent](#)
[MutationEvent.parent](#)
[Row.parent](#)
[XMLElement.xmlContent](#)

Return

[XMLElement.convertElementToTable\(\)](#)
[Text.convertToTable\(\)](#)
[Character.convertToTable\(\)](#)
[Word.convertToTable\(\)](#)
[Line.convertToTable\(\)](#)
[TextColumn.convertToTable\(\)](#)
[Paragraph.convertToTable\(\)](#)
[TextStyleRange.convertToTable\(\)](#)
[InsertionPoint.convertToTable\(\)](#)
[Tables.add\(\)](#)
[Table.getElements\(\)](#)
[Tables.anyItem\(\)](#)
[Tables.everyItem\(\)](#)
[Tables.nextItem\(\)](#)
[Tables.previousItem\(\)](#)
[Tables.itemByID\(\)](#)
[Tables.item\(\)](#)
[Tables.\[\]\(\)](#)
[Tables.itemByName\(\)](#)
[Tables.itemByRange\(\)](#)
[Tables.firstItem\(\)](#)
[Tables.lastItem\(\)](#)
[Tables.middleItem\(\)](#)
