

AD 2 AERODROMES**HAIFA AIRPORT / Uri MICHAELI AIRPORT**

Note: The following sections in this chapter are intentionally left blank: AD-2.7, AD-2.25

LLHA AD 2.1 Aerodrome Location Indicator And Name

LLHA - HAIFA AIRPORT / Uri MICHAELI AIRPORT

LLHA AD 2.2 Aerodrome Geographical And Administrative Data

1	ARP coordinates and site at AD	324835N 0350238E 163°/678 M from THR 15
2	Direction and distance from (city)	090°, 12 km from Haifa city center
3	Elevation/Reference temperature	28FT./31.5°C (August)
4	Geoid undulation at AD ELEV PSN	20.5 M
5	MAG VAR/Annual Change	5° E (2019)/0.08° increasing
6	AD Administration, address, telephone, telefax, e-mail address, AFS	Post: Israel Airports Authority (IAA) Haifa Airport 99 Julius Simon Rd. Haifa Phone: 972-4-8476100/1 Security Unit - 972-4-8476100, 972-50-9753105/ 6 Email: AD Administration/Operation and Security Center: mail_haifaairport@iaa.gov.il Email: ATC Tower: migdalha@iaa.gov.il AFS: LLHAZPZX
7	In the event of communication failure, the pilot should call Air traffic control tower	Phone: Control tower: 972-4-8476120 in case of comm. failure: 972-4-8729361
8	Types of traffic permitted (IFR/VFR)	CVFR only
9	Remarks	

LLHA AD 2.3 Operational Hours

1	AD Administration	Operation and Security Center operates during ATS operational hours, except on the eves of Rosh Hashana, Yom Kippur and Passover, when the service is not provided.
2	Customs and immigration	Prior coordination with Operation and Security Center required
3	Health and sanitation	NIL
4	AIS Briefing Office	By Ben-Gurion AIS office (See LLBG AD 2.2)
5	ATS Reporting Office (ARO)	NIL
6	MET Briefing Office	Israel Meteorological Service meteorological watch office, Bet Dagan (LLBD).

7	ATS	SUN, THU: 0800-2200 LT MON, TUE, WED: 0800-2000 LT. Additionally, between 2000-2200 LT, only commercial air transport operations (passenger flights), international or domestic operated by aircraft with capacity of 30 seats or more, will be permitted. FRI & HOL eve: 0700-1900 LT SAT & HOL: 0800-2000 LT. Additionally, between 2000-2200 LT, only commercial air transport operations (passenger flights), international or domestic operated by aircraft with capacity of 30 seats or more, will be permitted. Jewish New Year's Eve and Passover Eve (the first) - (See GEN 2.1) - Airport closed for ARR/DEP at 18:00 L.M.T. Yom Kippur - Day of Atonement (See Gen 2.1) - Airport closed for ARR/DEP at 14:00 L.M.T until holiday's following day.
8	Fueling	Fueling services are provided during ATS operational hours. SAT & HOL: outside the operational hours, prior condition required (24h in advance) through 'PAZ Aviation Services', Tel. +972-53-7211039.
9	Handling	To receive Handling services, please contact QAS:Phone: +972-3-9751333.
10	Security	As AD administration
11	De-icing	NIL
12	Remarks	Fixed-wing aircraft operations are prohibited outside published airport operating hours. Authorization for special operations, outside airport operating hours shall be subject to prior coordination with the Operations and Security Center, not less than 24 hours in advance. Helicopter medical evacuation operations or police helicopter operations are exempted from these restrictions and may operate outside airport operating hours, subject to prior authorization by airport management.at apron G, stand G3 coordination with 'Paz Aviation Services'.

LLHA AD 2.4 Handling Services And Facilities

1	Cargo-handling facilities	NIL
2	Fuel/oil types	Jet A-1 by prior coordination with 'PAZ Aviation Services' Tel. 053-7211039
3	Fueling facilities/capacity	Self-service 100LL & JET near stand J10, for local operators. Others: contact 'PAZ Aviation Services', Tel +972-53-7211039, prior coordination required (24h in advance). Oil – NIL Boarding passengers at the refuelling stand is forbidden.
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	Contact AEROTECH GNS: +972-3-5477891
7	Remarks	NIL

LLHA AD 2.5 Passenger Facilities

1	Hotels	In the city of Haifa
2	Restaurants	Inside the terminal and in the city
3	Transportation	Taxis and bus station outside the terminal building

4	Medical facilities	First-aid at AD Hospitals in the city of Haifa
5	Bank and Post Office	Nil
6	Tourist Office	In the city of Haifa
7	Remarks	Nil

LLHA AD 2.6 Rescue And Fire Fighting Services

1	AD category for fire fighting	CAT 5
2	Rescue equipment	Fire fighting vehicles & Ambulance
3	Capability for removal of disabled aircraft	For further information contact Haifa airport management: +972-4-8476100/1.
4	Remarks	It is the duty of the owner or operator of a disabled aircraft to have it removed from the runway as soon as possible. If the owner or operator does not remove a disabled aircraft from the runway as quickly as possible, the aircraft will be removed by the aerodrome authority through an external crane company at the owner's or operator's expense and responsibility.

LLHA AD 2.7 Seasonal Availability - Clearing

NIL

LLHA AD 2.8 Aprons, Taxiways And Check Locations/Positions Data

1	Designation, surface and strength of aprons (PCR)	A: Surface: ASPH, Strength: 250 / F / C / X / T Z: Surface: ASPH, Strength: 80 / F / C / X / T N: Surface: ASPH, Strength: 115 / F / C / X / T J: Surface: ASPH, Strength: 3 150 kg / 1.25 Mpa L: Surface: ASPH, Strength: 1 200 kg / 0.5 Mpa G: Surface: ASPH, Strength: 5 300 kg / 1.25 Mpa U: Surface: ASPH, Strength: 5 700 kg / 1.25 Mpa
2	Designation, width, surface and strength of taxiways	Surface: ASPH • TWY A, G: 30 M • TWY N: 31.14 M • TWY J: 13.56 M • TWY L: 11.63 M
3	Location and elevation to the nearest metre or foot of altimeter checkpoints	Location: At Apron Elevation: 28 FT.
4	Location of VOR checkpoints	Nil
5	Position of INS checkpoints in degrees, minutes, seconds and hundredths of seconds	Nil

6	Remarks	Aprons details and instructions, see aircraft parking chart: - Parking for international flights shall be approved in advance by the Operation and Security Center. Apron A: In front of the terminal for commercial aircraft's. - Stands A1 and A3 can accommodate to W.S of 27.05 meters only. - Stands A2 and A4 can accommodate up to W.S of 27.43 meters only. Aprons A, J, L, Z: For general aviation fixed-wing aircraft's. Apron G: For authorized helicopters only. Apron N: For domestic aircraft (as detailed in Domestic AIP). Apron Z: For authorized aircraft only. Taxi in: via taxiway Y-3, or follow tower instructions. Give way to traffic taxiing out of Apron Z. Taxi out: via Z-2, or follow tower instructions. - A/C parking stand shall be selected according to A/C W.S, as detailed in aircraft parking charts. Parking aircraft with small W.S in stands designed for larger W.S requires prior approval from the Operation and Security Center.
---	---------	--

LLHA AD 2.9 Surface Movement Guidance And Control System And Markings

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Taxiing information signs at all intersections with TWY and RWY and at all holding positions. Leading lines at apron. Nose-out guidance at aircraft stands - only in apron A stands A1-A4 and apron N.
2	RWY and TWY markings and LGT	RWY: Designation, THR center line, edge runway end as appropriate, marked and lighted, aiming point marked. TWY: Center line, marked, unlighted.
3	Stop bars	Nil
4	Remarks	Nil

LLHA AD 2.10 Aerodrome Obstacles

In Area 2a, Area 2b and Area 2c	
Obstacle data for Area 2a, 2b and 2c is available by contacting the Civil Aviation Authority of Israel: Post: Ministry of Transportation Civil Aviation Authority Infrastructure Div. Mrs. Nitzan Vainstain P.O.B 1101 Golan House, Golan st., Airport City 7019900, Israel. Phone: +972-3-9774568 Email: aip@mot.gov.il Obstacle Data effective: 04 FEB 2023	

In Area 3	
Obstacle data for Area 3 is maintained by the Israeli Airports Authority (IAA), which is the aerodrome operator of LLHA airport. However, this information is not available for publication or purchase.	

In Area 4	
Obstacle data for Area 4 is not applicable, since there are no ILS CAT II/III operations in LLHA airport.	

LLHA AD 2.11 Meteorological Information Provided

1	Associated MET office	Israel Meteorological Service, Bet Dagan (LLBD)
---	-----------------------	---

2	Hours of service MET office outside hours	Observations commence one hour before AD resuming operation and continue until closure. Briefing available from LLBD 24H each day.
3	Office responsible for TAF preparation Periods of validity	Israel Meteorological Service 24 HR (Long TAF).
4	Type of landing forecast Interval of issuance	Nil
5	Briefing/consultation provided	Telephone briefing with the Meteorological Watch Office at Israel Meteorological Service, Bet Dagan, can be established in the aerodrome meteorological station.
6	Flight documentation Language(s) used	By request from the local MET station, a folder may be provided containing: Charts, OPMET information, SIGMET, Aerodrome Warnings and low level forecasts for TEL-AVIV FIR available in ICAO abbreviated text or in English
7	Charts and other information available for briefing or consulting	Low level and upper wind and temperature chart for standard isobaric surface. Significant weather chart (low level, medium and high level)
8	Supplementary equipment available for providing information	Meteorological information terminal available at meteorological station in the AD containing: weather radar, weather satellite image display and animation, Upper Air temperature & wind profiles derived from Israeli radiosonds and AMDAR reports, SIGWX and T+W charts and updated OPMET information
9	ATS units provided with information	Haifa Tower.
10	Additional information (limitation of service, etc.)	Local MET station Tel: 972-4-8476132

LLHA AD 2.12 Runway Physical Characteristics

Designations RWY NR	TRUE BRG	Dimensions of RWY (m)	Strength (PCR) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY	Slope of RWY-SWY
1	2	3	4	5	6	7
15	159.80°	1 318 X 30	320/F/C/X/T Asphalt	THR 324855.55N 0350229.26E; RWY END 324817.81N 0350245.71E; GUND 20.5 M	THR 26 FT	-0.86%/ +Negligible (502 M) (785 M)
33	339.80°	1 318 X 30	320/F/C/X/T Asphalt	THR 324821.41N 0350244.14E; RWY END 324857.04N 0350228.58E; GUND 20.5 M	THR 16 FT	Negligible/ +0.86% (785 M) (502 M)

SWY dimensions (m)	CWY dimensions (m)	Strip dimensions (m)	Dimensions of RESA (m)	Location And Description Of Arresting System	OFZ	Remarks
8	9	10	11	12	13	14
Nil	90 X 80	1 318 X 80	RESA RWY 15–30 X 42	Nil	Nil	RESA + CWY ARE PART OF THE RWY*
Nil	90 X 80	1 318 X 80	RESA RWY 33–16 X 60	Nil	Nil	RESA + CWY ARE PART OF THE RWY
* Use of CWY for RWY 15 - coordination with ATC is required before line-up						

LLHA AD 2.13 Declared Distances

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
15	1 228	1 288	1 228	1 177	Nil
15	1 228	1 318	1 228	1 177	By prior coordination*
33	1 228	1 318	1 228	1 119	Nil
* Use of CWY for RWY 15 - coordination with ATC is required before line-up					

1. DECLARED REMAINING DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
15 – N	1 086				
15 – G	1 002				
15 – A/Z	750				
15 – Y1	560				
15 – Y3	680				
15 – U	462				
33 – N	NOT AUTHORIZED				
33 – G	175				
33 – A/Z	425				
33 – Y1	615				
33 – Y3	495				
33 - U	716				

LLHA AD 2.14 Approach And Runway Lighting

RWY designator	APCH LGT type LEN INTST	THR LGT Colour WBAR	VASIS (MEHT) PAPI	TDZ,LGT LEN	RWY Center Line LGT Length, spacing, colour, INTST	RWY edge LGT LEN, spacing Colour INTST	RWY End LGT colour WBAR	SWY LGT LEN (M) colour	Remarks
1	2	3	4	5	6	7	8	9	10
15	Nil	Green	PAPI Left/3° MEHT - 12.27m	REIL	Nil	1 206 M 60 M White LIH	Red	Nil	Nil
33	Nil	Green	PAPI Left/4° MEHT - 14.52m	REIL	Nil	1 206 M 60 M White LIH	Red	Nil	Nil

*RWY 15 Aiming point is located 250 M from THR, PAPI is located 300 M from THR.

LLHA AD 2.15 Other Lighting, Secondary Power Supply

1	ABN/IBN location, characteristics and hours of operation	ABN (Green/White) located on TWR, operating in IMC and at night.
2	LDI location and LGT	100 M SW of ARP lit.
	Anemometer location and LGT	TBD
3	TWY edge and center line lighting	Edge only
4	Secondary power supply/switch-over time	Secondary power supply to all lighting at AD. Switch-over time: 20 SEC
5	Remarks	Nil

LLHA AD 2.16 Helicopter Landing Area

Helicopters shall use RWY 15/33 for landing & take-off, following TWR instructions.
TWR may instruct helicopters to use short/long circuit (Ref. AD 2.2-15).
Helicopters may touch down at the intersection of their parking stand, if preferred.

LLHA AD 2.17 ATS Airspace

1	Designation and lateral limits	324511N 350418E - 325025N 350740E - 325039N 350602E - 325515N 350550E - 325525N 350455E - 325640N 350454E - 325644N 350421E - 324933N 345631E - 324740N 345631E - 324459N 350151E
2	Vertical limits	SFC/MSL - 3 000 FT MSL (3 500 FT during weekends)
3	Airspace classification	D
4	ATS unit call sign Language(s)	Haifa Tower English (Hebrew at ATC discretion)
5	Transition altitude	NIL
6	Remarks	NIL

LLHA AD 2.18 ATS Communication Facilities

Service designation	Call sign	Frequency	Hours of operation	Remarks
1	2	3	4	5
TWR	HAIFA TOWER	133.000 MHz	During AD operation hours	Primary frequency
		127.800 MHz		Secondary frequency
		121.500 MHz		Emergency freq.
ATIS	Haifa Information	135.400 MHz	During AD operation hours	Broadcast includes Local routine/special weather report of circuit area

LLHA AD 2.19 Radio Navigation And Landing Aids

Type of aid, MAG VAR CAT of ILS/MLS (For VOR/ILS/ MLS, give declination)	ID	Frequency	Hours of operation	Location of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
Nil						-

LLHA AD 2.20 Local Traffic Regulations

1. Taxiing to and from stands

Parking arrangements to be coordinated in advance through the Operation and Security Center.

Departing flight shall contact the TWR before start-up, report received ATIS letter, their parking position and obtain ATC clearance before commencing taxi.

Start up and taxi clearances shall be requested from TWR.

Taxi, air-taxi, or push-back in or out of two adjacent parking position simultaneously, is prohibited.

Pilots may request Runway intersection departure before line-up. See table 2.13A for RWY intersection's TORA.

A/C shall be ready for immediate departure upon line-up, and must not delay its take-off roll, unless otherwise approved by TWR.

Taxiing and maneuvering shall be the sole responsibility of the pilot. Adherence to TWR instructions.

Further information about regulations can be obtained from the TWR.

N and Z Apron: pilot and passenger access, including arrival from the Terminal to the apron and return is permitted only by prior coordination via email with Operations and Security Center.

2. Parking area for small aircraft (General aviation)

Parking at apron A, J, L, N, Z see AD 2 LLHA APDC.

Marshalling services are not provided.

Taxiing and maneuvering shall be the sole responsibility of the pilot.

Request ATC instructions if required.

Parking on Apron A will be as following:

- a. It is the pilot's responsibility to coordinate in advance with the operations and security center, the arrival and parking of aircraft whose home base is not Haifa.
- b. Stands A1 and A3 are planned for aircraft with a wingspan up to 27.05 meters only. Stands A2 and A4 are planned for aircraft with a wingspan up to 27.43 meters only. Entry and exit from these stands will be carried out according to the markings, and accompanied by a ground guide.
- c. Refuelling, treatments and maintenance of any kind are strictly prohibited at stands A16, A17 and A18.
- d. It is the pilot's responsibility to park the aircraft only on a stand suitable for its size. Parking in a larger position requires prior approval from the Operations and Security Center.

Parking at apron J: On stands J1 and J2 it is forbidden to park an aircraft deviating from rear restraint line.

Parking at apron L: Stand L5 is available for aircraft with Max wingspan of 11.00 meters.

3. **Engines Run-ups:**

Run up approval must be obtained by email from the Operation and Security Center.

Contact ATC tower for start-up clearance only after receiving a permission from the Operation and Security Center.

Company/Pilot responsible for the run-up, must secure the surrounding area and post a safety observer.

4. **Parking area for helicopters**

Parking at apron G, Different apron may be assigned by Operation and Security Center. see AD 2 LLHA APDCG.

Pilots/operators shall coordinate helicopter parking with Operation and Security Center by e-mail only.

Apron G: for helicopters with maximum helicopter length of 17.12 meters.

It is strictly prohibited for helicopters to hover above parking areas for inspection purposes.

5. **Apron - taxiing during winter conditions**

Nil

6. **Taxiing - limitations**

Insufficient safety distances restrict large aircraft's use of taxiway when using their own power.

Pilots shall coordinate in advance the operations of large aircraft with the Operation and Security Center.

Further information/instructions will be given by TWR.

7. **School and training flights technical test flights - use of runways**

Nil.

8. **Helicopter traffic - limitation**

Non-scheduled helicopter public air traffic is permitted only after prior approval from the Haifa Aerodrome Administration. Any contact concerning the above shall be made via the handling company or directly to the Operation and Security Center.

Any request for approval of traffic shall contain the following information:

- a. Owner/operator
- b. Type of helicopter, registration/call sign

c. Date, arrival time/departure time, destination(s).

Furthermore, other details relevant to the evaluation of the request shall be given as required.

9. Removal of disabled aircraft from runways

Aircraft involved in an accident shall be removed from the accident site only after obtaining permission of the chief investigator of aircraft accidents/incidents, or from the head of the investigation committee.

It is the duty of the owner or operator of a disabled aircraft to have it removed from the runway as soon as possible. If the owner or operator does not remove a disabled aircraft from the runway as quickly as possible, the aircraft will be removed by the aerodrome authority through an external crane company at the owner's or operator's expense and responsibility.

LLHA AD 2.21 NOISE ABATEMENT MONITORING & PROCEDURES

Flights beyond the fuel tanks are prohibited to minimize noise disturbance for the residents of the southern neighbourhoods of Qiryat Haim (see Visual Approach Chart).

LLHA AD 2.22 FLIGHT PROCEDURES

General

Flights within Haifa CTR shall be in accordance with Controlled Visual Flight Rules (CVFR) only, and conducted in accordance with CVFR routes chart.

Traffic pattern (see AD 2.2-Visual Circuit Chart)

- Fixed-wing A/C, "Long" circuit pattern. Altitude – 1000 ft.
 - RWY 33 – Right circuit, Base leg south of LLP04.
 - RWY 15 – Left circuit, extend Departure leg, Crosswind south of LLP04.
- Helicopters, "Short" circuit pattern, Altitude – 500 ft, day only.
 - RWY 33 – Right circuit, short Base leg north of LLP04.
 - RWY 15 – Left circuit, short departure leg, crosswind north of LLP04.

International flights – Arrivals

Before submitting arrival FPL, pilots shall receive Haifa AD administration approval at least 24 hours in advance, and coordinate any further changes.

Pilots shall report ETA to ZAHAV to Tel-Aviv Control (ACC), which will forward the information to Haifa TWR.

Arriving flights shall be transferred to Haifa TWR before GALIM 3000/5000 ft.

On initial contact, pilot shall report to Haifa TWR received ATIS letter, present altitude, and distance or ETA to GALIM.

International flights – Departures

Pilots shall coordinate departure flights with AD administration at least 24 hours in advance, and before submitting a FPL.

It is the pilot responsibility to inform the tower 15 minutes before the planned take-off time.

Departure flights shall be transferred to Tel Aviv Control at GALIM, 3000/5000 ft.

Communication failure

In case of Communication failure the pilot should call the control tower 972-4-8729361 and act as follows:

- **Arriving A/C:**
Proceed to GALIM via FPL Airway, unless previously cleared to another airway.

After passing GALIM, proceed inbound Haifa airport while maintaining 3000 ft.

Switch on the A/C landing lights.

Determine the Runway in Use, observing traffic in the circuit and/or the wind direction indicator ("Wind Sac").

Fly over the control TWR. Join down-wind leg while descending to 1000 ft.

Land after receiving Green light from the TWR

- **Departing A/C:**
Return to LLHA via GALIM at 3000 ft.

After passing GALIM proceed, as described for arriving A/C.

LLHA AD 2.23 ADDITIONAL INFORMATION

Bird concentrations in the vicinity of the airport

LLHA AD 2.24 Charts Related To An Aerodrome

Chart Name	Page
Aerodrome Chart - ICAO	AD 2 LLHA ADC
Aircraft Parking Chart	AD 2 LLHA APDC-1
Aircraft Parking Chart Apron G	AD 2 LLHA APDCG-1
Aircraft Parking Chart Apron N	AD 2 LLHA APDCN-1
Aircraft Parking Chart Apron Z	AD 2 LLHA APDCZ
Aerodrome Obstacle Chart – ICAO Type A (RWY 15/33)	AD 2 LLHA AOC-15-33
Standard Arrival Chart – Instrument (STAR) GALIM 1A, GALIM 1B	AD 2 LLHA STAR-1
Visual Circuit Chart	AD 2 LLHA VCC-1

THIS PAGE INTENTIONALLY LEFT BLANK