Using AI to assist high fidelity multiphase flow modeling in making atomization and spray predictions.

1. Background/Introduction

1.1 Relevance to DOE Genesis Mission

We are responding to "The Genesis Mission: Transforming Science and Energy with AI." In particular we address project topic 21, "Artificial Intelligence in Fluid Flow for Energy Components and Technologies." The focus area is 21A, "Physics-Informed AI for complex fluid phenomena."

This proposal requests funding in order to develop improved numerical methods, via AI enhancement, in order to simulate atomization and spray processes as they pertain to combustion in aircraft engines[4] and rotating detonation engines[6, 3] used by rockets.

As a group, the PIs Sussman, Shoele, and Arienti have developed over time state of the art adaptive, parallel, exascale enabled, numerical algorithms for carrying out high-fidelity numerical simulations of atomization and spray and related problems[4, 5, 3, 6, 29, 17, 30, 27, 21].

This all being said, there are limitations in **exascale CFD**, where multiscale interfacial physics imposes severe computational constraints[14]. It is proposed herein to develop an efficient computational system in which existing high-fidelity simulation and experimental data are used, sparingly, in order to develop sub-scale models which can then be used to solve a more general set of atomization and spray problems (e.g. varying the geometry, fluid physical properties, and boundary conditions).

Consistent with Topic Area 21, "Physics-Informed AI for complex fluid phenomena," we shall (1) develop the capability to assimilate data from high fidelity simulations and/or experiments into our existing foundational methodology for multiphase flow[4, 5, 3, 6, 29, 17, 30, 27, 21], and (2) use AI in order to learn sub-scale models for predicting the difference between underresolved simulations and super-resolved high fidelity simulations (and/or experiments).

The goal is to develop an AI-generated sub-scale model in order to minimize the frequency of having to run high-fidelity simulations.

We remark that the benefits of this proposal can be broad. In energy applications, accelerated multiphase simulation enables **improved predictive capability** for fuel injection, combustion processes, systems with boiling, evaporation, and condensation, and advanced propulsion systems. The integration of simulation with data-driven methodologies supports the development of **adaptive digital environments** in which modeling, data, and computation are tightly coupled to *accelerate discovery and innovation*.

1.2 Proposed Research in the context of the current state-of-the-art

Multiphase flows with *sharp, dynamically evolving interfaces* play a central role in energy conversion and transport systems, including fuel injection, spray combustion, rotating detonation engines, and phase-change-driven thermal processes[3, 5, 4, 6, 14, 29]. These flows are governed by *tightly coupled nonlinear interactions* among turbulence, interfacial forces, thermodynamics, and material response across a wide range of spatial and temporal scales, and are critical for identifying distinct mass and momentum processes at evolving interfaces. Their accurate prediction remains **one of the most challenging problems in computational science**.

Over the past several decades, semi-implicit **sharp-interface methods** have emerged and matured as a rigorous framework for modeling such systems with provable performance. Foundational work by [26] established level set methods for capturing evolving interfaces in multiphase flow. Subsequent developments led to conservative formulations[25] that significantly improved *mass conservation and robustness* in the presence of topology change.

A major advance in this area is the **moment-of-fluid (MOF)[9, 1, 12]** and cell-integrated semi-Lagrangian **compressible MOF framework developed by Jemison, Sussman, and Arienti[11]**. The compressible multiphase formulation developed by Jemison et al introduced a unified method that conserves mass, momentum, and energy while capturing shocks and material discontinuities without Riemann solvers. The material interfaces in [11] are represented sharply while at the same time preserving volume to machine precision in zero mach number regions. Our approach enables simulations across compressible and incompressible fluids through asymptotic-preserving semi-implicit pressure updates. Further developments demonstrated accurate treatment of *multi-material junctions* and surface tension effects in complex geometries[6, 3, 17, 27, 13, 30, 29].

In parallel, high-fidelity studies of fuel injection and atomization using DNS and LES approaches have highlighted the *extreme computational demands* of resolving interface breakup, turbulence interaction, and compressibility effects in realistic engine conditions and, more importantly, for problems with sharp mass transfer at the interface. In the article by Li and Soteriou[14], the authors demonstrate that, for simulating the atomization of a liquid jet in a cross flow (JICF), adaptive mesh refinement provides only a marginal benefit for practical multiphase flow problems. The JICF problem exhibits a feedback mechanism between the chaotic gas flow and the breakup of the liquid jet. This motivates new approaches to improve the solution procedure employed in these methods while not abandoning their unique predictive capabilities.

One possible avenue of improvement that we had considered, as well as that considered by others[30, 16], was to replace costly geometric operations in multiphase flow algorithms with surrogate AI-generated models. The key principle is that surrogate models must not compromise on the fidelity of the numerical algorithm. In particular, for volume tracking, or moment of fluid methods, it is essential that the "linearity preserving" and "volume preserving" properties of a multiphase flow system not be violated[9, 1, 23, 22, 24]. Yet, what was discovered by us[30], and also mentioned in[16] is that these AI generated surrogate algorithms, at best, provide a marginal benefit. We also bring attention to the following articles which give evidence that surrogate AI models will never beat finely tuned optimized algorithms[18, 7, 2, 15].

Another possible avenue of improvement is to develop a meshless method such as PINN[19, 10] or SPH[28, 20]. These meshless methods, or any other pure meshless method, are not volume preserving. In otherwords, in the limit as the mach number approaches zero, the volume should be preserved. We note that the volume error, using PINN, reported by [19] was *worse* than even that of classical level set methods.

It is proposed herein to make two new developments: (I) we shall improve our existing compressible multiphase flow algorithm[11, 3, 6] by developing an accompanying volume and mass preserving compressible multiphase flow nudging capability for the assimilation of multiphase flow data from either high-resolution, high-fidelity simulations, and/or experiments[8]. (II) We shall use the nudging correction generated from (I) to train a neural network to derive sub-scale models appropriate for underresolved multiphase flows. It is expected that our sub-scale model will be general for a wide

range of multiphase flows.

2. Project Objectives

The project objectives address project topic 21, "Artificial Intelligence in Fluid Flow for Energy Components and Technologies." The focus area is 21A, "Physics-Informed AI for complex fluid phenomena."

The project objectives are to (I) improve our existing compressible multiphase flow algorithm[11, 3, 6] by developing an accompanying compressible multiphase flow nudging capability for the assimilation of multiphase flow data from either high resolution, high fidelity simulations, and/or experiments. The nudging algorithm we propose to develop will enable volume and mass preserving "interface nudging" suitable for the complex atomization and spray problems that we consider. We propose to implement the algorithm developed Dommermuth et al[8]. In (31) of [8], the nudging term is $-\frac{p_s}{\rho}\nabla H$ in which p_s is a nudging stress that acts normal to the interface. p_s is proportional to the difference between the simulation level set function and an assimilated level set function. (II) We shall use the nudging correction, generated from (I), in order to train a neural network in order to derive sub-scale models appropriate for underresolved multiphase flows. It is expected that our sub-scale model will be general for a wide range of multiphase flows.

Our targeted canonical problems are (a) the atomization of a fuel Jet in a Cross Flow problem (JICF) which address combustion in aircraft engines[4] and (b) the shock cylinder/drop problem which address rotating detonation engines used by rockets[6, 3].

3. Proposed Research and Methods; Physics-Constrained Data Driven Model

The proposed research builds directly on prior work by PIs **Sussman, Shoele and Arienti[11, 27, 17, 30, 29]**, particularly the *cell-integrated semi-Lagrangian framework* and *moment-of-fluid interface representation*, which enable accurate tracking of deforming interfaces and efficient handling of *compressibility and stiffness*. Materials are represented using Volume fractions (zero order moment) and centroids (first order moment). Interfaces are captured. The governing equations include conservation of mass, momentum, energy, and species, with extensions for viscoelasticity, elasto-plasticity, and phase change. Interface conditions enforce *stress balance, velocity discontinuities due to mass transfer, and thermodynamic equilibrium*. Surface tension effects are modeled through *curvature-dependent forces*, and phase change is driven by *temperature and concentration gradients and corresponding nonlinear surface mass and chemical transport equations*.

In the proposed physics-constrained, solver-embedded learning framework, (1) high fidelity computational data and/or experimental data are assimilated via nudging into a coarse-grid simulation of two-phase flows, and (2) unresolved turbulence and interfacial dynamics are modeled using neural networks trained on the nudging source terms. Unlike conventional Physics-Informed Neural Network approaches that attempt to directly approximate the solution field, the present method retains the full structure of a conservative MOF-based two-phase flow solver, ensuring sharp interface representation, strict mass conservation, and compatibility with established numerical methods. The neural network is instead tasked with learning closure interfacial and bulk force corrections which will be embedded directly into the governing equations at each time step. Crucially, additional interface-aware constraints ensure that corrections remain localized and consistent with geometric

quantities such as interface normals and curvature, addressing a major limitation of existing data-driven models in multiphase flows. When high-fidelity data are available, a compressible multiphase data assimilation nudging technique is used to align the coarse solution with reference dynamics, enabling accurate reconstruction of key flow features at a fraction of the computational cost. We note that when material interfaces are nudged, we ensure volume and mass preservation using the algorithms developed by Dommermuth et al[8] (see their equation (31)).

In this work, since independently evolved coarse-grid and high-fidelity two-phase simulations can rapidly diverge due to nonlinear amplification of interfacial errors, the raw mismatch between them does not provide a clean learning target for unresolved physics. Instead, the coarse solution is periodically assimilated toward the restricted high-fidelity state, $Q^{n+1}_{hf\to c}$, and the resulting aligned coarse state is used as the initial condition for one-step coarse-grid advancement. The discrepancy between this uncorrected coarse update and the corresponding high-fidelity evolution defines the target correction for the neural network. This strategy ensures that the learned model captures missing subgrid and interfacial physics, rather than compensating for accumulated trajectory drift.

The neural network is trained to infer unresolved interfacial and near-interface corrections from coarse-grid flow fields and reconstructed interface features, enabling the coarse solver to recover high-fidelity dynamics that are otherwise lost at reduced resolution.

Let Q^n_a denote the assimilated coarse state at time t_n, and let $Q^{n+1}_{c,unc} = G_{\mathrm{MOF}}(Q^n_a)$ be the corresponding uncorrected one-step coarse update. The target correction is defined as the one-step discrepancy between the restricted high-fidelity evolution and the uncorrected coarse prediction, $F^n_{\mathrm{corr}} = (Q^{n+1}_{hf\to c} - Q^{n+1}_{c,unc})/\Delta t$. A neural network $\mathcal{N}_\theta$ is then trained to approximate the mapping from coarse-grid flow and interface features $z^n = \Phi(Q^n_a, \Gamma^n_a)$ to this correction, where Γ^n_a is obtained from the MOF reconstruction of the assimilated moments. The training objective minimizes the discrepancy between predicted and target corrections, $\mathcal{L}(\theta) = \sum_n \|W \cdot (\mathcal{N}_\theta(z^n) - F^n_{\mathrm{corr}})\|^2 + \mathcal{R}(\theta)$, incorporating optional weighting W and regularization $\mathcal{R}(\theta)$ concentrated near the interface.

Because the dominant modeling errors in coarse-grid two-phase simulations occur in mixed cells and in a narrow band surrounding the reconstructed interface, both supervision and regularization of the neural network are concentrated in these regions during training. Specifically, (1) the supervised loss is weighted by an interface-aware indicator so that discrepancies in interfacial regions contribute more strongly than errors in the bulk phases, where the coarse solver is typically already accurate. This weighting can be implemented using either a binary interface mask or a smooth distance-based function that increases the contribution of cells closer to the interface. (2) Physically motivated regularization terms are introduced to constrain the structure of the learned correction: 2a: A localization penalty is applied to discourage the network from producing spurious corrections away from the interface. 2b: A smoothness regularization is imposed within the interface band to prevent nonphysical oscillations and enforce spatial correction along the interface. 2b: A magnitude constraint is included to bound the correction and avoid overfitting or instability.

For interfacial force corrections, the third regularization term (3) is an additional geometric regularization that enforces alignment with the reconstructed interface normal, ensuring consistency with the underlying physics of interfacial interactions.

Together, these interface-focused weighting and regularization strategies ensure that the neural network learns physically meaningful, localized corrections associated with unresolved interfacial and subgrid-scale processes, while avoiding contamination from bulk-region noise or unphysical

behavior.

4. Milestones in the Nine Months

1. (Sussman Months 1-3): Enhance the existing compressible MOF algorithm[11, 3, 6, 29] by adding the ability to assimilate, via nudging, compressible multiphase interface, velocity, and temperature data. Volume and mass conservation is ensured during the nudging procedure via the algorithm reported in earlier work by Dommermuthg et al[8].

2. (Arienti Months 1-3): Develop routines that import high-resolution data[3, 6] into actively running coarse grid simulations. Write restriction routines which carry out the operation: $Q^{n+1}_{hf\to c}$.

3. (Shoele Months 1-3): Develop the neural network algorithm which minimizes the discrepancy between predicted and target corrections, $\mathcal{L}(\theta) = \sum_n \|W \cdot (\mathcal{N}_\theta(z^n) - F^n_{\text{corr}})\|^2 + \mathcal{R}(\theta)$, incorporating optional weighting W and regularization $\mathcal{R}(\theta)$ concentrated near material interfaces.

4. (Arienti, Sussman, Shoele Months 4-6): Integrate the developments in items 1-3 above: nudging data assimilation, AMReX data base management, AI generated sub-scale models. Diagnostic testing on 2D atomization and spray from shock-cylinder interaction. Verification and validation.

5. (Arienti, Sussman, Shoele Months 7-9): Same as task 4, except fully 3D problems will be investigated)

5. Data Sources and Models

The current version of the computer code that is used to generate results shown in Figure 3 of [4], Figures 4 and 6 of [3] and Figures 5 and 11a of [6] is stored on Git Hub:
`https://github.com/msussman42/amrex_implicit_interfaces.git`
The data in Figure 3 of [4], and Figure 4 of [3] can be regenerated from scratch within 30 days. The remainder of the data is stored by Marco Arienti on national Lab computers.

6. Decision Gate Metrics

We shall train our neural network subscale models on the 2D/3D water and Galinstan shock-cylinder interaction problems (Figures 4,6,7 of [3]). The effective fine grid resolution for the "high fidelity" simulation is $3072 \times 2304 \times 768$ (3D). The effective fine grid resolution for the "low fidelity" simulation is $384 \times 288 \times 96$. After training, we shall rerun the water and galinstan cases, except using the trained models instead of assimilating the "high fidelity" data. Then we shall compare the respective interfaces between (a) coarse grid, assimilated results, (b) coarse grid, model results, and (c) high fidelity results. Finally, we shall create two new cases, varying the Weber number and Reynolds number. For each of the new cases we shall compare to the high fidelity model: (a) coarse grid, no model, (b) coarse grid with model. The interface errors are computed using the symmetric difference error[12].

References

[1] Ahn, H. T., and Shashkov, M. Adaptive moment-of-fluid method. *Journal of Computational Physics 228*, 8 (2009), 2792–2821.

[2] Ancellin, M., Després, B., and Jaouen, S. Extension of generic two-component vof interface advection schemes to an arbitrary number of components. *Journal of Computational Physics 473* (2023), 111721.

[3] Arienti, M., Ballard, M., Sussman, M., Mazumdar, Y. C., Wagner, J. L., Farias, P. A., and Guildenbecher, D. R. Comparison of simulation and experiments for multimode aerodynamic breakup of a liquid metal column in a shock-induced cross-flow. *Physics of Fluids 31*, 8 (2019).

[4] Arienti, M., Li, X., Soteriou, M., Eckett, C., Sussman, M., and Jensen, R. Coupled level-set/volume-of-fluid method for simulation of injector atomization. *Journal of propulsion and power 29*, 1 (2013), 147–157.

[5] Arienti, M., and Sussman, M. An embedded level set method for sharp-interface multiphase simulations of diesel injectors. *International Journal of Multiphase Flow 59* (2014), 1–14.

[6] Arienti, M., Wenzel, E. A., Guildenbecher, D. R., and Beresh, S. J. Simulation and analysis of droplet aerobreakup in a ballistic wave system. *AIAA journal 63*, 8 (2025), 3309–3320.

[7] Diot, S., and François, M. M. An interface reconstruction method based on an analytical formula for 3d arbitrary convex cells. *Journal of Computational Physics 305* (2016), 63–74.

[8] Dommermuth, D. G., Lewis, C. D., Tran, V. H., and Valenciano, M. A. Direct simulations of wind-driven breaking ocean waves with data assimilation. *arXiv preprint arXiv:1410.0418* (2014). 30th symposium on naval hydrodynamics, Hobart Australia, November 2014.

[9] Dyadechko, V., and Shashkov, M. Moment-of-fluid interface reconstruction. *Los Alamos report LA-UR-05-7571* (2005).

[10] Jalili, D., Jang, S., Jadidi, M., Giustini, G., Keshmiri, A., and Mahmoudi, Y. Physics-informed neural networks for heat transfer prediction in two-phase flows. *International Journal of Heat and Mass Transfer 221* (2024), 125089.

[11] Jemison, M., Sussman, M., and Arienti, M. Compressible, multiphase semi-implicit method with moment of fluid interface representation. *Journal of Computational Physics 279* (2014), 182–217.

[12] Jemison, M., Sussman, M., and Shashkov, M. Filament capturing with the multimaterial moment-of-fluid method. *Journal of Computational Physics 285* (2015), 149–172.

[13] Li, G., Lian, Y., Guo, Y., Jemison, M., Sussman, M., Helms, T., and Arienti, M. Incompressible multiphase flow and encapsulation simulations using the moment-of-fluid method. *International Journal for Numerical Methods in Fluids 79*, 9 (2015), 456–490.

[14] Li, X., and Soteriou, M. C. High fidelity simulation and analysis of liquid jet atomization in a gaseous crossflow at intermediate weber numbers. *Physics of Fluids 28*, 8 (2016).

[15] López, J., and Hernández, J. Analytical and geometrical tools for 3d volume of fluid methods in general grids. *Journal of Computational Physics 227*, 12 (2008), 5939–5948.

[16] Mak, A., and Raessi, M. A machine learning approach to volume tracking in multiphase flow simulations. *Fluids 10*, 2 (2025).

[17] Maurya, G., Liu, Y., Sussman, M., and Shoele, K. Drop transmission after the impact on woven fabrics. *International Journal of Multiphase Flow 179* (2024), 104909.

[18] Milcent, T., and Lemoine, A. Moment-of-fluid analytic reconstruction on 3d rectangular hexahedrons. *Journal of Computational Physics 409* (2020), 109346.

[19] Mullins, M., Kamil, H., Fahsi, A., and Soulaïmani, A. Physics-informed neural networks for solving moving interface flow problems using the level set approach. *Physics of Fluids 37*, 10 (2025).

[20] Nair, P., and Tomar, G. Volume conservation issues in incompressible smoothed particle hydrodynamics. *Journal of Computational Physics 297* (2015), 689–699.

[21] Pei, C., Vahab, M., Sussman, M., and Hussaini, M. Y. A hierarchical space-time spectral element and moment-of-fluid method for improved capturing of vortical structures in incompressible multi-phase/multi-material flows. *Journal of Scientific Computing 81*, 3 (2019), 1527–1566.

[22] Puckett, E. On the second-order accuracy of volume-of-fluid interface reconstruction algorithms: convergence in the max norm. *Communications in Applied Mathematics and Computational Science 5*, 1 (2010), 99–148.

[23] Puckett, E. A volume-of-fluid interface reconstruction algorithm that is second-order accurate in the max norm. *Communications in Applied Mathematics and Computational Science 5*, 2 (2010), 199–220.

[24] Puckett, E. Second-order accuracy of volume-of-fluid interface reconstruction algorithms, ii: An improved constraint on the cell size. *Communications in Applied Mathematics and Computational Science 8*, 1 (2014), 123–158.

[25] Sussman, M., and Puckett, E. G. A coupled level set and volume-of-fluid method for computing 3d and axisymmetric incompressible two-phase flows. *Journal of Computational Physics 162*, 2 (2000), 301–337.

[26] Sussman, M., Smereka, P., and Osher, S. A level set approach for computing solutions to incompressible two-phase flow. *Journal of Computational physics 114*, 1 (1994), 146–159.

[27] Vahab, M., Sussman, M., and Shoele, K. Fluid-structure interaction of thin flexible bodies in multi-material multi-phase systems. *Journal of Computational Physics 429* (2021), 110008.

[28] Wang, M., Pan, Y., Shi, X., Wu, J., and Sun, P. Comparative study on volume conservation among various sph models for flows of different levels of violence. *Coastal Engineering 191* (2024), 104521.

[29] Wenzel, E. A., and Arienti, M. A conservative, interface-resolved, compressible framework for the modeling and simulation of liquid/gas phase change. *Journal of Computational Physics 477* (2023), 111957.

[30] Ye, Z., Estebe, C., Liu, Y., Vahab, M., Huang, Z., Sussman, M., Moradikazerouni, A., Shoele, K., Lian, Y., Ohta, M., et al. An improved coupled level set and continuous moment-of-fluid method for simulating multiphase flows with phase change. *Communications on Applied Mathematics and Computation 6*, 2 (2024), 1034–1069.