Adaptation

Philipp Koehn

20 October 2026



Adaptation



- Better quality when system is adapted to a task
- Domain adaptation to a specific domain, e.g., information technology
- Task adaptation to a specific language pair
- May also adapt to specific user (personalization)
- May optimize for a specific document or sentence

domains

Domain

- Definition

  a collection of text with similar topic, style, level of formality, etc.

- Practically: a corpus that comes from a specific source

Example

corpus	doc's	sent's	it tokens	en tokens	XCES/XML	raw	TMX	Moses
OpenSubtitles2018	48746	37.8M	304.8M	284.5M	[xces en it]	[en it]	[tmx]	[moses]
EUbookshop	9028	6.6M	268.7M	258.8M	[xces en it]	[en it]	[tmx]	[moses]
OpenSubtitles2016	35929	28.7M	230.3M	214.9M	[xces en it]	[en it]	[tmx]	[moses]
DGT	26880	3.2M	72.9M	64.0M	[xces en it]	[en it]	[tmx]	[moses]
Europarl	9461	2.0M	59.9M	58.9M	[xces en it]	[en it]	[tmx]	[moses]
JRC-Acquis	12042	0.8M	34.1M	34.5M	[xces en it]	[en it]	[tmx]	[moses]
Wikipedia	3	1.0M	26.5M	22.2M	[xces en it]	[en it]	[tmx]	[moses]
EMEA	1920	1.1M	12.0M	13.9M	[xces en it]	[en it]	[tmx]	[moses]
ECB	1	0.2M	5.5M	5.8M	[xces en it]	[en it]	[tmx]	[moses]
GNOME	1905	0.7M	3.8M	3.4M	[xces en it]	[en it]	[tmx]	[moses]
TED2013	1	0.2M	3.2M	2.7M	[xces en it]	[en it]	[tmx]	[moses]
Tanzil	15	0.1M	2.8M	2.4M	[xces en it]	[en it]	[tmx]	[moses]
Tatoeba	1	0.1M	3.6M	1.3M	[xces en it]	[en it]	[tmx]	[moses]
KDE4	1957	0.3M	2.2M	2.3M	[xces en it]	[en it]	[tmx]	[moses]
GlobalVoices	3220	81.3k	2.1M	2.0M	[xces en it]	[en it]	[tmx]	[moses]
News-Commentary11	1423	45.9k	1.3M	1.0M	[xces en it]	[en it]	[tmx]	[moses]
Books	8	33.1k	0.9M	0.8M	[xces en it]	[en it]	[tmx]	[moses]
Ubuntu	452	0.1M	0.8M	0.6M	[xces en it]	[en it]	[tmx]	[moses]
News-Commentary	1	18.6k	0.5M	0.5M	[xces en it]	[en it]	[tmx]	[moses]
PHP	3270	36.8k	0.5M	0.2M	[xces en it]	[en it]	[tmx]	[moses]
EUconst	47	10.2k	0.2M	0.2M	[xces en it]	[en it]	[tmx]	[moses]
OpenSubtitles	22	19.1k	0.2M	0.1M	[xces en it]	[en it]	[tmx]	[moses]
total	**156332**	**83.1M**	**1.0G**	**975.1M**	**83.1M**		**63.4M**	**77.4M**

Available parallel corpora on OPUS web site (Italian–English)

Differences in Corpora

Medical Abilify is a medicine containing the active substance aripiprazole.
It is available as 5 mg, 10 mg, 15 mg and 30 mg tablets, as 10 mg, 15 mg and 30 mg orodispersible tablets (tablets that dissolve in the mouth), as an oral solution (1 mg/ml) and as a solution for injection (7.5 mg/ml).

Software Localization Default GNOME Theme
OK
People

Literature There was a slight noise behind her and she turned just in time to seize a small boy by the slack of his roundabout and arrest his flight.

Law Corrigendum to the Interim Agreement with a view to an Economic Partnership Agreement between the European Community and its Member States, of the one part, and the Central Africa Party, of the other part.

Religion This is The Book free of doubt and involution, a guidance for those who preserve themselves from evil and follow the straight path.

News The Facebook page of a leading Iranian leading cartoonist, Mana Nayestani, was hacked on Tuesday, 11 September 2012, by pro-regime hackers who call themselves ”Soldiers of Islam”.

Movie subtitles We’re taking you to Washington, D.C.
Do you know where the prisoner was transported to?
Uh, Washington.
Okay.

Twitter Thank u @Starbucks & @Spotify for celebrating artists who #GiveGood with a donation to @BTWFoundation, and to great organizations by @Metallica and @ChanceTheRapper! Limited edition cards available now at Starbucks!

Dimensions

Topic The subject matter of the text, such as politics or sports.

Modality How was this text originally created? Is this written text or transcribed speech, and if speech, is it a formal presentation or an informal dialogue full of incompleted and ungrammatical sentences?

Register Level of politeness. In some languages, this is very explicit, such as the use of the informal *Du* or the formal *Sie* for the personal pronoun *you* in German.

Intent Is the text a statement of fact, an attempt to persuade, or communication between multiple parties?

Style Is it a terse informal text, are full of emotional and flowery language?

Dimensions

- In reality, no clear information about dimensions
- For example: Wikipedia
  - spans a whole range of topics
  - fairly consistent in modality and style
- Practical goal: enforce a certain level of politeness
- Probably
  - European parliament proceedings more polite
  - movie subtitles less polite

Impact of Domain


- Different word meanings
  - *bat* in baseball
  - *bat* in wildlife report
- Different style
  - *What's up, dude?*
  - *Good morning, sir.*

Diverse Problem

- Data may differ narrowly or drastically
- Amount of relevant and less relevant data differ
- Data may be split by domain or mixed
- Data may differ by quality
- Each corpus may be relatively homogeneous or heterogeneous
- May need to adapt on the fly


$\Rightarrow$ Different methods may apply, experimentation needed

Multiple Domain Scenario



- Multiple collections of data, clearly identified
  e.g., sports, information technology, finance, law, ...
- Train specialized model for each domain
- Route test sentences to appropriate model (using classifier, if not known)
- Probabilistic assignment

In/Out Domain Scenario



- Optimize system for just one domain
- Available data
  - small amounts of in-domain data
  - large amounts of out-of-domain data
- Need to balance both data sources

Why Use Out-of-Domain Data?



- In-domain data much more valuable
- But: gaps
  - word-to-be-translated may not occur
  - word-to-be-translated may not occur with the correct translation
- Motivation
  - out-of-domain data may fill these gaps
  - but be careful not to drown out in-domain data


Broader View of Adaptation

- Adapting large language models
  - many large language models have been made available
  - these translate reasonably well
  - adapting them to machine translation improves that
- Adapting multilingual translation models
  - existing large multilingual language models (such as NLLB)
  - pretraining a model on high resource language pairs

  → then fine-tune on targeted language pair
- In general: adapting pre-trained models
  - often much more monolingual and related parallel data
  - training in two steps
    - pretraining on related data
    - fine-tuning on relevant data


strategies

Combine Data




- Too biased towards out of domain data
- May flag translation options with indicator feature functions

Interpolate Data




Oversample in-domain data

Interpolate Models



Fine-Tuning



Domain-Aware Training

- Train a model on all domains
- Indicate domain for each input sentence
- Domain token
  - append domain token to each input sentence, e.g., <SPORTS>
  - label training data
  - label test data
- Neural machine translation models
  - domain token will have word embedding
  - attention model will rely on domain token as needed

unknown domains

Unknown Domain at Test Time




- Domain of input sentence unknown

- Classifier: predict domain of input sentence
  - predict domain token
  - augment input sentence

- Probability distribution over domains
  - sentences may not fall neatly into one of our pre-defined domains
  - e.g., rule violation in sports → SPORTS, LAW
  - encode soft domain assignment in vector
  - may be also used to label training data

Topic Models



- Cluster corpus by topic — Latent Dirichlet Allocation (LDA)
- Train separate sub-models for each topic
- For input sentence, detect topic (or topic distribution)

Latent Dirichlet Allocation (LDA)


- Formalized as a graphical model
- Sentences belong to a fixed number of topics
- Model
  - predicts distribution over topics
  - predicts words based on each topic
- For instance, typical topics
  - *European, political, policy, interests, ...*
  - *crisis, rate, financial, monetary, ...*

Sentence Embeddings

- Sentence embeddings
  - simple method: average of embedding of the words in the sentence
  - ongoing research on more complex methods
- Cluster sentences into topics: k-means clustering
  - randomly generate centroids (vectors in sentence embedding space)
  - assign each sentence to its closest centroid
  - re-compute centroid as center of the embeddings of its assigned sentences
  - iterate
- Input sentence to be translated
  - assign to topic, based on proximity to centroids
  - translate with topic-specific model

subsampling

Sentence Selection




- Select out-of-domain sentence pairs that are similar to in-domain data

Sentence Selection

- Various methods
- Goal 1: Increase coverage (fill gaps)
- Goal 2: Get content with in-domain content, style, etc.


Moore Lewis




- Build language models
  - out of domain
  - in domain
- Score each sentence
- Sub-select sentence pairs with

$$p_{\text{IN}}(f) - p_{\text{OUT}}(f) > \tau$$

Modified Moore Lewis





- 2 sets of language models
  - source language
  - target language
- Add scores

Coverage-Based Methods

- Problem with subsampling sentences based on similarity: not much new is added

- Original goal: increase coverage with out-of-domain data

→ coverage-based selection

Basic Approach

- Score each candidate sentence pair to be added based on word-based score

$$\frac{1}{|s_i|} \sum_{w \in s} \text{score}(w, s_{1,..,i-1})$$

- Simple word score: check if word w occurred in the previously added sentences $s_1, ..., s_{i-1}$

$$\text{score}(w, s_{1,..,i-1}) = \begin{cases} 0 & \text{if } w \in s_1, ..., s_{i-1} \\ 1 & \text{otherwise} \end{cases}$$

- Add sentence with highest score

Instance Weighting

- So far: either include sentence pair or not
- Now: weigh sentence pair based on relevance


- Use same scoring metrics as previously for filtering
- Scale learning rate by relevance score

Curriculum Training

- Recall: relevance score for each sentence pair
- Training epochs
  - start with all data (100%)
  - train only on somewhat relevant data (50%)
  - train only on relevant data (25%)
  - train only on very relevant data (10%)

adapting pre-trained models

Fine-Tuning



- First train system on out-of-domain data (or: all available data)
- Stop at convergence
- Then, continue training on in-domain data

Catastrophic Forgetting

- Fine tuning may overfit to in-domain data (catastrophic forgetting)
- Two goals
  - do well on in-domain data
  - maintain quality on out-of-domain data
- Makes model more robust on in-domain data as well

Updating Only Some Model Parameters



- Too many parameters, too few in-domain data
- Update only some parameters
  - weights for decoder state progression
  - output word prediction softmax
  - output word embeddings

Adaptation Parameters

- Leave general model parameters fixed
- Learning hidden unit contribution (LHUC) layer [Vilar, 2018]
  - learn scaling values in narrow range (say, factor 0 to 2)

$$a(\rho) = \frac{2}{1 + e^{\rho}}$$


  - scale values of decoder state s.

$$s_{\text{LHUC}} = a(\rho) \circ s$$

- Can be easily turned off


Low Rank Adaptation (LoRA)

- Generic method to use fewer parameters during adaptation
- Augment each parameter matrix with two smaller matrices



  - original matrix: $m \times m$ matrix
  - adaptation matrices: $m \times r$ and $r \times m$ with $r << m$
  - original matrix unchanged

QLoRA: Add Quantization



- Store values in 4 bit floats (or less) [Dettmers et al., 2023]
- Computation still in 16 bits

Regularized Training Objective



- Stated goal: do not diverge too far from the original model

- Default training objective
  - reduce the error on word predictions probability $t_i[y_i]$
  - given to the correct output word y_i at time step i

$$\text{cost} = -\log t_i[y_i]$$

- Measurement of difference to general model's prediction t_i^{BASE}

$$\text{cost}_{\text{REG}} = \sum_{y \in V} t_i^{\text{BASE}}[y] \log t_i[y]$$

- Combine both training objectives

$$(1 - \alpha)\ \text{cost} + \alpha\ \text{cost}_{\text{REG}}$$

- Balancing factor α can be used to balance in-domain / out-of-domain quality

adapting language models to machine translation


Fine-Tuning LLMs with QLoRA

- Convert parallel data into chat format

  Translate the following sentence from German to English.
  German: Das Haus ist groß.
  English: The house is big.

- Use it as instruction data for fine-tuning large language model

- Example: Fine-tuning LLMs with QLoRA [Zhang et al., 2022]




- Baseline: NMT Transformer trained on the same data

Fine-Tuning to Document-Level Data

- Document-level data (multiple sentences)


  Translate the following sentences from German to English.
  German: Das Haus ist groß. Ich mag es. Ich wohne dort mit meiner Familie.
  English: The house is big. I like it. I live there with my famiily.

- Document-level COMET scores (best scores with 10-sentence instructions)



Monolingual Data

- Recall: Current large language models predominately trained on English text



Llama2 trained on 89.7% English data

- Fine-tuning also on monolingual data in the relevant languages helpful

TowerBlocks



- Diverse dataset, includes traditional NLP tasks in multiple languages

WMT14 to WMT21 General Translation
WMT22 Few-shot General Translation w/ Quality Shots
NTREX General Translation
Flores Dev General Translation
FRMT General Translation
QT21 General Translation, Automatic Post Edition
ApeQuest General Translation, Automatic Post Edition
OPUS (Quality Filtered) General Translation
MT-GenEval General Translation, Context-Aware Translation
WMT20 to WMT22 Metrics MQM Machine Translation Evaluation
WMT17 to WMT22 Metrics Direct Assessments Machine Translation Evaluation
WMT21 Terminology Dev (filtered) Terminology-aware Translation
Tatoeba Dev (filtered) Multi-reference Translation
MultiCoNER 2022 and 2023 Dev Named-entity Recognition
PAWS-X Dev Paraphrase Generation
UltraChat 200k (filtered) Synthetic Chat data
Glaive Code Assistant (filtered) Code instructions

https://huggingface.co/datasets/Unbabel/TowerBlocks-v0.1

fine-grained adaptation


Fine-Grained Domains: Personalization



- Thousands of domains
  - machine translation system personalized for individual translators
  - machine translation system optimized for individual authors
- Domain token/classification idea does not scale well
- Not much data for each translator/author

$\Rightarrow$ Just learn adaptation parameters for the output embedding layer

Document-Level Adaptation



- Computer aided translation: translator post-edits machine translation
- Provides additional training data (translated sentences)
- Incrementally update model

Sentence-Level Adaptation

- Adapt model to each sentence to be translated

- Find most similar sentence in parallel corpus (fuzzy match)
- Retrieve it and its translation
- Adapt model with this sentence pair



questions?