

Table 6 Internally validated prediction performance

Required footnotes: model-population eyes and unique patients; 20 repeats of grouped five-fold outer/four-fold inner validation; training-only preprocessing; penalty grid/objective; mean repeat-level metrics; 1,000 patient-cluster bootstrap attempts, successful number and failed reasons. Calibration ideal values are intercept 0 and slope 1. Fold scores are not independent observations. Label confidence intervals approximate and exploratory. Current data readiness is unmet, so no actual performance values are supplied.

Model / comparison	MAE, logMAR (95% CI)	RMSE, logMAR (95% CI)	Calibration intercept / slope
Training mean reference	[not run / estimate]	[not run / estimate]	[intercept; slope not applicable if constant]
Clinical benchmark: baseline CDVA + cohort	[not run / estimate]	[not run / estimate]	[a; b; 95% CIs]
Ridge: six baseline predictors	[not run / estimate]	[not run / estimate]	[a; b; 95% CIs]
Ridge minus benchmark	[paired difference; 95% CI]	[paired difference; 95% CI]	[descriptive comparison]
Sensitivity: one eye per patient	[not run / estimate]	[not run / estimate]	[a; b; 95% CIs]
Sensitivity: Kmax/TCT imputation	[not run / estimate]	[not run / estimate]	[a; b; 95% CIs]

