

# R-Package ‘MrImputation II’

January 3, 2026

**Type** Package

**Version** 0.0.2

**Title** Multiple Ratio Imputation II

**Date** January 3, 2026

**Author** Masayoshi Takahashi ([mtakahashi615@g.chuo-u.ac.jp](mailto:mtakahashi615@g.chuo-u.ac.jp))

**Depends** R (>=4.5.0)

**Description** R-Package MrImputation II implements the methods proposed by Takahashi (2025) and Takahashi (2026). This is an extended version of Takahashi (2017a, 2017b), which originally implemented R-Package MrImputation.

**URL** <https://github.com/mtakahashi123/MrImputationII>

**Repository** GitHub

## R topics documented

MrImputation-package .....	2
BPTtest.....	2
ExampleData00.csv.....	3
ExampleData05.csv.....	4
ExampleData10.csv.....	4
mranalyze2 .....	5
mrdiag.....	6
mrimpute2 .....	6
outputimp.csv.....	8
thetahat .....	8

---

MrImputation- package	<i>Multiple ratio imputation with diagnostic tests</i>
--------------------------	--

---

### Description

To use this package, click “Code” and “Download ZIP” at <https://github.com/mtakahashi123/MrImputationII>. After downloading the package, set the working directory in R, and read R-Package MrImputationII using R-function `source` by either of the following methods.

#### Method 1

```
setwd("C:/Folder")
source("MrImputationII.R")
```

#### Method 2

```
source(file.choose())
```

### References

- Takahashi, M. (2026) “Multiple imputation by the flexible ratio estimator that automatically specifies the degree of heteroskedasticity.”
- Takahashi, M. (2025) “The treatment of missing values in official statistics.” *The Journal of Economics*, 65 (5/6), 125-136.
- Takahashi, M. (2017a) “Multiple ratio imputation by the EMB algorithm: Theory and simulation.” *Journal of Modern Applied Statistical Methods*, 16 (1), 630-656.
- Takahashi, M. (2017b) “JMASM44: Implementing multiple ratio imputation by the EMB Algorithm (R).” *Journal of Modern Applied Statistical Methods*, 16 (1), 657-673.

---

BPTtest	<i>R-function to diagnose the estimated theta</i>
---------	---

---

### Description

BPTtest implements the Breusch-Pagan-Takahashi test for the degree of heteroskedasticity.

**Usage**

```
BPTtest(y, x, theta = 0)
```

**Arguments**

<code>y</code>	Target variable for imputation
<code>x</code>	Auxiliary variable for the imputation model
<code>theta</code>	Value for the null hypothesis, i.e., the degree of heteroskedasticity. Default is 0.

**Value**

<code>BPT</code>	LM statistic for the BPT test for heteroskedasticity
<code>df</code>	Degrees of freedom
<code>p.value</code>	P-value. If the significance level is 0.05 and the p-value is less than 0.05, we reject the null hypothesis at the 5% error level, meaning that the estimated theta is considered to be wrong.

**References**

Takahashi, M. (2026) “Multiple imputation by the flexible ratio estimator that automatically specifies the degree of heteroskedasticity.”

Takahashi, M. (2025) “The treatment of missing values in official statistics.” *The Journal of Economics*, 65 (5/6), 125-136.

Breusch, T. S. and Pagan, A. R. (1979) “A simple test for heteroscedasticity and random coefficient variation.” *Econometrica*, 47 (5), 1287-1294.

**Example**

```
BPTtest(var1, var2, theta = 1.8956)
```

---

ExampleData00.csv    *Simulated data for example 1*

---

**Description**

This is a simulated dataset as an example. The true value of theta is set to 0.0.

**Usage**

```
data1 <- read.csv("ExampleData00.csv", header=TRUE)
attach(data1)
```

**Format**

A data frame with 1000 observations on the following two variables.

var1 the target variable for imputation with 285 observations missing.

var2 the auxiliary variable for the imputation model.

---

ExampleData05.csv *Simulated data for example 2*

---

**Description**

This is a simulated dataset as an example. The true value of theta is set to 0.5.

**Usage**

```
data1 <- read.csv("ExampleData05.csv", header=TRUE)
attach(data1)
```

**Format**

A data frame with 1000 observations on the following two variables.

var1 the target variable for imputation with 285 observations missing.

var2 the auxiliary variable for the imputation model.

---

ExampleData10.csv *Simulated data for example 3*

---

**Description**

This is a simulated dataset as an example. The true value of theta is set to 1.0.

**Usage**

```
data1 <- read.csv("ExampleData10.csv", header=TRUE)
attach(data1)
```

**Format**

A data frame with 1000 observations on the following two variables.

`var1` the target variable for imputation with 285 observations missing.

`var2` the auxiliary variable for the imputation model.

---

<code>mranalyze2</code>	<i>R-function to analyze multiply-imputed datasets after multiple ratio imputation</i>
-------------------------	--

---

**Description**

`mranalyze2` computes the mean, the standard error, the confidence intervals, the correlation coefficient, and the degrees of freedom after multiple ratio imputation. It automatically combines  $M$  estimates.

**Usage**

```
mranalyze2(data, alpha = 0.05)
```

**Arguments**

<code>data</code>	Multiply-imputed data after <code>mrimpute2</code>
<code>alpha</code>	Significance level. Default is 0.05.

**Value**

<code>ybar</code>	Sample mean of the target variable
<code>se</code>	Standard error of the sample mean
<code>CI.LL</code>	Lower limit of the confidence interval
<code>CI.UL</code>	Upper limit of the confidence interval
<code>corr</code>	Correlation coefficient
<code>df</code>	Degrees of freedom

**References**

Takahashi, M. (2026) “Multiple imputation by the flexible ratio estimator that automatically specifies the degree of heteroskedasticity.”

Takahashi, M. (2017a) “Multiple ratio imputation by the EMB algorithm: Theory and simulation.” *Journal of Modern Applied Statistical Methods*, 16 (1), 630-656.

Takahashi, M. (2017b) “JMASM44: Implementing multiple ratio imputation by the

EMB Algorithm (R).” *Journal of Modern Applied Statistical Methods*, 16 (1), 657-673.

### Example

```
outputimp <- read.csv(file.choose())
mranalyze2(outputimp)
mranalyze2(outputimp, alpha = 0.01)
```

---

mrdiag	<i>R-function to produce diagnostic plot for multiply-imputed datasets after multiple ratio imputation</i>
--------	--

---

### Description

mrdiag plots the density of observed data and multiply-imputed data.

### Usage

```
mrdiag(data)
```

### Arguments

data	Multiply-imputed data after mrimpute2
------	---------------------------------------

### References

van Buuren, S. (2018) *Flexible Imputation of Missing Data*, 2nd ed. CRC Press.

### Example

```
outputimp <- read.csv(file.choose())
mrdiag(outputimp)
```

---

mrimpute2	<i>R-function to compute multiple ratio imputation</i>
-----------	--

---

### Description

mrimpute2 multiply-imputes missing values based on multiple ratio imputation.

**Usage**

```
mrimpute2(y, x, M = 5, iter = 5)
```

**Arguments**

<code>y</code>	Target variable for imputation
<code>x</code>	Auxiliary variable for the imputation model
<code>M</code>	Number of multiply-imputed datasets. Default is 5.
<code>iter</code>	Number of iterations to estimate the degree of heteroskedasticity. Default is 5.

**References**

Takahashi, M. (2026) “Multiple imputation by the flexible ratio estimator that automatically specifies the degree of heteroskedasticity.”

Takahashi, M. (2017a) “Multiple ratio imputation by the EMB algorithm: Theory and simulation.” *Journal of Modern Applied Statistical Methods*, 16 (1), 630-656.

Takahashi, M. (2017b) “JMASM44: Implementing multiple ratio imputation by the EMB Algorithm (R).” *Journal of Modern Applied Statistical Methods*, 16 (1), 657-673.

**Example**

```
imp1 <- mrimpute2(var1, var2)
imp2 <- mrimpute2(var1, var2, M = 100)
imp3 <- mrimpute2(var1, var2, M = 100, iter = 10)
```

**Value**

A data frame with  $n$  observations on the following  $M + 2$  variables.

V1 the target variable for imputation. The same as `var1`.

V2 the auxiliary variable for the imputation model. The same as `var2`.

V3 multiply-imputed data of `var1`, where  $m = 1$ .

V4 multiply-imputed data of `var1`, where  $m = 2$ .

⋮

VM+2 multiply-imputed data of `var1`, where  $m = M$ .

---

outputimp.csv	<i>Multiply-imputed data for example</i>
---------------	--

---

### Description

This is an example of multiply-imputed dataset after multiple ratio imputation by R function `mrimpute2`.

### Usage

```
outputimp <- read.csv("outputimp.csv", header=TRUE)
attach(outputimp)
```

### Format

A data frame with 1000 observations on the following six variables.

V1 the target variable for imputation. The same as `var1`.

V2 the auxiliary variable for the imputation model. The same as `var2`.

V3 multiply-imputed data of `var1`, where  $m = 1$ .

V4 multiply-imputed data of `var1`, where  $m = 2$ .

V5 multiply-imputed data of `var1`, where  $m = 3$ .

V6 multiply-imputed data of `var1`, where  $m = 4$ .

V7 multiply-imputed data of `var1`, where  $m = 5$ .

---

thetahat	<i>R-function to estimate the degree of heteroskedasticity</i>
----------	--

---

### Description

`thetahat` estimates the degree of heteroskedasticity for ratio imputation.

### Usage

```
thetahat(y, x, iter = 5, convplot = TRUE)
```

### Arguments

<code>y</code>	Target variable for imputation
<code>x</code>	Auxiliary variable for the imputation model
<code>iter</code>	Number of iterations to estimate the degree of heteroskedasticity. Default is 5.



`convplot`      Convergence plot to check whether the estimated theta converges to a certain point. Default is TRUE.

**Value**

`theta.hat`      Estimated value of theta, which is the degree of heteroskedasticity.

**References**

Takahashi, M. (2026) “Multiple imputation by the flexible ratio estimator that automatically specifies the degree of heteroskedasticity.”

**Example**

```
t1 <- thetahat(var1, var2)
t1 <- thetahat(var1, var2, iter = 100)
t1 <- thetahat(var1, var2, iter = 100, convplot = FALSE)
```