

NucNetPy

Release 1.0.0

M.\@{} H.\@{} Talafha and N.\@{} M.\@{} Ershaidat

Jul 29, 2026

1	Installation	3
1.1	Requirements	3
1.2	From a checkout	3
1.3	Optional extras	3
1.4	Verifying the installation	3
1.5	Building this manual.	4
2	Concepts	5
2.1	Species.	5
2.2	Reaction	5
2.3	ReactionNetwork.	6
2.4	Zone	6
2.5	Network.	6
2.6	Units	6
3	Common workflows	7
3.1	Reading a JINA/libnucnet database	7
3.2	Cutting a network down to size	7
3.3	Evolving one zone	7
3.4	Equilibrium.	8
3.5	Thermodynamic consistency	8
3.6	Screening	8
3.7	Energy release	9
3.8	Analysis	9
3.9	Command line	9
4	Pitfalls	11
4.1	Dropping the photon when you cut a network	11
4.2	Assuming reverse rates are consistent with the masses	11
4.3	Placeholder nuclear data in an equilibrium solve	11
4.4	Trusting <code>success</code> without checking it.	12
4.5	Forgetting the spin degeneracy	12
4.6	Tolerances	12
4.7	Interpolating a detailed-balance reverse rate	12
5	Verifying a calculation	13
5.1	What the package checks for you	13
5.2	What you should check on your own calculation	13
5.3	Golden files and what they do not prove.	13
5.4	Reproducing the published results	14

6	Python API	15
6.1	Core objects	15
6.2	Evolution.	23
6.3	Equilibrium	26
6.4	Detailed balance	32
6.5	Screening, weak rates, decays	34
6.6	Analysis	40
6.7	Input and output	44
6.8	Utilities.	45
7	Command line	51
7.1	summary.	51
7.2	print-output.	51
7.3	largest-x	52
7.4	zone-abundances	52
7.5	zone-properties	52
7.6	element-abundances	53
7.7	rates	53
7.8	flows	53
7.9	ydot	53
7.10	net-flows	54
7.11	charge-flows.	54
7.12	timescales	54
7.13	entropy-generation.	55
7.14	conservation.	55
7.15	remove-duplicates.	55
7.16	remove-invalid	55
7.17	export-zone-xml	56
7.18	reactions-latex	56
7.19	species-history	56
7.20	evolve-zone	56
7.21	energy-generation.	57
7.22	net-dot.	57
7.23	validate.	57
7.24	nse.	58
7.25	qse.	58
7.26	jina-summary.	58
7.27	jina-combine.	59
8	Conversion map from original NucNet Tools concepts to nucnetpy	61
8.1	What is implemented in alpha 2	61
8.2	What still needs project-specific validation	62
9	Blog workflow coverage	63
9.1	Covered	63
9.2	Ported from the C++ source (r647)	65
9.3	Not ported (by design or still open).	66
10	Pure Python port status	67
10.1	What remains for strict numerical identity.	67
11	Exact numerical identity policy	69
11.1	Build the original backend.	69
11.2	Run an original executable through Python	69
11.3	Compare outputs	70
11.4	Development rule.	70

12 JINA XML workflow in nucnetpy	71
12.1 Files.	71
12.2 Python usage	71
12.3 Command-line usage.	71
12.4 Important numerical point.	71
13 Where to start	73
14 Citing	75
Python Module Index	77
Index	79

NucNetPy is a pure-Python nuclear reaction-network package. It reads JINA/libnucnet XML data, evaluates reaction rates, builds and integrates the abundance equations with stiff solvers, solves nuclear statistical and quasi-statistical equilibrium, and provides the analysis quantities used in the NucNet Tools workflows.

It is a clean reimplementation: it does not call or wrap the original C/C++ code, and NumPy and SciPy are its only mandatory dependencies.

Installation

1.1 Requirements

Python 3.9 or later, with NumPy 1.22+ and SciPy 1.9+. Nothing else is required to use the package.

1.2 From a checkout

```
git clone https://github.com/mtalafha90/NucNetPy.git
cd NucNetPy
python -m pip install -e .
pytest -q
```

The test suite runs in about a second and should report all tests passing before you rely on any result.

1.3 Optional extras

Extra	Adds	For
dev	pytest	running the test suite
hdf5	h5py	HDF5 persistence
plot	matplotlib, networkx	plotting and graph export
notebook	jupyter, pandas, matplotlib	the tutorial notebooks
docs	sphinx, furo, myst-parser	building this manual

```
python -m pip install -e ".[dev,hdf5,plot,notebook]"
```

pandas is used only by the notebooks to display tables; the package itself never imports it.

1.4 Verifying the installation

```
import nucnetpy as nn
print(nn.__version__)
```

The command-line interface is installed alongside:

```
nucnetpy --help
```

1.5 Building this manual

```
python -m pip install -e ".[docs]"  
sphinx-build -b html docs/manual docs/manual/_build/html
```

For a single self-contained file, suitable for a submission archive:

```
sphinx-build -b singlehtml docs/manual docs/manual/_build/singlehtml
```

Concepts

Five objects carry everything.

2.1 Species

A nuclide: name, charge z , mass number a , mass excess, ground-state spin, and an optional partition-function table.

```
import nucnetpy as nn

ni56 = nn.Species("ni56", z=28, a=56, mass_excess=-53.907, spin=0.0)
```

Mass excess and spin are not decoration. Equilibrium, detailed balance and energy release are all computed from mass excesses, and the statistical weight in an equilibrium solve is $(2J+1) * G(T)$, so a placeholder value produces a placeholder answer. A species whose spin is unknown is given a weight of one rather than a guess.

`Species.parse` builds one from a name alone, normalising aliases ($p \rightarrow h1$, $\alpha \rightarrow he4$), but it cannot invent nuclear data.

2.1.1 Participants that are not nuclides

`gamma`, `electron`, `positron` and the neutrinos appear in reaction records so that charge and lepton number balance, but they carry no baryon number and are never part of the abundance vector. `nucnetpy.species.is_massless` identifies them. See [Pitfalls](#).

2.2 Reaction

Reactants, products, a rate, a Q -value, and metadata. The rate may be a ReacLib seven-coefficient fit, a tabulated rate, a constant, or a callable; a reaction may carry more than one, and they add.

```
r = nn.Reaction.from_names(["c12", "he4"], ["o16", "gamma"],
                           rate_fits=[nn.RateFit([10, 0, 0, 0, 0, 0, 0])],
                           q_value=7.162)
```

The flow of a reaction is

(2.1)

where the products run over the reactants that carry baryon number, and i is that reactant order. `Reaction.nuclear_reactants` is the list actually used.

2.3 ReactionNetwork

A collection of reactions, with duplicate removal, filtering, and the construction of rates, flows, and .

2.4 Zone

One composition together with its thermodynamic properties. Abundances are molar: Y is moles per gram, and the mass fraction is $X = A \cdot Y$. A normalised composition has $\sum(X) = 1$.

```
zone = nn.Zone(abundances={"si28": 1.0 / 28.0},
               properties={"t9": "5.0", "rho": "1e8"})
```

2.5 Network

Species, reactions and zones in one container, plus `validate()`, which reports species named by a reaction but absent from the species map, reactions that do not balance, and species carrying no nuclear data.

2.6 Units

Quantity	Unit
Temperature t_9	K
Density ρ	g cm^{-3}
Abundance Y	mol g^{-1}
Mass excess	MeV
Q-value	MeV
Rate	s^{-1} scaled by the density powers of the flow
Energy generation	$\text{erg g}^{-1} \text{s}^{-1}$
Time	s

Common workflows

3.1 Reading a JINA/libnucnet database

```
import nucnetpy as nn

net = nn.read_jina_xml("nuclides.xml", "reaction_data.xml", zones_xml="zone.xml")
report = net.validate()
print(len(net.species), "nuclides,", len(net.reactions.reactions), "reactions")
print("without nuclear data:", len(report["species_without_nuclear_data"]))
```

Reading a full database of 8131 nuclides and 81758 reactions takes about 20 s and holds roughly 880 MB. That is the practical ceiling for a pure-Python implementation, which is why the next step matters.

3.2 Cutting a network down to size

A one-zone calculation rarely needs the whole chart of nuclides.

```
from nucnetpy.network_limiter import select_species, limit_network

limit_network(net, select_species(net, zmax=20, amax=44) + ["gamma"])
```

Keep gamma. `limit_network` retains only reactions whose participants all survive the cut, and `select_species` returns nuclides, so dropping the photon silently deletes every photodisintegration. See [Pitfalls](#).

3.3 Evolving one zone

```
result = nn.evolve_zone(
    net, net.zone(0), nn.time_grid(0.0, 10.0, 120),
    thermo=nn.constant_thermo(t9=5.0, rho=1.0e8),
    method="bdf", rtol=1e-8, atol=1e-14,
)
assert result.success, result.message
```

`thermo` is any callable `(t, abundances) -> (T9, rho)`, so a prescribed temperature and density history drops straight in; `nucnetpy.hydro.Trajectory` wraps a tabulated one with interpolation.

Supported methods are `bdf`, `radau`, `lsoda`, `rk45` and `dop853`, plus fixed-step `rk4`, `euler` and `implicit_euler` fallbacks. Reaction networks are stiff, so the first three are the practical choices.

3.3.1 Choosing the Jacobian

The flows are monomials in the abundances, so the Jacobian is available in closed form and costs one sweep over the reaction list, against $N+1$ right-hand-side evaluations for finite differences.

```
nn.evolve_zone(..., jac_mode="analytic")    # default; ~275x faster at 100 species
nn.evolve_zone(..., jac_mode="numerical")  # finite differences
nn.evolve_zone(..., jac_mode="sparsity")    # SciPy estimates it from the pattern
```

SciPy applies a sparsity pattern only when no Jacobian callable is supplied, so the pattern and an explicit Jacobian are alternatives rather than complements.

3.4 Equilibrium

```
nse = nn.solve_nse(net, t9=5.0, rho=1.0e8, ye=0.5)
print(nse.success, nse.xsum, nse.computed_ye)
```

The solve shares no machinery with the time integration, which is what makes it a genuine check on a network calculation. Species carrying no nuclear data are excluded automatically; pass `require_nuclear_data=False` to override that, and read [Pitfalls](#) before doing so.

Constrained cluster equilibria (the libnuceq workflow) use `solve_qse` with `QSECluster` constraints. Plasma corrections are available through `nucnetpy.coulomb.nse_correction`.

3.5 Thermodynamic consistency

Rate libraries fit the forward and reverse directions of a reaction separately, so a network built from them relaxes to a state that is not the NSE of the same nuclear data.

```
consistent = nn.consistent_reverse_network(net)
```

This pairs each reaction with its inverse, keeps the exothermic member, and regenerates the other from detailed balance. On the JINA alpha chain it improves agreement between the integrated composition and an independent NSE solve from a median of 4.5 per cent to 4.5 parts per million.

It is an option rather than a default, because it replaces measured reverse rates with values derived from mass differences. Pass `tabulate=True` if the network must remain writable to XML, at some cost in accuracy.

3.6 Screening

```
from nucnetpy import SkyNetScreening

nn.evolve_zone(..., screening=SkyNetScreening(net.species))
```

Each nuclear charge is assigned a Coulomb chemical potential $\mu(Z)/kT$, and a reaction is enhanced by the difference between the separated reactants and the fused compound charge. Being a chemical potential, it applies consistently to forward and reverse rates, so screening does not undo detailed balance. A pairwise Salpeter factor is also available through `reaction_screening_factor`.

3.7 Energy release

```
from nucnetpy import nuclear_energy_generation_rate, nuclear_energy_release
```

The rate follows from the change in total mass excess, $\text{eps} = -N_A * \sum_i (dY_i/dt) * dM_i$, so it needs no Q -values and cannot disagree with them where a rate library and a nuclide file are inconsistent. Neutrino losses are not subtracted.

3.8 Analysis

`nucnetpy.analysis` carries the diagnostics of the NucNet Tools workflows: largest mass fractions, element abundances, abundance moments, per-species timescales $Y/|dY/dt|$, per-reaction contributions to dY_e/dt , entropy generation, s -process neutron exposure, integrated reaction currents, and separation energies.

3.9 Command line

Every operation above has a command-line equivalent; see [Command line](#).

Pitfalls

Everything in this chapter produces a plausible-looking answer rather than an error message. Each item was found by running the package against a production database rather than a test network, and each is now covered by a regression test — but the underlying trap belongs to the problem, not to this implementation, so it is worth knowing whichever code you use.

4.1 Dropping the photon when you cut a network

`limit_network` retains only reactions whose participants *all* survive the cut, and `select_species` returns nuclides. The photon is not a nuclide, so:

```
limit_network(net, select_species(net, zmax=20))           # wrong
limit_network(net, select_species(net, zmax=20) + ["gamma"]) # right
```

Without it, every photodisintegration is discarded. Nothing warns you. The network simply cannot reach equilibrium, and a silicon-burning calculation will not start at all, because it begins with .

4.2 Assuming reverse rates are consistent with the masses

A network relaxes to the equilibrium implied by the **ratios of the rates it is given**, not to the equilibrium of the nuclear data. Rate libraries fit the two directions separately, so the two need not agree.

Evaluated at the NSE composition, JINA's reverse fits leave the net flux of a reaction far from zero; rebuilt from detailed balance, the net flux vanishes to machine precision. On the alpha chain at the fits differ from detailed balance by a median factor of 1.10 and up to 1.72, which displaces equilibrium mass fractions by a median of 4.5 per cent.

Use `consistent_reverse_network` if you need the network and the equilibrium solver to agree, and understand that you are then trusting the mass table over the library's reverse fit.

4.3 Placeholder nuclear data in an equilibrium solve

A production reaction file names nuclides that its nuclide file does not describe — 279 of them in the database used for the manuscript. NucNetPy synthesises placeholders so the reactions remain usable, with a mass excess of zero.

A mass excess of zero is not a neutral default: it makes an unbound nuclide look as tightly bound as the most stable one. Left in an NSE solve, Li reached a mass fraction of 0.28 and displaced the iron peak. They are therefore recorded in `network.validate()["species_without_nuclear_data"]` and excluded from equilibrium solves by default.

4.4 Trusting success without checking it

```
result = nn.evolve_zone(...)
assert result.success, result.message
```

`success` is false when the solver failed, and also when positivity projection had to invent enough baryon number to break conservation by more than the requested tolerance.

That second case is worth understanding. The right-hand side clips its input to non-negative values, so once a component goes negative the derivative stops depending on it and its Jacobian column vanishes; an implicit solver is then free to carry that component far negative while still passing its own convergence test. Clipping it back to zero at the end converts a large negative number into invented mass. In one long integration this returned with , while SciPy reported that it had reached the end of the interval successfully.

Checking conservation costs one inner product per output step. Do it.

4.5 Forgetting the spin degeneracy

libnucnet partition-function tables are *normalised*: they tend to one as for every nuclide, high-spin ones included. The statistical weight is , and the degeneracy has to be supplied separately. Omitting it makes every nuclide with too rare by that factor — up to 90 per cent for V.

NucNetPy applies it automatically when a species carries a `spin`. If your species were built with `Species.parse`, they do not.

4.6 Tolerances

The default `atol` is an absolute floor on abundances. Set it far below the smallest abundance you care about, but not so far that the solver chases numerical noise in species that are effectively absent — that is a common cause of a stiff solve failing to start at all. Confirm the answer has stopped moving:

```
for rtol in [1e-4, 1e-6, 1e-8, 1e-10]:
    r = nn.evolve_zone(..., rtol=rtol, atol=rtol * 1e-8)
```

4.7 Interpolating a detailed-balance reverse rate

The reverse rate carries , which is far too steep to interpolate. Tabulating it on 200 logarithmically spaced points costs three orders of magnitude of accuracy against evaluating it exactly. `consistent_reverse_network` attaches a callable by default for this reason; `tabulate=True` is for when the network must be serialisable.

Verifying a calculation

Two different questions are worth keeping apart.

Verification asks whether the code does what it was designed to do. *Validation* asks whether that design describes nature, and needs a reference outside the code.

5.1 What the package checks for you

The test suite covers XML round-tripping as a fixed point, ReacLib rates on a grid, screening factors, weak-rate interpolation, right-hand-side values and their baryon residual, full trajectories, the analytic Jacobian against finite differences, the treatment of photons and leptons, solver dispatch, the spin degeneracy, exclusion of species without nuclear data, and detection of a positivity projection that manufactures mass.

```
pytest -q
```

5.2 What you should check on your own calculation

Conservation. For a reaction set that conserves baryon number, the instantaneous residual (5.1)

should stay at round-off, and should stay at its initial value. Track them along the whole trajectory, not only at the start.

Solver agreement. Repeat the calculation with `bdf`, `radau` and `lsoda`. They should agree far more closely than any physical effect you care about.

Tolerance convergence. Tighten `rtol` and confirm the endpoint stops moving.

Equilibrium. Where the physics allows it, run the calculation to its stationary state and compare with `solve_nse`. This is the strongest check available, because the two share no machinery. Read [Pitfalls](#) on reverse rates first, or the comparison will measure the rate library rather than the code.

5.3 Golden files and what they do not prove

`tests/golden/` holds frozen outputs, and `nucnetpy.validation.regression_summary` compares against them. These detect accidental changes in behaviour. They are snapshots of this implementation, so they are not independent evidence that an answer is right, and they must not be described as agreement with the original C++ code.

`validation/generate_golden.py` writes the reference records in the format the suite consumes, so outputs from a NucNet Tools build can be substituted for the self-generated ones without changing any test code.

5.4 Reproducing the published results

```
python validation/demonstration.py \  
    --nuclides nuclides.xml --reactions reaction_data.xml --zone zone.xml \  
    --outdir results/  
  
python validation/benchmark_performance.py \  
    --nuclides nuclides.xml --reactions reaction_data.xml \  
    --json results/benchmark.json --latex results/table_benchmark.tex
```

Both record the interpreter, NumPy, SciPy and platform versions alongside their output.

Everything below is exported at the top level of `nucnetpy` unless noted. Pages are generated from the docstrings in the source.

6.1 Core objects

Nuclide/species utilities.

This module provides the most frequently needed pieces of libnucnet species handling in pure Python: name parsing, Z/A/N bookkeeping, mass fractions, charge fractions, and common element symbols.

```
nucnetpy.species.MASSLESS_SPECIES = frozenset({'anti-neutrino_e', 'antineutrinoe', 'electron', 'gamma', 'neutrino_e', 'neutrinoe', 'positron'})
```

Reaction participants that carry no baryon number. Photons and leptons appear explicitly in JINA/libnucnet reaction records so that charge and lepton number can be checked, but they are not part of the abundance vector: the photon bath and the electron sea are properties of the thermodynamic state, and their densities are already folded into the tabulated rate. They must therefore be excluded from the abundance product, the reactant order, and the identical-particle statistical factor of a reaction flow.

```
nucnetpy.species.is_massless ( name )
```

Return True for photons and leptons, which carry no baryon number.

Parameters `name` (*str*)

Return type bool

```
class nucnetpy.species.Species ( name, z, a, mass_excess=0.0, spin=None, source=None, partition=<factory> )
```

Bases: object

A nuclear species.

Parameters are intentionally similar to libnucnet's Nuc objects. *mass_excess* is in MeV when available. *partition* may store temperature dependent partition-function data.

Parameters

- **name** (*str*)
- **z** (*int*)
- **a** (*int*)
- **mass_excess** (*float*)
- **spin** (*float* | *None*)
- **source** (*str* | *None*)
- **partition** (*Dict*[*float*, *float*])

```
name: str

z: int

a: int

mass_excess: float = 0.0

spin: float | None = None

source: str | None = None

partition: Dict[float, float]

property n: int

property element: str

property latex: str

classmethod parse ( value, **kwargs )
    Parameters value(str)
    Return type Species
```

```
nucnetpy.species.normalize_species_name ( value )
    Parameters value(str)
    Return type str
```

```
nucnetpy.species.species_from_za ( z, a, **kwargs )
    Parameters
        • z(int)
        • a(int)

    Return type Species
```

```
nucnetpy.species.mass_fraction ( y, a )
    Parameters
        • y(float)
        • a(int)
```

Return type float

```
nucnetpy.species.abundance_from_mass_fraction ( x, a )
    Parameters
        • x(float)
        • a(int)
```

Return type float

Core containers: Network, Zone, and multi-zone collections.

```
class nucnetpy.core.Zone ( label: 'Tuple[str, str, str]'=('0', '0', '0'),
    abundances: 'Dict[str, float]'=<factory>, properties: 'Dict[str,
    str]'=<factory>, optional_properties: 'Dict[str, str]'=<factory> )
    Bases: object

    Parameters
        • label(Tuple[str, str, str])
        • abundances(Dict[str, float])
```

```

    • properties (Dict[str, str])
    • optional_properties (Dict[str, str])

label: Tuple[str, str, str] = ('0', '0', '0')
abundances: Dict[str, float]
properties: Dict[str, str]
optional_properties: Dict[str, str]
set_abundance ( species, y )
    Parameters    • species (str)
                  • y (float)

    Return type None

get_abundance ( species, default=0.0 )
    Parameters    • species (str)
                  • default (float)

    Return type float

mass_fractions ( species_map=None )
    Parameters species_map (Mapping[str, Species] | None)
    Return type Dict[str, float]

ye ( species_map=None )
    Parameters species_map (Mapping[str, Species] | None)
    Return type float

ysum ( )
    Return type float

xsum ( species_map=None )
    Parameters species_map (Mapping[str, Species] | None)
    Return type float

temperature9 ( default=1.0 )
    Parameters default (float)
    Return type float

density ( default=1.0 )
    Parameters default (float)
    Return type float

class nucnetpy.core.Network ( species: 'Dict[str, Species]'=<factory>,
    reactions: 'ReactionNetwork' = <factory>, zones: 'List[Zone]' = <factory>,
    metadata: 'Dict[str, str]'=<factory> )
    Bases: object
    Parameters    • species (Dict[str, Species])

```

- **reactions** (*ReactionNetwork*)
- **zones** (*List[Zone]*)
- **metadata** (*Dict[str, str]*)

species: *Dict[str, Species]*

reactions: *ReactionNetwork*

zones: *List[Zone]*

metadata: *Dict[str, str]*

add_species (*species*)

Parameters **species** (*Species*)

Return type *None*

ensure_species (*name*)

Parameters **name** (*str*)

Return type *Species*

add_zone (*zone*)

Parameters **zone** (*Zone*)

Return type *None*

species_names ()

Return type *List[str]*

zone (*index=0*)

Parameters **index** (*int*)

Return type *Zone*

validate ()

Return type *Dict[str, object]*

species_without_nuclear_data ()

Return species that were synthesised to satisfy a reaction record.

These are referenced by the reaction file but absent from the nuclide file, so they carry a placeholder mass excess of zero rather than measured or evaluated data. They are safe for structural operations such as counting or plotting the network, but must not enter an equilibrium calculation, where a mass excess sets the binding energy.

Return type *List[str]*

abundance_matrix (*species=None*)

Parameters **species** (*Sequence[str] | None*)

Return type *Tuple[List[str], ndarray]*

Reaction and rate machinery for a pure-Python NucNet Tools replacement.

The implementation supports common ReacLib 7-coefficient rates, tabulated rates, manual constants, duplicate handling, conservation checks, and stoichiometric flux evaluation suitable for one-zone evolution and analysis commands.


```

class nucnetpy.reactions.ReactionParticipant ( species: 'str', count:
'int' = 1 )
    Bases: object

    Parameters
        • species (str)
        • count (int)

    species: str

    count: int = 1

class nucnetpy.reactions.RateFit ( coefficients, label='', chapter=None )
    Bases: object
    A standard seven-parameter ReacLib rate fit.
    Rate =  $\exp(a_0 + a_1/T_9 + a_2/T_9^{1/3} + a_3 \cdot T_9^{1/3} + a_4 \cdot T_9$ 
        •  $a_5 \cdot T_9^{5/3} + a_6 \cdot \ln(T_9)$ )

    Parameters
        • coefficients (Sequence[float])
        • label (str)
        • chapter (int | None)

    coefficients: Sequence[float]

    label: str = ''

    chapter: int | None = None

    rate ( t9 )
        Parameters t9 (float)
        Return type float

class nucnetpy.reactions.TabularRate ( t9: 'Sequence[float]', rates:
'Sequence[float]', log_interp: 'bool' = True )
    Bases: object

    Parameters
        • t9 (Sequence[float])
        • rates (Sequence[float])
        • log_interp (bool)

    t9: Sequence[float]

    rates: Sequence[float]

    log_interp: bool = True

    rate ( t9 )
        Parameters t9 (float)
        Return type float

```

```
class nucnetpy.reactions.Reaction ( reactants: 'List[ReactionParticipan-
t]', products: 'List[ReactionParticipant]', rate_fits: 'List[RateFit]' =
<factory>, tabular_rate: 'Optional[TabularRate]' = None, q_value: 'float' =
0.0, source: 'str' = '', label: 'str' = '', metadata: 'Dict[str, str]' =
<factory>, constant_rate: 'Optional[float]' = None, rate_function: 'Option-
al[Callable[[float], float]]' = None )
```

Bases: object

Parameters

- **reactants** (*List[ReactionParticipant]*)
- **products** (*List[ReactionParticipant]*)
- **rate_fits** (*List[RateFit]*)
- **tabular_rate** (*TabularRate | None*)
- **q_value** (*float*)
- **source** (*str*)
- **label** (*str*)
- **metadata** (*Dict[str, str]*)
- **constant_rate** (*float | None*)
- **rate_function** (*Callable[[float], float] | None*)

reactants: *List[ReactionParticipant]*

products: *List[ReactionParticipant]*

rate_fits: *List[RateFit]*

tabular_rate: *TabularRate | None = None*

q_value: *float = 0.0*

source: *str = ''*

label: *str = ''*

metadata: *Dict[str, str]*

constant_rate: *float | None = None*

rate_function: *Callable[[float], float] | None = None*

Optional $f(t_9) \rightarrow$ rate evaluated exactly at the requested temperature. It is used for rates that are computed rather than fitted or tabulated, such as the detailed-balance reverse rates built by `nucnetpy.consistent_reverse_network()`, whose steep exponential temperature dependence is poorly captured by interpolation. A callable cannot be written to XML, so a network containing one does not round-trip; tabulate the rate instead when persistence is required.

classmethod from_names (*reactants, products, **kwargs*)

Parameters

- **reactants** (*Sequence[str]*)
- **products** (*Sequence[str]*)

Return type *Reaction*

property key: *Tuple[Tuple[Tuple[str, int], ...], Tuple[Tuple[str, int], ...]]*

property string: `str`

property latex: `str`

property nuclear_reactants: `List[ReactionParticipant]`

Reactants that carry baryon number.

Photons and leptons are dropped: a photodisintegration such as $\text{si28} + \gamma \rightarrow \text{mg24} + \text{he4}$ is a one-body process whose rate already contains the photon density, so including γ in the abundance product would multiply every such flow by $Y(\gamma) = 0$ and would raise the density power by one.

property reactant_order: `int`

bare_rate (*t9*, *rho*=1.0, *ye*=None)

Parameters

- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float* | *None*)

Return type `float`

rate (*t9*, *rho*=1.0, *ye*=None, *screening*=None)

Parameters

- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float* | *None*)
- **screening** (*Callable*[[*Reaction*, *float*, *float*, *float* | *None*], *float*] | *None*)

Return type `float`

statistical_factor ()

Return type `int`

flux (*abundances*, *t9*, *rho*=1.0, *screening*=None, *ye*=None)

Parameters

- **abundances** (*Mapping*[*str*, *float*])
- **t9** (*float*)
- **rho** (*float*)
- **screening** (*Callable*[[*Reaction*, *float*, *float*, *float* | *None*], *float*] | *None*)
- **ye** (*float* | *None*)

Return type `float`

stoichiometry ()

Return type *Dict*[*str*, *int*]

conserves_a_z (*species_map*)

Parameters **species_map** (*Mapping*[*str*, *Species*])

Return type *Tuple*[*bool*, *int*, *int*]

```
class nucnetpy.reactions.ReactionNetwork ( reactions: 'List[Reaction]' =
<factory> )
    Bases: object

    Parameters reactions (List[Reaction])

    reactions: List[Reaction]

    add ( reaction )
        Parameters reaction (Reaction)
        Return type None

    extend ( reactions )
        Parameters reactions (Iterable[Reaction])
        Return type None

    remove_duplicates ( )
        Return type ReactionNetwork

    invalid_reactions ( species_map )
        Parameters species_map (Mapping[str, Species])
        Return type List[Reaction]

    filter_valid ( species_map )
        Parameters species_map (Mapping[str, Species])
        Return type ReactionNetwork

    rates ( t9, rho=1.0 )
        Parameters
            • t9 (float)
            • rho (float)

        Return type Dict[str, float]

    flows ( abundances, t9, rho=1.0, screening=None, ye=None )
        Parameters
            • abundances (Mapping[str, float])
            • t9 (float)
            • rho (float)
            • screening (Callable[[Reaction, float, float, float |
                None], float] | None)
            • ye (float | None)

        Return type Dict[str, float]

    ydot ( abundances, t9, rho=1.0, screening=None, ye=None )
        Parameters
            • abundances (Mapping[str, float])
            • t9 (float)
            • rho (float)
            • screening (Callable[[Reaction, float, float, float |
                None], float] | None)
            • ye (float | None)
```

Return type *Dict*[str, float]

species_names ()

Return type *List*[str]

```
class nucnetpy.reactions.DetailedBalanceOptions ( t9, rho, ye,
equilibrium_ratio=1.0 )
```

Bases: object

Options for estimating reverse rates from forward rates.

Exact NucNet matching requires identical masses, partition functions, and Coulomb corrections. This helper provides a practical replacement hook.

Parameters

- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)
- **equilibrium_ratio** (*float*)

t9: float

rho: float

ye: float

equilibrium_ratio: float = 1.0

```
nucnetpy.reactions.reverse_rate_from_detailed_balance ( forward_rate,
equilibrium_ratio )
```

Return reverse rate using $\lambda_{\text{rev}} = \lambda_{\text{fwd}} / K_{\text{eq}}$.

Parameters

- **forward_rate** (*float*)
- **equilibrium_ratio** (*float*)

Return type float

```
nucnetpy.reactions.read_reaclib_text ( text )
```

Read a small ReacLib-like text block.

This parser accepts common two-line ReacLib records and a compact one-line form: reactants -> products ; a0 ... a6. It is intentionally permissive for migration from C++ examples and hand-written test networks.

Parameters **text** (*str*)

Return type *ReactionNetwork*

6.2 Evolution

One-zone and multi-zone evolution tools.

This layer implements the standard stoichiometric ODE interface and provides fixed-step, SciPy BDF/Radau/LSODA, optional sparse Jacobians, positivity projection, screening hooks, and weak-rate source terms.

```
nucnetpy.solver.constant_thermo ( t9=1.0, rho=1.0 )
```

Parameters

- **t9** (*float*)
- **rho** (*float*)

Return type *Callable*[[float, Mapping[str, float]], Tuple[float, float]]

nucnetpy.solver.**zone_thermo** (zone)

Parameters zone (*Zone*)

Return type *Callable*[[float, Mapping[str, float]], Tuple[float, float]]

nucnetpy.solver.**time_grid** (t0, t1, n, log=False)

Parameters • t0 (*float*)

• t1 (*float*)

• n (*int*)

• log (*bool*)

Return type *ndarray*

```
class nucnetpy.solver.EvolutionResult ( time: 'np.ndarray', species:
'List[str]', y: 'np.ndarray', success: 'bool' = True, message: 'str' = '',
nfev: 'int' = 0, njev: 'int' = 0 )
```

Bases: object

Parameters • time (*ndarray*)

• species (*List*[str])

• y (*ndarray*)

• success (*bool*)

• message (*str*)

• nfev (*int*)

• njev (*int*)

time: ndarray

species: List[str]

y: ndarray

success: bool = True

message: str = ''

nfev: int = 0

njev: int = 0

property final_abundances: Dict[str, float]

zone ()

Return type *Zone*

mass_fraction_history (species_map=None)

Return type *ndarray*

nucnetpy.solver.**rhs** (network, species, thermo, screening=None,
weak_rates=None)

Parameters • network (*Network*)

- **species** (*Sequence[str]*)
- **thermo** (*Callable[[float, Mapping[str, float]], Tuple[float, float]]*)
- **screening** (*Callable[[object, float, float, float | None], float] | None*)
- **weak_rates** (*Sequence[object] | None*)

`nucnetpy.solver.jacobian` (*network*, *species*, *thermo*, *screening=None*, *weak_rates=None*, *eps=1e-08*, *sparse=False*)

- Parameters**
- **network** (*Network*)
 - **species** (*Sequence[str]*)
 - **thermo** (*Callable[[float, Mapping[str, float]], Tuple[float, float]]*)
 - **screening** (*Callable[[object, float, float, float | None], float] | None*)
 - **weak_rates** (*Sequence[object] | None*)
 - **eps** (*float*)
 - **sparse** (*bool*)

`nucnetpy.solver.analytic_jacobian` (*network*, *species*, *thermo*, *screening=None*, *weak_rates=None*, *sparse=True*)

Return an analytic Jacobian of the stoichiometric right-hand side.

Differentiating the flow of Eq. (flow),

$$F_r = (\lambda_r \rho^{(n_r-1)} / \prod_i m_{ir}!) \prod_i Y_i^{m_{ir}},$$

with respect to a reactant abundance gives

$$dF_r/dY_j = m_{jr} Y_j^{m_{jr}-1} (\lambda_r \rho^{(n_r-1)} / \prod_i m_{ir}!) \prod_{i \neq j} Y_i^{m_{ir}},$$

so that $J_{ij} = \sum_r \nu_{ir} dF_r/dY_j$. The partial product is formed explicitly rather than as $F_r m_{jr} / Y_j$ so that the derivative stays correct when Y_j vanishes, which is the usual state of most species at the start of a calculation.

The whole matrix costs one sweep over the reaction list, whereas the finite-difference Jacobian of `jacobian()` costs $N+1$ evaluations of the full right-hand side. The saving therefore grows linearly with the number of evolved species.

`lambda_r` is treated as independent of composition. With a screening function or weak-rate tables that depend on Y_e the result is an approximate Jacobian: it changes the Newton convergence rate of an implicit solver but not the solution it converges to.

- Parameters**
- **network** (*Network*)
 - **species** (*Sequence[str]*)
 - **thermo** (*Callable[[float, Mapping[str, float]], Tuple[float, float]]*)
 - **screening** (*Callable[[object, float, float, float | None], float] | None*)
 - **weak_rates** (*Sequence[object] | None*)
 - **sparse** (*bool*)

`nucnetpy.solver.jacobian_sparsity` (*network*, *species*)

- Parameters**
- **network** (*Network*)

- **species** (*Sequence[str]*)

```
nucnetpy.solver.evolve_zone ( network, zone, times, thermo=None,
method='bdf', species=None, screening=None, weak_rates=None, rtol=1e-06,
atol=1e-30, use_jacobian=True, project_positive=True, jac_mode='analytic' )
```

Evolve one zone over times.

`jac_mode` selects how the Jacobian is supplied to the implicit SciPy solvers. "analytic" (the default) uses `analytic_jacobian()`, which differentiates the stoichiometric flows in closed form and costs one sweep over the reaction list. "numerical" uses the finite-difference `jacobian()`, costing $N+1$ right-hand-side evaluations. "sparsity" supplies no Jacobian and instead passes the stoichiometric sparsity pattern so that SciPy estimates the matrix by grouped finite differences.

Note that SciPy applies `jac_sparsity` only when no Jacobian callable is given, so the pattern and an explicit Jacobian are alternatives rather than complements.

Parameters

- **network** (*Network*)
- **zone** (*Zone*)
- **times** (*Sequence[float]*)
- **thermo** (*Callable[[float, Mapping[str, float]], Tuple[float, float]] | None*)
- **method** (*str*)
- **species** (*Sequence[str] | None*)
- **screening** (*Callable[[object, float, float, float] | None], float] | None*)
- **weak_rates** (*Sequence[object] | None*)
- **rtol** (*float*)
- **atol** (*float*)
- **use_jacobian** (*bool*)
- **project_positive** (*bool*)
- **jac_mode** (*str*)

Return type *EvolutionResult*

```
nucnetpy.solver.evolve_network_zones ( network, times, thermo=None,
method='bdf', **kwargs )
```

Parameters

- **network** (*Network*)
- **times** (*Sequence[float]*)
- **thermo** (*Callable[[float, Mapping[str, float]], Tuple[float, float]] | None*)
- **method** (*str*)

Return type *List[EvolutionResult]*

6.3 Equilibrium

Nuclear statistical equilibrium (NSE) and equilibrium helpers.

This module is a pure-Python counterpart to the most commonly used libnuceq workflows. It solves for chemical potentials that reproduce a requested ρ_0 , T_9 and Y_e and then returns NSE abundances

for the species that are present in a `nucnetpy.Network`.

The formulas are intentionally transparent and unit-aware. They are suitable for replacement workflows and regression testing, but exact equality with a specific compiled libnuceq build should be checked with the same nuclear masses, partition functions, Coulomb corrections, and numerical tolerances.

```
nucnetpy.nse.nse_prefactor ( sp, t9, rho, include_partition=True )
```

Return the NSE abundance prefactor excluding proton/neutron potentials.

The abundance is represented as $Y_i = \text{prefactor}_i * \exp(Z_i \mu_p / kT + N_i \mu_n / kT)$ where μ_p and μ_n are solved dimensionless chemical potential parameters in the internal solver. The mass excess term is included with the sign convention common in NSE abundance formulas.

Parameters

- **sp** (*Species*)
- **t9** (*float*)
- **rho** (*float*)
- **include_partition** (*bool*)

Return type float

```
class nucnetpy.nse.NSEResult ( t9: 'float', rho: 'float', ye: 'float', mu_p:
'float', mu_n: 'float', abundances: 'Dict[str, float]', success: 'bool',
message: 'str' = '' )
```

Bases: object

Parameters

- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)
- **mu_p** (*float*)
- **mu_n** (*float*)
- **abundances** (*Dict[str, float]*)
- **success** (*bool*)
- **message** (*str*)

t9: float

rho: float

ye: float

mu_p: float

mu_n: float

abundances: Dict[str, float]

success: bool

message: str = ''

zone ()

Return type *Zone*

property xsum: float

property computed_ye: float

```
nucnetpy.nse.solve_nse ( network, t9, rho, ye, species=None,
include_partition=True, tol=1e-08, max_iter=200, nse_correction=None,
require_nuclear_data=True )
```

Solve an NSE composition for a network.

The constraints are $\sum(A_i Y_i)=1$ and $\sum(Z_i Y_i)=Y_e$. The solve is performed on the well-scaled residuals $\log(\sum A_i Y_i)$ and $\sum(Z_i Y_i)/\sum(A_i Y_i) - Y_e$ using a numerically stable log-sum-exp, which keeps the iron-peak prefactors representable. A Levenberg–Marquardt least-squares solve is used when SciPy is available; otherwise an internal damped LM iteration is used. Several starting points are tried so the solve is robust across temperature/density regimes.

`nse_correction` is an optional callable (`species, t9, rho, ye`) $\rightarrow$ `f_corr` added to each species' NSE exponent, the libnucnet NSE correction factor hook. Pass `nucnetpy.coulomb.nse_correction()` for the Bravo & Garcia-Senz Coulomb correction.

Parameters

- **network** (*Network*)
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)
- **species** (*Sequence[str] | None*)
- **include_partition** (*bool*)
- **tol** (*float*)
- **max_iter** (*int*)
- **require_nuclear_data** (*bool*)

Return type *NSEResult*

```
nucnetpy.nse.equilibrium_ratio ( reaction, network, t9, rho, ye )
```

Return product/reactant NSE abundance ratio for a reaction.

Parameters

- **network** (*Network*)
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type float

Quasi-statistical equilibrium (QSE) with constrained clusters.

A pure-Python port of the libnuceq cluster workflow used by the NucNet Tools examples (`examples/analysis/compare_equil.cpp`) and the blog posts on cluster flows, (n,gamma)-(gamma,n) equilibrium, and comparing network calculations to equilibrium.

In libnuceq an equilibrium *cluster* is a subset of species (selected by an XPath expression such as `[z >= 6]`) whose total abundance is constrained to a prescribed value. Each cluster gets one extra chemical-potential multiplier `lambda_c` on top of the global proton/neutron potentials:

$$Y_i = \text{pref}_i * \exp(Z_i \mu_p + N_i \mu_n + \text{lambda_c}(i))$$

subject to $\sum A_i Y_i = 1$, $\sum Z_i Y_i = Y_e$, and $\sum_{i \text{ in } c} Y_i = Y_c$ for every cluster *c*. Full NSE is the special case with no clusters; an (n,gamma)-(gamma,n) r-process equilibrium is one cluster holding all heavy nuclei with `Y_c` equal to the current heavy-nuclei abundance.

Cluster membership is by species name; use `nucnetpy.network_limiter.select_species()` for XPath-like Z/A selection.

```

class nucnetpy.qse.QSECluster ( species, constraint, label='' )
    Bases: object
    A constrained equilibrium cluster: species names and their total Y.
    Parameters
        • species (Sequence[str])
        • constraint (float)
        • label (str)

    species: Sequence[str]

    constraint: float

    label: str = ''

class nucnetpy.qse.QSEResult ( t9: 'float', rho: 'float', ye: 'float', mu_p:
'float', mu_n: 'float', lambdas: 'List[float]', abundances: 'Dict[str, float]',
success: 'bool', message: 'str' = '' )
    Bases: object
    Parameters
        • t9 (float)
        • rho (float)
        • ye (float)
        • mu_p (float)
        • mu_n (float)
        • lambdas (List[float])
        • abundances (Dict[str, float])
        • success (bool)
        • message (str)

    t9: float

    rho: float

    ye: float

    mu_p: float

    mu_n: float

    lambdas: List[float]

    abundances: Dict[str, float]

    success: bool

    message: str = ''

    zone ( )
        Return type Zone

    property xsum: float

    property computed_ye: float

```

```
nucnetpy.qse.solve_qse ( network, t9, rho, ye, clusters, species=None,
include_partition=True, nse_correction=None, tol=1e-08, max_iter=300 )
```

Solve a constrained (QSE) equilibrium for a network.

`clusters` is a sequence of `QSECluster`; species not in any cluster follow unconstrained NSE. A species may belong to at most one cluster. With `clusters=[]` the result equals `solve_nse()`.

Parameters

- **network** (`Network`)
- **t9** (`float`)
- **rho** (`float`)
- **ye** (`float`)
- **clusters** (`Sequence[QSECluster]`)
- **species** (`Sequence[str] | None`)
- **include_partition** (`bool`)
- **tol** (`float`)
- **max_iter** (`int`)

Return type `QSEResult`

```
nucnetpy.qse.cluster_abundance ( abundances, cluster_species )
```

Return `Y_c`, the summed abundance of the cluster members.

Parameters

- **abundances** (`Mapping[str, float]`)
- **cluster_species** (`Sequence[str]`)

Return type `float`

```
nucnetpy.qse.cluster_ydot ( network, abundances, cluster_species, t9,
rho=1.0, use_reverse=False )
```

Return per-reaction contributions to dY_c/dt for a cluster.

Each reaction contributes $\text{flux} * (\text{net change in cluster member count})$; reactions that only shuffle abundance inside the cluster contribute nothing (blog: “Calculating cluster flows”, C++ `compute_Ycdot`). With `use_reverse=True` the net (forward minus detailed-balance reverse) flux is used. `sum(result.values())` is dY_c/dt .

Parameters

- **network** (`Network`)
- **abundances** (`Mapping[str, float]`)
- **cluster_species** (`Sequence[str]`)
- **t9** (`float`)
- **rho** (`float`)
- **use_reverse** (`bool`)

Return type `Dict[str, float]`

Coulomb (plasma) corrections to NSE, ported from NucNet Tools.

This is a direct port of `user/nse_corr.cpp` (r647): the Coulomb correction of Bravo & Garcia-Senz (MNRAS 307, 984, 1999) with the fit constants of Ogata & Ichimaru (Phys. Rev. A 36, 5451, 1987) and the one-component-plasma value $f(\Gamma=1)/kT = -0.420$ of Slattery, Doolen & DeWitt (1980).

The species Coulomb chemical potential per kT is

$$\begin{aligned} \Gamma_i > 1: \mu_C/kT &= a + 4b \Gamma^{1/4} - 4c \Gamma^{-1/4} + d \ln \Gamma - o \\ \Gamma_i \leq 1: \mu_C/kT &= (\beta/\Gamma) \Gamma^\gamma - \Gamma^{3/2}/\sqrt{3} \end{aligned}$$

with $G = \Gamma_i = Z^{(5/3)} \Gamma_e$ and the two branches matched in value and first derivative at $\Gamma_i = 1$. $\Gamma_e = e^2 / (a_e k T)$ uses the electron-cloud radius $a_e = (4 \pi \rho N_A Y_e / 3)^{(-1/3)}$.

The NSE correction factor is $f_{\text{corr}} = -\mu_C/kT$ (libnucnet convention): it is added to the exponent of the NSE abundance of each species and to the equilibrium constants used for detailed-balance reverse rates.

`nucnetpy.coulomb.gamma_e ( t9, rho, ye )`

Return the electron Coulomb coupling parameter Γ_e .

Parameters

- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type float

`nucnetpy.coulomb.species_coulomb_chemical_potential ( z, t9, rho, ye )`

Return μ_C/kT for a species of charge z (0 for neutrons).

Parameters

- **z** (*int*)
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type float

`nucnetpy.coulomb.species_coulomb_energy ( z, t9, rho, ye )`

Return the species Coulomb energy per particle in units of kT.

Parameters

- **z** (*int*)
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type float

`nucnetpy.coulomb.species_coulomb_entropy ( z, t9, rho, ye )`

Return the species Coulomb entropy per particle in units of k_B .

Parameters

- **z** (*int*)
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type float

`nucnetpy.coulomb.nse_correction ( species, t9, rho, ye )`

Return the NSE correction factor $f_{\text{corr}} = -\mu_C/kT$ for a species.

Signature-compatible with the `nse_correction` hooks accepted by `nucnetpy.nse.solve_nse()` and the detailed-balance helpers: pass this function (or your own with the same signature) to enable Coulomb corrections.

Parameters

- **t9** (*float*)
- **rho** (*float*)

- **ye** (*float*)

Return type float

`nucnetpy.coulomb.coulomb_entropy_per_nucleon ( abundances, species_map, t9, rho, ye )`

Return the total Coulomb entropy per nucleon in units of k_B .

$\sum_i Y_i * s_C(Z_i)$ — the plasma part of the entropy used in the blog workflow “Computing NSE corrections to the entropy”.

- Parameters**
- **t9** (*float*)
 - **rho** (*float*)
 - **ye** (*float*)

Return type float

6.4 Detailed balance

Reverse reaction rates from detailed balance.

This replaces the libnucnet behaviour of computing reverse rates from the forward rate, nuclear masses, and partition functions (blog workflows “Comparing forward and reverse reaction rates”, “Computing reaction flows”, and the (n,gamma)-(gamma,n) equilibrium studies).

For a reaction $\sum_r \nu_r R \rightarrow \sum_p \nu_p P$ that conserves Z and A , the equilibrium abundance ratio follows from the same Saha prefactors used by the NSE solver: $\ln K = \sum_p \nu_p \ln(\text{pref}_p) - \sum_r \nu_r \ln(\text{pref}_r)$ where $Y_i^{\text{eq}} = \text{pref}_i * \exp(Z_i \mu_p + N_i \mu_n)$ and the chemical-potential terms cancel for a balanced reaction. Matching forward and reverse fluxes at equilibrium gives

$$\lambda_{\text{rev}} = \lambda_{\text{fwd}} * \rho^{(n_r - n_p)} * (s_{\text{rev}} / s_{\text{fwd}}) / K$$

with n the reactant/product orders and s the duplicate-particle statistical factors. Because $\ln(\text{pref})$ contains $-\ln(\rho * N_A)$, the explicit density powers cancel and the reverse rate is a pure function of temperature, as it must be.

Photons and leptons (gamma, electron, ...) are ignored on either side, so the reverse of a radiative capture is the photodisintegration rate.

`nucnetpy.detailed_balance.log_equilibrium_constant ( reaction, species_map, t9, rho=1.0, include_partition=True )`

Return $\ln K$ with $K = \prod Y_p^{\text{eq}} / \prod Y_r^{\text{eq}}$ for the reaction.

Requires mass excesses (and optionally partition functions) on the species; the Q-value enters through the mass excesses as $\exp(Q/kT)$.

- Parameters**
- **reaction** (*Reaction*)
 - **species_map** (*Mapping[str, Species]*)
 - **t9** (*float*)
 - **rho** (*float*)
 - **include_partition** (*bool*)

Return type float

`nucnetpy.detailed_balance.reverse_rate ( reaction, species_map, t9, rho=1.0, forward=None, include_partition=True )`

Return the detailed-balance reverse rate for reaction at $t9$.

`forward` overrides the forward rate (default `reaction.rate(t9)`). The result is in the same

convention as forward rates: to obtain a flux it must be combined with $\rho^{**}(n_p - 1)$, product abundances, and the product-side statistical factor (see `net_flows()`).

Parameters

- **reaction** (*Reaction*)
- **species_map** (*Mapping[str, Species]*)
- **t9** (*float*)
- **rho** (*float*)
- **forward** (*float | None*)
- **include_partition** (*bool*)

Return type *float*

```
nucnetpy.detailed_balance.reverse_reaction ( reaction, species_map,
t9_grid=None, include_partition=True )
```

Return a Reaction for the reverse process with a tabulated rate.

The rate is sampled from `reverse_rate()` on `t9_grid` (default 30 points, $T_9 = 0.1 \dots 10$) so the reverse process — e.g. the (gamma,n) partner of an (n,gamma) capture — can be added to a network like any other reaction.

Parameters

- **reaction** (*Reaction*)
- **species_map** (*Mapping[str, Species]*)
- **t9_grid** (*Sequence[float] | None*)
- **include_partition** (*bool*)

Return type *Reaction*

```
nucnetpy.detailed_balance.consistent_reverse_network ( network,
t9_grid=None, include_partition=True, tabulate=False )
```

Return a copy of `network` whose reverse rates obey detailed balance.

Rate libraries such as JINA ReacLib supply the forward and reverse directions of a reaction as separately fitted expressions. Their ratio is therefore not exactly the equilibrium constant implied by the nuclear masses and partition functions in the accompanying nuclide file, and a network built from them relaxes to a stationary state that is not the nuclear statistical equilibrium of those same data. The discrepancy is not small: for the alpha chain at the fitted reverse rates differ from detailed balance by a median factor of 1.10, which displaces the equilibrium mass fractions by a median of 4.5 per cent.

This function pairs every reaction with its inverse, keeps the exothermic member of each pair, and regenerates the endothermic member from `reverse_rate()`. Reactions with no inverse in the network are carried over unchanged. The resulting network relaxes to the composition returned by `nucnetpy.solve_nse()` to about one part in 10^6 , so the integrator and the equilibrium solver become mutually consistent.

By default the reverse rate is attached as a callable evaluated exactly at whatever temperature the integrator asks for. This matters: the reverse rate carries a factor $\exp(-E/kT)$, which is far too steep to interpolate accurately, and tabulating it on 200 logarithmically spaced points degrades the agreement with equilibrium from one part in 10^6 to about one part in 10^4 . Pass `tabulate=True` to sample the rate on `t9_grid` instead, which is less accurate but can be written to XML.

Note that this replaces measured or evaluated reverse rates with values derived from mass differences, so it enforces thermodynamic consistency rather than improving individual rates. Where a library reverse rate is known to be better than the masses it is derived from, keep the library value instead.

Parameters

- **t9_grid** (*Sequence[float] | None*)
- **include_partition** (*bool*)
- **tabulate** (*bool*)

```
nucnetpy.detailed_balance.net_flows ( network, abundances, t9, rho=1.0,
include_partition=True )
```

Return {reaction: (forward, reverse, net)} fluxes for a network.

The forward flux follows `Reaction.flux()`; the reverse flux uses the detailed-balance rate with the product abundances. At NSE abundances the net flux of every balanced reaction vanishes.

Parameters

- **abundances** (*Mapping[str, float]*)
- **t9** (*float*)
- **rho** (*float*)
- **include_partition** (*bool*)

Return type *Dict[str, Tuple[float, float, float]]*

6.5 Screening, weak rates, decays

Electron-screening corrections for thermonuclear reaction rates.

The original NucNet Tools exposes user-defined screening callbacks. This module provides a Python callback-compatible implementation with common weak and intermediate-screening approximations. The API returns multiplicative factors applied to bare nuclear rates.

```
nucnetpy.screening.electron_number_density ( rho, ye )
```

Parameters

- **rho** (*float*)
- **ye** (*float*)

Return type *float*

```
nucnetpy.screening.debye_radius ( t9, rho, ye, ion_strength=0.0 )
```

Return Debye radius in cm.

`ion_strength` may be supplied as $\sum Z_i^2 Y_i$. If omitted, the electron term alone is used, which is the usual safe weak-screening fallback.

Parameters

- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)
- **ion_strength** (*float*)

Return type *float*

```
nucnetpy.screening.ion_strength ( abundances, species_map=None )
```

Parameters

- **abundances** (*Mapping[str, float]*)
- **species_map** (*Mapping[str, Species] | None*)

Return type *float*

```
class nucnetpy.screening.ScreeningContext ( t9: 'float', rho: 'float', ye:
'float', abundances: 'Mapping[str, float]', species_map: 'Optional[Map-
ping[str, Species]]' = None )
```

Bases: *object*

Parameters

- **t9** (*float*)
- **rho** (*float*)

- **ye** (*float*)
- **abundances** (*Mapping[str, float]*)
- **species_map** (*Mapping[str, Species] | None*)

t9: *float*

rho: *float*

ye: *float*

abundances: *Mapping[str, float]*

species_map: *Mapping[str, Species] | None = None*

property ion_strength: *float*

`nucnetpy.screening.weak_screening_factor ( z1, z2, t9, rho, ye, ion_strength_value=0.0 )`

Salpeter weak-screening enhancement factor.

The factor is $\exp(Z_1 Z_2 e^2 / (kT R_D))$. A cap prevents numerical overflow while retaining monotonic enhancement.

- Parameters**
- **z1** (*int*)
 - **z2** (*int*)
 - **t9** (*float*)
 - **rho** (*float*)
 - **ye** (*float*)
 - **ion_strength_value** (*float*)

Return type *float*

`nucnetpy.screening.graboske_intermediate_factor ( z1, z2, t9, rho, ye, ion_strength_value=0.0 )`

Smooth weak-to-intermediate approximation inspired by Graboske et al.

This is not tied to one compiled NucNet user file; it gives a stable, callback-compatible enhancement and can be replaced by a user function when exact project-specific screening is required.

- Parameters**
- **z1** (*int*)
 - **z2** (*int*)
 - **t9** (*float*)
 - **rho** (*float*)
 - **ye** (*float*)
 - **ion_strength_value** (*float*)

Return type *float*

`nucnetpy.screening.reaction_screening_factor ( reaction, context, model='weak' )`

- Parameters**
- **context** (*ScreeningContext*)
 - **model** (*str*)

Return type *float*

```
class nucnetpy.screening.SkyNetScreening ( species_map=None, max_z=110,  
pair_term=0.0 )
```

Bases: object

Screening as a Coulomb chemical potential per nuclear charge.

Instead of a pairwise enhancement factor, each charge Z is assigned a Coulomb chemical potential $\mu(Z)/kT$ in the plasma, and a reaction is enhanced by

$$\exp(\sum_{\text{reactants}} \mu(Z_i)/kT - \mu(\sum_i Z_i)/kT),$$

the difference between the potentials of the separated reactants and of the fused compound charge. This has two advantages over a pairwise factor: it extends naturally to reactions with more than two charged reactants, and because it is a chemical potential it can be applied to the forward and reverse directions consistently, so screening does not break detailed balance.

$\mu(Z)$ blends three regimes with smooth $\tanh$ switches: weak screening, $\mu_w = -Z^2 \text{zeta} \lambda_{D0} / 2$; intermediate screening, $\mu_i = -0.380 \lambda_{D0}^b \text{eta}_b Z^{(b+1)}$ with $b = 0.860$; and strong screening from a one-component-plasma fit.

The electron-positron pair contribution to zeta , which requires the electron degeneracy parameter from an equation of state, is not included. Pass `pair_term` if it is available. Neglecting it is accurate while pairs are unimportant, which covers ordinary stellar and explosive burning, but it should not be relied on where positrons are abundant.

The object is a callable suitable for the `screening` argument of `nucnetpy.evolve_zone()`. It caches $\mu(Z)$ and recomputes it in `update()`, which the network calls once per right-hand-side evaluation, so the cost does not scale with the number of reactions.

Parameters

- **species_map** (*Optional*[*Mapping*[*str*, *Species*]])
- **max_z** (*int*)
- **pair_term** (*float*)

```
update ( abundances, t9, rho, ye=None )
```

Recompute $\mu(Z)$ for this composition and thermodynamic state.

Parameters

- **abundances** (*Mapping*[*str*, *float*])
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float* | *None*)

Return type None

```
chemical_potential ( z )
```

Return $\mu(Z)/kT$ for charge z .

Parameters **z** (*int*)

Return type float

```
factor ( reaction )
```

Return the multiplicative screening enhancement of `reaction`.

Return type float

Weak-rate and neutrino helper layer.

Supports two-dimensional $T9/\rho\text{Ye}$ tables, simple FFN/Oda/Langanke-style text blocks after normalization, bilinear interpolation, and ODE source-term hooks.

```
class nucnetpy.weak.WeakRateTable ( parent: 'str', daughter: 'str', t9:  
'Sequence[float]', rho_ye: 'Sequence[float]', rates: 'np.ndarray', nu_loss:  
'Optional[np.ndarray]' = None, label: 'str' = '' )
```

Bases: object

Parameters

- **parent** (*str*)
- **daughter** (*str*)
- **t9** (*Sequence[float]*)
- **rho_ye** (*Sequence[float]*)
- **rates** (*ndarray*)
- **nu_loss** (*ndarray | None*)
- **label** (*str*)

parent: *str*

daughter: *str*

t9: *Sequence[float]*

rho_ye: *Sequence[float]*

rates: *ndarray*

nu_loss: *ndarray | None = None*

label: *str = ''*

rate (*t9, rho_ye*)

Parameters

- **t9** (*float*)
- **rho_ye** (*float*)

Return type *float*

neutrino_loss (*t9, rho_ye*)

Parameters

- **t9** (*float*)
- **rho_ye** (*float*)

Return type *float*

nucnetpy.weak.read_weak_table (*path, parent=None, daughter=None*)

Read a normalized weak-rate table.

Accepted format:

```
# parent fe56 daughter mn56
t9 rhoYe rate [nu_loss]
1.0 1e7 2.3e-4 1.0e-5
```

Repeated rows are reshaped into a rectangular T9 x rhoYe grid.

Parameters

- **path** (*str | Path*)
- **parent** (*str | None*)
- **daughter** (*str | None*)

Return type *WeakRateTable*

nucnetpy.weak.read_weak_tables (*paths*)

Parameters **paths** (*Iterable[str | Path]*)

Return type *List[WeakRateTable]*

```
nucnetpy.weak.compute_yedot ( abundances, weak_rates, species_map, t9,
rho, ye )
```

Parameters

- **abundances** (*Mapping*[*str*, *float*])
- **weak_rates** (*Sequence*[*WeakRateTable*])
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type *float*

```
nucnetpy.weak.weak_source_terms ( abundances, weak_rates, t9, rho, ye )
```

Parameters

- **abundances** (*Mapping*[*str*, *float*])
- **weak_rates** (*Sequence*[*WeakRateTable*])
- **t9** (*float*)
- **rho** (*float*)
- **ye** (*float*)

Return type *Dict*[*str*, *float*]

Nuclear decay helpers ported into Python.

```
class nucnetpy.decay.DecayRecord ( parent: 'str', daughter: 'str',
half_life: 'float', branch: 'float' = 1.0, mode: 'str' = 'decay' )
```

Bases: *object*

Parameters

- **parent** (*str*)
- **daughter** (*str*)
- **half_life** (*float*)
- **branch** (*float*)
- **mode** (*str*)

parent: *str*

daughter: *str*

half_life: *float*

branch: *float* = 1.0

mode: *str* = 'decay'

property rate: *float*

reaction ()

Return type *Reaction*

```
nucnetpy.decay.add_decay_records ( network, records )
```

Parameters **records** (*Iterable*[*DecayRecord*])

Return type *None*

```
nucnetpy.decay.decay_constant_from_half_life ( half_life )
```

Parameters `half_life` (*float*)

Return type *float*

```
nucnetpy.decay.fission_reaction ( parent, fragments, neutrons=0, rate=0.0,
mode='sf' )
```

Return a fission reaction parent → fragments + neutrons * n.

rate is the fission decay constant in 1/s (use `decay_constant_from_half_life()` for spontaneous-fission half-lives). mode labels the channel, e.g. "sf" (spontaneous) or "bdf" (beta-delayed); for neutron-induced fission build a normal two-reactant Reaction instead. Blog workflow: "Adding fission to an r-process calculation".

Parameters

- `parent` (*str*)
- `fragments` (*Iterable[str]*)
- `neutrons` (*int*)
- `rate` (*float*)
- `mode` (*str*)

Return type *Reaction*

Neutrino reaction-rate helper functions.

```
class nucnetpy.neutrino.NeutrinoLuminosity ( l0: 'float', tau: 'float |
None' = None )
```

Bases: *object*

Parameters

- `l0` (*float*)
- `tau` (*float | None*)

`l0`: *float*

`tau`: *float | None = None*

```
luminosity ( t )
```

Parameters `t` (*float*)

Return type *float*

```
class nucnetpy.neutrino.NeutrinoQuantity ( temperature: 'Sequence[float]',
log10_xsec: 'Sequence[float]' )
```

Bases: *object*

Parameters

- `temperature` (*Sequence[float]*)
- `log10_xsec` (*Sequence[float]*)

`temperature`: *Sequence[float]*

`log10_xsec`: *Sequence[float]*

```
cross_section ( tnu )
```

Parameters `tnu` (*float*)

Return type *float*

```
nucnetpy.neutrino.geometric_flux_rate ( luminosity, mean_energy_mev,  
radius_cm, cross_section_cm2 )
```

Parameters

- **luminosity** (*float*)
- **mean_energy_mev** (*float*)
- **radius_cm** (*float*)
- **cross_section_cm2** (*float*)

Return type *float*

6.6 Analysis

Analysis helpers equivalent to common NucNet Tools example programs.

```
nucnetpy.analysis.largest_mass_fractions ( zone, species_map, n=10,  
min_x=0.0 )
```

Parameters

- **zone** (*Zone*)
- **species_map** (*Mapping[str, Species]*)
- **n** (*int*)
- **min_x** (*float*)

```
nucnetpy.analysis.abundances_for_element ( zone, element, species_map )
```

Parameters

- **zone** (*Zone*)
- **element** (*str*)
- **species_map** (*Mapping[str, Species]*)

Return type *Dict[str, float]*

```
nucnetpy.analysis.abundances_vs_nucleon_number ( zone, species_map )
```

Parameters

- **zone** (*Zone*)
- **species_map** (*Mapping[str, Species]*)

Return type *Dict[int, float]*

```
nucnetpy.analysis.element_abundances ( zone, species_map )
```

Parameters

- **zone** (*Zone*)
- **species_map** (*Mapping[str, Species]*)

Return type *Dict[str, float]*

```
nucnetpy.analysis.abundance_moment ( zone, species_map, moment=1, kind='a'  
)
```

Parameters

- **zone** (*Zone*)
- **species_map** (*Mapping[str, Species]*)
- **moment** (*int*)
- **kind** (*str*)

Return type float

`nucnetpy.analysis.species_history ( network, species )`

Parameters

- **network** (*Network*)
- **species** (*str*)

Return type *List[Tuple[int, Tuple[str, str, str], float]]*

`nucnetpy.analysis.flows ( network, zone_index=0, t9=None, rho=None )`

Parameters

- **network** (*Network*)
- **zone_index** (*int*)
- **t9** (*float | None*)
- **rho** (*float | None*)

`nucnetpy.analysis.ydot ( network, zone_index=0, t9=None, rho=None )`

Parameters

- **network** (*Network*)
- **zone_index** (*int*)
- **t9** (*float | None*)
- **rho** (*float | None*)

`nucnetpy.analysis.energy_generation_rate ( network, zone_index=0, t9=None, rho=None )`

Parameters

- **network** (*Network*)
- **zone_index** (*int*)
- **t9** (*float | None*)
- **rho** (*float | None*)

Return type float

`nucnetpy.analysis.compare_rates ( net_a, net_b, t9, rho=1.0 )`

Parameters

- **net_a** (*Network*)
- **net_b** (*Network*)
- **t9** (*float*)
- **rho** (*float*)

Return type *List[Tuple[str, float, float, float]]*

`nucnetpy.analysis.separation_energy ( species_name, species_map, particle='n' )`

Return S_n or S_p in MeV, or None if the needed nuclides are absent.

$S_n(Z, A) = ME(Z, A-1) + ME(n) - ME(Z, A)$ and $S_p(Z, A) = ME(Z-1, A-1) + ME(p) - ME(Z, A)$.

Parameters

- **species_name** (*str*)
- **species_map** (*Mapping[str, Species]*)
- **particle** (*str*)

Return type float | None

`nucnetpy.analysis.charge_changing_flows ( network, zone_index=0, t9=None, rho=None )`

Return each reaction's contribution to dY_e/dt (flux times net ΔZ).

Only reactions with a nonzero nuclear charge change (weak reactions such as beta decays and electron captures) appear in the result; strong reactions conserve Z and contribute nothing. `sum(result.values())` is dY_e/dt .

Parameters

- **network** (*Network*)
- **zone_index** (*int*)
- **t9** (*float | None*)
- **rho** (*float | None*)

Return type *Dict[str, float]*

`nucnetpy.analysis.system_timescales ( network, zone_index=0, t9=None, rho=None )`

Return per-species timescales $Y / |dY/dt|$ in seconds.

Species with zero derivative get `inf`. The shortest timescales identify the stiffest components of the system (blog: "Computing system timescales").

Parameters

- **network** (*Network*)
- **zone_index** (*int*)
- **t9** (*float | None*)
- **rho** (*float | None*)

Return type *Dict[str, float]*

`nucnetpy.analysis.heavy_nuclei_abundance ( zone, species_map, zmin=3 )`

Return Y_h , the total abundance of nuclei with $Z \geq zmin$.

The photon-to-heavy-nucleus ratio and the r-process neutron-to-seed ratio are built from this quantity (blog: "Computing the number of heavy nuclei").

Parameters

- **zone** (*Zone*)
- **species_map** (*Mapping[str, Species]*)
- **zmin** (*int*)

Return type *float*

`nucnetpy.analysis.neutron_exposure ( result, thermo )`

Return the s-process neutron exposure $\tau = \int n_n v_T dt$ in mb^{-1} .

`result` is an *EvolutionResult* whose species include the neutron; `thermo` is the same (`t`, abundances) $\rightarrow$ (`t9`, `rho`) function used for the evolution. $n_n = \rho N_A Y_n$ and the thermal velocity is $v_T = \sqrt{2 k T / m_n}$ (blog: "Computing the s-process neutron exposure").

Return type *float*

`nucnetpy.analysis.reaction_entropy_changes ( network, abundances, t9, rho )`

Return per-reaction entropy change ΔS in units of k_B per reaction.

$\Delta S = -\sum_i \nu_i \mu_i/kT$ with Maxwell-Boltzmann chemical potentials $\mu_i/kT = \ln Y_i - \ln \text{pref}_i$; this equals the C++ per-reaction $Q/kT + \sum_r \ln(Y/Y_Q) - \sum_p \ln(Y/Y_Q)$ of NucNet Tools `flow_utilities.cpp` and, under detailed balance, $\ln(f/r)$.

Parameters

- **network** (*Network*)

- **abundances** (*Mapping[str, float]*)
- **t9** (*float*)
- **rho** (*float*)

Return type *Dict[str, float]*

`nucnetpy.analysis.entropy_generation_rate ( network, zone_index=0, t9=None, rho=None, use_reverse=True )`

Return dS/dt per nucleon in units of k_B per second.

Ports NucNet Tools `compute_entropy_generation_rate`: the sum over reactions of $(f - r) * \Delta S$ with r the detailed-balance reverse flux and $\Delta S = \ln(f/r)$ per reaction, so every term is non-negative and the total vanishes at NSE (blog series “Computing the entropy generation rate”). With `use_reverse=False` only forward fluxes are used ($dS/dt = -\sum_i (\mu_i/kT) dY_i/dt$). Electron/neutrino chemical potential terms of the C++ version are not included; nucnetpy networks carry weak reactions with their own tabulated rates instead.

Parameters

- **network** (*Network*)
- **zone_index** (*int*)
- **t9** (*float | None*)
- **rho** (*float | None*)
- **use_reverse** (*bool*)

Return type *float*

`nucnetpy.analysis.integrated_currents ( network, result, thermo, use_reverse=True )`

Return per-reaction time-integrated net currents over an evolution.

Ports NucNet Tools `update_flow_currents`: for each reaction the current accumulates $(\text{forward} - \text{reverse}) * dt$ across the time grid of `result` (an *EvolutionResult*), integrated here with the trapezoidal rule. The integrated current of a reaction is the net number of transitions per nucleon it produced over the calculation (blog: “Creating integrated currents diagrams”, “Analyzing integrated currents quantitatively”).

Parameters

- **network** (*Network*)
- **use_reverse** (*bool*)

Return type *Dict[str, float]*

`nucnetpy.analysis.nuclear_energy_generation_rate ( network, zone_index=0, t9=None, rho=None, screening=None, abundances=None, ydot_values=None )`

Return the nuclear energy generation rate in erg per gram per second.

The rate follows from the change in total mass excess of the composition,

$$\text{eps} = -N_A \sum_i (dY_i/dt) * \Delta M_i,$$

with ΔM_i the mass excess in MeV. This is exact, and it is preferable to summing Q_r times the flow of each reaction for two reasons. It needs no Q -values, so it cannot disagree with them where a rate library and a nuclide file are inconsistent, and it uses the same mass excesses as the equilibrium solver, so energy release and equilibrium are guaranteed to be built from one set of nuclear data.

A positive value denotes energy released to the plasma. Neutrino losses are not subtracted: energy carried away by neutrinos from weak reactions must be accounted for separately.

`abundances` and `ydot_values` override the zone composition and its derivative, which is useful when the rate is wanted along a trajectory that has already been integrated.

Parameters

- **network** (*Network*)
- **zone_index** (*int*)

- **t9** (*float* | *None*)
- **rho** (*float* | *None*)
- **abundances** (*Mapping[str, float]* | *None*)
- **ydot_values** (*Mapping[str, float]* | *None*)

Return type *float*

`nucnetpy.analysis.nuclear_energy_release ( network, initial, final )`

Return the energy released between two compositions, in erg per gram.

This is the time integral of `nuclear_energy_generation_rate()` and depends only on the endpoints, being the difference in total mass excess.

Parameters

- **network** (*Network*)
- **initial** (*Mapping[str, float]*)
- **final** (*Mapping[str, float]*)

Return type *float*

6.7 Input and output

Fast, permissive NucNet/JINA/libnucnet XML reader and writer.

This module is tuned for real JINA XML databases, where files may contain thousands of nuclides and tens of thousands of reactions. It supports:

- separate `<nuclear_data>` and `<reaction_data>` files,
- combined `<libnucnet_input>` output files,
- zone files with mass fractions or abundances,
- ReacLib/JINA `non_smoker_fit` blocks with a1-a7 coefficients,
- single-rate beta-decay style records,
- partition-function tables.

`nucnetpy.io.xml.read_xml ( path )`

Parameters **path** (*str* | *Path*)

Return type *Network*

`nucnetpy.io.xml.read_network_xml ( path )`

Parameters **path** (*str* | *Path*)

Return type *Network*

`nucnetpy.io.xml.read_xml_root ( root, source='<xml-root>' )`

Parameters **source** (*str*)

Return type *Network*

`nucnetpy.io.xml.write_xml ( network, path )`

Parameters

- **network** (*Network*)
- **path** (*str* | *Path*)

Return type *None*

```
nucnetpy.io.xml.write_zone_xml ( network, path )
```

Parameters

- **network** (*Network*)
- **path** (*str* | *Path*)

Return type *None*

```
nucnetpy.io.xml.read_xml_string ( text )
```

Parameters **text** (*str*)

Return type *Network*

JINA/libnucnet XML database helpers.

The original NucNet Tools workflow usually reads nuclide data and reaction data from JINA ReacLib /libnucnet XML files. These helpers keep that workflow in the pure-Python port: one file may contain nuclides, another may contain reactions, and both can be merged into one `nucnetpy.core.Network` object.

```
nucnetpy.io.jina.read_jina_xml ( nuclides_xml, reactions_xml,
zones_xml=None )
```

Read separate JINA/libnucnet nuclide and reaction XML files.

Parameters

- **nuclides_xml** (*str* | *Path*) – XML file containing <nuclide> records with Z, A, mass excess, spin, and optional partition-function data.
- **reactions_xml** (*str* | *Path*) – XML file containing <reaction> records and ReacLib rate fits.
- **zones_xml** (*str* | *Path* | *None*) – Optional XML file containing zones /abundances. If omitted, the returned network contains species and reactions but no zones.

Returns A single Python network object with species, reactions, and optionally zones.

Return type *Network*

```
nucnetpy.io.jina.combine_jina_xml ( nuclides_xml, reactions_xml,
output_xml, zones_xml=None )
```

Read separate JINA XML files and write one combined nucnetpy XML file.

Parameters

- **nuclides_xml** (*str* | *Path*)
- **reactions_xml** (*str* | *Path*)
- **output_xml** (*str* | *Path*)
- **zones_xml** (*str* | *Path* | *None*)

Return type *Network*

```
nucnetpy.io.jina.jina_database_summary ( net_or_nuclides,
reactions_xml=None, zones_xml=None )
```

Return a compact summary of a loaded JINA database.

Accepts either an already loaded *Network*, or file paths (`nuclides_xml`, `reactions_xml` [, `zones_xml`]).

Return type `dict[str, int]`

6.8 Utilities

Network limiting utilities for reduced-network calculations.

```
nucnetpy.network_limiter.select_species ( network, zmin=None, zmax=None,
amin=None, amax=None, elements=None )
```

Return species names matching Z/A ranges and/or element symbols.

A pure-Python replacement for the libnucnet nuclide XPath selections used in the blog workflows “Selecting an input network” and “Applying a nuclide XPath expression”. Combine with `limit_network()`:

```
limit_network(net, select_species(net, zmin=1, zmax=28, amax=60))
```

Parameters

- **zmin** (*int* | *None*)
- **zmax** (*int* | *None*)
- **amin** (*int* | *None*)
- **amax** (*int* | *None*)
- **elements** (*Iterable[str]* | *None*)

Return type *List[str]*

```
nucnetpy.network_limiter.limit_network ( network, species,
include_linked=False )
```

Parameters

- **species** (*Iterable[str]*)
- **include_linked** (*bool*)

Hydrodynamic trajectory utilities replacing user/hydro* helpers.

```
class nucnetpy.hydro.Trajectory ( time: 'np.ndarray', t9: 'np.ndarray',
rho: 'np.ndarray' )
```

Bases: *object*

Parameters

- **time** (*ndarray*)
- **t9** (*ndarray*)
- **rho** (*ndarray*)

time: *ndarray*

t9: *ndarray*

rho: *ndarray*

thermo (*t*, *y=None*)

Parameters **t** (*float*)

Return type *Tuple[float, float]*

```
classmethod from_columns ( time, t9, rho )
```

Parameters

- **time** (*Sequence[float]*)
- **t9** (*Sequence[float]*)
- **rho** (*Sequence[float]*)

Return type *Trajectory*

```
nucnetpy.hydro.read_trajectory ( path )
```

Parameters **path** (*str* | *Path*)

Return type *Trajectory*

```
nucnetpy.hydro.exponential_expansion ( t0, t9_0, rho_0, tau, n=200,
t_end=None )
```

Parameters

- **t0** (*float*)
- **t9_0** (*float*)
- **rho_0** (*float*)
- **tau** (*float*)
- **n** (*int*)
- **t_end** (*float* | *None*)

Return type *Trajectory*

Thermodynamic helper functions used by NucNet Tools examples.

These are practical approximations for pure-Python workflows. For exact publication comparisons, validate constants and EOS choices against the C++ libnucnet/libnuceq configuration used in the original calculation.

```
nucnetpy.thermo.ideal_gas_pressure ( rho, temperature, ytot )
```

Parameters

- **rho** (*float*)
- **temperature** (*float*)
- **ytot** (*float*)

Return type *float*

```
nucnetpy.thermo.radiation_pressure ( temperature )
```

Parameters **temperature** (*float*)

Return type *float*

```
nucnetpy.thermo.entropy_ideal_ions ( rho, temperature, ytot )
```

Parameters

- **rho** (*float*)
- **temperature** (*float*)
- **ytot** (*float*)

Return type *float*

```
nucnetpy.thermo.density_from_entropy ( entropy, temperature, ytot )
```

Parameters

- **entropy** (*float*)
- **temperature** (*float*)
- **ytot** (*float*)

Return type *float*

```
nucnetpy.thermo.temperature_from_entropy ( entropy, rho, ytot )
```

Parameters

- **entropy** (*float*)
- **rho** (*float*)
- **ytot** (*float*)

Return type *float*

```
nucnetpy.thermo.sound_speed_ideal_gamma ( rho, pressure,  
gamma=1.6666666666666667 )
```

Parameters

- **rho** (*float*)
- **pressure** (*float*)
- **gamma** (*float*)

Return type *float*

```
nucnetpy.thermo.q_energy_erg_per_g ( q_mev )
```

Parameters **q_mev** (*float*)

Return type *float*

Validation and regression utilities for replacing NucNet Tools workflows.

```
class nucnetpy.validation.ValidationIssue ( level: 'str', code: 'str',  
message: 'str' )
```

Bases: *object*

Parameters

- **level** (*str*)
- **code** (*str*)
- **message** (*str*)

level: *str*

code: *str*

message: *str*

```
nucnetpy.validation.validate_network ( network, strict=False )
```

Parameters

- **network** (*Network*)
- **strict** (*bool*)

Return type *List[ValidationIssue]*

```
nucnetpy.validation.validate_zone ( zone, network=None, atol=1e-06 )
```

Parameters

- **zone** (*Zone*)
- **network** (*Network | None*)
- **atol** (*float*)

Return type *List[ValidationIssue]*

```
nucnetpy.validation.compare_abundances ( a, b, rtol=1e-06, atol=1e-30 )
```

Parameters

- **a** (*Mapping[str, float]*)
- **b** (*Mapping[str, float]*)
- **rtol** (*float*)
- **atol** (*float*)

Return type *Dict[str, float]*

```
nucnetpy.validation.max_relative_abundance_error ( a, b, atol=1e-30 )
```

Parameters

- **a** (*Mapping[str, float]*)

- **b** (*Mapping*[*str*, *float*])
- **atol** (*float*)

Return type *float*

`nucnetpy.validation.regression_summary ( reference, candidate )`

- Parameters**
- **reference** (*Mapping*[*str*, *float*])
 - **candidate** (*Mapping*[*str*, *float*])

Return type *Dict*[*str*, *object*]

Pure-Python rate modification hooks replacing user/rate_modifiers.*.

class `nucnetpy.rate_modifiers.RateModifierRegistry` (*modifiers*: *'Dict*[*str*, *RateModifier*]*'*=<factory>)

Bases: *object*

Parameters **modifiers** (*Dict*[*str*, *Callable*[[*object*, *float*, *float*, *float* | *None*, *Mapping*[*str*, *float*]], *float*]])

modifiers: *Dict*[*str*, *Callable*[[*object*, *float*, *float*, *float* | *None*, *Mapping*[*str*, *float*]], *float*]]

register (*key*, *func*)

- Parameters**
- **key** (*str*)
 - **func** (*Callable*[[*object*, *float*, *float*, *float* | *None*, *Mapping*[*str*, *float*]], *float*)

Return type *None*

factor (*reaction*, *t9*, *rho*, *ye*, *abundances*)

- Parameters**
- **t9** (*float*)
 - **rho** (*float*)
 - **ye** (*float* | *None*)
 - **abundances** (*Mapping*[*str*, *float*])

Return type *float*

`nucnetpy.rate_modifiers.constant_factor ( value )`

Parameters **value** (*float*)

Return type *Callable*[[*object*, *float*, *float*, *float* | *None*, *Mapping*[*str*, *float*]], *float*]

`nucnetpy.rate_modifiers.exp_temperature_factor ( alpha, power=1.0 )`

- Parameters**
- **alpha** (*float*)
 - **power** (*float*)

Return type *Callable*[[*object*, *float*, *float*, *float* | *None*, *Mapping*[*str*, *float*]], *float*]

Graph export helpers replacing the Graphviz-oriented examples.

`nucnetpy.graph.reaction_network_dot ( network, min_rate=0.0, t9=1.0, rho=1.0 )`

- Parameters**
- **network** (*Network*)

- **min_rate** (*float*)
- **t9** (*float*)
- **rho** (*float*)

Return type str

Physical constants used by nucnetpy.

The values are SI/cgs mixed in the conventional astrophysical style used by network codes. They are intentionally centralized so advanced users can swap or audit constants when comparing with libnucnet/NucNet Tools builds.

Command line

Installing the package puts a `nucnetpy` command on the path. This page is generated from the argument parser, so it matches the code.

```
usage: nucnetpy [-h]

{summary, print-output, largest-x, zone-abundances, zone-properties, element-abundances, rates, flows, y
...

Pure-Python NucNet Tools replacement commands

positional arguments:
{summary, print-output, largest-x, zone-abundances, zone-properties, element-abundances, rates, flows, y
net-flows              forward, detailed-balance reverse, and net fluxes
  charge-flows          per-reaction dYe/dt contributions
  timescales            shortest species timescales Y/|dY/dt|
  entropy-generation    dS/dt per nucleon in k_B/s
  qse                   constrained cluster equilibrium (libnuceq)
  jina-summary          summarize separate JINA nuclide and reaction XML files
  jina-combine          combine JINA nuclide and reaction XML files into one
                        nucnetpy XML file

options:
  -h, --help            show this help message and exit
```

7.1 summary

```
usage: nucnetpy summary [-h] xml

positional arguments:
  xml

options:
  -h, --help  show this help message and exit
```

7.2 print-output

```
usage: nucnetpy print-output [-h] [--max-zones MAX_ZONES]
                             [--min-abundance MIN_ABUNDANCE]
                             xml
```

```
positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --max-zones MAX_ZONES
  --min-abundance MIN_ABUNDANCE
```

7.3 largest-x

```
usage: nucnetpy largest-x [-h] [-n N] [--zone-index ZONE_INDEX]
                          [--min-x MIN_X]
                          xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  -n N
  --zone-index ZONE_INDEX
  --min-x MIN_X
```

7.4 zone-abundances

```
usage: nucnetpy zone-abundances [-h] [--zone-index ZONE_INDEX]
                                [--min-abundance MIN_ABUNDANCE]
                                xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --min-abundance MIN_ABUNDANCE
```

7.5 zone-properties

```
usage: nucnetpy zone-properties [-h] [--zone-index ZONE_INDEX] xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
```

7.6 element-abundances

```
usage: nucnetpy element-abundances [-h] [--zone-index ZONE_INDEX] xml element

positional arguments:
  xml
  element

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
```

7.7 rates

```
usage: nucnetpy rates [-h] [--t9 T9] [--rho RHO] [--min-rate MIN_RATE] xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --t9 T9
  --rho RHO
  --min-rate MIN_RATE
```

7.8 flows

```
usage: nucnetpy flows [-h] [--zone-index ZONE_INDEX] [--t9 T9] [--rho RHO]
                    [--min-flow MIN_FLOW] xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --t9 T9
  --rho RHO
  --min-flow MIN_FLOW
```

7.9 ydot

```
usage: nucnetpy ydot [-h] [--zone-index ZONE_INDEX] [--t9 T9] [--rho RHO]
                    [--min-abs MIN_ABS] xml

positional arguments:
  xml

options:
```

```
-h, --help            show this help message and exit
--zone-index ZONE_INDEX
--t9 T9
--rho RHO
--min-abs MIN_ABS
```

7.10 net-flows

```
usage: nucnetpy net-flows [-h] [--zone-index ZONE_INDEX] [--t9 T9] [--rho RHO]
                        [--min-flow MIN_FLOW]
                        xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --t9 T9
  --rho RHO
  --min-flow MIN_FLOW
```

7.11 charge-flows

```
usage: nucnetpy charge-flows [-h] [--zone-index ZONE_INDEX] [--t9 T9]
                             [--rho RHO] [--min-flow MIN_FLOW]
                             xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --t9 T9
  --rho RHO
  --min-flow MIN_FLOW
```

7.12 timescales

```
usage: nucnetpy timescales [-h] [--zone-index ZONE_INDEX] [--t9 T9]
                           [--rho RHO] [-n N]
                           xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --t9 T9
  --rho RHO
  -n N
```

7.13 entropy-generation

```
usage: nucnetpy entropy-generation [-h] [--zone-index ZONE_INDEX] [--t9 T9]
                                   [--rho RHO]
                                   xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --t9 T9
  --rho RHO
```

7.14 conservation

```
usage: nucnetpy conservation [-h] [--max MAX] xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --max MAX
```

7.15 remove-duplicates

```
usage: nucnetpy remove-duplicates [-h] xml output

positional arguments:
  xml
  output

options:
  -h, --help            show this help message and exit
```

7.16 remove-invalid

```
usage: nucnetpy remove-invalid [-h] xml output

positional arguments:
  xml
  output

options:
  -h, --help            show this help message and exit
```

7.17 export-zone-xml

```
usage: nucnetpy export-zone-xml [-h] [--zone-index ZONE_INDEX] xml output

positional arguments:
  xml
  output

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
```

7.18 reactions-latex

```
usage: nucnetpy reactions-latex [-h] xml output

positional arguments:
  xml
  output

options:
  -h, --help            show this help message and exit
```

7.19 species-history

```
usage: nucnetpy species-history [-h] xml species

positional arguments:
  xml
  species

options:
  -h, --help            show this help message and exit
```

7.20 evolve-zone

```
usage: nucnetpy evolve-zone [-h] [--zone-index ZONE_INDEX] [--t0 T0] [--t1 T1]
                             [--steps STEPS] [--t9 T9] [--rho RHO]
                             [--method METHOD] [--log-time]
                             [--min-abundance MIN_ABUNDANCE]
                             xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --zone-index ZONE_INDEX
  --t0 T0
  --t1 T1
  --steps STEPS
```

```
--t9 T9
--rho RHO
--method METHOD
--log-time
--min-abundance MIN_ABUNDANCE
```

7.21 energy-generation

```
usage: nucnetpy energy-generation [-h] [--zone-index ZONE_INDEX] [--t9 T9]
                                   [--rho RHO]
                                   xml
```

positional arguments:
xml

options:
-h, --help show this help message **and** exit
--zone-index ZONE_INDEX
--t9 T9
--rho RHO

7.22 net-dot

```
usage: nucnetpy net-dot [-h] [-o OUTPUT] [--t9 T9] [--rho RHO]
                        [--min-rate MIN_RATE]
                        xml
```

positional arguments:
xml

options:
-h, --help show this help message **and** exit
-o OUTPUT, --output OUTPUT
--t9 T9
--rho RHO
--min-rate MIN_RATE

7.23 validate

```
usage: nucnetpy validate [-h] [--strict] [--max MAX] [--max-zones MAX_ZONES]
                        xml
```

positional arguments:
xml

options:
-h, --help show this help message **and** exit
--strict
--max MAX
--max-zones MAX_ZONES

7.24 nse

```
usage: nucnetpy nse [-h] --t9 T9 --rho RHO --ye YE [--coulomb]
                  [--min-abundance MIN_ABUNDANCE] [--min-x MIN_X]
                  xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --t9 T9
  --rho RHO
  --ye YE
  --coulomb             apply Bravo & Garcia-Senz Coulomb corrections
  --min-abundance MIN_ABUNDANCE
  --min-x MIN_X
```

7.25 qse

```
usage: nucnetpy qse [-h] --t9 T9 --rho RHO --ye YE [--cluster SP1,SP2,...:Y]
                  [--coulomb] [--min-abundance MIN_ABUNDANCE]
                  [--min-x MIN_X]
                  xml

positional arguments:
  xml

options:
  -h, --help            show this help message and exit
  --t9 T9
  --rho RHO
  --ye YE
  --cluster SP1,SP2,...:Y
                        cluster species and constrained total abundance;
                        repeatable
  --coulomb
  --min-abundance MIN_ABUNDANCE
  --min-x MIN_X
```

7.26 jina-summary

```
usage: nucnetpy jina-summary [-h] [--zones-xml ZONES_XML] [--show-invalid]
                             [--max-invalid MAX_INVALID]
                             nuclides_xml reactions_xml

positional arguments:
  nuclides_xml
  reactions_xml

options:
  -h, --help            show this help message and exit
  --zones-xml ZONES_XML
  --show-invalid
```



```
--max-invalid MAX_INVALID
```

7.27 jina-combine

```
usage: nucnetpy jina-combine [-h] [--zones-xml ZONES_XML]
                             nuclides_xml reactions_xml output_xml
```

positional arguments:

```
  nuclides_xml
  reactions_xml
  output_xml
```

options:

```
-h, --help            show this help message and exit
--zones-xml ZONES_XML
```

Conversion map from original NucNet Tools concepts to nucnetpy

Original area	Python replacement
Libnucnet__Nuc / species handling	<code>nucnetpy.species.Species</code> , <code>Network.species</code>
Libnucnet__Reac / reactions	<code>nucnetpy.reactions.Reaction</code> , <code>ReactionNetwork</code> , <code>RateFit</code> , <code>TabularRate</code>
ReacLib seven-parameter rates	<code>RateFit.rate(t9)</code>
Reaction duplicate/invalid utilities	<code>ReactionNetwork.remove_duplicates</code> , <code>filter_valid</code> , <code>CLI remove-duplicates</code> , <code>remove-invalid</code>
Zone XML and abundance output	<code>Zone</code> , <code>Network.zones</code> , <code>nucnetpy.io.xml</code>
Analysis examples (<code>print_output</code> , largest X, flows, <code>ydot</code>)	<code>nucnetpy.analysis</code> and CLI commands
Graph utilities	<code>nucnetpy.graph.reaction_network_dot</code> , CLI <code>net-dot</code>
Screening user callbacks	<code>nucnetpy.screening</code> with weak/intermediate models and solver callback hook
Weak-rate utilities	<code>nucnetpy.weak.WeakRateTable</code> , <code>read_weak_table</code> , solver weak-rate hook
libnuceq/NSE workflows	<code>nucnetpy.nse.solve_nse</code> , <code>equilibrium_ratio</code>
Matrix/Jacobian solver utilities	<code>nucnetpy.solver.jacobian</code> , <code>jacobian_sparsity</code> , SciPy BDF/Radau/LSODA
Multi-zone evolution	<code>evolve_network_zones</code>
HDF5 helper workflow	<code>nucnetpy.io.hdf5</code>

8.1 What is implemented in alpha 2

- Flexible XML parsing for common legacy structures and compact Python-written XML.
- Partition functions and optional properties are preserved.
- ReacLib, tabular, and constant rates are supported.
- NSE solves are available for network-level equilibrium initialization.
- Screening and weak-rate hooks are now solver-compatible.
- A sparse numerical Jacobian and sparsity pattern are available for stiff integration.
- Validation/regression helpers are included.

8.2 What still needs project-specific validation

A full replacement can now be used and extended, but exact reproduction of a historical C++ run requires comparing against your original input/output files. The main tunable points are:

1. exact XML schema variants used by your input files,
2. original mass excess and partition-function data,
3. exact screening callback selected in the original C++ build,
4. weak-rate table source and interpolation convention,
5. solver tolerance, timestep, and rate-modifier settings.

Blog workflow coverage

Mapping of the science workflows from Bradley Meyer's NucNet Tools blog (<https://sourceforge.net/u/mbradle/blog/>, 94 posts, 2012–2019) to nucnetpy features. Installation/infrastructure posts (Cygwin, Boost, compilers, AWS, SourceForge housekeeping — 24 posts) do not apply to a pure-Python package and are omitted.

9.1 Covered

Blog workflow	nucnetpy feature
Running a first network calculation; changing input conditions; dynamic H burning	<code>evolve_zone</code> , <code>constant_thermo</code> , CLI <code>evolve-zone</code>
Analyzing a network calculation; printing properties and mass fractions	<code>analysis</code> , CLI <code>print-output</code> , <code>largest-x</code> , <code>zone-*</code>
Understanding/updating/validating nuclear and reaction data	<code>io.xml</code> , <code>io.jina</code> , <code>validate_network</code> , CLI <code>validate</code>
Merging nuclear and reaction data	<code>combine_jina_xml</code> , CLI <code>jina-combine</code>
Calculating reaction rates	<code>RateFit</code> , <code>TabularRate</code> , CLI <code>rates</code>
Comparing forward and reverse reaction rates	<code>reverse_rate</code>, <code>reverse_reaction</code> (detailed balance)
Computing reaction flows (forward + reverse)	<code>net_flows</code>, CLI <code>net-flows</code> ; forward-only: <code>flows</code>
Constructing the rate equations	<code>solver.rhs</code> , <code>jacobian</code> , <code>jacobian_sparsity</code>
Finding valid reactions; conservation	<code>invalid_reactions</code> , <code>conserves_a_z</code> , CLI <code>conservation</code>
Modifying reaction rates during a calculation; user-defined rate modifiers	<code>rate_modifiers</code>
Specifying an abundance in a network calculation	<code>Zone.set_abundance</code>
Selecting an input network; limiting the reaction network	<code>select_species (new)</code> , <code>limit_network</code>
Nuclide XPath / XSLT node-set extraction	<code>select_species (Z/A/element selection)</code>
Sorting species in a network calculation	<code>Network.species_names (Z, A order)</code>
Calculating nuclear statistical equilibrium	<code>solve_nse</code> , CLI <code>nse</code>

Comparing network calculations to equilibrium	<code>solve_nse + regression_summary</code>
Studying the nuclear partition function	<code>Species.partition</code> , partition-aware NSE
Understanding abundance moments	<code>abundance_moment</code>
Computing the number of heavy nuclei	heavy_nuclei_abundance (new)
Computing system timescales	system_timescales (new) , CLI timescales
Computing charge-changing flows	charge_changing_flows (new) , CLI charge-flows
Computing the s-process neutron exposure	neutron_exposure (new)
Plotting abundances versus nucleon number	<code>abundances_vs_nucleon_number</code>
Plotting isotopic abundances versus time	<code>species_history</code> , <code>EvolutionResult.mass_fraction_history</code>
Computing separation energies	separation_energy (proton branch fixed)
Computing/understanding the entropy generation rate (incl. weak decay)	entropy_generation_rate (new) , CLI entropy-generation
Inverting the entropy to find the density	<code>thermo.density_from_entropy</code> , <code>temperature_from_entropy</code>
Computing thermodynamic quantities	<code>thermo</code>
Defining your own thermodynamic (trajectory) function	<code>ThermoFunction</code> callables, <code>hydro.Trajectory</code>
Using a thermodynamic trajectory file	<code>read_trajectory</code>
Running a network calculation with simple hydrodynamics	<code>exponential_expansion</code>
Including electron screening; supplying your own screening function	<code>screening</code> , solver <code>screening= hook</code>
Adding fission to an r-process calculation	fission_reaction (new)
Running an r-process calculation	<code>evolve_zone + JINA XML network</code>
(n,γ) - (γ,n) equilibrium studies	reverse_reaction to build photodisintegration partners; <code>solve_nse</code>
Creating flow diagrams (colors, scalings, currents)	<code>graph.reaction_network_dot</code> , CLI net-dot (basic)
Creating webnucleo reaction XML from text with Python	<code>read_reaclib_text</code> , <code>io.text</code> , <code>write_xml</code>
Using zone properties; global strings	<code>Zone.properties</code> , <code>Network.metadata</code>
Selecting a zone as input for a new calculation	CLI export-zone-xml
Controlling the frequency of writing output	<code>times</code> grid passed to <code>evolve_zone</code>
Using wutils to analyze output	<code>analysis module + io.hdf5</code>
Weak decays / entropy for weak decay	<code>weak tables + charge_changing_flows</code>
Updating mass excesses in a nuclide XML	<code>edit Species.mass_excess</code> , re-write_xml

Counting matrix elements; arrow matrix storage	jacobian_sparsity (SciPy sparse replaces arrow solver)
--	--

9.2 Ported from the C++ source (r647)

These items were verified against the actual NucNet Tools SVN trunk (nucnet-tools-code r647, downloaded from SourceForge) and ported from the named C++ files:

Blog work-flow	C++ origin	nucnetpy feature
Studying Coulomb corrections to NSE; including NSE corrections in a network calculation	user/nse_corr.cpp (Bravo & García-Senz 1999, Ogata & Ichimaru constants)	coulomb module: γ_e , species_coulomb_chemical_potential / _energy / _entropy, coulomb_nse_correction; solve_nse(..., nse_correction=...) hook
Computing NSE corrections to the entropy	user/nse_corr.cpp (species_coulomb_entropy)	coulomb_entropy_per_nucleon
Comparing network calculations to equilibrium; $(n, \gamma) - (\gamma, n)$ equilibrium; constraining the equilibrium	libnuceq clusters via examples/analysis/compare_equil.cpp	solve_qse with QSECluster constraints (one multiplier per cluster on top of μ_p/μ_n)
Calculating cluster flows	examples/analysis/compute_Ycdot.cpp	cluster_ydot, cluster_abundance

Creating /ana- lyzing inte- grated currents diagrams	user/flow_utilities.cpp (update_flow_currents: <code>current</code> <code>+= (f-r).dt</code>)	integrated_currents an EvolutionResult over
Computing the entropy gener- ation rate (per reac- tion, with reverse flows)	user/flow_utilities.cpp (compute_entropy_generation_rate)	entropy_generation_rate(use_reverse=True) $-\sum (f-r) \cdot \ln(f/r)$, non-negative, vanishes at NSE; reaction_entropy_changes

9.3 Not ported (by design or still open)

Blog workflow	Status
Constant-entropy evolution with self-consistent entropy inverter	partial — thermo inverters exist; no closed-loop driver
Electron/positron chemical-potential terms in entropy generation (libstatmech)	open — weak reactions carry tabulated rates instead
Fission <i>cycling</i> studies (automatic fragment distributions)	partial — fission_reaction builds channels; distributions are user input
Downloading webnucleo XML files	use the URLs in the blog post; nucnetpy reads them directly
XML inclusion (XInclude) / XSLT transforms	use lxml externally, then read_xml

Pure Python port status

The C++ source contains helper files under `nnt/` and `user/`. This alpha adds Python equivalents for the practical computational layers rather than a backend wrapper.

Original area	Python module	Status
<code>nnt/math.*</code>	<code>nucnetpy.mathutils</code>	Ported: linear, bilinear, 2-D interpolation behavior
<code>wrappers/containers</code>	<code>core.py</code> , <code>species.py</code>	Ported core containers
<code>network/reaction utilities</code>	<code>reactions.py</code> , <code>validation.py</code>	Ported main rate/flow/conser- vation APIs
<code>screen.*</code>	<code>screening.py</code>	Pure-Python weak and interme- diate screening; exact formula variants still need golden valida- tion
<code>weak_utilities.*</code> , <code>two_d_weak_rates.*</code>	<code>weak.py</code>	Ported 2-D weak-rate table inter- polation and weak source terms
<code>thermo.*</code>	<code>thermo.py</code> , <code>nse.py</code>	Partial: common thermody- namic helpers and NSE; detailed libstatmech parity requires vali- dation
<code>matrix_solver.*</code> , <code>ilu_solvers.*</code>	<code>matrix_solver.py</code> , <code>solver.py</code>	Ported to SciPy sparse solvers and stiff integrators
<code>hydro.*</code> , <code>hydro_helper.*</code>	<code>hydro.py</code>	Ported trajectory interpolation and exponential expansion
<code>network_limiter.*</code>	<code>network_limiter.py</code>	Ported species/reaction subnet- work limiting
<code>nuclear_decay_utilities.*</code>	<code>decay.py</code>	Ported half-life/decay record tools
<code>neutrino_rate_functions.*</code>	<code>neutrino.py</code>	Ported neutrino luminosity /cross-section helpers
<code>hdf5_routines.*</code>	<code>io/hdf5.py</code>	Ported compact HDF5 save/load
<code>graph.h</code>	<code>graph.py</code>	Ported DOT export

10.1 What remains for strict numerical identity

No C++ is used in this package. To make the Python code exactly match a chosen original C++ build, add golden-output tests generated once from the original tools, then tune the pure-Python formulas and tolerances until those tests pass.

The framework for this now exists in-repo. `tests/test_golden_identity.py` implements

the full recommended order below against golden files in `tests/golden/`, and validation `/generate_golden.py` regenerates those files:

1. XML round-trip tests for your real networks — `test_xml_round_trip`, `test_round_trip_is_a_fixed_point` (identity tests, no golden data needed).
2. Rate-by-rate ReacLib comparisons on a T9 grid — `test_reaclib_rates_on_t9_grid` vs `rates_reaclib.json`.
3. Screening-factor comparisons for your chosen user/screen.cpp model — `test_screening_factors` vs `screening.json`.
4. Weak-rate table comparisons — `test_weak_rate_table_interpolation` vs `weak_rates.json`.
5. One-zone RHS ydot comparisons at fixed state — `test_ydot_at_fixed_states` vs `ydot.json` (also asserts nucleon-number conservation of the RHS).
6. Full trajectory comparisons with identical time grids and tolerances — `test_full_trajectory` vs `trajectory.json` (deterministic fixed-step rk4), plus a solver cross-check that adaptive BDF agrees with the rk4 path.

Out of the box the goldens are self-consistent snapshots of the current Python numerics, so any future change to a formula fails the suite immediately. To validate against a specific C++ NucNet Tools build:

1. Replace the fixture inputs (`tests/golden/golden_network.xml`, `golden_weak_rates.txt`) with your production data, or keep them and reproduce the same inputs on the C++ side.
2. Run the same grids through the original tools and write their outputs into the data blocks of the JSON files (set `source` to your build id).
3. Loosen each file's `rtol/atol` to the agreement you require — the tolerances are read from the golden files, not hard-coded in the tests.

Exact numerical identity policy

A pure Python rewrite cannot honestly promise exact numerical identity with the original C++ NucNet Tools by itself. Identity depends on the original C/C++ source, libnucnet/libnuceq/statmech versions, GSL/libxml2 behavior, compiler, optimization flags, reaction ordering, matrix solver details, and floating-point rounding.

Therefore this package uses two backends:

1. **Exact backend:** calls the original C++ NucNet Tools executables or compiled wrappers. This is the backend to use when you need exact legacy identity.
2. **Python backend:** a Python implementation/scaffold for analysis, testing, and future line-by-line porting. This is useful, but it is not the source of truth for exact identity until validated against golden C++ outputs.

11.1 Build the original backend

The original C++ source tree is bundled under:

```
external/original_cpp
```

On your machine, install the original dependencies, usually including:

```
sudo apt install build-essential g++ make gsl-bin libgsl-dev libxml2-dev xsltproc wget
```

Then try:

```
nucnetpy-exact source
nucnetpy-exact make --jobs 4
```

The legacy Makefiles may download specific vendor packages such as libnucnet, libnuceq, wn_matrix, and statmech. For strict reproducibility, keep the same versions and compile flags as your original C++ installation.

11.2 Run an original executable through Python

Example:

```
nucnetpy-exact run print_output my_output.xml
```

or in Python:

```
from nucnetpy.exact import CppBackend
```

```
cpp = CppBackend(bin_dir="/path/to/original/build/bin")
result = cpp.run("print_output", ["my_output.xml"])
print(result.stdout)
```

11.3 Compare outputs

Byte-for-byte text comparison:

```
nucnetpy-exact compare cpp_output.txt python_output.txt
```

Floating-value comparison:

```
nucnetpy-exact compare cpp_output.txt python_output.txt --float --rtol 1e-14
--atol 0
```

For exact identity, use `--rtol 0 --atol 0`. In practice, different compilers or CPUs may produce last-bit differences even for the same C++ code.

11.4 Development rule

For every C++ example converted to Python, create a golden-output test:

1. Run the original C++ executable on the same input XML.
2. Save stdout as the golden file.
3. Run the Python equivalent.
4. Compare with zero tolerance first; if platform differences appear, record the exact tolerance and reason.

Only modules passing these golden tests should be advertised as exact replacements.

JINA XML workflow in nucnetpy

The original C++ NucNet Tools examples usually begin from JINA/libnucnet XML files. The Python port follows the same idea, but uses a Python object model.

12.1 Files

Use your stored XML files as follows:

- `jina_nuclides.xml`: nuclides/species, including Z, A, mass excess, spin, and partition data.
- `jina_reactions.xml`: reactions and ReacLib rate coefficients.
- optional `zones.xml`: initial abundances or output zones.

12.2 Python usage

```
from nucnetpy import read_jina_xml

net = read_jina_xml("jina_nuclides.xml", "jina_reactions.xml")
print(net.validate())
```

With zones:

```
net = read_jina_xml(
    "jina_nuclides.xml",
    "jina_reactions.xml",
    zones_xml="initial_zones.xml",
)
```

12.3 Command-line usage

```
nucnetpy jina-summary jina_nuclides.xml jina_reactions.xml
nucnetpy jina-combine jina_nuclides.xml jina_reactions.xml combined_network.xml
nucnetpy rates combined_network.xml --t9 1.0 --rho 1e5
nucnetpy conservation combined_network.xml
```

12.4 Important numerical point

To approach numerical identity with the original C++ tools, use the exact same JINA XML files, do

not reorder or filter reactions unless intentionally testing that operation, and compare rates/flows at fixed `T9`, `rho`, and abundance values.

Where to start

If you have never used the package, read [Installation](#) and [Concepts](#), then work through the tutorial notebooks in `notebooks/`, which are the fastest way in.

If you are migrating an existing NucNet Tools workflow, [Conversion map from original NucNet Tools concepts to nucnetpy](#) maps the original concepts onto this API and [Blog workflow coverage](#) maps each blog workflow onto the feature that replaces it.

If you are about to run a production calculation, read [Pitfalls](#) first. It describes two behaviours that produce plausible but wrong answers without raising an error.

Citing

Please cite the archived release ([10.5281/zenodo.20756798](https://doi.org/10.5281/zenodo.20756798)) and acknowledge the NucNet Tools and libnucnet ecosystem, whose data model and workflows this package reimplements, together with the JINA reaction-rate database that supplies the nuclear data.

n

nucnetpy

- nucnetpy.analysis, 40
- nucnetpy.constants, 50
- nucnetpy.core, 16
- nucnetpy.coulomb, 30
- nucnetpy.decay, 38
- nucnetpy.detailed_balance, 32
- nucnetpy.graph, 49
- nucnetpy.hydro, 46
- nucnetpy.io.jina, 45
- nucnetpy.io.xml, 44
- nucnetpy.network_limiter, 45
- nucnetpy.neutrino, 39
- nucnetpy.nse, 26
- nucnetpy.qse, 28
- nucnetpy.rate_modifiers, 49
- nucnetpy.reactions, 18
- nucnetpy.screening, 34
- nucnetpy.solver, 23
- nucnetpy.species, 15
- nucnetpy.thermo, 47
- nucnetpy.validation, 48
- nucnetpy.weak, 36

A

`a` (nucnetpy.species.Species attribute), 16
`abundance_from_mass_fraction()` (in module nucnetpy.species), 16
`abundance_matrix()` (nucnetpy.core.Network method), 18
`abundance_moment()` (in module nucnetpy.-analysis), 40
`abundances` (nucnetpy.core.Zone attribute), 17
`abundances` (nucnetpy.nse.NSEResult attribute), 27
`abundances` (nucnetpy.qse.QSEResult attribute), 29
`abundances` (nucnetpy.screening.ScreeningContext attribute), 35
`abundances_for_element()` (in module nucnetpy.analysis), 40
`abundances_vs_nucleon_number()` (in module nucnetpy.analysis), 40
`add()` (nucnetpy.reactions.ReactionNetwork method), 22
`add_decay_records()` (in module nucnetpy.decay), 38
`add_species()` (nucnetpy.core.Network method), 18
`add_zone()` (nucnetpy.core.Network method), 18
`analytic_jacobian()` (in module nucnetpy.-solver), 25

B

`bare_rate()` (nucnetpy.reactions.Reaction method), 21
`branch` (nucnetpy.decay.DecayRecord attribute), 38

C

`chapter` (nucnetpy.reactions.RateFit attribute), 19
`charge_changing_flows()` (in module nucnetpy.-analysis), 42

`chemical_potential()` (nucnetpy.screening.SkyNetScreening method), 36
`cluster_abundance()` (in module nucnetpy.qse), 30
`cluster_ydot()` (in module nucnetpy.qse), 30
`code` (nucnetpy.validation.ValidationIssue attribute), 48
`coefficients` (nucnetpy.reactions.RateFit attribute), 19
`combine_jina_xml()` (in module nucnetpy.io.jina), 45
`compare_abundances()` (in module nucnetpy.-validation), 48
`compare_rates()` (in module nucnetpy.analysis), 41
`compute_yedot()` (in module nucnetpy.weak), 38
`computed_ye` (nucnetpy.nse.NSEResult property), 28
`computed_ye` (nucnetpy.qse.QSEResult property), 29
`conserves_a_z()` (nucnetpy.reactions.Reaction method), 21
`consistent_reverse_network()` (in module nucnetpy.detailed_balance), 33
`constant_factor()` (in module nucnetpy.rate_-modifiers), 49
`constant_rate` (nucnetpy.reactions.Reaction attribute), 20
`constant_thermo()` (in module nucnetpy.solver), 23
`constraint` (nucnetpy.qse.QSECluster attribute), 29
`coulomb_entropy_per_nucleon()` (in module nucnetpy.coulomb), 32
`count` (nucnetpy.reactions.ReactionParticipant attribute), 19
`cross_section()` (nucnetpy.neutrino.NeutrinoQuantity method), 39

D

`daughter` (nucnetpy.decay.DecayRecord

attribute), 38
daughter (nucnetpy.weak.WeakRateTable attribute), 37
debye_radius() (in module nucnetpy.screening), 34
decay_constant_from_half_life() (in module nucnetpy.decay), 39
DecayRecord (class in nucnetpy.decay), 38
density() (nucnetpy.core.Zone method), 17
density_from_entropy() (in module nucnetpy.thermo), 47
DetailedBalanceOptions (class in nucnetpy.reactions), 23

E

electron_number_density() (in module nucnetpy.screening), 34
element (nucnetpy.species.Species property), 16
element_abundances() (in module nucnetpy.analysis), 40
energy_generation_rate() (in module nucnetpy.analysis), 41
ensure_species() (nucnetpy.core.Network method), 18
entropy_generation_rate() (in module nucnetpy.analysis), 43
entropy_ideal_ions() (in module nucnetpy.thermo), 47
equilibrium_ratio (nucnetpy.reactions.DetailedBalanceOptions attribute), 23
equilibrium_ratio() (in module nucnetpy.nse), 28
EvolutionResult (class in nucnetpy.solver), 24
evolve_network_zones() (in module nucnetpy.solver), 26
evolve_zone() (in module nucnetpy.solver), 26
exp_temperature_factor() (in module nucnetpy.rate_modifiers), 49
exponential_expansion() (in module nucnetpy.hydro), 47
extend() (nucnetpy.reactions.ReactionNetwork method), 22

F

factor() (nucnetpy.rate_modifiers.RateModifierRegistry method), 49
factor() (nucnetpy.screening.SkyNetScreening method), 36
filter_valid() (nucnetpy.reactions.ReactionNetwork method), 22
final_abundances (nucnetpy.solver.EvolutionResult property), 24
fission_reaction() (in module nucnetpy.decay), 39
flows() (in module nucnetpy.analysis), 41
flows() (nucnetpy.reactions.ReactionNetwork method), 22

flux() (nucnetpy.reactions.Reaction method), 21
from_columns() (nucnetpy.hydro.Trajectory class method), 46
from_names() (nucnetpy.reactions.Reaction class method), 20

G

gamma_e() (in module nucnetpy.coulomb), 31
geometric_flux_rate() (in module nucnetpy.neutrino), 40
get_abundance() (nucnetpy.core.Zone method), 17
graboske_intermediate_factor() (in module nucnetpy.screening), 35

H

half_life (nucnetpy.decay.DecayRecord attribute), 38
heavy_nuclei_abundance() (in module nucnetpy.analysis), 42

I

ideal_gas_pressure() (in module nucnetpy.thermo), 47
integrated_currents() (in module nucnetpy.analysis), 43
invalid_reactions() (nucnetpy.reactions.ReactionNetwork method), 22
ion_strength (nucnetpy.screening.ScreeningContext property), 35
ion_strength() (in module nucnetpy.screening), 34
is_massless() (in module nucnetpy.species), 15

J

jacobian() (in module nucnetpy.solver), 25
jacobian_sparsity() (in module nucnetpy.solver), 25
jina_database_summary() (in module nucnetpy.io.jina), 45

K

key (nucnetpy.reactions.Reaction property), 20

L

l0 (nucnetpy.neutrino.NeutrinoLuminosity attribute), 39
label (nucnetpy.core.Zone attribute), 17
label (nucnetpy.qse.QSECluster attribute), 29
label (nucnetpy.reactions.RateFit attribute), 19
label (nucnetpy.reactions.Reaction attribute), 20
label (nucnetpy.weak.WeakRateTable attribute), 37
lambdas (nucnetpy.qse.QSEResult attribute), 29
largest_mass_fractions() (in module nucnetpy.analysis), 40

latex (nucnetpy.reactions.Reaction property), 21
 latex (nucnetpy.species.Species property), 16
 level (nucnetpy.validation.ValidationIssue attribute), 48
 limit_network() (in module nucnetpy.network_limiter), 46
 log10_xsec (nucnetpy.neutrino.NeutrinoQuantity attribute), 39
 log_equilibrium_constant() (in module nucnetpy.detailed_balance), 32
 log_interp (nucnetpy.reactions.TabularRate attribute), 19
 luminosity() (nucnetpy.neutrino.NeutrinoLuminosity method), 39

M

mass_excess (nucnetpy.species.Species attribute), 16
 mass_fraction() (in module nucnetpy.species), 16
 mass_fraction_history() (nucnetpy.solver.EvolutionResult method), 24
 mass_fractions() (nucnetpy.core.Zone method), 17
 MASSLESS_SPECIES (in module nucnetpy.species), 15
 max_relative_abundance_error() (in module nucnetpy.validation), 48
 message (nucnetpy.nse.NSEResult attribute), 27
 message (nucnetpy.qse.QSEResult attribute), 29
 message (nucnetpy.solver.EvolutionResult attribute), 24
 message (nucnetpy.validation.ValidationIssue attribute), 48
 metadata (nucnetpy.core.Network attribute), 18
 metadata (nucnetpy.reactions.Reaction attribute), 20
 mode (nucnetpy.decay.DecayRecord attribute), 38
 modifiers (nucnetpy.rate_modifiers.RateModifierRegistry attribute), 49
 module

- nucnetpy.analysis, 40
- nucnetpy.constants, 50
- nucnetpy.core, 16
- nucnetpy.coulomb, 30
- nucnetpy.decay, 38
- nucnetpy.detailed_balance, 32
- nucnetpy.graph, 49
- nucnetpy.hydro, 46
- nucnetpy.io.jina, 45
- nucnetpy.io.xml, 44
- nucnetpy.network_limiter, 45
- nucnetpy.neutrino, 39
- nucnetpy.nse, 26
- nucnetpy.qse, 28
- nucnetpy.rate_modifiers, 49

nucnetpy.reactions, 18
 nucnetpy.screening, 34
 nucnetpy.solver, 23
 nucnetpy.species, 15
 nucnetpy.thermo, 47
 nucnetpy.validation, 48
 nucnetpy.weak, 36
 mu_n (nucnetpy.nse.NSEResult attribute), 27
 mu_n (nucnetpy.qse.QSEResult attribute), 29
 mu_p (nucnetpy.nse.NSEResult attribute), 27
 mu_p (nucnetpy.qse.QSEResult attribute), 29

N

n (nucnetpy.species.Species property), 16
 name (nucnetpy.species.Species attribute), 16
 net_flows() (in module nucnetpy.detailed_balance), 34
 Network (class in nucnetpy.core), 17
 neutrino_loss() (nucnetpy.weak.WeakRateTable method), 37
 NeutrinoLuminosity (class in nucnetpy.neutrino), 39
 NeutrinoQuantity (class in nucnetpy.neutrino), 39
 neutron_exposure() (in module nucnetpy.analysis), 42
 nfev (nucnetpy.solver.EvolutionResult attribute), 24
 njev (nucnetpy.solver.EvolutionResult attribute), 24
 normalize_species_name() (in module nucnetpy.species), 16
 nse_correction() (in module nucnetpy.-coulomb), 31
 nse_prefactor() (in module nucnetpy.nse), 27
 NSEResult (class in nucnetpy.nse), 27
 nu_loss (nucnetpy.weak.WeakRateTable attribute), 37
 nuclear_energy_generation_rate() (in module nucnetpy.analysis), 43
 nuclear_energy_release() (in module nucnetpy.-analysis), 44
 nuclear_reactants (nucnetpy.reactions.Reaction property), 21
 nucnetpy.analysis

- module, 40

 nucnetpy.constants

- module, 50

 nucnetpy.core

- module, 16

 nucnetpy.coulomb

- module, 30

 nucnetpy.decay

- module, 38

 nucnetpy.detailed_balance

- module, 32

 nucnetpy.graph

- module, 49
- nucnetpy.hydro
 - module, 46
- nucnetpy.io.jina
 - module, 45
- nucnetpy.io.xml
 - module, 44
- nucnetpy.network_limiter
 - module, 45
- nucnetpy.neutrino
 - module, 39
- nucnetpy.nse
 - module, 26
- nucnetpy.qse
 - module, 28
- nucnetpy.rate_modifiers
 - module, 49
- nucnetpy.reactions
 - module, 18
- nucnetpy.screening
 - module, 34
- nucnetpy.solver
 - module, 23
- nucnetpy.species
 - module, 15
- nucnetpy.thermo
 - module, 47
- nucnetpy.validation
 - module, 48
- nucnetpy.weak
 - module, 36

O

- optional_properties (nucnetpy.core.Zone attribute), 17

P

- parent (nucnetpy.decay.DecayRecord attribute), 38
- parent (nucnetpy.weak.WeakRateTable attribute), 37
- parse() (nucnetpy.species.Species class method), 16
- partition (nucnetpy.species.Species attribute), 16
- products (nucnetpy.reactions.Reaction attribute), 20
- properties (nucnetpy.core.Zone attribute), 17

Q

- q_energy_erg_per_g() (in module nucnetpy.thermo), 48
- q_value (nucnetpy.reactions.Reaction attribute), 20
- QSECluster (class in nucnetpy.qse), 29
- QSEResult (class in nucnetpy.qse), 29

R

- radiation_pressure() (in module nucnetpy.thermo), 47
- rate (nucnetpy.decay.DecayRecord property), 38
- rate() (nucnetpy.reactions.RateFit method), 19
- rate() (nucnetpy.reactions.Reaction method), 21
- rate() (nucnetpy.reactions.TabularRate method), 19
- rate() (nucnetpy.weak.WeakRateTable method), 37
- rate_fits (nucnetpy.reactions.Reaction attribute), 20
- rate_function (nucnetpy.reactions.Reaction attribute), 20
- RateFit (class in nucnetpy.reactions), 19
- RateModifierRegistry (class in nucnetpy.rate_modifiers), 49
- rates (nucnetpy.reactions.TabularRate attribute), 19
- rates (nucnetpy.weak.WeakRateTable attribute), 37
- rates() (nucnetpy.reactions.ReactionNetwork method), 22
- reactant_order (nucnetpy.reactions.Reaction property), 21
- reactants (nucnetpy.reactions.Reaction attribute), 20
- Reaction (class in nucnetpy.reactions), 20
- reaction() (nucnetpy.decay.DecayRecord method), 38
- reaction_entropy_changes() (in module nucnetpy.analysis), 42
- reaction_network_dot() (in module nucnetpy.-graph), 49
- reaction_screening_factor() (in module nucnetpy.screening), 35
- ReactionNetwork (class in nucnetpy.reactions), 22
- ReactionParticipant (class in nucnetpy.reactions), 19
- reactions (nucnetpy.core.Network attribute), 18
- reactions (nucnetpy.reactions.ReactionNetwork attribute), 22
- read_jina_xml() (in module nucnetpy.io.jina), 45
- read_network_xml() (in module nucnetpy.io.xml), 44
- read_reaclib_text() (in module nucnetpy.reactions), 23
- read_trajectory() (in module nucnetpy.hydro), 46
- read_weak_table() (in module nucnetpy.weak), 37
- read_weak_tables() (in module nucnetpy.weak), 37
- read_xml() (in module nucnetpy.io.xml), 44
- read_xml_root() (in module nucnetpy.io.xml), 44

read_xml_string() (in module nucnetpy.io.xml), 45
 register() (nucnetpy.rate_modifiers.RateModifierRegistry method), 49
 regression_summary() (in module nucnetpy.validation), 49
 remove_duplicates() (nucnetpy.reactions.ReactionNetwork method), 22
 reverse_rate() (in module nucnetpy.detailed_balance), 32
 reverse_rate_from_detailed_balance() (in module nucnetpy.reactions), 23
 reverse_reaction() (in module nucnetpy.detailed_balance), 33
 rho (nucnetpy.hydro.Trajectory attribute), 46
 rho (nucnetpy.nse.NSEResult attribute), 27
 rho (nucnetpy.qse.QSEResult attribute), 29
 rho (nucnetpy.reactions.DetailedBalanceOptions attribute), 23
 rho (nucnetpy.screening.ScreeningContext attribute), 35
 rho_je (nucnetpy.weak.WeakRateTable attribute), 37
 rhs() (in module nucnetpy.solver), 24

S

ScreeningContext (class in nucnetpy.screening), 34
 select_species() (in module nucnetpy.network_limiter), 46
 separation_energy() (in module nucnetpy.analysis), 41
 set_abundance() (nucnetpy.core.Zone method), 17
 SkyNetScreening (class in nucnetpy.screening), 36
 solve_nse() (in module nucnetpy.nse), 28
 solve_qse() (in module nucnetpy.qse), 30
 sound_speed_ideal_gamma() (in module nucnetpy.thermo), 48
 source (nucnetpy.reactions.Reaction attribute), 20
 source (nucnetpy.species.Species attribute), 16
 Species (class in nucnetpy.species), 15
 species (nucnetpy.core.Network attribute), 18
 species (nucnetpy.qse.QSECluster attribute), 29
 species (nucnetpy.reactions.ReactionParticipant attribute), 19
 species (nucnetpy.solver.EvolutionResult attribute), 24
 species_coulomb_chemical_potential() (in module nucnetpy.coulomb), 31
 species_coulomb_energy() (in module nucnetpy.coulomb), 31
 species_coulomb_entropy() (in module nucnetpy.coulomb), 31
 species_from_za() (in module nucnet-

py.species), 16
 species_history() (in module nucnetpy.analysis), 41
 species_map (nucnetpy.screening.ScreeningContext attribute), 35
 species_names() (nucnetpy.core.Network method), 18
 species_names() (nucnetpy.reactions.ReactionNetwork method), 23
 species_without_nuclear_data() (nucnetpy.core.Network method), 18
 spin (nucnetpy.species.Species attribute), 16
 statistical_factor() (nucnetpy.reactions.Reaction method), 21
 stoichiometry() (nucnetpy.reactions.Reaction method), 21
 string (nucnetpy.reactions.Reaction property), 21
 success (nucnetpy.nse.NSEResult attribute), 27
 success (nucnetpy.qse.QSEResult attribute), 29
 success (nucnetpy.solver.EvolutionResult attribute), 24
 system_timescales() (in module nucnetpy.analysis), 42

T

t9 (nucnetpy.hydro.Trajectory attribute), 46
 t9 (nucnetpy.nse.NSEResult attribute), 27
 t9 (nucnetpy.qse.QSEResult attribute), 29
 t9 (nucnetpy.reactions.DetailedBalanceOptions attribute), 23
 t9 (nucnetpy.reactions.TabularRate attribute), 19
 t9 (nucnetpy.screening.ScreeningContext attribute), 35
 t9 (nucnetpy.weak.WeakRateTable attribute), 37
 tabular_rate (nucnetpy.reactions.Reaction attribute), 20
 TabularRate (class in nucnetpy.reactions), 19
 tau (nucnetpy.neutrino.NeutrinoLuminosity attribute), 39
 temperature (nucnetpy.neutrino.NeutrinoQuantity attribute), 39
 temperature9() (nucnetpy.core.Zone method), 17
 temperature_from_entropy() (in module nucnetpy.thermo), 47
 thermo() (nucnetpy.hydro.Trajectory method), 46
 time (nucnetpy.hydro.Trajectory attribute), 46
 time (nucnetpy.solver.EvolutionResult attribute), 24
 time_grid() (in module nucnetpy.solver), 24
 Trajectory (class in nucnetpy.hydro), 46

U

update() (nucnetpy.screening.SkyNetScreening

method), 36

V

validate() (nucnetpy.core.Network method), 18
validate_network() (in module nucnetpy.validation), 48
validate_zone() (in module nucnetpy.validation), 48
ValidationIssue (class in nucnetpy.validation), 48

W

weak_screening_factor() (in module nucnetpy.screening), 35
weak_source_terms() (in module nucnetpy.weak), 38
WeakRateTable (class in nucnetpy.weak), 36
write_xml() (in module nucnetpy.io.xml), 44
write_zone_xml() (in module nucnetpy.io.xml), 45

X

xsum (nucnetpy.nse.NSEResult property), 27
xsum (nucnetpy.qse.QSEResult property), 29
xsum() (nucnetpy.core.Zone method), 17

Y

y (nucnetpy.solver.EvolutionResult attribute), 24
ydot() (in module nucnetpy.analysis), 41
ydot() (nucnetpy.reactions.ReactionNetwork method), 22
ye (nucnetpy.nse.NSEResult attribute), 27
ye (nucnetpy.qse.QSEResult attribute), 29
ye (nucnetpy.reactions.DetailedBalanceOptions attribute), 23
ye (nucnetpy.screening.ScreeningContext attribute), 35
ye() (nucnetpy.core.Zone method), 17
ysum() (nucnetpy.core.Zone method), 17

Z

z (nucnetpy.species.Species attribute), 16
Zone (class in nucnetpy.core), 16
zone() (nucnetpy.core.Network method), 18
zone() (nucnetpy.nse.NSEResult method), 27
zone() (nucnetpy.qse.QSEResult method), 29
zone() (nucnetpy.solver.EvolutionResult method), 24
zone_thermo() (in module nucnetpy.solver), 24
zones (nucnetpy.core.Network attribute), 18