Benchmarking long-read simulators against Oxford Nanopore whole-genome sequencing data

Mona L Taouk[1], **Danielle J Ingle**[1,2,†,*] **and Ryan R Wick**[1,2,†,*]

[1]Department of Microbiology and Immunology, The University of Melbourne at the Peter Doherty Institute for Infection and Immunity, Melbourne, Victoria, Australia and [2]Centre for Pathogen Genomics, The University of Melbourne, Parkville, Victoria, Australia

[†]These authors contributed equally

[*]Corresponding authors: danielle.ingle@unimelb.edu.au, ryan.wick@unimelb.edu.au

Abstract

Background: Oxford Nanopore Technologies (ONT) sequencing is increasingly used for whole-genome sequencing (WGS) across a wide range of applications. However, the platform has evolved rapidly through updates to flow cell chemistry and basecalling algorithms, altering the characteristics of the resulting sequencing data. Read simulators provide synthetic datasets with known ground truth, enabling controlled development and evaluation of methods. However, many existing simulators were developed for earlier versions of ONT sequencing or use generic long-read assumptions, and their realism for contemporary ONT data is unclear.

Results: We benchmarked six ONT-compatible read simulators (Badread, LongISLND, lrsim, NanoSim, PBSIM3 and SimLoRD) using a microbial genome reference and ONT R10.4.1 reads as the empirical standard. Each tool was configured to maximise realism, including training on empirical reads when supported. We compared simulated and real datasets with respect to read length, read accuracy, FASTQ quality scores and sequence error profiles. No simulator reproduced all metrics of the real data well. PBSIM3 most closely reproduced read accuracy and FASTQ quality scores, making it a strong simulator for broad read-level realism. However, it did not capture important features of the real error profile, including context-dependent substitution rates and homopolymer-length errors. Badread and LongISLND better reproduced some aspects of the error profile, but showed other departures from the real data.

Conclusion: PBSIM3 is a good general-purpose choice for many ONT WGS microbial simulation tasks because it reproduced several key read-level properties well. However, Badread or LongISLND may be preferable for applications where error structure is more important. No evaluated tool was realistic across all tested metrics, highlighting a gap for improved long-read simulators.

Key words: Oxford Nanopore, long-read sequencing, read simulators, benchmarking, sequencing errors

1. Background

Oxford Nanopore Technologies (ONT) sequencing has transformed long-read genomics by enabling real-time, portable and increasingly high-throughput sequencing[1]. Over the past decade, ONT platforms have changed rapidly, particularly through updates to nanopore chemistry and basecalling models[2,3]. Consequently, the characteristics of ONT data, such as error profiles and base quality scores (Q-scores), have shifted substantially over relatively short time frames of a few years[4,5]. ONT benchmarking studies can age quickly, because their conclusions depend on the chemistries, protocols and basecalling models available at the time[6]. Although ONT continues to evolve, recent changes in read accuracy are now more gradual than the major advances seen earlier in the platform's development. This increasing stability is making ONT more attractive for routine, high-throughput applications where analytical pipelines must withstand formal validation and accreditation[7,8].

As ONT sequencing matures, its use is expanding both in high-income countries, where laboratories are now more willing to invest in validation of ONT-based workflows, and in low- and middle-income settings, where ONT's low capital cost and portability make it a compelling alternative to some short-read sequencers[9–11]. In both contexts, there is a need for robust, realistic benchmarking of long-read analysis tools for tasks such as read mapping, variant calling and genome assembly[12–14]. Benchmarking using real ONT datasets is essential, but it is also constrained by sample availability, cost and the difficulty of establishing a ground truth, particularly for complex genomes[12]. Read simulators therefore play an important role: they provide synthetic datasets where the underlying sequence is exactly known, enabling controlled, reproducible evaluation of methods across a range of experimental designs. They can also supply the large labelled training sets needed for machine learning methods such as deep neural networks[15].

However, many widely used ONT-compatible simulators were originally developed for earlier generations of ONT (pre-R10.4.1 flowcells) or PacBio long-read sequencing, and they may incorporate assumptions that no longer hold for modern ONT[16–20]. For example, simulators often assumed high error rates and a simple error structure[16,18]. Since then, improvements in ONT chemistry and basecalling have improved read accuracy, altered the balance between substitutions and indels, and changed the

relationship between FASTQ Q-scores and error rates[8]. It is therefore unclear whether existing simulators can produce reads that resemble contemporary ONT data.

ONT simulators differ fundamentally in how they generate reads. Some tools rely on explicit training with real data, learning an empirical error model by aligning ONT reads to a reference genome and then using it to introduce errors into new sequences[16,17,19]. Others use pre-trained models that encapsulate typical error behaviour for a given technology and chemistry. Others generate reads from parametric distributions specified by the user, without direct training on empirical data[18,20]. These design choices affect not only how realistic the resulting reads are for a given technology snapshot, but also how easily the simulator can be adapted as ONT chemistries and basecalling models evolve. In particular, simulators that train an error profile from alignments of real reads to a reference have the potential to adapt to new read types.

In this context, 'realism' refers to how closely simulated reads resemble real ONT data across multiple dimensions that matter for downstream analysis. These include basic read-level metrics, such as the distributions of read length, read accuracy and FASTQ Q-scores, together with relationships between these metrics and finer-scale error profiles. The primary goal of this study is therefore to evaluate which currently available read simulators produce the most realistic data for modern ONT reads, focusing on faithfulness to empirical read characteristics.

2. Methods

2.1. Simulator selection

A literature search identified seven long-read simulators compatible with ONT reads. SimON-reads[21] was excluded because it failed to produce reads under any of the specified configuration flags and was deemed non-functional for this analysis. The other six simulators were successfully evaluated in this study: Badread v0.4.2[18], LongISLND v0.9.5 (`c458f56`)[19], lrsim v0.7[22], NanoSim v3.2.3[16], PBSIM3 v3.0.5[17], and SimLoRD v1.0.4[20].

2.2. Reference data

Real ONT reads used as the empirical benchmark were generated from *Listeria innocua* strain AUSMDU00097349 (accession SAMN46906078) on an ONT R10.4.1 PromethION flow cell and basecalled with Dorado v1.1.1[23] using the `dna_r10.4.1_e8.2_400bps_sup@v5.2.0` basecalling model, the latest available for this chemistry at the time of analysis. Reads were demultiplexed using the `dorado demux` with default parameters using the built-in `SQK-RBK114-96` kit barcodes, and reads assigned to barcode 5 (corresponding to the *L. innocua* sample) were retained. The demultiplexing step incidentally excludes some poor-quality reads with absent or unrecognisable barcodes, but no explicit Q-score or length filtering was applied.

The real read set comprised 680,482 reads with a total length of 3,803 Mbp, mean length of 5,588 bp and N50 length of 8,923 bp. The reads were split into two non-overlapping sets: a test set of 53,093 randomly selected reads (chosen to total 100× depth) and a training set containing the remaining 627,389 reads. The test set was used to evaluate real-read properties, while the training set was used to train simulators.

Simulated reads were generated from a complete, closed assembly of the same *L. innocua* strain. This 2,972,545 bp genome was produced in a previous study from the same ONT read set, with Illumina reads used for polishing[12]. Because the assembly was carefully resolved and polished, it provided a reliable ground truth for both read simulation and read evaluation.

2.3. Simulator configuration

Each simulator was configured to maximise the realism of generated reads. For simulators with explicit training or model-building steps (Badread, LongISLND, lrsim and NanoSim), models were built from the real read training set, using alignments to the reference genome where required. PBSIM3 was run in its sampling mode, using real training reads as the source of read lengths and FASTQ quality strings, and SimLoRD was configured to sample read lengths from the training reads. For options controlling overall error rate, error variability or error-type ratios, we used values estimated from the training reads. For NanoSim and PBSIM3, we tested various homopolymer modelling options (Figures S1 and S2) and used the settings which best matched the real reads: disabled homopolymer length simulation in NanoSim, and `--hp-del-bias 5` in PBSIM3. All tools were set to generate read sets of 100× depth (∼300 Mbp).

Each simulator tool was run through GNU Time to quantify its time to run. For tools with separate training and simulation steps, these were measured separately. lrsim (simulation step) and NanoSim support multithreading and were run using 16 threads. Badread, LongISLND, lrsim (training step), PBSIM3 and SimLoRD do not support multithreading and were therefore run with one thread.

Exact commands are documented in Supplementary Methods (methods.md) and are publicly available in the accompanying GitHub repository.

2.4. Evaluation metrics

Simulated and real test reads were compared across multiple read-level and base-level metrics to assess realism. We did not rely on formal statistical tests, because with datasets of this size, even trivial differences can be statistically significant. Instead, we compared the shapes of distributions and the relationships between variables in simulated and real data, which provides a more direct and interpretable measure of realism. We quantified discrepancies in read-length and Q-score distributions using the Wasserstein-1 distance, calculated as the integral of the absolute difference between their normalised weighted cumulative distribution functions (Table S4).

Read lengths were extracted from FASTQ files and summarised using seqkit v2.13.0[24]. Read length distributions were visualised as histograms using the same bin widths and axis limits across all datasets to enable direct visual comparison.

Real and simulated reads were aligned to the reference genome using minimap2 v2.30[25]. Secondary alignments were removed, and identity was then calculated as the number of matching bases divided by the alignment length. This is the "BLAST identity" approach to measuring sequence similarity, where the impact of insertions and deletions is proportional to their length (e.g. a 5-bp deletion affects identity the same as five 1-bp deletions)[26]. Empirical read Q-scores were computed as $Q = -10 \times \log_{10}(1 - \text{identity})$ for each read. Reported read Q-scores were calculated by converting each Phred-scaled quality value in the FASTQ file to an error probability, averaging those probabilities across the aligned portion of the read and then converting back to a Q-score.

To examine FASTQ Q-scores at the per-base level, each base was classified from the alignment as a match, mismatch or insertion, then grouped by its reported FASTQ Q-score. Because deletions have no corresponding read base and therefore no Q-score, they were represented indirectly by adjacent matching

bases counted at half weight. For each reported Q-score, we then calculated the observed error rate from the counts of mismatches, insertions and deletion-associated bases, and used these values to generate calibration plots.

To characterise the error profiles of the real and simulated reads, we analysed two specific error types: 3-mer substitutions and homopolymer lengths. For 3-mer substitutions, we counted substitutions on the sequenced strand in which the middle base differed and the immediate flanking bases matched, for which there are 192 possibilities. The rate of each was expressed as the number of observed substitutions divided by the number of occurrences of the reference 3-mer in the aligned sequence. Homopolymer lengths of 3–10 bp were assessed using Pomoxis v0.3.16 [27], and we defined error rate as the fraction of homopolymers in reads with an incorrect length. These analyses were not intended to capture all aspects of ONT sequencing errors, but instead provide two targeted, interpretable and directly comparable measures of error realism.

To examine how well simulated reads assemble, we generated random subsets of each test read set ranging from 1× to 50× depth, in 1× increments. Each read set was assembled using Flye v2.9.6 [28], metaMDBG v1.4 [29], miniasm v0.3 [30] plus Minipolish v0.2.1, Myloasm v0.7.0 [31] and Raven v1.8.3 [32]. For assemblies that produced at least a 2 Mbp contig ($\sim$ 2/3 of the genome size), assembly accuracy was quantified using the longest contig's alignment identity to the reference genome.

3. Results

3.1. Characteristics of real ONT reads

The real ONT reads had a mean empirical read Q-score of 19.0 and a mean reported read Q-score of 19.2 (Table S2). Read errors were 40.1% substitutions, 18.9% insertions and 41.0% deletions. The 3-mer substitution rates ranged from 0.0059% for `CTG`→`CGG` to 3.6% for `CGA`→`CAA`. Indel errors were especially common in longer homopolymers, with 9-bp homopolymers containing an error 35.6% of the time.

The per-base reported Q-scores ranged from 1 (predicted error rate of 79.4%) to 50 (predicted error rate of 0.001%). At a per-base level, these reported Q-scores were not perfectly calibrated, e.g. Q50 bases were incorrect (or associated with an adjacent deletion) 0.0157% of the time, equivalent to Q38. However, at the whole-read level (averaging all bases), reported and empirical Q-scores generally showed good agreement.

In this study, we did not apply a quality-based filter to the real reads, retaining all reads produced by the basecaller. This revealed a distinctive bimodal distribution in both empirical and reported Q-scores, with a small peak at ∼Q8 and a larger peak at ∼Q23. Bimodal distributions of read Q-scores have been previously observed in ONT datasets [33], but the lower peak may be absent from quality-filtered ONT datasets, e.g. those restricted to reads classified as "PASS" by ONT's MinKNOW software.

3.2. Simulator design and training strategies

The six evaluated read simulators (Badread, LongISLND, lrsim, NanoSim, PBSIM3 and SimLoRD) differ in how they model read length, sequence errors and Q-scores (Table 1) [16–20,22]. Badread uses parametric read length and identity distributions, with trained k-mer error and Q-score models. LongISLND uses a non-parametric model that samples bases and Q-scores from training reads with matching extended-k-mer contexts. lrsim uses a model derived from alignment statistics for read lengths and indel-size structure, with user-specified overall error parameters. NanoSim fits read length, alignment, Q-score and error distributions from aligned reads, using Markov models for error structure. PBSIM3 was run in sample mode, where it copies read lengths and Q-score strings from real reads and uses a user-specified error-type ratio. SimLoRD is based on a PacBio circular consensus sequencing (CCS) pass-count model; in this study, we disabled CCS-style behaviour to better approximate ONT sequencing, sampled read lengths from the training reads and supplied error parameters manually.

3.3. Read length distribution

LongISLND, lrsim, NanoSim, PBSIM3 and SimLoRD all used the training reads to model or sample read lengths, allowing them to approximate the empirical ONT read length distribution. Therefore, their simulated read length distributions were similar to the real reads (Table S1 and Figure S3).

In contrast, Badread generates read lengths from a gamma distribution defined by mean read length and standard deviation. It was therefore the only tool which did not closely replicate the empirical distribution.

3.4. Empirical and reported Q-score distributions

Each read that could be aligned to the reference genome was assigned an empirical Q-score, indicating its true accuracy. Each read also had a reported Q-score calculated from its FASTQ quality values. Comparing the joint and marginal distributions of these two Q-scores therefore provided a direct visual measure of how closely each simulated dataset resembled the real reads. Summary statistics of the read accuracy distributions and alignments are in Table S2, and metrics after removing reads with a reported Q-score of $<$10 are in Table S3.

Only PBSIM3 was able to closely reproduce the signature of the real reads, including their distinctive bimodal distribution with a lower peak at ∼Q8 and a higher peak at ∼Q23 (Figure 1). This likely reflects PBSIM3's sampling-based strategy: it copies read lengths and per-base FASTQ quality strings from training reads, samples template sequences of matching length from the reference genome, and introduces errors according to the sampled Q-scores. PBSIM3's reads only departed from the real reads in a few subtle ways: the real read distributions extended to lower qualities than the PBSIM3 reads, and the real reads had more outliers where empirical and reported Q-scores were in stark disagreement (e.g. reported Q20 but empirical Q10).

All other tools departed from the real-read Q-score distributions. Badread had a wide spread of empirical Q-scores, but its reported Q-scores rarely exceeded Q20. LongISLND produced very narrow distributions, with most reads in the Q14–15 range. lrsim produced a range of empirical Q-scores but did not model reported Q-scores at all, using the same Phred score character for every base in every read. NanoSim produced narrow distributions for both empirical and reported Q-scores. SimLoRD produced wide distributions, but it used only a single Phred score character in each read, leading to a discrete reported Q-score distribution.

When Q-scores were analysed at the per-base level rather than the whole-read level, PBSIM3 was again the most realistic simulator. Badread, LongISLND and PBSIM3 all broadly reproduced the distribution of reported base Q-scores for correctly called bases (Figure S4), but only PBSIM3 also closely matched the distribution of reported base Q-scores for error-associated bases (Figure S5) and for the Q-score calibration curve (Figure S6).

Table 1. Key characteristics of the six evaluated ONT read simulators.

Tool	Tested version	Intended data type	Read modelling approach	Read length	Sequence errors	Q-scores
Badread	0.4.2 (2024)	All long-read platforms	Draws fragment lengths from a gamma distribution and target accuracies from a normal or beta distribution. Introduces errors by replacing k-mers according to a trained k-mer alternative model, then assigns Q-scores based on the local alignment around each base.	Parametric	Trained	Trained
LongISLND	0.9.5 (2017)	All long-read platforms	Builds a non-parametric model indexed by extended k-mers, including homopolymer length and flanking context. During simulation, each local sequence context is assigned an emitted base and Q-score from matching training-read contexts.	Sampled	Trained	Trained
lrsim	0.7 (2025)	ONT	Uses a model file extracted from `samtools stats` output to reproduce the empirical read-length distribution and indel-size structure; overall error rate, read-to-read error variability and insertion/deletion/substitution ratios are supplied separately as command-line parameters.	Sampled	Parametric	Constant across all reads
NanoSim	3.2.3 (2025)	ONT	Fits statistical distributions to aligned reads, including read-length profiles, alignment structure, match/indel lengths and Q-scores, plus Markov models for error types and match runs; optional homopolymer modelling adds expansion/contraction profiles.	Trained	Trained	Trained
PBSIM3	3.0.5 (2025)	All long-read platforms	Sampling-based simulation randomly selects real reads and copies their lengths and complete FASTQ quality strings, then samples template sequence from the reference and introduces errors from per-base Q-scores using a user-specified substitution/insertion/deletion ratio.	Sampled	Q-score based + parametric	Sampled
SimLoRD	1.0.4 (2020)	PacBio	Read quality depends on a modelled number of PacBio CCS sequencing passes through each fragment. In this study, pass-based CCS behaviour was disabled, read lengths were sampled from real ONT reads and substitution, insertion and deletion rates were set manually.	Sampled	Parametric	Constant per read

3.5. Error profiles

Errors in the real reads were strongly context dependent: the 192 3-mer substitution error rates spanned nearly three orders of magnitude, from 0.0059% to 3.6% (Figure 2). This is consistent with ONT sequencing's raw-current signal (the "squiggle"), in which some k-mers produce less distinct signals and are therefore more prone to basecalling errors[34]. Badread and LongISLND were the only simulators to reproduce this broad pattern, although both produced elevated error rates for substitution types that were rare in the real reads. In contrast, lrsim, NanoSim, PBSIM3 and SimLoRD assigned roughly uniform error rates to all 3-mer substitution types, failing to reproduce the context-specific substitution errors seen in the real reads.

Homopolymer error rates in the real ONT reads rose at an increasing rate as homopolymers became longer (Figure 3). LongISLND reproduced this overall pattern most closely, although its curve showed an abrupt drop in error rate from 4-mer to 5-mer homopolymers due to a switch from per-base to whole-homopolymer sampling at length 5. All other tools reproduced this curvature poorly, with error rates that increased linearly with homopolymer length.

3.6. Assembly accuracy

Assembly accuracy vs read depth plots are in Figure S7. For the real reads, assembly accuracy improved with depth, up to ∼30× depth. Assemblies of real reads only achieved perfect accuracy (zero errors) three times. Assemblies of LongISLND simulated reads best matched this pattern, however Raven assemblies of LongISLND reads had notably lower accuracy. Badread, lrsim, PBSIM3 and SimLoRD all produced assemblies that were too accurate (frequently with no detected errors), indicating poor or incomplete modelling of systematic errors in ONT reads. NanoSim simulated reads had strong assembler-specific effects, with Flye assemblies often having zero errors but metaMDBG assemblies were very low accuracy.

3.7. Computational resources

Computational time and memory usage for each tool are listed in Table S6. Badread was the slowest tool tested, taking over 9 hours to complete its training step and over 30 minutes to complete its simulation step. When considering all steps, PBSIM3 was the overall fastest tool, taking ∼1.5 minutes to complete. When considering only the simulation step, lrsim was the fastest, completing in ∼1 second. NanoSim used the most memory, peaking at over 59 GB during its training step. PBSIM3 was the most memory efficient, using only ∼20 MB.

4. Discussion

This study benchmarked six ONT-compatible read simulators against contemporary R10.4.1 ONT real reads, with the goal of identifying which tools best reproduce empirical read characteristics. That is, we judged simulators by how closely their outputs




Figure 1: Empirical and reported read Q-scores. In each panel, the central scatter plot shows each aligned read's reported Q-score (x-axis) and empirical Q-score (y-axis). The reported read Q-score was calculated from the FASTQ quality string by converting base Q-scores to error probabilities, averaging those probabilities across the read, and converting the mean error probability back to a Q-score. Only the aligned region of the read was used to calculate reported read Q-score. The empirical read Q-score was calculated from the read-to-reference alignment identity, converted to Q-score. The top y-axis tick is labelled ∞ because some reads contained no errors, giving an empirical error rate of zero and therefore an infinite empirical Q-score. The top marginal histogram for each panel shows the distribution of reported read Q-scores, and the right marginal histogram shows the distribution of empirical read Q-scores. Histogram bars are weighted by aligned read length, so the marginal axes represent the number of aligned read bases in each bin. A simulator is more realistic if its plot closely matches that of the real reads. Wasserstein distances to quantify the difference in distributions are available in Table S4.

matched real reads across features relevant to downstream use, such as method development and pipeline validation. Our results demonstrate that no simulator perfectly captures all aspects of modern ONT reads, but PBSIM3, Badread and LongISLND performed best, depending on the key metric considered.

PBSIM3 performed strongly overall and was the most realistic simulator for several key properties of the read sets. Its simulated reads closely matched the real data in read length, empirical read accuracy and FASTQ Q-scores (Figure 1), making it a practical choice for users who want simulated datasets that resemble real ONT whole-genome sequencing output in broad terms. This realism likely comes from its sampling-based approach, where quality strings are copied from empirical data rather than generated de novo. However, a limitation of PBSIM3 was that it was less successful at reproducing the error profile of the real data (Figures 2 and 3).




Figure 2: Substitution rates by 3-mer context. Simulated vs real error rates for the 192 distinct 3-mer substitution types, in which only the middle base changes. Each point represents one 3-mer substitution. Real-read error rates range from 0.0059% (`CTG→CGG`) to 3.6% (`CGA→CAA`). A simulator is more realistic if the points lie close to the diagonal dashed line of equality. Mean absolute error distances to quantify the difference in distributions are available in Table S4.

Badread offers users parametric control over the simulated reads, which can be valuable when specific read-set properties are needed. This flexibility came at the expense of realism: its read length and accuracy distributions deviated from those of the real reads (Figures S3 and 1). Badread modelled substitution errors well (Figure 2) but captured homopolymer-length errors less well (Figure 3). Further, as Badread is implemented entirely in Python, it was slower to run than other tools.

LongISLND performed well at modelling substitutions (Figure 2), error rates in longer homopolymers (3) and reproducing assembly errors (Figure S7). However, its distributions of empirical and reported read Q-scores were unrealistically narrow, limiting its potential use as a simulator (Figure 1).

The remaining simulators were less suitable for realistic ONT read simulation. lrsim and SimLoRD were limited by their treatment of FASTQ Q-scores: lrsim assigns the same Q-score to every base in the entire output, while SimLoRD assigns a single Q-score per read. This makes both tools unsuitable for applications which use per-base Q-scores. NanoSim produced an unrealistically narrow distribution of read-level accuracy (Figure 1) and an unrealistically broad distribution of base-level accuracy (Figures S4 and S5).

In this study, we did not exhaustively explore every possible configuration of each tool. We aimed to run each one in the way that we judged most likely to maximise overall realism. Other configurations may have produced different results. For example, PBSIM3 includes an error-model HMM mode that may improve error realism, but this comes with trade-offs: read lengths and Q-scores are then generated from parametric models rather than sampled from empirical data, and it does not support training a custom model on user-provided data.

Another limitation is that our benchmarking focused only on WGS. Other applications of long-read sequencing, such as transcriptomics, amplicons and metagenomics, may prioritise different properties of simulated reads. We also did not assess how reads were distributed across the reference genome. Real sequencing datasets may show positional biases in read start sites or coverage, arising from library preparation, sequence composition or other experimental factors, and these biases could be important for some downstream analyses.

This study used a single *Listeria innocua* genome, sequenced using an R10.4.1 ONT flow cell and basecalled with Dorado's `sup@v5.2.0` model. This dataset was a practical choice because its highly accurate reference genome allowed for detailed analyses, and its small genome size limited computational requirements. Our findings are limited to the dataset and simulator configurations tested. Although the metrics we assessed are not specific to bacterial genomics, it remains to be evaluated whether the conclusions of this study generalise more broadly. Future work could test these simulators on other organisms (e.g. humans), sequencing chemistries, basecalling models and platforms (e.g. PacBio HiFi).

5. Conclusions

In the setting of ONT bacterial WGS, no simulator produced reads that looked realistic across all tested metrics. When used in its sampling-based mode, PBSIM3 is likely the best choice for many users. It was easy to run, fast to execute and performed well on several key properties of ONT whole-genome sequencing data, particularly read length and read-level accuracy metrics, although it failed to model error types well. Badread did better at modelling some error types and offers parametric control over the




Figure 3: Homopolymer error rates. Homopolymer error rate as reported by Pomoxis, plotted as a function of homopolymer length for real reads and six ONT read simulators. Error rate is defined here as the fraction of reads in which the homopolymer length was not represented correctly. Observation counts and numbers of distinct reference loci are in Table S5. Homopolymers of length 10 were excluded from this plot due to there being only two instances in the reference genome. A simulator is more realistic if its curve closely matches that of the real reads. Mean absolute error distances to quantify the difference in distributions are available in Table S4.

simulated read set, but at the cost of less realism and substantially slower run times. LongISLND modelled some error types well, but its simulated reads had an unrealistically narrow accuracy distribution. The remaining simulators each showed limitations that make them less suitable for general use. More broadly, the fact that no tool performed well on all metrics highlights an opportunity for improved long-read simulators that can combine realistic read-level distributions with more faithful modelling of sequencing errors.

6. Availability of data and materials

Detailed commands, custom scripts and complete analysis outputs are publicly available at: `github.com/mtaouk/ONT-Read-Simulator-Benchmarking`.

The reference genome and full read sets used in this study are available at: `doi.org/10.26188/32194977`.

7. Competing interests

The authors declare that there are no conflicts of interest.

8. Funding

This work was supported by the Australian Research Council Discovery Early Career Researcher Award [DE250100677 to R.R.W.], Emerging Leadership Fellowship from the National Health and Medical Research Council of Australia [2041653 to D.J.I.] and the Research Accelerator Fund – Bioinformatics 2024 generously supported by Doherty Institute philanthropic donations [to D.J.I.].

9. Authors' contributions

R.R.W. conceived the study. M.L.T. and R.R.W. performed analyses and drafted the manuscript. D.J.I. and R.R.W. supervised the work, contributed to study design and interpretation of results, and revised the manuscript critically. All authors read and approved the final manuscript.

References

1. Miten Jain, Hugh E Olsen, Benedict Paten, and Mark Akeson. The Oxford Nanopore MinION: delivery of nanopore sequencing to the genomics community. *Genome Biology*, 2016. doi:10.1186/s13059-016-1103-0.
2. Oxford Nanopore Technologies. Nanopore sequencing chemistry and basecalling updates, 2024.
3. Ryan R Wick, Louise M Judd, and Kathryn E Holt. Performance of neural network basecalling tools for Oxford Nanopore sequencing. *Genome Biology*, 2019. doi:10.1186/s13059-019-1727-y.
4. Franka J Rang, Wigard P Kloosterman, and Jeroen De Ridder. From squiggle to basepair: computational approaches for improving nanopore sequencing read accuracy. *Genome Biology*, 2018. doi:10.1186/s13059-018-1462-9.
5. Yunhao Wang, Yue Zhao, Audrey Bollas, Yuru Wang, and Kin Fai Au. Nanopore sequencing technology, bioinformatics and applications. *Nature Biotechnology*, 2021. doi:10.1038/s41587-021-01108-x.
6. Bert Bogaerts, An Van den Bossche, Bavo Verhaegen, Laurence Delbrassinne, Wesley Mattheus, Stéphanie Nouws, Maxime Godfroid, Stefan Hoffman, Nancy HC Roosens, Sigrid CJ De Keersmaecker, et al. Closing the gap: Oxford Nanopore Technologies R10 sequencing allows comparable results to Illumina sequencing for SNP-based outbreak investigation of bacterial pathogens. *Journal of Clinical Microbiology*, 2024. doi:10.1128/jcm.01576-23.
7. Heba H Mostafa. An evolution of Nanopore next-generation sequencing technology: implications for medical microbiology and public health. *Journal of Clinical Microbiology*, 2024. doi:10.1128/jcm.00246-24.
8. Mantas Sereika, Rasmus Hansen Kirkegaard, Søren Michael Karst, Thomas Yssing Michaelsen, Emil Aarre Sørensen, Rasmus Dam Wollenberg, and Mads Albertsen. Oxford Nanopore R10.4 long-read sequencing enables the generation of near-finished bacterial genomes from pure cultures and metagenomes without short-read or reference polishing. *Nature Methods*, 2022. doi:10.1038/s41592-022-01539-7.
9. Ekaterina Avershina, Stephan A Frye, Jawad Ali, Arne M Taxt, and Rafi Ahmad. Ultrafast and cost-effective pathogen identification and resistance gene detection in a clinical setting using nanopore Flongle sequencing. *Frontiers in Microbiology*, 2022. doi:10.3389/fmicb.2022.822402.
10. Michael A Moso, George Taiaroa, Eike Steinig, Madiyar Zhanduisenov, Grace Butel-Simoes, Ivana Savic, Mona L Taouk, Socheata Chea, Jean Moselen, Jacinta O'Keefe, et al. Non-SARS-CoV-2 respiratory viral detection and whole genome sequencing from COVID-19 rapid antigen test devices: a laboratory evaluation study. *The Lancet Microbe*, 2024. doi:10.1016/S2666-5247(23)00375-0.
11. Dropen Sheka, Nikolay Alabi, and Paul MK Gordon. Oxford nanopore sequencing in clinical microbiology and infection

diagnostics. *Briefings in Bioinformatics*, 2021. doi:10.1093/bib/bbaa403.

12. Ryan R Wick, Benjamin P Howden, and Timothy P Stinear. Autocycler: long-read consensus assembly for bacterial genomes. *Bioinformatics*, 2025. doi:10.1093/bioinformatics/btaf474.
13. Ivan Sovic, Mile Šikić, Andreas Wilm, Shannon Nicole Fenlon, Swaine Chen, and Niranjan Nagarajan. Fast and sensitive mapping of nanopore sequencing reads with GraphMap. *Nature Communications*, 2016. doi:10.1038/ncomms11307.
14. Mircea Cretu Stancu, Markus J Van Roosmalen, Ivo Renkens, Marleen M Nieboer, Sjors Middelkamp, Joep De Ligt, Giulia Pregno, Daniela Giachino, Giorgia Mandrile, Jose Espejo Valle-Inclan, et al. Mapping and phasing of structural variation in patient genomes using nanopore sequencing. *Nature Communications*, 2017. doi:10.1038/s41467-017-01343-4.
15. Lovro Vrček, Xavier Bresson, Thomas Laurent, Martin Schmitz, Kenji Kawaguchi, and Mile Šikić. Geometric deep learning framework for de novo genome assembly. *Genome Research*, 2025. doi:10.1101/gr.279307.124.
16. Chen Yang, Justin Chu, René L Warren, and Inanç Birol. NanoSim: nanopore sequence read simulator based on statistical characterization. *GigaScience*, 2017. doi:10.1093/gigascience/gix010.
17. Yukiteru Ono, Michiaki Hamada, and Kiyoshi Asai. PBSIM3: a simulator for all types of PacBio and ONT long reads. *NAR Genomics and Bioinformatics*, 2022. doi:10.1093/nargab/lqac092.
18. Ryan R Wick. Badread: simulation of error-prone long reads. *Journal of Open Source Software*, 2019. doi:10.21105/joss.01316.
19. Bayo Lau, Marghoob Mohiyuddin, John C Mu, Li Tai Fang, Narges Bani Asadi, Carolina Dallett, and Hugo YK Lam. LongISLND: in silico sequencing of lengthy and noisy datatypes. *Bioinformatics*, 2016. doi:10.1093/bioinformatics/btw602.
20. Bianca K Stöcker, Johannes Köster, and Sven Rahmann. SimLoRD: simulation of long read data. *Bioinformatics*, 2016. doi:10.1093/bioinformatics/btw286.
21. AstraBert. simON-reads. https://github.com/AstraBert/simON-reads, 2025. GitHub repository.
22. CoREse. lrsim. https://github.com/CoREse/lrsim, 2025. GitHub repository.
23. Oxford Nanopore Technologies. Dorado. https://github.com/nanoporetech/dorado, 2025. GitHub repository.
24. Wei Shen, Shuai Le, Yan Li, and Fuquan Hu. SeqKit: a cross-platform and ultrafast toolkit for FASTA/Q file manipulation. *PLOS ONE*, 2016. doi:10.1371/journal.pone.0163962.
25. Heng Li. Minimap2: pairwise alignment for nucleotide sequences. *Bioinformatics*, 05 2018. doi:10.1093/bioinformatics/bty191.
26. Heng Li. On the definition of sequence identity, 2018.
27. Oxford Nanopore Technologies. Pomoxis. https://github.com/nanoporetech/pomoxis, 2024. GitHub repository.
28. Mikhail Kolmogorov, Jeffrey Yuan, Yu Lin, and Pavel A Pevzner. Assembly of long, error-prone reads using repeat graphs. *Nature Biotechnology*, 2019. doi:10.1038/s41587-019-0072-8.
29. Gaëtan Benoit, Robert James, Sébastien Raguideau, Georgina Alabone, Tim Goodall, Rayan Chikhi, and Christopher Quince. High-quality metagenome assembly from nanopore reads with nanoMDBG. *Nature Communications*, March 2026. doi:10.1038/s41467-026-69760-y.
30. Heng Li. Minimap and miniasm: fast mapping and de novo assembly for noisy long sequences. *Bioinformatics*, July 2016. Number: 14. doi:10.1093/bioinformatics/btw152.
31. Jim Shaw, Maximillian G. Marin, and Heng Li. High-resolution metagenome assembly for modern long reads with myloasm. *Nature Biotechnology*, March 2026. doi:10.1038/s41587-026-03053-z.
32. Robert Vaser and Mile Šikić. Time- and memory-efficient genome assembly with Raven. *Nature Computational Science*, May 2021. Number: 5. doi:10.1038/s43588-021-00073-4.
33. Giulio Formenti, Bonhwang Koo, Marco Sollitto, Jennifer Balacco, Nadolina Brajuka, Richard Burhans, Erick Duarte, Alice M Giani, Kirsty McCaffrey, Jack A Medico, Eugene W Myers, Patrik Smeds, Anton Nekrutenko, and Erich D Jarvis. Evaluation of sequencing reads at scale using rdeval. *Bioinformatics*, 09 2025. doi:10.1093/bioinformatics/btaf416.
34. Raga Krishnakumar, Anupama Sinha, Sara W. Bird, Harikrishnan Jayamohan, Harrison S. Edwards, Joseph S. Schoeniger, Kamlesh D. Patel, Steven S. Branda, and Michael S. Bartsch. Systematic and stochastic influences on the performance of the MinION nanopore sequencer across a range of nucleotide bias. *Scientific Reports*, February 2018. doi:10.1038/s41598-018-21484-w.

Supplementary Information

Supplementary methods are available at: `github.com/mtaouk/ONT-Read-Simulator-Benchmarking`.

Table S1. Read length statistics.

Dataset	Number of reads	Total bases (bp)	Min length (bp)	Max length (bp)	Mean length (bp)	N50 length (bp)
Real reads	53,093	297,265,978	5	826,029	5,599.0	8,994
Badread	53,180	297,256,127	1	78,973	5,589.6	10,558
LongISLND	53,956	297,851,844	37	181,950	5,520.3	8,758
lrsim	53,013	297,445,673	10	89,609	5,610.8	8,869
NanoSim	53,227	309,873,325	50	214,233	5,821.7	8,771
PBSIM3	53,503	297,258,351	93	107,108	5,555.9	8,784
SimLoRD	53,202	300,580,690	5	700,862	5,649.8	9,033

Table S2. Read accuracy and alignment statistics. For empirical and reported Q-scores, the mean and standard deviation (SD) values are weighted by aligned read length. Reads without any errors in their alignments have an empirical Q-score of Q∞ and were therefore excluded from the empirical Q-score mean and SD calculations. The "Unaligned reads" column shows the percentage of reads without any alignment to the reference genome. The "Unaligned bases" column shows the percentage of total read bases which were not part of each read's best alignment, e.g. from unaligned regions at the start or end of reads. Error types are expressed as percentages of all aligned erroneous bases, with insertions and deletions counted by length.

	Empirical Q-score		Reported Q-score		Error types				
Dataset	Mean	SD	Mean	SD	Substitutions	Insertions	Deletions	Unaligned reads	Unaligned bases
Real reads	18.98	6.07	19.24	5.84	40.1%	18.9%	41.0%	1.06%	1.88%
Badread	18.20	5.06	16.48	3.16	39.8%	17.9%	42.4%	6.44%	4.06%
LongISLND	14.69	0.34	14.39	0.18	42.1%	16.8%	41.1%	0.24%	0.01%
lrsim	16.06	4.64	14.00	0.00	43.8%	21.7%	34.4%	0.18%	0.02%
NanoSim	14.89	3.01	16.29	0.46	32.3%	12.7%	54.9%	1.14%	2.50%
PBSIM3	19.89	5.68	19.30	5.78	46.8%	13.8%	39.4%	0.19%	0.17%
SimLoRD	14.77	3.97	14.64	4.03	44.4%	17.9%	37.7%	0.90%	0.05%

Table S3. Read accuracy and alignment statistics after Q10 filtering. This table contains the same data as Table S2, but after reads with a reported Q-score of <10 removed.

	Empirical Q-score		Reported Q-score		Error types				
Dataset	Mean	SD	Mean	SD	Substitutions	Insertions	Deletions	Unaligned reads	Unaligned bases
Real reads	20.53	4.76	20.84	4.26	35.1%	18.2%	46.8%	0.40%	0.71%
Badread	18.71	4.63	16.86	2.71	38.0%	19.3%	42.7%	4.43%	2.87%
LongISLND	14.69	0.34	14.39	0.18	42.1%	16.8%	41.1%	0.24%	0.01%
lrsim	16.06	4.64	14.00	0.00	43.8%	21.7%	34.4%	0.18%	0.02%
NanoSim	14.88	3.00	16.29	0.45	32.3%	12.8%	54.9%	0.09%	0.66%
PBSIM3	21.33	4.32	20.78	4.35	46.1%	14.3%	39.6%	0.00%	0.08%
SimLoRD	15.53	3.53	15.43	3.54	43.1%	17.8%	39.1%	0.50%	0.02%

Table S4. Distances between simulated-read and real-read distributions. Distance metrics comparing the simulated reads to the real reads for the following distributions: read length (Figure S3), empirical read Q-score (Figure 1 y-axis), reported read Q-score (Figure 1 x-axis), correct base Q-score (Figure S4), error base Q-score (Figure S5), 3-mer substitutions (Figure 2) and homopolymer length errors (Figure 3). Smaller values indicate a closer match between the simulated-read and real-read distributions, and a value of zero would indicate perfect agreement.

For the read length and Q-score distributions, the values are Wasserstein-1 distances. Read lengths are weighted by full read length, and read Q-scores are weighted by aligned read length. Reported read Q-scores are calculated over the aligned interval, and reads without any errors in their alignments have an empirical Q-score of Q∞ and were therefore excluded from the empirical Q-score distance.

For the 3-mer substitutions and homopolymer-length errors, the values are mean absolute errors (MAE). For the 3-mer substitutions, these were calculated in $\log_{10}$ space to match the plots in Figure 2. For the homopolymer-length errors, 10-mers were excluded due to their low frequency (Table S5).

Simulator	Read length	Empirical read Q-score	Reported read Q-score	Correct base Q-score	Error base Q-score	3-mer substitutions	Homopolymer errors
Badread	3381.92	1.54	3.47	0.69	4.57	0.161	3.40
LongISLND	2264.51	6.34	6.68	0.71	7.62	0.332	4.46
lrsim	2413.46	3.55	7.01	23.98	7.70	0.652	5.87
NanoSim	2484.42	4.83	5.49	9.16	8.07	0.547	4.90
PBSIM3	2430.03	0.92	0.07	0.10	0.51	0.541	4.22
SimLoRD	2570.21	4.43	4.74	22.02	4.60	0.720	8.98

Table S5. Homopolymer counts.

Homopolymer length (bp)	Reference genome	Real reads	Badread	LongISLND	lrsim	NanoSim	PBSIM3	SimLoRD
3	119,016	11,729,323	11,494,777	12,017,356	11,957,966	12,307,437	11,964,750	12,138,826
4	46,166	4,543,083	4,456,504	4,652,688	4,631,860	4,767,371	4,634,121	4,707,153
5	18,220	1,780,934	1,761,228	1,837,558	1,829,352	1,882,221	1,828,026	1,852,669
6	6,826	664,649	657,329	688,895	684,970	705,043	684,622	696,158
7	2,607	249,186	250,785	262,156	260,439	267,959	261,605	265,312
8	269	23,891	25,920	26,490	26,778	27,114	26,821	27,244
9	22	1,762	1,929	1,867	2,157	1,922	1,848	1,937
10	2	139	173	115	192	112	143	126

Table S6. Computational resources. Wall-clock execution time and maximum RAM usage for training and simulation commands. PBSIM3 and SimLoRD do not have a separate training step and so only list simulation times. All tools were run on a server with Dual AMD EPYC 7742 CPUs, 128 cores (256 threads) 503 GB RAM, running Red Hat Enterprise Linux 10.2.

Commands were run with 16 threads when possible. lrsim (simulation step) and NanoSim support multithreading and were run using 16 threads. Badread, LongISLND, lrsim (training step), PBSIM3 and SimLoRD do not support multithreading and were therefore run with one thread, but all read alignment commands were run with 16 threads.

	Training		Simulation	
Tool	Elapsed time (h:m:s)	Peak memory (GB)	Elapsed time (h:m:s)	Peak memory (GB)
Badread	9:01:56	12.99	0:31:30	0.42
LongISLND	0:14:57	6.39	0:04:26	14.49
lrsim	0:03:18	6.21	0:00:01	0.13
NanoSim	0:38:24	59.07	0:00:28	0.51
PBSIM3	—	—	0:01:32	0.02
SimLoRD	—	—	0:02:47	0.19




Figure S1: NanoSim homopolymer modes. To test NanoSim's homopolymer-length modelling, we ran NanoSim's read modelling step (`read_analysis.py genome`) using `-hp --min_homopolymer_len` h and NanoSim read simulation (`simulator.py genome`) using `-hp -k` h. We tested values of h ranging from 3–5 (values of 6 or greater caused NanoSim to crash), as well as no homopolymer modelling.

Despite intending to improve the realism of homopolymer-length errors, this modelling produced unrealistically low error rates at homopolymers at and above the value of h. This appears to result from a bug in NanoSim's training that biases its homopolymer model towards unrealistically low error rates. For the main results in this manuscript, we therefore did not use NanoSim's homopolymer length modelling.




Figure S2: PBSIM3 homopolymer modes. PBSIM3 contains a `--hp-del-bias` option which aims to simulate homopolymer deletion bias in ONT reads. To test this, we ran PBSIM3 using `--hp-del-bias` h using values of h ranging from 1–10 (the full range for this option). While higher values of h did produce more errors in longer homopolymers, it did not reproduce the inflection of the curve seen with the real reads. For the main results in this manuscript, we used `--hp-del-bias 5` since that minimised the discrepancy between the real read's homopolymer errors and PBSIM3's homopolymer errors (weighting the discrepancy using homopolymer occurrences).




Figure S3: Read length distributions. Histograms are shown for the real and simulated datasets. The x-axis shows read length in 1 kbp bins. Histogram bars are weighted by read length, so the y-axis represents the total number of bases contributed by reads in each length bin rather than the number of reads. A simulator is more realistic if its histogram closely matches that of the real reads. Wasserstein distances to quantify the difference in distributions are available in Table S4.




Figure S4: Correct base Q-score distribution. Reported base Q-score distributions for correctly called bases in the real and simulated datasets. In each panel, bars show the number of bases in each reported base Q-score bin. A base was counted as correct only if it matched the reference and was not adjacent to a deletion in the alignment. A simulator is more realistic if its histogram closely matches that of the real reads. Wasserstein distances to quantify the difference in distributions are available in Table S4.




Figure S5: Error-associated base Q-score distribution. Reported base Q-score distributions for error-associated bases in the real and simulated datasets. In each panel, bars show the number of error-associated bases in each reported base Q-score bin. Error-associated bases were defined as mismatches and insertions, plus deletion-associated events estimated as half the number of matched bases adjacent to deletions, because deleted bases themselves have no reported Q-score. A simulator is more realistic if its histogram closely matches that of the real reads. Wasserstein distances to quantify the difference in distributions are available in Table S4.




Figure S6: Q-score calibration curve. Per-base Q-score calibration for real and simulated datasets. Each point represents one reported base Q-score bin (x-axis), and its y-value is the empirical base Q-score calculated from the observed error rate among bases with that reported Q-score. For each Q-score bin, the empirical error rate was calculated as $(X + I + D/2)/(M + X + I + D/2)$, where X is the count of mismatching bases, I is the count of inserted bases, D is the count of matching bases adjacent to a deletion (regardless of the number of deleted bases) and M is the count of matching bases not adjacent to a deletion. The dashed diagonal indicates perfect calibration, where reported and empirical base Q-scores are equal.




Figure S7: Assembly accuracy. For each test read set, we randomly subsampled them to depths ranging from 1–50×. Each subsampled set was assembled with five assemblers: Flye, metaMDBG, miniasm+Minipolish, myloasm and Raven. Assembly accuracy was quantified by taking the longest contig (≥2 Mbp), trimming 1000 bp from each end (to remove assembly artefacts that can arise from non-circular read simulation), aligning to the reference genome and dividing the matching bases by the alignment length. Assemblies were excluded from this plot if their longest contig was shorter than 2 Mbp or if that contig (after trimming) did not produce a single end-to-end alignment. A simulator is more realistic if its plot closely matches that of the real reads.

While real reads rarely produced an error-free assembly (Q∞), simulated reads from Badread, lrsim, NanoSim, PBSIM3 and SimLoRD often did, demonstrating that they insufficiently model systematic read errors. LongISLND was best able to mimic the accuracy-vs-depth relationship of the real reads. Some assemblers performed poorly on reads from certain simulators: Raven with LongISLND, metaMDBG with NanoSim, myloasm with NanoSim and Raven with NanoSim.

Complete assemblies are drawn as filled points, while incomplete assemblies are drawn as hollow points. An assembly was considered complete if it had exactly two contigs, one with a length matching the chromosome (±1%) and the other with a length matching the plasmid (±1%). Considering read sets ≥20× depth, real reads produced a complete assembly 61.3% of the time, Badread 55.5%, LongISLND 10.3%, lrsim 22.6%, NanoSim 14.8%, PBSIM3 14.8% and SimLoRD 6.5%. Of all simulators, only Badread was able to run in a circular-aware mode, i.e. it generated reads that span the start/end junction of the reference sequences. This avoids breaks in read coverage at reference boundaries and likely contributed to its higher assembly completion rate compared with the other tools. While NanoSim does have a similar feature (`-dna_type circular`), this does not support reference with multiple sequences, and so it was not usable in this study.