



Inspiring Excellence

BRAC University

BRACU_DireCrows

MTB Ishmam

15 July, 2026

1 Contest

2 Mathematics

3 Data structures

4 Numerical

5 Number theory

6 Combinatorial

7 Graph

8 Geometry

9 Strings

10 Various

11 Techniques

Contest (1)

instructions.txt

```
1. vi ~/.bashrc: export PATH="$PATH:$HOME/cp"
2. mkdir -p ~/cp/{bits,t/bits} && cd ~/cp && vi cf
3. cp cf run; vi run; vi hash.sh; vi stress.sh
4. chmod +x cf run hash.sh stress.sh; exec bash
5. touch t.cpp in out exp bits/stdc++.h
6. subl . -> Write t.cpp and bits/stdc++.h
7. copy t.cpp as code.cpp & bits to t
8. cd t&&touch gen.cpp bf.cpp in out exp
----- Sublime -----
1. Tools->Build System->New Build System
{"shell_cmd": "~/cp/run $file_base_name",
"working_dir": "$file_path"}
2. Preferences->Key Bindings
{"keys": ["alt+shift+0"],
"command": "set_max_columns",
"args": { "columns": 2 }}
----- Windows -----
1. Open File Exp->Folder Options->View-> Uncheck Hide exten...
2. Add using cmd: setx "PATH=%PATH%;%USERPROFILE%\cp;C:\Program Files\CodeBlocks\MinGW\bin"
3. Check PATH: cmd: echo %PATH% | PowerShell: echo $env:PATH
4. CodeBlocks MinGW: fsanitize unavailable :(
```

cf.sh

```
#!/bin/bash
code=$1
```

```
1 g++ ${code}.cpp -o $code -std=c++20 -g -DDeBuG
   -Wall -Wshadow -fsanitize=address,
   undefined && ./ $code < in > out && diff
   exp out && echo -e "\nAC"
3 hash.sh
   8 lines
4 #!/bin/sh
8 cpp_cmd=${CPP:-cpp}
10 if ! "$cpp_cmd" -dD -P -fpreprocessed </dev/
   null >/dev/null 2>&1 && command -v cpp-15
   >/dev/null 2>&1; then
12   cpp_cmd=cpp-15
14 fi
16 "$cpp_cmd" -dD -P -fpreprocessed | tr -d '[:
   space:]' | md5sum | cut -c-6
18 stdc++.h
   90f4a7, 29 lines
20 #include <bits/stdc++.h>
22 using namespace std;
24 #define TT template <typename T
26 TT,typename=void> struct cerrok:false_type {};
28 TT> struct cerrok <T, void_t<decltype(cerr <<
   declval<T>()) >> : true_type {};
30 TT> constexpr void p1 (const T &x);
32 TT, typename V> void p1(const pair<T, V> &x) {
   cerr << "{"; p1(x.first); cerr << ", ";
   p1(x.second); cerr << "}";
   }
34 TT> constexpr void p1 (const T &x) {
   if constexpr (cerrok<T>::value) cerr << x;
   else { int f = 0; cerr << '{';
   for (auto &i: x)
   cerr << (f++ ? ", " : ""), p1(i);
   cerr << "}";
   }
36 void p2() { cerr << "]\n"; }
38 TT, typename... V> void p2(T t, V... v) {
   p1(t);
   if (sizeof...(v)) cerr << ", ";
   p2(v...);
   }
40 #ifdef DeBuG
42 #define dbg(x...) {cerr << "\t\e[93m"<<
   _func_<<":"<< _LINE_<<[" " << #x << " ]
   = ["; p2(x); cerr << "\e[0m";}
44 #endif
46 template.cpp
48 Description: Contest submission template.
49 "bits/stdc++.h"
   0bdd7b, 34 lines
51 using namespace std;
53 // #include <ext/pb_ds/assoc.container.hpp>
55 // #include <ext/pb_ds/tree_policy.hpp>
57 // using namespace __gnu_pbds;
59 #ifndef DeBuG
61 #define dbg(...)
63 #define TT template <typename T
65 #endif
67 #define TU TT, typename U>
69 #define int int64_t
71 #define endl '\n'
```

```
#define sz(x) (int) (x).size()
#define all(x) begin(x), end(x)
#define rep(i,a,b) for(int i=a; i<(b); ++i)
TU bool chmin(T&a,U b){return a>b?(a=b,1):0;}
TU bool chmax(T&a,U b){return a<b?(a=b,1):0;}
TT> using V = vector<T>; using vi = V<int>;
using ll = long long; using pii=pair<int,int>;
using vb = V<bool>; using vvi = V<vi>;
// TT> using oset = tree<T, null_type, less<T
   >, rb_tree_tag,
   tree_order_statistics_node_update>;
mt19937_64 rng(chrono::steady_clock::now().
   time_since_epoch().count());
#define rand(l, r) uniform_int_distribution<ll
   >(l, r) (rng)
73 void solve(int cs) {
   }
75 signed main() {
   cin.tie(0)->sync_with_stdio(0);
   int tc = 1;
   // #ifdef DeBuG
   cin >> tc;
   // #endif
   for(int cs = 1; cs <= tc; cs++)solve(cs);
   }
77 stress.sh
   14 lines
79 #!/bin/bash
81 cf gen > in # input generator
83 cf bf < in > exp # bruteforce
85 cf code < in > out # buggy code name
87 for ((i = 1; ; ++i)) do
   echo $i
   ./gen > in
   ./bf < in > exp
   ./code < in > out # buggy code name
   diff -w exp out || break
89 done
91 # Shows expected first, then user
93 notify-send "bug found!!!!"
95 rte.sh
   14 lines
97 #!/bin/bash
99 cf gen > in # input generator
101 cf code < in > out 2> err # file to rte test
103 for ((i = 1; ; ++i)) do
   echo $i
   ./gen > in
   ./code < in > out 2> err
   if [ $? -ne 0 ] || grep -q -E "
   AddressSanitizer|runtime error" err;
   then
   echo "RTE found!!!"
   cat err
   break
   fi
105 done
107 cf.bat
   5 lines
109 @echo off
111 setlocal
113 set "PATH=%PATH%;%USERPROFILE%\cp;C:\Program
   Files\CodeBlocks\MinGW\bin"
```

```
set prog=%1
g++ %prog%.cpp -o %prog% -DDeBuG -std=c++17 -g
-Wall -Wshadow && .\%prog% < in > out &&
fc exp out && echo AC
115 stress.bat
   9 lines
117 @echo off&setlocal
119 set "PATH=%PATH%;%USERPROFILE%\cp;C:\Program
   Files\CodeBlocks\MinGW\bin"
121 set i=1
123 :loop
125 echo %i%&gen>in&bf<in>exp&code<in>out
127 fc /w exp out>nul||goto bad
129 set /a i+=1&goto loop
131 :bad
133 echo Bug found&type exp&echo.&type out
135 Mathematics (2)
137 2.1 Equations
139 The extremum of a quadtratic is given by
141 x = -b/2a.
143 Cramer: Given an equation Ax = b, the
145 solution to a variable xi is given by
147 xi = det A'_i / det A [where A'_i is A with the i'th column
   replaced by b.]
149 Vieta: Let P(x) = a_n x^n + ... + a_0, be a
151 polynomial with complex coefficients and degree
153 n, having complex roots r_n, ..., r_1. Then for any
155 integer 0 ≤ k ≤ n,
157 ∑_{1≤i_1<i_2<...<i_k≤n} r_{i_1}r_{i_2}...r_{i_k} = (-1)^k a_n / a_{n-k}
159 Rational Root Theorem: If p/q is a reduced
161 rational root of a polynomial with integer
163 coeffs, then p | a_0 and q | a_n
165 2.2 Ceils and Floors
167 For x, y ∈ ℝ, m, n ∈ ℤ:
169 • ⌊x⌋ ≤ x < ⌊x⌋ + 1; ⌊x⌋ - 1 < x ≤ ⌊x⌋
171 • -⌊x⌋ = ⌈-x⌉; -⌈x⌉ = ⌊-x⌋
173 • ⌊x + n⌋ = ⌊x⌋ + n, ⌈x + n⌉ = ⌈x⌉ + n
175 • ⌊x⌋ = m ⇔ x - 1 < m ≤ x < m + 1
177 • ⌈x⌉ = n ⇔ n - 1 < x ≤ n < x + 1
179 • If n > 0, ⌊(x+m)/n⌋ = ⌊(x+m)/n⌋
181 • If n > 0, ⌈(x+m)/n⌉ = ⌈(x+m)/n⌉
183 • If n > 0, ⌊(x/m)⌋ = ⌊x/mn⌋
185 • If n > 0, ⌈(x/m)⌉ = ⌈x/mn⌉
187 • For m, n > 0, ∑_{k=1}^{n-1} ⌊km/n⌋ = ((m-1)(n-1)+gcd(m,n)-1)/2
```

2.3 Recurrences

If $a_n = c_1a_{n-1} + \cdots + c_ka_{n-k}$, and $r_1, \ldots, r_k$ are distinct roots of $x^k - c_1x^{k-1} - \cdots - c_k$, there are $d_1, \ldots, d_k$ s.t.

$$a_n = d_1r_1^n + \cdots + d_kr_k^n.$$

Non-distinct roots r become polynomial factors, e.g. $a_n = (d_1n + d_2)r^n$.

2.4 Trigonometry

$$\sin(v+w) = \sin v \cos w + \cos v \sin w$$

$$\cos(v+w) = \cos v \cos w - \sin v \sin w$$

$$\tan(v+w) = \frac{\tan v + \tan w}{1 - \tan v \tan w}$$

$$\sin v + \sin w = 2 \sin \frac{v+w}{2} \cos \frac{v-w}{2}$$

$$\cos v + \cos w = 2 \cos \frac{v+w}{2} \cos \frac{v-w}{2}$$

$$(V+W)\tan(\frac{v-w}{2}) = (V-W)\tan(\frac{v+w}{2})$$

V, W are sides opposite to angles v, w .

$$a \cos x + b \sin x = r \cos(x - \phi)$$

$$a \sin x + b \cos x = r \sin(x + \phi)$$

$$\text{where } r = \sqrt{a^2 + b^2}, \phi = \text{atan2}(b, a).$$

2.5 Geometry

2.5.1 Triangles

Side lengths: a, b, c

$$\text{Semiperimeter: } p = \frac{a+b+c}{2}$$

$$\text{Area: } A = \sqrt{p(p-a)(p-b)(p-c)}$$

$$\text{Circumradius: } R = \frac{abc}{4A}$$

$$\text{Inradius: } r = \frac{A}{p}$$

Length of median (divides triangle into two equal-area triangles):

$$m_a = \frac{1}{2}\sqrt{2b^2 + 2c^2 - a^2}$$

Length of bisector (divides angles in two):

$$s_a = \sqrt{bc[1 - (a/(b+c))^2]}$$

Law of sines, cosines & tangents:

$$\frac{\sin \alpha}{a} = \frac{\sin \beta}{b} = \frac{\sin \gamma}{c} = \frac{1}{2R}.....(1)$$

$$a^2 = b^2 + c^2 - 2bc \cos \alpha.....(2)$$

$$\frac{a+b}{a-b} = \frac{\tan((\alpha+\beta)/2)}{\tan((\alpha-\beta)/2)}.....(3)$$

2.5.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux


$$F = b^2 + d^2 - a^2 - c^2:$$

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and

$$A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$$

2.5.3 Spherical coordinates



$$\begin{aligned} x &= r \sin \theta \cos \phi & r &= \sqrt{x^2 + y^2 + z^2} \\ y &= r \sin \theta \sin \phi & \theta &= \text{acos}(z/\sqrt{x^2 + y^2 + z^2}) \\ z &= r \cos \theta & \phi &= \text{atan2}(y, x) \end{aligned}$$

2.6 Derivatives/Integrals

$$\frac{d}{dx} \arcsin x = \frac{1}{\sqrt{1-x^2}} \qquad \frac{d}{dx} \arccos x = -\frac{1}{\sqrt{1-x^2}}$$

$$\frac{d}{dx} \tan x = 1 + \tan^2 x \qquad \frac{d}{dx} \arctan x = \frac{1}{1+x^2}$$

$$\int \tan ax = -\frac{\ln |\cos ax|}{a} \qquad \int xe^{ax} dx = \frac{e^{ax}}{a^2}(ax-1)$$

$$\int e^{-x^2} = \frac{\sqrt{\pi}}{2} \text{erf}(x) \qquad \int x \sin ax = \frac{\sin ax - ax \cos ax}{a^2}$$

$$\int_a^b f(x)g(x)dx = [F(x)g(x)]_a^b - \int_a^b F(x)g'(x)dx$$

2.7 Sums

$$c^a + c^{a+1} + \cdots + c^b = \frac{c^{b+1} - c^a}{c - 1}, c \neq 1$$

$$1^4 + 2^4 + 3^4 + \cdots + n^4 = S_2 \times \frac{3n^2 + 3n - 1}{5} = S_4$$

$$b \sum_{k=0}^{n-1} (a+kd)r^k = \frac{ab - (a+nd)br^n}{1-r} + \frac{dbr(1-r^n)}{(1-r)^2}$$

To compute $1^k + \ldots + n^k$ in $\mathcal{O}(k \lg k + k \lg MOD)$ compute first $t = k + 2$ sums $y_1, \ldots, y_t$, then interpolate. Let $P = \prod_{i=1}^t (n-i)$. Then answer for n is

$$\sum_{i=1}^t \frac{P}{n-i} \cdot \frac{(-1)^{t-i} y_i}{(i-1)!(t-i)!}$$

Also $S_k = \frac{1}{k+1} \sum_{j=0}^k (-1)^j \binom{k+1}{j} B_j n^{k+1-j}$ where B_i are Bernoulli numbers.

2.8 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \ldots, (-\infty < x < \infty)$$

$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \ldots, (-1 < x \leq 1)$$

$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \ldots, (-1 \leq x \leq 1)$$

$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \ldots, (-\infty < x < \infty)$$

$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \ldots, (-\infty < x < \infty)$$

$$(1-x)^{-r} = \sum_{i=0}^{\infty} \binom{r+i-1}{i} x^i, (r \in \mathbb{R})$$

2.9 Bitwise Formulas

$$a|b = a \oplus b + a\&b$$

$$a \oplus (a\&b) = (a|b) \oplus b \qquad a \oplus b = (a\&b) \oplus (a|b)$$

$$a + b = a|b + a\&b \qquad a + b = a \oplus b + 2(a\&b)$$

$$\begin{aligned} a - b &= (a \oplus (a\&b)) - ((a|b) \oplus a) = \\ &((a|b) \oplus b) - ((a|b) \oplus a) = (a \oplus (a\&b)) - (b \oplus (a\&b)) = \\ &((a|b) \oplus b) - (b \oplus (a\&b)) \end{aligned}$$

2.10 Probability theory

Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

2.10.1 Discrete distributions

Binomial distribution

The number of successes in n independent yes/no experiments, each which yields success with probability p is

$\text{Bin}(n, p)$, $n = 1, 2, \ldots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small p .

First success distribution

The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1}, k = 1, 2, \ldots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

Poisson distribution

The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\text{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \ldots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

2.10.2 Continuous distributions

Uniform distribution

If the probability density function is constant between a and b and 0 elsewhere it is $\text{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

Exponential distribution

The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

Normal distribution

Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$

2.11 Markov chains

A *Markov chain* is a discrete random process with the property that the next state depends only on the current state. Let $X_1, X_2, \dots$ be a sequence of random variables generated by the Markov process. Then there is a transition matrix $\mathbf{P} = (p_{ij})$, with $p_{ij} = \Pr(X_n = i | X_{n-1} = j)$, and $\mathbf{p}^{(n)} = \mathbf{P}^n \mathbf{p}^{(0)}$ is the probability distribution for X_n (i.e., $p_i^{(n)} = \Pr(X_n = i)$), where $\mathbf{p}^{(0)}$ is the initial distribution.

π is a stationary distribution if $\pi = \pi \mathbf{P}$. If the Markov chain is *irreducible* (it is possible to get to any state from any state), then $\pi_i = \frac{1}{\mathbb{E}(T_i)}$ where $\mathbb{E}(T_i)$ is the expected time between two visits in state i . π_j / π_i is the expected number of visits in state j between two visits in state i .

For a connected, undirected and non-bipartite graph, where the transition probability is uniform among all neighbors, π_i is proportional to node i 's degree.

A Markov chain is *ergodic* if the asymptotic distribution is independent of the initial distribution. A finite Markov chain is ergodic iff it is irreducible and *aperiodic* (i.e., the gcd of cycle lengths is 1). $\lim_{k \rightarrow \infty} \mathbf{P}^k = 1\pi$.

A Markov chain is an A-chain if the states can be partitioned into two sets $\mathbf{A}$ and $\mathbf{G}$, such that all states in $\mathbf{A}$ are absorbing ($p_{ii} = 1$), and all states in $\mathbf{G}$ leads to an absorbing state in $\mathbf{A}$. The probability for absorption in state $i \in \mathbf{A}$, when the initial state is j , is $a_{ij} = p_{ij} + \sum_{k \in \mathbf{G}} a_{ik} p_{kj}$. The expected time until absorption, when the initial state is i , is $t_i = 1 + \sum_{k \in \mathbf{G}} p_{ki} t_k$.

2.12 Trivia

Pythagorean triples: The Pythagorean triples are uniquely generated by $a = k \cdot (m^2 - n^2)$, $b = k \cdot (2mn)$, $c = k \cdot (m^2 + n^2)$ with $m > n > 0$, $k > 0$, $\gcd(m, n) = 1$, both m, n not odd.

Primes: $p = 962592769$ is such that $2^{21} \mid p - 1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots modulo n exists iff $n = 1, 2, 4$ or, $n = p^k, 2p^k$ where p is an odd prime. Furthermore, the number of roots are $\phi(\phi(n))$.

To Find Generator g of M , factor $M - 1$ and get the distinct primes p_i . If $g^{(M-1)/p_i} \neq 1 \pmod{M}$ for each p_i then g is a valid root. Try all g until a hit is found (usually found very quick).

Esitmates: $\sum_{d|n} d = O(n \log \log n)$.

Prime count: 5133 upto 5e4. 9592 upto 1e5. 17984 upto 2e5. 78498 upto 1e6. 5761455 upto 1e8.

max NOD $\leq n$: 100 for $n = 5e4$. 500 for $n = 1e7$. 2000 for $n = 1e10$. 200 000 for $n = 1e19$.

max Unique Prime Factors: 6 upto 5e5. 7 upto 9e6. 8 upto 2e8. 9 upto 6e9. 11 upto 7e12. 15 upto 3e19.

Quadratic Residue: $(\frac{a}{p})$ is 0 if $p|a$, 1 if a is a quadratic residue, -1 otherwise. Euler: $(\frac{a}{p}) = a^{(p-1)/2} \pmod{p}$ (prime). Jacobi: if $n = p_1^{e_1} \dots p_k^{e_k}$ then $(\frac{a}{n}) = \prod (\frac{a}{p_i})^{e_i}$.

Chicken McNugget. If a, b coprime, there are $\frac{1}{2}(a-1)(b-1)$ numbers not of form $ax + by$ ($x, y \geq 0$), the largest being $ab - a - b$.

Data structures (3)

HashMap.h	
Description: Hash map with mostly the same API as unordered_map, but ~3x faster. Uses 1.5x memory. Initial capacity must be a power of 2 (if provided).	a77092, 7 lines
<pre>#include <bits/extc++.h> // To use most bits rather than just the lowest ones: struct chash { // large odd number for C const uint64_t C = 11(4e18 * acos(0)) 71; ll operator()(ll x) const { return __builtin_bswap64(x*C); } }; __gnu_pbds::gp_hash_table<ll,int,chash> h({}, { }, {}, {}, {1<<16});</pre>	

SegmentTreeKACTL.h	
Description: Zero-indexed max-tree. Bounds are inclusive to the left and exclusive to the right. Can be changed by modifying T, f and unit.	
Time: $\mathcal{O}(\log N)$	0f4bdb, 19 lines

<pre>struct Tree { typedef int T; static constexpr T unit = INT_MIN; T f(T a, T b) { return max(a, b); } // (any associative fn) vector<T> s; int n; Tree(int n = 0, T def = unit) : s(2*n, def), n(n) {} void update(int pos, T val) { for (s[pos += n] = val; pos /= 2;) s[pos] = f(s[pos * 2], s[pos * 2 + 1]); } T query(int b, int e) { // query [b, e) T ra = unit, rb = unit; for (b += n, e += n; b < e; b /= 2, e /= 2) { if (b % 2) ra = f(ra, s[b++]); if (e % 2) rb = f(s[--e], rb); } return f(ra, rb); } };</pre>	
--	--

SegmentTree.h	
Time: $\mathcal{O}(\log N)$	9f8f73, 61 lines
<pre>template<class S> struct segtree { int n; V<S> t; void init(int _n) { n = _; t.assign(n+n-1, S()); }</pre>	

<pre>void init(const V<S>& v) { n = sz(v); t.assign(n + n - 1, S()); build(0, 0, n-1, v); } template <typename... T> void upd(int l, int r, const T&... v) { assert(0 <= l && l <= r && r < n); upd(0, 0, n-1, l, r, v...); } S get(int l, int r) { assert(0 <= l && l <= r && r < n); return get(0, 0, n-1, l, r); } private: inline void push(int u, int b, int e) { if (t[u].lazy == 0) return; int mid = (b+e)>>1, rc = u+((mid-b+1)<<1); t[u+1].upd(b, mid, t[u].lazy); t[rc].upd(mid+1, e, t[u].lazy); t[u].lazy = 0; } void build(int u,int b,int e,const V<S>&v) { if (b == e) return void(t[u] = v[b]); int mid = (b+e)>>1, rc = u+((mid-b+1)<<1); build(u+1, b,mid,v); build(rc, mid+1,e,v); t[u] = t[u+1] + t[rc]; } template<typename... T> void upd(int u, int b, int e, int l, int r, const T&... v){ if (l <= b && e <= r) return t[u].upd(b, e, v...); push(u, b, e); int mid = (b+e)>>1, rc = u+((mid-b+1)<<1); if (l<=mid) upd(u+1, b, mid, l, r, v...); if (mid<r) upd(rc, mid+1, e, l, r, v...); t[u] = t[u+1] + t[rc]; } S get(int u, int b, int e, int l, int r) { if (l <= b && e <= r) return t[u]; push(u, b, e); S res; int mid = (b+e)>>1, rc = u+((mid-b+1)<<1); if (r<=mid) res = get(u+1, b, mid, l, r); else if (mid<l) res = get(rc,mid+1,e,l,r); else res = get(u+1, b, mid, l, r) + get(rc, mid+1, e, l, r); t[u] = t[u+1] + t[rc]; return res; } }; // Hash upto here = 773c09 /* (1) Declaration: Create a node class. Now, segtree<node> T; T.init(10) creates everything as node() Consider using V<node> leaves to build (2) upd(l, r, ...v): update range [l, r] order in ...v must be same as node.upd() fn */ struct node { ll sum = 0, lazy = 0; node () {} // write full constructor node operator+(const node &obj) { return {sum + obj.sum, 0}; } void upd(int b, int e, ll x) { sum += (e - b + 1) * x, lazy += x; } };</pre>	
--	--

UnionFind.h	
Description: Disjoint-set data structure.	
Time: $\mathcal{O}(\alpha(N))$	7aa27c, 14 lines
<pre>struct UF { vi e;</pre>	

<pre>UF(int n) : e(n, -1) {} bool sameSet(int a, int b) { return find(a) == find(b); } int size(int x) { return -e[find(x)]; } int find(int x) { return e[x] < 0 ? x : e[x] = find(e[x]); } bool join(int a, int b) { a = find(a), b = find(b); if (a == b) return false; if (e[a] > e[b]) swap(a, b); e[a] += e[b]; e[b] = a; return true; } };</pre>	
--	--

UnionFindRollback.h	
Description: Disjoint-set data structure with undo. If undo is not needed, skip st, time() and rollback().	
Usage: int t = uf.time(); ...; uf.rollback(t);	
Time: $\mathcal{O}(\log(N))$	de4ad0, 21 lines

<pre>struct RollbackUF { vi e; vector<pii> st; RollbackUF(int n) : e(n, -1) {} int size(int x) { return -e[find(x)]; } int find(int x) { return e[x] < 0 ? x : find(e[x]); } int time() { return sz(st); } void rollback(int t) { for (int i = time(); i --> t;) e[st[i].first] = st[i].second; st.resize(t); } bool join(int a, int b) { a = find(a), b = find(b); if (a == b) return false; if (e[a] > e[b]) swap(a, b); st.push_back({a, e[a]}); st.push_back({b, e[b]}); e[a] += e[b]; e[b] = a; return true; } };</pre>	
---	--

LineContainer.h	
Description: Container where you can add lines of the form $kx+m$, and query maximum values at points x . Useful for dynamic programming (“convex hull trick”).	
Time: $\mathcal{O}(\log N)$	Sec1c7, 30 lines

<pre>struct Line { mutable ll k, m, p; bool operator<(const Line& o) const { return k < o.k; } bool operator<(ll x) const { return p < x; } };</pre>	
--	--

<pre>struct LineContainer : multiset<Line, less<>> { // (for doubles, use inf = 1/.0, div(a,b) = a/b) static const ll inf = LLONG_MAX; ll div(ll a, ll b) { // floored division return a / b - ((a ^ b) < 0 && a % b); } bool isect(iterator x, iterator y) { if (y == end()) return x->p = inf, 0; if (x->k == y->k) x->p = x->m > y->m ? inf : -inf; else x->p = div(y->m - x->m, x->k - y->k);</pre>	
--	--

```
        return x->p >= y->p;
    }
    void add(ll k, ll m) {
        auto z = insert({k, m, 0}), y = z++, x = y
        ;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x
        , y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y
        ->p)
            isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());
        auto l = *lower_bound(x);
        return l.k * x + l.m;
    }
};
```

Lichao.h
Description: Add line segment, query minimum y at some x . Provide list of all query x points to constructor (offline solution). Use add_segment(line, l, r) to add a line segment $y = ax + b$ defined by $x \in [l, r)$. Use query(x) to get min at x .
Time: Both operations are $\mathcal{O}(\log \max n)$.

<pre>struct LiChaoTree { using Line = pair<ll, ll>; const ll linf = numeric_limits<ll>::max(); int n; vector<ll> xl; vector<Line> dat; LiChaoTree(const vector<ll>& _xl):xl(_xl){ n = l; while(n < xl.size())n <= 1; xl.resize(n,xl.back()); dat = vector<Line>(2*n-1, Line(0,linf)); } ll eval(Line f,ll x){return f.first * x + f. second;} void _add_line(Line f,int k,int l,int r){ while (l != r) { int m = (l + r) / 2; ll lx = xl[l],mx = xl[m],rx = xl[r - 1]; Line &g = dat[k]; if(eval(f,lx) < eval(g,lx) && eval(f,rx) < eval(g,rx)) { g = f; return; } if(eval(f,lx) >= eval(g,lx) && eval(f,rx) >= eval(g,rx)) return; if(eval(f,mx) < eval(g,mx))swap(f,g); if(eval(f,lx) < eval(g,lx)) k = k * 2 + l, r = m; else k = k * 2 + 2, l = m; } } void add_line(Line f){_add_line(f,0,0,n);} void add_segment(Line f,ll lx,ll rx){ int l = lower_bound(xl.begin(), xl.end(), lx) - xl.begin(); int r = lower_bound(xl.begin(), xl.end(), rx) - xl.begin(); int a0 = l, b0 = r, sz = 1; l += n; r += n; while(l < r){ if(r & 1) r--, b0 -= sz, _add_line(f,r - 1,b0,b0 + sz); if(l & 1) _add_line(f,l - 1,a0,a0 + sz), l++, a0 += sz; l >>= 1, r >>= 1, sz <= 1; } } };</pre>	566134, 43 lines
--	------------------

```
    }
    }
    ll query(ll x) {
        int i = lower_bound(xl.begin(), xl.end(),x
        ) - xl.begin();
        i += n - 1; ll res = eval(dat[i],x);
        while (i) i = (i - 1) / 2, res = min(res,
            eval(dat[i], x));
        return res;
    }
};
```

Treap.h
Description: A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.
Time: $\mathcal{O}(\log N)$

<pre>struct Node { Node *l = 0, *r = 0; int val, y, c = 1; Node(int val) : val(val), y(rand()) {} void recalc(); }; int cnt(Node* n) { return n ? n->c : 0; } void Node::recalc() { c = cnt(l) + cnt(r) + 1; } template<class F> void each(Node* n, F f) { if (n) { each(n->l, f); f(n->val); each(n->r , f); } } pair<Node*, Node*> split(Node* n, int k) { if (!n) return {}; if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k) auto [L,R] = split(n->l, k); n->l = R; n->recalc(); return {L, n}; } else { auto [L,R] = split(n->r,k - cnt(n->l) - 1) ; // and just "k" n->r = L; n->recalc(); return {n, R}; } } Node* merge(Node* l, Node* r) { if (!l) return r; if (!r) return l; if (l->y > r->y) { l->r = merge(l->r, r); return l->recalc(), l; } else { r->l = merge(l, r->l); return r->recalc(), r; } } Node* ins(Node* t, Node* n, int pos) { auto [l,r] = split(t, pos); return merge(merge(l, n), r); }</pre>	1754b4, 53 lines
--	------------------

```
// Example application: move the range [l, r)
to index k
void move(Node& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a,b) = split(t, l); tie(b,c) = split(b,
    r - 1);
    if (k <= l) t = merge(ins(a, b, k), c);
    else t = merge(a, ins(c, b, k - r));
}
```

FenwickTree.h
Description: update(i,x): a[i] += x;
query(i): sum in [0, i];
lower_bound(sum): min pos st sum of [0, pos]
>= sum, returns n if all < sum, or -1 if
empty sum.
Time: Both operations are $\mathcal{O}(\log N)$.

<pre>struct FT { int n; V<ll> s; FT(int _n) : n(_n), s(_n) {} void update(int i, ll x) { for (; i < n; i = i + 1) s[i] += x; } ll query(int i, ll r = 0) { for (; i > 0; i &= i - 1) r += s[i-1]; return r; } int lower_bound(ll sum) { if (sum <= 0) return -1; int pos = 0; for (int pw = 1 << __lg(n); pw; pw >= 1){ if (pos+pw <= n && s[pos + pw-1] < sum) pos += pw, sum -= s[pos-1]; } return pos; } }; // Hash = d05c4f without lower_bound</pre>	f74d01, 16 lines
--	------------------

FenwickTreeRange.h
Description: Range add Range sum with FT.
Time: Both operations are $\mathcal{O}(\log N)$.

<pre>FT f1(n), f2(n); // a[l...r] += v; 0 <= l <= r < n auto upd = [&](int l, int r, ll v) { f1.update(l, v), f1.update(r + 1, -v); f2.update(l, v*(l-1)), f2.update(r+1, -v*r); }; // a[l] + ... + a[r]; 0 <= l <= r < n auto sum = [&](int l, int r) { ++r; ll sub = f1.query(l) * (l-1) - f2.query(l); ll add = f1.query(r) * (r-1) - f2.query(r); return add - sub; };</pre>	8fc549, 11 lines
--	------------------

FenwickTree2d.h
Description: Computes sums $a[i,j]$ for all $i < I, j < J$, and increases single elements $a[i,j]$. Requires that the elements to be updated are known in advance (call fakeUpdate() before init()).
Time: $\mathcal{O}(\log^2 N)$. (Use persistent segment trees for $\mathcal{O}(\log N)$.)

<pre>"FenwickTree.h" struct FT2 { V<vi> ys; V<FT> ft; FT2(int limx) : ys(limx) {} void fakeUpdate(int x, int y) { for (;x<sz(ys);x =x+1) ys[x].push_back(y); } void init() { for (vi& v : ys) sort(all(v)), ft.emplace_back(sz(v)); }</pre>	d53ef2, 20 lines
--	------------------

```
int ind(int x, int y) {
    return (int)(lower_bound(all(ys[x]), y) -
        ys[x].begin()); }
void update(int x, int y, ll dif) {
    for (; x < sz(ys); x |= x + 1)
        ft[x].update(ind(x, y), dif);
}
ll query(int x, int y) { ll sum = 0;
    for (; x; x &= x - 1)
        sum += ft[x-1].query(ind(x-1, y));
    return sum;
}
};
```

RMQ.h
Description: Range Minimum Queries on an array. Returns min(V[a], V[a + 1], ... V[b - 1]) in constant time.
Usage: RMQ rmq(values);
rmq.query(inclusive, exclusive);
Time: $\mathcal{O}(|V| \log |V| + Q)$

<pre>template<class T> struct RMQ { V<V<T>> jmp; RMQ(const V<T>& V) : jmp(1, V) { for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k) { jmp.emplace_back(sz(V) - pw * 2 + 1); rep(j,0,sz(jmp[k])) jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw]); } } T query(int a, int b) { assert(a < b); // or return inf if a == b int dep = 31 - __builtin_clz(b - a); return min(jmp[dep][a], jmp[dep][b - (1 << dep)]); } };</pre>	7d2211, 15 lines
---	------------------

MoTree.h
Description: Build Euler tour of $2N$ size - write node at first enter and last exit. Now, Path(u,v) with $in[u] < in[v]$ is a segment. If $lca(u,v) = u$ then it is $[in[u], in[v]]$. Otherwise it is $[out[u], in[v]] + LCA$ node. Nodes that appear exactly once in each segment are relevant, ignore others, handle LCA separately.
Time: $\mathcal{O}\left(Q\sqrt{N}\right)$

MoUpdate.h
Description: Set block size $B = (2n^2)^{1/3}$. Sort queries by $(\lfloor \frac{L}{B} \rfloor, \lfloor \frac{R}{B} \rfloor, t)$, where t = number of updates before this query. Then process queries in sorted order, modify L, R and then apply/undo the updates to answer.
Time: $\mathcal{O}\left(Bq + qn^2/B^2\right)$ or $\mathcal{O}\left(qn^{2/3}\right)$ with that B.

Numerical (4)

4.1 Polynomials and recurrences

BerlekampMassey.h

Description: Recovers any n -order linear recurrence relation from the first $2n$ terms of the recurrence. Useful for guessing linear recurrences after brute-forcing the first terms. Should work on any field, but numerical stability for floats is not guaranteed. Output will have size $\leq n$.

Usage: `berlekampMassey({0, 1, 1, 3, 5, 11}) //`
`{1, 2} --> c[n] = c[n-1] + 2c[n-2]`

Time: $\mathcal{O}(N^2)$

`"/number-theory/ModPow.h"` 96548b, 20 lines

```
vector<ll> berlekampMassey(vector<ll> s) {
    int n = sz(s), L = 0, m = 0;
    vector<ll> C(n), B(n), T;
    C[0] = B[0] = 1;

    ll b = 1;
    rep(i,0,n) { ++m;
        ll d = s[i] % mod;
        rep(j,1,L+1) d = (d + C[j] * s[i - j]) % mod;
        if (!d) continue;
        T = C; ll coef = d * modpow(b, mod-2) % mod;
        rep(j,m,n) C[j] = (C[j] - coef * B[j - m]) % mod;

        if (2 * L > i) continue;
        L = i + 1 - L; B = T; b = d; m = 0;
    }

    C.resize(L + 1); C.erase(C.begin());
    for (ll& x : C) x = (mod - x) % mod;
    return C;
}
```

LinearRecurrence.h

Description: Generates the k 'th term of an n -order linear recurrence $S[i] = \sum_j S[i - j - 1]tr[j]$, given $S[0 \dots \geq n - 1]$ and $tr[0 \dots n - 1]$. Faster than matrix multiplication. Useful together with Berlekamp-Massey.

Usage: `linearRec({0, 1}, {1, 1}, k) //` k 'th Fibonacci number

Time: $\mathcal{O}(n^2 \log k)$

`f4e444, 26 lines`

```
typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);

    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i,0,n+1) rep(j,0,n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j,0,n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j]) % mod;
        res.resize(n + 1);
        return res;
    };

    Poly pol(n + 1), e(pol);
    pol[0] = e[1] = 1;

    for (++k; k; k /= 2) {
        if (k % 2) pol = combine(pol, e);
        e = combine(e, e);
    }

    ll res = 0;
    rep(i,0,n) res = (res + pol[i + 1] * S[i]) % mod;
}
```

```
    return res;
}

Polynomial.h
c9b7b0, 17 lines

struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i=sz(a); i--;) (val*=x) += a[i];
        return val;
    }
    void diff() {
        rep(i,1,sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for(int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b, b=c;
        a.pop_back();
    }
};
```

PolyRoots.h

Description: Finds the real roots to a polynomial.

Usage: `polyRoots({{2,-3,1}},-1e9,1e9) //` solve $x^2-3x+2 = 0$

Time: $\mathcal{O}(n^2 \log(1/\epsilon))$

`"Polynomial.h"` b00bfe, 23 lines

```
vector<double> polyRoots(Poly p, double xmin, double xmax) {
    if (sz(p.a)==2) { return {-p.a[0]/p.a[1]}; }
    vector<double> ret;
    Poly der = p;
    der.diff();
    auto dr = polyRoots(der, xmin, xmax);
    dr.push_back(xmin-1);
    dr.push_back(xmax+1);
    sort(all(dr));
    rep(i,0,sz(dr)-1) {
        double l = dr[i], h = dr[i+1];
        bool sign = p(l) > 0;
        if (sign ^ (p(h) > 0)) {
            rep(it,0,60) { // while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign) l = m;
                else h = m;
            }
            ret.push_back((l + h) / 2);
        }
    }
    return ret;
}
```

PolyInterpolate.h

Description: Given n points $(x[i], y[i])$, computes an n -1-degree polynomial p that passes through them: $p(x) = a[0] * x^0 + \dots + a[n - 1] * x^{n-1}$. For numerical precision, pick $x[k] = c * \cos(k/(n - 1) * \pi), k = 0 \dots n - 1$. For fast interpolation in $\mathcal{O}(n \log^2 n)$ use Lagrange. $P(x) = \sum_{i=1}^n y_i \prod_{j \neq i} \frac{x - x_j}{x_i - x_j}$. To compute values $\prod_{j \neq i} (x_i - x_j)$ fast, compute $A(x) = \prod_{i=1}^n (x - x_i)$ with divide and conquer. The required values are $A'(x_i)$, (values at derivative), compute fast with multipoint evaluation.

Time: $\mathcal{O}(n^2)$

`08bf48, 13 lines`

```
typedef vector<double> vd;
```

```
vd interpolate(vd x, vd y, int n) {
    vd res(n), temp(n);
    rep(k,0,n-1) rep(i,k+1,n)
        y[i] = (y[i] - y[k]) / (x[i] - x[k]);
    double last = 0; temp[0] = 1;
    rep(k,0,n) rep(i,0,n) {
        res[i] += y[k] * temp[i];
        swap(last, temp[i]);
        temp[i] -= last * x[k];
    }
    return res;
}
```

4.2 Fourier transforms

Let $\mathbb{F}$ denote some field. Let $\mathbb{P} = \mathbb{F}[x]$ and let $\mathbb{S} = \mathbb{F}[[x]]$. Let $A = a_0 + a_1x + \dots + a_nx^n \in \mathbb{P}$ and $B = b_0 + b_1x + \dots + b_mx^m \in \mathbb{P}$.

Naive Division + Remainder of A by B : $\mathcal{O}(nm)$ polynomial long division taught in school when $B \neq 0$.

Inverse of A : $A(0) \neq 0 \Rightarrow A^{-1} \in \mathbb{S}$. Let $T \in \mathbb{P}$ be s.t. $T(x^2) = A(x)A(-x)$. Then $A^{-1}(x) \equiv A(-x)/T(x^2) \pmod{x^j}$. To compute $A^{-1}(x) \pmod{x^j}$, we can then recursively $T^{-1}(x) \pmod{x^{\lfloor j/2 \rfloor}}$. Time complexity $\mathcal{O}(n + j \log j)$.

Hensel's lemma: Let r be a commutative ring and let $F \in r[x]$ and $a, q_0 \in r$ s.t. $F(q_0) \equiv 0 \pmod{a}$ and $F'(q_0)^{-1} \in r$. Then $F(q_1) \equiv 0 \pmod{a^2}$, where $q_1 \equiv q_0 - \frac{F(q_0)}{F'(q_0)} \pmod{a^2}$. This is useful in particular when $r = \mathbb{P}$ or $r = \mathbb{S}$.

Inverse of A : Hensel's lemma with $F(P) = A - P^{-1}$. $Q_0 \equiv a_0^{-1} \pmod{x^1}$, $Q_{j+1} \equiv Q_j(2 - AQ_j) \pmod{x^{2^{j+1}}}$. $F(Q_j) \equiv 0 \pmod{x^{2^j}}$. Still $\mathcal{O}(n + j \log j)$.

Faster Division: Given $P \in \mathbb{P}$, let P^R denote the polynomial with its coefficients reversed. If $A = DB + R$ with $\deg R < \deg B$, then $D^R \equiv A^R/B^R \pmod{x^{n-m+1}}$ and $R = A - BD$. Time complexity $\mathcal{O}((n + m) \log(n + m))$.

ln A : $(\ln A)' = A'/A$. So $\ln A = Q_0 + \int A'/A$ for some $Q_0 \in \mathbb{F}$. Intuition suggests that $Q_0 = \ln a_0$, since $\ln A(0) = Q_0 = \ln a_0$.

exp A : $Q_{k+1} \equiv Q_k(1 + A - \ln Q_k) \pmod{x^{2^{k+1}}}$.

A^j : Let $T \in \mathbb{P}$ be s.t. $T(0) = 1$ and $A(x) = \alpha x^t T(x)$ for some $\alpha \in k$. Then $A^j(x) = \alpha^j x^{jt} \exp[j \ln T(x)]$.

Chirp-Z: Given $z \in \mathbb{C}, s \in \mathbb{N}_{\geq 0}$. $A(z^{2^s}) = z^{s^2} \sum_{j=0}^n \left(a_j z^{j^2}\right) \left(z^{-(s-j)^2}\right)$. Clearly, $A(z^0), A(z^2), \dots, A(z^{2^s})$ can be computed in one convolution with time complexity $\mathcal{O}((s + n) \log(s + n))$. By applying $a_j \mapsto a_j z^j \forall j$, we can then apply the previous algo to compute $A(z^1), A(z^3), \dots, A(z^{2^s+1})$ in the same time complexity.

Multipoint-Eval: To calculate $A(x_0), \dots, A(x_{n-1})$, we use the fact that $\forall i, A(x_i) \equiv A(x) \pmod{x - x_i}$. Segment tree, segment $[l, r)$ has $P_{l,r} = \prod_{i=l}^{r-1} (x - x_j)$. We want $A_{l,r} = (A(x) \pmod{P_{l,r}})$. If $mid = \lfloor (l + r)/2 \rfloor$, then $A_{l,mid} = (A_{l,r} \pmod{P_{l,mid}})$ and $A_{mid,r} = (A_{mid,r} \pmod{P_{mid,r}})$. Finally, $A_{i,i+1} = A(x_i) \forall i$. $\mathcal{O}(n \log^2 n)$.

Interpolation: Given $(x_0, y_0), \dots, (x_{n-1}, y_{n-1})$ s.t. $x_0, \dots, x_{n-1}$ are distinct and $\forall i, A(x_i) = y_i$. Then $A(x) = \sum_{i=1}^n y_i \prod_{j \neq i} \frac{x - x_j}{x_i - x_j}$. Let $P(x) = \prod_j (x - x_j)$ and $\forall i, P_i = \prod_{j \neq i} (x_i - x_j)$. Then $P_i = P'(x_i)$, so use multipoint evaluation to compute $P_0, \dots, P_{n-1}$. Now, we recursively compute $A(x) = A_{0,n}(x)$ by letting $A_{l,r}(x) = A_{l,mid}(x) \prod_{mid \leq j < r} (x - x_j) + A_{mid,r}(x) \prod_{l \leq j < mid} (x - x_j)$. And $\forall i, A_{i,i+1}(x) = \frac{y_i}{P'_i}$. Here, $mid = \lfloor (l + r)/2 \rfloor$. $\mathcal{O}(n \log^2 n)$.

GCD and Resultants: Let $\lambda_1, \dots, \lambda_n$ and $\mu_1, \dots, \mu_m$ be the roots of A and B respectively, with multiplicity. Then the resultant $\mathcal{R}(A, B) = a_n^m b_m^n \prod_{i,j} (\mu_j - \lambda_j)$. $\mathcal{R}(A, B) = (-1)^{nm} \mathcal{R}(B, A)$. $\mathcal{R}(A, B) = 0$ iff A and B share a common root. $\mathcal{R}(A, B) = a_n^m b_m^m$ when $n = 0$ or $m = 0$. $\forall C \in k[x], \mathcal{R}(A, B) = b_m^{\deg A - \deg(A - CB)} \mathcal{R}(A - CB, B)$. So, we can compute $\gcd(A, B)$ and $\mathcal{R}(A, B)$ at the same time in $\mathcal{O}(mn)$: $\mathcal{R}(A, 0) = 0, \mathcal{R}(A, B) = b_m^n$, $\mathcal{R}(A, B) = b_m^{\deg A - \deg D} (-1)^{\deg B \deg D} \mathcal{R}(B, D)$. Here, $D = (A \pmod{B})$. We can use this to find intersection between two curves of the form $P(x, y) = 0$ and $Q(x, y) = 0$. Let $P_{y_0}(x) = P(x, y_0) \in k[x]$ and $Q_{y_0}(x) = Q(x, y_0) \in k[x]$. First, we can solve $R(y_0) = \mathcal{R}(P_{y_0}(x), Q_{y_0}(x)) = 0$ for y_0 . Then for those y_0 , we solve $P(x, y_0) = Q(x, y_0) = 0$. Under simple circumstances, we should get finitely many intersection points.

FastFourierTransform.h

Description: $\text{fft}(a)$ computes $\hat{f}(k) = \sum_x a[x] \exp(2\pi i \cdot kx/N)$ for all k . N must be a power of 2. Useful for convolution: $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For convolution of complex numbers or more than two vectors: FFT each poly, multiply result pointwise, divide by n , reverse(out.begin()+1,end), FFT back, then round(out[i].real()) or truncate out[i].imag(0). Rounding is safe if $(\sum a_i^2 + \sum b_i^2) \log_2 N < 9 \cdot 10^{14}$ (in practice 10^{16} ; higher for random inputs). Otherwise, use NTT/FFTMod.

Time: $\mathcal{O}(N \log N)$ with $N = |A| + |B|$ ($\sim 1s$ for $N = 2^{22}$ _{3dd197, 36 lines})

```
typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1); // (^ 10% faster if double)
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n); rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        rep(i,k,2*k) rt[i] = R[i] = i&1 ? R[i/2] * x : R[i/2];
    }
    vi rev(n);
    rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j
            ,0,k) {
            auto x = (double *)&rt[j+k], y = (double *)&a[i+j+k];
            C z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*y[0]);
            a[i + j + k] = a[i + j] - z;
            a[i + j] += z;
        }
    // Use vector<C> when complex covolution
    vd conv(const vd& a, const vd& b) {
        if (a.empty() || b.empty()) return {};
        vd res(sz(a) + sz(b) - 1);
        int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
        vector<C> in(n), out(n); // create in2
        copy(all(a), begin(in)); // copy(b) -> in2
        rep(i,0,sz(b)) in[i].imag(b[i]); // skip
        fft(in); // call extra fft for in2
        for (C& x : in) x *= x; // out_i=in_i*in2_i
        rep(i,0,n) out[i] = in[-i & (n - 1)] - conj(in[i]); // skip, rather divide by n
        fft(out);
        rep(i,0,sz(res)) res[i] = imag(out[i]) / (4 * n); // do rounding on out instead
        return res;
    }
}
```

FastFourierTransformMod.h

Description: Higher precision FFT, can be used for convolutions modulo arbitrary integers as long as $N \log_2 N \cdot \text{mod} < 8.6 \cdot 10^{14}$ (in practice 10^{16} or higher). Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$, where $N = |A| + |B|$ (twice as slow as NTT or FFT)

"FastFourierTransform.h"	b82773, 22 lines
--------------------------	------------------

typedef vector<ll> vl;

```
template<int M> vl convMod(const vl &a, const vl &b) {
    if (a.empty() || b.empty()) return {};
    vl res(sz(a) + sz(b) - 1);
    int B=32-__builtin_clz(sz(res)), n=1<<B, cut =int(sqrt(M));
    vector<C> L(n), R(n), outs(n), outl(n);
    rep(i,0,sz(a)) L[i] = C((int)a[i] / cut, (int)a[i] % cut);
    rep(i,0,sz(b)) R[i] = C((int)b[i] / cut, (int)b[i] % cut);
    fft(L), fft(R);
    rep(i,0,n) {
        int j = -i & (n - 1);
        outl[j] = (L[i] + conj(L[j])) * R[i] / (2.0 * n);
        outs[j] = (L[i] - conj(L[j])) * R[i] / (2.0 * n) / 1i;
    }
    fft(outl), fft(outs);
    rep(i,0,sz(res)) {
        ll av = ll(real(outl[i])+.5), cv = ll(imag(outs[i])+.5);
        ll bv = ll(imag(outl[i])+.5) + ll(real(outs[i])+.5);
        res[i] = ((av % M * cut + bv) % M * cut + cv) % M;
    }
    return res;
}
```

NumberTheoreticTransform.h

Description: $\text{ntt}(a)$ computes $\hat{f}(k) = \sum_x a[x]g^{xk}$ for all k , where $g = \text{root}^{(\text{mod}-1)/N}$. N must be a power of 2. Useful for convolution modulo specific nice primes of the form 2^ab+1 , where the convolution result has size at most 2^a . For arbitrary modulo, see FFTMod. $\text{conv}(a, b) = c$, where $c[x] = \sum a[i]b[x-i]$. For manual convolution: NTT the inputs, multiply pointwise, divide by n , reverse(start+1, end), NTT back. Inputs must be in $[0, \text{mod})$.

Time: $\mathcal{O}(N \log N)$

"../number-theory/ModPow.h"	ced03d, 35 lines
-----------------------------	------------------

const ll mod = (119 << 23) + 1, root = 62; // = 998244353
// For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 << 21
// and 483 << 21 (same root). The last two are > 10^9.

typedef vector<ll> vl;
void ntt(vl &a) {
 int n = sz(a), L = 31 - __builtin_clz(n);
 static vl rt(2, 1);
 for (static int k = 2, s = 2; k < n; k *= 2, s++) {
 rt.resize(n);
 ll z[] = {1, modpow(root, mod >> s)};
 rep(i,k,2*k) rt[i] = rt[i / 2] * z[i & 1] % mod;
 }
 vi rev(n);
 rep(i,0,n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
 rep(i,0,n) if (i < rev[i]) swap(a[i], a[rev[i]]);
 for (int k = 1; k < n; k *= 2)

```
    for (int i = 0; i < n; i += 2 * k) rep(j
        ,0,k) {
        ll z = rt[j + k] * a[i + j + k] % mod, & ai = a[i + j];
        a[i + j + k] = ai - z + (z > ai ? mod : 0);
        ai += (ai + z >= mod ? z - mod : z);
    }
    vl conv(const vl &a, const vl &b) {
        if (a.empty() || b.empty()) return {};
        int s = sz(a) + sz(b) - 1, B = 32 - __builtin_clz(s), n = 1 << B;
        int inv = modpow(n, mod - 2);
        vl L(a), R(b), out(n);
        L.resize(n), R.resize(n);
        ntt(L), ntt(R);
        rep(i,0,n)
            out[-i & (n - 1)] = (ll)L[i] * R[i] % mod * inv % mod;
        ntt(out);
        return {out.begin(), out.begin() + s};
    }
}
```

FastSubsetTransform.h

Description: (aka FWHT) Transform to a basis with fast convolutions of the form $c[z] = \sum_{z=x \oplus y} a[x] \cdot b[y]$, where $\oplus$ is one of AND, OR, XOR. The size of a must be a power of two.

Time: $\mathcal{O}(N \log N)$

	464cf3, 16 lines
--	------------------

void FST(vi& a, bool inv) {
 for (int n = sz(a), step = 1; step < n; step *= 2) {
 for (int i = 0; i < n; i += 2 * step) rep(j,i,1+step) {
 int &u=a[j], &v=a[j+step]; tie(u, v) = inv ? pii(v-u,u) : pii(v,u+v); // AND
 inv ? pii(v,u-v) : pii(u+v,u); // OR
 pii(u+v, u-v); // XOR
 }
 }
 if(inv) for(int&x : a) x/=sz(a); //XOR only
}

```
vi conv(vi a, vi b) {
    FST(a, 0); FST(b, 0);
    rep(i,0,sz(a)) a[i] *= b[i];
    FST(a, 1); return a;
}
```

FastSubsetConvolution.h

Description: $\text{ans}[i] = \sum_{j \subseteq i} f_j g_{i \oplus j}$

Time: $\mathcal{O}(n^2 2^n)$ or, $\mathcal{O}(N \log^2 N)$

	7571e4, 28 lines
--	------------------

int f[N], g[N], fh[LG][N], gh[LG][N], h[LG][N], ans[N];
void conv() {
 for (int mask = 0; mask < 1 << n; ++mask) {
 fh[__builtin_popcount(mask)][mask]=f[mask];
 gh[__builtin_popcount(mask)][mask]=g[mask];
 }
 for (int i = 0; i <= n; ++i) {
 for (int j = 0; j < n; ++j)
 for (int mask = 0; mask < 1 << n; ++mask)
 if (mask & 1 << j) {
 fh[i][mask] += fh[i][mask ^ 1 << j];
 gh[i][mask] += gh[i][mask ^ 1 << j];
 }

```
    }
    }
    for (int mask = 0; mask < 1 << n; ++mask) {
        for (int i = 0; i <= n; ++i)
            for (int j = 0; j <= i; ++j)
                h[i][mask] += fh[j][mask] * gh[i-j][mask];
    }
    for (int i = 0; i <= n; ++i) {
        for (int j = 0; j < n; ++j)
            for (int mask = 0; mask < 1 << n; ++mask)
                if (mask & 1 << j)
                    h[i][mask] -= h[i][mask ^ 1 << j];
    }
    for (int mask = 0; mask < 1 << n; ++mask)
        ans[mask]=h[__builtin_popcount(mask)][mask];
    }
}
```

GCDconvolution.h

Description: Computes $c_1, \dots, c_n$, where $c_k = \sum_{\text{gcd}(i,j)=k} a_i b_j$. Generate all primes upto n into pr first using sieve.

Time: $\mathcal{O}(N \log \log N)$

	bc0c7a, 19 lines
--	------------------

```
void fw_mul_transform (V<ll> &a) {
    int n = sz(a) - 1;
    for (const auto p : pr) {
        if (p > n) break;
        for (int i = n/p; i>0; --i) a[i]+=a[i*p];
    } // A[i] = \sum_{\{j\} a[i * j]}
    void bw_mul_transform (V<ll> &a) {
        int n = sz(a) - 1;
        for (const auto p : pr) {
            if (p > n) break;
            for (int i=1; i*p <= n; ++i) a[i]-=a[i*p];
        } // From A get a
    V<ll>gcd_conv (const V<ll>&a, const V<ll>&b){
        assert(sz(a) == sz(b)); int n = sz(a);
        auto A = a, B = b;
        fw_mul_transform(A); fw_mul_transform(B);
        for (int i = 1; i < n; ++i) A[i] *= B[i];
        bw_mul_transform(A); return A;
    }
}
```

LCMconvolution.h

Description: Computes $c_1, \dots, c_n$, where $c_k = \sum_{\text{lcm}(i,j)=k} a_i b_j$. Generate all primes upto n into pr first using sieve.

Time: $\mathcal{O}(N \log \log N)$

	1c5704, 19 lines
--	------------------

```
void fw_div_transform (V<ll> &a) {
    int n = sz(a) - 1;
    for (const auto p : pr) {
        if (p > n) break;
        for (int i=1; i*p <= n; ++i) a[i*p]+=a[i];
    } // A[i] = \sum_{\{d \mid i\} a[d]}
    void bw_div_transform (V<ll> &a) {
        int n = sz(a) - 1;
        for (const auto p : pr) {
            if (p > n) break;
            for (int i=n/p; i>0; --i) a[i*p]-=a[i];
        } // From A get a
    V<ll>lcm_conv (const V<ll>&a, const V<ll>&b){
        assert(sz(a) == sz(b)); int n = sz(a);
        auto A = a, B = b;
        fw_div_transform(A); fw_div_transform(B);
        for (int i = 1; i < n; ++i) A[i] *= B[i];
        bw_div_transform(A); return A;
    }
}
```

4.3 Matrices

Matrix.h

Description: Basic operations on square matrices.
Usage: Matrix<int, 3> A;
A.d = {{{{1,2,3}}, {{4,5,6}}, {{7,8,9}}}}};
array<int, 3> vec = {1,2,3};
vec = (A^N) * vec;

6ab5db, 26 lines

```
template<class T, int N> struct Matrix {
    typedef Matrix M;
    array<array<T, N>, N> d{};
    M operator*(const M& m) const {
        M a;
        rep(i,0,N) rep(j,0,N)
            rep(k,0,N) a.d[i][j] += d[i][k]*m.d[k][j];
        return a;
    }
    array<T, N> operator*(const array<T, N>& vec) const {
        array<T, N> ret{};
        rep(i,0,N) rep(j,0,N) ret[i] += d[i][j] * vec[j];
        return ret;
    }
    M operator^(ll p) const {
        assert(p >= 0);
        M a, b(*this);
        rep(i,0,N) a.d[i][i] = 1;
        while (p) {
            if (p&1) a = a*b;
            b = b*b;
            p >>= 1;
        }
        return a;
    }
};
```

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix.
Time: $\mathcal{O}(N^3)$

bd5cec, 15 lines

```
double det(vector<vector<double>>& a) {
    int n = sz(a); double res = 1;
    rep(i,0,n) {
        int b = i;
        rep(j,i+1,n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
        if (i != b) swap(a[i], a[b]), res *= -1;
        res *= a[i][i];
        if (res == 0) return 0;
        rep(j,i+1,n) {
            double v = a[j][i] / a[i][i];
            if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
        }
    }
    return res;
}
```

IntDeterminant.h

Description: Calculates determinant using modular arithmetics. Modulos can also be removed to get a pure-integer version.
Time: $\mathcal{O}(N^3)$

3313dc, 18 lines

```
const ll mod = 12345;
ll det(vector<vector<ll>>& a) {
```

```
int n = sz(a); ll ans = 1;
rep(i,0,n) {
    rep(j,i+1,n) {
        while (a[j][i] != 0) { // gcd step
            ll t = a[i][i] / a[j][i];
            if (t) rep(k,i,n)
                a[i][k] = (a[i][k] - a[j][k] * t) % mod;
            swap(a[i], a[j]);
            ans *= -1;
        }
        ans = ans * a[i][i] % mod;
        if (!ans) return 0;
    }
    return (ans + mod) % mod;
}
```

SolveLinear.h

Description: Solves $A * x = b$. If there are multiple solutions, an arbitrary one is returned. Returns rank, or -1 if no solutions. Data in A and b is lost.
Time: $\mathcal{O}(n^2m)$

44c9ab, 38 lines

```
typedef vector<double> vd;
const double eps = 1e-12;

int solveLinear(vector<vd>& A, vd& b, vd& x) {
    int n = sz(A), m = sz(x), rank = 0, br, bc;
    if (n) assert(sz(A[0]) == m);
    vi col(m); iota(all(col), 0);

    rep(i,0,n) {
        double v, bv = 0;
        rep(r,i,n) rep(c,i,m)
            if ((v = fabs(A[r][c]) > bv)
                br = r, bc = c, bv = v);
        if (bv <= eps) {
            rep(j,i,n) if (fabs(b[j]) > eps) return -1;
            break;
        }
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) swap(A[j][i], A[j][bc]);
        bv = 1/A[i][i];
        rep(j,i+1,n) {
            double fac = A[j][i] * bv;
            b[j] -= fac * b[i];
            rep(k,i+1,m) A[j][k] -= fac*A[i][k];
        }
        rank++;
    }

    x.assign(m, 0);
    for (int i = rank; i--;) {
        b[i] /= A[i][i];
        x[col[i]] = b[i];
        rep(j,0,i) b[j] -= A[j][i] * b[i];
    }
    return rank; // (multiple solutions if rank < m)
}
```

SolveLinear2.h

Description: To get all uniquely determined values of x back from SolveLinear, make the following changes:
"SolveLinear.h"

08e495, 7 lines

```
rep(j,0,n) if (j != i) // instead of rep(j,i
    +1,n)
// ... then at the end:
x.assign(m, undefined);
rep(i,0,rank) {
    rep(j,rank,m) if (fabs(A[i][j]) > eps) goto fail;
    x[col[i]] = b[i] / A[i][i];
fail:; }
```

SolveLinearBinary.h

Description: Solves $Ax = b$ over $\mathbb{F}_2$. If there are multiple solutions, one is returned arbitrarily. Returns rank, or -1 if no solutions. Destroys A and b .
Time: $\mathcal{O}(n^2m)$

fa2d7a, 34 lines

```
typedef bitset<1000> bs;

int solveLinear(vector<bs>& A, vi& b, bs& x, int m) {
    int n = sz(A), rank = 0, br;
    assert(m <= sz(x));
    vi col(m); iota(all(col), 0);
    rep(i,0,n) {
        for (br=i; br<n; ++br) if (A[br].any()) break;
        if (br == n) {
            rep(j,i,n) if(b[j]) return -1;
            break;
        }
        int bc = (int)A[br]._Find_next(i-1);
        swap(A[i], A[br]);
        swap(b[i], b[br]);
        swap(col[i], col[bc]);
        rep(j,0,n) if (A[j][i] != A[j][bc]) {
            A[j].flip(i); A[j].flip(bc);
        }
        rep(j,i+1,n) if (A[j][i]) {
            b[j] ^= b[i];
            A[j] ^= A[i];
        }
        rank++;
    }

    x = bs();
    for (int i = rank; i--;) {
        if (!b[i]) continue;
        x[col[i]] = 1;
        rep(j,0,i) b[j] ^= A[j][i];
    }
    return rank; // (multiple solutions if rank < m)
}
```

XorBasis.h

Description: Maintain the basis of bit vectors.
Time: $\mathcal{O}(D^2/64)$ per insert

0daa2d, 19 lines

```
const int D = 1000; // use ll if < 64
struct Xor_Basis {
    V<int> who; V<bitset<D>> a;
    Xor_Basis () : who(D, -1) {}
    bool insert (bitset<D> x) {
        for (int i = 0; i < D; ++i)
            if (x[i] && who[i]!=-1) x^=a[who[i]];
        int pivot = -1;
        for (int i = 0; i < D; ++i)
            if (x[i]) { pivot = i; break; }
        if (pivot == -1) return false;
```

```
// ^ null vector detected
who[pivot] = sz(a);
for (int i = 0; i < sz(a); ++i)
    if (a[i][pivot] == 1) a[i] ^= x;
a.push_back(x);
return true;
}
};
```

MatrixInverse.h

Description: Invert matrix A . Returns rank; result is stored in A unless singular (rank < n). Can easily be extended to prime moduli; for prime powers, repeatedly set $A^{-1} = A^{-1}(2I - AA^{-1}) \pmod{p^k}$ where A^{-1} starts as the inverse of $A \bmod p$, and k is doubled in each step.
Time: $\mathcal{O}(n^3)$

ebffff, 35 lines

```
int matInv(vector<vector<double>>& A) {
    int n = sz(A); vi col(n);
    vector<vector<double>> tmp(n, vector<double>(n));
    rep(i,0,n) tmp[i][i] = 1, col[i] = i;

    rep(i,0,n) {
        int r = i, c = i;
        rep(j,i,n) rep(k,i,n)
            if (fabs(A[j][k]) > fabs(A[r][c]))
                r = j, c = k;
        if (fabs(A[r][c]) < 1e-12) return i;
        A[i].swap(A[r]); tmp[i].swap(tmp[r]);
        rep(j,0,n)
            swap(A[j][i], A[j][c]), swap(tmp[j][i], tmp[j][c]);
        swap(col[i], col[c]);
        double v = A[i][i];
        rep(j,i+1,n) {
            double f = A[j][i] / v;
            A[j][i] = 0;
            rep(k,i+1,n) A[j][k] -= f*A[i][k];
            rep(k,0,n) tmp[j][k] -= f*tmp[i][k];
        }
        rep(j,i+1,n) A[i][j] /= v;
        rep(j,0,n) tmp[i][j] /= v;
        A[i][i] = 1;
    }

    for (int i = n-1; i > 0; --i) rep(j,0,i) {
        double v = A[j][i];
        rep(k,0,n) tmp[j][k] -= v*tmp[i][k];
    }

    rep(i,0,n) rep(j,0,n) A[col[i]][col[j]] = tmp[i][j];
    return n;
}
```

Tridiagonal.h

Description: $x = \text{tridiagonal}(d, p, q, b)$ solves the equation system

$$\begin{pmatrix} b_0 \\ b_1 \\ b_2 \\ b_3 \\ \vdots \\ b_{n-1} \end{pmatrix} = \begin{pmatrix} d_0 & p_0 & 0 & \cdots & 0 \\ q_0 & d_1 & p_1 & \cdots & 0 \\ 0 & q_1 & d_2 & p_2 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & q_{n-3} & d_{n-2} & p_{n-2} \\ 0 & 0 & \cdots & 0 & q_{n-2} & d_{n-1} \end{pmatrix} \begin{pmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \\ \vdots \\ x_{n-1} \end{pmatrix}$$

This is useful for solving problems on the type
 $a_i = b_i a_{i-1} + c_i a_{i+1} + d_i, 1 \leq i \leq n,$

where a_0, a_{n+1}, b_i, c_i and d_i are known. a can then be obtained from

```
{a_i} = tridiagonal({1, -1, -1, ..., -1, 1}, {0, c_1, c_2, ..., c_n}, {b_1, b_2, ..., b_n, 0}, {a_0, d_1, d_2, ..., d_n, a_{n+1}}).
```

Fails if the solution is not unique.

If $|d_i| > |p_i| + |q_{i-1}|$ for all i , or $|d_i| > |p_{i-1}| + |q_i|$, or the matrix is positive definite, the algorithm is numerically stable and neither `tr` nor the check for `diag[i] == 0` is needed.

Time: $\mathcal{O}(N)$

```
typedef double T;
V<T> tridiagonal(V<T> diag, const V<T>& super,
    const V<T>& sub, V<T> b) {
    int n = sz(b); vi tr(n);
    rep(i,0,n-1) {
        if (abs(diag[i]) < 1e-9 * abs(super[i])) {
            // diag[i] == 0
            b[i+1] -= b[i] * diag[i+1] / super[i];
            if (i+2 < n) b[i+2] -= b[i] * sub[i+1] /
                super[i];
            diag[i+1] = sub[i]; tr[++i] = 1;
        } else {
            diag[i+1] -= super[i]*sub[i]/diag[i];
            b[i+1] -= b[i]*sub[i]/diag[i];
        }
    }
    for (int i = n; i--;) {
        if (tr[i]) {
            swap(b[i], b[i-1]);
            diag[i-1] = diag[i];
            b[i] /= super[i-1];
        } else {
            b[i] /= diag[i];
            if (i) b[i-1] -= b[i]*super[i-1];
        }
    }
    return b;
}
```

4.4 Optimization

GoldenSectionSearch.h

Description: Finds the argument minimizing the function f in the interval $[a, b]$ assuming f is unimodal on the interval, i.e. has only one local minimum and no local maximum. The maximum error in the result is ϵ . Works equally well for maximization with a small change in the code. See TernarySearch.h in the Various chapter for a discrete version.

Usage: `double func(double x) { return 4+x+.3*x*x; }`
`double xmin = gss(-1000,1000,func);`
Time: $\mathcal{O}(\log((b-a)/\epsilon))$

```
double gss(double a, double b, double (*f)(double)) {
    double r1 = (sqrt(5)-1)/2, eps = 1e-7;
    double x1 = b - r*(b-a), x2 = a + r*(b-a);
    double f1 = f(x1), f2 = f(x2);
    while (b-a > eps)
        if (f1 < f2) { //change to > to find maximum
            b = x2; x2 = x1; f2 = f1;
            x1 = b - r*(b-a); f1 = f(x1);
        } else {
            a = x1; x1 = x2; f1 = f2;
            x2 = a + r*(b-a); f2 = f(x2);
        }
}
```

```
return a;
}
```

HillClimbing.h

Description: Poor man's optimization for unimodal functions.

Seeeaf, 14 lines

```
typedef array<double, 2> P;

template<class F> pair<double, P> hillClimb(P start, F f) {
    pair<double, P> cur(f(start), start);
    for (double jmp = 1e9; jmp > 1e-20; jmp /= 2) {
        rep(j,0,100) rep(dx,-1,2) rep(dy,-1,2) {
            P p = cur.second;
            p[0] += dx*jmp;
            p[1] += dy*jmp;
            cur = min(cur, make_pair(f(p), p));
        }
    }
    return cur;
}
```

Integrate.h

Description: Simple integration of a function over an interval using Simpson's rule. The error should be proportional to h^4 , although in practice you will want to verify that the result is stable to desired precision when epsilon changes.

4756fc, 7 lines

```
template<class F>
double quad(double a, double b, F f, const int n = 1000) {
    double h = (b - a) / 2 / n, v = f(a) + f(b);
    rep(i,1,n*2)
        v += f(a + i*h) * (i&1 ? 4 : 2);
    return v * h / 3;
}
```

IntegrateAdaptive.h

Description: Fast integration using an adaptive Simpson's rule.

Usage: `double sphereVolume = quad(-1, 1, [](double x) { return quad(-1, 1, [&](double y) { return quad(-1, 1, [&](double z) { return x*x + y*y + z*z < 1; }}});});`

92dd79, 15 lines

```
typedef double d;
#define S(a,b) (f(a) + 4*f((a+b) / 2) + f(b)) * (b-a) / 6
```

```
template <class F>
d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b, eps / 2, S2);
}

template<class F>
d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
}
```

Simplex.h

Description: Solves a general linear maximization problem: maximize $c^T x$ subject to $Ax \leq b, x \geq 0$. Returns -inf if there is no solution, inf if there are arbitrarily good solutions, or the maximum value of $c^T x$ otherwise. The input vector is set to an optimal x (or in the unbounded case, an arbitrary solution fulfilling the constraints). Numerical stability is not guaranteed. For better performance, define variables such that $x = 0$ is viable.

Usage: `vvd A = {{1,-1}, {-1,1}, {-1,-2}};`
`vvd b = {1,1,-4}, c = {-1,-1}, x;`
`T val = LPSolver(A, b, c).solve(x);`
Time: $\mathcal{O}(NM * \#pivots)$, where a pivot may be e.g. an edge relaxation. $\mathcal{O}(2^n)$ in the general case.

aa8530, 68 lines

```
typedef double T; // long double, Rational, double + mod<P>...
typedef vector<T> vd;
typedef vector<vd> vvd;
```

```
const T eps = 1e-8, inf = 1/.0;
#define MP make_pair
#define ltj(X) if(s == -1 || MP(X[j],N[j]) < MP(X[s],N[s])) s=j
```

```
struct LPSolver {
    int m, n;
    vi N, B;
    vvd D;
```

```
LPSolver(const vvd& A, const vd& b, const vd & c) :
    m(sz(b)), n(sz(c)), N(n+1), B(m), D(m+2, vd(n+2)) {
    rep(i,0,m) rep(j,0,n) D[i][j] = A[i][j];
    rep(i,0,m) { B[i] = n+i; D[i][n] = -1; D[i][n+1] = b[i];}
    rep(j,0,n) { N[j] = j; D[m][j] = -c[j]; }
    N[n] = -1; D[m+1][n] = 1;
}
```

```
void pivot(int r, int s) {
    T *a = D[r].data(), inv = 1 / a[s];
    rep(i,0,m+2) if (i != r && abs(D[i][s]) > eps) {
        T *b = D[i].data(), inv2 = b[s] * inv;
        rep(j,0,n+2) b[j] -= a[j] * inv2;
        b[s] = a[s] * inv2;
    }
    rep(j,0,n+2) if (j != s) D[r][j] *= inv;
    rep(i,0,m+2) if (i != r) D[i][s] *= -inv;
    D[r][s] = inv;
    swap(B[r], N[s]);
}
```

```
bool simplex(int phase) {
    int x = m + phase - 1;
    for (;;) {
        int s = -1;
        rep(j,0,n+1) if (N[j] != -phase) ltj(D[x][j]);
        if (D[x][s] >= -eps) return true;
        int r = -1;
        rep(i,0,m) {
            if (D[i][s] <= eps) continue;
            if (r == -1 || MP(D[i][n+1] / D[i][s], B[i])
                < MP(D[r][n+1] / D[r][s], B[r])) r = i;
```

```
    }
    if (r == -1) return false;
    pivot(r, s);
}
```

```
T solve(vd &x) {
    int r = 0;
    rep(i,1,m) if (D[i][n+1] < D[r][n+1]) r = i;
    if (D[r][n+1] < -eps) {
        pivot(r, n);
        if (!simplex(2) || D[m+1][n+1] < -eps)
            return -inf;
        rep(i,0,m) if (B[i] == -1) {
            int s = 0;
            rep(j,1,n+1) ltj(D[i][j]);
            pivot(i, s);
        }
    }
    bool ok = simplex(1); x = vd(n);
    rep(i,0,m) if (B[i] < n) x[B[i]] = D[i][n+1];
    return ok ? D[m][n+1] : inf;
}
};
```

Number theory (5)

5.1 Modular arithmetic

mint.h

Description: Modular integer operators. Set MOD before using the structure.

5047a0, 28 lines

```
const ll MOD = 998244353;
struct mint {
    ll x;
    mint(ll _ = 0) : x((_ % MOD + MOD) % MOD) {}
    mint operator+(const mint&b) const{return x+b.x;}
    mint operator-(const mint&b) const{return x-b.x;}
    mint operator*(const mint&b) const{return x*b.x;}
    mint operator/(const mint&b) const{return *this*inv(b);}
    mint operator^(ll b) const { // a^b^c=(a^b)^c
        assert(b >= 0); // not (a^b)^c -> actual
        ord
        mint a = *this, ret = 1;
        while (b) {
            if (b & 1) ret = ret * a;
            a = a * a; b >>= 1;
        }
        return ret;
    }
    static ll euclid(ll a, ll b, ll& x, ll& y) {
        if (!b) return x = 1, y = 0, a;
        ll g = euclid(b, a % b, y, x);
        return y -= a / b * x, g;
    }
    static mint inv(const mint&a) {
        ll x, y, g = euclid(a.x, MOD, x, y);
        assert(g == 1);
        return x;
    }
};
```

combi.h

Description: Precomputes factorials and inverse factorials for binomial coefficients modulo a prime. Assumes $0 < N \leq MOD$.

Time: $\mathcal{O}(N)$ construction and $\mathcal{O}(1)$ per query.

"mint.h"

d5edbb, 17 lines

```
struct combi {
    int N; vector<mint> fac, ifac, inv;
    combi(int _N) : N(_N), fac(_N), ifac(_N),
        inv(_N) {
        assert(0 < N && N <= MOD);
        fac[0] = ifac[0] = 1;
        if (N > 1) inv[1] = 1;
        rep(i,2,N) inv[i] = inv[MOD % i] * (-MOD / i);
        rep(i,1,N) {
            fac[i] = fac[i - 1] * i;
            ifac[i] = ifac[i - 1] * inv[i];
        }
        inline mint ncr(int n, int r) const {
            assert(0 <= n && n < N);
            return n < r || r < 0 ? 0 : fac[n] * ifac[r] * ifac[n - r];
        }
    };
};
```

ModInverse.h

Description: Pre-computation of modular inverses. Assumes $LIM \leq \text{mod}$ and that mod is a prime.

"6f684f, 3 lines"

```
const ll mod = 1000000007, LIM = 200000;
ll* inv = new ll[LIM] - 1; inv[1] = 1;
rep(i,2,LIM) inv[i] = mod - (mod / i) * inv[mod % i] % mod;
```

ModPow.h

const ll mod = 1000000007; *// faster if const*

b83e45, 8 lines

```
ll modpow(ll b, ll e) {
    ll ans = 1;
    for (; e; b = b * b % mod, e /= 2)
        if (e & 1) ans = ans * b % mod;
    return ans;
}
```

ModLog.h

Description: Returns the smallest $x > 0$ s.t. $a^x = b \pmod m$, or -1 if no such x exists. $\text{modLog}(a,1,m)$ can be used to calculate the order of a .

Time: $\mathcal{O}(\sqrt{m})$

c040b8, 11 lines

```
ll modLog(ll a, ll b, ll m) {
    ll n = (ll) sqrt(m) + 1, e = 1, f = 1, j = 1;
    unordered_map<ll, ll> A;
    while (j <= n && (e = f = e * a % m) != b % m)
        A[e * b % m] = j++;
    if (e == b % m) return j;
    if (__gcd(m, e) == __gcd(m, b))
        rep(i,2,n+2) if (A.count(e = e * f % m))
            return n * i - A[e];
    return -1;
}
```

ModSum.h

Description: Sums of mod'ed arithmetic progressions. $\text{modsum}(to, c, k, m) = \sum_{i=0}^{to-1} (ki + c) \% m$. divsum is similar but for floored division.

Time: $\log(m)$, with a large constant.

5c5bc5, 16 lines

```
typedef unsigned long long ull;
ull sumsq(ull to) { return to / 2 * ((to-1) | 1); }

ull divsum(ull to, ull c, ull k, ull m) {
    ull res = k / m * sumsq(to) + c / m * to;
    k %= m; c %= m;
    if (!k) return res;
    ull to2 = (to * k + c) / m;
    return res + (to - 1) * to2 - divsum(to2, m - 1 - c, m, k);
}

ll modsum(ull to, ll c, ll k, ll m) {
    c = ((c % m) + m) % m;
    k = ((k % m) + m) % m;
    return to * c + k * sumsq(to) - m * divsum(to, c, k, m);
}
```

ModMulLL.h

Description: Calculate $a \cdot b \bmod c$ (or $a^b \bmod c$) for $0 \leq a, b \leq c \leq 7.2 \cdot 10^{18}$.

Time: $\mathcal{O}(1)$ for modmul , $\mathcal{O}(\log b)$ for modpow

bb5d8f, 11 lines

```
typedef unsigned long long ull;
ull modmul(ull a, ull b, ull M) {
    ll ret = a * b - M * ull(1.L / M * a * b);
    return ret + M * (ret < 0) - M * (ret >= (1L - M));
}

ull modpow(ull b, ull e, ull mod) {
    ull ans = 1;
    for (; e; b = modmul(b, b, mod), e /= 2)
        if (e & 1) ans = modmul(ans, b, mod);
    return ans;
}
```

ModSqrt.h

Description: Tonelli-Shanks algorithm for modular square roots. Finds x s.t. $x^2 = a \pmod p$ ($-x$ gives the other solution).

Time: $\mathcal{O}(\log^2 p)$ worst case, $\mathcal{O}(\log p)$ for most p

"ModPow.h"

19a793, 24 lines

```
ll sqrt(ll a, ll p) {
    a %= p; if (a < 0) a += p;
    if (a == 0) return 0;
    assert(modpow(a, (p-1)/2, p) == 1); // else no solution
    if (p % 4 == 3) return modpow(a, (p+1)/4, p);
    // a^(n+3)/8 or 2^(n+3)/8 * 2^(n-1)/4 works
    if p % 8 == 5
        ll s = p - 1, n = 2;
        int r = 0, m;
        while (s % 2 == 0)
            ++r, s /= 2;
        while (modpow(n, (p - 1) / 2, p) != p - 1)
            ++n;
        ll x = modpow(a, (s + 1) / 2, p);
        ll b = modpow(a, s, p), g = modpow(n, s, p);
        for (;;) {
            ll t = b;
```

LinearSieve.h

Description: Can be used to precompute multiplicative functions using $f(px) = f(p)f(x)$ when $p \nmid x$. We compute $f(px) = f(p^{e+1} \cdot x/p^e) = f(p^{e+1})f(x/p^e)$ by multiplicativity (bookkeeping e , the max power of p dividing x where p is the smallest prime dividing x). If $f(px)$ can be computed easily when $p \mid x$ then we can simplify the code.

Time: $\mathcal{O}(n)$

e696bd, 16 lines

```
int func[N],cnt[N]; bool isc[N]; V<int> prime;
void sieve (int n) {
    fill(isc, isc + n, false); func[1] = 1;
    for (int i = 2; i < n; ++i) {
        if (!isc[i]) {
            prime.push_back(i); func[i]=1; cnt[i]=1;
        }
        for (int j = 0; j < prime.size () && i * prime[j] < n; ++j) {
            isc[i * prime[j]] = true;
            if (i % prime[j] == 0) {
                func[i * prime[j]] = func[i] / cnt[i] * (cnt[i] + 1);
                cnt[i * prime[j]] = cnt[i] + 1; break;
            } else {
                func[i * prime[j]] = func[i] * func[prime[j]];
                cnt[i * prime[j]] = 1;
            }
        }
    }
}
```

phiFunction.h

Description: Euler's ϕ function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n . $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p - 1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1}p_2^{k_2}...p_r^{k_r}$ then $\phi(n) = (p_1 - 1)p_1^{k_1-1}...(p_r - 1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n} (1 - 1/p)$. $\sum_{d|n} \phi(d) = n$, $\sum_{1 \leq k \leq n, \gcd(k,n)=1} k = n\phi(n)/2, n > 1$.

Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod n$.

Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod p \forall a \nmid p$

cd7dcd, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
    rep(i,0,LIM) phi[i] = i&1 ? i : i/2;
    for (int i = 3; i < LIM; i += 2) if(phi[i] == i)
        for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

FastEratosthenes.h

Description: Prime sieve for generating all primes smaller than LIM.

Time: $LIM=1e9 \approx 1.5s$

6b2912, 20 lines

```
const int LIM = 1e6;
```

MillerRabin.h

Description: Deterministic Miller-Rabin primality test. Guaranteed to work for numbers up to $7 \cdot 10^{18}$; for larger numbers, use Python and extend A randomly.

Time: 7 times the complexity of $a^b \bmod c$.

"ModMulLL.h"

60dcd1, 12 lines

```
bool isPrime(ull n) {
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    ull A[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022},
        s = __builtin_ctzll(n-1), d = n >> s;
    for (ull a : A) { // ^ count trailing zeroes
        ull p = modpow(a%n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i --)
            p = modmul(p, p, n);
        if (p != n-1 && i != s) return 0;
    }
    return 1;
}
```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).

Time: $\mathcal{O}\left(n^{1/4}\right)$, less for numbers with small factors.

"ModMulLL.h", "MillerRabin.h"

d8d98d, 18 lines

```
ull pollard(ull n) {
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    auto f = [&](ull x) { return modmul(x, x, n) + i; };
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
        if ((q = modmul(prd, max(x,y) - min(x,y), n)) prd = q;
            x = f(x), y = f(f(y));
        }
        return __gcd(prd, n);
    }
    vector<ull> factor(ull n) {
```

```
    if (n == 1) return {};  
    if (isPrime(n)) return {n};  
    ull x = pollard(n);  
    auto l = factor(x), r = factor(n / x);  
    l.insert(l.end(), all(r));  
    return l;  
}
```

5.3 Divisibility

CRT.h

Description: Chinese Remainder Theorem.
crt(a, m, b, n) computes x such that $x \equiv a \pmod m$, $x \equiv b \pmod n$. If $|a| < m$ and $|b| < n$, x will obey $0 \leq x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.
Time: $\log(n)$

"euclid.h"	04d93a, 7 lines
<pre>ll crt(ll a, ll m, ll b, ll n) { if (n > m) swap(a, b), swap(m, n); ll x, y, g = euclid(m, n, x, y); assert((a - b) % g == 0); // else no solution x = (b - a) % n * x % n / g * m + a; return x < 0 ? x + mn/g : x; }</pre>	

5.3.1 Bézout’s identity

For $a \neq, b \neq 0$, then $d = \gcd(a, b)$ is the smallest positive integer for which there are integer solutions to $ax + by = d$. If (x, y) is one solution, then all solutions are given by $(x + kb/d, y - ka/d)$, $k \in \mathbb{Z}$. Find one solution using egcd.

5.4 Fractions

FracBinarySearch.h

Description: Given f and N , finds the smallest fraction $p/q \in [0, 1]$ such that $f(p/q)$ is true, and $p, q \leq N$. You may want to throw an exception from f if it finds an exact solution, in which case N can be removed.
Usage: fracBS({}(Frac f) { return f.p>=3*f.q; }, 10); // {1,3}
Time: $\mathcal{O}(\log(N))$

struct Frac { ll p, q; };	27ab3e, 25 lines
<pre>template<class F> Frac fracBS(F f, ll N) { bool dir = 1, A = 1, B = 1; Frac lo{0, 1}, hi{1, 1}; // Set hi to 1/0 to search (0, N] if (f(lo)) return lo; assert(f(hi)); while (A B) { ll adv = 0, step = 1; // move hi if dir, else lo for (int si = 0; step; (step *= 2) >= si) { adv += step; Frac mid{lo.p * adv + hi.p, lo.q * adv + hi.q}; if (abs(mid.p) > N mid.q > N dir == !f(mid)) { adv -= step; si = 2; } hi.p += lo.p * adv; hi.q += lo.q * adv; dir = !dir; } }</pre>	

CRT FracBinarySearch IntPerm multinomial

```
        swap(lo, hi);  
        A = B; B = !adv;  
    }  
    return dir ? hi : lo;  
}
```

5.5 Mobius Function

$$\mu(n) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \Leftrightarrow f(n) = \sum_{d|n} \mu(d)g(n/d)$$

Other useful formulas/forms:

$$\sum_{d|n} \mu(d) = [n = 1], \phi(n) = \sum_{d|n} \mu(d) \frac{n}{d}$$

$$g(n) = \sum_{n|d} f(d) \Leftrightarrow f(n) = \sum_{n|d} \mu(\frac{d}{n})g(d)$$

$$g(n) = \sum_{1 \leq m \leq n} f(\lfloor \frac{n}{m} \rfloor) \Leftrightarrow f(n) = \sum_{1 \leq m \leq n} \mu(m)g(\lfloor \frac{n}{m} \rfloor)$$

If f multiplicative, $\sum_{d|n} \mu(d)f(d) = \prod_{\text{prime } p|n} (1 - f(p))$ and $\sum_{d|n} \mu^2(d)f(d) = \prod_{\text{prime } p|n} (1 + f(p))$.

If $s_f(n) = \sum_{i=1}^n f(i)$ is a prefix sum of multiplicative f then $s_{f*g}(n) = \sum_{1 \leq xy \leq n} f(x)g(y)$. Then $s_f(n) = \{s_{f*g}(n) - \sum_{d=2}^n s_f(\lfloor n/d \rfloor)g(d)\}/g(1)$ where $f * g(n) = \sum_{d|n} f(d)g(n/d)$ (Dirichlet).

Precompute (linear sieve) $\mathcal{O}(n^{2/3})$ first values of s_f for complexity $\mathcal{O}(n^{2/3})$.

Useful sums and convolutions: $\epsilon = \mu * \mathbf{1}$, $\text{id} = \phi * \mathbf{1}$, $\text{id} = g * \text{id}_2$, where $\epsilon(n) = [n = 1]$, $\mathbf{1}(n) = 1$, $\text{id}(n) = n$, $\text{id}_k(n) = n^k$, $g(n) = \sum_{d|n} \mu(d)nd$.

coprime pairs in $[1, n]$ is $\sum_{d=1}^n \mu(d) \lfloor n/d \rfloor^2$. Sum of GCD pairs in $[1, n]$ is $\sum_{d=1}^n \phi(d) \lfloor n/d \rfloor^2$. Sum of LCM pairs in $[1, n]$ is $\sum_{d=1}^n (\frac{\lfloor n/d \rfloor (1 + \lfloor n/d \rfloor)}{2})^2 g(d)$, where g is defined above with $g(p^k) = p^k - p^{k+1}$.

Combinatorial (6)

6.1 Permutations

IntPerm.h

Description: Permutation -> integer conversion. (Not order preserving.) Integer -> permutation can use a lookup table.
Time: $\mathcal{O}(n)$

int permToInt(vi& v) { int use = 0, i = 0, r = 0; for(int x:v) r = r * ++i + __builtin_popcount(use & -(1<<x)), use = 1 << x; // (note: minus, not ~!) return r; }	044568, 6 lines
---	-----------------

multinomial.h

Description: Computes $\binom{v_0+\cdots+v_{n-1}}{v_0,\dots,v_{n-1}}$ a0a312, 6 lines

```
ll multinomial(vi& v) {  
    ll c = 1, m = v.empty() ? 1 : v[0];  
    rep(i, 1, sz(v)) rep(j, 0, v[i])  
        c = c * ++m / (j+1);  
    return c;  
}
```

Cycles Let $g_S(n)$ be the number of n -permutations whose cycle lengths all belong to the set S . Then $\sum_{n \geq 0} g_S(n) \frac{x^n}{n!} = \exp\left(\sum_{n \in S} \frac{x^n}{n}\right)$
Derangements Permutations of a set such that none of the elements appear in their original position. $D(n) = (n - 1)(D(n - 1) + D(n - 2)) = nD(n - 1) + (-1)^n = \lfloor \frac{n!}{e} \rfloor$

Burnside’s Lemma Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals $\frac{1}{|G|} \sum_{g \in G} |X^g|$, where X^g are the elements fixed by g ($g.x = x$). If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get $g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k)\phi(n/k)$.

Partition function Number of ways of writing n as a sum of positive integers, disregarding the order of the summands. $p(0) = 1$, $p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k - 1)/2)$. $p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$
First few values: 1, 1, 2, 3, 5, 7, 11, 15, 22, 30.
 $p(20) = 627, p(50) \approx 2e5, p(100) \approx 2e8$.

Lucas’ Theorem: Let n, m be non-negative integers and p a prime. Write $n = n_k p^k + \dots + n_1 p + n_0$ and $m = m_k p^k + \dots + m_1 p + m_0$. Then $\binom{n}{m} \equiv \prod_{i=0}^k \binom{n_i}{m_i} \pmod p$.

Bernoulli numbers EGF of Bernoulli numbers is $B(t) = \frac{t}{e^t - 1}$ (FFT-able). $\sum \frac{B_i}{i!} x^i = \frac{x}{1 - e^{-x}}$.

$B[0, \dots] = [1, -\frac{1}{2}, \frac{1}{6}, 0, -\frac{1}{30}, 0, \frac{1}{42}, \dots]$.
Sums of powers:

$$\sum_{i=1}^n n^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k \cdot (n+1)^{m+1-k}$$

Stirling numbers of the first kind Number of permutations on n items with k cycles.
 $c(n, k) = c(n - 1, k - 1) + (n - 1)c(n - 1, k)$,
 $c(0, 0) = 1, \sum_{k=0}^n c(n, k)x^k = x(x + 1) \dots (x + n - 1)$
 $c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$
 $c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$
Stirling numbers of the second kind Partitions of n distinct elements into exactly k non-empty subsets. $S(n, k) = S(n - 1, k - 1) + kS(n - 1, k)$.
 $S(n, 1) = S(n, n) = 1$.
 $S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$.

Eulerian numbers Number of n -permutations with exactly k rises (positions i with $p_i > p_{i-1}$).
 $E(n, k) = (n - k)E(n - 1, k - 1) + (k + 1)E(n - 1, k)$.
 $E(n, 0) = E(n, n - 1) = 1$.
 $E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k + 1 - j)^n$.
Bell numbers Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$
 $B(3) = 5 = \{a|b|c, a|bc, b|ac, c|ab, abc\}$. For p prime, $B(p^m + n) \equiv mB(n) + B(n + 1) \pmod p$.

Catalan numbers
 $C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$
 $C_0 = 1, C_{n+1} = \frac{2(2n+1)}{n+2} C_n, C_{n+1} = \sum C_i C_{n-i}$
 $C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$
- UR path from $(0, 0)$ to (n, n) below $y = x$.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n + 1$ leaves (0 or 2 children).
- ordered trees with $n + 1$ vertices.
- ways a convex polygon with $n + 2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

Labeled unrooted trees: # on n vertices: n^{n-2}
on k existing trees of size n_i : $n_1 n_2 \dots n_k n^{k-2}$
with degrees d_i : $(n - 2)! / ((d_1 - 1)! \dots (d_n - 1)!)$
ways to connect k components with $k - 1$ edges: $s_1 \dots s_k \cdot n^{k-2}$

Number of Spanning Trees Create an $N \times N$ matrix mat, and for each edge $a \rightarrow b \in G$, do mat[a][b]--, mat[b][b]++ (and mat[b][a]--, mat[a][a]++ if G is undirected). Remove the i th row and column and take the determinant; this yields the number of directed spanning trees rooted at i (if G is undirected, remove any row/column).
Erdős–Gallai theorem A simple graph with node degrees $d_1 \geq \dots \geq d_n$ exists iff $d_1 + \dots + d_n$ is even and for every $k = 1 \dots n$,

$$\sum_{i=1}^k d_i \leq k(k - 1) + \sum_{i=k+1}^n \min(d_i, k).$$

Sprague-Grundy Theorem: Viewing the game as a DAG, where a player moves from one node v to to

Graph (7)

7.1 Shortest Paths

BellmanFord.h
Description: Calculates shortest paths from s in a graph that might have negative edge weights. Unreachable nodes get $\text{dist} = \text{inf}$; nodes reachable through negative-weight cycles get $\text{dist} = -\text{inf}$. Assumes $V^2 \max |w_i| < \sim 2^{63}$.
Time: $\mathcal{O}(VE)$

```
const ll inf = LLONG_MAX;
struct Ed { int a, b, w, s() { return a < b ? a : -a; }};
struct Node { ll dist = inf; int prev = -1; };

void bellmanFord(vector<Node>& nodes, vector<Ed>& eds, int s) {
    nodes[s].dist = 0;
    sort(all(eds), [](Ed a, Ed b) { return a.s() < b.s(); });

    int lim = sz(nodes) / 2 + 2; // /3+100 with shuffled vertices
    rep(i,0,lim) for (Ed ed : eds) {
        Node cur = nodes[ed.a], &dest = nodes[ed.b];
        if (abs(cur.dist) == inf) continue;
        ll d = cur.dist + ed.w;
        if (d < dest.dist) {
            dest.prev = ed.a;
            dest.dist = (i < lim-1 ? d : -inf);
        }
    }
    rep(i,0,lim) for (Ed e : eds) {
        if (nodes[e.a].dist == -inf)
            nodes[e.b].dist = -inf;
    }
}
```

830a8f, 23 lines

FloydWarshall.h

Description: Calculates all-pairs shortest path in a directed graph that might have negative edge weights. Input is an distance matrix m , where $m[i][j] = \text{inf}$ if i and j are not adjacent. As output, $m[i][j]$ is set to the shortest distance between i and j , inf if no path, or $-\text{inf}$ if the path goes through a negative-weight cycle.
Time: $\mathcal{O}(N^3)$

```
const ll inf = 1LL << 62;
void floydWarshall(vector<vector<ll>>& m) {
    int n = sz(m);
    rep(i,0,n) m[i][i] = min(m[i][i], 0LL);
    rep(k,0,n) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) {
            auto newDist = max(m[i][k] + m[k][j], -inf);
            m[i][j] = min(m[i][j], newDist);
        }
    rep(k,0,n) if (m[k][k] < 0) rep(i,0,n) rep(j,0,n)
        if (m[i][k] != inf && m[k][j] != inf) m[i][j] = -inf;
}
```

531245, 12 lines

Johnson.h

Description: APSP on weighted directed graphs with no negative cycles. Add a dummy node q connected by 0-weighted edge to each other node. Then run Bellman from q to find minimum weight $h(v)$ of a path $q \rightsquigarrow v$ (terminate if negative cycle found). Next, reweight the original graph: $\forall u \rightarrow v$ with weight $w(u,v)$, assign new weight $w(u,v) + h(u) - h(v)$. Now $D(u,v) = \text{Dijkstra}(u,v) + h(v) - h(u)$.
Time: $\mathcal{O}(\text{Bellman}) + \mathcal{O}(V) * \mathcal{O}(\text{Dijkstra})$

7.2 Network flow

Dinic.h

Description: Flow algorithm. with complexity
Time: $\mathcal{O}(VE \log U)$ where $U = \max |\text{cap}|$. $\mathcal{O}(\min(E^{1/2}, V^{2/3})E)$ if $U = 1$; $\mathcal{O}(\sqrt{VE})$ for bipartite matching.

d7f0f1, 40 lines

```
struct Dinic {
    struct Edge {
        int to, rev; ll c, oc;
        ll flow() { return max(oc - c, 0LL); }
    }; // .flow() gives actual flow
    vi lvl, ptr, q;
    vector<vector<Edge>> adj;
    Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
    void addEdge(int a, int b, ll c, ll rcap=0) {
        adj[a].push_back({b, sz(adj[b]), c, c});
        adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
    } // rcap = c on bidirectional
    ll dfs(int v, int t, ll f) {
        if (v == t || !f) return f;
        for (int& i = ptr[v]; i < sz(adj[v]); i++){
            Edge& e = adj[v][i];
            if (lvl[e.to] == lvl[v] + 1)
                if (ll p = dfs(e.to, t, min(f,e.c))) {
                    e.c -= p, adj[e.to][e.rev].c += p;
                    return p;
                }
        }
        return 0;
    }
    ll calc(int s, int t) {
        ll flow = 0; q[0] = s;
        rep(L,0,31) do { // 'int L=30' maybe faster for random data
            lvl = ptr = vi(sz(q));
            int qi = 0, qe = lvl[s] = 1;
            while (qi < qe && !lvl[t]) {
                int v = q[qi++];
                for (Edge e : adj[v])
                    if (!lvl[e.to] && e.c >> (30 - L))
                        q[qe++] = e.to, lvl[e.to] = lvl[v] + 1;
            }
            while (ll p = dfs(s,t,LLONG_MAX)) flow += p;
        } while (lvl[t]);
        return flow;
    }
    bool leftOfMinCut(int a) {return lvl[a] != 0;}
};
```

PushRelabel.h

Description: Push-relabel using the highest label selection rule and the gap heuristic. Quite fast in practice. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(V^2 \sqrt{E})$

2fd373, 40 lines

```
struct PushRelabel {
```

```
struct Edge { int dest, back; ll f, c; };
vector<vector<Edge>> g; vector<ll> ec;
vector<Edge>> cur; vector<vi> hs; vi H;
PushRelabel(int n) : g(n), ec(n), cur(n), hs(2*n), H(n) {}
void addEdge(int s, int t, ll cap, ll rcap=0) {
    if (s == t) return;
    g[s].push_back({t, sz(g[t]), 0, cap});
    g[t].push_back({s, sz(g[s]) - 1, 0, rcap});
} // rcap = cap on bidirectional
void addFlow(Edge& e, ll f) {
    Edge &back = g[e.dest][e.back];
    if (!ec[e.dest] && f) hs[H[e.dest]].push_back(e.dest);
    e.f += f; e.c -= f; ec[e.dest] += f;
    back.f -= f; back.c += f; ec[back.dest] -= f;
}
ll calc(int s, int t) {
    int v = sz(g); H[s] = v; ec[t] = 1;
    vi co(2*v); co[0] = v-1;
    rep(i,0,v) cur[i] = g[i].data();
    for (Edge& e : g[s]) addFlow(e, e.c);

    for (int hi = 0;;) {
        while (hs[hi].empty()) if (!hi--) return -ec[s];
        int u = hs[hi].back(); hs[hi].pop_back();
        while (ec[u] > 0) { // discharge u
            if (cur[u] == g[u].data() + sz(g[u])) {
                H[u] = 1e9;
                for (Edge& e : g[u]) if (e.c && H[u] > H[e.dest] + 1)
                    H[u] = H[e.dest] + 1, cur[u] = &e;
                if (++co[H[u]], !--co[hi] && hi < v)
                    rep(i,0,v) if (hi < H[i] && H[i] < v)
                        --co[H[i]], H[i] = v + 1;
                hi = H[u];
            } else if (cur[u] -> c && H[u] == H[cur[u] -> dest] + 1)
                addFlow(*cur[u], min(ec[u], cur[u] -> c));
            else ++cur[u];
        }
    }
}
bool leftOfMinCut(int a) {return H[a] >= sz(g);}
```

MinCostMaxFlow.h

Description: Min-cost max-flow. If costs can be negative, call `setpi` before maxflow, but note that negative cost cycles are not supported. To obtain the actual flow, look at positive values only.

Time: $\mathcal{O}(FE \log(V))$ where F is max flow. $\mathcal{O}(VE)$ for `setpi`.

15e3e9, 62 lines

```
#include <bits/extc++.h>
const ll INF = numeric_limits<ll>::max() / 4;
```

```
struct MCMF {
    struct edge {
        int from, to, rev; ll cap, cost, flow;
    };
    int N; V<V<edge>> ed; vi seen;
    V<ll> dist, pi; V<edge>& par;
    MCMF(int N) : N(N), ed(N), seen(N),
        dist(N), pi(N), par(N) {}
    void addEdge(int from, int to, ll cap, ll cost) {
        if (from == to) return;
```

```
ed[from].push_back(edge{ from,to,sz(ed[to]),cap,cost,0 });
ed[to].push_back(edge{ to,from,sz(ed[from])-1,0,-cost,0 });
}
void path(int s) {
    fill(all(seen), 0); fill(all(dist), INF);
    dist[s] = 0; ll di;
    __gnu_pbds::priority_queue<pair<ll,int>>q;
    V<decltype(q)::point_iterator> its(N);
    q.push({ 0, s });
    while (!q.empty()) {
        s = q.top().second; q.pop();
        seen[s] = 1; di = dist[s] + pi[s];
        for (edge& e : ed[s]) if (!seen[e.to]) {
            ll val = di - pi[e.to] + e.cost;
            if (e.cap - e.flow > 0 && val < dist[e.to]) {
                dist[e.to] = val; par[e.to] = &e;
                if (its[e.to] == q.end())
                    its[e.to] = q.push({ -dist[e.to], e.to });
                else q.modify(its[e.to], { -dist[e.to], e.to });
            }
        }
        rep(i,0,N) pi[i] = min(pi[i] + dist[i], INF);
    } // Hash without maxflow() setpi() = 061a45
    pair<ll, ll> maxflow(int s, int t) {
        ll totflow = 0, totcost = 0;
        while (path(s), seen[t]) {
            ll fl = INF;
            for (edge* x = par[t]; x; x = par[x->from])
                fl = min(fl, x->cap - x->flow);
            totflow += fl;
            for (edge* x = par[t]; x; x = par[x->from]) {
                x->flow += fl;
                ed[x->to][x->rev].flow -= fl;
            }
        }
        rep(i,0,N) for (edge& e : ed[i]) totcost += e.cost * e.flow;
        return {totflow, totcost/2};
    } // Hash without setpi() = d04eb5
    void setpi(int s) {
        fill(all(pi), INF); pi[s] = 0;
        int it = N, ch = 1; ll v;
        while (ch-- && it--)
            rep(i,0,N) if (pi[i] != INF)
                for (edge& e : ed[i]) if (e.cap)
                    if ((v = pi[i] + e.cost) < pi[e.to])
                        pi[e.to] = v, ch = 1;
            assert(it >= 0); // negative cost cycle
    }
};
```

MinCut.h

Description: After running max-flow, the left side of a min-cut from s to t is given by all vertices reachable from s , only traversing edges with positive residual capacity.

GlobalMinCut.h

Description: Find a global minimum cut in an undirected graph, as represented by an adjacency matrix.

Time: $\mathcal{O}(V^3)$

8b0e19, 21 lines

Time 2 ($\mathcal{V}$) **Flow Computations** at [t][t], co[t][t];

Time 2 ($\mathcal{V}$) **Flow Computations** at [t][t], co[t][t];

$F(v) = \sum_{(x,v)} l(x,v) - \sum_{(v,x)} l(v,x)$. Also set new upperbounds to $c(e) - l(e)$.

Max flow with lower bound (no demands):
 Binary search on max flow F . Add edge $T \rightarrow S$ with bounds $[F, \infty]$, and set all $d(v) = 0$. Now feasibility implies that a construction with at least F flow

```

matching, and the complement is a maximum independent
set.
"HopcroftKarp.h" 23c286, 18 lines
vi cover(vector<vi>& g, int n, int m) {
    vi match(m, -1);
    int res = hopcroftKarp(g, match);
    vector<bool> lfound(n, true), seen(m);

```

```

Probability  $N/\text{mod}$ .
Time:  $\mathcal{O}(N^3)$ 
"../numerical/MatrixInverse-mod.h" 9ecad0, 37 lines
V<pii> generalMatrixInverse(int N, V<pii>& ed) {
V<V<ll>> mat(N, V<ll>>(int) N), A;
for (pii pa : ed) {
    int a=pa.first,b=pa.second,r=rand()%mod;

```

Time 2 ($\mathcal{V}$) **Flow Computations** at [t][t], co[t][t];

```
int low=val[j]=++Time, x; z.push_back(j);
for (auto e : g[j]) if (comp[e] < 0)
    low = min(low, val[e] ? : dfs(e,g,f));
if (low == val[j]) {
    do {
        x = z.back(); z.pop_back();
        comp[x] = ncomps; cont.push_back(x);
    } while (x != j);
    f(cont); cont.clear(); ncomps++;
}
return val[j] = low;
}

template<class G,class F> void scc(G& g, F f){
    int n = sz(g);
    val.assign(n, 0); comp.assign(n, -1);
    Time = ncomps = 0;
    rep(i,0,n) if (comp[i] < 0) dfs(i, g, f);
}
```

BiconnectedComponents.h

Description: Finds all biconnected components in an undirected graph, and runs a callback for the edges in each. In a biconnected component there are at least two distinct paths between any two nodes. Note that a node can be in several components. An edge which is not in a component is a bridge. A node is a cut point if (1) Exists in multiple bccs, or (2) Endpoint of a bridge with degree > 1 (self loops don't count as degree).

Usage: int eid = 0; g.resize(N);
for each edge (a,b) {
g[a].emplace_back(b, eid);
g[b].emplace_back(a, eid++); }
bicomps([&](const vi& edgelist) {...});

Time: $\mathcal{O}(E + V)$

```
vector<vector<pii>> g;
vi num, st; int Time;
template<class F>
int dfs(int at, int par, F& f) {
    int me = num[at] = ++Time, top = me;
    for (auto [y, e] : g[at]) if (e != par) {
        if (num[y]) {
            top = min(top, num[y]);
            if (num[y] < me) st.push_back(e);
        } else {
            int si = sz(st), up = dfs(y, e, f);
            top = min(top, up);
            if (up == me) {
                st.push_back(e);
                f(vi(st.begin() + si, st.end()));
                st.resize(si);
            }
            else if (up < me) st.push_back(e);
            else { /* e is a bridge */ }
        }
    }
    return top;
}

template<class F> void bicomps(F f) {
    Time = 0; num.assign(sz(g), 0);
    rep(i,0,sz(g)) if (!num[i]) dfs(i, -1, f);
}
```

BlockCutTree.h

Description: Finds the block-cut tree of a bidirectional graph. Tree nodes are either cut points or a block. All edges are between a block and a cut point. Combining all nodes in a block with its neighbor cut points give the whole BCC.

Usage: art[i] = true if cut point. Cut-points are relabeled within [1,ncut]. Higher labels are for blocks. Resets: art, g[1,n], tree[1,ptr], st, comp[1,cur], ptr, cur, in;

```
bitset <N> art;
vector <int> g[N], tree[N], st, comp[N];
int n, m, ptr, cur, ncut, in[N],low[N],id[N];
void dfs (int u, int from = -1) {
    in[u] = low[u] = ++ptr; st.emplace_back(u);
    for (int v : g[u]) if (v ^ from) {
        if (!in[v]) {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] >= in[u]) {
                art[u] = in[u] > 1 or in[v] > 2;
                comp[++cur].emplace_back(u);
                while (comp[cur].back() ^ v) {
                    comp[cur].emplace_back(st.back());
                    st.pop_back();
                }
            } else { low[u] = min(low[u], in[v]); }
        }
    }
}

void buildTree() {
    ptr = 0;
    for (int i = 1; i <= n; ++i) {
        if (art[i]) id[i] = ++ptr;
    } ncut = ptr;
    for (int i = 1; i <= cur; ++i) {
        int x = ++ptr;
        for (int u : comp[i]) {
            if (art[u]) {
                tree[x].emplace_back(id[u]);
                tree[id[u]].emplace_back(x);
            } else { id[u] = x; }
        }
    }
}

int main() {
    for (int i = 1; i <= n; ++i)
        if (!in[i]) dfs(i);
    buildTree();
}
```

2sat.h

Description: Calculates a valid assignment to boolean variables a, b, c,... to a 2-SAT problem, so that an expression of the type (a||b)&&(!a||c)&&(d||!b)&&... becomes true, or reports that it is unsatisfiable. Negated variables are represented by bit-inversions (~x).

Usage: TwoSat ts(number of boolean variables);
ts.either(0, ~3); // Var 0 is true or var 3 is false
ts.setValue(2); // Var 2 is true
ts.atMostOne({0,~1,2}); // <= 1 of vars 0, ~1 and 2 are true
ts.solve(); // Returns true iff it is solvable
ts.values[0..N-1] holds the assigned values to the vars

Time: $\mathcal{O}(N + E)$, where N is the number of boolean variables, and E is the number of clauses.

```
struct TwoSat {
    int N;
    vector<vi> gr;
    vi values; // 0 = false, 1 = true

    TwoSat(int n = 0) : N(n), gr(2*n) {}

    int addVar() { // (optional)
        gr.emplace_back();
        gr.emplace_back();
    }
}
```

```
return N++;
}

void either(int f, int j) {
    f = max(2*f, -1-2*f);
    j = max(2*j, -1-2*j);
    gr[f].push_back(j^1);
    gr[j].push_back(f^1);
}

void setValue(int x) { either(x, x); }

void atMostOne(const vi& li) { // (optional)
    if (sz(li) <= 1) return;
    int cur = ~li[0];
    rep(i,2,sz(li)) {
        int next = addVar();
        either(cur, ~li[i]);
        either(cur, next);
        either(~li[i], next);
        cur = ~next;
    }
    either(cur, ~li[1]);
}

vi val, comp, z; int time = 0;
int dfs(int i) {
    int low = val[i] = ++time, x; z.push_back(i);
    for(int e : gr[i]) if (!comp[e])
        low = min(low, val[e] ? : dfs(e));
    if (low == val[i]) do {
        x = z.back(); z.pop_back();
        comp[x] = low;
        if (values[x>>1] == -1)
            values[x>>1] = x&1;
    } while (x != i);
    return val[i] = low;
}

bool solve() {
    values.assign(N, -1);
    val.assign(2*N, 0); comp = val;
    rep(i,0,2*N) if (!comp[i]) dfs(i);
    rep(i,0,N) if (comp[2*i] == comp[2*i+1])
        return 0;
    return 1;
}

};
```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}(V + E)$

```
vi eulerWalk(vector<vector<pii>>& gr, int
    nedges, int src=0) {
    int n = sz(gr);
    vi D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = sz(gr[x]);
```

```
if (it == end){ ret.push_back(x); s.
    pop_back(); continue; }
tie(y, e) = gr[x][it++];
if (!eu[e]) {
    D[x]--, D[y]++;
    eu[e] = 1; s.push_back(y);
}
}

for (int x : D) if (x < 0 || sz(ret) !=
    nedges+1) return {};
return {ret.rbegin(), ret.rend()};
}
```

De-Bruijn Sequence: of order n on a k -size alphabet A is a cyclic sequence in which every possible length n string on A occurs exactly once as a substring. $B(k,n)$ has length k^n and number of distinct sequences is $\{(k!)^{k^{n-1}}\}/k^n$. Find an Euler tour on graph where nodes are $n - 1$ length strings and each node has k outgoing edges for each character.

GrayCode.h

Description: Sequence of binary strings where each successive values differ in only 1 bit. Can be used to find Hamiltonian cycle on n -dimensional hypercube by calling $g(0), ..., g(2^n - 1)$.

```
int g (int n) { return n ^ (n >> 1); }
int rev_g (int g) { int n = 0;
    for (; g; g >= 1) n ^= g;
    return n;
}
```

7.5 Coloring

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D , computes a $(D + 1)$ -coloring of the edges such that no neighboring edges share a color. (D -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

Time: $\mathcal{O}(NM)$

```
vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;

    for (pii e : eds) ++cc[e.first], ++cc[e.second];

    int u, v, ncols = *max_element(all(cc)) + 1;
    vector<vi> adj(N, vi(ncols, -1));
    for (pii e : eds) {
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);
        int at = u, end = u, d, c = free[u], ind = 0, i = 0;
        while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
            loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
        cc[loc[d]] = c;
        for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
            swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
        while (adj[fan[i]][d] != -1) {
            int left = fan[i], right = fan[++i], e = cc[i];
            adj[u][e] = left;
```

```
adj[left][e] = u;
adj[right][e] = -1;
free[right] = e;
}
adj[u][d] = fan[i];
adj[fan[i]][d] = u;
for (int y : {fan[0], u, end})
    for (int& z = free[y] = 0; adj[y][z] != -1; z++);
}
rep(i,0,sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
return ret;
}
```

7.6 Heuristics

MaximalCliques.h

Description: Runs a callback for all maximal cliques in a graph (given as a symmetric bitset matrix; self-edges not allowed). Callback is given a bitset representing the maximal clique.

Time: $\mathcal{O}\left(3^{n/3}\right)$, much faster for sparse graphs
b0d5b1, 12 lines

```
typedef bitset<128> B;
template<class F>
void cliques(vector<B>& eds, F f, B P = ~B(),
             B X={}, B R={}) {
    if (!P.any()) { if (!X.any()) f(R); return;
    }
    auto q = (P | X)._Find_first();
    auto cands = P & ~eds[q];
    rep(i,0,sz(eds)) if (cands[i]) {
        R[i] = 1;
        cliques(eds, f, P & eds[i], X & eds[i], R)
        ;
        R[i] = P[i] = 0; X[i] = 1;
    }
}
```

MaximumClique.h

Description: Quickly finds a maximum clique of a graph (given as symmetric bitset matrix; self-edges not allowed). Can be used to find a maximum independent set by finding a clique of the complement graph.

Time: Runs in about 1s for n=155 and worst case random graphs (p=.90). Runs faster for sparse graphs.
17e0be, 49 lines

```
typedef vector<bitset<200>> vb;
struct Maxclique {
    double limit=0.025, pk=0;
    struct Vertex { int i, d=0; };
    typedef vector<Vertex> vv;
    vb e;
    vv V;
    vector<vi> C;
    vi qmax, q, S, old;
    void init(vv& r) {
        for (auto& v : r) v.d = 0;
        for (auto& v : r) for (auto j : r) v.d += e[v.i][j.i];
        sort(all(r), [](auto a, auto b) { return a.d > b.d; });
        int mxD = r[0].d;
        rep(i,0,sz(r)) r[i].d = min(i, mxD) + 1;
    }
    void expand(vv& R, int lev = 1) {
        S[lev] += S[lev - 1] - old[lev];
        old[lev] = S[lev - 1];
    }
}
```

```
while (sz(R)) {
    if (sz(q) + R.back().d <= sz(qmax))
        return;
    q.push_back(R.back().i);
    vv T;
    for(auto v:R) if (e[R.back().i][v.i]) T.push_back({v.i});
    if (sz(T)) {
        if (S[lev]++ / ++pk < limit) init(T);
        int j = 0, mxk = 1, mnk = max(sz(qmax) - sz(q) + 1, 1);
        C[1].clear(), C[2].clear();
        for (auto v : T) {
            int k = 1;
            auto f = [&](int i) { return e[v.i][i]; };
            while (any_of(all(C[k]), f)) k++;
            if (k > mxk) mxk = k, C[mxk + 1].clear();
            if (k < mnk) T[j++].i = v.i;
            C[k].push_back(v.i);
        }
        if (j > 0) T[j - 1].d = 0;
        rep(k,mnk,mxk + 1) for (int i : C[k]) T[j].i = i, T[j++].d = k;
        expand(T, lev + 1);
    } else if (sz(q) > sz(qmax)) qmax = q;
    q.pop_back(), R.pop_back();
}
}
vi maxClique() { init(V), expand(V); return qmax; }
Maxclique(vb conn) : e(conn), C(sz(e)+1), S(sz(C)), old(S) {
    rep(i,0,sz(e)) V.push_back({i});
}
};
```

MaximumIndependentSet.h

Description: To obtain a maximum independent set of a graph, find a max clique of the complement. If the graph is bipartite, see MinimumVertexCover.

7.7 Trees

BinaryLifting.h

Description: Calculate power of two jumps in a tree, to support fast upward jumps and LCAs. Assumes the root node points to itself.

Time: construction $\mathcal{O}(N \log N)$, queries $\mathcal{O}(\log N)$
b1ce80, 25 lines

```
vector<vi> treeJump(vi& P){
    int on = 1, d = 1;
    while(on < sz(P)) on *= 2, d++;
    vector<vi> jmp(d, P);
    rep(i,1,d) rep(j,0,sz(P))
        jmp[i][j] = jmp[i-1][jmp[i-1][j]];
    return jmp;
}

int jmp(vector<vi>& tbl, int nod, int steps){
    rep(i,0,sz(tbl))
        if(steps&(1<<i)) nod = tbl[i][nod];
    return nod;
}

int lca(vector<vi>& tbl, vi& depth, int a, int b) {
    if (depth[a] < depth[b]) swap(a, b);
}
```

```
a = jmp(tbl, a, depth[a] - depth[b]);
if (a == b) return a;
for (int i = sz(tbl); i--;) {
    int c = tbl[i][a], d = tbl[i][b];
    if (c != d) a = c, b = d;
}
return tbl[0][a];
}
```

LCA.h

Description: Data structure for computing lowest common ancestors in a tree (with 0 as root). C should be an adjacency list of the tree, either directed or undirected.

Time: $\mathcal{O}(N \log N + Q)$

"/data-structures/RMQ.h" 0f62fb, 21 lines

```
struct LCA {
    int T = 0;
    vi time, path, ret;
    RMQ<int> rmq;

    LCA(vector<vi>& C) : time(sz(C)), rmq((dfs(C, 0,-1), ret)) {}

    void dfs(vector<vi>& C, int v, int par) {
        time[v] = T++;
        for (int y : C[v]) if (y != par) {
            path.push_back(v), ret.push_back(time[v]);
            dfs(C, y, v);
        }
    }

    int lca(int a, int b) {
        if (a == b) return a;
        tie(a, b) = minmax(time[a], time[b]);
        return path[rmq.path(a, b)];
    }

    //dist(a,b){return depth[a] + depth[b] - 2*depth[lca(a,b)];}
};
```

CompressTree.h

Description: Given a rooted tree and a subset S of nodes, compute the minimal subtree that contains all the nodes by adding all (at most $|S| - 1$) pairwise LCA's and compressing edges. Returns a list of (par, orig_index) representing a tree rooted at 0. The root points to itself.

Time: $\mathcal{O}(|S| \log |S|)$

"LCA.h" 9775a0, 21 lines

```
typedef vector<pair<int, int>> vpi;
vpi compressTree(LCA& lca, const vi& subset) {
    static vi rev; rev.resize(sz(lca.time));
    vi li = subset, &T = lca.time;
    auto cmp = [&](int a, int b) { return T[a] < T[b]; };
    sort(all(li), cmp);
    int m = sz(li)-1;
    rep(i,0,m) {
        int a = li[i], b = li[i+1];
        li.push_back(lca.lca(a, b));
    }
    sort(all(li), cmp);
    li.erase(unique(all(li)), li.end());
    rep(i,0,sz(li)) rev[li[i]] = i;
    vpi ret = {pii(0, li[0])};
    rep(i,0,sz(li)-1) {
        int a = li[i], b = li[i+1];
        ret.emplace_back(rev[lca.lca(a, b)], b);
    }
}
```

```
return ret;
}
```

HLD-easy.h

Description: Subtree of v: $[in_v, out_v)$. Path from v to the last vertex in ascending heavy path from v (which is nxt_v) will be in $[in_{nxt_v}, in_v]$.

Usage: each g[u] must not contain the parent. call dfs.sz(), then dfs.hld(). Be careful about switching to 1-indexing.

430255, 12 lines

```
void dfs_sz(int u = 0) { sz[u] = 1;
    for(auto &v: g[u]) {
        dfs_sz(v); sz[u] += sz[v];
        if(sz[v] > sz[g[u][0]]) swap(v, g[u][0]);
    }
}
void dfs_hld(int u = 0) { in[u] = t++;
    for(auto v: g[u]) {
        nxt[v] = (v == g[u][0] ? nxt[u] : v);
        dfs_hld(v);
    } out[u] = t;
}
```

HLD-ruhan.h

Description: 0-based indexing, HLDSegTree refers to the type of the segment tree The segment tree must have update([l, r], +dx) and query([l, r]) methods.

Time: $\mathcal{O}((\log N)^2)$ (not sure about this, though).
d12c9a, 69 lines

```
template<class T, class HLDSegTree>
class HLD {
    int n;
    V<int> par, heavy, level, root, tree_pos;
    HLDSegTree tree;
private:
    int dfs(const V<V<int>>& graph, int u);
    template<class BinOp>
    void process_path(int u, int v, BinOp op);
public:
    HLD(int n_, const V<V<int>>& graph) : n(n_),
        par(n), heavy(n, -1), level(n), root(n),
        tree_pos(n), tree(n) {
        par[0] = -1;
        level[0] = 0;
        dfs(graph, 0);
        int ii = 0;
        for(int u = 0; u < n; u++) {
            if(par[u] != -1 && heavy[par[u]] == u)
                continue;
            for(int v = u; v != -1; v = heavy[v]) {
                root[v] = u;
                tree_pos[v] = ii++;
            }
        }
    }
    void update(int u, int v, T val) {
        process_path(u, v, [this, val](int l, int r) { tree.update(l, r, val); });
    }
    T query(int u, int v) {
        T res = T();
        process_path(u, v, [this, &res](int l, int r) { res += tree.query(l, r); });
        return res;
    }
};
template<class T, class HLDSegTree>
```

```
int HLD<T, HLDSTree>::dfs(const V<V<int>>&
graph, int u) {
    int cc = 1, max_sub = 0;
    for(int v : graph[u]) {
        if(v == par[u]) continue;
        par[v] = u;
        level[v] = level[u] + 1;
        int sub = dfs(graph, v);
        if(sub > max_sub) {
            max_sub = sub;
            heavy[u] = v;
        }
        cc += sub;
    }
    return cc;
}
template<class T, class HLDSTree>
template<class BinOp>
void HLD<T, HLDSTree>::process_path(int u,
int v, BinOp op) {
    for(; root[u] != root[v]; v = par[root[v]])
    {
        if(level[root[u]] > level[root[v]]) swap
(u, v);
        op(tree_pos[root[v]], tree_pos[v]);
        assert(v != -1);
    }
    if(level[u] > level[v]) swap(u, v);
    op(tree_pos[u], tree_pos[v]);
}
```

LinkCutTree.h

Description: Represents a forest of unrooted trees. You can add and remove edges (as long as the result is still a forest), and check whether two nodes are in the same tree.

Time: All operations take amortized $\mathcal{O}(\log N)$
615462, 90 lines

```
struct Node { // Splay tree. Root's pp
contains tree's parent.
    Node *p = 0, *pp = 0, *c[2];
    bool flip = 0;
    Node() { c[0] = c[1] = 0; fix(); }
    void fix() {
        if (c[0]) c[0]->p = this;
        if (c[1]) c[1]->p = this;
        // (+ update sum of subtree elements etc.
        if wanted)
    }
    void pushFlip() {
        if (!flip) return;
        flip = 0; swap(c[0], c[1]);
        if (c[0]) c[0]->flip ^= 1;
        if (c[1]) c[1]->flip ^= 1;
    }
    int up() { return p ? p->c[1] == this : -1;
    }
    void rot(int i, int b) {
        int h = i ^ b;
        Node *x = c[i], *y = b == 2 ? x : x->c[h],
        *z = b ? y : x;
        if ((y->p = p)) p->c[up()] = y;
        c[i] = z->c[i ^ 1];
        if (b < 2) {
            x->c[h] = y->c[h ^ 1];
            y->c[h ^ 1] = x;
        }
        z->c[i ^ 1] = this;
        fix(); x->fix(); y->fix();
    }
    if (p) p->fix();
    swap(pp, y->pp);
}
void splay() {
    for (pushFlip(); p; ) {
        if (p->p) p->p->pushFlip();
        p->pushFlip(); pushFlip();
        int c1 = up(), c2 = p->up();
        if (c2 == -1) p->rot(c1, 2);
        else p->p->rot(c2, c1 != c2);
    }
}
Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(),
this);
}
}
struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}

    void link(int u, int v) { // add an edge (u,
v)
        assert(!connected(u, v));
        makeRoot(&node[u]);
        node[u].pp = &node[v];
    }
    void cut(int u, int v) { // remove an edge (
u, v)
        Node *x = &node[u], *top = &node[v];
        makeRoot(top); x->splay();
        assert(top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else {
            x->c[0] = top->p = 0;
            x->fix();
        }
    }
    bool connected(int u, int v) { // are u, v
in the same tree?
        Node* nu = access(&node[u])->first();
        return nu == access(&node[v])->first();
    }
    void makeRoot(Node* u) {
        access(u);
        u->splay();
        if(u->c[0]) {
            u->c[0]->p = 0;
            u->c[0]->flip ^= 1;
            u->c[0]->pp = u;
            u->c[0] = 0;
            u->fix();
        }
    }
    Node* access(Node* u) {
        u->splay();
        while (Node* pp = u->pp) {
            pp->splay(); u->pp = 0;
            if (pp->c[1]) {
                pp->c[1]->p = 0; pp->c[1]->pp = pp;
            }
            pp->c[1] = u; pp->fix(); u = pp;
        }
        return u;
    }
}
};
```

```
if (p) p->fix();
swap(pp, y->pp);
}
void splay() {
    for (pushFlip(); p; ) {
        if (p->p) p->p->pushFlip();
        p->pushFlip(); pushFlip();
        int c1 = up(), c2 = p->up();
        if (c2 == -1) p->rot(c1, 2);
        else p->p->rot(c2, c1 != c2);
    }
}
Node* first() {
    pushFlip();
    return c[0] ? c[0]->first() : (splay(),
this);
}
}
struct LinkCut {
    vector<Node> node;
    LinkCut(int N) : node(N) {}

    void link(int u, int v) { // add an edge (u,
v)
        assert(!connected(u, v));
        makeRoot(&node[u]);
        node[u].pp = &node[v];
    }
    void cut(int u, int v) { // remove an edge (
u, v)
        Node *x = &node[u], *top = &node[v];
        makeRoot(top); x->splay();
        assert(top == (x->pp ? x->c[0]));
        if (x->pp) x->pp = 0;
        else {
            x->c[0] = top->p = 0;
            x->fix();
        }
    }
    bool connected(int u, int v) { // are u, v
in the same tree?
        Node* nu = access(&node[u])->first();
        return nu == access(&node[v])->first();
    }
    void makeRoot(Node* u) {
        access(u);
        u->splay();
        if(u->c[0]) {
            u->c[0]->p = 0;
            u->c[0]->flip ^= 1;
            u->c[0]->pp = u;
            u->c[0] = 0;
            u->fix();
        }
    }
    Node* access(Node* u) {
        u->splay();
        while (Node* pp = u->pp) {
            pp->splay(); u->pp = 0;
            if (pp->c[1]) {
                pp->c[1]->p = 0; pp->c[1]->pp = pp;
            }
            pp->c[1] = u; pp->fix(); u = pp;
        }
        return u;
    }
}
};
```

TreeBinarize.h

Description: Given a weighted tree in edge-listing representation, transforms it into a binary tree by adding at most $2n$ extra nodes.

Usage: call add.edge() for both directions to create the tree. Then call binarize(1). Will change n.

84b697, 31 lines

```
// N = 3 * max nodes, M = 2 * N
int n, o = 2;
int to[M], wgt[M], prv[M], nxt[M], lst[N], deg[N];

void add_edge (int u, int v, int w) {
    to[o] = v, wgt[o] = w, deg[v]++;
    prv[o] = lst[u], lst[u] = nxt[lst[u]] = o++;
}
void binarize (int u, int f = 0) {
    int d = deg[u] - 2 - (f != 0);
    if (d > 0) {
        int tmp_lst = (to[lst[u]] == f ? prv[lst[u]] : lst[u]), x;
        for (int e = lst[u], at = n+d; at > n; ){
            x = prv[e];
            if (to[e] == f) { e = x; continue; }
            nxt[x] = nxt[e];
            nxt[e] ? prv[nxt[e]] = x : lst[u] = x;
            prv[e] = lst[at], nxt[e] = 0;
            lst[at] = nxt[lst[at]] = e, deg[at]++;
            to[e ^ 1] = at;
            if (e != tmp_lst) --at;
            e = x;
        }
        for (int i=1, p=u; i <= d; p = n + i++){
            add_edge(p, n + i, 0);
            add_edge(n + i, p, 0);
            n += d, deg[u] -= d + 1;
        }
        for (int e = lst[u]; e; e = prv[e])
            if (to[e] != f) binarize(to[e], u);
    }
}
```

CentroidDecomp.h

Description: Divide and conquer on trees. Useful for solving problems regarding all pairs of paths. Simple modifications are needed to integrate TreeBinarize into this.

Usage: Just call decompose(1). ctp[u] = parent of u in ctree. cth[u] = height of u in ctree, root has height = 1. dist[u][h] = original tree distance (u -> ctree ancestor of u at height h).

Time: $\mathcal{O}(N \lg N)$
096de1, 24 lines

```
// H = _lg(N), reset: cth, ctp, dist
int sub[N], cth[N], dist[N][H + 1];
void dfs_siz (int u, int f) {
    sub[u] = 1;
    for (int v : g[u]) if (!cth[v] && v ^ f)
        dfs_siz(v, u), sub[u] += sub[v];
}
int fc (int u, int f, int lim) {
    for (int v : g[u]) if (!cth[v] && v ^ f &&
sub[v] > lim) return fc(v, u, lim);
    return u;
}
void dfs_dist (int u, int f, int d, int h) {
    dist[u][h] = d;
    for (int v : g[u]) if (!cth[v] && v ^ f)
        dfs_dist(v, u, d + 1, h);
}
```

```
}
void decompose (int u, int f = 0, int h = 1) {
    dfs_siz(u, 0);
    u = fc(u, 0, sub[u] >> 1);
    dfs_dist(u, 0, 0, h);
    cth[u] = h, ctp[u] = f; // u now deleted
    for (int v : g[u]) if (!cth[v])
        decompose(v, u, h + 1);
}
```

Geometry (8)

8.1 Geometric primitives

Point.h

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)
ef0c0e, 29 lines

```
template <class T> int sgn(T x) { return (x >
0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T _x=0, T _y=0) : x(_x), y(_y){}
    bool operator<(P p) const { return tie(x,y) <
tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==
tie(p.x,p.y); }
    P operator+(P p) const{return P(x+p.x,y+p.y);}
    P operator-(P p) const{return P(x-p.x,y-p.y);}
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).
cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    double dist() const { return sqrt((double)
dist2()); }
    // angle to x-axis in interval [-pi, pi]
    double angle() const { return atan2(y, x); }
    // makes dist() = 1
    P unit() const { return *this/dist(); }
    // rotate by +90 degree
    P perp() const { return P(-y, x); }
    P normal() const { return perp().unit(); }
    //rotate 'a' radians ccw around (0,0)
    P rotate(double a) const { return P(x*cos(a)-y
*sin(a),x*sin(a)+y*cos(a)); }
    friend ostream& operator<<(ostream& os, P p) {
        return os<<"("<< p.x << ", " << p.y << ")";
    };
};
```

lineEquation.h

Description: Gives normalized line equation $ax + by = c$, passing through points p and q.

Time: $\mathcal{O}(1)$
18bb58, 12 lines

```
tuple<ll,ll,ll> get_line_eq (Point p, Point q)
{
    Point normal = (q - p).perp();
    if (normal.x < 0) {
        normal.x *= -1;
        normal.y *= -1;
    } else if (normal.x == 0 && normal.y < 0) {
        normal.y *= -1;
    } // ax + by = c
    ll c = normal.dot(p);
    ll g = gcd(c, gcd(normal.x, normal.y));
}
```



```
    return {normal.x / g, normal.y / g, c / g};
}
```

lineDistance.h

Description:
Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. a==b gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.



"Point.h"9d57f2, 13 lines

```
template<class P>
double lineDist(const P& a, const P& b, const
               P& p) {
    return (double) (b-a).cross(p-a) / (b-a).dist()
            ;
}
```

SegmentDistance.h

Description:
Returns the shortest distance between point p and the line segment from point s to e.



"Point.h"5c88f4, 6 lines

```
Usage: Point<double> a, b(2,2), p(1,1);
bool onSegment = segDist(a,b,p) < 1e-10;

typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t = min(d,max(.0, (p-
        s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
}
```

SegmentIntersection.h

Description:
If a unique intersection point between the line segments going from s1 to e1 and from s2 to e2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long.



```
Usage: vector<P> inter =
segInter(s1,e1,s2,e2);
if (sz(inter)==1)
cout << "segments intersect at " << inter[0]
<< endl;
"Point.h", "OnSegment.h"9d57f2, 13 lines

template<class P> vector<P> segInter(P a, P b,
                                     P c, P d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
        oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-
    endpoint point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(
        od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
    if (onSegment(a, b, c)) s.insert(c);
    if (onSegment(a, b, d)) s.insert(d);
    return {all(s)};
}
```

lineIntersection.h

Description:
If a unique intersection point of the lines going through s1,e1 and s2,e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer co-ordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.



"Point.h"a01f81, 8 lines

```
Usage: auto res = lineInter(s1,e1,s2,e2);
if (res.first == 1)
cout << "intersection point at " <<
res.second << endl;
"Point.h"a01f81, 8 lines

template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2)
{
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {-(s1.cross(e1, s2) == 0), P(0, 0)}
        ;
    auto p = s2.cross(e1, e2), q = s2.cross(e2,
        s1);
    return {1, (s1 * p + e1 * q) / d};
}
```

sideOf.h

Description: Returns where p is as seen from s towards e. 1/0/-1 ⇔ left/on line/right. If the optional argument eps is given 0 is returned if p is within distance eps from the line. P is supposed to be Point<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long.

Usage: bool left = sideOf(p1,p2,q)==1;

"Point.h"3af81c, 9 lines

```
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross
    (e, p)); }
```

```
template<class P>
int sideOf(const P& s, const P& e, const P& p,
           double eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
}
```

OnSegment.h

Description: Returns true iff p lies on the line segment from s to e. Use (segDist(s,e,p)<=epsilon) instead when using Point<double>.

"Point.h"c597e8, 3 lines

```
template<class P> bool onSegment(P s, P e, P p
    ) {
    return p.cross(s, e) == 0 && (s - p).dot(e -
        p) <= 0;
}
```

linearTransformation.h

Description:
Apply the linear transformation (translation, rotation and scaling) which takes line p0-p1 to line q0-q1 to point r.



"Point.h"03a306, 6 lines

```
typedef Point<double> P;
P linearTransformation(const P& p0, const P&
    p1,
    const P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq),
        dp.dot(dq));
    return q0 + P((r-p0).cross(num), (r-p0).dot(
        num))/dp.dist2();
}
```

LineProjectionReflection.h

Description: Projects point p onto line ab. Set refl=true to get reflection of point p across line ab instead. The wrong point will be returned if P is an integer point and the desired point doesn't have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow.

"Point.h"b5562d, 5 lines

```
template<class P>
P lineProj(P a, P b, P p, bool refl=false) {
    P v = b - a;
    return p - v.perp()* (1+refl)*v.cross(p-a)/v.
        dist2();
}
```

Angle.h

Description: A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

Usage: vector<Angle> v = {w[0], w[0].t360() ...}; // sorted

```
int j = 0; rep(i,0,n) { while (v[j] <
v[i].t180()) ++j; }
// sweeps j such that (j-i) represents the
number of positively oriented triangles with
vertices at 0 and i
0f0602, 35 lines
```

```
struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t
        (t) {}
    Angle operator-(Angle b) const { return {x-b
        .x, y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }
    Angle t90() const { return {-y, x, t + (half
        () && x >= 0)}; }
    Angle t180() const { return {-x, -y, t +
        half()}; }
    Angle t360() const { return {x, y, t + 1}; }
};
bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also
    compare distances
    return make_tuple(a.t, a.half(), a.y * (1l)b
        .x) <
        make_tuple(b.t, b.half(), a.x * (1l)b
        .y);
}
```

// Given two points, this calculates the smallest angle between them, i.e., the angle that covers the defined line segment.

```
pair<Angle, Angle> segmentAngles(Angle a,
    Angle b) {
    if (b < a) swap(a, b);
    return (b < a.t180() ?
        make_pair(a, b) : make_pair(b, a.
            t360()));
}
Angle operator+(Angle a, Angle b) { // point a
    + vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b
    - angle a
    int tu = b.t - a.t; a.t = b.t;
    return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x
        , tu - (b < a)};
}
```

8.2 Circles

CircleIntersection.h
Description: Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

"Point.h"84d6d3, 11 lines

```
typedef Point<double> P;
bool circleInter(P a,P b,double r1,double r2,
    pair<P, P>* out) {
    if (a == b) { assert(r1 != r2); return false
        ; }
    P vec = b - a;
```

```
double d2 = vec.dist2(), sum = r1+r2, dif =
    r1-r2,
    p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 =
        r1*r1 - p*p*d2;
if (sum*sum < d2 || dif*dif > d2) return
    false;
P mid = a + vec*p, per = vec.perp() * sqrt(
    fmax(0, h2) / d2);
*out = {mid + per, mid - per};
return true;
}
```

CircleTangents.h
Description: Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

"Point.h"b0153d, 13 lines

```
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P
    c2, double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2
        - dr * dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign
            ) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```

CircleLine.h
Description: Finds the intersection between a circle and a line. Returns a vector of either 0, 1, or 2 intersection points. P is intended to be Point<double>.

"Point.h"e0cfba, 9 lines

```
template<class P>
vector<P> circleLine(P c, double r, P a, P b)
{
    P ab = b - a, p = a + ab * (c-a).dot(ab) /
        ab.dist2();
    double s = a.cross(b, c), h2 = r*r - s*s /
        ab.dist2();
    if (h2 < 0) return {};
    if (h2 == 0) return {p};
    P h = ab.unit() * sqrt(h2);
    return {p - h, p + h};
}
```

CirclePolygonIntersection.h

Description: Returns the area of the intersection of a circle with a ccw polygon.
Time: $\mathcal{O}(n)$


"../content/geometry/Point.h"alee63, 19 lines

```
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps)
{

```

```
auto tri = [&](P p, P q) {
    auto r2 = r * r / 2;
    P d = q - p;
    auto a = d.dot(p)/d.dist2(), b = (p.dist2
        ()-r*r)/d.dist2();
    auto det = a * a - b;
    if (det <= 0) return arg(p, q) * r2;
    auto s = max(0., -a-sqrt(det)), t = min
        (1., -a+sqrt(det));
    if (t < 0 || 1 <= s) return arg(p, q) * r2
        ;
    P u = p + d * s, v = p + d * t;
    return arg(p,u) * r2 + u.cross(v)/2 + arg(
        v,q) * r2;
};
auto sum = 0.0;
rep(i,0,sz(ps))
    sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)]
        - c);
return sum;
}
```

circumcircle.h
Description: The circumirle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



"Point.h"1caa3a, 9 lines

```
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const
    P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist
        ()/
        abs((B-A).cross(C-A))/2;
}
P ccCenter(const P& A, const P& B, const P& C)
{
    P b = C-A, c = B-A;
    return A + (b*c.dist2()-c*b.dist2()).perp()/
        b.cross(c)/2;
}
```

MinimumEnclosingCircle.h

Description: Computes the minimum circle that encloses a set of points.
Time: expected $\mathcal{O}(n)$

"circumcircle.h"09dd0a, 17 lines

```
pair<P, double> mec(vector<P> ps) {
    shuffle(all(ps), mt19937(time(0)));
    P o = ps[0];
    double r = 0, EPS = 1 + 1e-8;
    rep(i,0,sz(ps)) if ((o - ps[i]).dist() > r *
        EPS) {
        o = ps[i], r = 0;
        rep(j,0,i) if ((o - ps[j]).dist() > r *
            EPS) {
            o = (ps[i] + ps[j]) / 2;
            r = (o - ps[i]).dist();
            rep(k,0,j) if ((o - ps[k]).dist() > r *
                EPS) {
                o = ccCenter(ps[i], ps[j], ps[k]);

```

```
        r = (o - ps[i]).dist();
    }
    }
    return {o, r};
}
```

8.3 Polygons
InsidePolygon.h
Description: Returns true if p lies within the polygon. If strict is true, it returns false for points on the boundary. The algorithm uses products in intermediate steps so watch out for overflow.

```
Usage: vector<P> v = {P{4,4}, P{1,2}, P{2,1}};
bool in = inPolygon(v, P{3, 3}, false);
Time:  $\mathcal{O}(n)$ 
```

"Point.h", "OnSegment.h", "SegmentDistance.h"2bf504, 11 lines

```
template<class P>
bool inPolygon(vector<P> &p, P a, bool strict
    = true) {
    int cnt = 0, n = sz(p);
    rep(i,0,n) {
        P q = p[(i + 1) % n];
        if (onSegment(p[i], q, a)) return !strict;
        //or: if (segDist(p[i], q, a) <= eps)
            return !strict;
        cnt ^= ((a.y<p[i].y) - (a.y<q.y)) * a.
            cross(p[i], q) > 0;
    }
    return cnt;
}
```

PolygonArea.h
Description: Returns twice the signed area of a polygon. Clockwise enumeration gives negative area. Watch out for overflow if using int as T!

"Point.h"f12300, 6 lines

```
template<class T>
T polygonArea2(vector<Point<T>>& v) {
    T a = v.back().cross(v[0]);
    rep(i,0,sz(v)-1) a += v[i].cross(v[i+1]);
    return a;
}
```


PolygonCenter.h
Description: Returns the center of mass for a polygon.
Time: $\mathcal{O}(n)$

"Point.h"9706dc, 9 lines

```
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = sz(v) - 1; i < sz(v); j
        = i++) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i
            ]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}
```

PolygonCut.h

Description: Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.



Usage: vector<P> p = ...;
p = polygonCut(p, P(0,0), P(1,0));

"Point.h", "lineIntersection.h"f2b7d4, 13 lines

```
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P
    s, P e) {
    vector<P> res;
    rep(i,0,sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] :
            poly.back();
        bool side = s.cross(e, cur) < 0;
        if (side != (s.cross(e, prev) < 0))
            res.push_back(lineInter(s, e, cur, prev)
                .second);
        if (side)
            res.push_back(cur);
    }
    return res;
}
```

PolygonUnion.h
Description: Calculates the area of the union of n polygons (not necessarily convex). The points within each polygon must be given in CCW order. (Epsilon checks may optionally be added to sideOf/sgn, but shouldn't be needed.)
Time: $\mathcal{O}(N^2)$, where N is the total number of points

"Point.h", "sideOf.h"3931c6, 33 lines

```
typedef Point<double> P;
double rat(P a, P b) { return sgn(b.x) ? a.x/b
    .x : a.y/b.y; }
double polyUnion(vector<vector<P>>& poly) {
    double ret = 0;
    rep(i,0,sz(poly)) rep(v,0,sz(poly[i])) {
        P A = poly[i][v], B = poly[i][(v + 1) % sz
            (poly[i])];
        vector<pair<double, int>> segs = {{0, 0},
            {1, 0}};
        rep(j,0,sz(poly)) if (i != j) {
            rep(u,0,sz(poly[j])) {
                P C = poly[j][u], D = poly[j][(u + 1)
                    % sz(poly[j])];
                int sc = sideOf(A, B, C), sd = sideOf(
                    A, B, D);
                if (sc != sd) {
                    double sa = C.cross(D, A), sb = C.
                        cross(D, B);
                    if (min(sc, sd) < 0)
                        segs.emplace_back(sa / (sa - sb),
                            sgn(sc - sd));
                } else if (!sc && !sd && j<i && sgn((B
                    -A).dot(D-C))>0){
                    segs.emplace_back(rat(C - A, B - A),
                        1);
                    segs.emplace_back(rat(D - A, B - A),
                        -1);
                }
            }
        }
    }
```

```
sort(all(segs));
for (auto& s : segs) s.first = min(max(s.first, 0.0), 1.0);
double sum = 0;
int cnt = segs[0].second;
rep(j,1,sz(segs)) {
    if (!cnt) sum += segs[j].first - segs[j-1].first;
    cnt += segs[j].second;
}
ret += A.cross(B) * sum;
}
return ret / 2;
```

ConvexHull.h
Description: Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.



```
Time:  $\mathcal{O}(n \log n)$ 
"Point.h" 310954, 13 lines
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
    if (sz(pts) <= 1) return pts;
    sort(all(pts));
    vector<P> h(sz(pts)+1);
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(all(pts)))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0) t--;
            h[t++] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}
```

HullDiameter.h
Description: Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).
Time: $\mathcal{O}(n)$

```
"Point.h" c571b8, 12 lines
typedef Point<ll> P;
array<P, 2> hullDiameter(vector<P> S) {
    int n = sz(S), j = n < 2 ? 0 : 1;
    pair<ll, array<P, 2>> res({0, {S[0], S[0]}})
        ;
    rep(i,0,j)
        for (; j = (j + 1) % n) {
            res = max(res, {(S[i] - S[j]).dist2(), {S[i], S[j]}});
            if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] - S[i]) >= 0)
                break;
        }
    return res.second;
}
```

PointInsideHull.h
Description: Determine whether a point t lies inside a convex hull (CCW order, with no collinear points). Returns true if point lies within the hull. If strict is true, points on the boundary aren't included.
Time: $\mathcal{O}(\log N)$

```
"Point.h", "sideOf.h", "OnSegment.h" 71446b, 14 lines
typedef Point<ll> P;

bool inHull(const vector<P>& l, P p, bool strict = true) {
    int a = 1, b = sz(l) - 1, r = !strict;
    if (sz(l) < 3) return r && onSegment(l[0], l.back(), p);
    if (sideOf(l[0], l[a], l[b]) > 0) swap(a, b);
    ;
    if (sideOf(l[0], l[a], p) >= r || sideOf(l[0], l[b], p) <= -r)
        return false;
    while (abs(a - b) > 1) {
        int c = (a + b) / 2;
        (sideOf(l[0], l[c], p) > 0 ? b : a) = c;
    }
    return sgn(l[a].cross(l[b], p)) < r;
}
```

LineHullIntersection.h
Description: Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon: $\bullet (-1, -1)$ if no collision, $\bullet (i, -1)$ if touching the corner i , $\bullet (i, i)$ if along side $(i, i + 1)$, $\bullet (i, j)$ if crossing sides $(i, i + 1)$ and $(j, j + 1)$. In the last case, if a corner i is crossed, this is treated as happening on side $(i, i + 1)$. The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.
Time: $\mathcal{O}(\log n)$

```
"Point.h" 7cf45b, 39 lines
#define cmp(i,j) sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 + n) < 0
template <class P> int extrVertex(vector<P>& poly, P dir) {
    int n = sz(poly), lo = 0, hi = n;
    if (extr(0)) return 0;
    while (lo + 1 < hi) {
        int m = (lo + hi) / 2;
        if (extr(m)) return m;
        int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi : lo) = m;
    }
    return lo;
}

#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
```

```
rep(i,0,2) {
    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
        int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
        (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
}
if (res[0] == res[1]) return {res[0], -1};
if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) % sz(poly)) {
        case 0: return {res[0], res[0]};
        case 2: return {res[1], res[1]};
    }
return res;
}
```

minkowskiSum.h
Description: Minkowski sum of two sets $A + B = \{a + b | a \in A, b \in B\}$. P and Q must be ccw oriented polygons. Cool application: Minimum distance between two polygons P and Q in $\mathcal{O}(|P| + |Q|)$. Negate Q and take the sum $P + (-Q)$. Then find shortest distance from $(0, 0)$ to the polygon. If origin is already inside answer is 0, otherwise it is distance between the origin and some edge/vertex.

```
307816, 21 lines
typedef Point<ll> P;
void reorder_polygon(vector<P> &p) {
    int pos = 0;
    for (int i = 1; i < sz(p); i++) {
        if (p[i].y < p[pos].y || (p[i].y == p[pos].y && p[i].x < p[pos].x))
            pos = i;
    } rotate(p.begin(), p.begin() + pos, p.end());
}
vector<P> minkowski(vector<P> p, vector<P> q) {
    reorder_polygon(p); reorder_polygon(q);
    p.push_back(p[0]); p.push_back(p[1]);
    q.push_back(q[0]); q.push_back(q[1]);

    vector<P> result; int i = 0, j = 0;
    while (i < sz(p) - 2 || j < sz(q) - 2) {
        result.push_back(p[i] + q[j]);
        auto c = (p[i + 1] - p[i]).cross(q[j + 1] - q[j]);
        if (c >= 0 && i < sz(q) - 2) ++i;
        if (c <= 0 && j < sz(p) - 2) ++j;
    } return result;
}
```

8.4 Misc. Point Set Problems

ClosestPair.h
Description: Finds the closest pair of points.
Time: $\mathcal{O}(n \log n)$

```
"Point.h" ac41a6, 17 lines
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(all(v), [](P a, P b) { return a.y < b.y; });
    pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
```

```
int j = 0;
for (P p : v) {
    P d(1 + (1ll)sqrt(ret.first), 0);
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p + d);
    for (; lo != hi; ++lo)
        ret = min(ret, {(lo - p).dist2(), {lo, p}});
    S.insert(p);
}
return ret.second;
}
```

kdTree.h
Description: KD-tree (2d, can be extended to 3d)

```
"Point.h" bac5b0, 63 lines
typedef long long T;
typedef Point<T> P;
const T INF = numeric_limits<T>::max();

bool on_x(const P& a, const P& b) { return a.x < b.x; }
bool on_y(const P& a, const P& b) { return a.y < b.y; }

struct Node {
    P pt; // if this is a leaf, the single point in it
    T x0 = INF, x1 = -INF, y0 = INF, y1 = -INF; // bounds
    Node *first = 0, *second = 0;

    T distance(const P& p) { // min squared distance to a point
        T x = (p.x < x0 ? x0 : p.x > x1 ? x1 : p.x);
        T y = (p.y < y0 ? y0 : p.y > y1 ? y1 : p.y);
        return (P(x,y) - p).dist2();
    }

    Node(vector<P>&& vp) : pt(vp[0]) {
        for (P p : vp) {
            x0 = min(x0, p.x); x1 = max(x1, p.x);
            y0 = min(y0, p.y); y1 = max(y1, p.y);
        }
        if (vp.size() > 1) {
            // split on x if width >= height (not ideal...)
            sort(all(vp), x1 - x0 >= y1 - y0 ? on_x : on_y);
            // divide by taking half the array for each child (not best performance with many duplicates in the middle)
            int half = sz(vp)/2;
            first = new Node({vp.begin(), vp.begin() + half});
            second = new Node({vp.begin() + half, vp.end()});
        }
    }
};

struct KDTree {
    Node* root;
```

```
KDTree(const vector<P>& vp) : root(new Node(
    {all(vp)})) {}

pair<T, P> search(Node *node, const P& p) {
    if (!node->first) {
        // uncomment if we should not find the
        // point itself:
        // if (p == node->pt) return {INF, P()};
        return make_pair((p - node->pt).dist2(),
            node->pt);
    }

    Node *f = node->first, *s = node->second;
    T bfirst = f->distance(p), bsec = s->
        distance(p);
    if (bfirst > bsec) swap(bsec, bfirst),
        swap(f, s);

    // search closest side first, other side
    // if needed
    auto best = search(f, p);
    if (bsec < best.first)
        best = min(best, search(s, p));
    return best;
}

// find nearest point to a point, and its
// squared distance
// (requires an arbitrary operator< for
// Point)
pair<T, P> nearest(const P& p) {
    return search(root, p);
}
};
```

FastDelaunay.h

Description: Fast Delaunay triangulation. Each circumcircle contains none of the input points. There must be no duplicate points. If all points are on a line, no triangles will be returned. Should work for doubles as well, though there may be precision issues in 'circ'. Returns triangles in order {t[0][0], t[0][1], t[0][2], t[1][0], ...}, all counter-clockwise.

Time: $O(n \log n)$

```
"Point.h" eefdf5, 88 lines
typedef Point<ll> P;
typedef struct Quad<P>
typedef __int128_t ll1; // (can be ll if
    coords are < 2e4)
P arb(LLONG_MAX, LLONG_MAX); // not equal to
    any other point
```

```
struct Quad {
    Q rot, o; P p = arb; bool mark;
    P& F() { return r()->p; }
    Q& r() { return rot->rot; }
    Q prev() { return rot->o->rot; }
    Q next() { return r()->prev(); }
} *H;

bool circ(P p, P a, P b, P c) { // is p in the
    circumcircle?
    ll1 p2 = p.dist2(), A = a.dist2()-p2,
        B = b.dist2()-p2, C = c.dist2()-p2;
    return p.cross(a,b)*C + p.cross(b,c)*A + p.
        cross(c,a)*B > 0;
}

Q makeEdge(P orig, P dest) {
```

```
Q r = H ? H : new Quad{new Quad{new Quad{new
    Quad{0}}}};
H = r->o; r->r()->r() = r;
rep(i,0,4) r = r->rot, r->p = arb, r->o = i
    & 1 ? r : r->r();
r->p = orig; r->F() = dest;
return r;
}

void splice(Q a, Q b) {
    swap(a->o->rot->o, b->o->rot->o); swap(a->o,
        b->o);
}

Q connect(Q a, Q b) {
    Q q = makeEdge(a->F(), b->p);
    splice(q, a->next());
    splice(q->r(), b);
    return q;
}

pair<Q,Q> rec(const vector<P>& s) {
    if (sz(s) <= 3) {
        Q a = makeEdge(s[0], s[1]), b = makeEdge(s
            [1], s.back());
        if (sz(s) == 2) return { a, a->r() };
        splice(a->r(), b);
        auto side = s[0].cross(s[1], s[2]);
        Q c = side ? connect(b, a) : 0;
        return {side < 0 ? c->r() : a, side < 0 ?
            c : b->r() };
    }

#define H(e) e->F(), e->p
#define valid(e) (e->F().cross(H(base)) > 0)
    Q A, B, ra, rb;
    int half = sz(s) / 2;
    tie(ra, A) = rec({all(s) - half});
    tie(B, rb) = rec({sz(s) - half + all(s)});
    while ((B->p.cross(H(A)) < 0 && (A = A->next
        ())) ||
        (A->p.cross(H(B)) > 0 && (B = B->r()
            ->o)))
        Q base = connect(B->r(), A);
        if (A->p == ra->p) ra = base->r();
        if (B->p == rb->p) rb = base;

#define DEL(e, init, dir) Q e = init->dir; if
    (valid(e)) \
        while (circ(e->dir->F(), H(base), e->F()))
            { \
                Q t = e->dir; \
                splice(e, e->prev()); \
                splice(e->r(), e->r()->prev()); \
                e->o = H; H = e; e = t; \
            }
        for (;;) {
            DEL(LC, base->r(), o); DEL(RC, base, prev
                ());
            if (!valid(LC) && !valid(RC)) break;
            if (!valid(LC) || (valid(RC) && circ(H(RC)
                , H(LC))))
                base = connect(RC, base->r());
            else
                base = connect(base->r(), LC->r());
        }
        return { ra, rb };
    }

vector<P> triangulate(vector<P> pts) {
```

```
sort(all(pts)); assert(unique(all(pts)) ==
    pts.end());
if (sz(pts) < 2) return {};
Q e = rec(pts).first;
vector<Q> q = {e};
int qi = 0;
while (e->o->F().cross(e->F(), e->p) < 0) e
    = e->o;
#define ADD { Q c = e; do { c->mark = 1; pts.
    push_back(c->p); \
    q.push_back(c->r()); c = c->next(); } while
    (c != e); }
ADD; pts.clear();
while (qi < sz(q)) if (!(e = q[qi++])->mark)
    ADD;
return pts;
}
```

Voronoi.h

Description: Not so fast Voronoi from FastDelaunay Assumes that there are no duplicate points and that not all points are on a single line. Each circumcircle contains none of the input points. Should work for doubles as well, but haven't checked This can be optimized to use much less memory if needed. Also manually fix BIG.

Time: $O(n \log n)$

```
"FastDelaunay.h" ale388, 66 lines
struct voronoi_graph {
    using P = Point<ll>;
    using Pd = Point<double>;

    const double BIG = 1e8;

    static Pd promote (P p) { return Pd(p.x, p.y)
        ; }

    vector<tuple<P,P,P>> nodes;
    vector<vector<tuple<pair<P,P>, int, Pd>>> adj
        ;
    // ((A, B), v, Direction)
    // the edge, when extended to a line, is the
    // perpendicular bisector of the segment
    // AB
    // v is the index of the adjacent node. it
    // is -1 if the edge goes to infity
    // circumcenter(node) + Direction gives us
    // the other vertex
```

```
voronoi_graph(const vector<P>& pts) {
    auto t = delaunay::triangulate(pts);
    assert (sz(t) % 3 == 0);
    nodes.resize(sz(t) / 3);
    for (int i = 0; i < sz(t); i += 3)
        nodes[i / 3] = {t[i], t[i+1], t[i+2]};
    sort(all(nodes));
    adj.resize(sz(nodes));

    vector<pair<pair<P,P>, tuple<P,P,P>>>
        delaunay_edges;
    delaunay_edges.reserve(sz(t));
    for (int i = 0; i < sz(t); i += 3) {
        for (int j = i; j < i + 3; j++)
            for (int k = j + 1; k < i + 3; k++)
                delaunay_edges.emplace_back(pair(min(t[j]
                    ], t[k]), max(t[j], t[k])), tuple(t[i]
                    ], t[i+1], t[i+2]));
    }
    sort(all(delaunay_edges));
```

```
for (int i = 0; i < sz(delaunay_edges); i++)
    {
        const int x = lower_bound(all(nodes),
            delaunay_edges[i].second) - nodes.begin
            ();
        auto [a,b,c] = delaunay_edges[i].second;
        if (c == delaunay_edges[i].first.first || c
            == delaunay_edges[i].first.second)
            swap(b, c);
        if (c == delaunay_edges[i].first.first || c
            == delaunay_edges[i].first.second)
            swap(a, c);
        if (c == delaunay_edges[i].first.first || c
            == delaunay_edges[i].first.second)
            assert (false);

        if (i+1 < sz(delaunay_edges) &&
            delaunay_edges[i+1].first ==
            delaunay_edges[i].first) {
            const int y = lower_bound(all(nodes),
                delaunay_edges[i+1].second) - nodes.
                begin();
            auto dir = get_vertex(y) - get_vertex(x);
            adj[x].emplace_back(delaunay_edges[i].
                first, y, dir);
            adj[y].emplace_back(delaunay_edges[i].
                first, x, dir * (-1.0));
        } else if (i == 0 || delaunay_edges[i-1].
            first != delaunay_edges[i].first) {
            bool out = (a - c).dot(b - c) < 0;
            auto dir = ((promote(a + b) / 2.0) -
                get_vertex(x)) * (out ? -1.0 : 1.0);
            adj[x].emplace_back(delaunay_edges[i].
                first, -1, dir * BIG);
        }
    }
}

Pd get_vertex (int i) {
    auto [a, b, c] = nodes[i];
    return ccCenter(promote(a), promote(b),
        promote(c));
}

pair<Pd,Pd> get_edge (int i, int j) {
    const Pd vi = get_vertex(i);
    return {vi, vi + get<2>(adj[i][j])};
}
};
```

hplane-cpalg.h

Description: Half plane intersection in $O(n \log n)$. The direction of the plane is ccw of pq vector in Halfplane struct. Usage: Status:

```
2e310c, 75 lines
const long double eps = 1e-9, inf = 1e9;

struct Point {
    long double x, y;
    explicit Point(long double x = 0, long
        double y = 0) : x(x), y(y) {}
    friend Point operator+(const Point &p,
        const Point &q) { return Point(p.x + q
            .x, p.y + q.y); }
    friend Point operator-(const Point &p,
        const Point &q) { return Point(p.x - q
            .x, p.y - q.y); }
```

```
friend Point operator*(const Point &p,
const long double &k) { return Point(p
.x * k, p.y * k); }
friend long double dot(const Point &p,
const Point &q) { return p.x * q.x + p
.y * q.y; }
friend long double cross(const Point &p,
const Point &q) { return p.x * q.y - p
.y * q.x; }
};

struct Halfplane {
Point p, pq;
long double angle;
Halfplane() {}
Halfplane(const Point &a, const Point &b)
: p(a), pq(b - a) {
angle = atan2(pq.y, pq.x);
}
bool out(const Point &r) { return cross(pq
, r - p) < -eps; }
bool operator<(const Halfplane &e) const {
return angle < e.angle; }
friend Point inter(const Halfplane &s,
const Halfplane &t) {
long double alpha = cross((t.p - s.p),
t.pq) / cross(s.pq, t.pq);
return s.p + (s.pq * alpha);
}
};

vector<Point> hp_intersect(vector<Halfplane> &
H) {

Point box[4] = {Point(Inf, Inf), Point(-
Inf, Inf), Point(-Inf, -Inf),
Point(Inf, -Inf)};

for (int i = 0; i < 4; i++) {
Halfplane aux(box[i], box[(i + 1) %
4]);
H.push_back(aux);
}

sort(H.begin(), H.end());
deque<Halfplane> dq;
int len = 0;
for (int i = 0; i < int(H.size()); i++) {
while (len > 1 && H[i].out(inter(dq[
len - 1], dq[len - 2]))) {
dq.pop_back(); --len;
}
while (len > 1 && H[i].out(inter(dq
[0], dq[1]))) {
dq.pop_front(); --len;
}
if (len > 0 && fabs1(cross(H[i].pq, dq
[len - 1].pq)) < eps) {
if (dot(H[i].pq, dq[len - 1].pq) <
0.0)
return vector<Point>();
if (H[i].out(dq[len - 1].p)) {
dq.pop_back();
--len;
} else
continue;
}
dq.push_back(H[i]);
++len;
}
```

```

}
while (len > 2 && dq[0].out(inter(dq[len -
1], dq[len - 2]))) {
dq.pop_back(); --len;
}

while (len > 2 && dq[len - 1].out(inter(dq
[0], dq[1]))) {
dq.pop_front(); --len;
}
if (len < 3)
return vector<Point>();
vector<Point> ret(len);
for (int i = 0; i + 1 < len; i++) {
ret[i] = inter(dq[i], dq[i + 1]);
}
ret.back() = inter(dq[len - 1], dq[0]);
return ret;
}


```

8.5 3D

PolyhedronVolume.h

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

3058c3, 6 lines

```
template<class V, class L>
double signedPolyVolume(const V& p, const L&
trilist) {
double v = 0;
for (auto i : trilist) v += p[i.a].cross(p[i
.b]).dot(p[i.c]);
return v / 6;
}
```

Point3D.h

Description: Class to handle points in 3D space. T can be e.g. double or long long.

8058ae, 32 lines

```
template<class T> struct Point3D {
typedef Point3D P;
typedef const P& R;
T x, y, z;
explicit Point3D(T x=0, T y=0, T z=0) : x(x)
, y(y), z(z) {}
bool operator<(R p) const {
return tie(x, y, z) < tie(p.x, p.y, p.z);
}
bool operator==(R p) const {
return tie(x, y, z) == tie(p.x, p.y, p.z);
}
P operator+(R p) const { return P(x+p.x, y+p
.y, z+p.z); }
P operator-(R p) const { return P(x-p.x, y-p
.y, z-p.z); }
P operator*(T d) const { return P(x*d, y*d,
z*d); }
P operator/(T d) const { return P(x/d, y/d,
z/d); }
T dot(R p) const { return x*p.x + y*p.y + z*
p.z; }
P cross(R p) const {
return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p
.y - y*p.x);
}
T dist2() const { return x*x + y*y + z*z; }
double dist() const { return sqrt((double)
dist2()); }
//Azimuthal angle (longitude) to x-axis in
interval [-pi, pi]
```

```
double phi() const { return atan2(y, x); }
//Zenith angle (latitude) to the z-axis in
interval [0, pi]
double theta() const { return atan2(sqrt(x*x
+y*y),z); }
P unit() const { return *this/(T)dist(); }
//makes dist()=1
//returns unit vector normal to *this and p
P normal(P p) const { return cross(p).unit()
; }
//returns point rotated 'angle' radians ccw
around axis
P rotate(double angle, P axis) const {
double s = sin(angle), c = cos(angle); P u
= axis.unit();
return u*dot(u)*(1-c) + (*this)*c - cross(
u)*s;
}
};


```

3dHull.h

Description: Computes all faces of the 3-dimension hull of a point set. *No four points must be coplanar*, or else random results will be returned. All faces will point outwards.

Time: $\mathcal{O}(n^2)$

"Point3D.h" 5b45fc, 49 lines

typedef Point3D<double> P3;

```
struct PR {
void ins(int x) { (a == -1 ? a : b) = x; }
void rem(int x) { (a == x ? a : b) = -1; }
int cnt() { return (a != -1) + (b != -1); }
int a, b;
};


```

struct F { P3 q; int a, b, c; };

```
vector<F> hull3d(const vector<P3>& A) {
assert(sz(A) >= 4);
vector<vector<PR>> E(sz(A), vector<PR>(sz(A)
, {-1, -1}));
#define E(x,y) E[f.x][f.y]
vector<F> FS;
auto mf = [&](int i, int j, int k, int l) {
P3 q = (A[j] - A[i]).cross((A[k] - A[i]));
if (q.dot(A[l]) > q.dot(A[i]))
q = q * -1;
F f(q, i, j, k);
E(a,b).ins(k); E(a,c).ins(j); E(b,c).ins(i
);
FS.push_back(f);
};
rep(i,0,4) rep(j,i+1,4) rep(k,j+1,4)
mf(i, j, k, 6 - i - j - k);

rep(i,4,sz(A)) {
rep(j,0,sz(FS)) {
F f = FS[j];
if(f.q.dot(A[i]) > f.q.dot(A[f.a])) {
E(a,b).rem(f.c);
E(a,c).rem(f.b);
E(b,c).rem(f.a);
swap(FS[j--], FS.back());
FS.pop_back();
}
}
int nw = sz(FS);
rep(j,0,nw) {
```

```
F f = FS[j];
#define C(a, b, c) if (E(a,b).cnt() != 2) mf(f
.a, f.b, i, f.c);
C(a, b, c); C(a, c, b); C(b, c, a);
}
}
for (F& it : FS) if ((A[it.b] - A[it.a]).
cross(
A[it.c] - A[it.a]).dot(it.q) <= 0) swap(it
.c, it.b);
return FS;
};


```

sphericalDistance.h

Description: Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f1 (ϕ_1) and f2 (ϕ_2) from x axis and zenith angles (latitude) t1 (θ_1) and t2 (θ_2) from z axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. dx*radius is then the difference between the two points in the x direction and d*radius is the total distance between the points.

P61107, 8 lines

```
double sphericalDistance(double f1, double t1,
double f2, double t2, double radius) {
double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1
);
double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1
);
double dz = cos(t2) - cos(t1);
double d = sqrt(dx*dx + dy*dy + dz*dz);
return radius*2*asin(d/2);
}


```

warsawGeo3D.h

Description: 3D geometry

c53353, 336 lines

```
using LD = long double;
const LD kEps = 1e-9;
const LD kPi = acosl(-1);
LD Sq(LD x) { return x * x; }
struct Point {
LD x, y;
Point() {}
Point(LD a, LD b) : x(a), y(b) {}
Point(const Point& a) : Point(a.x, a.y) {}
void operator=(const Point &a) { x = a.x; y
= a.y; }
Point operator+(const Point &a) const {
Point p(x + a.x, y + a.y); return p; }
Point operator-(const Point &a) const {
Point p(x - a.x, y - a.y); return p; }
Point operator*(LD a) const { Point p(x * a,
y * a); return p; }
Point operator/(LD a) const { assert(abs(a)
> kEps); Point p(x / a, y / a); return p
; }
Point &operator+=(const Point &a) { x += a.x
; y += a.y; return *this; }
Point &operator-=(const Point &a) { x -= a.x
; y -= a.y; return *this; }
LD CrossProd(const Point &a) const { return
x * a.y - y * a.x; }
LD CrossProd(Point a, Point b) const { a -=
*this; b -= *this; return a.CrossProd(b)
; }
};


```

```

struct Line {
    Point p[2];
    Line(Point a, Point b) { p[0] = a; p[1] = b; }
    Point &operator[](int a) { return p[a]; }
};

struct P3 {
    LD x, y, z;
    P3 operator+(P3 a) { P3 p{x + a.x, y + a.y, z + a.z}; return p; }
    P3 operator-(P3 a) { P3 p{x - a.x, y - a.y, z - a.z}; return p; }
    P3 operator*(LD a) { P3 p{x * a, y * a, z * a}; return p; }
    P3 operator/(LD a) { assert(a > kEps); P3 p{x / a, y / a, z / a}; return p; }
    P3 &operator+=(P3 a) { x += a.x; y += a.y; z += a.z; return *this; }
    P3 &operator-=(P3 a) { x -= a.x; y -= a.y; z -= a.z; return *this; }
    P3 &operator*=(LD a) { x *= a; y *= a; z *= a; return *this; }
    P3 &operator/=(LD a) { assert(a > kEps); x /= a; y /= a; z /= a; return *this; }
    LD &operator[](int a) {
        if (a == 0) return x;
        if (a == 1) return y;
        return z;
    }
    bool IsZero() { return abs(x) < kEps && abs(y) < kEps && abs(z) < kEps; }
    LD DotProd(P3 a) { return x * a.x + y * a.y + z * a.z; }
    LD Norm() { return sqrt(x * x + y * y + z * z); }
    LD SqNorm() { return x * x + y * y + z * z; }
    void NormalizeSelf() { *this /= Norm(); }
    P3 Normalize() {
        P3 res(*this); res.NormalizeSelf();
        return res;
    }
    LD Dis(P3 a) { return (*this - a).Norm(); }
    pair<LD, LD> SphericalAngles() {
        return {atan2(z, sqrt(x * x + y * y)), atan2(y, x)};
    }
    LD Area(P3 p) { return Norm() * p.Norm() * sin(Angle(p)) / 2; }
    LD Angle(P3 p) {
        LD a = Norm();
        LD b = p.Norm();
        LD c = Dis(p);
        return acos((a * a + b * b - c * c) / (2 * a * b));
    }
    LD Angle(P3 p, P3 q) { return p.Angle(q); }
    P3 CrossProd(P3 p) {
        P3 q(*this);
        return {q[1] * p[2] - q[2] * p[1], q[2] * p[0] - q[0] * p[2], q[0] * p[1] - q[1] * p[0]};
    }
    bool LexCmp(P3 &a, const P3 &b) {
        if (abs(a.x - b.x) > kEps) return a.x < b.x;
        if (abs(a.y - b.y) > kEps) return a.y < b.y;
        return a.z < b.z;
    }
};

```

```

}
};

struct Line3 {
    P3 p[2];
    P3 &operator[](int a) { return p[a]; }
    friend ostream &operator<<(ostream &out, Line3 m);
};

struct Plane {
    P3 p[3];
    P3 &operator[](int a) { return p[a]; }
    P3 GetNormal() {
        P3 cross = (p[1] - p[0]).CrossProd(p[2] - p[0]);
        return cross.Normalize();
    }
    void GetPlaneEq(LD &A, LD &B, LD &C, LD &D) {
        P3 normal = GetNormal();
        A = normal[0];
        B = normal[1];
        C = normal[2];
        D = normal.DotProd(p[0]);
        assert(abs(D - normal.DotProd(p[1])) < kEps);
        assert(abs(D - normal.DotProd(p[2])) < kEps);
    }
    vector<P3> GetOrthonormalBase() {
        P3 normal = GetNormal();
        P3 cand = {-normal.y, normal.x, 0};
        if (abs(cand.x) < kEps && abs(cand.y) < kEps) {
            cand = {0, -normal.z, normal.y};
        }
        cand.NormalizeSelf();
        P3 third = Plane{P3{0, 0, 0}, normal, cand}.GetNormal();
        assert(abs(normal.DotProd(cand)) < kEps && abs(normal.DotProd(third)) < kEps && abs(cand.DotProd(third)) < kEps);
        return {normal, cand, third};
    }
};

struct Circle3 {
    Plane pl; P3 o; LD r;
};

struct Sphere {
    P3 o; LD r;
};

// angle PQR
LD Angle(P3 P, P3 Q, P3 R) { return (P - Q).Angle(R - Q); }

P3 ProjPtToLine3(P3 p, Line3 l) { // ok
    P3 diff = l[1] - l[0];
    diff.NormalizeSelf();
    return l[0] + diff * (p - l[0]).DotProd(diff);
}

LD DisPtLine3(P3 p, Line3 l) { // ok
    // LD area = Area(p, l[0], l[1]); LD dis1 = 2 * area / l[0].Dis(l[1]);
    LD dis2 = p.Dis(ProjPtToLine3(p, l)); // assert(abs(dis1 - dis2) < kEps);
    return dis2;
}

LD DisPtPlane(P3 p, Plane pl) {

```

```

    P3 normal = pl.GetNormal();
    return abs(normal.DotProd(p - pl[0]));
}

P3 ProjPtToPlane(P3 p, Plane pl) {
    P3 normal = pl.GetNormal();
    return p - normal * normal.DotProd(p - pl[0]);
}

bool PtBelongToLine3(P3 p, Line3 l) { return DisPtLine3(p, l) < kEps; }

bool Lines3Equal(Line3 p, Line3 l) {
    return PtBelongToLine3(p[0], l) && PtBelongToLine3(p[1], l);
}

bool PtBelongToPlane(P3 p, Plane pl) { return DisPtPlane(p, pl) < kEps; }

Point PlanePtTo2D(Plane pl, P3 p) { // ok
    assert(PtBelongToPlane(p, pl));
    vector<P3> base = pl.GetOrthonormalBase();
    P3 control{0, 0, 0};
    REP(tr, 3) { control += base[tr] * p.DotProd(base[tr]); }
    assert(PtBelongToPlane(pl[0] + base[1], pl));
    assert(PtBelongToPlane(pl[0] + base[2], pl));
    assert((p - control).IsZero());
    return {p.DotProd(base[1]), p.DotProd(base[2])};
}

Line PlaneLineTo2D(Plane pl, Line3 l) {
    return {PlanePtTo2D(pl, l[0]), PlanePtTo2D(pl, l[1])};
}

P3 PlanePtTo3D(Plane pl, Point p) { // ok
    vector<P3> base = pl.GetOrthonormalBase();
    return base[0] * base[0].DotProd(pl[0]) + base[1] * p.x + base[2] * p.y;
}

Line3 PlaneLineTo3D(Plane pl, Line l) {
    return {PlanePtTo3D(pl, l[0]), PlanePtTo3D(pl, l[1])};
}

Line3 ProjLineToPlane(Line3 l, Plane pl) { // ok
    return {ProjPtToPlane(l[0], pl), ProjPtToPlane(l[1], pl)};
}

bool Line3BelongToPlane(Line3 l, Plane pl) {
    return PtBelongToPlane(l[0], pl) && PtBelongToPlane(l[1], pl);
}

LD Det(P3 a, P3 b, P3 d) { // ok
    P3 pts[3] = {a, b, d};
    LD res = 0;
    for (int sign : {-1, 1}) {
        REP(st_col, 3) {
            int c = st_col;
            LD prod = 1;
            REP(r, 3) {
                prod *= pts[r][c];
                c = (c + sign + 3) % 3;
            }
            res += sign * prod;
        }
    }
    return res;
}

LD Area(P3 p, P3 q, P3 r) {

```

```

    q -= p; r -= p;
    return q.Area(r);
}

vector<Point> InterLineLine(Line &a, Line &b) {
    // working fine
    Point vec_a = a[1] - a[0];
    Point vec_b1 = b[1] - a[0];
    Point vec_b0 = b[0] - a[0];
    LD tr_area = vec_b1.CrossProd(vec_b0);
    LD quad_area = vec_b1.CrossProd(vec_a) + vec_a.CrossProd(vec_b0);
    if (abs(quad_area) < kEps) { // parallel or coinciding
        if (abs(b[0].CrossProd(b[1], a[0])) < kEps) {
            return {a[0], a[1]};
        } else return {};
    }
    return {a[0] + vec_a * (tr_area / quad_area)};
}

vector<P3> InterLineLine(Line3 k, Line3 l) {
    if (Lines3Equal(k, l)) return {k[0], k[1]};
    if (PtBelongToLine3(l[0], k)) return {l[0]};
    Plane pl{l[0], k[0], k[1]};
    if (!PtBelongToPlane(l[1], pl)) return {};
    Line k2 = PlaneLineTo2D(pl, k);
    Line l2 = PlaneLineTo2D(pl, l);
    vector<Point> inter = InterLineLine(k2, l2);
    vector<P3> res;
    for (auto P : inter) res.push_back(PlanePtTo3D(pl, P));
    return res;
}

LD DisLineLine(Line3 l, Line3 k) { // ok
    Plane together{l[0], l[1], l[0] + k[1] - k[0]}; // parallel FIXME
    Line3 proj = ProjLineToPlane(k, together);
    P3 inter = (InterLineLine(l, proj))[0];
    P3 on_k_inter = k[0] + inter - proj[0];
    return inter.Dis(on_k_inter);
}

Plane ParallelPlane(Plane pl, P3 A) { // plane parallel to pl going through A
    P3 diff = A - ProjPtToPlane(A, pl);
    return {pl[0] + diff, pl[1] + diff, pl[2] + diff};
}

// image of B in rotation wrt line passing through origin s.t. A1->A2
// implemented in more general case with similarity instead of rotation
P3 RotateAccordingly(P3 A1, P3 A2, P3 B1) { // ok
    Plane pl{A1, A2, {0, 0, 0}};
    Point A12 = PlanePtTo2D(pl, A1);
    Point A22 = PlanePtTo2D(pl, A2);
    complex<LD> rat = complex<LD>(A22.x, A22.y) / complex<LD>(A12.x, A12.y);
    Plane plb = ParallelPlane(pl, B1);
    Point B2 = PlanePtTo2D(plb, B1);
    complex<LD> Brot = rat * complex<LD>(B2.x, B2.y);
    return PlanePtTo3D(plb, {Brot.real(), Brot.imag()});
}

vector<Circle3> InterSpherePlane(Sphere s, Plane pl) { // ok
    P3 proj = ProjPtToPlane(s.o, pl);

```



```
LD dis = s.o.Dis(proj);
if (dis > s.r + kEps) return {};
if (dis > s.r - kEps) return {{pl, proj, 0}}
    ; // is it best choice?
return {{pl, proj, sqrt(s.r * s.r - dis *
dis)}};
}
bool PtBelongsToSphere(Sphere s, P3 p) { return
    abs(s.r - s.o.Dis(p)) < kEps; }
struct PointS { // just for conversion
    purposes, probably toEucl suffices
    LD lat, lon;
    P3 toEucl() { return P3(cos(lat) * cos(lon),
        cos(lat) * sin(lon), sin(lat)); }
    PointS(P3 p) {
        p.NormalizeSelf();
        lat = asin(p.z);
        lon = acos(p.y / cos(lat));
    }
};
LD DistS(P3 a, P3 b) { return atan2l(b.
    CrossProd(a).Norm(), a.DotProd(b)); }
struct CircleS {
    P3 o; // center of circle on sphere
    LD r; // arc len
    LD area() const { return 2 * kPi * (1 - cos(
        r)); }
};
CircleS From3(P3 a, P3 b, P3 c) { // any three
    different points
    int tmp = 1;
    if ((a - b).Norm() > (c - b).Norm()) {
        swap(a, c); tmp = -tmp;
    }
    if ((b - c).Norm() > (a - c).Norm()) {
        swap(a, b); tmp = -tmp;
    }
    P3 v = (c - b).CrossProd(b - a);
    v = v * (tmp / v.Norm());
    return CircleS{v, DistS(a, v)};
}
CircleS From2(P3 a, P3 b) { // neither the
    same nor the opposite
    P3 mid = (a + b) / 2;
    mid = mid / mid.Norm();
    return From3(a, mid, b);
}
LD SphAngle(P3 A, P3 B, P3 C) { // angle at A,
    no two points opposite
    LD a = B.DotProd(C);
    LD b = C.DotProd(A);
    LD c = A.DotProd(B);
    return acos((b - a * c) / sqrt((1 - Sq(a)) *
        (1 - Sq(c))));
}
LD TriangleArea(P3 A, P3 B, P3 C) { // no two
    points opposite
    LD a = SphAngle(C, A, B);
    LD b = SphAngle(A, B, C);
    LD c = SphAngle(B, C, A);
    return a + b + c - kPi;
}
vector<P3> IntersectionS(CircleS c1, CircleS
    c2) {
    P3 n = c2.o.CrossProd(c1.o), w = c2.o * cos(
        c1.r) - c1.o * cos(c2.r);
    LD d = n.SqNorm();
    if (d < kEps) return {}; // parallel circles
        (can fully overlap)
```

```
LD a = w.SqNorm() / d;
vector<P3> res;
if (a >= 1 + kEps) return res;
P3 u = n.CrossProd(w) / d;
if (a > 1 - kEps) {
    res.push_back(u);
    return res;
}
LD h = sqrt((1 - a) / d);
res.push_back(u + n * h);
res.push_back(u - n * h);
return res;
}
bool Eq(LD a, LD b) { return abs(a - b) < kEps
    ; }
vector<P3> intersect(Sphere a, Sphere b,
    Sphere c) { // Does not work for 3
        colinear centers
    vector<P3> res; // Bardzo podejrzana funkcja
        .
    P3 ex, ey, ez;
    LD r1 = a.r, r2 = b.r, r3 = c.r, d, cnd_x =
        0, i, j;
    ex = (b.o - a.o).Normalize();
    i = ex.DotProd(c.o - a.o);
    ey = ((c.o - a.o) - ex * i).Normalize();
    ez = ex.CrossProd(ey);
    d = (b.o - a.o).Norm();
    j = ey.DotProd(c.o - a.o);
    bool cnd = 0;
    if (Eq(r2, d - r1)) {
        cnd_x = +r1; cnd = 1;
    }
    if (Eq(r2, d + r1)) {
        cnd_x = -r1; cnd = 1;
    }
    if (!cnd && (r2 < d - r1 || r2 > d + r1))
        return res;
    if (cnd) {
        if (Eq(Sq(r3), (Sq(cnd_x - i) + Sq(j))))
            res.push_back(P3{cnd_x, LD(0), LD(0)});
    } else {
        LD x = (Sq(r1) - Sq(r2) + Sq(d)) / (2 * d)
            ;
        LD y = (Sq(r1) - Sq(r3) + Sq(i) + Sq(j)) /
            (2 * j) - (i / j) * x;
        LD u = Sq(r1) - Sq(x) - Sq(y);
        if (u >= -kEps) {
            LD z = sqrtl(max(LD(0), u));
            res.push_back(P3{x, y, z});
            if (abs(z) > kEps) res.push_back(P3{x, y
                , -z});
        }
    }
    for (auto &it : res) it = a.o + ex * it[0] +
        ey * it[1] + ez * it[2];
    return res;
}
```

Strings (9)

```
KMP.h
Description: pi[x] computes the length of the longest
    prefix of s that ends at x, other than s[0...x] itself (aba-
    caba -> 0010123). Can be used to find all occurrences of
    a string.
Time: O(n)
```

d4375c, 16 lines

```
vi pi(const string& s) {
    vi p(sz(s));
    rep(i,1,sz(s)) {
        int g = p[i-1];
        while (g && s[i] != s[g]) g = p[g-1];
        p[i] = g + (s[i] == s[g]);
    }
    return p;
}

vi match(const string& s, const string& pat) {
    vi p = pi(pat + '\0' + s), res;
    rep(i,sz(p)-sz(s),sz(p))
        if (p[i] == sz(pat)) res.push_back(i - 2 *
            sz(pat));
    return res;
}
```

Zfunc.h

```
Description: z[i] computes the length of the longest
    common prefix of s[i:] and s, except z[0] = 0. (abacaba
    -> 0010301)
Time: O(n)
```

ee09e2, 12 lines


```
vi Z(const string& S) {
    vi z(sz(S));
    int l = -1, r = -1;
    rep(i,1,sz(S)) {
        z[i] = i >= r ? 0 : min(r - i, z[i - 1]);
        while (i + z[i] < sz(S) && S[i + z[i]] ==
            S[z[i]])
            z[i]++;
        if (i + z[i] > r)
            l = i, r = i + z[i];
    }
    return z;
}
```

Manacher.h

```
Description: For each position in a string, computes
    p[0][i] = half length of longest even palindrome around
    pos i, p[1][i] = longest odd (half rounded down).
Time: O(N)
```

e7ad79, 13 lines

```
array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi,2> p = {vi(n+1), vi(n)};
    rep(z,0,2) for (int i=0,l=0,r=0; i < n; i++)
        {
            int t = r-i+!z;
            if (i<r) p[z][i] = min(t, p[z][l+t]);
            int L = i-p[z][i], R = i+p[z][i]-!z;
            while (L>=1 && R+1<n && s[L-1] == s[R+1])
                p[z][i]++, L--, R++;
            if (R>r) l=L, r=R;
        }
    return p;
}
```



PalindromicTree.h

```
Description: Makes a trie of O(|S|) vertices containing
    all distinct palindromes of a string. Suffix links give the
    longest proper suffix/prefix of that palindrome which is
    also a palindrome.
Usage: S := 1-indexed string. append
    characters 1-by-1.
    After adding the ith character, ptr points to
    the node containing
    the longest palindrome ending at i. Change
    ALPHA, ID() as problem requires.
Time: O(|S|)
```

13f2cf, 36 lines

```
const int ALPHA = 26;
struct PalindromicTree {
    struct node {
        int to[ALPHA];
        int link, len;
        node(int a=0, int b=0) : link(a), len(b) {
            memset(to, 0, sizeof to);
        };
        V<node> T; int ptr;
        int ID(char x) { return x - 'a'; }
        void init() {
            T.clear(); ptr = 1;
            T.emplace_back(0, -1); // 0=Odd root
            T.emplace_back(0, 0); // 1=Even root
        }
        void append(int i, string &s) {
            while (s[i - T[ptr].len - 1] != s[i])
                ptr = T[ptr].link;

            int id = ID(s[i]);
            // if node already exists, return
            if (T[ptr].to[id]) return void(ptr = T[ptr
                ].to[id]);
            int tmp = T[ptr].link;
            while (s[i - T[tmp].len - 1] != s[i])
                tmp = T[tmp].link;

            int newlink = T[ptr].len == -1 ? 1 : T[tmp
                ].to[id];

            // ptr is the parent of this new node
            T.emplace_back(newlink, T[ptr].len + 2);

            // Now shift ptr to the newly created node
            T[ptr].to[id] = sz(T) - 1;
            ptr = sz(T) - 1;
        }
};
```

MinRotation.h

```
Description: Finds the lexicographically smallest rota-
    tion of a string.
```

Usage: rotate(v.begin(), v.begin()+minRotation(v), v.end());
Time: $\mathcal{O}(N)$

d07a42, 8 lines

```
int minRotation(string s) {
    int a=0, N=sz(s); s += s;
    rep(b,0,N) rep(k,0,N) {
        if (a+k == b || s[a+k] < s[b+k]) {b += max(0, k-1); break;}
        if (s[a+k] > s[b+k]) {a = b; break;}
    }
    return a;
}
```

SuffixArray.h
Description: Builds suffix array for a string. sa[i] is the starting index of the suffix which is *i*'th in the sorted suffix array. The returned vector is of size *n* + 1, and sa[0] = n. lcp[i] = lcp(sa[i], sa[i-1]), lcp[0] = 0. The input string must not contain any nul chars.
Time: $\mathcal{O}(n \log n)$

635552, 22 lines

```
struct SuffixArray {
    vi sa, lcp; // passing V<int> also works
    SuffixArray(string s, int lim=256) {
        s.push_back(0); int n = sz(s), k = 0, a, b;
        vi x(all(s)), y(n), ws(max(n, lim));
        sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
            p = j, iota(all(y), n - j);
            rep(i,0,n) if(sa[i]>=j) y[p++] = sa[i]-j;
            fill(all(ws), 0);
            rep(i,0,n) ws[x[i]]++;
            rep(i,1,lim) ws[i] += ws[i - 1];
            for(int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i,1,n) a=sa[i-1], b=sa[i], x[b] =
                (y[a]==y[b] && y[a+j] == y[b+j]) ? p-1 : p++;
        }
        for (int i=0,j; i<n-1; lcp[x[i++]]=k)
            for (k && k--, j = sa[x[i] - 1];
                s[i + k] == s[j + k]; k++);
    } // loop with no body, wrong indentation
};
```

SuffixTree.h
Description: Ukkonen's algorithm for online suffix tree construction. Each node contains indices [l, r] into the string, and a list of child nodes. Suffixes are given by traversals of this tree, joining [l, r] substrings. The root is 0 (has l = -1, r = 0), non-existent children are -1. To get a complete tree, append a dummy symbol – otherwise it may contain an incomplete path (still useful for substring matching, though).
Time: $\mathcal{O}(26N)$

ca8d4d, 50 lines

```
struct SuffixTree { // N ~ 2*maxlen+10
    enum { N = 200010, ALP = 26 };
    int toi(char c) { return c - 'a'; }
    string a; // v = cur node, q = cur position
    int t[N][ALP], l[N], r[N], p[N], s[N], v=0, q=0, m=2;

    void ukkadd(int i, int c) { suff:
        if (r[v]<q) {
            if (t[v][c]==-1) { t[v][c]=m; l[m]=i;
                p[m++]=v; v=s[v]; q=r[v]; goto suff; }
            v=t[v][c]; q=l[v];
        }
    }
```

```
    if (q==-1 || c==toi(a[q])) q++; else {
        l[m+1]=i; p[m+1]=m; l[m]=l[v]; r[m]=q;
        p[m]=p[v]; t[m][c]=m+1;
        t[m][toi(a[q])] = v;
        l[v]=q; p[v]=m;
        t[p[m]][toi(a[l[m]])] = m;
        v=s[p[m]]; q=l[m];
        while (q<r[m]) { v=t[v][toi(a[q])]; q+=
            r[v]-l[v]; }
        if (q==r[m]) s[m]=v; else s[m]=m+2;
        q=r[v]-(q-r[m]); m+=2; goto suff;
    }
}
SuffixTree(string a) : a(a) {
    fill(r,r+N,sz(a));
    memset(s, 0, sizeof s);
    memset(t, -1, sizeof t);
    fill(t[l],t[l+ALP,0]);
    s[0] = 1; l[0] = l[1] = -1; r[0] = r[1] =
        p[0] = p[1] = 0;
    rep(i,0,sz(a)) ukkadd(i, toi(a[i]));
}
// example: find longest common substring (
// uses ALP = 28)
pii best;
int lcs(int node, int i1, int i2, int olen)
{
    if (l[node]<=i1 && i1<r[node]) return 1;
    if (l[node]<=i2 && i2<r[node]) return 2;
    int mask = 0, len = node ? olen + (r[node]
        - l[node]) : 0;
    rep(c,0,ALP) if (t[node][c] != -1)
        mask |= lcs(t[node][c], i1, i2, len);
    if (mask == 3)
        best = max(best, {len, r[node] - len});
    return mask;
}
static pii LCS(string s, string t) {
    SuffixTree st(s + (char)('z' + 1) + t + (
        char)('z' + 2));
    st.lcs(0, sz(s), sz(s) + 1 + sz(t), 0);
    return st.best;
}
};
```

Hashing.h
Description: Static hashing for 0-indexed string. Intervals are [l, r].

82983c, 20 lines

```
template<const ll M, const ll B>
struct Hashing {
    int n; V<ll> h, pw;
    Hashing(const string &s) : n(sz(s)),h(n+1),
        pw(n+1) {
        pw[0] = 1; // ^ s is 0 indexed
        for (int i = 1; i <= n; ++i)
            pw[i] = (pw[i-1] * B) % M,
            h[i] = (h[i-1] * B + s[i-1]) % M;
    }
    ll eval(int l, int r) { // assert(l <= r);
        return (h[r+1] - (h[l] * pw[r-l+1])%M +
            M)%M;
    }
};
struct Double_Hash {
    using H1 = Hashing<916969619, 101>;
    using H2 = Hashing<285646799, 103>;
    H1 h1; H2 h2;
    Double_Hash(const string &s):h1(s),h2(s){
        pii eval(int l, int r)
```

```
    { return {h1.eval(l,r), h2.eval(l,r)}; }
};
```

HashingDynamic.h
Description: Hashing with point updates on string (0-indexed). upd(i, x): s[i] += x. Intervals are [l, r].
Time: $\mathcal{O}(n \log n)$

c51931, 33 lines

```
template<const ll M, const ll B>
struct Dynamic_Hashing {
    int n; V<ll> h, pw;
    void upd(int pos, int c_add) {
        if (c_add < 0) c_add = (c_add + M) % M;
        for (int i = ++pos; i <= n; i += i&-i)
            h[i] = (h[i]+c_add *1LL* pw[i - pos])%M;
    }
    ll get(int pos, int r = 0) {
        for (int i = ++pos, j = 0; i; i -= i&-i) {
            r = (r + h[i] * 1LL * pw[j]) % M;
            j += i&-i;
        } return r;
    }
    Dynamic_Hashing(const string &s) : n(sz(s)),
        h(n+1), pw(n+1) {
        pw[0] = 1; // ^ s is 0 indexed
        for (int i = 1; i <= n; ++i) pw[i] = (pw[i
            -1] * 1LL * B) % M;
        for (int i = 0; i < n; ++i) upd(i, s[i]);
    }
    ll eval(int l, int r) { // assert(l <= r);
        return (get(r) - ((get(l-1) * 1LL * pw[r-l
            +1]) % M) + M) % M;
    }
};
struct Double_Dynamic {
    using DH1 = Dynamic_Hashing<916969619, 571>;
    using DH2 = Dynamic_Hashing<285646799, 953>;
    DH1 h1; DH2 h2;
    Double_Dynamic(const string &s) : h1(s), h2(
        s) {}
    void upd(int pos, int c_add) {
        h1.upd(pos, c_add);
        h2.upd(pos, c_add);
    }
    pll eval(int l, int r)
        { return {h1.eval(l,r), h2.eval(l,r)}; }
};
```

AhoCorasick-arman.h
Usage: insert strings first (0-indexed). Then call prepare to use everything. link = suffix link. to[ch] = trie transition. jump[ch] = aho transition to ch using links.
Time: $\mathcal{O}(AL)$

36fab, 35 lines

```
const int L = 5000; // Total no of characters
const int A = 10; // Alphabet size

struct Aho_Corasick {
    struct Node {
        bool end_flag;
        int par, pch, to[A], link, jump[A];
        Node() {
            par = link = end_flag = 0;
            memset(to, 0, sizeof to);
            memset(jump, 0, sizeof jump);
        }
    }; Node t[L]; int at;
    Aho_Corasick() { at = 0; }

    void insert(string &s) {
```

```
    int u = 0;
    for (auto ch : s) {
        int &v = t[u].to[ch - '0'];
        if (!v) v = ++at;
        t[v].par = u; t[v].pch = ch - '0'; u=v;
    } t[u].end_flag = true;
}
void prepare() {
    for(queue<int>q({0});!q.empty();q.pop()){
        int u = q.front(), w = t[u].link;
        for (int ch = 0; ch < A; ++ch) {
            int v = t[u].to[ch];
            if (v) {
                t[v].link = t[w].jump[ch];
                q.push(v);
            }
            t[u].jump[ch] = v ? v : t[w].jump[ch];
        }
    }
}
}aho;
```

Various (10)

Random.h
Description: Nice uniform real/int distribution wrapper

24d233, 9 lines

```
mt19937 rng(chrono::steady_clock::now().
    time_since_epoch().count());
// use mt19937.64 for long long
uniform_int_distribution<int> dist1(lo, hi);
uniform_real_distribution<> dist2(lo, hi);
// Usage
#define rand(l,r) uniform_int_distribution<ll>
    >(l, r)(rng.64)
int val = rng(), val3 = dist1(rng);
ll val2 = rng.64(); double val4 = dist2(rng);
shuffle(vec.begin(), vec.end(), rng);
```

10.1 Intervals
IntervalContainer.h
Description: Add and remove intervals from a set of disjoint intervals. Will merge the added interval with any overlapping intervals in the set when adding. Intervals are [inclusive, exclusive).
Time: $\mathcal{O}(\log N)$

edce47, 23 lines

```
set<pii>::iterator addInterval(set<pii>& is,
    int L, int R) {
    if (L == R) return is.end();
    auto it=is.lower_bound({L, R}), before=it;
    while (it != is.end() && it->first <= R) {
        R = max(R, it->second);
        before = it = is.erase(it);
    }
    if (it != is.begin() && (--it)->second >= L)
        {
            L = min(L, it->first);
            R = max(R, it->second);
            is.erase(it);
        }
    return is.insert(before, {L,R});
}
```

```
void removeInterval(set<pii>& is,int L,int R){
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L) is.erase(it);
```



```
    else (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}
```

IntervalCover.h

Description: Compute indices of smallest set of intervals covering another interval. Intervals should be [inclusive, exclusive). To support [inclusive, inclusive], change (A) to add || R.empty(). Returns empty set on failure (or if G is empty).
Time: $\mathcal{O}(N \log N)$

```
template<class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0); sort(all(S), [&](int a, int b) { return I[a] < I[b]; });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { // (A)
        pair<T, int> mx = make_pair(cur, -1);
        while (at<sz(I) && I[S[at]].first <= cur){
            mx = max(mx, make_pair(I[S[at]].second, S[at]));
            at++;
        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
    return R;
}
```

ConstantIntervals.h

Description: Split a monotone function on [from, to) into a minimal set of half-open intervals on which it has the same value. Runs a callback g for each such interval.
Usage: constantIntervals(0, sz(v), [&](int x){return v[x];}, [&](int lo, int hi, T val){...});
Time: $\mathcal{O}(k \log \frac{n}{k})$

```
template<class F, class G, class T>
void rec(int from, int to, F& f, G& g, int& i, T& p, T q) {
    if (p == q) return;
    if (from == to) {
        g(i, to, p);
        i = to; p = q;
    } else {
        int mid = (from + to) >> 1;
        rec(from, mid, f, g, i, p, f(mid));
        rec(mid+1, to, f, g, i, p, q);
    }
}
template<class F, class G>
void constantIntervals(int from, int to, F f, G g) {
    if (to <= from) return;
    int i = from; auto p = f(i), q = f(to-1);
    rec(from, to-1, f, g, i, p, q);
    g(i, to, q);
}
```

10.2 Misc. algorithms

LIS.h

Description: Compute indices for the longest increasing subsequence.

```
Time:  $\mathcal{O}(N \log N)$ 
2932a0, 17 lines
template<class I> vi lis(const vector<I>& S) {
    if (S.empty()) return {};
    vi prev(sz(S));
    typedef pair<I, int> p;
    vector<p> res;
    rep(i, 0, sz(S)) {
        // change 0 -> i for longest non-decreasing subsequence
        auto it = lower_bound(all(res), p{S[i], 0});
        if (it == res.end()) res.emplace_back(), it = res.end()-1;
        *it = {S[i], i};
        prev[i] = it == res.begin() ? 0 : (it-1)->second;
    }
    int L = sz(res), cur = res.back().second;
    vi ans(L);
    while (L--) ans[L] = cur, cur = prev[cur];
    return ans;
}
```

FastKnapsack.h

Description: Given N non-negative integer weights w and a non-negative target t, computes the maximum S <= t such that S is the sum of some subset of the weights.
Time: $\mathcal{O}(N \max(w_i))$

```
b20ccc, 16 lines
int knapsack(vi w, int t) {
    int a = 0, b = 0, x;
    while (b < sz(w) && a + w[b] <= t) a += w[b++];
    if (b == sz(w)) return a;
    int m = *max_element(all(w));
    vi u, v(2*m, -1);
    v[a+m-t] = b;
    rep(i, b, sz(w)) {
        u = v;
        rep(x, 0, m) v[x+w[i]] = max(v[x+w[i]], u[x]);
        for (x = 2*m; --x > m;) rep(j, max(0, u[x]), v[x])
            v[x-w[j]] = max(v[x-w[j]], j);
    }
    for (a = t; v[a+m-t] < 0; a--);
    return a;
}
```

10.3 Dynamic programming

KnuthDP.h

Description: When doing DP on intervals: $a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$, where the (minimal) optimal k increases with both i and j , one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j - 1]$ and $p[i + 1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b, c) \leq f(a, d)$ and $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$ for all $a \leq b \leq c \leq d$. Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.
Time: $\mathcal{O}(N^2)$

DivideAndConquerDP.h

Description: Given $a[i] = \min_{lo(i) \leq k < hi(i)} (f(i, k))$ where the (minimal) optimal k increases with i , computes $a[i]$ for $i = L..R - 1$.
Time: $\mathcal{O}((N + (hi - lo)) \log N)$

```
d38d2b, 18 lines
struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best (LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid)))
            best = min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second+1);
        rec(mid+1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};
```

10.4 Debugging tricks

- signal(SIGSEGV, [](int) { _Exit(0); }); converts segfaults into Wrong Answers. Similarly one can catch SIGABRT (assertion failures) and SIGFPE (zero divisions). _GLIBCXX_DEBUG failures generate SIGABRT (or SIGSEGV on gcc 5.4.0 apparently).
- feenableexcept(29); kills the program on NaNs (1), 0-divs (4), infinities (8) and denormals (16).

10.5 Optimization tricks

__builtin_ia32_ldmxcsr(40896); disables denormals (which make floats 20x slower near their minimum value).

10.5.1 Bit hacks

- x & -x is the least bit in x.
- for (int x = m; ; x = (x - 1) & m) // Here x is a submask of m if (!x) break;
- c = x&-x, r = x+c; Now ((r^x) >> 2)/c) | r is the next number after x with the same number of bits set.
- rep(b, 0, K) rep(i, 0, (1 << K)) if (i & 1 << b) D[i] += D[i^(1 << b)]; computes all sums of subsets, aka SOS DP.

variableBitset.h

```
bcf4b2, 8 lines
template<int N> void solve(int n) {
    if (n > N) {
        solve<min(2*N, 1'000'000)>(n);
    }
}
```

```
    return;
} // Now solving with bitset<N>;
} // call solve<I>(n)
```

10.5.2 Pragmas

- #pragma GCC optimize ("Ofast") will make GCC auto-vectorize loops and optimizes floating points better.
- #pragma GCC target ("avx2") can double performance of vectorized code, but causes crashes on old machines.
- #pragma GCC optimize ("trapv") kills the program on integer overflows (but is really slow).

FastMod.h

Description: Compute $a \% b$ about 5 times faster than usual, where b is constant but not known at compile time. Returns a value congruent to $a \pmod b$ in the range $[0, 2b)$.

```
751a02, 8 lines
typedef unsigned long long ull;
struct FastMod {
    ull b, m;
    FastMod(ull b) : b(b), m(-1ULL / b) {}
    ull reduce(ull a) { // a % b + (0 or b)
        return a - (ull)((__uint128_t(m) * a) >> 64) * b;
    }
};
```

FastInput.h

Description: Read an integer from stdin. Usage requires your program to pipe in input from file.
Usage: ./a.out < input.txt
Time: About 5x as fast as cin/scanf.

```
7b3c70, 15 lines
inline char gc() { // like getchar()
    static char buf[1 << 16];
    static size_t bc, be;
    if (bc >= be) {
        buf[0] = 0, bc = 0;
        be = fread(buf, 1, sizeof(buf), stdin);
    } return buf[bc++]; // returns 0 on EOF
}
int readInt() {
    int a, c;
    while ((a = gc()) < 40);
    if (a == '-') return -readInt();
    while ((c = gc()) >= 48) a = a*10+c-480;
    return a - 48;
}
```

BumpAllocator.h

Description: When you need to dynamically allocate many objects and don't care about freeing them. "new X" otherwise has an overhead of something like 0.05us + 16 bytes per allocation.

```
745db2, 8 lines
// Either globally or in a single class:
static char buf[450 << 20];
void* operator new(size_t s) {
    static size_t i = sizeof buf;
    assert(s < i);
    return (void*)&buf[i -= s];
}
```

```
}
void operator delete(void*) {}
```

SmallPtr.h
Description: A 32-bit pointer that points into BumpAl-
locator memory.

"BumpAllocator.h"2dd6c9, 10 lines

```
template<class T> struct ptr {
    unsigned ind;
    ptr(T* p = 0) : ind(p ? unsigned((char*)p -
        buf) : 0) {
        assert(ind < sizeof buf);
    }
    T& operator*() const { return *(T*)(buf +
        ind); }
    T* operator->() const { return &***this; }
    T& operator[](int a) const { return (&***this
        )[a]; }
    explicit operator bool() const { return ind;
    }
};
```

BumpAllocatorSTL.h
Description: BumpAllocator for STL containers.
Usage: vector<vector<int, small<int>>>>
ed(N);

bb66d4, 14 lines

```
char buf[450 << 20] alignas(16);
size_t buf_ind = sizeof buf;

template<class T> struct small {
    typedef T value_type;
    small() {}
    template<class U> small(const U&) {}
    T* allocate(size_t n) {
        buf_ind -= n * sizeof(T);
        buf_ind &= 0 - alignof(T);
        return (T*)(buf + buf_ind);
    }
    void deallocate(T*, size_t) {}
};
```

Unrolling.h

5e0f99, 14 lines

```
#define F {...; ++i;}
int i = from;
while (i&3 && i < to) F // for alignment, if
    needed
while (i + 4 <= to) { F F F F }
while (i < to) F

int n32 = n / 32;
while (n32--) {
#define F(i) a[i] = a[i] == x ? y : a[i];
#define FP(i) F(i+0) F(i+1) F(i+2) F(i+3)
    FP(0); FP(4); FP(8); FP(12);
    FP(16); FP(20); FP(24); FP(28);
    a += 32;
}
```

Dates.h
Description: Convert dates to day number and reverse.

b203cf, 18 lines

```
int date_to_int(int y, int m, int d) {
    if (m <= 2) y--, m += 12;
    return 365*y + y/4 - y/100 + y/400 + (153*m
        - 457)/5 + d - 306;
}
```

```
void int_to_date(int z, int &y, int &m, int &d
    ) {
    z += 306;
    int a = z + 68569;
    int b = 4*a/146097;
    a = a - (146097*b + 3)/4;
    int c = 4000*(a + 1)/1461001;
    a = a - 1461*c/4 + 31;
    int e = 80*a/2447;
    d = a - 2447*e/80;
    a = e/11;
    m = e + 2 - 12*a;
    y = 100*(b - 49) + c + a;
}
```

Techniques (11)

techniques.txt

Invariants, Monovariants, whatever-variants, see what changes and what does not from start to finish.
Greedy: sorting, matroid, matroid intersection, add and remove, etc.
Extreme values for greedy: Find the maximum achievable. Is it always achievable? Figure out the necessary conditions. Maybe they are also sufficient (and vice versa)
Fix a parameter and maximize the result wrt that parameter. Can you binary search there too?
Construct the lower/upper bounds.
Guess the form, and use induction to prove it.
When asked about how many beautiful things exist, you must ask how it is beautiful.
Backward solving.
Look at the constraints properly.
Thoroughly read the problem again.
Do your integers fit in int? Convert to long long when dealing with large bitshifts and what not. Check constants and single letter variables.
Try out cases, bruteforce for patterns if pc is available. If many people solved it, it is usually something simple. But dont get stuck in trying to find patterns.
Try to simplify the problem, or solve simpler cases: functional graphs, DAGs, cycles, and strongly connected components instead of directed graphs; trees, cycles, and biconnected components instead of graphs; paths instead of trees; 1D instead of 2D; permutation instead of arrays; etc.
Pigeonhole principle, birthday paradox, inclusion-exclusion, double counting, etc.
Maybe your idea is fast enough in practice or maybe your complexity analysis is too loose.
BFS, DFS, BFS trees, DFS trees, hall-marriage for bipartite graphs.
Topological sorting can maybe make dp on DAGs faster or save memory.
Min cut is powerful for stuff like the project selection problem: n machines with cost q_i and m projects with revenue p_i, with each project requiring a set of machines.

SQRT decomp for time or memory, binary jumping, and other forms of divide and conquer.
Online MO?
Two-pointer
Offline preprocessing
Bitsets to optimize silly bruteforce
Games: nim, grundy, pattern, etc.
Geometry: isometries and other transformations (manhattan-to-chebyshev, translations, rotations, etc), line sweep, radial sweep, lots of sweeping. Turn other problems into geometry problems.
Hashing: strings, sets, multisets, rooted trees, ordered rooted trees, etc. Super powerful.
String: tries, suffix trees, suffix arrays, kmp, etc.
Randomization.
HLD, centroid decomp, treaps, seg tree, persistent seg tree, sliding window, etc.
FFT and friends: generating functions.
DP: memory optimization, CHT, LiChao, D&C, Knuth, functions as values, aliens trick (for problems involving partition into k segments, set a penalty for creating partitions, then binary search on penalty value and compare with the optimal solution where any number of partitioning is allowed), prefix sum, seg tree, etc.
Remember about boundary cases.
Functional graphs, especially for permutation problems.
Bitwise or randomized for interactive problems with logarithmic number of allowed inputs
.