

# Tidy evaluation with rlang :: CHEAT SHEET




## Vocabulary

**Tidy Evaluation (Tidy Eval)** is not a package, but a framework for doing non-standard evaluation (i.e. delayed evaluation) that makes it easier to program with tidyverse functions.

**pi**

**Symbol** - a name that represents a value or object stored in R. `is_symbol(expr(pi))`



**Environment** - a list-like object that binds symbols (names) to objects stored in memory. Each env contains a link to a second, **parent** env, which creates a chain, or search path, of environments. `is_environment(current_env())`

**rlang::caller\_env**(n = 1) Returns calling env of the function it is in.

**rlang::child\_env**(parent, ...) Creates new env as child of .parent. Also **env**.

**rlang::current\_env**() Returns execution env of the function it is in.

**1**

**Constant** - a bare value (i.e. an atomic vector of length 1). `is_bare_atomic(1)`

**abs ( 1 )**

**Call object** - a vector of symbols/constants/calls that begins with a function name, possibly followed by arguments. `is_call(expr(abs(1)))`

**pi** — code  
3.14 — result

**Code** - a sequence of symbols/constants/calls that will return a result if evaluated. Code can be:

1. Evaluated immediately (**Standard Eval**)
2. Quoted to use later (**Non-Standard Eval**)

`is_expression(expr(pi))`

**e**  
a + b

**Expression** - an object that stores quoted code without evaluating it. `is_expression(expr(a + b))`

**q**  
a + b, a b

**Quosure** - an object that stores both quoted code (without evaluating it) and the code's environment. `is_quosure(quo(a + b))`

**rlang::quo\_get\_env**(quo) Return the environment of a quosure.

**rlang::quo\_set\_env**(quo, expr) Set the environment of a quosure.


**rlang::quo\_get\_expr**(quo) Return the expression of a quosure.

**Expression Vector** - a list of pieces of quoted code created by base R's `expression` and `parse` functions. Not to be confused with **expression**.

## Quoting Code

Quote code in one of two ways (if in doubt use a quosure):

### QUOSURES




**Quosure** - An expression that has been saved *with an environment* (aka a closure).

A quosure can be evaluated later in the stored environment to return a predictable result.


**rlang::quo**(expr) Quote contents as a quosure. Also **quos** to quote multiple expressions. `a <- 1; b <- 2; q <- quo(a + b); qs <- quos(a, b)`

**rlang::enquo**(arg) Call from within a function to quote what the user passed to an argument as a quosure. Also **enquos** for multiple args. `quote_this <- function(x) enquo(x)`  
`quote_these <- function(...) enquos(...)`

**rlang::new\_quosure**(expr, env = caller\_env()) Build a quosure from a quoted expression and an environment. `new_quosure(expr(a + b), current_env())`



### EXPRESSION



**Quoted Expression** - An expression that has been saved by itself.


A quoted expression can be evaluated later to return a result that will depend on the environment it is evaluated in

**rlang::expr**(expr) Quote contents. Also **exprs** to quote multiple expressions. `a <- 1; b <- 2; e <- expr(a + b); es <- exprs(a, b, a + b)`

**rlang::enexpr**(arg) Call from within a function to quote what the user passed to an argument. Also **enexprs** to quote multiple arguments. `quote_that <- function(x) enexpr(x)`  
`quote_those <- function(...) enexprs(...)`

**rlang::ensym**(x) Call from within a function to quote what the user passed to an argument as a symbol, accepts strings. Also **ensyms**. `quote_name <- function(name) ensym(name)`  
`quote_names <- function(...) ensyms(...)`

## Parsing and Deparsing




**Parse** - Convert a string to a saved expression.

**Deparse** - Convert a saved expression to a string.

**rlang::parse\_expr**(x) Convert a string to an expression. Also **parse\_exprs**, **sym**, **parse\_quo**, **parse\_quos**. `e <- parse_expr("a + b")`

**rlang::expr\_text**(expr, width = 60L, nlines = Inf) Convert expr to a string. Also **quo\_name**. `expr_text(e)`

## Evaluation



To evaluate an expression, R:

1. Looks up the symbols in the expression in the active environment (or a supplied one), followed by the environment's parents
2. Executes the calls in the expression

**The result of an expression depends on which environment it is evaluated in.**

### QUOTED EXPRESSION

**rlang::eval\_bare**(expr, env = parent.frame()) Evaluate expr in env. `eval_bare(e, env = GlobalEnv)`

### QUOSURES (and quoted exprs)

**rlang::eval\_tidy**(expr, data = NULL, env = caller\_env()) Evaluate expr in env, using data as a **data mask**. Will evaluate quosures in their stored environment. `eval_tidy(q)`

**Data Mask** - If data is non-NULL, `eval_tidy` inserts data into the search path before env, matching symbols to names in data.

Use the pronoun **.data\$** to force a symbol to be matched in data, and **!!** (see back) to force a symbol to be matched in the environments.

`a <- 1; b <- 2`  
`p <- quo(.data$a + !!b)`  
`mask <- tibble(a = 5, b = 6)`  
`eval_tidy(p, data = mask)`

## Building Calls

**rlang::call2**(fn, ..., .ns = NULL) Create a call from a function and a list of args. Use **exec** to create and then evaluate the call. (See back page for **!!!**) `args <- list(x = 4, base = 2)`

**log** (x = 4, base = 2)

**2**

`call2("log", x = 4, base = 2)`  
`call2("log", !!!args)`

`exec("log", x = 4, base = 2)`  
`exec("log", !!!args)`


# Quasiquotation (!! , !!! , :=)

## QUOTATION

Storing an expression without evaluating it.  
`e <- expr(a + b)`

## QUASIQUOTATION

Quoting some parts of an expression while evaluating and then inserting the results of others (**unquoting** others).  
`e <- expr(a + b)`




rlang provides **!!**, **!!!**, and **:=** for doing quasiquotation.


**!!**, **!!!**, and **:=** are not functions but syntax (symbols recognized by the functions they are passed to). Compare this to how

. is used by `magrittr::%>%()`  
. is used by `stats::lm()`  
.x is used by `purrr::map()`, and so on.


**!!**, **!!!**, and **:=** are only recognized by some rlang functions and functions that use those functions (such as tidyverse functions).




**!!** Unquotes the symbol or call that follows. Pronounced "unquote" or "bang-bang." `a <- 1; b <- 2`  
`expr(log(!!a + b))`



Combine **!!** with **()** to unquote a longer expression.  
`a <- 1; b <- 2`  
`expr(log(!!(a + b)))`



**!!!** Unquotes a vector or list and splices the results as arguments into the surrounding call. Pronounced "unquote splice" or "bang-bang-bang." `x <- list(8, b = 2)`  
`expr(log(!!!x))`



**:=** Replaces an `=` to allow unquoting within the name that appears on the left hand side of the `=`. Use with **!!**  
`n <- expr(uno)`  
`tibble::tibble(!!n := 1)`

# Programming Recipes

**Quoting function**- A function that quotes any of its arguments internally for delayed evaluation in a chosen environment. You must take **special steps to program safely** with a quoting function.

## How to spot a quoting function?

A function quotes an argument if the argument returns an error when run on its own.

Many tidyverse functions are quoting functions: e.g. **filter**, **select**, **mutate**, **summarise**, etc.

```
dplyr::filter(cars, speed == 25)
  speed dist
1    25   85
```

```
speed == 25
Error!
```

## PROGRAM WITH A QUOTING FUNCTION

```
data_mean <- function(data, var) {
  require(dplyr)
  var <- rlang::enquo(var)      1
  data %>%
    summarise(mean = mean(!!var)) 2
}
```

1. Capture user argument that will be quoted with `rlang::enquo`.
2. Unquote the user argument into the quoting function with **!!**.

## MODIFY USER ARGUMENTS

```
my_do <- function(f, v, df) {
  f <- rlang::enquo(f)      1
  v <- rlang::enquo(v)      2
  todo <- rlang::quo(!!f)(!!v) 3
  rlang::eval_tidy(todo, df)
}
```

1. Capture user arguments with `rlang::enquo`.
2. **Unquote** user arguments into a new expression or quosure to use
3. **Evaluate** the new expression/quosure instead of the original argument

## PASS MULTIPLE ARGUMENTS TO A QUOTING FUNCTION

```
group_mean <- function(data, var, ...) {
  require(dplyr)
  var <- rlang::enquo(var)      1
  group_vars <- rlang::enquos(...) 1
  data %>%
    group_by(!!!group_vars) %>% 2
    summarise(mean = mean(!!var))
}
```

1. Capture user arguments that will be quoted with `rlang::enquos`.
2. Unquote splice the user arguments into the quoting function with **!!!**.

## APPLY AN ARGUMENT TO A DATA FRAME

```
subset2 <- function(df, rows) {
  rows <- rlang::enquo(rows)    1
  vals <- rlang::eval_tidy(rows, data = df) 2
  df[vals, , drop = FALSE]
}
```

1. Capture user argument with `rlang::enquo`.
2. Evaluate the argument with `rlang::eval_tidy`. Pass the data frame to **data** to use as a data mask.
3. **Suggest** in your documentation that your users use the **.data** and **.env** pronouns.

## WRITE A FUNCTION THAT RECOGNIZES QUASIQUOTATION (!! , !!! , :=)



1. Capture the quasiquotation-aware argument with `rlang::enquo`.
2. Evaluate the arg with `rlang::eval_tidy`.

```
add1 <- function(x) {
  q <- rlang::enquo(x)      1
  rlang::eval_tidy(q) + 1    2
}
```

## PASS TO ARGUMENT NAMES OF A QUOTING FUNCTION

```
named_m <- function(data, var, name) {
  require(dplyr)
  var <- rlang::enquo(var)      1
  name <- rlang::ensym(name)    1
  data %>%
    summarise(!!name := mean(!!var)) 2
}
```

1. Capture user argument that will be quoted with `rlang::ensym`.
2. Unquote the name into the quoting function with **!!** and **:=**.

## PASS CRAN CHECK

```
#' @importFrom rlang .data      1
mutate_y <- function(df) {
  dplyr::mutate(df, y = .data$a + 1) 2
}
```

Quoted arguments in tidyverse functions can trigger an **R CMD check** NOTE about undefined global variables. To avoid this:

1. Import `rlang::.data` to your package, perhaps with the `roxygen2` tag **@importFrom rlang .data**
2. Use the **.data** pronoun in front of variable names in tidyverse functions