



HOCHSCHULE KONSTANZ TECHNIK, WIRTSCHAFT UND GESTALTUNG
UNIVERSITY OF APPLIED SCIENCES

Context-Aware Museum Guide for Mobile Devices

Maurizio Tidei

Constance, 16.04.2015

MASTER'S THESIS

MASTERARBEIT

zur Erlangung des akademischen Grades

Master of Science (M. Sc.)

an der

Hochschule Konstanz

Technik, Wirtschaft und Gestaltung

Fakultät Informatik

Studiengang Master of Science Informatik

Thema: **Context-Aware Museum Guide for Mobile Devices**

Masterkandidat: Maurizio Tidei, Kapellenstr.4, 78262 Gailingen

1. Prüfer: Prof. Dr. Marko Boger
2. Prüfer: Prof. Dr. Christian Johner

Ausgabedatum: 16.10.2014

Abgabedatum: 16.04.2015

Zusammenfassung (Abstract)

Thema: Context-Aware Museum Guide for Mobile Devices

Masterkandidat: Maurizio Tidei

Firma: HTWG / contexagon GmbH

Betreuer: Prof. Dr. Marko Boger
Prof. Dr. Christian Johner

Abgabedatum: 16.04.2015

Schlagworte: Contextual Computing, Indoor Navigation, Scala, Swift

Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet. Lorem ipsum dolor sit amet, consetetur sadipscing elitr, sed diam nonumy eirmod tempor invidunt ut labore et dolore magna aliquyam erat, sed diam voluptua. At vero eos et accusam et justo duo dolores et ea rebum. Stet clita kasd gubergren, no sea takimata sanctus est Lorem ipsum dolor sit amet.

Ehrenwörtliche Erklärung

Hiermit erkläre ich *Maurizio Tidei*, geboren am 23.11.1980 in Singen, dass ich

- (1) meine Masterarbeit mit dem Titel

Context-Aware Museum Guide for Mobile Devices

bei der HTWG / contexagon GmbH unter Anleitung von Prof. Dr. Marko Boger selbständig und ohne fremde Hilfe angefertigt und keine anderen als die angeführten Hilfen benutzt habe;

- (2) die Übernahme wörtlicher Zitate, von Tabellen, Zeichnungen, Bildern und Programmen aus der Literatur oder anderen Quellen (Internet) sowie die Verwendung der Gedanken anderer Autoren an den entsprechenden Stellen innerhalb der Arbeit gekennzeichnet habe.

Ich bin mir bewusst, dass eine falsche Erklärung rechtliche Folgen haben wird.

Konstanz, 16.04.2015

(Unterschrift)

Acknowledgements

Lorem ipsum dolor

Contents

Abstract	ii
Ehrenwörtliche Erklärung	iii
Acknowledgements	iv
Contents	v
List of Figures	vii
Abbreviations	viii
1 Introduction	1
1.1 The goal of this work	1
1.2 Motivation	2
1.3 The Approach	2
2 Theoretical Background	3
2.1 What is Context-Aware Computing?	3
2.1.1 Definition of Context	3
2.1.2 Categories of Context	4
2.1.3 Categories of Context-Aware Applications	5
2.1.4 Ubiquitous Computing	6
2.2 Sensors of Mobile Devices	7
2.2.1 Accelerometer	7
2.2.2 Gyroscope	7
2.2.3 Magnetometer	8
2.2.4 Barometer	8
2.2.5 Proximity Sensor	8
2.2.6 Light Sensor	8
2.3 Localization Techniques	8
2.4 Bluetooth Low Energy iBeacons	8
2.5 Swift	8
2.5.1 What is Swift?	8
2.5.2 Comparison Scala and Swift	9
2.5.3 Major Differences to Scala	11

2.5.3.1	Implicit Type Conversions	11
2.5.3.2	Optionals	11
2.5.3.3	Getter and Setter	13
2.5.3.4	Exception Handling	14
2.5.3.5	Summary	15
2.6	iOS and Cocoa Touch	15
 A Appendix Title Here		 16
 Bibliography		 17

List of Figures

Abbreviations

INS	I nternal N avigation S ystem
MEMS	M icro e lectro m echanical S ystem
DSL	D omain S pecific L anguage
REPL	R ead- E val- P rint- L oop

Chapter 1

Introduction

Mobile Devices are rapidly evolving to very powerful personal devices full of sensors that provide several kind of context information, combined with great computing power in an hand held device.

This level of computing power was reserved for stationary desktop computers a few years ago, or to room filling supercomputers some decades ago. At the same time, the devices are spreading out to more and more people.

This development empowers a new kind of computing to find it's way out of research laboratories, where such systems ran on special hardware in artificial environments, into our daily lives: [cf. [1](#)] *context-aware computing*.

1.1 The goal of this work

This thesis is about designing and implementing a context-aware mobile system for guiding a visitor through indoor and outdoor exhibitions like parks and a museums.

The goal is to design a flexible software platform that is easily adaptable to fit different exhibitions and runs on commodity hardware.

The system consists of two main parts:

The first one is a kind of a content management system that allows to define all relevant textual and audio information describing the exhibitions areas and single exhibits using a web interface.

The second one is the application running on the mobile device of the visitor. The goal is to provide relevant information at the right time to the visitor, thus enhancing his experience.

1.2 Motivation

This work is a basis for the first product of the start-up contexagon GmbH in Kreuzlingen, Switzerland. The company was founded in September 2014 by the author, Maurizio Tidei, and Sascha P. Lorenz ¹ after several conversations with museum directors in the area of the Lake of Constance in Summer 2014, which expressed interest in such a solution and encouraged us in pursuing the development of an affordable system based on commodity hardware and a highly configurable software platform.

1.3 The Approach

Since the location context is key for the system that has to be designed, first, different methods for providing the location context are evaluated (Chapter 2.1).

Chapter 2.2 describes the chosen programming languages and tools.

Out of the possible context providing methods, the best fitting ones are tested in several technology prototypes (Chapter 3).

The system design will be discussed in Chapter 4.

The first results using the application in a real-life scenario in the "Schloss Arenenberg" Park and World War I exposition are presented in Chapter 5.

Chapter 6 handles the conclusion and future work.

¹S. P. Lorenz is currently writing his Master Thesis on Big Data Processing, e.g. for analyzing visitor interests

Chapter 2

Theoretical Background

2.1 What is Context-Aware Computing?

The term "context-aware computing" was first used by B. Schilit et. al. 1994 in the paper "Context-Aware Computing Applications" [2]. They introduce a this new kind of computing as a "new class of applications that are aware of the context in which they are run. Such context-aware systems adapts according to the location of use, the collection of nearby people, hosts, and accessible devices, as well as to changes to such things over time".

2.1.1 Definition of Context

Schilit defined context by enumeration of examples that are all related to location and proximity.

Dey and Abowd provided a precise universal definition of context in their paper "Towards a Better Understanding of Context and Context-Awareness" published 1999 [3]: "Context is any information that can be used to characterize the situation of an entity. An entity is a person, place, or object that is considered relevant to the interaction between a user and an application, including the user and applications themselves."

While being precise, this definition is too general to get an idea of which kind of context information an application could use. So the following subchapter provides a wider list of context examples and a categorization.

2.1.2 Categories of Context

There are many different types of context:

Computing Context

Some examples are network connectivity, communication costs and bandwidth or available resources like printers, displays and input devices.

User Context

- The user's *identity*, including his age, gender, education, profession, interests. In today's age of social media the user's connections to other people and their identity are important and widely available as well.
- The *location* is the most obvious kind of user context. It can be subdivided in two different sub types of location:
Logical location, e.g. "at home" or "at work" or slightly different "in a library, restaurant, cinema"
Absolute location, e.g. "47°40'02.0"N 9°10'19.7"E" as geographic coordinates on earth or 2nd floor room 205 in the F-Building of HTWG Konstanz.
- The *emotional state* indicating if the user is happy, angry, worried etc. At which level is the personal stress level?
- *Fisical state*: Is the user rested or tired?
- The user's *health state*, determined by measuring some vital parameters (e.g. hearth rate, blood pressure and oxygen saturation). Many dedicated low-cost hardware items for this kind of measurements were released in 2014 or are announced for this year.
- Information about other people or mobile devices nearby forms the *co-location* context.
- The current *activity*. For example walking, driving a car, riding a bicycle or jogging. Some of this activities need to be further specificated, e.g. jogging to practice sport or jogging for catching a train.

Time Context

The time context, such as the current time of the day, the day of the week, the current season or the full date.

Physical Context

Some examples for environment information are the current temperature, the weather, the intensity of ambient light, the noise level and even traffic condition.

cf. [\[4\]](#)

2.1.3 Categories of Context-Aware Applications

Schilit and his co-authors describe the following four categories of context-aware applications:

- **Proximate Selection**

Highlighting actions or information based on the current location of the user is called "Proximate Selection". While this user interface technique generally requires a user entering his location manually, context-aware systems default it automatically to the currently sensed location.

Nowadays, we encounter this behavior in many smartphone applications like weather forecasts for the current city, searching nearby stores in digital yellow-pages or even when performing online searches on non-portable computers.

- **Automatic Contextual Reconfiguration**

"Automatic Contextual Reconfiguration" means loading and activating different system configurations based on the current context of use. For example, loading a different digital whiteboard per room gives the illusion of accessing it as if it was physically mounted in that room. But the considered context information is not limited to the location. Changing the energy plan of a notebook based on the connection status of the A/C power cable or the current battery level are further examples for this category.

- Contextual Information and Commands

This category contains systems providing the right piece of information and offering the adequate actions at the right time fitting the current context.

Retrieving information provided as text, audio, picture and video form, fitting to the current location context of the user is obviously a key feature of the museum guide that is developed as part of this master thesis.

- Context-Triggered Actions

Context-triggered actions are applications that execute a defined action when a specific predefined context-state is reached. In contrast to contextual information and commands, these actions are automatically executed. Combining multiple rules allows designing more complex behaviors.

Obviously, nowadays there are many applications that fit in two or more categories. A modern smartphone based navigating system for example offers functions like "Take me to a gas station", displaying a list with the nearest one already preselected (proximate selection). When light conditions change, like when entering a tunnel or when it gets dark, the display is automatically dimmed. The pedestrian mode is an example for two categories: The device senses steps and switches automatically into pedestrian mode considering paths not accessible by car (automatic contextual reconfiguration) and offering commands like "Take me back to my parking lot" (contextual commands).

2.1.4 Ubiquitous Computing

The vision and research field of ubiquitous computing was coined 1991 by Mark Weiser of Xerox PARC in his article "The Computer for the 21st Century" [5]. Weiser's starts his article with these words: "The most profound technologies are those that disappear. They weave themselves into the fabric of everyday life until they are indistinguishable from it."

For computers that means being integrated in common objects of daily usage, supporting humans without demanding their full attention.

As very good example for a technology that disappeared in the background he uses the vanishing of electric motors. At the beginning, big powerful engines powered a whole

fabric, with axles and belts distributing the force to the single machines. Later each machine had its own motor and today several electric motors - miniaturized and bigger ones - are integrated into a single device. Often they work in the background letting us focus on the main task. Already in 1991, as he writes, a typical car had more than 20 motors to start the engine, lock and unlock the doors, clean the windshield, open and close the windows and so on.

Although Weiser didn't use the term context-awareness, he already recognized the importance of the location context: "We have found two issues of crucial importance: location and scale. Little is more basic to human perception than physical juxtaposition, and so ubiquitous computers must know where they are. [...] If a computer merely knows what room it is in, it can adapt its behavior in significant ways without requiring even a hint of artificial intelligence."

2.2 Sensors of Mobile Devices

2.2.1 Accelerometer

2.2.2 Gyroscope

Pedometer ref.

2.2.3 Magnetometer

2.2.4 Barometer

Some of the latest smartphones and tablets are equipped with a barometer for measuring the air pressure. This information combined with the current weather dependent ground pressure can be used to determine the current altitude or the floor of the building the device is in.

2.2.5 Proximity Sensor

The proximity sensor typically measures the distance of the device's front to the next object. It is used to turn off the display when holding a mobile phone at the ear or to determine if the phone is inside a pocket.

2.2.6 Light Sensor

The light sensor measures the intensity of the light. It is primarily used to adapt the screen brightness to the ambient light.

2.3 Localization Techniques

2.4 Bluetooth Low Energy iBeacons

Bluetooth Low Energy (BLE) is a standard

2.5 Swift

2.5.1 What is Swift?

Swift is a modern programming language released by Apple in 2014. In [6] Apple introduces Swift as "a new programming language for iOS and OS X that builds on the best of C and Objective-C, without the constraints of C compatibility".

Since Swift is a cutting-edge language, this section is dedicated more attention as one would normally do for a implementation language inside a thesis.

Developers already familiar with the well designed functional programming language Scala will recognize several concepts. It has a concise Syntax avoiding big parts of boilerplate code and syntactic noise, supports functional programming and is statically typed.

The following section is an overview comparison of Scala and Swift features, created during the familiarization with Swift for this thesis. Language features marked with a * will be discussed separately in section 2.5.3.

2.5.2 Comparison Scala and Swift

Language Feature	Scala	Swift
Type inference	yes	yes
Line end separates commands (no need for semicolon)	yes	yes
Implicit type conversions *	yes	no
Default access levels (access level has to be only provided if it differs from default)	yes	yes
Functions are first class types ¹	yes	yes
Closures	yes	yes
Curried functions	yes	yes
Operator functions	yes	yes
Optionals *	via <code>Option[T]</code> class	widely used, dedicated Syntax
Switch with pattern matching	yes	yes
String interpolation	yes <code>"Hello \$nameVar"</code>	yes <code>"Hello \(nameVar)"</code>
Keyword for variable definition	<code>var radius = 1</code>	<code>var radius = 1</code>
Keyword for constant definition	<code>let pi = 3.14</code>	<code>val pi = 3.14</code>
Array literal	<code>Array(1,2,3)</code>	<code>[1,2,3]</code>
Map literal	<code>Map(1->"a", 2->"b")</code>	<code>[1:"a", 2:"b"]</code> ²
If condition must be boolean	yes	yes
Tuples	yes, but without named elements	yes

¹Functions can be passed to functions, returned from functions, created at runtime and assigned to variables

²Maps are called dictionaries in Swift

Language Feature	Scala	Swift
Ranges	<code>for i <- 0 to 4</code> <code>0 until 4</code>	<code>for i in 0...4</code> <code>0..<code>4</code></code>
Constructor	<code>def this()</code>	<code>init()</code>
Extended getter/setter concept *	yes, no observers	yes, very flexible concept including observers (<code>willSet()</code> <code>didSet()</code> events)
Interfaces	<code>trait</code>	<code>protocol</code>
Extension of existing types	yes	yes
Struct	no	yes
Enum	via extending the Enumeration class	yes, dedicated keyword
”Any” Type	<code>Any</code> , <code>AnyVal</code> , <code>AnyRef</code>	<code>Any</code> (instance of any type, even function types) <code>AnyObject</code> (instance of any class type)
Query an instance of a type by a key in brackets, like arrays or maps	<code>obj(index)</code> calls <code>obj.apply</code> method <code>obj(index) = newValue</code> calls <code>obj.update(0,</code> <code>newValue)</code>	<code>subscript(i:T) -> T2</code> { <code>get {...}</code> <code>set(newValue) {...}</code> }
Memory Management	JVM Garbage Collection	Automatic Reference Counting
Nested Functions	yes	yes
Generics	yes	yes

2.5.3 Major Differences to Scala

In this section, the major differences between Scala and Swift that are encountered during the first Swift projects are described.

2.5.3.1 Implicit Type Conversions

In Swift, every type conversion has to be explicit. Even when using different numerical types inside an arithmetic expression, the conversion is not done automatically, in contrast to Scala and even Java. So this code yields a compile time error for example:

```
let a = 1.0
let b = 2
let c = a + b // compiler error: cannot invoke '+' with an
               argument list of type '(@lvalue Double, @lvalue Int)
```

To get an integer 3 assigned to the variable 'c', you need to cast 'a' to Int. For a decimal 3.0, the variable 'b' has to be cast to Double.

```
let c = Int(a) + b // ok, c is 3 Int
let d = a + Double(b) // ok, d is 3.0 Double
```

Although initially it can be a bit frustrating running into compile errors of this kind, you get used to explicitly casting the values to the desired types fast. The advantage of this approach is that the developer explicitly sees the type of the resulting value without having to remember language specific rules.

In contrast, Scala has a powerful implicit type conversion system. Combined with operator overloading it enables developers to create beautiful internal DSL (Domain Specific Languages) that read more like natural language. ³ But, as M. Odersky rightly wrote in [8, Chapter 6.13], "... bear in mind that with power comes responsibility. If used unartfully, both operator methods and implicit conversions can give rise to client code that is hard to read and understand."

2.5.3.2 Optionals

Variables are non nullable by default in Swift. So the following code will not compile:

```
var name = "Swift"
name = nil // compile time error: Type 'String' does not conform
           to protocol 'NilLiteralConvertible'
```

As a consequence, the variable can safely be accessed at any time without the danger of a `NullPointerException` respectively a `nil` runtime error.

³A good example for using implicit conversion to build a DSL query language can be found at [7]

To allow a variable to assume the value of nil (the null equivalent in Swift), it's type has to be defined as optional by the '?' postfix to the type name.

```
var name:String? = "Swift"
println(name)    // prints 'Optional("Swift")' to the console
println(name!)  // prints 'Swift'
name = nil      // ok
let statement = name + " is great" // compile time error: value of
    optional type 'String?' not unwrapped
println(name!)  // runtime error: unexpectedly found nil while
    unwrapping an Optional value
```

The first println statement outputs 'Optional("Swift")' because the string value is wrapped inside the optional and needs to be unwrapped using the '!' postfix. Note that trying to unwrap an optional without value yields a runtime error.

A convenient way of querying properties or calling methods on optionals is called optional chaining. Imagine a circle object with an optional custom style that may have a border, which in turn has an optional custom color. To check the existence of the custom border color, instead of

```
if circle.style != nil && circle.style.border != nil && circle.
    style.border.color != nil
```

it is possible to write

```
if circle.style?.border?.color != nil
```

If any link in this chain is nil, the whole chain fails gracefully and returns nil.

Another concept in the context of optionals are failable initializers (known as constructors in other languages). When explicitly defining an initializer as failable appending a question mark (init?), it's return type is optional variant of the type it should initialize. That can be useful for handling invalid parameter values or other initialization problems.

Optionals are widely used in Swift's iOS APIs and their syntax one of the first things noticed when looking to Swift sources as a novice. In my opinion, the usage of optionals results in being more aware of the presence or absence of values and coding more prudently. Of course, optionals can only add real value if not blindly unwrapped just to silence the compiler errors.

2.5.3.3 Getter and Setter

Swift has a well designed flexible property system, with a concise getter and setter syntax thanks to built-in language support.

It addresses the two main problems, encapsulation and computing bound to accessing or mutating a property, classical getter and setter methods solve, without the overhead of writing separate accessing and mutating methods for an object's properties.

Encapsulation can be archived by restricting write access to a stored property with the `private(set)` keyword.

```
private(set) var age = 55
```

This restricts write access to the current source file in Swift⁴.

In case some computation is needed to update dependent values, Swift offers the `willSet` and `didSet` observers that are executed right before and after a stored property is mutated.

```
var age = 55 {  
    didSet {  
    }  
    willSet {  
    }  
}
```

If a property is purely computed, it can be defined in a similar way.

```
var name:String = {  
    get {  
    }  
    set(newName) {  
    }  
}
```

The setter is optional. Nothing changes for the calls for accessing and mutating that property: `obj.name = "newName"` executes the set block, `obj.name` the get block.

⁴It is still possible to restrict the access to instances of the class by using a separate file for the class definition.

2.5.3.4 Exception Handling

The exception concept is completely missing in Swift. Unfortunately, there is no official explanation from Swift's designers for this decision.

Using Swift's tuples it is possible to return multiple return values, for example an optional return value paired with an optional error object (cf. [?]):

```
func doSomething(param: String) -> (return: String?, error:
    NSError?)
```

Another option to consider is creating an enumeration with a success and a error member.

```
enum Result {
    case Success(res: Int)
    case Error(msg: String)
}

func next() -> Result {
    return Result.Success(res: 3)
}

switch next() {
case .Error(let msg):
    println("Something went wrong: " + msg)
case .Success(let res):
    println("OK: " + String(res))
}
```

These alternatives misses the exceptions ability to retract some levels of the call stack and retry without explicitly passing an error object up the call chain.

2.5.3.5 Summary

Swift is currently the most modern programming language available for a mobile platform. It is a great step forward compared with it's predecessor Objective C. Although it's expressive and concise syntax and it's Playground and REPL (Read-Eval-Print-Loop) feature, Swift remains a compiled language. Like Objective C, it is compiled into machine code by the LLVM compiler, which proved to be very fast.

2.6 iOS and Cocoa Touch

iOS Cocoa Touch Framework Developing with XCode

Appendix A

Appendix Title Here

Write your Appendix content here.

Bibliography

- [1] Robert Scoble and Shel Israel. *Age of Context: Mobile, Sensors, Data and the Future of Privacy*. Patrick Brewster Press, 1st edition, 2013.
- [2] Bill Schilit, Norman Adams, and Roy Want. Context-aware computing applications. In *In Proceedings of the Workshop on Mobile Computing Systems and Applications*, pages 85–90. IEEE Computer Society, 1994.
- [3] Gregory D. Abowd and Anind K. Dey. Towards a better understanding of context and context-awareness. In *Proceedings of the 1st International Symposium on Hand-held and Ubiquitous Computing*, HUC '99, pages 304–307, London, UK, UK, 1999. Springer-Verlag. ISBN 3-540-66550-1. URL <http://dl.acm.org/citation.cfm?id=647985.743843>.
- [4] Ferreira Paulo and Alves Pedro. *Distributed Context-Aware Systems*. Springer-Verlag, 2014.
- [5] Mark Weiser. The computer for the 21st century. *Scientific American*, 265(3):66–75, September 1991.
- [6] *The Swift Programming Language*. Swift Programming Series. Apple Inc., 1st edition, 2014.
- [7] Jan Macacek. Type-safe dsl.
- [8] Martin Odersky, Lex Spoon, and Bill Venners. *Programming in Scala: A Comprehensive Step-by-step Guide*. Artima Incorporation, USA, 2nd edition, 2010. ISBN 0981531601, 9780981531601.