



AJAX and Data Access

Marco Torchiano

Version 2.0.0 - May 2020

License

This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

- You are free to:
 - **Share** - copy and redistribute the material in any medium or format
 - **Adapt** - remix, transform, and build upon the materialfor any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.
- Under the following terms:
 - **Attribution** - You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
 - **ShareAlike** - If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

AJAX

AJAX

Asynchronous Javascript And XML

A technique for creating fast and dynamic web pages.

Allows javascript code to:

- retrieve data from a server (after the page has loaded),
- send data to a server (in background),
- update a web page contents without reloading it.

AJAX steps

- Javascript generate a request to a server
 - an `XMLHttpRequest` object is used to build and send the request
- When the response from the server arrives
 - a (call-back) operation is performed on the data

Note 1: the content has *NOT* necessarily to be XML.

Note 2: the request can contain data and the reply be just a confirmation.

5

`XMLHttpRequest` Object

Issuing requests:

- Create the object: `new XMLHttpRequest()`
- Prepare the request: `open(method, url, async)`
 - *method* is either `"GET"` or `"POST"`
 - *url* is the url of the resource
 - *async* is a boolean
- Send the request: `send(data)`
 - *data* is optional, used for `POST` request

6

XMLHttpRequest Object


Retrieving responses:

- `onreadystatechange` callback function invoked on any state change event
- `readyState` current state of the request
- `status` final HTTP response code (e.g. `200` for OK)
- `responseText` response body (when *done*)
- `responseXml` response as XML document
 - (traversable with a DOM)

7

State diagram for XMLHttpRequest

The current state is available through `readyState`:



The values are defined as constants in `XMLHttpRequest`

8

Response status

- It is the HTTP response status code
 - Defined after `readyState===XMLHttpRequest.DONE`
- Success outcomes of the request are:
 - `200`: resource retrieved
 - `304`: resource [not modified](#)
 - response to a conditional request (e.g. get if not changed)

```
okStatus = s => [200,304].indexOf(s) >= 0;
```

9

Synchronous request

The `send()` method blocks until a response is received.

```
function loadSync(url, success){
  var xhr = new XMLHttpRequest();
  xhr.open("GET", url, false); // synch
  try{
    xhr.send();
    if(okStatus(xhr.status)) {
      success(xhr.responseText); // call back
    }
  }catch(err){
    console.error("Request failed: " + url);
  }
}
```

10

Synchronous request usage

```
var DS= // prefix for data files
"http://softeng.polito.it/courses/VIQ/datasets/";
loadSync(DS+"GoT.txt",function(txt){
    console.log("Got it!:\n" + txt)
})
console.log("--- Completed! ---")
```

↩

```
Got it!:
Jon Snow
Tyrion Lannister
Daenerys Targaryen
Arya Stark
--- Completed! ---
```

11

Asynchronous request (AJAX)

```
function loadASync(url,success){
    var xhr = new XMLHttpRequest();
    xhr.open("GET",url,true);
    xhr.onreadystatechange = function(){
        if(this.readyState == XMLHttpRequest.DONE)
            if(okStatus(this.status)){
                success(this.responseText);
            }else{
                console.error("Request failed : " + url);
            }
    };
    xhr.send();
}
```

12

AJAX sample

```
loadAsync(DS+"GoT.txt",function(txt){  
    var res = document.createElement("pre");  
    res.appendChild(document.createTextNode(txt));  
    document.getElementById("ajax-sample").  
        appendChild(res)  
});
```

```
Jon Snow  
Tyrion Lannister  
Daenerys Targaryen  
Arya Stark
```

13

Load Dynamic Content

Dynamic content loading requires:

- a data file with the content
 - e.g. `GoT.csv`
- a placeholder where to show content
 - e.g. element inside a page
- a function to generate content
 - e.g. generate a `<table>` from a table object

14

Generating content (innerHTML)

```
function tableToHtmlElement(data){
  var res = document.createElement("table")
  var html = "<tr>";
  for(h in data[0]){
    if(data[0].hasOwnProperty(h)) html+="<th>"+h;
  }
  html+="</tr>";
  for(var i=0; i<data.length; ++i){
    html+="<tr>";
    for(f in data[i]) html+="<td>"+data[i][f];
    html+="</tr>";
  }
  res.innerHTML = html;
  return res;
}
```

15

Generating content (Full DOM)

```
function tableToHtmlElement1(data){
  let res = document.createElement("table")
  let row = document.createElement("tr");
  for(h in data[0]){
    let c = document.createElement("th");
    c.appendChild(document.createTextNode(h));
    row.appendChild(c);
  }
  res.appendChild(row);
  for(var i=0; i<data.length; ++i){
    row = document.createElement("tr");
    for(f in data[i]){
      let c = document.createElement("td");
      c.appendChild(document.createTextNode(data[i][f]));
      row.appendChild(c);
    }
    res.appendChild(row);
  }
  return res;
}
```

16

CSV load sample

```
loadASync(DS+"GoT.csv",function(data){
  var tab = tableToHtmlElement(csvParse(data));
  document.getElementById("csv-load-sample").
    appendChild(tab)
});
```

ID	Surname	Name
4321	Snow	Jon
5765	Lannister	Tyrion
4663	Targaryen	Daenerys
9896	Stark	Arya

17

JSON load sample

```
loadASync(DS+"GoT.json",function(txt){
  let data = JSON.parse(txt);
  let tab = tableToHtmlElement(data);
  document.getElementById("json-load-sample").
    appendChild( tab );
});
```

ID	Surname	Name
4321	Snow	Jon
5765	Lannister	Tyrion
4663	Targaryen	Daenerys
9896	Stark	Arya

18

Same-Origin Policy

Same-Origin Policy

Browsers restrict a page in using resources from the *same origin* only , i.e. same: protocol, host, and port.

Cross-origin resources are typically:

- allowed for *write* operations (e.g. link open)
- allowed for *embedding* operations (e.g. images, scripts)
- **NOT** allowed for *read* operations, i.e. when a script attempts to read properties of the resource

SOP limitation is adopted to avoid vulnerabilities, e.g. Cross-Site Request Forgery

Relaxing Same-Origin Policy

- Setting `document.domain` to a common domain
 - works for different frames, not for XHR requests
- Using the Cross-Origin Resource Sharing standard
- Using the JSONP standard

21

Cross-Origin Resource Sharing

CORS allows a foreign CO server to enable sharing

- Client sends a `Origin` header specifying the requester origin
- CO Server returns a `Access-Control-Allow-Origin` header that specifies which origins are allowed
 - e.g. `*` for unlimited sharing
 - In *Apache* a the `.htaccess` file should contain a line like: `Header set Access-Control-Allow-Origin "*"`

22

JSONP

- Client
 - includes a `<script>` element
 - whose `src` attribute points to the JSON content
 - adds a `?callback=process` at the end of the URL
- Server wraps the JSON content with `process(` and `)`
- Client evaluates the returned code as Javascript, so
 - invokes the `process` function
 - the function receive the JSON as argument

This works because scripts are not restricted by Same-Origin Policy

23

Load and process JSONP

Inject a `<script>` element and an handler function that are later removed.

```
function loadJSONP(url, process){
  var s = document.createElement("script");
  var cbname = "_cbf"+Math.round(Math.random()*1e9);
  window[cbname]=function(obj){
    process(obj);
    document.body.removeChild(s);
    delete window[cbname] ;
  };
  s.src = url + "?callback=" + cbname;
  document.body.appendChild(s);
}
```

24

JSONP load sample

```
loadJSONP(DS+"GoT.php",function(data){
    var tab = tableToHtmlElement(data)
    document.getElementById("jsonp-load-sample").
        appendChild( tab );
});
```

ID	Surname	Name
4321	Snow	Jon
5765	Lannister	Tyrion
4663	Targaryen	Daenerys
9896	Stark	Arya

25

JSON server-side script (PHP)

```
<?php header('content-type: application/json;' .
    'charset=utf-8');

$myfile = fopen("GoT.json", "r") or
    die("Unable to open file!");
$data = fread($myfile,filesize("GoT.json"));

echo $_GET['callback'] . '(' . $data . ')';
```

26

References

- W3C. XMLHttpRequest Level 1. <http://www.w3.org/TR/XMLHttpRequest/>
- W3Schools. AJAX Tutorial. <http://www.w3schools.com/ajax/default.asp>
- Jesse Ruderman (MDN). Same-origin Policy. https://developer.mozilla.org/en-US/docs/Web/Security/Same-origin_policy
- MDN, HTTP access control (CORS). https://developer.mozilla.org/en-US/docs/HTTP/Access_control_CORS
- Wikipedia. JSONP. <https://en.wikipedia.org/wiki/JSONP>
- B.Ippolito. Remote JSON - JSONP. <https://bob.ippoli.to/archives/2005/12/05/remote-json-jsonp/>
- OWASP. Cross-Site Request Forgery. https://www.owasp.org/index.php/Cross-Site_Request_Forgery_%28CSRF%29