



CSS

Marco Torchiano

Version 2.3.1 - April 2020

License

This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

- You are free to:
 - Share - copy and redistribute the material in any medium or format
 - Adapt - remix, transform, and build upon the material

for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

- Under the following terms:
 - **Attribution** - You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
 - **ShareAlike** - If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

Basics

CSS

Cascading Style Sheets (CSS) is a language for specifying how documents are presented

CSS enables the separation of:

- Contents (HTML)
- Formatting / presentation (CSS)

Advantages

- Avoid duplication:
 - formatting is written once and applied uniformly to the all pages in the site
- Easier maintenance
 - there is one source of truth for the presentation: any change to the CSS style automatically propagates to all the linking documents
- Reuse
 - same content can be shown with different styles

5

CSS working

CSS defines a set of rules.

Each rule is made up of:

- **selector**: identifies which HTML elements are targeted
- **declaration block**, contains several *declarations* each consisting of
 - **property**: specifies the feature (e.g. color, size, font, etc.) of the styled HTML elements
 - **value**: defines the value to control the appearance of the feature for the selected element(s)

6

CSS Rules

```
selector {  
  property1: value1;  
  property2: value2;  
  /* ... */ }
```

- the *selector* selects the elements the rule applies to,
- each declaration define the style:
 - the *properties* are presentation features,
 - the *values* are the options/values of the features.

7

Basic Selectors

- **Element** type selectors,
 - e.g. `p`
selects all elements of the given type
- **Class** selectors,
 - e.g. `.example`
selects all elements with the given class
- **ID** selectors,
 - e.g. `#warning`
selects the individual elements with the given id

8

IDs and Classes

- Classes are defined by the `class` attribute

A class can be applied to multiple elements and any element can belong to several classes.

```
<p class="quote high">
```

- IDs are defined by the `id` attribute of an element

They are meant to be unique and single.

```
<p id="warning">
```

9

Selector Composition

- **alternatives:** `,` separate alternative selectors for which the rule applies, e.g.
 - `p, li` applies to both `<p>` and `` elements
- **combination:** sequence of collated selectors define the joint conditions for applying the rule, e.g.
 - `p.warning` applies to all `<p>` elements with class `warning`
 - `p#quote` applies to the `<p>` element with id `example`

10

Application of CSS to HTML

- **Embedded**
 - using the html `style` element
- **External**
 - using a html `link` element referring to an external style sheet
- **Inline**
 - using the `style` attribute of html elements
 - contains only the declarations
 - the selector is implied (the current element)

11

Embedded style with id

```
<style type="text/css">
  p#warning {
    color:darkgreen;
    font-size:200%;
    font-family: futura;
  }
</style>
<p>Hitchhiker's Guide to the Galaxy</p>
<p id="warning">DON'T PANIC</p>
```

Hitchhiker's Guide to the Galaxy

DON'T PANIC

12

Embedded style with class

```
<style type="text/css">
  p.l { color:navy; }
  p.high { font-size:150%; }</style>
<p class="l">DrF: Abby someone. Abby who?</p>
<p class="l">I: Abby... Normal.</p>
<p class="l high">DrF: Abby Normal?</p>
<p class="l">I: I'm almost sure that was the name.</p>
```

DrF: Abby someone. Abby who?

I: Abby... Normal.

DrF: Abby Normal?

I: I'm almost sure that was the name.

13

External style

The `head` element can include a `link` element that refers to a separate resource:

```
<link rel="stylesheet" href="styles.css" >
```

External styles can be imported from an embedded style

```
<style type="text/css">
  @import url("styles.css");
  /* ... */
</style>
```

14

Inline style

```
<p style="color:dodgerblue;">
I've seen things you people wouldn't believe.
</p>
<p>
Attack ships <em style="background-color:red;">
on fire </em> off the shoulder of Orion.
</p>
```

I've seen things you people wouldn't believe.

Attack ships **on fire** off the shoulder of Orion.

Style Attributes

Color

- `color` defines the text color
- `background-color` or just `background` defines the background color of the element
 - Note: block elements (e.g. `<p>`) usually span the full width of the page.

Color can be define as:

- name
- rgb
- hsl

17

Background Color

```
<p style="background:green;">
Paragraph with bg color</p>
<p>And another with
<b style="background:red">bold
element</b>.</p>
```

Paragraph with bg color

And another with **bold element**.

18

Color Names

- Name
 - CSS has a set of predefined names,
see: <https://www.w3.org/TR/css-color-3/#svg-color>
 - The basic standard names supported are:

aqua	black	blue	fuchsia
gray	green	lime	maroon
navy	olive	purple	red
silver	teal	white	yellow

19

Color RGB

- Levels of **R**ed **G**reen and **B**lue
can be specified as
 - `rgb(0,0,0)` with each number (between 0 and 255) indicating the R, G, and B intensity
`rgb(255,0,0)` `rgb(0,255,0)` `rgb(0,0,255)`
 - hex notation `#000000`, where each pair of digits represents the value of one component
`#ff0000` `#00ff00` `#0000ff`

20

Color HSL

- Levels of **H**ue, **S**aturation, and **L**ightness
 - hue is a degree on the color wheel from 0 to 360: 0 is red, 120 is green, 240 is blue.
 - saturation is a percentage where 0% is a gray and 100% is fully saturated color
 - lightness is a percentage where 0% is black and 100% is white

can be specified as `hsl(0,0%,0%)`

`hsl(0,100%,50%)`

`hsl(120,100%,50%)`

`hsl(240,100%,50%)`

21

Color wheel




Image cc-by-sa by [jacobolus](#)

22


Transparency

- Both RGB, and HSL can have an additional parameter, *alpha*; a number between 0.0 (fully transparent) and 1.0 (fully opaque).
 - the functions are `rgba()` and `hsla()`
 - full transparent color is named `transparent`

23

Transparency: example

```
<div style="background-color:rgba(255,0,0,.33);">
  </div>
<div style="background-color:rgba(0,255,0,.33);
  left:100px;"></div>
<div style="background-color:rgba(0,0,255,.33);
  left:50px;top:100px;"></div>
```



24

Border

Defines the border of the element

- `border-width`: width, typically in `px`
- `border-style`: type of the line
 - can be: `none`, `solid`, `dotted`, `dashed`, `double`
- `border-color`: any color
- `border-radius`: radius of the vertex connections

25

Border

A compact form is possible that lists all the elements separated by spaces:

```
border: 2px solid black;
```

is equivalent to:

```
border-width: 2px;  
border-style: solid;  
border-color: black;
```

26

Size Units

Absolute sizes:

- `in`, `cm`, `mm`: represent the corresponding length
- `px`: represents a screen pixel, or *display unit* (1/96 of inch or 0.26 mm @ 71 cm distance)
 - Note: a CSS pixel (px) **is not** a device pixel!
- `pt`: represents a screen point (1/72 of inch)

Relative sizes:

- `%` relative size w.r.t. the parent/container element


27

Units

Unit	Description
<code>em</code>	the computed value of the font-size on the element on which it is used.
<code>ex</code>	the current font's x-height, equal to the height of a lowercase 'x'
<code>ch</code>	the advance of the '0' (zero) glyph in the current font, <code>ch</code> stands for character.
<code>rem</code>	the computed value of the font-size property for the document's root element.

28

Box Model



Box Model

29

Box Model

Border, Margin, and Padding features can be expressed:

- overall: same value applies to all four sides of box
- separately for each side: `top`, `right`, `bottom`, `left`
e.g. `margin-top: 26pt;`

The values in clockwise order from the top:

e.g. `border-width: 1pt 2pt 4pt 8pt;`

Two values meaning top&bottom, left&right

For the border the side is indicated before the feature:

e.g. `border-left-width: 2pt;`

30

Display and Visibility

- `display`:
 - `none` prevents rendering the element,
 - `block` forces line break,
 - `inline` placed in line, size is given by content,
 - `inline-block` allow for width and height and vertical spacing.
- `visibility`:
 - `hidden` not shown though occupies the relative space in the page
 - `visible` can be seen

31

Box Model Example

```
<p>Various <b style=
  "border-width: 2pt      6pt      8pt  16pt;
                    /*top    right bottom left */
  border-color: orange green purple gray;
  border-style: dotted solid;
  padding: 0px 10px 20px 40px;">Text</b>.</p>
<p>And other text...</p>
```




Various Text .

And other text...

32

Box Model Example with Inline-block

```
<p>Various <b style=
"display: inline-block;
border-width: 2pt      6pt      8pt      16pt;
               /*top    right bottom left */
border-color: orange green purple gray;
border-style: dotted solid;
padding: 0px 10px 20px 40px;">Text</b>.</p>
<p>And other text...</p>
```

Various .

And other text...

33

Size

`height` and `width` define the size of the element. Valid values are:

- `auto` : size is computed by the browser,
- absolute size as number with unit,
- a `%` relative to the container element.

`max-width` defines the maximum width, the element is resized when the window is smaller than the specified value.

- `none` means there is no max width

34

Text

- `text-align`: `left`, `right`, `center`, `justify`
- `text-decoration`: `none`, `underline`, `overline`, `line-through`
- `text-transform`: `uppercase`, `lowercase`, `capitalize`
- `text-indent`: `length`
- `line-height`: `normal`, `number`, `length`, `%`

35

Font

- `font-family`: `serif`, `sans-serif`, or font name, e.g. "Times New Roman"
- `font-style`: `normal`, `italic`, `oblique`
- `font-variant`: `normal`, `small-caps`
- `font-weight`: `normal`, `bold`, `bolder`, `lighter`, `number` (400 is normal, 700 is bold)
- `font-size`: `medium`, `xx-small`, `x-small`, `small`, `large`, `x-large`, `xx-large`, `smaller`, `larger`, `length`, `%`

36

Lists

- `list-style-type`
 - unordered ``: `disc`, `circle`, `square`, `none`
 - ordered ``: `decimal`, `lower-alpha`, `lower-roman`, ...
- `list-style-position`
 - `outside` (default) outside the `li` element
 - `inside` inside the `li` element, takes space
- `list-style-image`: specifies an image with `url('image.gif')`

37

Example list

```
<ol style="list-style-type: upper-roman;  
        padding-left: 1em;">  
<li>1st</li> <li>2nd</li> <li>3rd</li>  
<li style="list-style-position: inside;">4th</li>  
</ol>
```

- I. 1st
- II. 2nd
- III. 3rd
- IV. 4th

38

Selectors

Selector combination and relationship

Selector	Selects
$A \ E$	Any E element that is a <i>descendant</i> of an A element
$A > E$	Any E element that is a <i>child</i> of an A element
$B + E$	Any E element that is the <i>next sibling</i> of a B element
$B \sim E$	Any E element that is <i>any sibling</i> of a B element

Example selectors

```
<style> section.e { color:darkorange; }
          section .e { color: purple; }
          section > .e { border: 2pt solid; }
</style>
<section class='e'>Section with class 'e'</section>
<section><p><em class="e">Em w/class 'e' descendant
                        of a section</em></p>
<p class='e'>P w/class 'e' child of a section</p>
</section>
```

Section with class 'e'

Em w/class 'e' descendant of a section

P w/class 'e' child of a section

41

Childrens

Selector	Selects
<code>E:first-child</code>	Any <code>E</code> element that is the first child of its parent
<code>E:last-child</code>	Any <code>E</code> element that is the last child of its parent
<code>E:nth-child(n)</code>	Any <code>E</code> element that is the n^{th} child of its parent (n can be a number, <code>odd</code> , <code>even</code> , or any expression, e.g. <code>2n+1</code>)
<code>E:only-child</code>	Any <code>E</code> element that is the only child of its parent

42

Example selectors

```
<style>
.c :first-child { border: 1pt solid;}
.c :nth-child(odd){ color:darkorange; }
.c :nth-child(3n) { background-color: tan; }
.c :last-child { border: 1pt dashed;}
</style>
<p class="c">
<b>Sunday</b>, <b>Monday</b>, <b>Tuesday</b>,
<b>Wednesday</b>, <b>Thursday</b>, <b>Friday</b>,
<b>Saturday</b>
</p>
```

Sunday, Monday, Tuesday, Wednesday, Thursday, Friday, Saturday

43

Pseudo classes

Selector	Selects
<code>:link</code>	Normal state of a link
<code>:visited</code>	Links that have already been visited
<code>:active</code>	Links that are being clicked
<code>:hover</code>	Elements (e.g. links but not only) that are hovered on

44

Example selectors

```
<style> .p :link { color: orange;}
        .p :visited{ color: gray; }
        .p :hover { background-color: yellow;}
</style>
<p class="p">
There are <a href="http://www.polito.it">visited
links</a>, <a href="exist.not">non visited links
</a>, and <em>non links</em> children</p>
<p class="p">Text is not a child but
<fake>fake is</fake>.</p>
```

There are visited links, non visited links, and *non links* children
Text is not a child but fake is.

45

Attribute selectors

Selector	Selects
<code>E[attr]</code>	Any <code>E</code> with an attribute <code>attr</code>
<code>E[attr="val"]</code>	Any <code>E</code> with an attribute <code>attr</code> having a value <code>"val"</code>
<code>E[attr^="beg"]</code>	Any <code>E</code> with an attribute <code>attr</code> having a value starting with <code>"beg"</code>
<code>E[attr\$="end"]</code>	Any <code>E</code> with an attribute <code>attr</code> having a value ending with <code>"end"</code>
<code>E[attr*="sub"]</code>	Any <code>E</code> with an attribute <code>attr</code> having a value containing <code>"sub"</code>

46

Cascade

Sources

CSS declaration for style attributes may origin from different sources:

- User-agent stylesheets
 - defined in the browser, provide default styles
- Author stylesheets
 - defined by web developers
- User stylesheets
 - might be defined by the user to customize user experience

Specificity

Specificity is a priority assigned to rules, according to the following order:

1. `style` attribute of element
2. `#id` selector
3. attribute selector (including `class`)
4. element name selector

49

Cascade

The cascading algorithm determines how to find the value to apply for each property for each document element.

Rules are ordered by:

- `!important` specifier
- source (user,author,user-agent)
- specificity
- order of appearance (last declaration first)

50

Advanced Attributes

Tables

- borders can be set for `table`, `th`, `td` or a subset of them
 - `border-collapse`: if `collapse` merges adjacent borders
- `height` and `width` define the size of the table

Example Tables

```
<style>
.extab tr{ background-color: lime;}
.extab tr:nth-child(odd){
    background-color: yellow;}</style>
<table class="extab">
  <tr><td>Daenerys</td><td>Targaryen</td></tr>
  <tr><td>Jon</td><td>Snow</td></tr>
  <tr><td>Tyrion</td><td>Lannister</td></tr>
</table>
```

Daenerys	Targaryen
Jon	Snow
Tyrion	Lannister

53

Floating

Elements can float

- `float: none, left, right`
- `clear: none, left, right, both`

On which side of the element other text is *not* allowed to wrap

Note: a floating element is not used to compute the container size, so it can *overflow* the container.

- `overflow: auto` adapts the container size including floating elements

54

Example Float

```
<section style="border:solid purple;">
<p style="width:30%;float:left;border:dashed gray">
There must be some kind of way outta here<br>
said the joker to the thief</p>
<p style="border:dashed orange;">
There's too much confusion<br>
I can't get no relief.</p></section>
```

There must be some kind of way outta here	There's too much confusion I can't get no relief.
said the joker to the thief	

55

Example Float Overflow

```
<section style="border:solid purple;overflow:auto">
<p style="width:30%;float:left;border:dashed gray">
There must be some kind of way outta here<br>
said the joker to the thief</p>
<p style="border:dashed orange;">
There's too much confusion<br>
I can't get no relief.</p></section>
```

There must be some kind of way outta here	There's too much confusion I can't get no relief.
said the joker to the thief	

56

Position

- `position` defines the positioning strategy
 - `static`: follow the page flow
 - `relative`: placed at offset from normal position
 - `fixed`: placed at offset w.r.t. viewport
 - `absolute`: placed at offset w.r.t. position ancestor
 - `sticky`: like *relative*, switch to *fixed* when reaching margin
- the actual offset is specified using `top` `bottom` `left` `right`

57

Example: header (css)

```
<style>
.myheader {
  position: absolute;
  top: 0px;
  left: 0; right: 0; /* full width */
  margin-top: 0pt;
  height: 25pt;
  border: 1pt orange solid;
}
.mybody {
  position: relative;
  padding-top: 25pt;
}
</style>
```

58

Example: header (html)

```
<body class="mybody">
<p>Mon<br>Tue<br>Wed<br>Thu<br>Fri<br>Sat</p>
<p>Jan<br>Feb<br>Mar<br>Apr<br>May<br>Jun</p>
<header class="myheader">Time - PF</header>
</body.>
```

Time - PF

Mon
Tue
Wed
Thu
Fri
Sat

References

Online resources

- MDN - CSS: Cascading Style Sheets
<https://developer.mozilla.org/en-US/docs/Web/CSS>
- W3C CSS home page
<https://www.w3.org/Style/CSS/Overview.en.html>
- W3C CSS Tutorials
<https://docs.webplatform.org/wiki/css/tutorials>
- W3Schools Tutorial on CSS
<http://www.w3schools.com/css/default.asp>