



# DOM

Marco Torchiano

Version 2.4.1 - May 2020

## License

---

This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

- You are free to:
  - Share - copy and redistribute the material in any medium or format
  - Adapt - remix, transform, and build upon the material

for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

- Under the following terms:
  - **Attribution** - You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
  - **ShareAlike** - If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

# Introduction

## DOM


---

### Document Object Model

Set of objects that represent the structure of a document loaded in the browser. Can be used to:

- explore the content of the document
  - e.g. get lists of elements,
- modify the attributes of the elements
  - e.g. class or style,
- change the structure of the document
  - i.e. add and remove elements.

# DOM Example



5

## Type of objects

The DOM is a graph where the (Element) objects are **nodes** and direct containment is represented by **edges**

- **Text** nodes represent the text fragments
- **Comment** nodes represent comments
- **HTMLElement** nodes represent elements
  - There are specific types of nodes  
e.g. **HTMLBodyElement**, **HTMLDivElement**, ...

6

# Retrieve elements

---

- `getElementById()` the element with the given *id*
- `getElementsByTagName()` all the elements with a given tag
- `getElementsByClassName()` all the elements with a given tag
- `childNodes` the elements included in the current one
- `children` as above excluding text and comments

7

# Node lists

---

Multiple nodes are collected in:

- `NodeList` when all nodes are required
  - e.g. through `childNodes`
- `HTMLCollection` for HTML elements only
  - e.g. through `children`

Both object types can be iterated using:

- `length`: number of elements
- `[]` or `item()`: return the element at given index

8

# Node lists

```
var pars = document.getElementsByTagName("p");  
console.log("Found " + pars.length+ " paragraphs");
```

↪ Found 40 paragraphs

```
for(let n of pars[2].childNodes)  
  console.log(n.nodeName + " : " +  
              n.textContent.slice(0,28)+  
              (n.textContent.length>28?"...":""));
```

↪

```
#text : This work is licensed under ...  
A : Creative Commons Attribution...  
#text : .
```

9

# Elements

Special collections inside `document`:

- `documentElement` the root element (i.e. `<html>`)
- `body` returns the `<body>` element
- `head` returns the `<head>` element
- `title` returns the content of `<title>` element
- `forms` returns all `<form>` elements
- `links` returns all `<a>` elements with `href`
- `scripts` returns all `<script>` elements
- `images` returns all `<img>` elements

10

# Create content

---

- `innerHTML` sets the internal HTML of the element

```
var s=document.getElementById("create-content");  
s.innerHTML += "<p>The new content!</p>";
```

- *attribute* access **any** attribute of element
  - `style` accesses the element's style, the individual style attributes can be accessed as sub-properties

```
s.style.color = "navy"; ~ "navy"
```

The new content!

11

## DOM manipulation: creation

---

DOM nodes can be created using `document`:

- `createElement ( type )` creates an element of the given type
- `createTextNode ( content )` creates a text node

Elements and nodes are created as *detached*, they need to be **attached** and placed somewhere in the current DOM graph.

12

# DOM manipulation: placement

---

The created items can be attached and placed with respect to an existing element:

- `appendChild ( node )` appends the node as the last child of the element
- `insertBefore ( node, ref )` appends the node after the `ref` node
- `removeChild ( node )` removes the child node

13

# DOM manipulation: placement

---

- `insertAdjacentHTML ( 'pos', text )` add HTML code w.r.t. element
  - `pos` can be `beforebegin`, `afterend`, `afterbegin`, `beforeend`
  - `text` is HTML code that is parsed and then added
- `insertAdjacentElement ( pos, element )` similar to above but adds an element

14

## appendChild example

```
var t = document.getElementById( 'tgAppend' );  
var n = document.createElement( 'em' );  
n.appendChild( document.createTextNode( ' Hi!' ) );  
t.appendChild(n);
```

```
<p id="tgAppend">Content of paragraph</p>
```

Content of paragraph *Hi!*

15

## insertBefore example

```
var t = document.getElementById( 'tgInsert' );  
var ref = document.getElementById( 'tgRef' );  
var n = document.createTextNode( ' THE ' );  
t.insertBefore( n, ref );
```

```
<p id="tgInsert">Content of  
  <b id="tgRef">paragraph</b></p>
```

Content of THE paragraph

16



# Adjacent HTML example

---

```
var t = document.getElementById("tgAdjacent");
t.insertAdjacentHTML('beforebegin', '<b>BB</b>');
t.insertAdjacentHTML('afterbegin', '<b>AB</b> ');
t.insertAdjacentHTML('beforeend', ' <b>BE</b>');
t.insertAdjacentHTML('afterend', '<b>AE</b>');
```

```
<p id="tgAdjacent" style="background:aqua">Content</p>
```

BB  
AB Content BE  
AE

17

## Events

---

Events are triggered by specific actions performed on the elements of a page.

Events can be handled by means of specific methods called *handlers*:

- elements object expose special properties corresponding to events
- such properties can be assigned to functions that will handle them
  - in javascript e.g. `element.onclick = func`,
  - in html e.g. `<p onclick="func()">`

18

# Events

---

In event handlers `this` refers to the element destination of the event.

```
var a = document.getElementsByTagName("h2")[17]
a.onmouseover=function(){
    this.style.color = "red";
    this.style.fontWeight = "normal";
};
a.onmouseout=function(){
    this.style.color = "black";
    this.style.fontWeight = "bold";
};
```

19

## Common events

---

- `onclick` click on the element
- `onmouseover` mouse moving over the element
- `onmouseout` mouse exiting from element
- `onkeypress` keyboard key pressed
- `onchange` form input element value is changed
- `onload` the object (e.g. the page) has been loaded

The event are triggered for an element and all its containers.

20

# BOM

## Browser Object Model

The main browser object is `window`; it contains the properties:

- `document`
- `location`
- `innerHeight`, `innerWidth`
- `screen`
- `history`

**Note:** all properties of `window` are directly accessible, i.e. `window` is the *global* context.

# Location

---

The `location` property object includes

- `href`: the full URL
- `hostname`, e.g. `softeng.polito.it`
- `protocol`, e.g. `http:`
- `pathname`, e.g. `/courses/VIQ/`
- `search`, e.g. `?par=val`

Can be assigned to navigate to a new URL in the same window/tab.

23

## Window on load event

---

Operations on the DOM must be performed after its structure is complete and stable.

The `onload` event can be used to trigger operations on DOM once stable.

```
window.onload = function(){  
    // place here the code working on DOM  
}
```

24

# Window: methods

---

Main methods:

- `open()` open a URL in a new window/tab
- `alert()` show notification window
- `confirm()` show a dialog to ask a question,
  - returns a boolean
- `prompt()` show a dialog to ask for information,
  - returns the string entered

25

# Window: Timing

---

- `setTimeout(function, milliseconds)`  
Executes a function, after waiting a specified number of milliseconds.
- `setInterval(function, milliseconds)`  
Executes a function repeatedly every given milliseconds.
- `clearInterval( itvlObj )`,  
`clearTimeout( itvlObj )`  
Cancel the scheduled invocation
  - use the handle returned by `set..` function

26

# Animation Example

---

Using an interval to change attributes:

```
(function(){ // using a closure
  var i=0;
  var step=1;
  var h = document.getElementsByTagName("h2")[25];
  setInterval(function(){ // function to be called
    if(i>=255) step=-1;
    if(i<=0) step+=1;
    h.style.color='rgb('+i+', '+i+', '+i+')';
    i+=step;
  },10); // every 10 ms
})();
```

27

## References

---

- W3Schools. JavaScript Tutorial. <http://www.w3schools.com/js/default.asp>
- W3Schools- JavaScript Reference. <http://www.w3schools.com/jsref/default.asp>
- W3C - DOM Parsing. <https://www.w3.org/TR/DOM-Parsing/>
- DOM Examples:
  - On Codepen: <http://codepen.io/mtorchiano/pen/VaEmOm?editors=1010>
- W3Schools. jQuery Tutorial. <https://www.w3schools.com/jquery/default.asp>

28