



HTML 5

Marco Torchiano

Version 1.6.2 - April 2020

License

This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International License](https://creativecommons.org/licenses/by-sa/4.0/).

- You are free to:
 - Share - copy and redistribute the material in any medium or format
 - Adapt - remix, transform, and build upon the material

for any purpose, even commercially.

The licensor cannot revoke these freedoms as long as you follow the license terms.

- Under the following terms:
 - **Attribution** - You must give appropriate credit, provide a link to the license, and indicate if changes were made. You may do so in any reasonable manner, but not in any way that suggests the licensor endorses you or your use.
 - **ShareAlike** - If you remix, transform, or build upon the material, you must distribute your contributions under the same license as the original.

Introduction

What is HTML

HTML (**H**yper**T**ext **M**arkup **L**anguage)

- Is a language used to describe the contents of web documents.
- HTML documents consist of a set of tree-structured elements and text.
- HTML specifies content, separately from presentation (see CSS)

History

1991:

first version of HTML by Tim Berners-Lee

1999:

HTML 4.01 Recommendation

2000:

XHTML, eXtensible HyperText Markup Language,
bridge between HTML and XML

2014:

W3C HTML 5 Candidate Recommendation

2017:

HTML 5.2 - W3C Recommendation

5

Example

```
<!DOCTYPE html>
<html>
  <head lang="en"><meta charset="utf-8">
    <title>Sample page</title>
  </head>
  <body> <!-- this is a comment -->
    <h1>Sample page</h1>
    <p>With a <a href="demo.html">link</a></p>
  </body>
</html>
```

Sample page

Sample page
With a [link](#)

6

HTML Syntax

- Text fragment, e.g. `With a`
- Tag, e.g. `<body>`
Most tags are defined in pairs:
 - opening, e.g. `<p>`
 - closing, e.g. `</p>`
- Elements, i.e. a pair of opening and closing tags with their contents, e.g. `<h1>Sample page</h1>`
- Attributes of elements, e.g. `href="demo.html"`
 - Consist of a pair `name="value"`
 - Defined in the opening tag of an element

7

Structure and elements

Basic Structure

- `!DOCTYPE` declaration
- `html` content, including:
 - `head` block
includes (meta-)information about the document, which are not shown
 - `body` block
the wrapper that surrounds the actual content of the page that is shown in the browser window

9

Example

```
<!DOCTYPE html>
<html>
  <head lang="en">
    <meta charset="utf-8">
    <title>Page title</title>
  </head>
  <body>
    <p>This is the <strong>content</strong>.</p>
  </body>
</html>
```

Page title

This is the **content**.

10

Element types

Block:

high level, define the structure of the document.

A block element is rendered starting on a new line, breaking away from the previous content

Inline:

contained within block elements, typically surround only small portions.

Inline elements rendering do not imply a break in the document flow

11

Head

- Title of the document `<title>` + `</title>`
- Charset `<meta charset="utf-8">`
- Meta information: `<meta name=".." content="..">`, where name can be:
 - `description`
 - `keywords`
 - `author`
- Style `<style type="text/css">` + `</style>`
- Scripts `<script>` + `</script>`

12

Body

- Any element
 - excluding those in `<head>`
 - including `<script>`
- The body contents rendering is shown inside the browser window

13

Text block elements

- Headings `<h1>`, `<h2>`, `<h3>`, ...
- Paragraph `<p>`
- Quotations `<blockquote>`
- Preformatted text `<pre>`

NOTE: Multiple spaces are collapsed into a single space

14

Text block examples

```
<h3>Level 3          heading</h3>
<p>Paragraph, may include several lines...</p>
<pre>
    formatted
    exactly as in source    code
</pre>
```

Level 3 heading

Paragraph, may include several lines...

```
    formatted
    exactly as in source    code
```

15

Text inline elements

- Emphasis `` (and older *italics* `<i>`)
- Strong `` (and older **bold** ``)
- Line break `
`

Note: line breaks in code are ignored: you should use either `<p>` or `
`

16

Text inline examples

Normal code `with emphasis`
or `<i>italics</i>`.

`
`

`strong emphasis` or `bold`

`
`

`<p>And other paragraphs</p>`

Normal code *with emphasis* or *italics*.

strong emphasis or **bold**

And other paragraphs

17

Lists

- Unordered ``
- Ordered ``
- Definition `<dl>`

List items for ordered and unordered list are defined with `` elements.

Definition items consist in a term `<dt>` and a definition `<dd>`

Lists (also of different types) can be nested.

18

Unordered List

```
<ul>
  <li>an item</li>
  <li>another item, and </li>
  <li>yet another item</li>
</ul>
```

- an item
- another item, and
- yet another item

19

Ordered List

```
<ol>
  <li>first item</li>
  <li>second item</li>
  <li>third item</li>
</ol>
```

1. first item
2. second item
3. third item

20

Definition List

```
<dl>
  <dt>List</dt>
  <dd>A sequence of items</dd>
  <dt>Item</dt>
  <dd>An element of a list</dd>
</dl>
```

List

A sequence of items

Item

An element of a list

21

Links

Links are parts of a document pointing to other resources.

- Element `<a>` marks a fragment as a link.

The attributes of the element are:

- `href`: the locator for the resource the link points to
- `title`: additional information shown on *hover*

22

Link example

```
<p>This is a link to PoliTo  
<a href="http://www.polito.it"  
  title="PoliTo" >home</a>.</p>  
<p>...and this is a link to  
  <a href="/VIQ"  
    title="Only works online"  
  >course home page</a>.</p>
```

This is a link to PoliTo [home](http://www.polito.it).
...and this is a link to [course home page](/VIQ).

23

URL

Uniform Resource Locator

scheme : // host / path ? query # fragment

- Not all components are required
- Different subsets are possible, e.g.:
 - *scheme + host*
 - *scheme + host + path*
 - *host + path*
 - *path* (relative)

24

URL components (1)

- `scheme` defines the protocol to retrieve the resource:
 - can be `http`, `https`, `file`, `ftp`, etc.
- `host` corresponds to a valid internet domain name
 - `localhost` refer to the browser's host
- `path` is mapped to a path on the server file system
 - a folder (e.g. `/VIQ`)
 - a file (e.g. `/VIQ/labs17/Lab2.html`)

25

URL components (2)

- `query` is used to pass parameters to an application server using the HTTP `GET` method
 - typically mapped from the fields of a form
 - e.g. `key1=value1&key2=value2`
- `fragment` refers to positions of elements inside a page
 - elements are identified by means of a unique `id` attribute

26

Fragment links

A link to a fragment needs a target fragment identified by means of an `id` parameter:

```
<section id="info-section"> ... </section>
```

A link can refer to that fragment using the id preceded by the `#` character:

```
<a href="#info-section">link to Info section</a>
```

27

Images

Images can be inserted using a `` element.

- `src` specifies the location of the image as a URL
- `title` provides a tooltip
- `width` and `height` define the size of the image if defined page rendering is faster

Note: images (``) are *inline* elements!

- `<figure>` is a block-element intended to contain images
- `<figcaption>` element defines the caption

28

Example image

```
This is an image .
<figure><figcaption>Example image</figcaption>

</figure>
```

This is an image .

Example image



- The actual rendering depends on style.

29

Structural elements (HTML 4)

- Headers: `<h1>` - `<h6>`
- Divs: `<div>` block container
Used to add blocks in the page with special formatting
- Spans: `` inline container
Used to apply special formatting to a span of text

30

Sectioning elements (HTML5)

- `<article>`: a complete, or self-contained, composition in a document
- `<section>`: a generic section of a document, typically with a heading.
- `<nav>`: a section with navigation links
- `<aside>`: content that is tangentially related to the content around
- `<h1>` - `<h6>`: a section heading
- `<header>`: a group of introductory or navigational aids
- `<footer>`: a footer for its nearest ancestor

31

Tables

Tables arrange elements in rows and columns.

The element `<table>` includes

- Row elements, `<tr>` that include
 - Cells elements `<td>` that include
 - the cell content (i.e. any html)

The elements are described *by row*

- Header cells are represented by element `<th>`
- Table caption is defined in a `<caption>` element

32

Table example

```
<table>
<caption>Departments staff size</caption>
<tr><th>Department</th><th>Staff</th></tr>
<tr><td>Computer science</td><td>68</td></tr>
<tr><td>Chemistry</td><td>120</td></tr>
</table>
```

Departments staff size	
Department	Staff
Computer science	68
Chemistry	120

Note: the exact rendering depends on the style.

Characters

Entities

- Entities are used to represent special characters and characters not present or *typeable* with a keyboard
 - Special characters (e.g. `<`, `>`, and `&`) cannot appear directly inside an html document
- Entities:
 - start with `&`
 - terminate with `;`
 - in between there is a name or a code value

35

Entities examples

- Named entities:
 - `<` : `<`
 - `>` : `>`
 - `&` : `&`
- Code entities
 - `©` : ©

Note: the actual character depends on the *charset* of the document.

36

Character set and encoding

- A character set is the a set of characters
 - e.g., ASCII defines 127 character (letters + numbers + symbols)
- The character set encoding is a mapping from the character set to a sequence of bytes
 - e.g., ASCII letter `I` corresponds to 0x41 (65 decimal)
- Encoding is used by the browser to convert the stream of bytes into characters

37

Unicode

Standard that assigns a unique code to every character in any language

- Core specification gives the general principles
- Code charts show representative glyphs for all the Unicode characters.
- Annexes supply detailed normative information
- Character Database normative and informative data for implementers

38

Characters, Glyphs

- **Character**: the abstract concept

e.g. LATIN SMALL LETTER I

- **Glyph**: the graphical representation of a character

e.g. 

Font: a collection of glyphs

39

Codepoints

- **Codepoint**: the numeric representation of a character

Included in the range 0 to $10FFFF_{16}$ (23 bits)

Represented with U+ followed by the hexadecimal code

e.g. U+0069 for i (LATIN SMALL LETTER I)

e.g. U+16B5 for ƿ (RUNIC LETTER G)

e.g. U+0913 for ओ (DEVANAGARI LETTER O)

40

Encoding

Mapping from a byte sequence to a code point.

- UTF-32: fixed width, high memory occupation (4 bytes)
e.g., 'l', `U+0069` is represented as `0x00000069`
- UTF-16: variable width, represents
 - codepoints from `U+0` to `U+ffff` on 16 bits (2 bytes)
 - codepoints from `U+10000` to `U+10ffff` on 32 bits (4 bytes)

e.g., 'è', `U+00E8` is represented as `0x00E8`

41

Encoding UTF-8

- UTF-8: variable width,
 - codepoints `U+00` to `U+7f` are mapped directly to bytes, i.e. *ASCII transparent*
 - most non-ideographyc codepoints are represented by 2 bytes
- e.g. 'è', `U+00E8` is mapped to `0xC3` + `0xA8`.

42

Encoding mismatch

- A mismatch occurs when the encoding used to convert a byte sequence to characters is not the same used to perform the coding.
- When character 'è' (U+00E8) is encoded using UTF-8 it results into two bytes: 0xC3 + 0xA8. ISO-8859-1 encoding interprets the above two bytes as the characters 'Ã'.
- Viceversa, 'è' is encoded by ISO-8859-1 as 0xE8 which is an invalid character in UTF-8 encoding (usually represented as ?)

43

Forms

Forms

Forms are html structures that allow the user to enter information mean to be sent to the web server

- The form definition is enclosed in a `<form>` block element
- The `<form>` element has two attributes:
 - `method` specifies how data is transmitted
 - either `GET` or `POST`
 - `action` specifies the location (URL) that will receive the data

45

Methods: `GET` vs. `POST`

Differ in the way they encode the from values

- `GET` encodes them as a query portion in the URL

```
GET /api/get.jsp?USER=John&PASS=53cr3t HTTP/1.0
```

- `POST` encodes them as additional elements in the HTTP Request

```
POST /api/post.jsp HTTP/1.0
```

```
USER=John  
PASS=53cr3t
```

46

Form items

- Items in the form are represented by

- `<input>`
- `<textarea>`
- `<select>`

The elements have two main attributes:

- `name` name of the data item
- `value` value of the variable (initial or predefined for e.g. a button or hidden element)

47

`<Input>` element

- Attribute `type` defines the type of input:
 - `text`: text field
 - `submit`: button
 - `checkbox`: a checkbox
 - `radio`: a radio button (several with the same name)
 - `file`: file selection
 - `password`: text field with masked characters
 - `hidden`: invisible element

48

Example types

Text:

Radio: Yes: ☐

No: ☐

Checks: Gift: ☐

Card: ☐

Number:

Password:

Range:

File: Ne....

49

Other inputs

- **<textarea>**
 - attributes **cols** and **rows**
 - can enclose the initial value of the text
- **<select>** encloses a list of elements
 - **<option>** elements define the items of the list
 - the label is enclosed in the element
 - attribute **value** defines the relative value

50

Text area example

```
<textarea name="description" cols="45" rows="3">
```

A long time ago in a galaxy far,
far away....

It is a period of civil war.
Rebel spaceships, striking
from a hidden base, have won
their first victory against
the evil Galactic Empire.</textarea>

A long time ago in a galaxy far,
far away....

51

Select example

```
<select name="lecture">
<option value="L1">Introduction </option>
<option value="L2">Data Visualization</option>
<option value="L3">Measurement</option>
<option value="L4">Descriptive Stats</option>
<option value="L5">Perception</option>
</select>
```

Introduction



52

Labels and fieldsets

For accessibility define labels explicitly

- `<label>` defines elements
 - `for` refers to an input via its `id`
- `<fieldset>` groups related inputs
 - element `<legend>` encloses a name for the fieldset

53

Labels and fieldsets

```
<fieldset><legend>Course features</legend>
<label for="course">Course name:</label>
<input type="text" name="course" id="course"><br>
<label for="cfu">Credits:</label>
<input type="number" name="cfu" id="cfu"
      min="3" max="24">
</fieldset>
```

Course features

Course name:

Credits:

54

Terminology

Mime type

- Multipurpose Internet Mail Extensions

Specify the nature of the data in the body of a MIME entity, by giving media type and subtype identifiers

[RFC2046](#)

- Encoded using the format:

top-level / subtype ; param = x value

Top-level mime types

- `text` textual information
- `image` image data (binary)
- `audio` audio data (binary)
- `video` video data (binary)
- `application` some kind of data interpretable by an application

All mime types must be registered with the [IANA](#).

57

Mime types catalog

- `text/plain` typically require a *charset* parameter:
`Content-type: text/plain; charset=iso-8859-1`
- `text/html`

Common image types:

- `image/jpeg`
- `image/png`
- `image/svg+xml`

General binary content `application/octet-stream`.

58

References

W3C HTML 5.2 Recommendation: <https://www.w3.org/TR/html5/>

WHATWG - Web Hypertext Application Technology Working Group: <https://html.spec.whatwg.org>

W3C: https://docs.webplatform.org/wiki/guides/the_basics_of_html

RFC2046 - MIME - Multipurpose Internet Mail Extensions: <https://tools.ietf.org/html/rfc2046>

UNICODE: <http://www.unicode.org/versions/latest/>

MDN Web technology reference: <https://developer.mozilla.org/en-US/docs/Web/Reference>

W3Schools HTML5 Tutorial: <https://www.w3schools.com/html/default.asp>