External Plugin Interfaces for OpenStack QA Projects

Matthew Treinish mtreinish@kortar.org mtreinish on Freenode Andrea Frittoli andrea frittoli@hp.com andreaf on Freenode

Oct 27, 2015

https://github.com/mtreinish/external_plugins

What is OpenStack QA?

► Official Mission Statement:

Develop, maintain, and initiate tools and plans to ensure the upstream stability and quality of OpenStack, and its release readiness at any point during the release cycle.


Current QA Projects

- ► bashate
- ▶ devstack
- ► devstack-plugin-cookiecutter
- ► devstack-vagrant
- ► grenade
- ▶ tempest
- ► tempest-lib
- ► tempest-plugin-cookiecutter
- ▶ stackviz
- ► hacking
- ► eslint-config-openstack
- ▶ os-testr
- openstack-health dashboard


Scaling Limitations

- ▶ Previously QA projects supported all incubated and integrated OpenStack projects
- ► This works with 5 projects
- ► At 10 things are stretched very thinly

OpenStack Project Growth



Tempest Tests per Project



The Big Tent...



QA in the Big Tent

- ► QA projects now directly support base
- ▶ Provide stable plugin interfaces to expand functionality
- ▶ Better fits with the growth in projects


Current Projects QA directly supports in-tree

- ► Keystone
- ► Nova
- ► Glance
- ► Cinder
- ► Neutron
- ► Swift

Devstack Plugins

- Serve different functions
 - ► Enable deploying extra projects in devstack
 - ► Enable using custom drivers in devstack
 - ► Enable deploying extra services on top of a devstack cloud
- ▶ Bits of bash code that live outside of devstack tree
- Called via a strong contract
- Registry of plugins maintained by the community: http://docs.openstack.org/developer/devstack/plugin-registry.html

Projects using Devstack Plugins



 $Source: \ git \ log \ -diff-filter = A \ -format = \%cd \ -date = short \ -1 \ - \ devstack/plugin.sh$

Howto write a Devstack Plugin

- ▶ Devstack plugin cookie-cutter: git://git.openstack.org/openstack-dev/devstack-plugin-cookiecutter
- settings
 - ► Global variables
 - Sourced very early
- ► plugin.sh
 - ► Main plugin file
 - ► Implement hooks for different phases of stack
 - Implement hooks for unstack and clean


Howto write a Devstack Plugin

```
function pre install {{cookiecutter.service}}() {
   # Install OS packages if necessary with "install package ...".
function install {{cookiecutter.service}}() {
   # Install the service.
function configure {{cookiecutter service}}() {
   # Configure the service.
function init {{cookiecutter.service}}() {
   # Initialize and start the service.
function shutdown {{cookiecutter.service}}() {
   # Shut the service down.
function cleanup {{cookiecutter service}}() {
   # Cleanup the service.
```

Tempest Plugins

- ▶ Integrates any external tests into a tempest run
- Unifies configuration between plugin(s) and in-tree
- ► Based on stevedore extension manager
- Automatically discovered when installed
- ► Test code built on top of tempest-lib

Projects using tempest plugins



 $Source: \ git \ blame \ -L \ '/^tempest/, +1' \ setup.cfg \ | \ awk \ '\{print \ \$1\}' \ | \ xargs \ git \ | og \ -1 \ -format=\%cd \ -date=short$

Howto Write a Tempest Plugin

- ► Tempest plugin cookie-cutter: git://git.openstack.org/openstack/tempest-plugin-cookiecutter
- ► Code can be hosted in existing or dedicated git project
- Extend plugins. TempestPlugin from tempest (or tempest-lib)
- ► Implement all abstract methods
 - Test discovery
 - Configuration options
- ► Is everything you need is tempest-lib?
- Setup Cl

Howto Write a Tempest Plugin


Howto Write a Tempest Plugin

```
Oabc abstractmethod
def register opts (self, conf):
    "<sup>III</sup>Method to add additional configuration options to tempest. This
    method will be run for the plugin during the register opts() function
    in tempest config
    :param ConfigOpts conf: The conf object that can be used to register
        additional options on.
    return
Qabc abstractmethod
def get opt lists (self):
    """ Method to get a list of options for sample config generation
    return option list: A list of tuples with the group name and options
                          in that group.
    :rtvpe: list
    return []
```

Grenade Plugins

- ► Enables running upgrades from out of tree
- ► Enables adding additional services to the old devstack
- ► Add additional resource creation and checks during the upgrade

Projects using Grenade Plugins



 $Source: \ git \ log \ -diff-filter = A \ -format = \%cd \ -date = short \ -1 \ - \ devstack/upgrade/upgrade.sh$

Howto Write a Grenade Plugin

- ► upgrade.sh
 - ► The script to run the upgrade after the old has been shutdown
- ▶ shutdown.sh
 - ► The script to shutdown a service
- settings
 - register any devstack plugins
 - register any services for upgrade
- resources.sh
 - Create resources
 - ► Check resource survival across upgrade
 - ► Teardown resource after upgrade
- ► Per Release manual steps
 - Any manual steps to upgrade between releases

Where to get more information

- ► Tempest Plugin Docs: http://docs.openstack.org/developer/tempest/plugin.html
- ► Devstack Plugin Docs: http://docs.openstack.org/developer/devstack/plugins.html
- ► Grenade Plugin Docs: http://docs.openstack.org/developer/grenade/plugins.html
- openstack-dev ML: openstack-dev@lists.openstack.org
- ► #openstack-qa on Freenode

Questions?