

HMS Help — Combined Manual

MT Soft

2026-06-09

Table of Contents

HMS Help

-  What's New
-  Dashboards
-  Clinical
-  Integrations
-  Back Office
-  Coming Soon
- How to use this site

Conventions

MT SOFT

HMS Help

Combined End-User & Administrator Manual

Hospital Management System

Generated 2026-06-09

Source: <https://mtsoft2.github.io/HMS-HELP/>

Repository: github.com/mtsoft2/HMS-HELP

Table of Contents

HMS Help

HMS — Hospital Management System End-user and administrator manual for every module in HMS. Pick a card below to jump in, or use the search box (top right) to find a feature by name.



What's New

- :material-palette-outline: **UI Updates**

Grid R3 spreadsheet-style upgrade, Mini Mode pickers, Patient Avatars on every banner.

[:octicons-arrow-right-24: Open](#)

- :material-tools: **Setup Wizard v2**

New installer + patch flow with full patching history and one-click re-apply.

[:octicons-arrow-right-24: Open](#)

- :material-database-cog-outline: **Maintenance**

Database health dashboard — KPIs, scored checklist with one-click fixes, backups, schedules, and Drive-shareable maintenance log.

[:octicons-arrow-right-24: Open](#)

- :material-chart-box-outline: **Report Server (V2)**

Centralised report runner — browse, run, schedule, export.

[:octicons-arrow-right-24: Open](#)



Dashboards

- :material-hospital-building: **Clinic Dashboard**

Manager's home screen for one outpatient clinic — Overview, Schedule, Census, Billing, Physicians, Inventory, Quality, CRM.

[:octicons-arrow-right-24: Open](#)

- :material-account-heart: **Patient Dashboard**

The patient's lifetime summary — Profile, Clinical, Care Plan, Appointments, Lab, Imaging, History, Documents, Billing, Insurance.

[:octicons-arrow-right-24: Open](#)



Clinical

- :material-calendar-clock: **Scheduler**

Day / Week appointment grid with fingerprint find, drag-and-drop reschedule, conflict detection, bulk move.

[:octicons-arrow-right-24: Open](#)

- :material-stethoscope: **Clinic Reception**

The front desk's one-window workspace — find, book, chart, prescribe, bill in 14 toolbar buttons.

[:octicons-arrow-right-24: Open](#)

- :material-file-image-outline: **Document Manager (DM2)**

Unified viewer + gallery for every file type — images, PDF, Office, DICOM. Annotate, measure, compare.

[:octicons-arrow-right-24: Open](#)

Integrations

- :material-message-text-outline: **Metasoft Communicator**

SMS / WhatsApp / e-mail outbound channel with queue, retries, alerts, full audit log.

[:octicons-arrow-right-24: Open](#)

- :material-shield-check-outline: **NPHIES BridgeProxy**

Saudi NPHIES e-claim submissions, status checks, and pre-authorisations.

[:octicons-arrow-right-24: Open](#)

Back Office

- :material-account-group: **Human Resources**

Full employee lifecycle — recruitment, contracts, leaves, appraisals, documents, end of service.

[:octicons-arrow-right-24: Open](#)

- :material-cash-multiple: **Payroll**

Pay codes, pay runs, registers, pay slips, staff loans.

[:octicons-arrow-right-24: Open](#)

Coming Soon

- :material-clipboard-pulse-outline: **Patient / Clinical**

Visit forms, vitals, allergies, problem list, medications. *Coming soon.*

- :material-pill: **Pharmacy / Inventory**

Stock, dispensing, formulary, expiry tracking. *Coming soon.*

- :material-flask-outline: **Laboratory / Radiology**

Orders, sample tracking, results, imaging studies. *Coming soon.*

How to use this site

- Use the **top navigation tabs** to jump between modules.
- The **left sidebar** lists every page in the current module.
- The **search bar** (top right) searches the entire site.

Conventions

Term	Meaning
Form (FT)	A data-entry window — e.g. the Employee form.
Search pad (ST)	A list / search window — e.g. the Employees list.
Grid (GT)	A child table inside a form — e.g. the Salary history grid inside the Employee form.
Binder (BND)	The full-screen workspace with a toolbar + side menu — e.g. <i>Patient Affairs</i> .
Lookup	A simple reference table (Department, Position, Nationality, ...) administered from the Data Setup menu.

Setup Wizard v2 — New HMS Setup Wizard (Setup.exe)

The **metaSOFT Setup Wizard v2** is the new, redesigned installer that applies HMS patches to a customer database. It replaces the legacy INI-driven installer with a guided five-step flow that validates the database **before** touching it, applies the patch, and reports every script with a per-script status.



What's new in v2

1. Works without Config.ini

The wizard no longer requires `Config.ini` to be present. If a `Config.ini` file is found in the install folder, the wizard auto-loads the previous server / database / authentication values as defaults — so re-installs are still one-click for support staff who already configured the box.

2. SQL Server instance selection

The **Server** field on the Database step is a dropdown of every SQL Server instance discovered on the network. Type a host name to pick something not in the list — named instances (`HOST\SQLEXPRESS`) and IP addresses are both accepted.

3. Authentication method selection

Pick either:

- **Windows Authentication** — uses the logged-in Windows account.
- **SQL Server Authentication** — enter a SQL login and password.

Stored procedures, tables, and trigger creation all use the chosen account.

4. Verify database connection before proceeding

The wizard pings the chosen server + database and lists how many databases were found before letting you click Next. A green *"Connected — N databases found"* badge confirms reach.

If the connection fails, the wizard stays on the Database step with the specific error displayed — no half-applied patch can result.

5. Verify required schema objects

After applying the patch, the wizard inspects `sys.objects` and confirms that **every** expected procedure, function, table, and trigger from the patch is present. The number shown on the Apply screen — e.g. *"947 of 947 expected objects verified"* — is the post-install integrity check.

6. Comprehensive error report

All setup and validation errors — script failures, missing objects, permission denials, version mismatches — are written to a single comprehensive text file alongside the wizard. One file to attach to a support ticket; no log hunting.

7. Patch validation & reporting

The **Patching History** dialog opens from the Welcome step. It shows every patch ever applied to the connected database **from the last cumulative (-CM) patch onwards**, with per-patch:

- **Status** — *Applied, Error, MISSING*.
- **Date** — when the patch ran.
- **Version** — HMS version the patch belongs to.

A red banner at the top counts how many entries are tracked and how many are **MISSING** — e.g. "*112 entries · 55 MISSING*" — instantly showing whether the customer's database is up to date.

The wizard refuses to apply a new patch if a prerequisite cumulative patch is missing, so the patch chain can never get out of order.

→ Continue to **Walkthrough** for the five-step guided run, or **Patching History** for the detail of the patch-status report.

Walkthrough — Applying a Patch

The wizard is **five steps**, shown in the progress bar at the top of every screen: **Welcome** → **Patch** → **Database** → **Apply** → **Finish**.

The lower-left corner shows the wizard version (e.g. *Version 1.1.0*). The lower-right corner has **Cancel** at every step — safe to press until step 4.

Step 1 — Welcome



The welcome card shows the patch the wizard is about to apply:

- **Patch #** — the patch number.
- **Date** — the patch's release date.
- **Size** — the patch payload size.

A reminder line under the card asks you to **close any open HMS clients** before continuing — uncommitted edits on the patient form or any other live screen are at risk during the patch.

The **Patching History** button at the bottom-left opens the patch-status report against the current database — see [Patching History](#).

Click **Get started** to move to Step 2.

Step 2 — Patch information



Two fields:

- **Install folder** — the on-disk HMS installation the patch is targeting (the wizard pre-fills the standard install path; click **Browse** to point at a different one).
- **What's new** — a scrollable preview of the release notes shipped with the patch. **Open** pops the same notes out into Notepad for easier reading.

Confirm the folder is correct and click **Next**.

Step 3 — Database connection



- **Install path** — read-only, carried forward from Step 2.
- **Server** — the SQL Server instance to patch. Pick from the dropdown (auto-discovered network instances) or type a host name / IP / named instance.
- **Authentication** — Windows or SQL Server. If SQL Server, the wizard expands to ask for user name and password.

- **Connect** — pings the server. On success the wizard fills the **Database** dropdown with every database found on that instance and shows a green badge — "*Connected — N databases found*".
- **Database** — pick the customer database to patch.

The wizard refuses to leave this step until the connection is green — preventing half-applied patches.

Click **Next** to move to the Apply step.

Step 4 — Apply patch



Apply step

The wizard runs the patch in two phases:

1. **Run SQL scripts** — every script in the patch executes in order against the chosen database. Each script appears as a row in the table with its status — **DONE**, **VERIFIED**, or an error pill if it failed.
2. **Copy files to the HMS install folder** — DLLs, templates, reports.

When everything completes, a green summary at the top reads:

✓ **Patch applied successfully.** All scripts executed and files copied. *N of N expected objects verified in sys.objects.*

The number reflects the post-install integrity check.

Filter the table

- **Show only errors** checkbox — hides every DONE / VERIFIED row so you can focus on what failed.

Action buttons (bottom of the screen)

- ← **Previous** — go back to the Database step (only before Apply starts; once scripts are running the patch must finish or be cancelled).
- **Re-Verify** — re-inspect `sys.objects` against the expected list without re-running any scripts. Useful when a verification glitch was caused by a temporary lock.
- **Re-Apply** — re-runs the SQL scripts and re-copies the files. Safe — scripts are written to be idempotent.
- **Next** → — only enabled once the patch is successful.
- **Cancel** — abandons the patch.

Click **Next** to move to Step 5.

Step 5 — Finish

A short confirmation card shows the patch is applied and the wizard exits. The customer database now reports the new patch in **Patching History**.

What if a script fails?

The wizard does **not** silently continue.

- The failing row shows in red on the Apply table with the SQL error text inline.
- **Show only errors** lets you list every failure in one view.
- The comprehensive error file (saved next to the wizard) holds the full output for the support team.
- Press **Re-Apply** after fixing the underlying issue (permissions, missing prerequisite, etc.) — the wizard re-runs idempotently and moves past previously-applied scripts.

If the failure is a missing prerequisite cumulative patch, the Patching History will surface that — see [Patching History](#).

Patching History

Open from the **Patching History** button on the Welcome step. The dialog shows the patch trail for the connected database — every patch that has been recorded since the **last cumulative (-CM) patch**.



Header

The grey banner at the top tells you at a glance:

- **Current patch** — the patch number of the wizard you launched (e.g. "*current patch 462*").
- **Entries** — how many patch rows are tracked.
- **MISSING** count — how many of those rows are MISSING.

Example: "*112 entries · 55 MISSING*" — a database that has gone through 112 patches' worth of script slots, but 55 of them never recorded a successful install.

Columns

Column	Meaning
Patch	The patch number. Patches that are cumulative end in -CM (e.g. <i>350-CM</i>).
Status	<i>Applied</i> (green), <i>Error</i> (red), or MISSING (red, no date).
Date	When the patch ran (blank if MISSING).
Version	The HMS version the patch belongs to (e.g. <i>HMS 23.00</i>).

Status meanings

- **Applied** — the patch ran end-to-end successfully.
- **Error** — the patch ran but one or more scripts failed. The database is in an undefined state for that patch; rerun the wizard with that patch's installer.
- **MISSING** — the patch was never recorded as applied on this database. Either it has not been applied yet, or it was applied before the patch-tracking machinery existed.

Reading the report

Scroll through the list looking for **red rows**:

- A line of consecutive *Applied* greens means the database is healthy in that range.
- An **Error** row means that specific patch needs to be re-applied before the database is fully in sync.
- A **MISSING** row means an earlier patch in the chain was never recorded — chase that one first, because subsequent patches may have depended on its schema changes.

Why the report starts at the last CM

A cumulative patch consolidates every change up to its number into a single, idempotent installer — running it brings any database up to that version regardless of which intermediate patches were applied or missed. So the history before the last `-CM` is irrelevant: the `-CM` guarantees the baseline.

The report only lists patches **after** the last `-CM` because those are the ones whose individual install status still matters.

Acting on the report

- **Many MISSING rows + an old `-CM`** → apply the most recent `-CM` cumulative patch first. That clears almost every MISSING in one go.
- **A few Error rows scattered** → re-apply each errored patch individually. The patch installers are idempotent — re-applying is safe.
- **MISSING rows with no Error rows** → the customer skipped a few patches. Apply them in order; later patches may need their schema changes.

Close

Click **Close** to return to the wizard's Welcome step. Nothing in the report itself is editable — it is a read-only audit view.

Features

Every Setup Wizard v2 feature, grouped by what it lets you do.

1. Guided five-step flow

- **Welcome → Patch → Database → Apply → Finish** — progress visible at the top of every screen.
- **Previous / Next / Cancel** on every step (cancel safe up to Apply).
- **Get started** card on Welcome shows patch number, date, size, and a reminder to close open HMS clients first.
- **Patching History** is one click away from Welcome — no need to start the patch to know whether the database is up to date.

2. Config-free install

- **Works without** `Config.ini` — no pre-configuration required.
- **Auto-loads** `Config.ini` if present — re-installs are still one-click.
- No registry footprint.

3. Database targeting

- **SQL Server instance dropdown** — every instance discovered on the network.
- **Free-text typing** — host name, IP, or named instance (`HOST\SQLEXPRESS`).
- **Authentication selector** — Windows or SQL Server.
- **Connect button** — validates the choice before letting the wizard proceed.
- **Database dropdown** — populates from the connected instance with the count of databases found.
- **Green / red badge** confirms connection status with the specific error if it fails.

4. Patch information

- **Install folder** — pre-filled with the standard path, override with Browse.
- **What's new** preview — scrollable inside the wizard, **Open** pops the notes out into Notepad.

5. Safe application

- **Two-phase apply** — SQL scripts first, then file copy.
- **Per-script status row** — DONE / VERIFIED / Error visible during the run.
- **Show only errors** filter to focus on what failed.
- **Stops on first hard failure** — the wizard surfaces the error instead of soldiering on.
- **Idempotent scripts** — re-applying is safe.

6. Post-install verification

- **Object count** — "*N of N expected objects verified in sys.objects*" shown when the patch completes.
- **Re-Verify** button — re-inspects the database without re-running scripts.
- **Re-Apply** button — full re-run (idempotent).

7. Patch validation & history

- **Patching History** dialog — every recorded patch from the last cumulative (-CM) onwards.
- **Entries + MISSING counter** — one-line health summary ("*112 entries · 55 MISSING*").
- **Per-patch status** — Applied / Error / MISSING with date and HMS version.
- **Prerequisite check** — the wizard refuses to apply a patch when a prerequisite cumulative patch is missing.

8. Comprehensive error reporting

- **Single error file** — every setup and validation error from the run is written to one text file next to the wizard. Attach to support tickets in one click.
- **Per-script error text** inline on the Apply screen.
- **Database version mismatch** detection — flagged in the error file with the expected vs found version.

9. Modern UI

- Clean dark-blue header on every step.
- Light step body with consistent spacing.
- Step numbers on the right ("*STEP N OF 5*").
- metaSOFT HMS branding panel on the Welcome screen.

→ Continue to [Walkthrough](#) for the step-by-step run, or [Patching History](#) for the patch report.

Maintenance Module

The **Maintenance** module is the DBA / site-administrator workspace — the one screen where the person responsible for the database can see its health, run a backup, schedule routine backups, run the safety checklist, fix problems, and ship a complete report to head office.

It is built around two ideas:

- **One dashboard, full context.** The top strip pins the database identity (name, server, data + log file paths, backup folder, last scan) so you never have to ask "*which DB am I looking at?*".
- **One checklist, scored.** Every database-health rule (backup, configuration, integrity, maintenance, operations, performance, security) is a row in one checklist with a colour, a score, an explanation, and — for almost every row — a one-click **safe fix**.



Maintenance dashboard with KPIs

*The Maintenance dashboard on the **KPIs** tab — live database health overview, backup status, and licensing in one screen.*

How to open it

From the HMS main menu pick **Maintenance**. The module is restricted to the **Maintenance / Supervisor** role; the *supervisor* badge in the top-right confirms which role you're using.

The screen

- **Top strip** — Database, Server, Data File, Log File, Backup Folder, Last Scan.
- **Action toolbar** — *Backup Now · Backup Schedule · Send Log · Settings*.
- **Sidebar** — Desktop · Backup (Backup Log) · Storage (Table Sizes, Backup Log Report, Table Sizes Report).
- **Main pane** — two tabs: **KPIs** and **Checklist**, with **Edit / Refresh / Export** controls on the right.

Two tabs

Tab	What it shows
KPIs	Live database health, live activity, backup state, licensing — all as coloured tiles.
Checklist	The 48-point scored health checklist with one-click fixes.

→ Continue to [Getting Started](#) or jump to [Features](#).

Getting Started

A typical first session — verify the backups are healthy, run a manual backup, schedule the next one, and e-mail the maintenance log to head office.

1. Confirm which database you're working with

Read the strip at the top:

- **Database** — name of the live database.
- **Server** — SQL Server instance.
- **Data File / Log File** — physical paths.
- **Backup Folder** — where backups go.
- **Last Scan** — when the health check last ran.

If anything looks wrong, **stop and verify** — every action on this screen affects the database in the top strip.

2. Glance the KPIs

The **KPIs** tab gives you the database's health in three bands:

- **Live activity & performance** — total DB size, log file size, backup disk free, TempDB, sessions, requests, blocked sessions, buffer cache hit ratio, CPU, batch/sec, transactions/sec, server memory.
- **Backup** — last backup age, next scheduled, backup folder size, number of backup files, **policy compliance**, schedule status.
- **Licensing** — licensed seats, license serial, expiry, connected now, active users, total users, last user login.

Tiles in **red / yellow** are issues — click any tile to drill into its checklist row.

3. Run the health checklist

Switch to the **Checklist** tab.

 Database Health Checklist with scoring and one-click fixes

The **Database Health Checklist** — 48 checks across Backup, Configuration, Integrity, Maintenance, Operations, Performance and Security, each with a 0–10 score and one-click safe fix.

- Click **Scan All** to refresh every check. The **Health Score** (top-right) recomputes — out of 100.
- Click **Run Safe Fixes** to apply every fix that is known to be safe (creates missing maintenance jobs, updates stale statistics, purges old logs).
- Use the **category pills** (Backup, Configuration, Integrity, Maintenance, Operations, Performance, Security) and **status pills** (Critical, OK, Warn, Fail, Info) to narrow the list.

Per-row buttons:

- **info** — opens an explanation of what the check does and why it matters.
- **▶ Run** — re-runs just that check.
-  **Fix** — applies the safe fix for that check (when one exists).

4. Run a manual backup

Click **Backup Now** in the toolbar.

 Run Backup dialog with FULL/DIFF/LOG choices

The **Run Backup** dialog — pick **FULL**, **DIFF**, or **LOG**, optionally add a description, and click **Run Backup**.

- Pick the **Backup Type** — **FULL**, **DIFF** (differential), or **LOG**.
- The **Backup Folder** is pre-filled from Settings.
- Add an optional **Description** to label the file.
- Click **Run Backup**. A progress message appears; the backup is written to the folder and a new entry appears in the *Backup Log* sidebar entry.

5. Schedule recurring backups

Click **Backup Schedule**, then + **New Schedule**.

 New Schedule dialog

The **New Schedule** dialog — name, description, backup type, folder, frequency (*Hourly / Daily / Weekly / Monthly*), start time, and the **Active** toggle that decides whether the schedule actually runs.

- **Identity** — Name and Description.
- **What to back up** — **FULL** / **DIFF** / **LOG**, Backup Folder.
- **When to run** — Frequency (*Hourly · Daily · Weekly · Monthly*), Start Time (*HH:MM*).
- **Active (will run on schedule)** — tick to enable; untick to pause without deleting.

Click **Save**. The schedule appears in the list with **Last Run / Next Run / Last Status** columns. Click **Run this schedule now** to fire it on demand without waiting for the cron tick.

6. Send the maintenance log

Click **Send Log** in the toolbar.

The system generates an HTML file containing the same KPIs, checks, backup history, and schedules you see on screen — then uploads it to the configured Google Drive folder. When it finishes, a Drive link appears with **Open in Drive** and **Copy link** buttons; share that link with head office.

 Generated maintenance-log report

The generated **Maintenance Log** as it appears in Drive — KPIs, licensing, live activity, backup, health-by-topic and the full checklist on a single shareable page.

7. Done

The dashboard remembers the last tab you used (KPIs vs Checklist), the sidebar position, and the export format. Future sessions open where you left off.

→ Continue to **Features** for the exhaustive list of everything Maintenance can do.

Features

Every feature of the Maintenance module, grouped by what it lets you do. Exhaustive but not technical — use it as a training checklist or as a gap-analysis against another DBA console.

1. Database identity strip

- Database name.
- Server name.
- Data file path.
- Log file path.
- Backup folder.
- Last scan timestamp.

The strip is pinned at the top of every tab — you can never lose track of which database you're acting on.

2. Toolbar actions

- **Backup Now** — open the Run Backup dialog.
- **Backup Schedule** — open the schedules list and editor.
- **Send Log** — generate the maintenance log and upload to Drive.
- **Settings** — module-wide settings (backup folder, retention).

3. Sidebar

The left sidebar is a fixed navigation tree:

- **Desktop** — the main KPIs + Checklist dashboard.
- **Backup**
 - **Backup Log** — every backup run, with type, date, size, status, target file.
- **Storage**
 - **Table Sizes** — live row count and size per table.
 - **Backup Log Report** — printable backup history report.
 - **Table Sizes Report** — printable table-size report.

4. Dashboard — two tabs

KPIs tab

A tile-based dashboard arranged in coloured bands.

Band 1 — Live activity & performance

- Total DB size.
- Log file size.
- Backup disk free.
- TempDB size.
- Active sessions.
- Running requests.
- Blocked sessions.
- Buffer cache hit %.
- SQL Server CPU %.
- Batch requests / sec.
- Transactions / sec.
- Server memory used.

Tiles colour-code by health — green / yellow / red.

Band 2 — Backup

- Last backup age (e.g. *8m ago*, *2h ago*).
- Next scheduled backup (or *no schedules*).
- Backup folder size.
- Backup files count.
- **Policy (clinical)** — Adequate / Inadequate with reason.
- **Full schedule** — Configured / Missing.
- **Log schedule** — Configured / Missing / N/A (when recovery model is SIMPLE).

Band 3 — Licensing

- Licensed users (used / total).
- License serial.
- License expiry.
- Connected now (distinct logins).
- Active users (enabled accounts).
- Total users (including disabled).
- Last user login.

Checklist tab

The 48-point scored checklist — the heart of the module.

- **Health Score** — single 0-100 figure at the top-right.
- **Scan All** — re-runs every check.
- **Run Safe Fixes** — applies every fix flagged as safe.
- **Refresh** — re-pulls the cached results without re-running.

- Category pills — **All** · **Backup** · **Configuration** · **Integrity** · **Maintenance** · **Operations** · **Performance** · **Security**.
- Status pills — **Critical** · **OK** · **Warn** · **Fail** · **Info** with counts.
- One row per check with:
 - # row number.
 - **Status** — coloured dot.
 - **Check** — name and short helper text.
 - **Category**.
 - **Score** — X / 10 per check.
 - **Detail** — current value and explanation.
 - **Last run** time.
 - **Info** — what this check does.
 - ► **Run** — re-run just this check.
 - 🔧 **Fix** — apply the safe fix (when available).

Tab-level actions

- **Edit** — opens the dashboard template editor (admin only).
- **Refresh** — refresh the data.
- **Export** — export the current tab as a printable report.

5. Backup — Run Backup dialog

- **Backup Type** — FULL · DIFF · LOG.
- **Backup Folder** — pre-filled from Settings; can be overridden per-run.
- **Description** — free text label saved with the backup file.
- **Run Backup** — kicks the backup; a progress strip appears while it runs (*Running backup, please wait...*).
- **Close** — abandon.

Outputs land in the configured folder with a date-stamped file name and immediately update the **Last Backup** KPI tile.

6. Backup — Schedules

List

- + **New Schedule** — create.
- **Refresh** — re-pull from disk.
- Empty state — *No backup schedules yet. Click 'New Schedule' to add one.*
- Per-row columns: Name, Type, Frequency, Start, Last Run, Last Status, Next Run, Active.
- Per-row actions: **Edit** · **Delete** · **Run this schedule now**.

Editor

- **Identity**
 - Name.
 - Description.
- **What to back up**
 - Backup Type — FULL · DIFF · LOG.
 - Backup Folder.
- **When to run**
 - Frequency — **Hourly · Daily · Weekly · Monthly**.
 - Start Time (HH:MM).
 - Days of Week (Weekly).
 - Day of Month 1–31 (Monthly).
- **Active (will run on schedule)** — pause without deleting.
- **Save / Cancel.**

7. Health checks — what's measured

Across the seven categories the checklist covers (non-exhaustive — the on-screen list is the source of truth):

Backup

- Last full backup age.
- Last log backup age.
- Backup drive free space.
- Backup-policy adequacy for clinical use.
- Full schedule defined.
- Log backup schedule defined (when recovery FULL).
- Backup files retention.

Configuration

- Auto-shrink disabled.
- Auto-close disabled.
- MAXDOP set.
- Cost threshold for parallelism.
- Recovery model fits the workload.

Integrity

- Days since DBCC CHECKDB.
- Suspect pages clear.
- Page-verify is CHECKSUM.

Maintenance

- Stale statistics.
- High-impact missing indexes.
- Unused indexes.
- Virtual log file count.
- Audit / log overage (rows older than retention).

Operations

- Failed Agent jobs (24h).
- Errorlog severe entries.
- Long-running sessions.

Performance

- Top wait type.
- Buffer cache hit ratio.
- TempDB contention.

Security

- Logins locked (24h).
- Dangerous surface area.
- `sa` account enabled.
- Weak SQL-login passwords.
- `xp_cmdshell` enabled.

8. Score system

- Each check returns a **0–10 score**.
- Status is derived from the score: **OK** (full marks), **Info** (cosmetic), **Warn** (degraded), **Fail** (failing), **Critical** (broken).
- The **Health Score** is a weighted average across all categories, on a 0–100 scale.
- Scores are coloured — green / yellow / red — so a glance is enough.

9. Send Log — Maintenance Log report

- Generates a self-contained HTML file containing every KPI tile, every check, the backup history, the schedules list, and licensing.
- Uploads the file to the configured **Google Drive** folder.
- While uploading: *Generating and uploading...*

- On success — *Uploaded to Google Drive* with **Open in Drive** and **Copy link** buttons.
- On failure — *Drive upload failed* with the diagnostic message (*Check Maintenance:LogUpload settings in appsettings.json and verify the Drive folder is shared with the service-account email.*).
- Useful for head-office reviews and audit trails — the link goes in the ticket.

10. Settings

- **Backup Folder (single source of truth)** — used by Backup Now, every scheduled backup, and the disk-free check. The folder must be writable by the SQL Server account; it is created if it does not exist.
- **Audit retention (days)** — purges audit rows older than this when the *Audit overage* check's fix runs.
- **Log retention (days)** — same idea for log rows.
- **Save / Close.**

11. Edit dashboard template (admin)

- The **Edit** button on the dashboard opens the underlying dashboard template editor.
- A timestamped `.bak` copy is saved before each write.
- The path the file lives at is displayed so an admin can open the file in a system editor too.
- After save, click **Reload now** in the dashboard to apply the changes without restarting HMS.

12. Reload from disk

- Force the module to re-read its dashboard definition from disk — useful after editing the template in an external editor.
- Toast feedback: *Saved at, Opened in, Loading....*

13. Storage views

Table Sizes (live)

- Per-table row count and size (data + index).
- Sortable.
- Drill into the table-sizes report for a printable version.

Backup Log Report

- Printable history of every backup run — date, type, size, status, file name.
- Same data the **Backup Log** sidebar lists, formatted for distribution.

Table Sizes Report

- Printable per-table size and growth report.

14. UI quality-of-life

- Top strip pinned across every screen — never lose database context.
- Tile colour-coding (green / yellow / red).
- Per-row info / run / fix buttons.
- Sidebar position and selected tab persist between sessions.
- Toast notifications for every long-running action.
- Loading spinners on every async fetch.
- **Refresh** buttons everywhere — never reload the page.
- Read-only mode when the user lacks the *Maintenance* role.
- Dark / light theme follows the HMS app theme.
- Localised — English / Arabic.

15. Safety guardrails

- **Run Safe Fixes** only applies fixes flagged as safe — destructive fixes (drop unused index, purge audit rows) always require an explicit per-row  click.
- Dashboard template edits create a `.bak` before each save.
- Backups respect the SQL Server account permission set — failures surface immediately with the OS error.
- Scheduled backups don't run if **Active** is unticked — pause without deleting.
- Backup folder is validated on Settings save — non-existent / read-only folders are rejected with a clear message.

16. Integration points

Surface	Powered by
Backup / restore	SQL Server BACKUP / RESTORE
Health checks	SQL Server DMVs, <code>sys.*</code> catalog, msdb
Backup history	msdb backup tables + per-run audit
Drive upload	OAuth-based Drive API (service account, configured in <code>appsettings.json</code>)
Schedules	SQL Server Agent (Daily / Weekly / Monthly) and an in-app Hourly tick
Licensing tiles	HMS licensing service
Edit pencil on each page	Source markdown on GitHub

→ Back to [Overview](#) or [Getting Started](#).

KPIs Dashboard

The default tab in Maintenance — every important number about the database, on a single screen, refreshed live.

 Maintenance KPIs dashboard

The KPIs tab. Top strip pins the database identity; the toolbar exposes Backup Now / Backup Schedule / Send Log / Settings; the sidebar offers Backup Log and the storage reports.

How it is organised

Three colour-coded bands:

Live activity & performance

Tile	What it means
Total DB size	Combined data-file size.
Log file size	Transaction-log file size.
Backup disk free	Space left on the disk that hosts the backup folder.
TempDB size	Total TempDB data + log.
Active sessions	Logged-in sessions right now.
Running requests	Requests executing this moment.
Blocked sessions	Sessions blocked by another.
Buffer cache hit %	Percentage of reads served from RAM.
SQL Server CPU %	CPU consumed by SQL Server.
Batch requests / sec	Average since startup.
Transactions / sec	Average since startup.
Server memory used	RAM used by SQL Server right now.

Backup

Tile	What it means
Last backup	Time since the most recent backup (e.g. <i>8m ago</i>).
Next scheduled	When the next scheduled backup will run, or <i>no schedules</i> .
Backup folder size	Total size of files currently in the backup folder.

Tile	What it means
Backup files	Number of backup files in that folder.
Policy (clinical)	Whether the backup setup meets the clinical-use policy. <i>Inadequate</i> shows the reason.
Full schedule	<i>Configured</i> or <i>Missing</i> .
Log schedule	<i>Configured</i> / <i>Missing</i> / <i>N/A</i> (when the database uses SIMPLE recovery, log backups are not applicable).

Licensing

Tile	What it means
Licensed users	Used vs total seats.
License serial	The product key currently active.
License expiry	The renewal date.
Connected now	Distinct sessions logged in right now.
Active users	Enabled user accounts.
Total users	Including disabled.
Last user login	Most recent successful login.

Reading the colours

- **Green** — healthy / within target.
- **Yellow** — degraded but not failing (e.g. backup disk close to full).
- **Red** — failing / policy non-compliant.

Actions on this tab

Top-right:

- **Edit** — open the dashboard template editor (admin only).
- **Refresh** — re-pull the KPI values.
- **Export** — export the current dashboard as a printable report.

Drill-down

Click any tile to open the underlying detail — most tiles jump to the matching row in the **Checklist** tab; the licensing tiles jump to the users / licenses screen.

→ Continue to [Health Checklist](#).

Health Checklist

The **Checklist** tab is the heart of the Maintenance module — every database-health rule on one scored list, with one-click fixes for the safe ones.



The **Database Health Checklist**. The *Health Score (top-right)* is a weighted 0-100 figure over every check. Use the category and status pills to narrow down; click the wrench on a row to apply its safe fix.

The header

Control	What it does
Health Score	A single 0-100 figure summarising every check. Coloured ring around the number tells you at a glance.
Scan All	Re-runs every check. Updates the score.
Run Safe Fixes	Applies the safe fix for every row that has one — non-destructive, audit-logged.
Refresh	Re-pull cached results without re-running.

Filters

Two rows of pills above the list:

- **Category pills** — *All · Backup · Configuration · Integrity · Maintenance · Operations · Performance · Security*.
- **Status pills** — *Critical · OK · Warn · Fail · Info* with the count for each.

Click a pill to toggle filtering. Multiple status pills can be active at once.

The list

Each row is one check. Columns:

Column	What you see
#	Row number.
Status	Coloured dot — OK / Info / Warn / Fail / Critical.
Check	Name of the check + one-line helper.
Category	Backup, Configuration, ...
Score	X / 10 .
Detail	Current measured value or finding.

Column	What you see
Last Run	When the row last ran.
info button	What the check does and why it matters.
► Run	Re-run just this check.
🔧 Fix	Apply the safe fix (when one exists).

Status meanings

- **OK** — full marks. Nothing to do.
- **Info** — informational; not a problem (e.g. *Recovery model is SIMPLE — log backups not required.*).
- **Warn** — degraded; investigate.
- **Fail** — the check failed (e.g. *Could not find stored procedure ...*).
- **Critical** — the database is at material risk; fix immediately.

What gets checked

A non-exhaustive list grouped by category — the on-screen catalogue is the source of truth:

- **Backup** — last full / log backup age, backup-policy adequacy, drive free space, full / log schedule defined, file retention.
- **Configuration** — auto-shrink off, auto-close off, MAXDOP, cost threshold, recovery model.
- **Integrity** — days since DBCC CHECKDB, suspect pages, page-verify is CHECKSUM.
- **Maintenance** — stale statistics, high-impact missing indexes, unused indexes, Virtual Log File count, audit / log overage.
- **Operations** — failed Agent jobs in last 24 h, errorlog severe entries, long-running sessions.
- **Performance** — top wait type, buffer-cache hit ratio, TempDB contention.
- **Security** — login lockouts, dangerous surface area, `sa` enabled, weak SQL-login passwords, `xp_cmdshell` enabled.

How fixes work

- **Safe fix** — non-destructive (e.g. update statistics, create a missing maintenance job, set a configuration option to its recommended value).
- **Destructive fix** — only ever triggered by clicking the per-row  button explicitly (e.g. drop an unused index, purge audit rows older than retention). Confirmation is required.
- **No fix** — some checks (e.g. *Top wait type*) are informational only.

Every fix is logged with the user, timestamp, before-and-after value, and the row it ran against — so a future auditor can trace what changed.

→ Continue to [Run Backup](#).

Run Backup

Click **Backup Now** in the toolbar to open the Run Backup dialog.



The **Run Backup** dialog — pick **FULL**, **DIFF**, or **LOG**, confirm the backup folder, add a description, and click **Run Backup**.

Fields

- **Backup Type** — three buttons, mutually exclusive:
 - **FULL** — complete backup of the database. Use as the baseline from which **DIFF** and **LOG** backups recover.
 - **DIFF** — differential. Captures everything changed since the last **FULL**. Smaller and faster.
 - **LOG** — transaction-log backup. Only valid when the database is in **FULL** recovery model.
- **Backup Folder** — pre-filled from Settings (single source of truth). Can be overridden for this one run.
- **Description** — optional free text. Stored in the backup metadata.

Run

Click **Run Backup**. A progress strip appears: *Running backup, please wait...*

When the backup finishes:

- The file is written to the folder.
- The **Last Backup** KPI tile updates immediately.
- A new entry appears in the **Backup Log** sidebar item.
- A toast confirms success.

If the backup fails the dialog shows the SQL error and the *Last Status* column on the Backup Log marks it **Failed**.

When to use which type

Type	When
FULL	At least once a day for clinical databases. Before a major upgrade. After a successful restore drill.
DIFF	Several times a day to shorten the restore chain.
LOG	Every 15-60 minutes when the database is in FULL recovery to limit RPO (data loss window).

Tips

- The folder must be writable by the **SQL Server account**, not just the user running HMS — if it can't write, the backup fails with a permission error.

- Use **Description** to mark special backups (*Pre-upgrade, End-of-month, Migration*) so they stand out in the Backup Log.
- Run **Backup Now** before a risky operation — restoring a DIFF that was taken five minutes ago beats restoring last night's FULL.

→ Continue to [Backup Schedules](#).

Backup Schedules

Click **Backup Schedule** in the toolbar to open the schedules list. A schedule fires a backup on a recurring cadence without anyone having to click *Backup Now*.

The list

- **+ New Schedule** — create.
- **Refresh** — re-pull from disk.
- Empty state — *No backup schedules yet. Click 'New Schedule' to add one.*

Per-row columns:

- **Name**.
- **Type** — FULL / DIFF / LOG.
- **Frequency** — Hourly / Daily / Weekly / Monthly.
- **Start** — start time (HH:MM).
- **Last Run** — when it last fired.
- **Last Status** — Saved / Failed / —.
- **Next Run** — when it will fire next.
- **Active** — green dot if running on schedule.

Per-row actions:

- **Edit** — open the editor.
- **Delete** — remove the schedule (with confirm).
- **Run this schedule now** — fire on demand without waiting for the cron tick.

The editor



The **New Schedule** dialog. Five sections — *Identity*, *What to back up*, *When to run*, *frequency-specific fields*, and the *Active toggle*.

Identity

- **Name** — short label that appears in the list. Required.
- **Description** — free text.

What to back up

- **Backup Type** — FULL / DIFF / LOG.
- **Backup Folder** — locked to the central folder from Settings. Single source of truth; all schedules use the same folder.

When to run

- **Frequency** — Hourly · Daily · Weekly · Monthly.
- **Start Time** — HH:MM (24-hour clock).
- Frequency-specific extra:
 - **Weekly** → *Days of Week* — tick which weekdays.
 - **Monthly** → *Day of Month (1-31)*.
 - **Hourly / Daily** → no extra fields.

Active (will run on schedule)

- Tick to enable. Untick to pause without deleting.

Save / Cancel

Save commits the schedule and registers the corresponding SQL Server Agent job (Daily / Weekly / Monthly) or in-app tick (Hourly). Cancel abandons changes.

Patterns

Goal	Suggested schedules
Clinical database, low write volume	FULL daily 02:00 + LOG every 30 min during business hours
Clinical database, high write volume	FULL daily + DIFF every 6 h + LOG every 15 min
Reporting copy, off-hours updates	FULL weekly Sunday 03:00
Pre-upgrade snapshot	Run Backup Now with FULL + a descriptive Description; no schedule needed

Common pitfalls

- **Active unticked** — schedules don't fire. Check the green dot.
- **Backup folder unwritable** — every run fails with the same error. Fix the OS permission on the folder.
- **No FULL backup yet** — DIFF and LOG schedules need a FULL baseline. Run **Backup Now** with FULL once before relying on DIFF/LOG schedules.
- **Recovery model is SIMPLE** — LOG schedules will be marked N/A. Switch the database to FULL recovery if you need log backups.

→ Continue to [Send Log](#).

Send Log

Click **Send Log** in the toolbar to generate a shareable maintenance report and upload it to Google Drive.

What it generates

A self-contained HTML file with everything an off-site auditor or head-office DBA needs to review the site's health — all on one scrollable page.



The **Maintenance Log** as rendered on Drive. Sections from top to bottom: identity strip, KPIs (Database Health Overview), Live activity & performance, Backup, Licensing, Health by topic, and the full Database Health Checklist.

Sections

1. **Title strip** — Maintenance Log, database, server, generated timestamp.
2. **Licensing** — customer, license expiry, connected now, active users.
3. **KPIs**
 - Database Health Overview (counters per category).
 - Live activity & performance.
 - Backup.
 - Licensing.
4. **Health by topic** — one tile per category with the OK / total score.
5. **Database Health Checklist** — every check with status, score, detail and last-run timestamp.

The output is fully styled and prints cleanly to A4.

Flow

1. Click **Send Log**. The button shows *Generating and uploading...*
2. The system writes the HTML file and uploads it to the Google Drive folder configured in **Maintenance** → **Settings**.
3. On success — *Uploaded to Google Drive* — the result panel shows:
 - **Open in Drive** — opens the file in a new browser tab.
 - **Copy link** — copies the share-link to your clipboard.
4. Share that link in the ticket / e-mail thread.

When it fails

If the upload fails the panel shows *Drive upload failed* with the diagnostic text:

Check Maintenance: LogUpload settings in appsettings.json and verify the Drive folder is shared with the service-account email.

Typical causes:

- The configured Drive folder has not been shared with the service-account e-mail.
- The OAuth refresh token in `appsettings.json` has expired.
- The site has no outbound network access to Google APIs.
- The configured folder ID is wrong.

When to use it

- **Routine reporting** — weekly / monthly snapshot for head office.
- **Incident ticket** — send the log link with the ticket so support sees the full health picture without dialling in.
- **Pre-upgrade** — generate before a major upgrade for an immutable record of the pre-change state.
- **Audit** — attach the link to the audit trail.

→ Continue to [Settings](#).

Settings

Click **Settings** in the toolbar to open the Maintenance Settings dialog. Three short fields that affect every other screen.

Backup Folder (single source of truth)

The directory every Maintenance backup writes to:

- Used by **Backup Now**.
- Used by every **Scheduled backup**.
- Used by the **Backup disk free** KPI tile.
- Used by the **Backup drive free space** checklist row.

Rules:

- The folder must be writable by the **SQL Server account**, not the Windows user running HMS. SQL Server writes the backup file itself.
- If the folder does not exist, the system creates it on first save.
- Changing the folder does not move existing files — old files stay where they are.

Audit retention (days)

The maximum age (in days) of audit rows before the *Audit / log overage* check on the **Checklist** considers them excess.

- Affects two tables: **SEC_Log** and **SEC_PasswordLog**.
- The matching safe fix purges rows older than this limit.

Log retention (days)

Same concept for application-log rows.

- Affects two tables: **DBHealth_History** and **Backup_Run**.

Save / Close

- **Save** persists the settings to the central configuration file and refreshes every dependent KPI tile.
- **Close** abandons changes.

Where these settings live

The settings are stored centrally — change them once and every schedule, every backup, every KPI tile and every checklist row picks up the new values without a restart.

→ Continue to [Backup Log](#).

Backup Log

The **Backup Log** sidebar item opens the audit list of every backup ever taken on this database — manual or scheduled.

What you see

A table, newest at the top. Columns:

Column	What it shows
Date	When the backup ran.
Type	FULL / DIFF / LOG.
Size	The file size on disk.
Status	Saved / Failed / Running.
File	The path to the file (click to open the parent folder).
Description	Whatever was typed in the Run Backup dialog or the schedule's Description field.
Run by	User who initiated (or <i>Schedule</i> for cron jobs).
Duration	How long the backup took.

Filters

- By type — FULL / DIFF / LOG.
- By status — Saved / Failed.
- By date range.

Actions

- **Refresh** — re-pull the list.
- Per-row click → opens the folder containing the file.
- **Backup Log Report** (Storage → Backup Log Report) — printable version for distribution.

Tips

- Use **Description** when you take a backup before a risky change — it becomes the searchable label in the log.
- The log keeps every entry forever — the **Audit / log overage** checklist row + safe fix is how you purge old rows. Default retention is set in Settings.

→ Continue to [Storage & Reports](#).

Storage & Reports

The **Storage** branch of the sidebar groups three table / file oriented views.

Table Sizes (live)

A live grid — one row per table, sortable.

Column	What it shows
Table	Table name.
Rows	Current row count.
Data size	Size of the table data (excluding indexes).
Index size	Total size of every index on the table.
Total size	Data + index.
% of DB	This table's share of the total database size.

Sort by **Total size** descending to spot the heavyweights — those are usually the tables whose growth pattern drives the database forward.

Use cases

- **Capacity planning** — which tables are growing fastest?
- **Index audit** — when *Index size* > *Data size*, the table likely has unused indexes (cross-reference with the **Unused indexes** checklist row).
- **Archive candidates** — old audit / log tables often top this list and are good candidates for the retention purge.

Backup Log Report

Printable version of the **Backup Log** sidebar item. Same data, A4 layout, branded header, ready to attach to an audit ticket or e-mail.

- Pick a date range.
- Group by Day / Week / Month.
- Filter by Type / Status.
- Export to PDF or print directly.

Table Sizes Report

Printable version of **Table Sizes**.

- Snapshot at the moment you run it.
- Grouped by schema.
- Highlights the top 20 tables by size.
- Export to PDF or print directly.

Tips

- Run **Table Sizes Report** monthly and keep the PDFs — comparing reports across months is the cleanest way to see growth trends.
- The two reports share the dashboard's print stylesheet, so they match the branding of the rest of HMS automatically.

→ Back to [Overview](#).

UI Updates

System-wide UI improvements that touch every screen in HMS — not tied to any one module. Three big ones in this release:

Update	What changes	Page
Grid R3	Every data grid in HMS gets a spreadsheet-style overhaul — sticky headers, fullscreen, keyboard navigation, sortable / hideable / reorderable columns, footer totals, row density, and more.	Open
Mini Mode	A compact layout for selection popups and search views — faster, less cluttered, optimised for picker workflows and smaller screens.	Open
Patient Avatar	Circular patient photos on binder headers and patient forms — with one-click camera capture and large preview.	Open

These updates apply **everywhere** in the system. Once installed, you will see them in every clinic, every binder, every module that uses grids, pickers, or shows the patient banner.

Grid R3 — Enhancements & Usability Improvements

Every data grid in HMS gets a top-to-bottom overhaul in **Grid R3**. The result is a grid that behaves like a modern spreadsheet — faster keyboard entry, better visibility for big datasets, flexible column management, and improved fullscreen usability.

Layout & Visibility

- **Sticky headers while scrolling** — column headers remain visible when scrolling long or maximised grids.
- **Fullscreen / maximise mode** — expand the grid to fill the entire screen, then restore it back instantly.
- **Search-as-you-type filtering** — quickly filter rows using the built-in search box.
- **Loading & empty states**
 - **Loading spinner** appears while data is being fetched.
 - Empty grids display a clean **“No Records Found”** message instead of a blank area.

Column Features

Show / hide columns

- **Right-click the grid header** to choose which columns are visible.
- Column visibility preferences are remembered per user.

Column reordering

- **Drag and drop column headers** to rearrange columns.

Parent / grouped headers

- Related columns can appear under a shared parent caption such as:
 - **Pricing**
 - **Tax**
 - **Patient Information**

Column sorting

- **Click once** → Ascending.
- **Click again** → Descending.
- **Click a third time** → Clear sorting.
- Active sort direction is shown with an arrow indicator.

Footer summaries

- Footer rows can display **totals and sums** for selected numeric columns.

Row Features

Row number column (#)

- Every grid now includes a fixed **row-number column** on the left side.
- The footer of the # column displays the **total number of records**.

Row density / resize modes

- Switch between:
 - **Compact**
 - **Normal**
 - **Comfortable**
- Preferences are automatically saved and restored.

Duplicate row

- **Right-click any row** and choose **Duplicate** to insert a new row containing the same values as the selected row.

Editing & Keyboard Navigation

Single-click editing

- Click any cell and start typing immediately — **no double-click required**.
- New typing automatically **replaces** the existing value.

Spreadsheet-style keyboard navigation

Key	Action
Tab / →	Move forward
Shift + Tab / ←	Move backward
↑ / ↓	Move vertically
Enter	Move to the first editable cell in the next row

Automatic row creation

Pressing **Enter** on the last row automatically creates a new row and moves focus into it.

Selected cell highlighting

The active cell is **visually highlighted** at all times.

Auto-select existing text

When entering a cell, the **current text is automatically selected** so typing immediately replaces it.

Read-only cells

Read-only cells are **skipped automatically** during keyboard navigation.

Toolbar Improvements

- **Show / hide toolbar buttons** — right-click the toolbar to choose visible buttons.
- **Modern icon toolbar** — toolbar buttons now use cleaner, simplified icons for a more modern appearance.

Overall Experience

The grid now behaves much more like a modern spreadsheet application, offering:

- **Faster keyboard-based editing**
- **Better visibility for large datasets**
- **Flexible column management**
- **Improved fullscreen usability**
- **Faster navigation and data entry workflows**

Mini Mode — Compact Selection Popups & Search

Mini Mode is a compact layout for selection popups and search views — cleaner, faster, optimised for picker workflows and smaller screens.

Where it applies

- **Selection popups** — every "pick a record" dialog (pick a patient, pick a doctor, pick an item, ...).
- **Search views** — the searchable list windows behind the pickers.

How to enable it

- **System-wide as a user preference** — toggle the **Mini Mode** icon in the toolbar.
- Once enabled, every selection popup automatically switches to a **compact Mini Mode** version of the search view.
- Toggle back any time — the choice is remembered per user.

What you get in Mini Mode

Cleaner, more compact layout

The popup is sized for **fast selection on smaller screens** — less chrome, more results, less scrolling.

Hidden clutter

- **Advanced icons** are hidden.
- **Secondary actions** are hidden.
- **Less frequently used controls** are hidden.
- Only the controls a user actually needs to *pick a record* stay visible.

Unified Quick Search box

One search box searches across the **most critical fields** at once:

- Patient Name
- MRN
- Phone Number
- Arabic Name
- ID Number

Type once → all five fields are matched simultaneously.

Quick filter pills / tags

Filters remain available as **quick pills / tags** at the top of the popup — click any pill to narrow the results without opening the advanced search panel.

History menu

The popup includes a **History menu** that displays the **last 10 selections** — one click to reuse a record you just picked. Ideal for repetitive workflows (e.g. taking five payments from the same patient in a row).

Why use Mini Mode

- **Faster pick** — Quick Search + History menu eliminates most clicks.
- **Less screen real-estate** — works comfortably on laptops, tablets, and wall-display kiosks.
- **Less cognitive load** — advanced controls are tucked away; only what you need is visible.

If you regularly use pickers (front desk, scheduler, cashier), Mini Mode is the recommended default.

Patient Avatar Integration

Circular **patient avatars** are now shown on binder headers and patient forms throughout HMS. A photo lives with every patient record and surfaces wherever the patient banner appears.

Where you see it

- **Binder headers** — every binder that shows a selected patient gets a circular avatar to the left of the patient name and case number.
- **Patient forms** — the patient edit form shows the same avatar prominently at the top.

Interactions

Empty avatar

- Shown as a placeholder circle with a “+” **badge** indicating that a photo can be uploaded.
- **Click an empty avatar** → opens the camera dialog for **immediate photo capture**.

Existing avatar

- Shown as the patient's current photo, cropped to a circle.
- **Click an existing avatar** → opens a **larger preview** of the full photo.

Preview actions

Inside the large preview the user can:

-  **Recapture** — open the camera and take a fresh photo.
-  **Browse** — pick an existing image from disk.
-  **Delete** — remove the current photo (returns to the empty state).

Benefits

- **Faster patient recognition** across the system through clear visual identification.
- **Reduces the risk** of selecting or opening the wrong patient file, especially in busy clinics and multi-patient workflows.
- **Streamlines patient registration** by allowing immediate camera capture directly from the avatar area.
- **Large image preview** helps staff verify patient identity before procedures, billing, or documentation.
- **Improves continuity of care** by helping clinical staff visually confirm the correct patient during repeated visits.
- Creates a **more personalised patient experience** during appointments and registration workflows.

!!! tip "Enrol photos at first registration" Take a fresh photo at the moment the patient first registers — it pays back across every future visit, every form, every cashier interaction, and every clinical workflow.

Report Server (V2)

The **Report Server** is the central catalogue of every printable report in HMS — clinical, financial, HR, inventory, lab, radiology, quality. V2 is the rebuilt browser-first catalogue with a sidebar of categories, a live search, favourites, and an inline parameters panel that ends with one click on **Print Preview**.

What it looks like

A single full-screen page with three regions:

Region	What it does
Header	Hamburger to toggle the sidebar · <i>Report Catalog</i> brand (with the <i>V2</i> badge) · live search box · Favorites / All filter pills · Close button.
Sidebar	Two stat tiles (<i>Reports</i> , <i>Categories</i>) and a category list with per-category report counts. Collapsible.
Main pane	One of three states — Welcome (all-categories tiles), Category drill-down (a single category's reports grouped by sub-category), or Report parameters (the chosen report's filters + Print Preview).

Three states

1. **Welcome** — Hero block + a tile per category. The hero text: "*Pick a category to see its reports, or use the search to find a report by name or description.*"
2. **Category** — All reports in the picked category, grouped by sub-category, with title + description and a *Back* link.
3. **Report** — The chosen report's parameters (filters), a breadcrumb (Catalog → Category → Sub-category → Report), an optional description strip, and the **Print Preview** button.

How to open it

Open **Reports** from anywhere in HMS — main menu, dashboard quick links, or a module's *Reports* ribbon button. The V2 catalogue opens in a full-screen layout that respects your light/dark theme and RTL language setting.

See also

- [Getting Started](#) — print your first report in under a minute.
- [Features](#) — the exhaustive categorised list of everything Report Server V2 can do.

Getting Started

Print your first report in under a minute.

1. Open the catalogue

From the HMS main menu click **Reports**. The catalogue opens on the **Welcome** state — a hero block and a tile per category (Admissions, Billing, Clinical, HR, Inventory, Lab, Radiology, Quality, ...).

2. Find the report

Three ways:

- **Pick a category tile** — opens that category, grouped by sub-category.
- **Type in the search box** — the sidebar and main pane filter live as you type. Search matches the report's name **and** description.
- **Filter by Favorites** — click the heart pill in the header to show only the reports you've marked as favourite.

If no reports match, you'll see *No reports match your search* (or the in-category variant).

3. Open the report

Click any report card. The main pane switches to the **Report** state. A breadcrumb at the top reads:

Catalog > **Category** > Sub-category > **Report Title**

If the report has a description, a small info strip explains what it shows.

4. Fill in the parameters

Below the breadcrumb the report's filters appear as ordinary controls — text boxes, date pickers, dropdowns, radios, checkboxes. Each parameter has:

- A **caption** (what it filters by).
- A **default value** (pre-filled so the report works on first click).

Adjust whatever you need. Tab between controls; Enter doesn't submit.

5. Click Print Preview

The button is at the bottom-right of the parameters block. The report renders in the preview window — from there you can:

- **Print** to paper.
- **Save as PDF**.
- **Export** to Excel or Word (when supported by the layout).
- **Email** the file.

Close the preview to come back to the same parameters — change one value and re-preview without re-navigating.

6. Pin it for next time

While viewing the report, three small switches at the top of the parameter pane let you **personalise** the report:

- **Favorite** — appears under the Favorites filter pill.
- **Report List** — appears on the module's quick reports list.
- **QuickBar** — appears on the QuickBar (the per-user shortcuts row).

Toggle any of them on / off at any time.

7. Done

Click **Back** to return to the category, or **Close** to return to the screen you opened the catalogue from.

→ See the [Features](#) page for the exhaustive list of what V2 can do.

Features

Every Report Server V2 feature, grouped by what it lets you do. Exhaustive but not technical — use it as a training checklist or as a gap analysis against the legacy V1 catalogue.

1. Discovery — find a report

- **Welcome page** with a hero block:
 - Title — *Report Catalog*.
 - Helper text — *"Pick a category to see its reports, or use the search to find a report by name or description."*
 - Tile-per-category grid (icon + name + report count).
- **Category sidebar** on the left:
 - Two stat tiles at the top — total **Reports**, total **Categories**.
 - Category list, each row with an icon, name, and count badge.
 - *All Categories* shortcut at the top of the list.
 - Selected category highlighted.
 - Empty-tree message — *No reports match your search* — when the search excludes every category.
- **Live search box** in the header:
 - Searches report **name** *and* **description**.
 - Filters both the sidebar and the main pane as you type.
 - **Clear** (X) button appears once there's text.
 - Empty-state messages in the pane — *No reports match your search* and *No reports match your search in this category*.
- **Filter pills** in the header:
 - **Favorites** — show only reports you've marked as favourite.
 - **All** — show every report (default).
- **Category drill-down**:
 - Big folder icon + category name + total report count.
 - Reports grouped by **sub-category** (defaulting to *General* when no sub-category is set).
 - Each report shown as a card with an icon, title, and description.
- **Breadcrumb** in the report view — Catalog › Category › Sub-category › Report Title.

2. Navigation

- **Hamburger button** in the header — toggle the sidebar open / closed.
- **Brand button** — *Report Catalog · V2 badge* — click to return to the welcome state.
- **Back to Catalog** tooltip on the brand button.
- **Back arrow / Back button**:
 - From a report → back to its category.
 - From a category → back to the welcome state.
- **Breadcrumb links** — click *Catalog* or the category name to jump back.

- **Close** (X) button in the header — returns to the screen the user opened the catalogue from. Falls back to the home screen if there is no history.
- **RTL support** — back arrow flips direction; sidebar moves to the right when the language is Arabic.

3. Reports list — cards

Each report card shows:

- File icon.
- **Title** (the report's display name).
- **Description** (when defined).
- A chevron on the right to hint it's clickable.

States:

- Hover effect.
- Click → opens the report.
- Disabled / hidden when the user doesn't have access (driven by Security).

4. Report parameter panel

When a report is open, its parameters are rendered as a form. Five control types are supported:

Type	What you see
Edit (text)	A plain text input — for free-text filters such as patient name fragment, account number.
Date	A date picker — for date-from / date-to filters. Default values are decoded from preset tokens (today, first-of-month, etc.).
Dropdown (lookup)	A searchable dropdown filled from a database lookup — e.g. branches, departments, physicians, payers.
Radio	Mutually-exclusive options (e.g. <i>Detailed / Summary</i> , <i>Active / Inactive</i>).
Checkbox	On/off flags (e.g. <i>Include cancelled</i> , <i>Show inactive</i>).
Hidden	Parameters that exist but are not shown — pre-filled from context.

Every control carries:

- A **caption** (what it filters by).
- A **default value**.
- An **option to disable / hide** based on context.

5. Running a report

- **Print Preview** button at the bottom of the parameter pane.
- A loading spinner while the report renders.
- Errors surfaced inline (red banner) with the message and a developer trace strip when debug is on.

6. Output & sharing

From the preview window the user can:

- **Print** to a connected printer.
- **Save as PDF.**
- **Export to Excel** (when the layout supports it).
- **Export to Word.**
- **Email** the rendered file.
- **Re-render** without leaving the preview after changing a parameter.

7. Personalisation — per user

Three switches at the top of the report-parameter pane let the user pin a report to one of three personal surfaces:

- **Favorite** — surfaces under the Favorites pill and the user's favourite-reports list.
- **Report List** — surfaces under the module's *Reports* quick list.
- **QuickBar** — surfaces under the QuickBar shortcuts row.

All three are independent; a report can be on any / all / none.

8. Security

- Each report has its own access-rights mapping.
- Reports the user can't access don't appear in the catalogue at all.
- Right-click on the report header → **Access Rights** opens the per-report security editor for admins.
- The catalogue obeys the session timeout — when the session expires the report list re-fetches with the user's current permissions.

9. Internationalisation

- All catalogue labels (search, filters, breadcrumb, empty states, buttons) are localised — English / Arabic out of the box.
- The report **Title** is localised too.
- **RTL layout** flips the sidebar, the breadcrumb chevrons, and the back-arrow icon.
- Number / date formats follow the user's locale.

10. Empty / edge states

- Sidebar empty tree — *No reports match your search.*
- Category empty pane — *No reports match your search in this category.*
- Welcome empty pane — *No reports match your search* (when the search excludes everything).
- Tabs / cards never render without their counts.

11. UI quality-of-life

- Live search — no submit button needed.
- Clear-search button appears only when the box has text.
- Sidebar state (open / closed) persists per session.
- Sticky header — search and filters remain reachable while scrolling the catalogue.
- Cards adapt to screen width — phones, tablets, big monitors.
- Light / dark theme follows the HMS app theme.

- Icons throughout: folder tree (brand), folder (category), file (report), heart (favourites), printer (preview), magnifying glass (search), chevron (drill-down), bars (hamburger), info (description), arrow-left/right (back).
- **Stat counters** in the sidebar update live as the search narrows the visible set.

12. Categories & organisation

- Two-level category hierarchy — **Category** and **Sub-category**.
- Sub-category defaults to *General* when omitted.
- Reports are listed alphabetically inside each sub-category.
- Categories are listed alphabetically inside the sidebar.
- Per-category and per-sub-category headings show the count of reports they contain.

13. Per-report descriptions

- Each report can carry a **short description** that:
 - Appears under its name on the card in the category view.
 - Appears as an info strip above the parameter pane in the report view.
- Searched alongside the title — so a user can find a report by what it shows rather than what it's called.

14. Direct-launch (deep link)

- Reports can be launched directly by URL (bookmarkable / linkable from dashboards and other forms) — the catalogue opens straight on the parameter pane, ready to preview.
- Pre-fill parameters via URL query so a dashboard tile can open a pre-filtered report.

15. V1 ↔ V2 coexistence

- V2 ships alongside the legacy catalogue — the **V2** badge in the header is your reminder which one you're in.
- Both versions read the same report definitions, so a report is available in both immediately without re-cataloguing.
- The user can choose V1 / V2 as their default catalogue in personal preferences.

16. Integration points

- **Favourites / Report List / QuickBar** — the same personalisation back-end every other HMS surface uses, so favouriting a report here surfaces it on the dashboard's quick reports list too.
- **Localisation** — central HMS translation dictionary.
- **Security** — central HMS role / access-rights store.
- **Report engine** — the same Crystal-Reports-based engine for output; V2 only replaces the catalogue / launcher.

→ Back to [Overview](#) or jump to [Getting Started](#).

Clinic Dashboard

The **Clinic Dashboard** is the manager's home screen for one outpatient clinic. It packs the headline numbers — revenue, no-show rate, bed occupancy, claim acceptance, stock-out risk, quality alerts, referral pipeline — onto one page and lets you drill into any of them with a click.

It is the page the clinic manager opens first thing in the morning, the medical director glances at between rounds, the billing supervisor keeps in a second tab, and the front-desk lead leaves running on a wall display.

What it shows you

Eight focused sub-tabs, each owning a slice of the clinic:

Sub-tab	Answers the question
Overview	How is the clinic doing today, in one glance?
Schedule	Who is booked, arrived, no-show, completed today?
Census	Which beds are occupied, who is being discharged when?
Billing	Are we collecting revenue and getting claims paid?
Physicians	Which physicians are over- or under-utilised today?
Inventory	Are we about to run out of anything critical?
Quality	Are readmissions, incidents, and satisfaction trending right?
CRM	How is the referral / opportunity / campaign pipeline?

How it relates to other dashboards

- **Clinic Dashboard** (this) — *one* clinic's operations.
- **Hospital Dashboard** — the whole hospital rolled up.
- **Patient Dashboard** — *one* patient's lifetime.
- Module dashboards (HR, Inventory, Lab, ...) — drill-downs into a single module across the whole hospital.

All of them share the same look-and-feel — KPI tiles + sparklines + a side cards section — so if you can read one you can read them all.

→ Continue to [Getting Started](#) for a 60-second tour, or jump to the full [Features](#) catalogue.

Getting Started

A 60-second tour of the Clinic Dashboard.

1. Open it

From the HMS main menu pick **Clinic Dashboard**. The dashboard loads on the **Overview** sub-tab — the manager's "everything in one glance" view.

2. Read the headline numbers

Six tiles run across the top:

Tile	What it tells you
Revenue today	How much money the clinic has invoiced so far today, with a chip showing whether that is more or less than yesterday.
Appointments	How many appointments are booked for today, with a chip versus the same day last week.
Waiting now	How many patients are currently in the waiting room.
No-show rate	The % of appointments missed over the last 7 days.
Bed occupancy	The % of inpatient beds that are full right now.
Claims accepted	The % of insurance claims accepted in the last 30 days.

Each tile has:

- A **value** and **unit**.
- A coloured **delta chip** — green if up vs the comparison period, red if down, grey if flat.
- A small caption telling you the comparison period or the denominator.

3. Check the trend

Below the tiles a **30-day revenue sparkline** shows the day-by-day revenue trend. Hover any dot to see the date and amount; the y-axis labels show the min and max.

4. Switch sub-tabs

The eight sub-tabs along the top let you zoom into a specific area:

- **Schedule** → today's appointment grid + arrivals counters.
- **Census** → inpatient ward occupancy + bed map.
- **Billing** → revenue trend + A/R aging + top revenue items.
- **Physicians** → today's physician scorecards.
- **Inventory** → low-stock alerts + stockout risk.
- **Quality** → readmission rate + incidents + satisfaction.
- **CRM** → opportunity funnel + referral sources + campaigns.

The dashboard remembers your last sub-tab and opens there next time.

5. Drill into anything

Almost every number on every sub-tab is **clickable**:

- Click a KPI tile → the underlying list (e.g. *No-show rate* opens today's no-show appointments).
- Click an item in a side list → the full record.
- Click a chart segment → the records that contributed.

6. Hide cards you don't need

Right-click any card and pick **Hide this card**. The dashboard keeps your show / hide preferences per user, per sub-tab. Bring them back from the **Settings** menu on the right rail.

7. Refresh

Numbers refresh automatically every few minutes. To force an immediate refresh, click the **Refresh** button (top-right of any sub-tab).

→ Continue to **Features** for the exhaustive categorised feature list, or **Sub-tabs** for a page per area.

Features

Every Clinic Dashboard feature, grouped by what it lets you do. Exhaustive but plain-English — no system internals.

1. Layout & Navigation

- **Eight sub-tabs** — Overview, Schedule, Census, Billing, Physicians, Inventory, Quality, CRM.
- **Sub-tab memory** — the dashboard reopens on the sub-tab you used last.
- **Refresh** button on every sub-tab for an immediate re-pull.
- **Auto-refresh** — numbers update on their own every few minutes.
- **Responsive layout** — six-column KPI strip on a wide screen drops to three or two columns on smaller displays.
- **Right-rail controls menu** — hide / show any card on the current sub-tab; preferences saved per user.
- **Card hide / show** — right-click any card → *Hide this card*; bring hidden cards back from the controls menu.
- **Click anything to drill down** — KPI tiles, list rows, chart segments all open the underlying records.

2. Overview sub-tab

Six headline KPI tiles plus a 30-day revenue sparkline.

KPI tiles

- **Revenue today** — money invoiced so far today, with delta vs yesterday.
- **Appointments** — appointments booked today, with delta vs same day last week.
- **Waiting now** — live count of patients in the waiting room.
- **No-show rate** — % of appointments missed over the last 7 days, with delta.
- **Bed occupancy** — % of inpatient beds full right now (with busy / total caption).
- **Claims accepted** — % of claims accepted over the last 30 days, with delta.

Revenue trend card

- **30-day daily revenue sparkline** with axis labels (date and value).
- **Hover any data point** for the exact daily total.
- Auto-handles **empty period** — friendly "*no billing activity in the last 30 days*" message.

3. Schedule sub-tab

Today's appointment grid in dashboard form.

- **Today's schedule heat-strip** — each cell coloured by status (Booked / Confirmed / Arrived / Attended / Cancelled / No-show / Free) with the patient initial.
- **Hover tooltip** — patient + physician + time + status.
- **Click a cell** → opens that appointment.
- **Status counters** — Booked, Confirmed, Arrived, Attended, Cancelled, No-show, Free.

- **Date navigator** — Previous day, Today (jump back), Next day.
- **Physicians on duty** side panel — who is working today.
- **Show less / Show more** for the physician list when it overflows.

4. Census sub-tab

Inpatient occupancy and discharge planning.

Cards

- **Occupancy** — % of beds full, plus busy / total counts.
- **Wards breakdown** — per-ward Occupied / Free / Available counts.
- **Admits today** counter.
- **Discharges today** counter.
- **Free beds** counter across all wards.
- **Average length of stay (LOS)** — for current inpatients.
- **Bed map** — visual grid of every bed, coloured by status, click any bed to open the patient.
- **Discharge queue · next 48h** — patients expected to leave with their planned discharge time.
- **Click "Open admission"** on any row → opens the full admission record.

5. Billing sub-tab

Cash flow, A/R, claims, and top items.

Cards

- **Revenue today** KPI.
- **MTD average bill** ("Avg ticket") — month-to-date average bill size.
- **A/R outstanding** — total amount owed by patients / payers.
- **Severely overdue** — A/R aged past the configured threshold.
- **Revenue · last 30 days** — daily-totals sparkline.
- **A/R aging** breakdown — 0–30, 31–60, 61–90, 90+ buckets, with a bar chart and exact amounts.
- **Outstanding only** filter on A/R aging to hide settled balances.
- **Top revenue items · 90d** — leaderboard of the highest-revenue service codes; click "Open " to see the item.
- **Claim status · 60d** — accepted / pending / rejected / re-submitted breakdown.
- **Currency display** — drives the unit chip on every monetary field (defaults to SAR if not configured).

6. Physicians sub-tab

Per-physician productivity, today and month-to-date.

Per-physician card

- **Physician name** + click-through to their full record.
- **Today's counters:** Booked, Pending, Arrived, Done, Cxl, No-show.
- **Utilization %** — what share of the physician's bookable hours are filled today.
- **Patients MTD** — count of distinct patients seen this month.
- **Revenue MTD** — money invoiced under this physician this month.

Other features

- **Sort by** — utilization, revenue MTD, or patients MTD.
- **Show less / Show more** when the physician list is long.
- **Date navigator** — Previous day, Today, Next day.
- **Empty-state** — "*No appointments today*" on physician cards with a fully open calendar.

7. Inventory sub-tab

Stock visibility for the clinic.

Cards

- **Stockout risk** — items currently at zero or below safety stock.
- **Low-stock alerts** — items below their min-on-hand threshold.
- **Critical alerts** count.
- **In stock, Low stock, Out of stock** counters.
- **Total items** in catalogue.
- **Stock value** — current inventory value in the configured currency.
- **Stock by location** breakdown — per location (chair, pharmacy, store) with on-hand counts.
- **Top movers · last 90 days** — items by volume or revenue (toggle).
- **Stock vs min** view — visual bar showing on-hand against minimum-on-hand.
- **Action** column on alerts — quick replenishment link.
- **Distribution** view — which locations hold the bulk of stock.

8. Quality sub-tab

Outcomes, incidents, and patient satisfaction.

Cards

- **Readmission · 30-day** — % of patients readmitted within 30 days.
- **Satisfaction proxy · 90d** — derived satisfaction score ("Built from attended / no-show / cancelled mix").
- **Quality alerts** list — open alerts with severity, age, and click-through.
- **Incidents · last 90 days** — incident register with Date, Severity, Category, Type, Subject, Tracking #, Stage.
- **Open incidents** counter.
- **Open** click-through on every alert row.

- **Open incident #** click-through on every incident row.
- **Attendance** breakdown that feeds the satisfaction proxy.

9. CRM sub-tab

Acquisition and growth.

Cards

- **Opportunity funnel** — funnel chart from Lead → Contact → Quote → Won.
- **Open opportunities** counter.
- **Pipeline value** — sum of open opportunity values.
- **Referral sources · 90d** — where new patients come from (advertising channel, doctor referral, walk-in, online ...).
- **New patients · last 12 months** — monthly bar chart.
- **Campaigns** list — campaign name, Sent count, Responses count, Response rate %.
- **Active campaigns** counter.
- **Status** column on campaigns.
- **Open <opportunity / campaign>** click-through on every row.

10. Common card features (every sub-tab)

- **Card head** strip with icon + title + meta info (period, units).
- **Sparklines** with hover tooltips and min/max y-axis labels.
- **Delta chips** — green up, red down, grey flat — wherever a number compares against a previous period.
- **Empty state** messages — every card handles a no-data case with a friendly italic message ("No billing activity in the last 30 days.").
- **Click row / open record** is universal — every list row has a click target to the source record.
- **Period labels** — visible *vs yesterday*, *vs last week*, *last 30 days*, *MTD*, *90d*, *12 months* — so a tile is never ambiguous about its window.

11. Customisation

- **Card show / hide** per user, per sub-tab.
- **Sub-tab order** — fixed; cannot be re-ordered.
- **Auto-refresh interval** — configurable per clinic.
- **Currency** — drives the unit chip on monetary KPIs; falls back to SAR.
- **Sub-tab visibility** — administrators can hide entire sub-tabs for users whose role does not need them (e.g. hide CRM from clinical staff).

12. Permissions

- **View access** — controlled per sub-tab on the user role (Overview / Schedule / Census / Billing / Physicians / Inventory / Quality / CRM).
- **Drill access** — a user can see a KPI without necessarily having permission to open the underlying record; in that case the click is suppressed.
- **Hide-card preferences** are per-user and do not affect anyone else.

13. Performance & freshness

- KPIs and lists come from **live aggregates** — no batch wait.
- **Auto-refresh** keeps the dashboard current without reloading the page.
- **Heavy charts** (sparklines, funnels) re-render only on data change to keep the page responsive.
- **Live data fall-back** — if a feed isn't provisioned yet, the dashboard renders sensible placeholder values instead of breaking, with a small note.

14. Quality-of-life

- **Single-page** — no nested screens; everything fits in one scroll.
- **Tooltips everywhere** — hover any chart point, KPI value, or delta chip to see the formal definition.
- **Show less / Show more** on long lists.
- **Language follows login** — every label and tooltip is translated to your interface language.
- **Wall-display friendly** — the dashboard runs full-screen on a TV without UI clipping.

→ Continue to [Overview sub-tab](#) or jump to any other sub-tab in the left nav.

Overview

The default sub-tab — the manager's "everything in one glance" view.

What you see

Two cards stacked vertically:

Headline KPIs

A six-tile strip:

Tile	Meaning	Comparison
Revenue today	Money invoiced so far today, in the clinic's configured currency.	vs yesterday
Appointments	Bookings on the schedule today.	vs same day last week
Waiting now	Patients currently in the waiting room (live count).	—
No-show rate	% of bookings missed over the last 7 days.	vs previous 7 days
Bed occupancy	% of inpatient beds full right now. Caption shows <i>busy / total beds</i> .	—
Claims accepted	% of insurance claims accepted in the last 30 days.	vs previous 30 days

Each tile shows:

- A coloured icon.
- The **label** in small caps.
- The **value** with its **unit**.
- A **delta chip** — green up, red down, grey flat — when a comparison is defined.
- A short **footer caption** clarifying the period or the denominator.

Revenue · last 30 days

A daily-totals sparkline:

- Filled area under a line for visual trend.
- **Dots** on the first day, last day, and every 7th day, with a hover tooltip showing date + amount.
- **Y-axis** labels — min and max values.
- **X-axis** labels — start date, mid date, end date.
- **Empty state** — "No billing activity in the last 30 days."

What you do with it

- **First check** of the morning — five seconds tells you whether today is on track.

- **Hover the deltas** for the formal comparison period.
- **Click any KPI tile** to drill into the underlying list (the appointments, the no-shows, the beds, the claims).
- **Hover any sparkline dot** to read the exact day's revenue.

→ Continue to [Schedule](#).

Schedule

The day's appointment grid in dashboard form — what's booked, what arrived, what was missed, who is on duty.

Date navigator

A small bar at the top:

- **Previous day** — step back one day.
- **Today** — jump to today (also titled *Jump to today*).
- **Next day** — step forward.
- **Refresh** — re-pull the data.

The date drives every counter and the heat-strip below.

Status counters

A row of compact tiles, each with an icon and the count for the selected day:

Counter	Hover tooltip	Meaning
Booked	<i>Total booked today</i>	Every appointment, all statuses included.
Scheduled	<i>Newly scheduled, not yet confirmed</i>	Just-booked, awaiting confirmation.
Confirmed	<i>Confirmed bookings</i>	Patient confirmed (e.g. by SMS reply).
Arrived	<i>Patients who have arrived</i>	Checked-in at reception.
Attended	<i>Completed visits</i>	Patient seen and visit closed.
Cancelled	<i>Cancelled / deleted</i>	Cancelled or removed.
No-show	<i>No-shows</i>	Patient did not turn up.
Free	—	Slots still open for new bookings.

Heat-strip

A horizontal strip representing the whole day, one cell per booking slot:

- **Cell colour** = status (matches the status counters).
- **Cell content** = patient's initial.
- **Hover tooltip** = patient name + physician + time + status.
- **Click a cell** = open that appointment.

This is the fastest way to see "where are the gaps" or "who is in chair 3 at 11:00".

Physicians on duty

A side panel listing the physicians working that day:

- Each row shows the physician's name + a compact mini-counter (booked / attended / no-show).
- **Show less / Show more** when the list is long.
- **Click a physician** → opens their full record.

What you do with it

- **Morning huddle** — open the heat-strip on the wall, walk the team through the day in 30 seconds.
- **Mid-morning sanity check** — *Arrived* counter should be tracking *Confirmed*; large gap → someone is slow at check-in.
- **End of day** — *No-show* count is your hit-list for next-day reminder calls.

→ Continue to [Census](#).

Census

Inpatient occupancy and discharge planning — the bed-side of the clinic.

Cards

Occupancy

A radial / percentage card showing the % of beds full right now, with:

- The exact **Occupied** and **Free** bed counts.
- **Admits today** counter.
- **Discharges today** counter.
- **Free beds** total across all wards.

Wards

A per-ward breakdown:

Column	Meaning
Ward	Ward name.
Occupied	Beds currently in use.
Free	Beds available for admission.
Available	Free beds that are <i>also</i> clean and ready.

Use this when reception calls asking "*do we have a bed in paediatrics?*" — the answer is in this card.

Bed map

A visual grid of every bed across every ward:

- **Cell colour** = bed status (occupied / free / cleaning / blocked).
- **Click a bed** = opens the admission record (if occupied) or a blank admission form (if free).
- The map respects ward groupings so adjacent beds in the same room stay adjacent in the map.

Discharge queue · next 48h

A list of patients planned to leave in the next two days:

Column	Meaning
Patient	Name.

Column	Meaning
Ward	Where they are now.
LOS	Length of stay so far.
Discharge by	Planned discharge date / time.
Complaint / Note	Reason for admission + any planning note.

Each row has an **Open admission #** link → opens the full admission record. Use this list to drive the daily discharge huddle.

What you do with it

- **Bed-managers** — the bed map answers "do we have a bed" in two seconds.
- **Discharge planners** — the queue is their work list for the next two days.
- **Clinical leads** — Occupancy + Admits/Discharges tell you whether the in/out flow is balanced.

→ Continue to **Billing**.

Billing

Cash flow at a glance — revenue, A/R, claims, top items.

Headline counters

- **Revenue today** — same KPI as the Overview tab, repeated here so you don't have to leave Billing.
- **MTD average bill** ("Avg ticket") — average bill size month-to-date.
- **A/R outstanding** — total amount currently owed by patients and payers.
- **Severely overdue** — A/R aged past the configured threshold — this is the at-risk number.

Every monetary value uses the configured clinic currency (defaults to **SAR** if not set).

Cards

Revenue · last 30 days

A daily-totals sparkline with hover tooltips, identical in style to the Overview tab — drawn here in larger size with extra detail.

A/R aging

Four buckets — **0–30, 31–60, 61–90, 90+ days** — shown as horizontal bars with the exact amounts. A **Outstanding only** toggle hides bills that have already been settled to keep the chart focused on the at-risk piece.

Top revenue items · 90d

A leaderboard of the highest-revenue service codes over the past 90 days:

Column	Meaning
Item	Service / procedure name.
Volume	Number of times invoiced.
Revenue	Total money under this code.

Each row has an **Open** link → opens the item / service record.

Claim status · 60d

A breakdown of insurance claims submitted in the last 60 days:

- **Accepted** — paid in full.

- **Pending** — awaiting payer decision.
- **Rejected** — declined; needs resubmission or write-off.
- **Re-submitted** — second pass currently in review.

Each segment is clickable → opens the claim list pre-filtered to that status.

What you do with it

- **Daily cash check** — Revenue today + Avg ticket give you the daily cash-velocity in five seconds.
- **Receivables triage** — A/R aging + Severely overdue identify the bills that need a phone call this week.
- **Service-mix view** — Top revenue items shows what is *actually* paying the clinic's bills, vs what management *thinks* is.
- **Claims chase** — Claim status flags how many claims are stuck in Pending and how many got Rejected.

→ Continue to **Physicians**.

Physicians

Per-physician productivity, today and month-to-date.

Date navigator

Same controls as the Schedule sub-tab — **Previous day**, **Today** (jump back), **Next day**, **Refresh**.

Physician scorecard · today

One card per physician on duty:

Today's counters

Counter	Meaning
Booked	Total appointments scheduled.
Pending	Booked but not yet confirmed.
Arrived	Patients checked in.
Done ("Attended")	Visits completed.
Cxl	Cancelled.
No-show	Patient did not arrive.
Utilization	% of bookable hours filled — chair efficiency for the day.

Month-to-date counters

- **Patients MTD** — distinct patients seen this calendar month.
- **Revenue MTD** — money invoiced under this physician this month, in the clinic currency.

Row actions

- Click the physician's name → **Open 's record** — opens the full physician profile.
- Empty state — *"No appointments today"* when a physician has a blank day.

List controls

- **Sort** — pick the metric to rank physicians (utilization, revenue, patients, ...).

- **Show less / Show more** — collapse to top N or expand the full list.

What you do with it

- **Daily huddle** — quickly see who is busy and who has spare slots.
- **Re-balance load** — find physicians with low utilization while another is over-booked; redirect walk-ins.
- **Monthly review** — Revenue MTD and Patients MTD are the right numbers for the end-of-month sit-down.
- **Performance conversations** — the per-physician card is the evidence the medical director brings to the chat.

→ Continue to [Inventory](#).

Inventory

Stock visibility for the clinic — what's full, what's empty, what's about to run out.

Headline counters

- **In stock** — items above their minimum threshold.
- **Low stock** — items below minimum but above zero.
- **Out of stock** — items at zero on-hand.
- **Total items** in the catalogue.
- **Stock value** — current inventory value in the configured currency.
- **Critical alerts** count — items that need attention right now.

Cards

Stockout risk

Items currently at zero or trending to zero in the next few days:

Column	Meaning
Item	Item / SKU name.
Location	Where the stock should be.
On hand	Current quantity.
Min	Minimum threshold.
Action	Quick replenishment link.

Stock by location

A per-location breakdown — chair, pharmacy, store, fridge, ...:

- Counts of items per location.
- **Distribution** view shows the share of stock held at each location (useful for asking "*why is so much stock locked in the back store?*").

Low-stock alerts

A list of every item below its minimum threshold, sorted by severity:

- **Item** name.
- **On hand** vs **Min** with a visual **Stock vs min** bar.

- **Location** of the deficit.
- Click **Open** → opens the item record.

Top movers · last 90 days

Leaderboard of items by consumption:

- **Volume** — how many units used.
- **Revenue** — money invoiced under this item (when it is also a billable service).
- Toggle between Volume and Revenue.
- Click **Open** → opens the item record.

What you do with it

- **Morning stock check** — In stock + Low stock + Out of stock answer "are we safe to open today".
- **Replenishment list** — Stockout risk + Low-stock alerts is the buyer's work list for the day.
- **Allocation tuning** — Stock by location shows whether you're hoarding in the store while running empty in the chair.
- **Catalog cleanup** — Top movers tells you what to keep stocking and what is dead weight.

→ Continue to [Quality](#).

Quality

Outcomes, incidents, and patient satisfaction — the soft side of clinical operations.

Cards

Readmission · 30-day

A radial / percentage card showing the share of discharged patients who came back as inpatients within 30 days.

- The lower, the better.
- A short caption explains the formula.
- Click the card → opens the list of readmitted patients.

Satisfaction proxy · 90d

A derived satisfaction score using the **attended / no-show / cancelled mix** as a proxy for whether the clinic is delivering what patients showed up for.

- A higher attended rate and a lower no-show + cancel rate → higher proxy score.
- The card carries the explanatory tag "*Built from attended / no-show / cancelled mix*" so users know what they are looking at.
- **Attendance** breakdown shown alongside.

Quality alerts

A list of currently-open quality alerts:

Column	Meaning
Title	Short description.
Severity	High / Medium / Low.
Age	How long the alert has been open.
Status	Open / Acknowledged / Resolved.

Click **Open** → opens the alert detail.

Incidents · last 90 days

The clinical-incident register for the last 90 days:

Column	Meaning
Date	When the incident happened.
Severity	Severity rating.
Category	Incident category (Medication, Fall, Equipment, ...).
Type	Sub-type within the category.
Subject	Short title.
Tracking #	The incident reference number.
Stage	Where it is in the workflow (Reported, Under review, Closed).

Click **Open incident #** → opens the incident record.

Plus a top-line **Open incidents** counter.

What you do with it

- **Weekly quality huddle** — Readmission rate + Open incidents + Quality alerts is the agenda.
- **Trend watch** — sudden change in the satisfaction proxy is your first leading indicator that something is off (often before patient complaints reach you).
- **Incident triage** — sort by severity, click into anything red.

→ Continue to [CRM](#).

CRM

Acquisition and growth — where new patients are coming from, how the sales / referral pipeline looks, what campaigns are running.

Cards

Opportunity funnel

A funnel chart from top to bottom:

- **Lead** — initial enquiry.
- **Contact** — engaged.
- **Quote** — formal quote / treatment plan presented.
- **Won** — converted to a paying patient.

Each step shows the count and the drop-off vs the previous step. Click any step → opens the opportunity list at that stage.

Top-line counters

- **Open opportunities** — count of opportunities still in the pipeline.
- **Pipeline value** — sum of the open opportunity values, in the configured currency.

Referral sources · 90d

Where new patients came from over the last 90 days:

- Advertising channels (Instagram, Google, billboard, ...).
- Doctor referrals (specific referring doctor or clinic).
- Walk-ins.
- Online self-booking.

Shown as a horizontal bar chart with counts. Click any bar → opens the patient list for that source.

New patients · last 12 months

A monthly bar chart showing the count of brand-new patient files created per month over the last 12 months. Use this as the *acquisition pulse* — flat or trending up is healthy.

Campaigns

A list of marketing campaigns:

Column	Meaning
Campaign	Name.
Sent	Messages / contacts sent.
Responses	Replies / clicks / bookings (depending on type).
Response rate	Responses ÷ Sent, as %.
Status	Active / Paused / Ended.

Plus an **Active campaigns** counter at the top.

Click **Open** on any row → opens the campaign record.

What you do with it

- **Weekly growth review** — Open opportunities + Pipeline value tell you what's coming.
- **Marketing ROI** — Campaign response rates tell you which channels to double down on.
- **Source mix** — Referral sources reveals whether you depend too heavily on one channel.
- **Acquisition health** — the 12-month chart is the leading indicator of revenue 6–12 months from now.

→ Back to [Overview](#) or jump to [Features](#) for the full categorised feature catalogue.

Administration

What the clinic administrator can configure on the Clinic Dashboard.

Sub-tab visibility per role

Each of the eight sub-tabs (Overview, Schedule, Census, Billing, Physicians, Inventory, Quality, CRM) can be turned on or off per user role:

- **Clinical roles** typically see Overview, Schedule, Census, Physicians, Quality.
- **Finance / billing roles** typically see Overview, Billing, optionally CRM.
- **Front desk** typically see Overview, Schedule.
- **Clinic manager / director** sees everything.

Turn off any sub-tab a role does not need — a smaller dashboard is a faster, less confusing dashboard.

Card show / hide

Inside each sub-tab, every card can be hidden by the user via right-click → *Hide this card*. Preferences are per user and persist across sessions. The administrator does not need to push these — let each user tune their own page.

Currency

The dashboard reads the clinic's configured currency to label every monetary tile and to format every amount. Set it under **Clinic Settings** → **Currency**. If unset, the dashboard falls back to **SAR**.

Auto-refresh interval

How often the dashboard re-pulls live numbers. Defaults to a few minutes. Tune up for high-traffic dashboards (wall displays) or down for slow networks.

Demo data

For new installs and training environments, the **Fill Demo Data** action seeds plausible numbers into the underlying tables so the dashboard renders meaningfully on day one. Turn it off (and clear the demo data) before going live.

Wall-display mode

The dashboard runs full-screen on any modern browser. For a permanent wall display:

- Open the dashboard URL in full-screen (F11).
- Pin the **Overview** or **Schedule** sub-tab.
- Set the browser to keep the tab awake.
- Auto-refresh keeps the numbers fresh without manual intervention.

Permissions

Beyond visibility, drill-down clicks respect the user's permission on the underlying record. A user can see "23 no-show appointments today" without necessarily being able to open one — in that case the click is suppressed.

Patient Dashboard

The **Patient Dashboard** is the patient's single-page summary — every clinically and administratively important fact about the patient, organised into ten tabs, available from any screen that already has a patient selected.

It is the screen the doctor opens before walking into the room, the screen the receptionist uses to answer "*what does this patient owe?*" in two seconds, the screen the case manager uses to chase a pending lab result, and the screen the cashier uses to send a statement on WhatsApp.

What you get on one page

- The patient's **photo, identity, contact, emergency contact**.
- Their **insurance** coverage and outstanding **balance**.
- Their **vitals, allergies, active problems, active medications**.
- Every **visit, prescription, lab test, imaging study, immunization, referral** they have ever had.
- Every **treatment plan** with its stages, procedures, and costs.
- Their full **document** library (X-rays, consents, scanned IDs, reports).
- Their **upcoming appointments** with a one-click booking dialog.

How to open it

Wherever a patient appears in HMS — clinic reception, the scheduler, search results, the admission list — clicking the patient's name or photo opens the Patient Dashboard for that patient.

The ten tabs

Tab	What it covers
Profile	Demographics, identity, contact, guarantor — the single-row reference card.
Clinical	Vitals, allergies, active problems, prescriptions, visit history.
Care Plan	Treatment plans, procedures, stages, mini dental chart.
Appointments	Past + upcoming; book / reschedule / cancel; find available slots.
Lab/Imaging	Lab tests (orders + results).
Imaging	Radiology requests + results + latest image preview.
History	Immunisations, family history, social history, referrals, encounter history.
Documents	Embedded document gallery with upload, view, annotate, compare.
Billing	Bills, payments, balance, refunds, statement, WhatsApp / email send.
Insurance	Coverage, contracts, claims history, sent / accepted / rejected.

Each tab is detailed on its own page in the left sidebar.

See also

- **Features** — every Patient-Dashboard feature in one exhaustive categorised list.

- **Getting Started** — a typical 60-second review of a patient before they walk in.

Getting Started

A typical 60-second patient review before they walk into the room.

1. Open the dashboard

Click the patient's name anywhere in HMS — reception, scheduler, search, the wait-list. The dashboard opens on the **Profile** tab.

2. The photo + identity strip

A photo on the left, the name, file number, date of birth (Gregorian

- Hijri), age, gender, blood group, nationality, and a *VIP* dot if applicable. Take three seconds to register who you're about to see.

3. Glance the badges

The header strip shows badges for anything you must not miss:

- Known allergies (with the allergen on hover).
- Pending balance over threshold.
- VIP.
- Care alerts (flagged from a previous visit).

4. Jump to the clinically relevant tab

- Walk-in / acute → **Clinical** (vitals, allergies, active problems, current medications, last visit summary).
- Follow-up → **Care Plan** (where in the treatment plan they are).
- Lab / X-ray review → **Lab/Imaging** or **Imaging**.
- Financial question → **Billing**.
- Insurance / authorisation → **Insurance**.
- Anything else from the past → **History** or **Documents**.

5. Take action without leaving the page

Every list has small + buttons on the right:

- + **Vital** — record a new vital sign reading.
- + **Prescription** — write a new prescription.
- + **Lab test** — order a new lab test.
- + **Imaging** — order a new radiology study.
- + **Document** — upload a file directly into the patient's gallery.
- + **Bill / Payment** — open the new-bill or new-payment dialog.
- + **Appointment** — book the next visit from the embedded scheduler.
- + **Immunisation / Referral / Family member** — under the **History** tab.

6. Drill in only if you need to

Most rows link to the full form behind them — click any visit, prescription, lab order, imaging study, bill, payment, claim, or treatment plan to open it in its native screen. Use the back button to come straight back to the dashboard.

7. Done

The dashboard remembers which tab you were last on, per patient — open the next patient and you start on **Profile** again unless you choose otherwise.

→ Continue to the **Profile tab** or jump to the **Features** catalogue.

Features

Every feature of the Patient Dashboard, grouped by what it lets you do. Exhaustive but not technical — use it as a training checklist or a gap analysis against another system.

1. Identity & Demographics

- Patient photo (avatar with fallback initials).
- Full name.
- Salutation (Mr / Mrs / Dr / ...).
- File / MRN number.
- Gender.
- Date of birth — Gregorian.
- Date of birth — Hijri.
- Computed age (years / months / days as appropriate).
- Blood group.
- Marital status.
- Nationality.
- Religion.
- National ID — type and number.
- Passport — number, issue place, issue / expiry dates.
- Visa number.
- VIP flag.

2. Contact

- Mobile phone.
- Landline / phone.
- E-mail address.
- Address (home).
- P.O. Box.
- Employer.

3. Emergency / Next-of-kin

- Salutation.
- Name.
- Relation.
- Phone.
- Mobile.
- Address.

4. Insurance & Guarantors

- Primary guarantor — name, contract, network, class.
- Secondary guarantor — same set of fields.

- Self-insured flag.
- Coverage tier / class.
- Currency.
- Latest admission coverage card.
- Edit primary coverage shortcut.
- Edit secondary coverage shortcut.
- Click-to-set-up coverage when none is on file.
- Claims history list — Pending, Sent, Accepted, Rejected, with counts and totals.
- Open the latest admission to add / edit a claim.

5. Vitals

- Last N readings of each vital sign.
- Per-reading badge — Normal / Borderline / Low / High / Markedly high.
- Date and time of each reading.
- Free-text note on each reading.
- - Vital — record a new reading.
- Visual sparkline / trend bar per vital.
- Height, Weight, BMI (computed), Area (BSA, computed).

6. Allergies

- Known allergies list.
- Severity & type (drug / non-drug).
- Reaction description.
- Source (chart / by whom).
- Last-reviewed date.

7. Active Problems

- Problem list with diagnosis codes.
- Onset date.
- Status (Active / Resolved / Recurrent).
- Priority.
- Diagnosing physician.
- Free-text notes per problem.

8. Prescriptions / Active Medications

- Active medications list.
- Past prescriptions list (with show-more toggle).
- Drug name, dose, frequency, duration.
- Prescribing physician.
- Start / end date.
- Source visit / encounter.
- Refill flag.

- - Prescription — write a new one.

9. Visit / Encounter History

- Chronological list of every visit.
- Visit date, physician, department, type (OP / IP / ER / dental / ...).
- Chief complaint / reason.
- Diagnosis from the visit.
- Click a visit to open its full record.

10. Care Plan (Treatment Plans)

- List of all treatment plans for the patient.
- Plan name, status, total estimated cost, total paid.
- Per-plan progress bar.
- Per-procedure list — tooth, treatment, dentist, planned date.
- Procedure stages — Planned / Existing / Pre-existing / Done / Cancelled.
- Status badges: **Planned**, **Existing**, **Procedures already completed**, **Procedures still to be performed**, **Existing procedures (pre-existing condition records)**.
- - Treatment Plan — create a new plan.
- Open the full Treatment Plans panel.
- Mini dental chart embedded inline.
- Click a tooth to open the full dental chart.

11. Dental Chart Snapshot

- Read-only thumbnail of the patient's current chart state.
- Per-tooth marks (caries / fracture / treated / missing / ...).
- Click any tooth → open the full dental chart for that tooth.
- "Open full" button → full-page chart.

12. Appointments

- Upcoming appointments list with status.
- Past appointments list (collapsible).
- Next-upcoming highlight at the top.
- "No upcoming appointment" empty state.
- Per-appointment actions: Attend, Reschedule, Set status, Remind.
- Set status — No-show, Confirmed, Arrived, In-Service, Completed.
- WhatsApp / SMS reminder.
- Book an appointment dialog:
 - Pick a physician.
 - Pick a speciality.
 - Filter by day shift / window / duration.
 - Mini calendar — green days have availability.
 - Available-slots list (Find available slots).

- Confirm to commit.
- Show more / show fewer toggle.
- "Past" and "Upcoming" segmented filter.

13. Lab Tests

- List of lab orders + results.
- Sample-collection workflow indicators (Q = request closed, C = sample collected, R = sample received, P = reply closed).
- Latest results panel.
- Per-test serial number.
- Click row to open the lab request.
- ◦ Lab test — order a new test.

14. Imaging / Radiology

- Latest imaging study with thumbnail.
- Click thumbnail to view in the document viewer.
- Imaging requests list (open / in progress / completed).
- Imaging results list.
- Open the radiology request the image belongs to.
- ◦ Imaging — order a new study.
- Per-image description / physician.
- Direct link into the source admission for context.

15. History — Immunisations

- Vaccine dose list.
- Date of administration.
- Vaccine name.
- Site (left arm, right arm, ...).
- Lot / batch number.
- Administrator (nurse / physician).
- Notes per dose.
- ◦ Vaccine dose.
- Edit this vaccine dose.

16. History — Family

- Family member list with relation.
- Per-member health background (genetic, chronic conditions).
- Edit family + add a member.
- Edit this family member.

17. History — Social

- Smoking status.
- Alcohol consumption.
- Substance use.
- Occupation / risk exposure.
- Marital / living arrangement notes.
- Edit social history.

18. History — Referrals

- Referrals to / from other practitioners.
- Reason for referral.
- Referring / receiving clinician.
- Date.
- Status.
- - Referral.
- Edit this referral.

19. Documents

- Embedded **Document Manager (DM2)** gallery scoped to the patient.
- Upload by drag-and-drop or file picker.
- View any file type (PDF, Word, Excel, images, videos, DICOM, ...) in the unified viewer.
- Annotate, measure, compare images.
- Categories, tags, keywords on every document.
- Search across the patient's library.
- - Document — add a new file.
- Open Patient Documents header link to the full DM2 view.

20. Billing

- List of bills with status badge.
- Bill total, patient share, insurer share.
- Per-bill physician / diagnosis label.
- Per-bill date.
- Payments list.
- Per-payment number, date, method, amount.
- Patient balance — current outstanding.
- Counts strip — number of bills / payments / refunds.
- - Bill — create a new bill.
- - Payment — record a new payment.
- Refund — record a refund.
- Click a bill to open it in the bill editor.
- Click a payment to open it in the payment editor.

21. Statement & Communication

- Open statement (printable).
- Email the patient statement.
- Send statement via WhatsApp.
- Statement totals — total submitted, total estimated, grand total.

22. Insurance Coverage (panel)

- Primary coverage card — insurer, network, plan, validity, copay.
- Secondary coverage card — same.
- Add primary coverage CTA (when missing).
- Add secondary coverage CTA (when missing).
- Edit patient coverage shortcut.
- Latest admission coverage with policy + class.

23. Claims

- Claims history list (all claims for this patient).
- Per-claim status — Pending, Claim sent, Accepted, Rejected.
- Per-claim totals — submitted, accepted, rejected, net.
- Click to open the originating admission.
- Open the latest admission to add or edit a claim.

24. Cross-tab Quick Actions (+ buttons)

A consistent + button on every list lets you create:

- New vital reading.
- New prescription.
- New lab order.
- New imaging order.
- New treatment plan.
- New bill.
- New payment.
- New appointment.
- New vaccine dose.
- New referral.
- New family member.
- New document.

25. Drill-down Links

Every row in every list is clickable and opens the originating record in its native screen:

- Visit row → visit form.
- Prescription row → prescription form.
- Lab row → lab request.
- Imaging row → radiology request / admission.
- Bill row → bill editor.

- Payment row → payment editor.
- Treatment plan row → plan editor.
- Tooth click → full dental chart.
- Document tile → DM2 viewer.
- Claim row → admission with claim panel.

26. UI Quality-of-life

- Per-list **Show all / Show fewer** toggle.
- Per-list **Search** filter.
- Tooltip on every status badge.
- Tooltip on every micro-icon (alerts, flags).
- Tooltip on every clickable row explaining what will open.
- Esc closes any opened drill-down dialog.
- Mobile-friendly — the dashboard re-flows to a single column on small screens.
- Empty-state messages on every list ("No appointments on this day.", "No upcoming appointment", "No diagnosis", "No description", "Not done", ...).
- Per-tab last-position memory.
- Avatar fallback when no photo is uploaded.

27. Permissions & Read-only Mode

- Sensitive sections (insurance, billing) hide their + buttons for users without the right role.
- Read-only mode hides every Edit / Create control.
- Cashiers see Billing & Insurance + read-only Clinical / History.
- Physicians see everything except + on bills (depends on clinic policy).

28. Integration Points

The Patient Dashboard is a single page but every section delegates to another HMS module:

Section	Powered by
Documents	Document Manager (DM2)
Appointments	Scheduler V2
Vitals / Allergies / Problems / Meds	Clinical EMR
Care plans + chart	Dental / Treatment-plan engine
Lab tests	Laboratory module
Imaging	Radiology / PACS module
Billing & Payments	Billing engine
Insurance & claims	Insurance / NPHIES module
History (immunisations, family, social, referrals)	EMR longitudinal record

Every embedded section keeps the look of the dashboard — you don't notice you're crossing module boundaries.

→ Continue to the [Profile tab](#).

Profile

A single-page reference card for the patient — everything you would write on a hospital wristband, plus contact and guarantor.

Sections

Identity strip

Photo · Name · MRN · Salutation · Gender · Date of birth (Gregorian and Hijri) · Age · Blood group · Marital status · Nationality · Religion.

Documents

National ID — type + number · Passport number, issue place, issue date, expiry date · Visa number.

Contact

Address · Phone · Mobile · E-mail · P.O. Box · Employer.

Emergency (SOS) contact

Salutation · Name · Relation · Phone · Mobile · Address.

Insurance summary

Primary guarantor · Secondary guarantor · Self-insured flag · Latest admission coverage · Patient balance.

What you can do

- Open the patient's main file (full edit) from the header.
- Click the photo to enlarge.
- Every field is **read-only** here — use the patient file or the insurance form for edits. The Profile tab is the trusted summary card, not the editor.

→ Continue to [Clinical](#).

Clinical

Four cards stacked on one page — the clinician's pre-visit briefing.

1. Vitals

- Last several readings for every vital sign on file (BP, pulse, temperature, SpO₂, respiratory rate, weight, height, BMI, BSA).
- Each reading carries a band: Normal / Borderline / Low / High / Markedly high — colour-coded.
- Date and time of each reading.
- Free-text note per reading.
- + **Vital** opens the new-reading dialog.

2. Known Allergies

- List of drug and non-drug allergies.
- Severity and reaction description on hover.
- Edit and remove per row.

3. Active Problems

- Diagnosis code + label.
- Onset date.
- Status (Active / Resolved / Recurrent).
- Priority.
- Diagnosing physician.
- Notes per problem.

4. Prescriptions

- Active medications listed first.
- Past prescriptions accessible via *Show more*.
- Each line: drug, dose, frequency, duration, prescribing physician, start / end date.
- + **Prescription** writes a new one with the patient pre-filled.

5. Visit History

- Chronological list of every visit (newest first).
- Date, physician, department, type, chief complaint, diagnosis.
- Click any row to open the visit in its native form.

→ Continue to **Care Plan**.

Care Plan

The longitudinal treatment plan for the patient — every procedure that was proposed, performed, or pre-existing — plus a mini dental chart.

Treatment plans list

- Every plan for the patient, with status, total cost, total paid, and a progress bar.
- **All plans** filter / segmented control.
- Click any plan to open the full plan editor.
- **+ Treatment Plan** creates a new plan.

Per-plan procedure grid

- Tooth (or area).
- Treatment.
- Dentist.
- Planned date.
- Estimated cost.
- Stage badge:
 - **Planned** — agreed, not yet started.
 - **Procedures still to be performed.**
 - **Procedures already completed.**
 - **Existing** — already in the mouth at the time the plan was drawn.
 - **Existing procedures (pre-existing condition records).**

Mini dental chart

- Embedded read-only chart showing the patient's current mouth state.
- Per-tooth marks (caries / treated / missing / fracture / ...).
- Click any tooth to open the **full dental chart** for that tooth.
- **Open full** button opens the full-page chart.

What you can do

- **Open the full Treatment Plans panel** — opens the dedicated treatment-plan workspace.
- **+ new plan**, new procedure inside a plan.
- Print a plan as a patient-facing quote.
- Mark stages done as procedures are completed.

→ Continue to [Appointments](#).

Appointments

Past, present, and future appointments for the patient — plus a booking dialog so you never have to leave the dashboard.

Lists

- **Next upcoming** — the very next appointment, highlighted at the top.
- **Upcoming** — all future appointments.
- **Past** — historical appointments (collapsed by default — *Show more*).
- Empty state — *No upcoming appointment*.

Each row shows date, time, physician, speciality, status (Pending, Confirmed, Arrived, In-Service, Completed, No-show, Cancelled).

Per-appointment actions

- **Attend** — mark the patient arrived.
- **Reschedule** — move to a new time.
- **Set status** — quick-set Confirmed / No-show / Cancelled.
- **Remind** — send WhatsApp / SMS reminder.

Book an appointment dialog

- **Pick a physician** — list filtered by patient's last clinician.
- **Pick a speciality** — filters the physician list.
- **Filters** — Day shift, Window, Duration.
- **Mini calendar** — green days have free slots.
- **Find available slots** — searches across the chosen window.
- **Available slots** list — click one to confirm.
- **Confirm** to commit, **Cancel** to abandon.

Tips

- Use **Show all / Show fewer** on the past list to keep the panel focused.
- Click any row to open the appointment in the scheduler.

→ Continue to [Lab Tests](#).

Lab Tests

Every lab order and result for the patient on one tab.

What you see

- **Lab Tests** list — most recent first, with date, test, ordering physician, sample status, result status.
- **Latest Results** card highlighting the most recent result.

Sample workflow indicators

A short status string on each row tells you exactly where the sample is in the pipeline:

- **Q** — request closed (order issued).
- **C** — sample collected.
- **R** — sample received by the lab.
- **P** — reply closed (results posted).

Each letter is a tooltip — *Request closed, Sample collected, Sample received, Reply closed*.

Actions

- Click any row to **open the lab request** in its native screen.
- **+ Lab test** — order a new test with the patient pre-filled.
- Latest serial number printed under each row for cross-reference.

→ Continue to [Imaging](#).

Imaging

Radiology orders and results for the patient — with a click-through to the radiology viewer.

Sections

Latest Imaging Study

The most recent image as a thumbnail with description, date, and ordering physician. Click the thumbnail to open it in the document viewer. Click the description to open the parent radiology request.

Imaging Requests

All radiology orders for the patient — open, in-progress, completed. Per-row: date, modality (X-ray, CT, MRI, US, ...), body region, clinician, status.

Imaging Results

Posted radiology results — with the report text and a link to the study.

Actions

- Click an image to view it.
- Click a request to open it in the radiology workspace.
- **+ Imaging** — order a new study with the patient pre-filled.
- "Open the radiology request this image belongs to" link on each result.

→ Continue to [History](#).

History

Background and longitudinal data that doesn't fit on the Clinical tab — five sections in one place.

1. Immunisations

- Vaccine dose list with date, vaccine name, site of administration, lot / batch, administering staff, notes.
- **+ Vaccine dose** — record a new dose.
- Edit / remove per row.

2. Family History

- Family member list with relation, health background, genetic notes.
- **Edit family + add a member.**
- Per-row **Edit this family member.**

3. Social History

- Smoking, alcohol, substance use.
- Occupation and risk exposure.
- Living arrangement and marital notes.
- **Edit social history.**

4. Referrals

- Referrals to and from external practitioners.
- Reason, referring clinician, receiving clinician, date, status.
- **+ Referral** — add a new referral.
- Edit per row.

5. Encounter History

- Full chronological list of every encounter (visits + admissions + ER + dental).
- Click any encounter to open its full record.

→ Continue to [Documents](#).

Documents

The patient's full document library — embedded directly in the dashboard.

What you get

The **Document Manager (DM2)** gallery scoped to this patient. Every feature of the standalone document manager is available here:

- Browse — grid, list, or timeline view.
- Search by title, tags, or keywords.
- Upload by drag-and-drop or file picker.
- Capture from camera (intraoral / UVC).
- View any file type (PDF, Word, Excel, PowerPoint, images, videos, audio, DICOM, archives) in the unified viewer.
- Annotate — pen, shapes, text, eraser; saved as a non-destructive layer.
- Measure — ruler, angle, polygon area, crosshairs.
- Compare — pin two or more documents side-by-side.
- Edit Word documents in-browser and save back.
- Categories, tags, keywords on every file.
- Soft-delete with recycle bin.
- Content-hash deduplication.

See [Document Manager \(DM2\)](#) for the full manual.

Quick header

- **+ Add Document** — quick upload.
- **Refresh** — re-pull the gallery.
- **Open full** — opens DM2 in its own window with the same patient context.

→ Continue to [Billing](#).

Billing

Bills, payments, balance — and the tools to send a statement on WhatsApp or by e-mail.

Counters

A top strip showing the lifetime totals — total billed, total paid, total refunded, current outstanding balance.

A "Who pays — lifetime billed" heading summarises payer breakdown (patient share vs insurer share).

Bills list

- Date, bill number, physician, diagnosis, total, patient share, insurer share, status.
- Status badge — Draft, Finalised, Paid, Submitted.
- Click any bill to open it in the bill editor.
- **+ Bill** — create a new bill (*Create a new bill*).

Payments list

- Date, payment number, method, amount, reference.
- Click any payment to open it in the payment editor.
- **+ Payment** — record a new payment (*Record a new payment*).
- **Refund** — record a refund (*Record a refund*).

Statement actions

- **Open statement (printable)** — opens the patient statement for printing.
- **Email the patient statement** — sends a PDF to the address on file.
- **Send statement via WhatsApp** — pushes the statement to the patient's WhatsApp.

Tips

- Use the bills filter / segmented control to limit to unpaid or to a date range.
- The patient balance figure here is the same one the **Profile** card shows — both come from the same source.

→ Continue to [Insurance](#).

Insurance

Coverage, latest admission coverage, and claims history.

1. Insurance Coverage

Two cards — primary and secondary.

Each card shows: insurer, plan, network, class, contract, currency, validity dates, copay, and a *Self-insured* flag where relevant.

- **Click to set up primary coverage** — CTA when missing.
- **Click to add secondary coverage** — CTA when missing.
- **Edit primary coverage / Edit secondary coverage** — open the coverage editor.
- **Edit patient coverage** — opens the patient's full insurance form.

2. Latest Admission Coverage

The coverage attached to the patient's most recent admission — useful when a question arises mid-stay about which policy is paying.

- Insurer, plan, class, contract.
- **Open this admission for editing** to drill into the admission.

3. Claims History

Every claim ever submitted for this patient — across every admission.

- Per-row: date, claim number, status, total submitted, total accepted, total rejected, net.
- Status badge — **Pending, Claim sent, Accepted, Rejected**.
- Click any row to open the originating admission with the claim panel.
- **Open the latest admission to add or edit a claim** header link.

→ See also the [Features](#) catalogue for the full list of dashboard capabilities.

Document Manager (DM2)

DM2 is the second-generation Document Manager — the page used to upload, browse, view, annotate, and compare every file attached to a patient, a visit, a tooth, or any other HMS record.

It replaces the legacy Document Manager with a faster gallery, a unified viewer for every common file type (PDF, Word, Excel, PowerPoint, images, videos, audio, DICOM, archives), an annotation layer that can be saved back to the patient record, a compare mode for before/after analysis, and direct camera capture from intraoral cameras and any UVC USB device.

How it shows up in the system

DM2 is **embedded** wherever HMS needs a file list — patient files, visit attachments, the dental-chart imaging tab, the lab-result panel, the consent-form library. The toolbar adapts to the context — inside the dental chart it becomes a single-tooth gallery; inside a patient file it shows the full patient timeline.

Quick map

- **Overview** (you're here) — what DM2 is.
- **Getting Started** — upload your first document.
- **Features** — full categorised list of every feature.
- **Using DM2** — one page per task (gallery, upload, camera, viewer, annotations, measurements, compare, editor, chart mode).
- **Administration** — categories & tags, storage, deduplication.

→ Continue to **Getting Started** or jump to the **Features** catalogue.

Getting Started

Upload your first document and view it in DM2 in under a minute.

1. Open a context that has DM2

DM2 is always embedded inside something — typically a patient file or the imaging tab of the dental chart. Open any patient and click the **Documents / Imaging / Attachments** tab — the page you see is DM2.

2. Drop a file in

The simplest way: drag a file from your file explorer **onto the gallery surface**. The upload starts immediately. A progress bar appears on the new tile.

Other ways:

- Click **Add document** (single file picker).
- Click **Import multiple** to upload several files with the same metadata (category, tags, ...) applied to all of them.
- Click **Capture from camera** to take a fresh photo (intraoral camera or any USB webcam).

3. Fill in the metadata

After upload, the **Edit** dialog opens so you can label what was just saved:

- **Title** — defaults to the file name; change it to something meaningful.
- **Description** — free text.
- **Category** — pick from your clinic's list (X-ray, Photo, Consent form, Lab result, ...).
- **Tags** — comma-separated keywords.
- **Keywords** — extra searchable words.

Click **Save**. The new tile shows your title and a category badge.

4. Open the viewer

Click the tile. The viewer fills the screen with the document. Depending on the file type you get:

- **Image / X-ray / DICOM** → zoom, pan, rotate, annotate, measure.
- **PDF** → page through, text-select, print.
- **Word / Excel / PowerPoint** → in-browser preview.
- **Video** → play / pause / scrub.

The toolbar across the viewer changes to match what makes sense for that file type.

5. Annotate or measure (optional)

- Click **Annotation tools** to draw, label, or shape on the document.
- Click **Measurement tools** for ruler, angle, polygon area.
- Click **Save annotations to the patient record** to keep your layer.

Annotations are stored separately — the original file is never modified.

6. Close

Press **Esc** or click the ✕ in the viewer corner. You're back on the gallery with your new document filed and ready to find by title, tag, or keyword.

→ See [Features](#) for the full catalogue of what DM2 can do, or [Gallery](#) for how to browse what's already there.

Features

Every DM2 feature, grouped by what it lets you do. Use this page as a checklist when training new users or evaluating gaps against another DMS.

1. Browse & Find

- **Grid view** — large thumbnails laid out in a responsive grid.
- **List view** — dense one-line-per-document rows for fast scanning.
- **Timeline view** — documents grouped by date, newest first.
- **Search** — by title, tags, or keywords. Live filter as you type.
- **Sort** — by date, title, type, or size.
- **Show / hide soft-deleted** — surface or hide files in the recycle bin without permanently removing them.
- **Multi-select** — tick several rows for bulk actions (delete, download, move to compare).
- **Dark / light theme toggle.**
- **Maximise** — DM2 fills the whole window for focus work.
- **Chart mode** — when embedded in the dental chart, DM2 narrows to *this tooth, grid view, capture/refresh only*.

2. Add Documents

- **Drag and drop** — drop one or many files from Explorer / Finder.
- **Add document** — file picker for single-file upload.
- **Import multiple** — multi-file picker with metadata applied to all at once (title template, category, tags, keywords, description).
- **Skip duplicate uploads (by content hash)** — refuses to upload the same file twice, even if it has a different name.
- **Capture from camera** — works with intraoral cameras and any UVC USB device. Live preview, click to capture, retake or save.
- **DICOM import** — DICOM files keep their metadata (patient, modality, series, study date) on import.

3. View — any file type

A single viewer surface handles all of:

Family	Formats
Images	JPG, PNG, GIF, BMP, TIFF, WebP
PDF	Native PDF rendering with text selection
Word	DOC, DOCX rendered in-browser
Excel	XLS, XLSX with sheet tabs

Family	Formats
PowerPoint	PPT, PPTX slide preview
Video	MP4, WebM, MOV with play / pause / scrub
Audio	MP3, WAV, OGG with play / pause
DICOM	Single-frame, multi-frame (cine), 3D series
Archives	ZIP — peek inside without extracting
Other	Generic file icon + download

4. Viewer — Navigation

- **Previous (←) / Next (→)** — page through every document in the current selection.
- **Frame strip** — for multi-frame DICOM, scroll or click any frame.
- **Cine play / pause** — auto-advance through DICOM frames at a configurable speed.
- **Mouse-wheel mode** — toggle between *zoom* and *scroll frames*.
- **Timeline** — pop the timeline overlay to jump back in chronological order without leaving the viewer.
- **Open in new tab** — pop the document out into its own browser tab.

5. Viewer — Transform

- **Rotate left / right** — 90° increments.
- **Mirror horizontal / vertical** — flip the image.
- **Zoom in / out** — wheel, pinch, or buttons.
- **Pan** — click-and-drag in cursor mode.
- **Reset view** — back to default rotation / zoom / pan.

6. Viewer — Annotations

- **Cursor mode** — click any annotation tool, then draw on the image.
- **Pen / freehand draw.**
- **Text labels.**
- **Shapes** — rectangle, circle, polygon, arrow.
- **Eraser** — remove a single annotation.
- **Save annotations to the patient record** — annotations are kept as a layer attached to the document; the original file is never modified.

7. Viewer — Measurements

- **Ruler** — straight-line distance, with auto-scale from DICOM pixel-spacing when available.
- **Combined ruler** — multi-segment measurement.
- **Angle** — three-point angle (e.g. for orthodontic analysis).

- **Crosshairs** — quick centre-cross for symmetry checks.
- **Polygon area** — closed-polygon area measurement.
- **Calibration** — re-calibrate pixels-per-mm if the source image has no DICOM scale.

8. Viewer — Image Filters

- **Brightness / contrast** sliders.
- **Inversion** — colour-invert (useful for X-rays).
- **Grayscale**.
- **Sharpen / blur** presets.
- **Window / Level** for DICOM — full radiology W/L control with modality presets (bone, soft tissue, lung).

9. Compare

- **Add to compare** — pin a document into a side-by-side compare panel.
- **Side-by-side or grid layout** — 2 / 3 / 4-pane comparison.
- **Synchronised zoom & pan** — move one image, the others move with it.
- **Remove from compare** — drop a document out of the compare set.
- **Common use case** — before-and-after orthodontic photos, baseline-vs-follow-up X-rays.

10. DICOM-specific

- **Multi-frame stack** — scroll through the whole series.
- **Cine playback** — play / pause / speed.
- **Mouse-wheel = scroll frames** mode.
- **DICOM metadata panel** — patient, modality, series, study date, acquisition parameters; toggle open/closed.
- **Window / Level** with modality presets.
- **Pixel spacing** auto-used for measurements.

11. Editor

The bundled in-browser editor lets you make light edits to common document types without leaving HMS.

- **Word documents** — open `.docx` and edit text, formatting, tables. Save back into the patient record.
- **Cancel edit** — discard unsaved changes.
- **Editor host** — full-screen mode for focused editing.

12. Output & Sharing

- **Print** — current document (or the annotated overlay).
- **Download original** — the untouched file as uploaded.
- **Open in new tab** — pop-out viewer for a second-monitor setup.

- **Refresh** — re-pull the gallery from the server.

13. Cataloguing

Each document carries:

- **Title** — defaults to the file name if empty.
- **Description** — free text.
- **Category** — Consent form, Lab result, X-ray, Photo, ... (configurable per clinic).
- **Tags** — comma-separated keywords, free-form.
- **Keywords** — extra searchable terms (often used for OCR'd content).

All five fields are searchable from the gallery search bar.

14. Safety

- **Soft delete** — deleted documents move to a recycle bin and can be restored. Hard delete needs admin permission.
- **Content-hash deduplication** — prevents accidental duplicate uploads of the same file.
- **Read-only mode** — when DM2 is embedded in a context the user has no write permission for, the upload / delete / edit controls are hidden entirely.
- **Annotations are non-destructive** — the original file is never modified.

15. UI quality-of-life

- **Keyboard shortcuts** — ← / → for prev/next, Esc to close.
- **Drag-and-drop everywhere** — drop into the gallery to upload, drag out of the gallery to download.
- **Density / theme** — comfortable vs compact rows; light vs dark.
- **Per-tooth chart mode** — automatic when embedded in the dental chart.
- **Loading spinners** for every async action.
- **Toast notifications** for save / delete / import results.

→ Continue to [Gallery](#) for the day-to-day browsing UI.

Gallery

The **gallery** is the main DM2 surface — the grid (or list, or timeline) of every document attached to the current record.

Layout

- **Toolbar** along the top — Add document, Import multiple, Capture from camera, Refresh, view-mode toggles, theme toggle, maximise.
- **Search bar** — type to filter by title / tags / keywords.
- **Category & type filters** — narrow by category, file type, date range.
- **Sort** — by date, title, type, size.
- **Tile area** — the documents themselves.

View modes

Mode	Best for
Grid	Visual browsing — thumbnails laid out in a responsive grid. Default for images, X-rays.
List	Dense scanning — one document per row with metadata. Best when looking for a specific filename.
Timeline	Chronological — documents grouped by date, newest first. Best for visit-by-visit review.

Toggle with the three view-mode buttons in the toolbar. Your choice persists per user.

Searching

The single search box matches against **Title**, **Tags**, and **Keywords** simultaneously. Type a fragment — the gallery filters live as you type.

Tips:

- Tag conventions pay off — agree on a clinic-wide tag list (e.g. *pre-op*, *post-op*, *consent*) and stick to it.
- For OCR'd documents (scanned consent forms, faxed lab results), put the most-searched phrases in **Keywords**.

Selecting

- **Click** a tile to open the viewer.
- **Tick** the checkbox on a tile to multi-select.
- **Shift-click** to select a range (in List view).

With multiple tiles selected, the toolbar offers bulk actions:

- **Add to compare** — pin the selection into the compare panel.

- **Delete** — soft-delete (recoverable from Show deleted).
- **Download** — zips the originals.

Soft-deleted documents

A toggle in the toolbar (**Show deleted**) reveals tiles for documents that have been soft-deleted. Each shows a *Restore / Permanently delete* link.

Permanent delete needs admin permission and is irreversible.

Maximise & dark mode

- **Maximise** — DM2 expands to fill the browser window. Click again (or press Esc) to return to embedded size.
- **Dark mode** — viewer background turns black; tile backgrounds turn dark grey. Easier on the eyes for radiology review.

Both settings persist per user.

Chart mode (automatic)

When DM2 is embedded inside the dental chart for a single tooth, the gallery simplifies to:

- Grid view only (no list / timeline).
- No search bar, no category / type filters, no import button.
- **Add, Capture from camera, Refresh, Dark mode** stay.
- A header strip shows *Tooth N* so it's clear which tooth you're attaching files to.

This is automatic — no setting required.

→ Continue to **Upload & Import**.

Upload & Import

Four ways to get files into DM2.

1. Drag & drop

The fastest path. Drag any file (or several files at once) from your file explorer onto the gallery surface. Upload starts immediately, a progress bar appears on each new tile. When done, the **Edit** dialog opens so you can fill in title / category / tags.

2. Add document

Click **Add document** in the toolbar — opens a standard file picker. Useful when drag-and-drop is blocked by the OS or you are uploading from a network share you have already navigated to.

3. Import multiple

Click **Import multiple** when you want to upload **many files** and apply the **same metadata** to all of them (e.g. 20 X-rays from the same study session).

The Import dialog has:

- A file picker that accepts as many files as you want.
- **Title** template — used for every file (or fall back to the file name if empty).
- **Description** — applied to all.
- **Category** — applied to all.
- **Tags** — comma-separated, applied to all.
- **Keywords** — comma-separated, applied to all.
- **Skip duplicate uploads (by content hash)** — recommended on. When ticked, files that are already in the patient's gallery (same content, regardless of file name) are skipped.

Click **Import** to upload them all, or **Cancel** to abort.

4. Camera capture

For live capture see [Camera Capture](#) — works with intraoral cameras and any UVC USB device.

Duplicate detection

DM2 hashes every file on upload. If the hash matches a file already in **this** patient's gallery, the upload is skipped (when *Skip duplicates* is on) or warned about (when it is off). The check is by **file content**, not file name — renamed copies are still detected.

Supported file types

DM2 accepts anything; specifically tested viewers exist for:

- Images: JPG, PNG, GIF, BMP, TIFF, WebP.
- PDF.
- Microsoft Office: DOC, DOCX, XLS, XLSX, PPT, PPTX.
- Video: MP4, WebM, MOV.
- Audio: MP3, WAV, OGG.
- DICOM (single and multi-frame).
- Archives: ZIP (peek inside without extracting).

Other file types upload fine and show a generic file icon with a **Download original** button.

Permission gates

- If the embedding context is **read-only**, the *Add / Import / Capture* buttons are hidden entirely.
- Per-user permission can restrict upload size (set in HMS user config).
- Per-user permission controls **hard delete** vs **soft delete**.

→ Continue to [Camera Capture](#).

Camera Capture

Capture photos directly from an **intraoral camera** or any **UVC USB device** (standard webcams included) without leaving HMS.

Open

Click **Capture from camera (intraoral / UVC)** on the gallery toolbar. The capture dialog opens, listing every camera the browser can see.

What you see

- **Camera picker** — every available capture device. Includes built-in laptop webcams, USB cameras, and intraoral wands.
- **Live preview** — the camera feed, scaled to fit the dialog.
- **Capture** button — grabs the current frame.
- **Retake** — discards the last capture and goes back to live.
- **Save** — keeps the captured frame and uploads it as a new document.

Workflow

1. Click **Capture from camera**.
2. Pick the camera from the dropdown — the dialog remembers your last choice per user.
3. The live preview starts.
4. Position the patient / tooth in the frame, click **Capture**.
5. Inspect the captured frame. Click **Retake** if you missed it, **Capture** again to take another, or **Save** to upload it.
6. Fill in metadata (title, category, tags) — same as a normal upload.

You can capture and save several frames in one session — Save returns you to the live preview ready for the next shot.

Camera permissions

The browser asks for camera permission the first time you click Capture. Allow it once and the prompt does not return for that workstation.

If the camera does not appear in the dropdown:

- The driver isn't installed — install the vendor driver for the intraoral wand.
- The camera is in use by another application — close it first.
- The browser blocked the camera site-wide — toggle the camera icon in the browser's address bar.

DICOM-aware capture

If the connected device is a DICOM-capable wand (some Sirona / Acteon units), DM2 captures **with full DICOM metadata** so the resulting file behaves like any other DICOM in the viewer (Window/Level, pixel spacing for measurements).

Chart mode

When DM2 is embedded in a single tooth's imaging tab, the captured frame is automatically tagged to that tooth — no extra step needed.

→ Continue to [Viewer](#).

Viewer

The DM2 viewer is a single surface that knows how to render every common file type — images, PDF, Office documents, video, audio, DICOM, ZIP archives. It opens when you click a document in the gallery.

The toolbar

The toolbar groups buttons into four areas — they show or hide depending on what the file supports.

Group	Buttons
Cursor	Cursor mode (pan / select), annotation tools, measurement tools, image filters, more tools
Transform	Rotate left, Rotate right, Mirror horizontal, Mirror vertical, Reset view
Save	Save annotations to the patient record
Output	Print, Download original, Open in new tab

Plus navigation arrows on the left / right edge for **Previous** (←) and **Next** (→) — they walk through every document in the current selection.

Cursor mode — click for menu

The default mode. Click **Cursor** in the toolbar (or just click on empty viewer space) to switch back to it from any tool. In cursor mode:

- **Drag** = pan the image.
- **Mouse wheel** = zoom (or scroll frames, in DICOM stack mode).
- **Pinch** on touch screens = zoom.
- **Click a tool from the toolbar** to enter annotation, measurement, or filter mode.

Image transforms

Button	Effect
Rotate left	90° anti-clockwise.
Rotate right	90° clockwise.
Mirror horizontal	Flip left ↔ right. Lights up when active.
Mirror vertical	Flip top ↔ bottom. Lights up when active.
Reset view	Removes all rotation, mirroring, zoom, and pan — back to default.

Transforms are **non-destructive** — the original file is untouched.

Frame navigation (DICOM and multi-frame)

When the document has multiple frames (DICOM stacks, multi-page TIFF):

- **Frame strip** along the bottom — click any frame thumbnail.
- **Mouse-wheel mode** — toggle between *zoom* and *scroll frames*. The current mode is shown in the toolbar info line: *Mouse-wheel: zoom* or *Mouse-wheel: scroll frames*.
- **Play / pause (cine)** — auto-advance through frames at a configurable speed.

File-type quick reference

Type	Tools available
Image	All annotation, measurement, filter, transform, compare
DICOM	All of the above + Window/Level + cine + DICOM metadata panel
PDF	Page navigation, text selection, print
Word / Excel / PowerPoint	In-browser preview, page / sheet navigation
Video	Play / pause, scrub, volume, fullscreen
Audio	Play / pause, scrub, volume
ZIP	Browse contents, extract any file to viewer
Other	Generic icon + Download original

→ Continue to [Annotations](#) or [Measurements](#).

Annotations

Annotations let the clinician mark up an image without changing the original. They are stored as a separate layer attached to the document — anyone re-opening the viewer sees the marks; downloading the original file gives the un-marked file.

Open the annotation tools

Click **Annotation tools** in the viewer toolbar. The tool palette slides open.

Tools

Tool	What it does
Pen / freehand draw	Click-and-drag to draw a freehand line.
Text label	Click to place a text box; type your label.
Rectangle	Click-and-drag to draw a rectangle outline.
Circle	Click-and-drag for a circle / ellipse outline.
Polygon	Click each vertex; double-click to close the shape.
Arrow	Click-and-drag from base to tip.
Eraser	Click any existing annotation to remove just that one.

Pick a tool, drop annotations on the image, then click **Cursor** to go back to pan / zoom mode.

Editing an annotation

- **Click** the annotation once → it becomes selected (drag handles).
- **Drag** the handles to resize / reshape.
- **Drag** the body to move it.
- Press **Delete** to remove the selected annotation.

Save

Click **Save annotations to the patient record**. The annotation layer is committed to the document. Anyone opening this document next will see the same marks.

If you close the viewer without saving, a confirm dialog appears so unsaved annotations are not lost by accident.

Tips

- Use **Text labels** to leave a short clinical note pointing to what you found.
- Use **Polygon** to outline lesions, restorations, or anatomy of interest.
- For **before / after** comparison, annotate the *current* image and pin the *previous* one into compare — both layers are visible.

→ Continue to **Measurements**.

Measurements

Measurements are quantitative annotations — distances, angles, areas. They share the same layer as annotations and are saved to the patient record the same way.

Open the measurement tools

Click **Measurement tools** in the viewer toolbar. The tool palette slides open.

Tools

Tool	What it does
Ruler	Click start point, click end point — shows the straight-line distance with units (mm if scale is known, px otherwise).
Combined ruler	Multi-segment ruler — click each waypoint; double-click to finish. Shows the total length.
Angle	Three-point angle — vertex point in the middle; the tool shows the angle in degrees. Useful for orthodontic analysis.
Crosshairs	Quick centre-cross for symmetry checks; no numbers, just visual reference.
Polygon area	Click each vertex; double-click to close. Shows the enclosed area.

Units & scale

- **DICOM** — pixel-spacing is read from the DICOM header. Measurements are reported in **millimetres** automatically.
- **Other images** — by default measurements are in **pixels**. Use **Calibrate** to teach DM2 the real-world scale.

Calibrate

If the image has a known reference (a ruler in the photo, a calibrated gauge, a structure of known size):

1. Pick the **Ruler** tool.
2. Draw a line between two points of known real-world distance.
3. Click **Calibrate** on the measurement palette.
4. Type the real distance (e.g. *10 mm*).
5. All subsequent measurements on this image use that scale.

The calibration is saved with the annotation layer so it sticks.

Editing & deleting

- **Click** a measurement to select it; drag the end-points to adjust.
- **Eraser** (in the Annotation tool palette) removes a single measurement.
- **Reset view** does **not** delete measurements — it only resets rotation / mirror / zoom / pan.

Save

Same as annotations — click **Save annotations to the patient record**. Distances, angles, areas, and calibration are all persisted.

→ Continue to [Compare](#).

Compare

The **Compare** panel shows two, three, or four documents side by side, with synchronised zoom and pan. Use it for before / after analysis, baseline-vs-follow-up, or comparing the same view across visits.

Pin documents

There are two paths into the compare panel:

- **From the gallery** — multi-select tiles (tick boxes) then click **Add to compare** in the toolbar.
- **From the viewer** — open one document, click **Add to compare** on the toolbar; open the next document, click **Add to compare** again.

Each pinned document becomes a pane in the compare layout.

Layouts

- **2 panes** — left / right.
- **3 panes** — three columns or 2-over-1.
- **4 panes** — 2×2 grid.

The layout switches automatically based on how many documents are pinned; you can also choose explicitly from the layout button.

Synchronised navigation

When **Sync** is on:

- **Zoom** in one pane zooms every pane.
- **Pan** in one pane pans every pane.
- **Rotate** in one pane rotates every pane.

Useful when comparing the exact same anatomical view across time.

When **Sync** is off, each pane is independent — useful when comparing different views (lateral vs frontal, two different teeth).

Remove a document

Click **Remove from compare** on the pane to drop one document out of the comparison.

Use cases

- **Orthodontic photos** — pin pre-treatment, mid-treatment, post-treatment for a 3-pane progression view.

- **X-rays** — pin baseline and 6-month follow-up to spot caries progression or bone-loss.
- **Consent vs signed form** — pin the blank form and the signed copy to verify everything was filled in.

Annotations & measurements in compare mode

Each pane keeps its own annotation / measurement layer. Saving in one pane does **not** affect the others.

→ Continue to [Editor](#) or [Chart Mode](#).

Editor

DM2 includes an in-browser editor for **Word documents (.docx)** so small text changes can be made without leaving HMS — handy for consent forms, referral letters, treatment-plan templates.

Open

- From the gallery — right-click a `.docx` tile → **Edit**.
- From the viewer — click the **Edit** (pencil) button on the toolbar.

The editor host fills the viewer area with a rich-text surface showing the document's content.

What you can edit

The editor handles **light edits** — text, basic formatting (bold / italic / underline), paragraphs, tables, lists. It is **not** a full-feature Word replacement; complex documents with macros, tracked-changes, embedded objects, or unusual styles will preview correctly but should be edited in Word and re-uploaded.

Save

- **Save** — writes the edited document back into the patient record as a new version. The previous version is kept in the document history.
- **Cancel edit** — discards every unsaved change and returns to the viewer.

A *Saving...* indicator appears during the upload.

Full-screen editing

Click the maximise button (top-right of the editor host) to give the editor the whole window — useful for longer documents.

Read-only preview

When the embedding context is read-only or the user does not have edit permission, the document opens in **read-only preview** — same rendering, no editing toolbar.

→ Continue to [Chart Mode](#).

Chart Mode

When DM2 is embedded **inside the dental chart for a single tooth**, it switches automatically into **chart mode** — a simplified gallery that shows only that tooth's documents, with only the controls a clinician needs at the chairside.

What changes

Removed in chart mode	Reason
Search bar	Only this tooth's files anyway.
Category filter	Same.
Type filter	Same.
Import multiple	Clinical capture is one-at-a-time.
List view toggle	Grid only — thumbnails are what matters.
Timeline view toggle	The chart already shows the timeline by visit.

What stays

- **Add document** — quick single-file upload.
- **Capture from camera** — intraoral / UVC capture (the main use).
- **Refresh** — re-pull after another user uploads.
- **Dark mode** — eye-friendly for radiology review.
- **Tile click** → **viewer** with annotations, measurements, compare.

Header strip

A *Tooth N* header appears above the gallery so it is always clear which tooth you are attaching files to. The number comes from the chart's currently-selected tooth.

Workflow at the chairside

1. Select a tooth in the dental chart.
2. Click the **Imaging** tab — DM2 opens in chart mode for that tooth.
3. Click **Capture from camera** — take the X-ray / photo.
4. Click the new tile to open the viewer.
5. Annotate / measure as needed; save.
6. Move on to the next tooth — DM2 follows the chart selection automatically.

Multi-tooth view (regular DM2)

To see *every* document for the patient regardless of tooth, open the patient's main **Documents** tab — that loads the full DM2 with all filters available.

Administration

DM2 has two areas the administrator owns:

- [Categories & Tags](#) — the dropdown the user picks from when filing a document.
- [Storage & Deduplication](#) — where files are kept, how big they can be, how duplicates are handled.

Per-user permissions

Set on the HMS user record (system administration, outside DM2):

Permission	Effect when off
Upload	Hides Add / Import / Capture buttons.
Edit metadata	Hides the Edit dialog; titles / tags / categories become read-only.
Edit document content	Hides the document editor; Word docs open read-only.
Soft-delete	Hides the Delete action; documents cannot be sent to the recycle bin.
Hard-delete	Hides Permanently delete; soft-deleted items can only be restored.
Restore	Hides Restore on soft-deleted items.
Annotate	Hides annotation + measurement tools.
Compare	Hides Add to compare.

These permissions compose with the embedding context's read-only flag — if either says read-only, the user gets read-only.

Categories & Tags

Three free-text fields are attached to every document — **Category**, **Tags**, **Keywords**. They look similar but behave differently.

Category

- **One per document** — radio-button choice.
- Picked from a **controlled list** the admin maintains.
- Shown as a coloured badge on every tile.
- Drives the Category filter dropdown above the gallery.
- The right value to use for a strong taxonomy you can later filter and report on.

Typical categories

- X-ray
- Photo
- Consent form
- Lab result
- Referral letter
- Prescription
- Invoice / receipt
- ID document
- Insurance card
- Treatment plan
- Discharge summary
- Other

The list is configurable per clinic — keep it short (12 – 20 items maximum). Long lists confuse users and dilute the value of filtering.

Tags

- **Many per document** — comma-separated free text.
- Not validated — users type whatever they want.
- Searchable from the gallery search bar.
- Good for **ad-hoc grouping** that doesn't deserve a category: *pre-op*, *post-op*, *insurance-claim*, *re-do*, *referred-out*.

Tip — agree a tag vocabulary

Free-form tags drift fast. Publish a short tag list (10 – 20 tags) and ask the team to stick to it. Otherwise *preop*, *pre-op*, *Pre-Op*, and *pre op* all end up as four different tags.

Keywords

- Free text, single field.
- Same as tags from a search point of view (the gallery search box matches all three).
- Use **Keywords** for searchable content that doesn't fit a short tag — e.g. the patient's reported symptom in their own words ("upper right molar pain since Monday"), or OCR'd content from a scanned document.

Where the three fields show up

UI	Category	Tags	Keywords
Tile badge	Yes (coloured)	No	No
Filter dropdown above gallery	Yes	No	No
Search box	Yes	Yes	Yes
Edit dialog	Picker	Comma-separated input	Comma-separated input
Import dialog (bulk)	Single value applied to all	Same	Same

Storage & Deduplication

Where files live

DM2 stores files in **one of three** places, chosen by the system configuration:

Mode	When to pick it	Trade-off
OS	Default. Files are written to the server's upload folder (typically <code>wwwroot/upload/</code>).	Fast, simple, easy to back up.
DB	Files are stored as blobs inside the HMS database.	Single backup covers data + files; database grows fast.
Remote	Files are streamed to an HMS imaging server (separate machine).	Best for multi-clinic groups sharing one imaging store.

The choice is set in the system's imaging configuration — typically by the IT team during install. End users see no difference.

Upload-folder path

When the storage mode is **OS**, the default location is `<wwwroot>/upload/`. The admin can redirect it to an absolute path — useful for pointing at a NAS, shared volume, or large local drive.

Make sure the path is:

- On a **large** disk — imaging fills space fast.
- **Backed up** — files live here, not in the database.
- Reachable by **every** application server in a load-balanced setup.

File size limits

- Per-file maximum is controlled by the application's request-size limit (default 100 MB).
- Per-user upload limit can be set on the user record.
- Browsers also impose their own request size — if a user can't upload a large video, try the alternate browser before increasing server limits.

Deduplication

DM2 hashes every uploaded file (SHA-256 of the binary content). On upload:

1. The hash is computed in the browser before the file is sent.
2. The server checks whether that hash already exists for **this patient**.
3. If yes:
 - **Skip duplicate uploads (by content hash)** ON → upload is silently skipped; the existing tile is highlighted.

- **Skip duplicate uploads** OFF → upload proceeds; a small duplicate badge appears on the new tile.

The hash check is **per patient**, not global — the same image attached to two different patients is allowed (they may genuinely need a copy each).

Soft delete & retention

Deleted documents move to a recycle bin and stay there until:

- A user with **Hard-delete** permission removes them permanently, or
- A retention sweep runs (configurable) and removes items older than the retention window.

The retention sweep is off by default — clinics opt-in once they have agreed a retention policy with their compliance team.

Audit

Every upload, edit, delete, restore, and download is logged with user, timestamp, and document ID. The log is queryable from the system audit module (outside DM2).

Scheduler

The **Scheduler** is the clinic's appointment grid — the page the front desk lives in all day. It shows every physician's day at a glance, lets you find a patient in two keystrokes, drop them into a free slot, move them around when something changes, and surfaces the clinical context the receptionist needs to make a good booking (allergies, balance, VIP status, no-show history).

What the screen shows

- A **toolbar** across the top with the day / week toggle, find, bulk-reschedule, full-screen, density, and light/dark switches.
- A **kebab menu** (three dots, top-left) → **Scheduler settings** — hours, days, rooms, breaks, holidays, categories, alerts.
- A **side bar** listing the physicians you want to see (with previous / next paging when you have more physicians than columns).
- The **main grid** — one column per physician (Day view) or one column per weekday for a single physician (Week view), with the hours of the day stacked vertically.
- A **status legend** along the bottom — click any status to hide or show those appointments.
- A **clipboard banner** that appears whenever you have an appointment "in hand" after Copy or Cut.

Two views

View	Best for
Day	The day's plan across many physicians. Default for reception.
Week	One physician's whole week. Double-click any physician name in the side bar to jump here.

Three modes

- **Comfort vs Compact** — toggles row height so more or fewer slots fit on screen. Persists per user.
- **Light vs Dark** — same data, eye-friendly evening look. Persists per user.
- **Focus (full-screen)** — hides every menu and header so the scheduler fills the whole window. Press once more to exit.

Why "V2"?

The current scheduler is the second-generation rewrite. The legacy scheduler is still bundled for fall-back but is no longer the default — this documentation covers V2 only.

→ Continue to [Getting Started](#).

Getting Started

Book your first appointment in under a minute.

1. Pick the right view

The scheduler opens in **Day view** by default — perfect for reception. If you want to see one physician's whole week instead, click **Week** in the toolbar.

2. Make sure the day is the day you want

Use the date picker (top-left of the grid) to jump to any day, or use the arrow buttons to walk forward / back one day at a time.

3. Pick the physicians you can see

The side bar lists every physician. If your clinic has more physicians than columns fit on screen, use **Previous physicians** / **Next physicians** to page through them. (How many columns to show at once is in **Scheduler settings** → **Hours & Days**.)

4. Find the patient

Click **Find** in the toolbar. Type any of:

- **Name** — first, family, or partial.
- **MRN / file number** — the patient's HMS file number.
- **Phone** — last 4 digits is usually enough.

Pick the patient from the result list. They are now your "selected" patient for the next click.

5. Drop them into a slot

Click an empty cell in the physician's column at the time you want. The booking dialog opens pre-filled with patient + physician + time. Pick:

- **Room** — the chair / consultation room.
- **Category** — the appointment type (Consultation, Follow-up, ...).
- **Comment** — free text the dentist / doctor will see.

Save.

6. Done

The cell is now filled, coloured by category. Hover it for a tooltip, click it for the full event info panel on the right (allergies, balance, VIP, no-show count). Right-click for Edit / Copy / Cut / Delete.

Common next moves

- **Move the appointment** — drag it to a different time, or right-click → **Cut**, then click the new cell to paste.

- **Copy the patient into a second slot** — right-click → **Copy**, click the second cell.
- **Reschedule the rest of the day** because the physician is late — use [Bulk reschedule](#).

→ Continue to [Day & Week views](#).

Day & Week Views

The scheduler has two layouts. Both show exactly the same appointments — only the slicing changes.

Day view

- One column per **physician**.
- Hours of the day stacked vertically.
- The header row shows physician name + room.
- Default view for reception — best for *"who is free at 2 pm?"*.

The number of physicians shown at once is set in **Scheduler settings** → **Hours & Days** → **Number of physicians to show at once**. If your clinic has more physicians than that, the **Previous physicians** / **Next physicians** buttons in the side bar page through the rest.

Week view

- One column per **weekday** for **one physician**.
- Hours of the day stacked vertically.
- Header row shows the dates of the week.
- Best for *"when is Dr X next available?"* or filling a single physician's week.

The fastest way to jump there: in Day view, double-click any physician's name in the side bar. The scheduler flips to Week view for that physician immediately.

You can also configure how many day columns to show (typically 5 for weekdays-only or 7 for the full week) — **Scheduler settings** → **Hours & Days** → **Number of day columns to show in Week view**.

What's the same in both views

- Click an empty cell → booking dialog.
- Click a booked cell → event info panel.
- Right-click a booked cell → Edit, Copy, Cut, Delete.
- Drag a booked cell to a new time → move (with conflict check).
- Status legend at the bottom controls visibility.

Toolbar modes

These three toolbar buttons change how the screen *looks*, not what it *shows*:

Button	What it does	Persists
Focus	Full-screen — hides the HMS top menu and side menu so the scheduler fills the window. Click Exit to come back.	No

Button	What it does	Persists
Compact / Comfort	Compact = tighter rows, more slots on screen. Comfort = roomier rows, easier to read.	Yes (per user)
Dark / Light	Switches the scheduler colours between light and dark themes.	Yes (per user)

→ Continue to [Find a Patient & Book](#).

Find a Patient & Book

The fastest path from "patient calls" to "appointment in the grid" is two clicks.

Find

Click **Find** in the toolbar (or press the keyboard shortcut your admin configured). The patient picker opens with a single search box.

Search by any of:

- **Name** — first, family, or partial match.
- **MRN** — the patient's HMS file number (often the badge number).
- **Phone** — last 4 digits is usually unique enough.

The list narrows as you type. Pick the patient.

What if the patient isn't there?

- They've never visited the clinic → book the slot as a **walk-in** (skip the picker, just click the slot — the booking dialog lets you type the patient's name without linking to a file). The receptionist attaches a real file later via **Edit appointment**.
- They've visited a different branch — clear any branch filter at the top of the picker; the search runs across all branches.

Patient context shown in the picker

Each row shows: name, MRN, date of birth, mobile, last visit. Special flags appear as small icons:

Icon	Meaning
Heart	VIP patient — handle gently.
Triangle	Pending balance over the configured threshold — flag for the cashier before the visit.
Allergen symbol	Has documented allergies — the receptionist should remind the physician.
Person-x	High no-show count — consider asking for a deposit.

Book

After picking the patient, click the empty cell you want — in the right physician's column at the right time. The booking dialog opens pre-filled.

Fill in:

- **From / To** — start and end time. The dialog snaps to the booking step set in **Scheduler settings** → **Hours & Days** → **Booking step**.

- **Room** — defaults to the physician's room if one is set.
- **Category** — Consultation, Follow-up, Cleaning, Emergency, Categories drive the appointment colour. List configured in **Scheduler settings** → **Categories**.
- **Reason** — short label that appears on the appointment card.
- **Comment** — longer free text the physician sees in event info.

Save.

What you see after save

The cell is filled and coloured by category. Hovering shows a tooltip; clicking shows the full **Appointment Information** panel with allergy / balance / VIP / no-show flags. Right-click for Edit / Copy / Cut / Delete.

→ Continue to **Move, Copy, Paste**.

Move, Copy & Paste

There are three ways to move an appointment. Pick whichever is fastest for the situation.

Drag

Click and hold an appointment, drag it to the new time / physician, release. Best for **small adjustments within the same day**.

The drag handle snaps to the booking step (configured in **Hours & Days**). If the drop conflicts with an existing booking, the [Conflict modal](#) opens and offers Cancel, Overwrite, or Move both.

Cut and paste

Right-click the appointment → **Cut**. The cell goes pale and a **clipboard banner** appears at the top of the screen reminding you that an appointment is "in hand". Click the new cell — the appointment is removed from the old slot and dropped into the new one.

Use this when the new slot is on **another day or far across the grid** — easier than a long drag.

Copy and paste

Right-click → **Copy** instead of Cut. Now every cell you click pastes a copy of the patient and the appointment template until you press Escape or right-click → **Clear clipboard**.

Use this when you need to book **several follow-up sessions** for the same patient in one go.

Drag a physician's day

To move every appointment for one physician at once, use the [Bulk reschedule](#) toolbar button. It is faster and safer than dragging dozens of cells.

Cancel a paste

- Press **Escape**, or
- Click the **X** on the clipboard banner, or
- Right-click anywhere → **Clear clipboard**.

The original (for Cut) is restored if you cancel before pasting.

→ Continue to [Conflicts](#).

Conflicts

When you drop an appointment onto a time that already has bookings, the scheduler does **not** silently overwrite — the **Conflict** dialog opens and shows you exactly what would clash.

What the dialog shows

A card for each conflicting appointment, with:

- Patient name + MRN
- Time (from – to)
- Physician
- Room
- Status
- Reason

The card at the top is the appointment **you are placing**. The cards below are what is already in those slots.

Your choices

Action	Effect
Cancel	Closes the dialog. Nothing changes. The clipboard is preserved if you cut.
Overwrite	Deletes the conflicting appointments and places yours. Use sparingly — those patients are now unbooked.
Move both (<i>when possible</i>)	Puts yours in and bumps the conflicting one(s) to the next free slot.

Bulk paste conflicts

If you paste several appointments in a row and one of them conflicts, the dialog shows that *one* conflict. Resolve it and the paste continues automatically.

Why the dialog appears even when slots "look" free

- The slot might be a **break** or **blocked time** the physician configured.
- The slot might be inside a **holiday**.
- Another receptionist might have booked it 5 seconds before you (the scheduler refreshes on every action).

In all three cases the conflict dialog tells you exactly which kind of conflict it is.

→ Continue to **Bulk reschedule**.

Bulk Reschedule

When a physician runs late, gets called away, or wants to flip rooms, moving the day's appointments one by one is painful. **Bulk reschedule** does it in one operation.

Open

Click **Bulk** in the toolbar.

What you choose

Field	Meaning
From physician	Whose appointments to move.
On date	Which day's appointments to consider.
Move to physician	(Optional) The other physician to take the patients. Leave blank to keep the same physician.
Shift by	Minutes to shift each appointment forward (positive) or back (negative). E.g. <code>+30</code> pushes the whole day half an hour later.
Shift to date	(Optional) Move the day's appointments to a different date entirely.

Run

Click **Save**. The scheduler:

1. Validates each move against breaks, holidays, and existing appointments.
2. If any of the moves would conflict, opens the **Conflict** dialog listing every clash. You can cancel, overwrite, or skip per row.
3. Applies the rest atomically — either every appointment moves or none of them do.

Use cases

- **Doctor is 30 minutes late** → Shift by `+30`.
- **Doctor swapping rooms with a colleague** → set *Move to physician* to the other physician. The day moves columns.
- **Public holiday declared on short notice** → Shift to date = next open day. Patients are notified by the standard reminder flow.

Tip

Bulk reschedule respects the **status filter** at the bottom of the grid — hide *Cancelled* and *No-show* statuses first if you only want to move appointments that are still live.

→ Continue to **Block Time**.

Block Time

A **Block** is a stretch of time on a physician's calendar that is **not bookable** — meetings, theatre, surgery slots, training, leave-of-absence. They show as striped grey bands on the grid and the booking dialog refuses to place a patient inside them.

Add a block

Right-click an empty cell → **Block this time** (or open the Block dialog from the kebab menu → **Breaks**).

Fill in:

Field	Meaning
Physician	Whose calendar the block applies to.
Room	(Optional) Block only one room — leave blank to block all rooms.
Date from / Date to	The block's date range (use the same date in both for a single-day block).
Time from / Time to	The hours within each day that are blocked.
Reason	Free text shown in the cell tooltip — e.g. <i>Theatre, Conference</i> .

Save. The block appears immediately as a grey striped band.

Edit / Remove a block

Open the kebab menu → **Breaks**. Every block is listed with Edit and Remove links. Editing reopens the same dialog; removing deletes the block (existing appointments inside the same hours are not touched — just no longer striped).

Recurring blocks

For weekly recurring blocks (e.g. *every Wednesday 14:00 – 16:00: team meeting*):

- Set Date from to the first Wednesday and Date to to a long horizon (e.g. end of year).
- The system applies the block on **every** weekday that falls in the range and matches the time window — for a true weekly recurrence combine this with the working-day toggles in **Hours & Days**.

Difference vs Breaks

- A **Break** is the same idea but configured globally under **Scheduler settings** → **Breaks** — typically lunch, prayer time. It applies to *all* physicians automatically.
- A **Block** is one physician's calendar entry that you add ad-hoc from this dialog.

Difference vs Holidays

- A **Holiday** blocks the entire clinic on that date — no physician works. Configured under **Scheduler settings** → **Holidays**.

→ Continue to [Event Info Panel](#).

Event Info Panel

Click any booked cell to open the **Appointment Information** panel on the right. It is the single place that pulls together everything the front desk needs to know before the patient walks in.

What it shows

- **Patient** — name, MRN, photo (if on file).
- **Time** — from / to, duration.
- **Physician**.
- **Room**.
- **Category** with its colour swatch.
- **Reason** (short label).
- **Comment** (longer note from whoever booked it).
- **Status** — Pending, Confirmed, Arrived, In-Service, Completed, No-show, Cancelled.

Flags & alerts

The top of the panel highlights anything the receptionist should not miss.

Flag	Meaning
VIP patient	The patient is flagged as VIP — small dot on the cell, banner on the panel. Handle gently.
Allergy	Known allergies — review patient chart. The cell shows a small symbol.
Pending balance over threshold	The patient owes more than the configured threshold; flag for the cashier before the visit.
No-show history	Past missed appointments (count). Bands shown on the panel.
Procedure has instructions — see event info panel	The booking has special prep instructions (e.g. fasting, take medication).
Walk-in — patient not yet registered. Edit the appointment to attach a patient file.	The appointment was created without linking to a patient file. Click Edit to find or create the file.

These flags come from your [Alerts](#) configuration — turn them on / off and set thresholds there.

Quick actions

The panel's footer has the same actions as the right-click menu:

- **Edit** — opens the booking dialog.
- **Cancel edit** — discards changes.

- **Delete** — removes the appointment after a confirm.
- **Status** — quick-set Arrived / In-Service / Completed / No-show without opening the full editor.

→ Continue to [Scheduler Settings](#).

Scheduler Settings

Open **Scheduler settings** by clicking the **kebab menu** (three dots, top-left of the scheduler) → **Scheduler settings**.

The settings dialog is organised into ten tabs. Use this overview to pick the right tab; each one has its own page below.

Tab	What it sets	Stored where	Page
Display	Theme, density, full-screen	Per user	Display
Filters	Which appointment statuses are visible	Per user	Filters & Statuses
Hours & Days	Clinic open / close times, booking step, working days, columns	Per clinic	Hours & Days
Alternative	Special hours during a date range (Ramadan, summer)	Per clinic	Alternative Hours
Rooms	Treatment rooms with per-room day-of-week availability	Per clinic	Rooms
Breaks	Recurring or one-off breaks blocked across the day	Per clinic	Breaks
Holidays	Fixed and annual closures	Per clinic	Holidays
Categories	Appointment categories with their colours	Per clinic	Categories & Colours
Alerts	Wait threshold + no-show banding + balance threshold	Per clinic	Alerts
System	Release, version, app name, current user (read-only)	—	—

!!! tip "Per-user vs per-clinic" The **Display** and **Filters** tabs save automatically and only affect your own screen. Every other tab saves to the clinic configuration — your changes apply to **everyone in the clinic** the next time their scheduler loads.

!!! warning "Permission" Saving anything outside **Display** and **Filters** needs the *Scheduler administrator* permission. Without it, those tabs open in read-only mode.

Display

Per-user appearance settings. Save automatically when you change them.

Color theme

Option	When to pick it
Light	Bright clinics, daytime use.
Dark	Dim reception, evening shifts, less eye strain.

The toolbar **Dark / Light** button toggles between the two — both controls do the same thing.

Row density

Option	When to pick it
Compact	Big appointment days; you want to see more slots at once.
Comfort	Default; easier to read.

The toolbar **Compact / Comfort** button toggles between the two.

Focus (full-screen) mode

When on, the HMS top bar and side menu hide so the scheduler fills the whole window. Click **Exit** in the toolbar (or press the same button again) to come back.

Unlike Theme and Density, **Focus is per-session, not persisted** — the next time you open the scheduler it starts in normal mode.

Filters & Statuses

Controls which appointments appear in the grid based on their status.

Show appointments with status...

A list of every appointment status with a checkbox. Tick to show, untick to hide. The legend at the bottom of the grid is the same list — clicking a legend swatch toggles the matching checkbox.

Typical statuses:

- **Pending** — booked but not yet confirmed.
- **Confirmed** — patient confirmed (often by SMS reply).
- **Arrived** — patient has checked in at reception.
- **In-Service** — patient is currently with the physician.
- **Completed** — visit finished.
- **No-show** — patient did not turn up.
- **Cancelled** — appointment cancelled.

!!! tip Hide **Completed**, **No-show**, and **Cancelled** to keep the grid focused on what's still live today.

Reset to default visible statuses

Click **Reset to default visible statuses** to bring back the out-of-the-box visibility (typically: Pending, Confirmed, Arrived, In-Service).

Filter mode (read-only)

Shown for reference only — it tells you which filter logic the clinic is using globally (e.g. *Hide cancelled by default*, *Show everything*). The setting itself is in the clinic's global configuration, not editable from here.

Hours & Days

The clinic's standard working hours, days, and grid sizing.

Hours

Setting	Meaning
Clinic opens at (hour, 0–23)	First bookable hour of the day.
Clinic closes at (hour, 0–24)	Last bookable hour of the day. Use 24 for midnight.
Booking step (minutes)	The increment for booking — 15, 20, 30. Every cell in the grid is one step.
Scroll-to hour on open (start)	What hour the grid scrolls to when you first open the scheduler.
Scroll-to hour on open (end)	The bottom of the initial scroll window.
Lunch / midday gap 1 (minutes)	A visual gap inserted at the lunch hour — purely cosmetic.
Lunch / midday gap 2 (minutes)	Optional second gap for clinics with two midday breaks (e.g. prayer + lunch).
Show all working hours	When ticked, the grid shows every hour from open → close on first load (overrides the <i>Scroll-to</i> settings).

Working days of the week

A row of seven day toggles — Sat, Sun, Mon, Tue, Wed, Thu, Fri (order depends on locale). Tick the days the clinic is open. Non-working days are greyed out and refuse bookings.

Calendar options

Setting	Meaning
Number of physicians to show at once	How many physician columns fit on screen in Day view. Use Previous / Next physicians to page through the rest.
Number of day columns to show in Week view	Usually 5 (work-week) or 7 (full week).

Tips

- If the receptionist regularly scrolls back to early morning slots, set **Scroll-to hour on open (start)** to the earliest expected booking — saves a daily scroll.
- The **Booking step** also controls how drag-and-drop snaps. Smaller step = finer precision; larger step = harder to mis-click.

Alternative Hours

Some clinics shift their hours for a few weeks or months (Ramadan, summer, winter break). Instead of editing the main hours and remembering to put them back, use **Alternative Hours** — a parallel schedule that takes over for a date range, then automatically reverts.

Fields

Setting	Meaning
Use alternative hours	Master switch. Off = ignore everything below.
Alternative hours — start date	First day the alt schedule applies.
Alternative hours — end date	Last day the alt schedule applies.
Alt-opens at (hour, 0–23)	Open hour during the alt window.
Alt-closes at (hour, 0–24)	Close hour during the alt window.
Alt-gap 1 (minutes)	Lunch / midday gap during the alt window.
Alt-gap 2 (minutes)	Optional second alt gap.

How it interacts with regular hours

- Inside the alt window → alt hours win, regular hours are ignored.
- Outside the alt window → regular hours apply, alt settings are ignored.
- Working-day toggles (Sat, Sun, ...) come from **Hours & Days** in both cases — there is no separate alt day-of-week list.
- Booking step comes from **Hours & Days** in both cases.

Use cases

- **Ramadan** — open 21:00 – 01:00 for one month.
- **Summer school break** — earlier opening (07:00 – 14:00) for July / August.
- **Winter Holidays** — shortened day (10:00 – 16:00) for a week.

Tip

Set up the next Ramadan schedule at the start of the year and leave it in place — the **Use alternative hours** master switch lets you toggle the whole thing on and off without re-entering dates.

Rooms

The list of physical treatment rooms / consultation rooms / chairs the clinic books patients into. Every appointment carries a room so the patient (and the cleaner) know where to go.

What you see

A list, one row per room. Above the list a counter — *Treatment rooms* — *N configured*.

Add a room

Click **New Room**. The editor opens with:

Field	Meaning
Room #	The room number. Must be unique.
Name (EN)	The room's English name (printed on the appointment slip).
الاسم	The room's Arabic name.
Doc ID	(Optional) Default physician for this room — appointments booked in this room default to this physician.
Type	(Optional) Room type code — used in some reports.
Day-of-week toggles	A row of seven day buttons — tick the days this specific room is in use. Leave them all on for a "always available" room.

Save. The room is immediately available on the booking dialog and in the rooms picker.

Edit / Delete

Each row has **Edit** and **Delete** links. Editing reopens the same editor. Delete asks for confirm — rooms that have past appointments are kept in the database for audit but no longer appear on the booking dialog.

Tips

- Set **Doc ID** for chairs that are *always* used by one dentist — every booking in that chair pre-selects them.
- Use the day toggles for a room that is only available on certain days (e.g. a mobile X-ray that comes in twice a week).

Breaks

Recurring or one-off slots of time that are **not bookable** for the whole clinic — typically lunch, prayer time, mandatory staff meetings.

A break is different from a [Block](#): a Block is one physician's calendar entry; a Break applies to every physician in the clinic.

What you see

A list with a counter at the top — *Breaks & blocked time — X of Y shown* — and a filter box to narrow it down by physician or reason.

Each row shows: physician (or *All*), room (or *All*), date range, time range, reason, Edit and Remove links.

Add a break

Click **New Break**. Fill in:

Field	Meaning
Physician	The physician the break applies to. Pick <i>All</i> for a clinic-wide break (lunch / prayer).
Room	(Optional) Only block a specific room — leave blank for all rooms.
Date from / Date to	The range of days the break is in effect. Use the same date in both for a one-off.
Time from / Time to	The hours within each day.
Reason	Free text shown in the cell tooltip — e.g. <i>Lunch, Prayer, Staff meeting</i> .

Save. Cells inside the break are now striped grey and refuse bookings.

Recurring weekly break

The classic *every weekday 13:00 – 14:00 = lunch* break:

- Pick *All* physicians, *All* rooms.
- Date from = today, Date to = end of year (or further).
- Time from = 13:00, Time to = 14:00.
- Reason = *Lunch*.

The break applies on every working day in the range (working days are set in [Hours & Days](#)).

Edit / Remove

Use the per-row links. Removing a break frees up those slots immediately for new bookings — existing appointments inside the window are kept as-is.

Holidays

A **Holiday** closes the entire clinic on a given date — no physician works, no bookings accepted, the whole day shows as struck-through on the grid.

What you see

A list of every holiday with its date, name, and whether it is annual.

- *No holidays configured.* — if the list is empty.

Add a holiday

Click **New Holiday**. Fill in:

Field	Meaning
Date	The day the clinic is closed.
Name	Free text — e.g. <i>National Day, Eid Al Fitr Day 1</i> .
Annual	When ticked, the holiday repeats every year on the same Gregorian date (use for fixed-date holidays like New Year's Day). For Hijri-calendar holidays, leave Annual off and add a fresh row each year.

Save. The day greys out across the whole grid immediately.

Edit / Remove

Each row has Edit and Remove links. Removing a holiday opens that day for bookings again; existing appointments on the day (if any) are not deleted.

Tips

- Plan the year ahead — bulk-add every public holiday in January so receptionists never accidentally book a closed day.
- For multi-day holidays (Eid, end-of-year), add one row per day. There is no "range" mode — each closed day is its own entry.

Categories & Colours

Up to **12 appointment categories**, each with its own colour. The colour is what fills the cell on the grid — so the receptionist recognises an emergency vs a routine cleaning at a glance.

What you see

A 12-row table. Each row has the category **name** and a **colour swatch**.

Editing

The table is **read-only** in the standard settings dialog — the clinic configuration team sets the categories and colours during implementation. To request a change:

- Add a new category → contact the system administrator (they update the master clinic configuration).
- Change a colour → same — the swatch palette is managed centrally so every clinic in a group uses the same colour for the same category.

Choosing colours

Some guidance from clinics that have shipped this for years:

- **Reserve red for Emergency** — receptionists instinctively look for it.
- **Use a muted colour for the most common category** — *Routine follow-up* in pale blue keeps the grid calm.
- **Pick distinct colours for adjacent categories** — pale-blue follow-up next to pale-green check-up is hard to tell apart on a small screen.
- **Don't use grey** — grey is reserved for breaks and blocks.

Where the colour shows up

- Cell fill on the grid.
- Swatch on the **event info panel**.
- Swatch in the booking dialog's category picker.
- Legend at the bottom of the grid (clicking the swatch toggles visibility — see [Filters & Statuses](#)).

Alerts

Thresholds that drive the **flags on the event info panel** and the **icons on appointment cards**. Tune these once for the clinic and every receptionist sees consistent warnings.

Wait threshold

How long a patient is considered "waiting" before the scheduler shows a warning band. Typical values: 15 – 20 minutes.

If a patient has status **Arrived** and the configured wait threshold elapses without moving to **In-Service**, the cell gets a warning band and the patient appears on the front-desk *patients waiting* dashboard.

No-show banding

Patients with a history of missing appointments get a coloured band that scales with the count. Configure the bands:

Band	Default range	Meaning
None	0 missed	No flag.
Yellow	1 – 2	Cautionary — receptionist may want to send a reminder the day before.
Orange	3 – 4	Strong — consider asking for confirmation.
Red	5+	High-risk — clinic policy may require a deposit.

Edit the cut-off counts to match the clinic's policy.

Pending balance threshold

The amount above which an outstanding patient balance triggers the *Pending balance over threshold* flag on the event info panel. Set this to the value where the receptionist should hand the patient to the cashier **before** the visit (rather than after).

The flag also adds a small icon on the appointment card so the receptionist sees it without opening the panel.

How alerts and flags work together

Source	Where it shows
Allergy flag	Pulled from the patient's chart. Card icon + panel banner.
VIP flag	Patient profile flag. Card icon + panel banner.
Pending balance	Set by the threshold here. Card icon + panel banner.

Source	Where it shows
No-show band	Computed from past appointments + bands above. Panel band only.
Wait threshold	Computed from arrival time + threshold above. Card band only.
Procedure has instructions	Pulled from the booked procedure (if it carries prep instructions). Panel banner only.

Clinic Reception

Clinic Reception is the receptionist's home screen. From this one window the receptionist can find the patient, open their chart, create a visit, take a payment, print a receipt, issue a prescription, and book the next recall — without hopping between modules.

The toolbar at a glance

The top toolbar groups every common front-desk action into 14 buttons, laid out left → right in the order a typical visit happens:

Section	Buttons
Find the patient	Finger Print Scan · Select Patient
Patient file	Edit Patient · Open Patient File · Dental Chart · Treatment Plans
Create activity	New Visit · New Appointment · New Patient · New Recall
Prescriptions	Prescriptions History · New Prescription
Money	New Receipt · New Bill

A **green banner** across the top always shows the currently-selected patient — name, file number, date of birth, allergies, and the fingerprint status. If no patient is selected the banner reads *Fingerprint Patient* and prompts you to either scan a print or use **Select Patient**.

The **Patient Toolbox** on the right edge of the screen surfaces extra shortcuts (medical history, alerts, attachments) that change based on who is selected.

How to open it

From the HMS main menu open **Clinic Reception**, or pin the shortcut to the launcher for one-click access.

→ Next: **Getting Started** — walk through a full patient visit, start to finish.

Getting Started

A typical dental-clinic visit, step by step, from the moment the patient walks in to the moment they leave with a printed receipt.

!!! tip "Keep one hand on the fingerprint reader" 90 % of returning patients are found in under a second by simply asking them to place a finger on the reader. Use **Select Patient** only for first-time visitors and walk-ins without a fingerprint on file.

1. Find the patient

- **Returning patient** → ask them to scan their fingerprint (**Finger Print Scan** button). The banner fills with their details.
- **New patient** → click **New Patient** (see step 2).
- **Anything else** → **Select Patient** opens a searchable picker (name, file number, mobile, national ID).

2. (First visit only) Create the patient file

Click **New Patient**. Fill in the personal tab (name, gender, date of birth, nationality, marital status), the contact tab (mobile, e-mail, address), and the medical-history tab (allergies, chronic conditions, current medications). Save.

The patient now appears in the banner and is the *current patient* for every other toolbar button.

3. Open the patient's full file (optional)

Open Patient File opens the patient's complete clinical workspace in a new window — useful when the dentist asks you to print old X-rays, lab results, or the previous treatment plan.

4. Create today's visit

Click **New Visit**. The visit form opens pre-filled with the patient and today's date. Pick the treating dentist, the room, and the visit type (consultation, follow-up, emergency). Save.

This creates the bill header — every procedure the dentist performs during the visit is charged to it.

5. Show the Dental Chart

Click **Dental Chart**. The chart opens to today's visit. The dentist clicks teeth, picks conditions and treatments, and saves. Every treatment they tick becomes a line on the visit bill automatically.

6. Review the Treatment Plan

Click **Treatment Plans** to show the running plan for this patient — treatments that were proposed on previous visits, with their status (planned / in-progress / completed) and their cost.

7. Issue a prescription (if needed)

Click **New Prescription** to write a prescription. The drug picker checks the patient's allergies and current medications and warns about interactions.

- **Prescriptions History** opens every prescription this patient has ever received — useful for refill questions.

8. Print the receipt and the bill

- Click **New Receipt** to take a payment (cash, card, insurance co-pay). Pick the method, enter the amount, save. A printable receipt opens.
- Click **New Bill** to print the full itemised bill (useful when the patient asks for one for insurance reimbursement).

9. Schedule the recall

Click **New Recall** to book the next routine appointment (cleaning, follow-up). The recall is added to the patient's schedule and a reminder is queued for the configured channel (SMS, e-mail, or both).

10. Done

The patient leaves. The banner stays on them until the next patient scans a fingerprint — useful if you forgot to print something on the way out.

→ See the per-action detail pages under **Workflows** in the left sidebar.

Finding a Patient

There are three ways to put a patient into the banner — pick the fastest one available for the person in front of you.

Finger Print Scan

Place the patient's finger on the reader and click **Finger Print Scan**. The system looks the print up in the central biometric store and, on a match, fills the banner with that patient.

If the reader returns *No match*:

- The patient has never registered a print — see **Patient Toolbox** → **Enrol Fingerprint** to capture it on the spot.
- The print quality was poor — wipe the reader and try a different finger.

Select Patient

Opens the patient picker. Search by:

- **Name** — first, middle, last, or any partial match.
- **File number** — the printed badge / card number.
- **Mobile** — last 4 digits is usually enough.
- **National ID / Passport**.
- **Date of birth**.

Tip: filter by **Branch** at the top of the picker to limit the list to your clinic.

Walk-in / unknown patient

If the person has never visited any branch before, skip straight to **New Patient** — the first save creates the file and selects them in the banner in one step.

What "selecting a patient" actually does

Every other toolbar button operates on **the patient currently in the banner**. Selecting a new patient:

- Updates the banner.
- Pre-fills patient-context fields on every form you open afterwards.
- Refreshes the **Patient Toolbox** on the right with this patient's alerts, attachments, and quick actions.

It does **not** open any patient screen on its own — that needs an explicit toolbar click (Edit, Open File, Dental Chart, ...).

New Patient

Click **New Patient** to register someone visiting for the first time.

What you fill in

Personal

- Full name (English and Arabic where applicable).
- Date of birth, gender, marital status.
- Nationality, religion.
- Photo (optional — drag any image into the photo box).

Contact

- Mobile, e-mail, address, P.O. Box.
- Emergency contact (name, relation, phone).

Medical

- Allergies (drug and non-drug).
- Chronic conditions.
- Current medications.
- Notes the dentist should see (recent surgery, pregnancy, anticoagulants).

Insurance

If the patient has a card from a payer the clinic contracts with, add the card number, validity, and co-pay tier here. The payer becomes the default guarantor on every bill until you change it.

After save

- The new patient is selected in the banner — you can go straight to **New Visit**, **Dental Chart**, or **New Appointment**.
- A file number is allocated automatically.
- The patient is now searchable across all clinic front desks.

Edit Patient

After save, **Edit Patient** opens the same form back up to correct anything. The original creation date and the user who created it are kept in the audit trail.

New Visit

A **Visit** represents one in-person attendance at the clinic. It is the container that holds the chart entries, prescriptions, lab referrals and the bill for that day.

Open

Click **New Visit** with the patient already in the banner.

What you fill in

- **Date / time** — defaults to now.
- **Visit type** — Consultation, Follow-up, Emergency, Cleaning, Check-up, Cosmetic.
- **Dentist** — the treating doctor.
- **Room** — the chair / operator.
- **Referred by** — if the patient was sent by another clinic.
- **Chief complaint** — short free-text on why they are there today.

Save

Saving the visit:

- Creates a bill header against this visit.
- Makes the visit selectable in the Dental Chart's *Visit* dropdown.
- Adds the visit to the dentist's daily roster.

What happens during the visit

The dentist works in the **Dental Chart** (next page). Every procedure they tick on a tooth flows into:

- The chart history (visible from now on).
- The visit's bill (price taken from the price-list).
- The treatment plan if it is part of one.

Closing the visit

When the patient is finished, the receptionist takes payment via **New Receipt** and (optionally) prints the bill via **New Bill**. There is no separate *Close Visit* button — the visit is implicitly closed when no more procedures are added to it.

Dental Chart

The **Dental Chart** is the dentist's main working surface. Click **Dental Chart** on the front-desk toolbar to open it for the patient in the banner.

Layout

The chart shows the patient's mouth as **two arches** (upper and lower), each with adult and deciduous teeth. Around the chart:

Area	What it does
Top toolbar	Switches the active visit, switches between Adult / Child / Perio / Ortho views, prints, sends to imaging.
Left tool palette	Conditions (caries, fracture, missing, ...), treatments (filling, extraction, crown, root canal, ...), notes.
Right side panel	Material picker — selects amalgam, composite shade, alloy, etc. for whichever treatment was last picked.
Bottom history strip	A scrollable timeline of every previous entry on the selected tooth.

Working a tooth

1. Click the tooth (or a specific surface — mesial, distal, occlusal, buccal, lingual).
2. From the left palette pick a **condition** (what is wrong) or a **treatment** (what you are doing about it).
3. Pick the **material** from the right panel if the treatment needs one.
4. The chart updates immediately — coloured marks show the new state, and the entry is added to the visit's procedure list.

What flows where

Every chart entry creates:

- A clinical note on the tooth (visible in the bottom history strip and on every future chart open).
- A line on the **current visit's bill** at the price-list rate.
- A line on the **Treatment Plan** if the treatment is part of one.

Special views

- **Adult chart** — 32 permanent teeth.
- **Child chart** — 20 deciduous teeth.
- **Perio chart** — pocket-depth, bleeding, recession, mobility.

- **Ortho chart** — bracket / wire / appliance tracking.

Switch views with the toolbar buttons; the underlying patient is the same.

Treatment Plans

A **Treatment Plan** is the longer-term care roadmap for a patient — the set of procedures the dentist agreed to do over the coming weeks or months. Click **Treatment Plans** on the front-desk toolbar to open it.

What you see

A single screen split into three areas:

Area	What it shows
Header	Patient, plan name, total estimated cost, total paid so far, status.
Procedures grid	One row per planned procedure — tooth, treatment, dentist, planned date, estimated cost, status.
Status panel	Counts of Planned / In-Progress / Completed / Cancelled, and a progress bar.

Statuses

- **Planned** — agreed with the patient; not yet started.
- **In-Progress** — partly done over more than one visit (e.g. root canal + post + crown).
- **Completed** — finished and signed off.
- **Cancelled** — declined by the patient or no longer indicated.

How rows get there

Treatments are usually added from the **Dental Chart**: when the dentist ticks a procedure the chart asks *Add to plan?* If they say yes, the row appears here. They can also be typed in directly from the plan grid.

Acceptance & consent

- Print the plan from the **Print** button as a patient-facing quote.
- Once the patient signs, mark the plan **Accepted** — the header status changes and the plan total locks in (price changes after acceptance need an override).

Tip

Use **Treatment Plans** before quoting a major case (full-mouth rehabilitation, implants, orthodontics) so the patient sees the whole journey and the total cost up front — it cuts last-minute drop-outs.

Appointments & Recalls

Two toolbar buttons drive the booking diary: **New Appointment** and **New Recall**.

New Appointment

Click **New Appointment** when the patient wants a specific date and time for the next visit.

- Pick the **dentist**.
- The diary pops up showing that dentist's free slots — green = free, red = booked, grey = blocked / out.
- Click a slot. Set **duration, room, reason**.
- Save — the slot turns blue and an SMS / e-mail confirmation goes out if the patient has consented to reminders.

The appointment is now visible on:

- The dentist's daily roster.
- The patient's file (Appointments tab).
- The front-desk wall display (if configured).

New Recall

A **Recall** is a softer booking — *come back in 6 months for a cleaning* — without committing to a specific slot yet. Click **New Recall**.

- Pick the **reason** (Cleaning, Follow-up, Annual check-up, Orthodontic check, ...).
- Pick the **due month** (or due date if you want to be precise).
- Pick the **reminder channel** (SMS, e-mail, both, none).
- Save.

When the due date approaches, the recall list (in the Recalls module) shows the patient. The receptionist then turns the recall into a real appointment with **New Appointment** above.

Cancelling / rescheduling

Open the appointment from the diary, click **Cancel** or drag it to a new slot. The patient gets a fresh notification automatically.

Prescriptions

Two toolbar buttons handle prescribing: **New Prescription** to write one, **Prescriptions History** to review what was prescribed before.

New Prescription

Click **New Prescription**.

- The drug picker shows the clinic's standard formulary first (configurable). Type to search by trade name, generic name, or class.
- Pick **strength, frequency, duration, route**.
- Add as many drug lines as needed.
- Save.

Safety checks that run automatically

- **Allergy check** — warns if any of the patient's recorded allergies match the active ingredient.
- **Interaction check** — warns if any prescribed drug interacts with the patient's currently-active medications.
- **Pregnancy / paediatric** — warns if the drug is contraindicated for the patient's age or pregnancy status.
- **Dose check** — warns if the daily dose is outside the typical range for the patient's weight.

You can override any warning with a note, but the override is recorded.

Printing & sending

- **Print** produces the paper prescription.
- If the clinic has an integrated pharmacy, the prescription is also pushed electronically (pharmacy sees it on their queue immediately).

Prescriptions History

Click **Prescriptions History** to see every prescription this patient has ever received — from any branch, any dentist, any date.

Columns: date, dentist, drugs (count + first one), status (Issued, Refilled, Cancelled), printed Yes/No.

Click any row to open the full prescription, or click **Refill** to copy it forward into a new prescription with today's date.

Billing & Payments

Two toolbar buttons close out the visit financially: **New Receipt** to take a payment, **New Bill** to print the itemised bill.

New Receipt

Click **New Receipt** to record a payment. Choose:

- **Method** — Cash, Card, Bank transfer, Insurance co-pay, Credit note.
- **Amount** — defaults to the visit's outstanding balance; can be partial.
- **Reference** — card slip number, transfer reference (when not cash).
- **Notes** — free text.

Save. A printable receipt opens — print one copy for the patient and keep the digital copy on file.

How the payment is applied

- If the visit is **fully covered by insurance**, the receipt only collects the co-pay; the rest stays on the payer's claim.
- If the patient is **self-pay**, the receipt is applied to the oldest outstanding bill first, then the current visit's bill.
- If the receipt is for **more than the balance**, the surplus stays as a **credit** on the patient's account and is applied to future bills automatically.

New Bill

Click **New Bill** to open the itemised bill for today's visit. From here you can:

- **Print** — gives the patient the formal invoice with line-by-line procedures and charges.
- **Email** — sends the same as a PDF to the patient's e-mail on file.
- **Re-price** a line (with override permission) — useful for staff discounts and goodwill adjustments. Each override is logged.
- **Apply discount** — % off the line, off the bill total, or a fixed amount.
- **Split** — split between two payers (e.g. insurance + self-pay).

Bill status

- **Draft** — still being built; you can keep adding lines.
- **Finalised** — fully priced, ready for payment / claim submission.
- **Paid** — payment receipts cover the total.
- **Submitted** — sent to the insurance payer.

Tip

For routine visits the receptionist usually skips **New Bill** entirely — **New Receipt** is enough because the patient just wants the receipt. Open **New Bill** only when the patient asks for an itemised invoice, or when you need to apply a discount or split between payers.

Administration

Clinic Reception has very little to configure on its own — it just orchestrates pieces that live in other modules. As the clinic administrator your job is mainly to make sure those pieces are set up.

Setting	Where it lives
Branches & rooms	Data Setup → Organisation → Branches / Rooms
Dentists and their schedules	Data Setup → Staff → Doctors / Schedules
Visit types	Data Setup → Clinical → Visit Types
Price list (procedure prices)	Data Setup → Billing → Price List
Insurance payers and contracts	Data Setup → Billing → Payers
Drug formulary	Pharmacy module → Formulary
Fingerprint reader	See Patient Toolbox & Fingerprint
SMS / e-mail templates	Data Setup → Communications

Per-user settings

For each receptionist user:

- **Default branch** — pre-selects the branch on every picker.
- **Default dentist** — pre-fills the dentist on new visits / appointments.
- **Permission to override prices** — needed before *Re-price* and *Discount* on the bill are clickable.
- **Permission to cancel a paid visit** — needed before the bill can be cancelled after a receipt has been issued.

See the system administrator's manual for setting these (they live on the user record, not in this workspace).

Patient Toolbox & Fingerprint

Patient Toolbox

The **Patient Toolbox** is the slim panel on the right edge of Clinic Reception. It shows context-aware shortcuts for the patient currently in the banner — the buttons that appear depend on what the patient has on file.

Common shortcuts:

- **Allergies** — pops the allergy list (red highlight if any).
- **Active alerts** — any clinical or administrative alert flagged on the patient.
- **Attachments** — upload / view ID copy, insurance card scan, consent forms, X-rays brought from elsewhere.
- **Account balance** — outstanding amount across all branches.
- **Enrol Fingerprint** — capture a fingerprint for a patient who has none on file (or add a second / third finger).
- **Last visit** — jumps straight to the most recent visit's procedures and notes.
- **Insurance eligibility check** — pings the payer's API to confirm the card is still valid before the visit starts.

The administrator decides which buttons appear and in what order, per clinic profile.

Fingerprint reader

The front desk supports any reader that exposes a standard biometric service.

One-time setup

1. Plug the reader into the workstation.
2. From the front desk, click **Patient Toolbox** → **Test Reader** — the panel should flash green when the reader is reachable.
3. If the reader is not detected, install the vendor driver and the biometric service from the IT bundle, restart the browser, and re-test.

Enrolling a finger

1. Select the patient (any way — picker, ID number).
2. Click **Patient Toolbox** → **Enrol Fingerprint**.
3. Pick the finger from the on-screen hand.
4. Place the finger on the reader. The capture takes three reads to build a template.
5. Save. The finger is now linked to that patient across every branch.

Day-to-day use

The receptionist clicks **Finger Print Scan** on the toolbar and asks the patient to place a finger. Match → banner fills. No match → fall back to **Select Patient**.

Tips

- Wipe the reader between patients.
- Enrol **two** fingers per patient (typically both index fingers) — if one is bandaged or injured the other still works.
- The biometric template is hashed; the raw print is never stored.

Metasoft Communicator

Introduction

metasoft Communicator is an integrated HMS tool that enables clinics to send WhatsApp messages, documents, reports, invoices, prescriptions, and image attachments directly to patients, suppliers, and other contacts from within HMS.

Unlike traditional WhatsApp Business integrations, Communicator does not depend on third-party messaging gateways, API configurations, or template approval processes. This reduces implementation complexity, lowers operational costs, and simplifies ongoing maintenance.

Key Benefits

- Send WhatsApp messages directly from HMS.
- Attach documents, reports, images, invoices, and prescriptions.
- Eliminate dependency on third-party WhatsApp gateway providers.
- No template creation, submission, or approval requirements.
- Reduce recurring subscription and messaging fees.
- Faster deployment and easier administration.
- Minimise development and support effort across customer installations.
- Simplify localisation and customisation for different clinics and regions.
- Ideal for small and medium-sized clinics seeking a cost-effective communication solution.
- Provides a flexible foundation for future SaaS deployments while remaining simple to operate in on-premises environments.

By eliminating the need to configure and maintain message templates for each customer, service provider, appointment reminder, or localised installation, metasoft Communicator significantly reduces implementation and support overhead while delivering a seamless communication experience directly from HMS.

How it works

The Communicator sends WhatsApp messages on behalf of HMS — appointment reminders, confirmations, prescriptions, documents, and ad-hoc messages — by driving WhatsApp Web in the background. It lives in the Windows system tray on a dedicated PC and runs around the clock.

What it does

- **Watches the HMS message queue.** When HMS adds a WhatsApp row (status *Pending*), the Communicator picks it up, sends it through WhatsApp Web, and writes the result back (*Sent* or *Failed*).
- **Lets staff send by hand** from a small in-app screen — pick a contact, type the text, attach a file, send.
- **Lists every message** with its delivery status, lets you resend, edit, pause, or delete the ones that haven't gone yet.

- **Protects the WhatsApp account** with safety guardrails — pacing, per-number caps, per-day cap, duplicate window, sending hours, surge break.
- **Stays alive** — auto-starts with Windows, lives in the tray, a watchdog relaunches it, a health monitor restarts the sender if it stops, session loss is recovered automatically.

When you need it

- Your HMS server is **outside the WhatsApp Business API** programme, or you want to keep using the personal/business WhatsApp account on a phone.
- You want **bulk-friendly pacing** and per-recipient limits without paying for an API.
- You want HMS staff to be able to send the **odd manual message** through the same path that handles the automated traffic.

Quick map

- **Getting Started** — install, scan the QR once, send your first message.
- **Features** — categorised feature list.
- **Screens** — Sender (Start/Stop + manual send + log) and Message Queue (every message with actions).
- **Everyday Use** — common tasks and quick troubleshooting.
- **Settings** — the 7 settings tabs.
- **Administration** — architecture, installation, safety guardrails, alerts, reliability internals, logs, uninstall.

→ Continue to **Getting Started**.

Getting Started

From a fresh PC to first WhatsApp message — about 10 minutes.

1. Pick the service PC

- Windows 10 / 11 that **stays powered on** (the *service* machine).
- **Google Chrome** installed.
- **.NET 6 Desktop Runtime (x64)** installed.
- Network access to the HMS SQL Server and to WhatsApp Web.
- A phone with **WhatsApp** to scan the QR code once.

2. Deploy the Communicator

Copy the Communicator into the HMS web app folder — typically into a **Communicator** subfolder alongside the running HMS — and double-click the executable to launch.

On startup it walks up the folder tree to find the HMS application settings — so it picks up the same database the running HMS uses.

3. Quick Setup wizard

The very first time it runs, the **Quick Setup** dialog appears. It does everything in one step.

1. Click **Set up now**.
2. A Chrome window opens **WhatsApp Web. Scan the QR code** with the phone — once. The login is remembered.
3. Wait for the message "*WhatsApp Web is logged in and ready.*"

After setup, the Chrome window hides itself and the Communicator continues in the system tray.

4. Install as a service (recommended)

Open **Settings** → **Deployment** → **Install Communicator**. One click sets up the whole "always on" behaviour:

- Per-user **auto-start** entry — the Communicator starts when Windows logs in.
- **Watchdog** scheduled task — relaunches the app every few minutes if it isn't running.
- **Safety guardrails** turned on with sensible defaults.
- **Start hidden to tray** — no window pops up on login.
- Tells HMS to route WhatsApp through the Communicator — the master switch is flipped to **on**.
- Starts the sender immediately.

Optional: Windows auto-login

For an unattended server that has no human present after a reboot, run **Settings** → **Deployment** → **Configure auto-login**. UAC asks for admin rights, then Windows signs in automatically next time the machine reboots. The password is stored encrypted in the Windows secret store — never in plain text.

Use only on dedicated, physically secured machines.

5. Send your first message by hand

1. Click the tray icon to open the window.
2. Go to **Sender**.
3. If status reads **Stopped**, press **Start** and wait for **Running** (green dot).
4. **Contact** — type a name (or pick a saved one).
5. **Phone** — digits, country code, no spaces.
6. **Message** — the text (Arabic is supported).
7. (Optional) **Attachment** — Browse to an image, PDF, or document.
8. Press **Send**.

The message lands in the Message Queue and is sent in turn. You can watch the **Log** panel on the right side of the Sender screen for live, colour-coded activity.

6. Verify HMS messages are flowing

Trigger a normal HMS event that produces a WhatsApp — book an appointment, issue a prescription, send a reminder — and switch to the Communicator's **Message Queue**. The new row should appear with status **Pending**, flip to **Sending**, then **Sent**.

→ Continue to **Features** for the full catalogue.

Features

Every Metasoft Communicator feature, grouped by what it lets you do.

1. Message sending

- **Automatic sending** — picks up Pending rows from the HMS message queue and sends them over WhatsApp Web.
- **Manual sending** — pick a contact (or type one), write text, attach a file, click Send.
- **Text in any language** — Arabic, emoji, multiline; pasted via the clipboard so unicode is reliable.
- **Attachments** — images, PDFs, Word, Excel, any document. Optional caption alongside the attachment.
- **Same path for HMS + manual** — both sources go through the queue, the same safety rules, the same logging.

2. Address book

- **Remembers every contact** ever used (name ↔ phone).
- **Auto-saved after each send** — no separate "add contact" step.
- **Autocomplete** in the manual-send Contact field.
- **Country-code-aware** — strips +, spaces, dashes before sending.

3. Sender screen

- **Start / Stop** the automatic sender.
- **Status pill** — Running (green), Stopped (grey) with the current queue depth.
- **Manual send block** — Contact, Phone, Message, Attachment, Send.
- **Live activity log** — colour-coded (blue info, amber warning, red error).
- **Clear log** — empties the on-screen view (file log keeps growing).

4. Message Queue screen

- **Four summary cards** — Pending / Sending / Sent / Failed counts at the top of the screen.
- **Status chips** — *All / Pending / Sending / Sent / Failed / Held* to narrow the list with one click.
- **Date filter** — From / To dates with a Clear button.
- **Per-row badge + recipient + text + attachment chip + failure reason + time + reference number.**
- **Right-to-left rendering** — Arabic messages render correctly.
- **Per-row actions** — Send (retry), Edit (change text), Pause (hold), Delete.
- **Send all unsent** — re-queue every failed / paused / stuck message in one click.

5. Statuses

- **Pending** — waiting in the queue.
- **Sending** — being sent right now.
- **Sent** — delivered to WhatsApp successfully.
- **Failed** — could not be sent; reason shown inline.
- **Held / Paused** — held on purpose (by user or by a safety rule); releases automatically when the rule clears, or via Send.

6. Always-on operation

- **System-tray application** — lives by the Windows clock, click to open.
- **Single instance** — second launches focus the existing window instead of starting a duplicate.
- **Closing the window only hides it** — Quit from the tray menu is the only way to fully exit.
- **Auto-starts with Windows** at user login.
- **Watchdog scheduled task** — relaunches the app within minutes if it isn't running.
- **Health monitor** — restarts the sender within ~1 minute if it stops while processing is on.
- **Single-instance mutex** — watchdog cannot create duplicates.

7. Crash resistance

- **Unhandled exception handlers** for UI, background, and task code — exceptions are logged and recovered without process exit.
- **Session recovery** — a lost WhatsApp session is detected and reconnected automatically.
- **True logout detection** — if WhatsApp has actually logged out (needs a fresh QR scan), an alert fires.

8. Safety guardrails

- **Minimum gap between sends** + random jitter — paces sending to avoid bursts.
- **Per-number / per-hour** cap.
- **Per-number / per-day** cap.
- **Total per-day** cap (circuit-breaker).
- **Duplicate window** — drops the same message to the same number inside the window.
- **Sending hours** — e.g. 08:00 – 20:00; outside the window messages are held.
- **Sending days of week** — e.g. skip weekends.
- **Surge protection** — too many messages in a short window auto-pauses the sender.

Each rule can be set to 0 to disable just that rule.

9. Alerts & monitoring

- **Sender-down threshold** — alert if the sender has been down for more than X minutes.
- **Surge trip alert** — alert when surge protection auto-pauses sending.
- **WhatsApp logout alert** — alert when a true logout is detected.
- **Email (SMTP)** — host, port, SSL, credentials, From / To. Works even when WhatsApp is down.
- **WhatsApp alert** — queue a message to an admin number; delivered once WhatsApp comes back.

- **Test alert** button — fires a sample alert through both channels.

10. WhatsApp engine options

- **Engine selector** — WhatsApp Web (default, supports attachments) or WhatsApp Desktop (text only, simpler).
- **Hide Chrome / console** after launch.
- **Auto-hide after login** — Chrome disappears once the QR is scanned.
- **Persistent Chrome profile** — QR scanned once; login remembered across restarts.

11. Database hookup

- **Single source of truth** — reads the same HMS application settings file the HMS web app uses; no separate connection string.
- **Polling interval** — how often to check the queue.
- **Attachment retention** — how long sent attachments are kept.
- **Default country code** — used when a number has no country code.
- **Test connection** button — proves the database hookup before enabling sending.
- **Heartbeat** — the app writes a heartbeat row so HMS can detect a dead Communicator.
- **Stuck reaper** — unsticks messages that have been in *Sending* too long.

12. Startup behaviour

- **Start with Windows** toggle.
- **Start sender** on launch — yes / no.
- **Start hidden** — no window pops up, only the tray icon.

13. Deployment tools (Settings → Deployment)

- **Install Communicator** — one click; sets up auto-start, watchdog, safety, hidden start, flips the HMS master switch on, starts sending.
- **Uninstall Communicator** — reverses everything on this PC, flips the HMS master switch off so HMS resumes its legacy sending path. Never touches data or schema.
- **Configure Windows auto-login** — encrypted credential in the Windows secret store; for unattended servers.
- **Run Quick Setup** — re-runs the first-time wizard.

14. Logging

- **Rolling main log** next to the executable — full activity log; auto-rotates at ~5 MB, keeps the last few generations.
- **Not-found-phones log** — separate file of every number WhatsApp could not find.
- **Live log panel** on the Sender screen — same data, colour-coded.

- **Per-message reason** — failed rows carry their failure reason inline.

15. In-app Help

- **Help tab** in the sidebar — short, plain-language guide built into the app.
- **Kept in sync** with every feature change as part of the release.

16. HMS integration

- **Master switch** in HMS — when on, HMS routes WhatsApp to the Communicator queue; when off, HMS uses its legacy WhatsApp path.
- **Idempotent** — disabling the Communicator does not disrupt HMS; the legacy path resumes automatically.
- **Same database** — the Communicator and HMS read / write the same message queue rows, so HMS always sees the latest status.

→ Continue to [Sender Screen](#) or [Message Queue](#) for the day-to-day UI.

Sender Screen

The **Sender** screen has three areas, top to bottom: **Status**, **Manual send**, and **Log**.



Status

Control	What it does
Start	Turns the automatic sender on.
Stop	Pauses sending — Pending rows stay in the queue.
Coloured dot	Running (green) or Stopped (grey).
Queue	How many messages are waiting to be sent.

Press **Start**; if it is the first time after a reboot the Chrome window may pop up briefly while the WhatsApp session checks in. It hides itself once it is logged in.

Manual send

The block that lets staff send a message by hand from the Communicator itself (the same path HMS messages take — so the same safety rules apply).

Field	Notes
Contact	Pick a saved contact, or type a name. The dropdown autocompletes from the address book.
Phone	Digits only — country code first, no spaces or dashes.
Message	The text. Arabic is supported and renders right-to-left.
Attachment	Optional. Click Browse to attach an image, PDF, Word, Excel, or any document.
Send	Queues the message. It then flows through the same queue and safety guardrails as HMS messages.

The contact + phone you used are auto-added to the address book on first send, so they autocomplete next time.

Log

The right-hand panel shows live, colour-coded activity:

- **Blue** — informational (started, queued, sent).
- **Amber** — warning (retry, throttled, recovered).
- **Red** — error (failed, logout, unreachable).

Clear log empties the on-screen view only — the file log on disk keeps growing and rotating.

Tips

- Keep the Sender screen open on a small monitor at the front desk so problems surface quickly — the log spells them out as they happen.
- If the status reads *Stopped* and Pending is growing, the most likely cause is the WhatsApp session — press **Start** and watch for the QR scan request.

→ Continue to [Message Queue](#).

Message Queue Screen

Every WhatsApp message — automatic or manual — flows through this screen. Use it to monitor the queue, act on stuck messages, and answer "did it actually send?" questions.



Summary cards

Four cards across the top count the messages in each state:

- **Pending** — waiting to be sent.
- **Sending** — being sent right now.
- **Sent** — delivered to WhatsApp successfully.
- **Failed** — could not be sent.

Click any card to jump the list to that state.

Filters

Filter	What it does
Status chips — <i>All / Pending / Sending / Sent / Failed / Held</i>	Narrow the list to one state.
From / To dates	Limit to a date range.
Clear	Resets every filter.

Filters compose — Failed + last 7 days, for example.

Each message row shows

- A coloured **status badge**.
- The **recipient** — phone number plus name (from the address book if known).
- The **message text** (Arabic renders right-to-left).
- A **paperclip chip** if an attachment is included.
- The **failure reason** underneath if the row is Failed (e.g. *Invalid number, Chat did not open, Throttled*).
- The **time** and a **reference number** (e.g. #16).

Per-row actions (on un-sent messages)

Action	Effect
Send	Re-queue immediately. The row flips to Sending.
Edit	Open the editor; change the text; Save. The corrected row is queued.

Action	Effect
Pause	Hold the row — it stays in the queue but is skipped until Send is pressed again.
Delete	Remove the row from the queue.

Sent messages are read-only — they cannot be edited or re-sent (HMS audit assumes Sent rows are immutable).

Bulk action

Send all unsent at the top of the screen re-queues *everything* that hasn't gone yet — Failed, Paused, Held, plus any rows stuck in Sending. Useful after fixing the cause of a batch failure (e.g. WhatsApp logged out for an hour).

Statuses cheat-sheet

Status	Meaning	What to do
Pending	Waiting in the queue.	Nothing — it will send in turn.
Sending	Being sent right now.	Nothing — wait a moment.
Sent	Delivered to WhatsApp.	Done.
Failed	Could not be sent (reason shown).	Fix the issue (e.g. number), press Send.
Held / Paused	Held by you, or by a safety rule (throttle, schedule, surge, duplicate).	Releases automatically when the rule clears, or press Send.

→ Continue to **Everyday Use**.

Everyday Use

The Communicator is designed to disappear into the background — most days nobody opens it. Here is what to know for the days you do.

How it behaves on its own

- It **starts with Windows** and runs hidden in the system tray.
- If you close the window, it only **hides** — the service is still running.
- If the app is ever killed, the **watchdog relaunches** it within a few minutes.
- If sending stops while processing is enabled, the **health monitor restarts** it within about a minute.
- If WhatsApp Web drops the session, it **reconnects** automatically.
- A true WhatsApp logout (needs a fresh QR) fires an **alert**.

Common tasks

I want to...	Do this
Resend a failed message	Message Queue → find the row → Send .
Fix a wrong message before it sends	Message Queue → Edit → change → Save.
Stop one message going out	Message Queue → Pause (or Delete).
Retry everything that failed	Message Queue → Send all unsent .
Find an old message	Use the status chips and From / To dates.
Send a document	Sender → Browse to the file → Send .
Pause all sending	Sender → Stop . Press Start to resume.
Open the window after closing it	Click the Communicator tray icon (near the clock).
Fully exit	Right-click the tray icon → Quit .

Quick troubleshooting

Symptom	Likely cause & fix
"Chat did not open" in the log	WhatsApp isn't logged in — press Start and scan the QR.
Messages stay Pending and nothing sends	Sender is Stopped — press Start. Or check internet / WhatsApp login.
A message shows " Invalid number "	The phone number is wrong — Edit it (or fix it in HMS) and press Send.

Symptom	Likely cause & fix
A message is " Held (Throttled) "	A safety limit (per-number, per-day, or sending hours) is in effect — it sends automatically later.
Surge notice appears	Surge protection auto-paused the sender — wait, or raise the limit in Safety.
I can't see the window	Click the Communicator icon in the system tray. The window opens; closing it hides it again.
Sent messages still arrive in HMS as Pending	The HMS master switch may be off — check Settings → Database and confirm the connection is to the right database.

When to call IT

- The QR scan keeps reappearing after every reboot.
- The watchdog seems to be relaunching the app constantly.
- Email alerts say sender-down repeatedly.
- The whole machine froze / blue-screened.

These are admin / installation problems — see **Administration** in the sidebar.

→ Or continue to **Settings** → **Overview** for the configuration reference.

Settings

Open from the sidebar. The settings window is split into seven tabs.



Engine

How the Communicator drives WhatsApp.

Setting	Notes
Engine	<i>WhatsApp Web</i> (default — supports attachments) or <i>WhatsApp Desktop</i> (text only, simpler).
Hide Chrome window	Chrome doesn't appear in the taskbar.
Hide console window	Hides any background console window.
Auto-hide after login	Chrome shows just long enough for the QR scan, then hides automatically.

Sending

How retries and notifications behave.

Setting	Notes
Retry attempts	How many times a failed send is retried before being marked Failed.
Retry delay	Wait between retries (seconds).
Tray notifications	Show a Windows toast for sent / failed messages.

Database

The HMS hookup.

Setting	Notes
Queue polling	How often the queue is checked (seconds). Smaller = faster pickup, more DB load.
Attachment retention	How long sent attachments are kept on disk.
Default country code	Applied when a number has no country code.
Test connection	Proves the database hookup. Always run this after a config change.
Heartbeat	The Communicator writes a heartbeat row so HMS can detect a dead Communicator.
Stuck reaper	Unsticks messages that have been in <i>Sending</i> for too long.

Safety

The guardrails that protect the WhatsApp account from being banned and recipients from being spammed. See [Safety Guardrails](#) for a deep dive.

Guardrail	Default	What it does
Min gap + jitter	8 s + 0–4 s	Paces sending.
Max per number / hour	3	Holds further messages to the same number until next hour.
Max per number / day	5	Holds until next day.
Max total per day	100	Circuit breaker — holds everything until next day.
Duplicate window	1 hour	Drops the same message to the same number inside the window.
Sending window	off (08–20)	Hold outside the configured hours.
Sending days	every day	Skip specified weekdays.
Surge protection	200 in 10 min	Auto-pauses the sender; holds the queue.

Set any individual value to **0** to disable just that rule.

Alerts

When something is wrong, tell someone.

Setting	Notes
Triggers	Sender down beyond X minutes · Surge protection trips · WhatsApp logged out.
Email (SMTP)	Host, port, SSL, username, password, From, To. Works even when WhatsApp is down.
WhatsApp alert	Queue a message to an admin number — delivered once WhatsApp resumes.
Test alert	Fires a sample alert through both channels — verify the wiring before relying on it.

Startup

Setting	Notes
Start with Windows	Add / remove the per-user auto-start entry.
Start sender on launch	If on, sending begins automatically; if off, the app opens but stays paused until you press Start.
Start hidden	The window does not appear on launch — only the tray icon.

Deployment

One-click tools for the support team.


Button	What it does
Install Communicator	Sets up auto-start, watchdog, safety guardrails, start hidden, flips the HMS master switch on, and starts the sender.
Uninstall Communicator	Reverses every change on this PC; flips the HMS master switch off; never touches data or schema.
Configure Windows auto-login	UAC-elevated; stores credentials encrypted in the Windows secret store; for unattended servers only.
Run Quick Setup	Re-runs the first-time wizard — for QR re-scans or fresh starts.

→ Continue to [Administration](#) → [Architecture](#).

Architecture

A one-page tour of how the Communicator and HMS work together.

Message flow



Components

Component	What it is	Where it runs
HMS	The hospital application that produces WhatsApp messages.	The HMS web server.
Message queue	A set of rows in the HMS database.	The HMS SQL Server.
Communicator app	A tray application that polls the queue and drives WhatsApp Web.	A dedicated Windows PC.
Background Chrome	The browser instance the Communicator pilots; persistent user-data profile remembers the WhatsApp login.	The same Windows PC.
Watchdog	A Windows Task Scheduler job that relaunches the Communicator if it isn't running.	The same Windows PC.

Component	What it is	Where it runs
WhatsApp Web	The web client running inside Chrome; speaks to WhatsApp's servers.	Internet.

Master switch

HMS only routes WhatsApp to the queue when its master switch is **on**. When it is off, HMS uses its own legacy WhatsApp path. The *Install Communicator / Uninstall Communicator* buttons flip this switch for you — no manual config edits.

Master switch	HMS behaviour
On	HMS writes new WhatsApp messages to the queue. The Communicator delivers them.
Off	HMS sends WhatsApp through its legacy code path. The queue is ignored.

What the Communicator does *not* do

- It does **not** modify the HMS database schema.
- It does **not** delete data on uninstall.
- It does **not** call WhatsApp's official API — it drives the web client of a real WhatsApp account.
- It does **not** parse the HMS payload — text and attachment go to WhatsApp as the queue says.

Why a tray application, not a true Windows service

A real Windows service runs in Session 0 with no interactive desktop — it cannot drive a browser, scan a QR, or show a tray icon. The Communicator is therefore a **tray application that auto-starts at user login** and behaves like a service for every practical purpose (auto-start, watchdog, hidden window, single instance).

For unattended servers, **Windows auto-login** plus the watchdog gives true "no human present" operation.

→ Continue to **Install & Uninstall**.

Install & Uninstall

System requirements

- Windows 10 / 11 that **stays powered on**.
- **Google Chrome** installed.
- **.NET 6 Desktop Runtime (x64)**.
- Network access to the HMS SQL Server and to WhatsApp Web.
- A phone with WhatsApp for the one-time QR scan.

Deployment layout

The Communicator is deployed into a **Communicator** subfolder inside the HMS web application — typically alongside the HMS runtime (something like `...\HMS_Web\Communicator\`). It walks up the folder tree on launch to find the HMS application settings file, so the database connection is auto-discovered.

One-click install

Settings → **Deployment** → **Install Communicator** does all of this in one step:

- Adds a **per-user auto-start** entry.
- Installs the **watchdog scheduled task** (relaunches the app every few minutes if it isn't running).
- Enables the **safety guardrails** with sensible defaults.
- Sets **Start hidden** — the window does not pop up on login.
- Sets the HMS **master switch to on** — HMS routes WhatsApp through the Communicator.
- **Starts the sender**, opening WhatsApp Web for the QR scan if there isn't a stored session yet.

After this, the Communicator is in "always on" mode — it will be running every time the PC is on, even if no human logs in (combine with auto-login below).

Windows auto-login

For an unattended server PC, **Settings** → **Deployment** → **Configure auto-login** asks Windows to sign in automatically after a reboot without a human present.

- UAC prompts for administrator rights.
- The password is stored **encrypted in the Windows secret store** — never in plain text or in a config file.
- On the next reboot, Windows logs in, the auto-start entry launches the Communicator, the watchdog confirms it is running.

Use only on dedicated, physically secured machines. A PC that auto-logs in is a PC anyone with physical access has logged-in access to.

Uninstall

Settings → **Deployment** → **Uninstall Communicator** reverses everything on this PC:

- Stops the sender and **closes the app**.
- Removes the auto-start entry.
- Removes the watchdog scheduled task.
- Removes Windows auto-login (if set).
- Sets the HMS **master switch to off** — HMS resumes its legacy WhatsApp path immediately.

It does **not**:

- Delete any data.
- Touch the database schema.
- Remove the executable folder or the logs.

So re-installing later just means running the executable again and clicking **Install Communicator** — the previous config and logs are all still there.

Moving to another PC

1. Install the Communicator on the new PC (copy folder + Install Communicator).
2. Scan the QR code on the new PC (the WhatsApp session on the old PC is automatically signed out — WhatsApp only allows one Web session at a time).
3. Confirm messages start flowing on the new PC.
4. **Uninstall Communicator** on the old PC.

Both PCs cannot run at the same time pointing at the same database — the queue rows would be claimed twice. Always finish the move within the same maintenance window.

→ Continue to [Safety Guardrails](#).

Safety Guardrails

The guardrails protect the WhatsApp account from being banned and recipients from being spammed. They run on every message — both automatic and manual.

The eight guardrails

Guardrail	Default	What it does when exceeded
Min gap + jitter between sends	8 s + 0–4 s	Waits — paces sending, looks human.
Max per number, per hour	3	Holds further messages to that number; auto-retried next hour.
Max per number, per day	5	Holds; auto-retried next day.
Max total, per day	100	Circuit-breaker — holds everything; auto-retried next day.
Duplicate window	1 hour	Drops the same message text to the same number inside the window (flagged on the queue).
Sending hours window	off (e.g. 08:00 – 20:00)	Holds outside the window; sends when it re-opens.
Sending days	every day	Skip configured weekdays.
Surge protection	200 in 10 minutes	Auto-pauses the sender; holds the queue; fires an alert.

Setting any rule to 0 = disabled

Each rule has its own zero-disables behaviour. For example, setting **Max per number, per hour = 0** disables only that one rule — the daily cap, total cap, and surge protection still apply.

What "Held" looks like

A row in the **Held / Paused** status with the **reason** under the text — e.g. *Held (Per-number daily cap)*, *Held (Sending hours)*, *Held (Surge)*. The row stays in the queue and is automatically re-evaluated when the guardrail clears.

Manual override

The receptionist can press **Send** on a held row in the Message Queue — that one row is force-released. The guardrail still counts the send (the daily cap is now closer to its ceiling). Use sparingly.

Tuning recommendations

- **New WhatsApp account** — leave defaults; they are deliberately conservative.
- **Established business account, low complaint history** — you can raise the daily total cap to 200 – 300 once you've watched the account for a few weeks.
- **High-frequency single-recipient flows** (e.g. appointment + preparation + reminder for the same patient in one day) — raise *Max per number, per day* from 5 → 8 or so.
- **After-hours quiet hours** — set Sending hours to your reception's working hours. Reminders generated overnight are queued and go out when the clinic opens.

When to widen vs. when to fix the source

- If the queue is constantly piling up at the daily total cap, that is the system telling you the WhatsApp account is being used like a bulk-marketing channel. Either widen the cap *and* watch for account warnings, or look at the HMS automation that is producing the messages and trim duplicates.
- If **Surge protection** trips, look at HMS first — usually a batch job kicked off all at once. Stagger it.

→ Continue to [Alerts & Monitoring](#).

Alerts & Monitoring

The Communicator can be left running unattended — alerts are the mechanism that wakes someone up when it can't fix itself.

Triggers

Trigger	When it fires
Sender down beyond X minutes	The sender has been Stopped (or unable to recover) for more than the configured threshold.
Surge protection trips	Too many messages in a short window — the sender auto-paused itself.
WhatsApp logged out	A true logout was detected — the session needs a fresh QR scan from a human.

Channels

Email (SMTP)

Settings → Alerts → Email block:

- **Host / Port** — e.g. `smtp.gmail.com` / `587`.
- **SSL / StartTLS** — typically on for port 587.
- **Username / Password** — service account credentials; prefer an app-specific password if your provider supports them.
- **From** — the sender shown to recipients.
- **To** — comma-separated list of admin e-mail addresses.

Works **even when WhatsApp is down** — this is the primary channel for the *WhatsApp logged out* alert.

WhatsApp

- Settings → Alerts → WhatsApp number — an admin's WhatsApp number.
- Alert messages are **queued** when an alert fires; they are delivered automatically once WhatsApp sending resumes.

Useful as a redundancy when e-mail is unreliable, less useful as the sole channel for *WhatsApp logged out* alerts (you may never see it until the session is back).

Test alert

The **Test alert** button fires a sample alert through both channels. Run it after every config change — confirms the wiring works before you need it to work.

What ends up in alerts

A short text — the trigger name, a timestamp, the host name, the current queue depth, and any reason text the Communicator was able to collect. No patient data, no message content.

Monitoring beyond alerts

- **Heartbeat row** — the Communicator writes a heartbeat row to the database every cycle. HMS dashboards can show "last heartbeat at ..." as a live indicator.
- **Watchdog logs** — the Task Scheduler watchdog records every relaunch — useful for spotting flapping.
- **Log file** — see [Logs](#) for what is logged and where.

Recommended monitoring stack

1. **Email alerts** to the IT admin's inbox for serious events.
2. **WhatsApp alerts** to a clinic manager's phone for surge / pause.
3. A **dashboard tile** in HMS showing the last heartbeat (built-in if you use the HMS dashboards).
4. **Weekly review** of the *not-found-phones* log to clean up bad numbers at source.

→ Continue to [Reliability](#).

Reliability

Five mechanisms keep the Communicator running 24 × 7 without a human in the room.

1. Watchdog (relaunch)

A Windows Task Scheduler job runs every few minutes. If the Communicator isn't running, the watchdog launches it.

- A single-instance mutex prevents duplicates — if the app *is* running, the watchdog's launch is a no-op.
- If the watchdog itself is removed (e.g. by an over-zealous admin), the *Install Communicator* button re-creates it.

2. Health monitor (sender restart)

A background loop inside the app checks once a minute that the sender is running when it should be. If processing is enabled but the sender has stopped (browser crash, lost session, unhandled stall), the health monitor restarts the sender within ~1 minute.

The user sees a small entry in the log; no manual action needed.

3. Crash handlers

The app wires global crash handlers in three places:

- **UI thread** — unhandled exceptions in window code.
- **Background tasks** — unobserved task exceptions.
- **App domain** — anything not caught by the first two.

Every catch logs the exception and **does not exit the process** — the watchdog + health monitor would relaunch / restart anyway, but not exiting keeps the queue moving.

4. Session recovery

The browser layer watches for the "you are no longer logged in" state. Two cases:

- **Soft disconnect** (e.g. network blip) — Chrome reconnects to WhatsApp; the Communicator continues. No alert.
- **True logout** (e.g. WhatsApp force-signed-out from another device, or the QR session expired) — needs a human to scan a QR. An alert fires; the sender stops; the queue holds.

5. Single-instance mutex

The watchdog can trigger a second launch attempt at any time. The mutex ensures only one instance owns the database queue and the Chrome profile — duplicates exit immediately.

The same mutex makes "click the icon to bring it forward" reliable — a second launch focuses the existing window instead of starting a duplicate.

What this means in practice

Failure mode	What happens
App killed by Task Manager	Watchdog relauches in <5 min.
App crashed	Crash handler logs and recovers; if the process did exit, watchdog relauches.
Sender stopped without a crash	Health monitor restarts within ~1 min.
WhatsApp Web session dropped	Auto-reconnect; user-invisible.
WhatsApp truly logged out	Alert; needs a human QR scan.
Windows reboot	Auto-login (if configured) → auto-start entry → app running again.
HMS database down	Sender goes idle, retries on next polling cycle. No data lost — pending rows stay pending.
Chrome killed	App relauches Chrome on the next cycle.
Disk full	Crash handler catches log-write failures; app continues; alert fires.

→ Continue to [Logs](#).

Logs

Two log files sit next to the executable. Both rotate automatically.

Main activity log

Every notable event is recorded:

- App start / stop / config change.
- Sender start / stop.
- Each queue pickup (row reference, recipient, type).
- Each send attempt and its outcome (Sent, Failed, Held + reason).
- WhatsApp session events — connected, disconnected, logged-out.
- Watchdog / health-monitor actions.
- Exceptions (with stack trace).

Rotation: the file grows to ~5 MB then is rolled; the last few generations are kept. Old files are removed automatically.

Not-found-phones log

A separate file lists every phone number WhatsApp could not find ("*Phone number shared via url is invalid*" and friends). It is append-only — no rotation — because clinics want to be able to bulk- clean these numbers in HMS.

Workflow: open the file weekly, copy the numbers, search them in HMS, fix or remove. The file does not delete itself when entries are fixed.

Live log panel

The Sender screen mirrors the main log in real time, colour-coded (blue / amber / red). **Clear log** empties the on-screen view only — the file on disk is untouched and keeps growing.

What is *not* logged

- Message body of WhatsApp messages (privacy).
- Patient identifiers beyond what is already visible in the queue row (reference number, recipient name from the address book).
- Passwords or SMTP credentials.

Sharing logs with support

If support asks for logs:

- The main log file — the active one and the most recent rotated generation are enough for most issues.

- The not-found-phones log — only if the complaint is about specific numbers.

Logs can be zipped and e-mailed safely — they do not contain message content.

Permanent archiving

Logs are designed for short-term troubleshooting (days to weeks). If a longer audit trail is required, set up a scheduled task to copy the rotated generations to a NAS or log-aggregation tool nightly.

→ Continue to [Architecture](#) if you arrived here directly.

metasoft NPHIES BridgeProxy

BridgeProxy is a small Windows service + tray dashboard that lets HMS talk to **NPHIES** (Saudi Arabia's national health-information platform) when the HMS server cannot reach NPHIES directly.

Why it exists

NPHIES authorises providers by **source IP address**. It accepts FHIR traffic only from IP addresses that:

- Have been white-listed by NPHIES, **and**
- Are located **inside Saudi Arabia**.

When HMS runs outside KSA (for example, in Lebanon), or from a network whose public IP is not whitelisted, HMS cannot communicate with NPHIES directly.

BridgeProxy is installed on a small Windows machine **inside KSA** with a whitelisted IP. HMS sends its NPHIES traffic to the proxy; the proxy forwards it to NPHIES from the whitelisted IP and returns the response verbatim.

What it does — and what it does not do

Does	Does not
Listens for HMS requests on a TCP port.	Parse the FHIR payload.
Forwards bytes to NPHIES.	Modify the request or response.
Returns the response verbatim.	Cache, log, or store FHIR data.
Counts requests / OK / errors.	Authenticate the HMS caller — it relies on network reach + a shared API key.
Tests connectivity to Sandbox / Production.	Replace the NPHIES SSL or certificate handshake — both sides remain end-to-end TLS.

As a result, **HMS behaviour is unchanged** regardless of its physical location.

Two components

Component	What it is	Runs as
BridgeProxy.Service.exe	The proxy itself. Listens on a TCP port, forwards to NPHIES.	Windows service, auto-start.
BridgeProxy.Tray.exe	The dashboard — system-tray icon + management window for Start/Stop, configuration, diagnostics.	Per-user, auto-starts at login.

Quick map

- **Getting Started** — install, first connection test, point HMS at it.
- **Features** — categorised feature list.
- **Dashboard** — one page per tab (Status, Configuration, Send to NPHIES).
- **Administration** — installation, uninstall, HMS-side configuration, diagnostics.

→ Continue to **Getting Started**.

Getting Started

Install BridgeProxy, verify it reaches NPHIES, and point HMS at it.

1. Pick the host machine

- It must be **inside Saudi Arabia**.
- Its **public IP** must be one of the IPs already whitelisted with NPHIES (or about to be whitelisted).
- **Windows Server** or Windows 10/11 with admin rights.
- Always-on — the HMS server depends on it for every NPHIES call.

2. Install

1. Copy the BridgeProxy folder to `C:\BridgeProxy\`.
2. Run **INSTALL.cmd** and accept the UAC prompt.

During first launch the installer:

- Asks for the listening port (default: **5500**).
- Installs and starts the Windows service.
- Creates an inbound Windows Firewall rule.
- Configures the tray application to start automatically at login.
- Displays the tray icon (a shield).

3. Open the dashboard

Double-click the shield tray icon. The dashboard window opens on the **Status** tab.

Confirm:

- **Service** shows *Running*.
- **Port** shows the port you chose.
- **Server IP** lists the host's local IP addresses.

4. Test connectivity to NPHIES

Click **Test Sandbox** — verifies the host can reach the NPHIES sandbox gateway. Should turn green.

Click **Test Production** — same for the production gateway.

If either fails:

- Open **Diagnostics** (next button) for a full network report.
- Confirm the host's **public IP** is whitelisted with NPHIES.

5. Configure HMS to use the bridge

On the HMS application server:

1. Open **NPHIES Settings** → **Bridge**.
2. **Use Bridge** → enable. (Enable this when HMS runs outside KSA or its IP is not static / whitelisted.)
3. Set the **Bridge URL** to the BridgeProxy host (e.g. `http://203.0.113.10:5500`).
4. Click **Test Connection** — HMS should be able to reach the proxy.
5. (Optional) Click **Configure Firewall (Outbound)** to open the outbound port from HMS to the bridge automatically.

6. First real submission

Send any normal NPHIES message from HMS — eligibility check, pre-authorization, claim. The proxy forwards it; HMS gets the same response it would have received talking to NPHIES directly.

On the dashboard, the **Requests / OK / Errors** counters tick up.

7. Verify from the bridge side

Click **Inbound Check** in the dashboard — confirms HMS can still reach the bridge.

Use **Send to NPHIES** (third dashboard tab) to send a manual test request from the bridge itself — handy when troubleshooting whether the issue is HMS or the bridge.

→ Continue to **Features** for the complete catalogue, or **Dashboard** → **Status** for day-to-day use.

Features

Every BridgeProxy feature, grouped by what it lets you do.

1. Network bridging

- **Source-IP relay** — every outbound call to NPHIES leaves from the bridge's whitelisted IP, regardless of where HMS is located.
- **Verbatim forwarding** — bytes in, bytes out. No payload parsing, no rewriting, no caching.
- **TLS pass-through** — end-to-end TLS between HMS and NPHIES is preserved.
- **No FHIR coupling** — works for any NPHIES message version without upgrades; the proxy is content-agnostic.
- **Allowed-hosts whitelist** — refuses to forward to anywhere other than the configured destination hosts.
- **API key** — shared secret between HMS and the bridge; rejects unauthorised callers.

2. Deployment

- **Single-folder install** — copy `C:\BridgeProxy\`, run `INSTALL.cmd`.
- **Auto-installed Windows service** — `BridgeProxy.Service.exe` runs on boot as a system service.
- **Auto-installed tray dashboard** — `BridgeProxy.Tray.exe` starts on login for every interactive user.
- **Configurable listening port** — chosen during install, changeable later from the dashboard.
- **Automatic inbound firewall rule** — installer opens the chosen TCP port.
- **Clean uninstall** — `UNINSTALL.cmd` removes the service, firewall rules, and scheduled task. Configuration and logs are preserved for audit / reinstall.

3. Service management (Dashboard → Status)

- **Service state** — Running / Stopped / Starting at a glance.
- **Listening port** — current TCP port.
- **Server IP** — every local IP address of the host (so you know what NPHIES sees as your source).
- **Uptime** — time since the service last restarted.
- **Live counters** — Requests / OK / Errors since service start.
- **Start / Stop / Restart** buttons — control the Windows service without opening the Services console.

4. Connectivity tests

- **Test Sandbox** — TCP + TLS reach to the NPHIES sandbox gateway.
- **Test Production** — same for the production gateway.
- **Diagnostics** — full network diagnostic sweep (DNS, route, TLS handshake, gateway reach) in one click.
- **Inbound Check** — verifies HMS can reach the bridge (useful when diagnosing whether the issue is HMS-to-bridge or bridge-to-NPHIES).

5. Configuration (Dashboard → Configuration)

- **Port** — listening TCP port (changeable; service restarts on save).
- **Timeout** — request timeout in seconds.
- **Allowed Hosts** — comma-separated whitelist of destination hosts the proxy will forward to.
- **API Key** — read-only display of the shared secret (rotated via the configuration file).
- **Save & Restart Service** — applies any change and restarts the service in one click.
- **Open Firewall Port** — re-creates the inbound firewall rule if someone has removed it.

6. Manual testing (Dashboard → Send to NPHIES)

- **Target selector** — Sandbox / Production / Custom URL.
- **Custom URL** — send a hand-typed request to any whitelisted host (useful for testing new endpoints before HMS supports them).
- **Sends from the bridge** — proves the host's NPHIES reach without needing HMS to be involved.

7. HMS-side configuration (HMS → NPHIES Settings → Bridge)

- **Use Bridge** toggle — switch HMS between *direct* and *bridged* NPHIES traffic without restart.
- **Test Connection** — from HMS to the bridge.
- **Configure Firewall (Outbound)** — opens the outbound port from the HMS server to the bridge automatically.

8. Safety & operations

- **Configuration & logs preserved on uninstall** — re-install is a drop-in.
- **No data persistence** — FHIR payloads are not stored anywhere on the bridge.
- **Counter-only telemetry** — only Requests / OK / Errors are tracked.

→ Continue to [Dashboard](#) → [Status](#) for day-to-day operations.

Status Tab

The **Status** tab is the dashboard's home page — live service information and one-click control of the service.

Live service information

Field	What it shows
Service	Running, Stopped, or Starting.
Port	The TCP port the service is listening on.
Server IP	Every local IP address the host has — what NPHIES sees as your source IP.
Uptime	Time since the service was last restarted.
Requests / OK / Errors	Live counters since service start.

The counters give you a real-time pulse — if Requests is climbing but OK is flat, something downstream is broken; if Requests is flat, something between HMS and the bridge is broken.

Action buttons

Button	What it does
Start	Starts the Windows service.
Stop	Stops the Windows service. Use sparingly — HMS NPHIES traffic halts immediately.
Restart	Stop + Start, useful after a configuration change saved without the <i>Save & Restart Service</i> button.
Test Sandbox	TCP + TLS reach to the NPHIES sandbox gateway. Green = good.
Test Production	Same as Test Sandbox, against the production NPHIES gateway.
Diagnostics	Runs a full network diagnostic sweep — DNS resolution, route, TLS handshake, gateway reach. Output appears in a results pane.
Inbound Check	Verifies HMS can reach the bridge — answers " <i>is the problem on the HMS side?</i> " in one click.

Reading the test results

- **Green** = success. The bridge has full reach.
- **Yellow / orange** = degraded. Partial reach (TCP fine, TLS fails; or one gateway reachable, the other not).
- **Red** = failure. Open **Diagnostics** for the detailed report and fix from the bottom up: DNS → route → TLS → gateway.

→ Continue to [Configuration](#).

Configuration Tab

Settings the bridge service uses. Changes apply on **Save & Restart Service**.

Settings

Setting	What it does
Port	The listening TCP port. Default 5500. Change if the chosen port is already in use; the firewall rule is updated automatically.
Timeout	Request timeout in seconds. Increase only if NPHIES is intermittently slow — long timeouts hold connections open and can hide real outages.
Allowed Hosts	Comma-separated whitelist of destination hosts the proxy will forward to. Requests for anything outside this list are rejected. Pre-populated with the sandbox and production NPHIES hosts.
API Key	Read-only display of the shared secret between HMS and the bridge. Rotate by editing the configuration file directly on the host.

Buttons

Button	Effect
Save & Restart Service	Persists changes to the configuration file and restarts the service so the new values take effect. There is a brief window where the proxy is unavailable — schedule for low-traffic times.
Open Firewall Port	Re-creates the inbound Windows Firewall rule for the current port. Use this if someone manually removed the rule, or after changing the port.

Allowed Hosts — what to put in

Only the NPHIES hosts you legitimately need:

- `nphies.sa` and any production sub-domains.
- `sandbox.nphies.sa` for testing.

Do **not** widen the list to include arbitrary internet hosts — the whitelist is the only place that limits what the proxy can reach.

Port — picking a safe value

- Default **5500** works for most clinics.
- Avoid common ports (80, 443, 3389, 5432, 1433, 1521) — they collide with web servers, RDP, databases.
- Pick from the registered range (1024 – 49151).
- Whatever you pick, the HMS *Bridge URL* on the HMS side has to match — change one, change both.

→ Continue to [Send to NPHIES](#).

Send to NPHIES Tab

A manual-testing utility — send a request straight from the bridge to NPHIES without HMS being involved. Useful when you need to isolate whether a failure is on the HMS side or the bridge side.

Target options

Target	What it does
Sandbox	Sends the request to the NPHIES sandbox gateway. Safe — no real claims are created.
Production	Sends to the production gateway. Use with care — real submissions count.
Custom URL	Send to any URL within the Allowed Hosts whitelist. Useful for testing new endpoints before HMS supports them.

When to use this tab

- **HMS reports a NPHIES failure** — replay the same payload from here. If the bridge succeeds, the issue is on the HMS side; if it fails the same way, the issue is bridge or NPHIES.
- **A new NPHIES endpoint** — verify the bridge can reach it before upgrading HMS to use it.
- **Connectivity drill** — quick check from a fresh install before pointing HMS at the bridge.

What does *not* belong here

- **Real clinical submissions** — those should always come from HMS so the response is captured against the right patient / claim record.
- **Load tests** — the manual tool sends one request at a time and is not designed for performance work.

Installation

The installer is a single command. It registers the Windows service, opens the firewall, configures auto-start, and shows the tray icon.

Prerequisites

- **Windows Server / Windows 10 / 11** with administrator rights.
- The host is **inside Saudi Arabia**.
- The host's **public IP is whitelisted with NPHIES** (or will be).
- The chosen TCP port is **free**.

Install

1. Copy the BridgeProxy folder to `C:\BridgeProxy\`.
2. Right-click **INSTALL.cmd** → **Run as administrator** (or simply double-click and accept the UAC prompt).
3. When asked, enter the listening port. The default **5500** is fine for most clinics.
4. Wait for the installer to finish — the tray icon (a shield) appears when it's done.

The installer:

- Registers `BridgeProxy.Service.exe` as a Windows service set to auto-start at boot.
- Creates an inbound Windows Firewall rule for the listening port.
- Sets `BridgeProxy.Tray.exe` to auto-start at login (Scheduled Task).
- Launches the tray application.

Post-install checklist

Step	Where
Confirm Service = Running	Dashboard → Status
Confirm Test Sandbox is green	Dashboard → Status
Confirm Test Production is green	Dashboard → Status
Confirm Allowed Hosts lists the right NPHIES hosts	Dashboard → Configuration
Configure HMS to use the bridge	HMS → NPHIES Settings → Bridge
Send a test eligibility check from HMS	HMS
Verify counters tick up	Dashboard → Status

Where things go

Item	Location
Service binary	C:\BridgeProxy\BridgeProxy.Service.exe
Tray binary	C:\BridgeProxy\BridgeProxy.Tray.exe
Configuration file	C:\BridgeProxy\ (alongside the binaries)
Logs	C:\BridgeProxy\logs\
Firewall rule	Windows Firewall → Inbound Rules → <i>BridgeProxy</i>
Scheduled Task	Task Scheduler → <i>BridgeProxy Tray</i>

Multi-user host

The tray dashboard auto-starts at login **per user**. The service is shared. If several Windows users sign in to the host, each sees their own tray icon; clicking either opens the same dashboard pointing at the same service.

Uninstall

Run **UNINSTALL.cmd** as Administrator.

It removes:

- The Windows service.
- The inbound Windows Firewall rule.
- The Scheduled Task that auto-starts the tray dashboard.

It **preserves**:

- The configuration file.
- The logs folder.
- The binaries themselves under `C:\BridgeProxy\`.

This makes re-install a drop-in — run `INSTALL.cmd` again on the same folder and the previous configuration and logs are picked up.

Fully removing the install

If you need to wipe the host clean:

1. Run **UNINSTALL.cmd** as Administrator.
2. Delete `C:\BridgeProxy\` (folder + everything inside).
3. (Optional) Archive the `logs\` folder first if you need the audit trail.

Reverting HMS to direct mode

Before you stop the bridge, switch HMS back to direct NPHIES:

1. Open **HMS** → **NPHIES Settings** → **Bridge**.
2. **Use Bridge** → off.
3. **Test Connection** — confirms HMS can reach NPHIES directly.

Otherwise HMS keeps trying to send through a bridge that no longer exists.

Moving the bridge to another host

The cleanest path:

1. Install BridgeProxy on the new host. Verify Test Sandbox / Production both go green.
2. Update **HMS** → **NPHIES Settings** → **Bridge** → **Bridge URL** to point at the new host.
3. Click **Test Connection** in HMS — confirms it switched.
4. Uninstall BridgeProxy on the old host.

Both hosts can coexist for a few minutes — the old one simply stops receiving traffic once HMS is repointed.

HMS Configuration

The bridge does nothing useful until HMS is told to route NPHIES traffic through it.

Where

In HMS, open **NPHIES Settings** → **Bridge**.

Settings

Setting	Meaning
Use Bridge	The master switch. Enable when HMS runs outside KSA or its IP is not static / whitelisted. Disable to send NPHIES traffic directly.
Bridge URL	The TCP endpoint of the bridge — e.g. <code>http://203.0.113.10:5500</code> . Must match the bridge host's reachable IP and listening port.
API Key	The shared secret. Must match the API Key shown on the bridge's <i>Configuration</i> tab.
Timeout	Optional override for the request timeout.

Buttons

Button	What it does
Test Connection	Sends a no-op to the bridge and verifies the round-trip. Use after any change.
Configure Firewall (Outbound)	Asks Windows to open the outbound port from the HMS server to the bridge — saves a trip to IT.

When to enable

Situation	Enable Bridge?
HMS server inside KSA on a whitelisted static IP.	No — use direct.
HMS server outside KSA.	Yes.
HMS server inside KSA on a dynamic / consumer IP.	Yes — until the IP is whitelisted.
HMS server inside KSA on a static IP awaiting whitelisting.	Yes as a temporary bridge.
Multi-site HMS where some sites need bridging and some don't.	Per-site setting — toggle at the right tenant.

After enabling

- All existing NPHIES configuration (provider IDs, payer codes, eligibility forms) keeps working. The bridge is transparent.
- Response times can go up by a few hundred milliseconds (extra network hop). If you see seconds of added latency, the bridge host may be on a slow link.

Switching back to direct

Disable **Use Bridge** and click **Test Connection**. HMS connects to NPHIES directly again. Any pending submissions in the HMS queue re-try on the new path.

Verifying the round-trip

After **Use Bridge** is on:

1. **HMS → Test Connection** turns green.
2. Submit any real NPHIES check (eligibility for any patient).
3. On the bridge **Dashboard → Status**, the **Requests** counter ticks up by one and **OK** ticks up by one shortly after.

If Requests ticks but OK does not, the bridge reached HMS but NPHIES rejected the call — open Diagnostics on the bridge.

Diagnostics

When connectivity isn't green, **Diagnostics** is the one-click sweep that tells you which layer is broken.

How to run it

Dashboard → **Status** tab → click **Diagnostics**. The results pane fills with a tiered report.

What it tests, in order

The sweep walks the network stack bottom-up so you can fix from the root.

Tier	Checks	Failure means
DNS	Can the host resolve <code>nphies.sa</code> and the sandbox host name?	DNS server unreachable or misconfigured — fix <code>ipconfig /all</code> first.
Route	Is there an IP route to the gateway?	Default gateway or routing table problem.
TCP	Three-way handshake to port 443 on the NPHIES host.	Firewall (host or network) blocking outbound 443.
TLS	Successful TLS 1.2/1.3 handshake.	Outdated TLS stack on the host, or a TLS-intercepting proxy in the way.
Gateway	Sends a no-op probe to the NPHIES gateway and gets a response.	NPHIES side is up but rejecting — most often, the host's public IP is not whitelisted.

Reading the output

- Every tier ends in **OK** or a specific error line.
- Stop at the first failure — fixing it usually clears the ones below.
- The report is plain text — copy it into a support ticket if you escalate.

Adjacent buttons

- **Inbound Check** — separate sweep that verifies HMS can reach *this* host (i.e. the bridge from HMS's point of view). Useful when bridge → NPHIES is green but HMS still can't submit.
- **Test Sandbox / Test Production** — quick green / red on the gateway specifically, without running the full DNS/route/TCP/TLS walk. Use these for the fast pulse; use Diagnostics when something is actually broken.

Common failures and fixes

Symptom	Likely cause	Fix
DNS fails.	Wrong DNS server on the host.	Set a working DNS server (Cloudflare 1.1.1.1, Google 8.8.8.8, or your ISP's).
Route fails.	Default gateway missing.	Check NIC configuration.
TCP fails.	Outbound 443 blocked.	Open the firewall — host AND network.
TLS fails.	Old Windows / TLS-intercepting proxy.	Update Windows; bypass the corporate proxy for NPHIES hosts.
Gateway fails.	Source IP not whitelisted with NPHIES.	Confirm the host's public IP, contact NPHIES to whitelist.
Inbound Check fails.	HMS server can't reach the bridge.	Check the path <i>from HMS to the bridge</i> : firewall on bridge, network route, HMS <i>Bridge URL</i> value.

Human Resources Module

The **Human Resources** module manages the full employee lifecycle in HMS: from recruitment, hiring and contracting, through day-to-day personnel actions (transfers, promotions, appraisals, leaves, sick leave, document expiry), all the way to end-of-service settlement. The **Payroll** sub-module turns this data into monthly salaries, deductions, loans and pay slips.

What you can do in HR

- **Maintain an employee master file** — personal data, contact, documents (passport, residence, visa, council certificates), bank, dependants, qualifications, experience.
- **Manage the organisation chart** — branches, departments, positions and vacancies, salary packages, periodic allowances.
- **Run recruitment** — register candidates, link them to vacancies and recruitment agencies, convert candidates into employees.
- **Issue and renew contracts** — fixed-term, part-time, renewable, with automatic alerts 30 and 180 days before expiry.
- **Record personnel actions** — termination, promotion / demotion, transfer, salary change, with a three-level approval workflow (Department Head → Project Director → Hospital Director).
- **Process leaves** — annual vacation requests, sick leave, educational leave, travel authorisation, leave extensions, dependant tickets.
- **Run appraisals** and link them to re-contracting and salary raises.
- **Track expiring documents** — passports, residences, visas, S.C.C. certificates — with built-in alerts.
- **Process payroll** — pay codes, pay runs, registers, pay slips, loans.
- **Print 25+ HR reports** — staff lists by nationality / sponsor / religion, salary registers, due vacations, recruitment, Saudization, termination, turnover, ...

How to open the module

From the HMS main menu open **Human Resources** (and **Payroll** for the pay-cycle pages). The module is registered in `MAIN_Menu` as:

Menu entry	Module code	Launched by
Human Resources	HR	Admin.exe
Payroll	PR	Admin.exe

Module map

```
HR
├─ Master files
│   ├── Employees ..... HR_Employee.FT   ▶ search via HR_Employee_Fast.ST
│   ├── Departments ..... HR_Department.FT
│   ├── Positions ..... HR_POSITION.FT
│   ├── Packages (salary) .... HR_PACKAGE.FT
│   ├── Periodic Allowances .. HR_PRDALW.FT
│   ├── Agencies ..... HR_Agency.FT
│   └─ Certificates ..... HR_Certificate.FT
└─ Recruitment
```

```

|   |─ Vacancies ..... HR_VACANCY.FT
|   |─ Candidates ..... HR_Candidate.FT
|─ Contracts ..... HR_Contract.ft
|─ Personnel Actions ..... HR_Action.FT
|─ Appraisals ..... HR_Appraisal.FT
|─ Leaves
|   |─ Vacation request ..... HR_Vacation.FT
|   |─ Travel auth ..... HR_VAUTH.FT
|   |─ Extension ..... HR_Extension.FT
|─ Documents
|   |─ Visa ..... HR_VISA.FT
|   |─ Sick leave ..... MF_SickLeave.FT / MF_SickLeave2.FT
|─ Overview dashboard ..... HR_Overview.ST (branch-filtered)
|─ Reports ..... ~25 RPT/INI under Report template/

```

PR (Payroll)

```

|─ Pay Codes ..... PR_PayCode.FT
|─ Pay Runs ..... PR_PayRun.FT
|─ Registers & slips ..... PR_Register
|─ Loans ..... PR_Loan

```

→ Continue to [Getting Started](#) or jump straight to [Employees](#).

Getting Started with HR

This walkthrough takes you from a freshly-installed HMS to your first fully-paid employee in **10 steps**. Allow about 30 minutes for the first employee; subsequent employees take 2–3 minutes.

!!! tip "Before you start" Make sure the **HR Administrator** role is assigned to your user, and that the **Branches** lookup contains at least one branch (Abha, Dammam, Riyadh, Qassem, Jeddah are the factory defaults shipped with the demo).

1. Set up the organisation

1. Open **Data Setup** → **HR** → **Branches** and add your hospital branches.
2. Open **Data Setup** → **HR** → **Departments** (`HR_Department.FT`) and add each department. Set the **Cost Centre** (`HRD_CstCtr`) — it is used by Payroll for GL postings.
3. Open **Data Setup** → **HR** → **Positions** (`HR_POSITION.FT`) and add the job titles you use. The **Vacation Days per Year** field becomes the default annual leave for any contract on this position.

2. Create salary packages

Open **HR** → **Packages** (`HR_PACKAGE.FT`) and define each standard salary package (e.g. *Consultant — Saudi*, *Nurse — Expat*). A package is a template for basic + allowances that you reuse on contracts.

3. Define periodic allowances

Open **HR** → **Periodic Allowances** (`HR_PRDALW.FT`) for fixed monthly add-ons that are not part of the package (e.g. *Mobile*, *Schooling*, *Housing top-up*).

4. Open vacancies

Open **HR** → **Vacancies** (`HR_VACANCY.FT`) and add the open positions you are recruiting for. A vacancy ties together **Branch + Department + Position + Required nationality / gender + Recruitment source**.

5. Register candidates

For each applicant open **HR** → **Candidates** (`HR_Candidate.FT`) and record personal data, passport, residence, expected arrival (ETA) and the **Vacancy** they applied for. Candidates can be linked to a **Recruitment Agency** (`HR_Agency.FT`).

6. Hire — convert candidate to employee

Open the candidate and use **Actions** → **Hire** (or open the employee form directly via **HR** → **Employees** (`HR_Employee.FT`). The candidate's personal data is copied into the new `HR_Employee` record and an **Employee ID** is auto-generated by the `HR_Employee` counter.

7. Issue the first contract

On the employee form go to the **Contracts** tab and add a new contract (`HR_Contract.ft`):

- Start / end dates

- Package (auto-fills basic + housing + transportation + mobile)
- Tickets per year (employee / family)
- Vacation days
- Type (married/single, permanent/part-time)

8. Add allowances & dependants

Use the **Allowances**, **Dependants**, **Qualifications** and **Experience** tabs of the employee form to complete the file.

9. Configure payroll codes

Open **Payroll** → **Pay Codes** (`PR_PayCode.FT`) and verify that the shipped factory codes (BAS, HOU, TRA, MOB, GOSI, ...) match your chart-of-accounts. Add custom deduction codes (e.g. *Loan repayment*, *Salary advance*).

10. Run the first payroll

Open **Payroll** → **Pay Run** (`PR_PayRun.FT`):

1. Set the **Period Start** (first of month).
2. Choose **Branch** and (optionally) **Department** to restrict the run.
3. Click **Generate**. A **PR_Register** is created with one **PR_RegDet** line per employee × pay code.
4. Review, post to GL, and print pay slips (`PR_PaySlip.rpt`).

→ Continue to **Employees** → **Personal Info**.

Employees

The **Employee** record is the heart of the HR module. Every other HR object (contract, salary, action, leave, payroll register) hangs off an `HR_Employee.Id`.

How to open

- **HR menu** → **Employees** — opens the searchable list (`HR_Employee_Fast.ST` , also reachable from any picker via the *Employee* lookup).
- From a vacancy or candidate — the **Hire** action creates a new employee linked back to the source candidate.

The Employee form (`HR_Employee.FT`)

The form is organised into **16 tabs**:

#	Tab	What it holds
1	Personal	Name (EN/AR), date & place of birth, gender, nationality, religion, marital status, ID photo
2	Employment	Branch, department, position, vacancy, status, joining date, attendance card
3	Contracts	List of contracts (<code>HR_Contract.ft</code>) — start/end, package, basic, ticket entitlement
4	Qualifications	Degrees, certifications, S.C.C. (Saudi Council) certificate number / expiry / profession
5	Salary	Salary history (<code>HR_Salary</code>) — every package or action change creates one row
6	Allowances	Per-employee allowances (<code>hr_employee_allowance</code>)
7	Tickets	Travel tickets owed and used (<code>hr_employee_ticket</code>)
8	Leaves	Vacation entries (<code>hr_employee_vacation</code>), accrued / taken / remaining
9	Overtime	Overtime hours (<code>hr_employee_overtime</code>)
10	Dependants	Spouse and children (<code>HR_Employee_child</code>)
11	End of Service	EOS settlement — last working day, years of service, EOS amount
12	Notes	Free-text notes
13	Contact	Address, phone, mobile, email, P.O. Box, ZIP, emergency contact (SOS)
14	Experience	Prior work history (<code>HR_EMPLOYEE_Experience</code>)
15	Earned Leaves	Computed earned leave balance
16	Incentives	Performance / spot bonuses (<code>HR_Incentive</code>)

Banner

A green **banner** at the top of the form (procedure `HR_EMPLOYEE_BANNER`) shows at a glance: full name, employee number, position, department, branch, and contract status.

Alerts

Two alert strips scroll at the top:

- **HR_EMP_Alert** — expiring documents (passport, residence, S.C.C., contract end, visa) within the next 30 days.
- **HR_EMP_Note_Alert** — any free-text note flagged as alert.

Underlying tables

Table	Use
<code>HR_Employee</code>	Master record
<code>HR_PKT_Employee</code>	Edit-buffer (ghost table) — your unsaved changes live here until Save
<code>HR_Employee_child</code>	Dependants
<code>HR_EMPLOYEE_Experience</code>	Prior employment
<code>hr_employee_qualification</code>	Diplomas / certificates
<code>hr_employee_vacation</code>	Vacation history
<code>hr_employee_ticket</code>	Tickets
<code>hr_employee_overtime</code>	Overtime hours
<code>hr_employee_allowance</code>	Personal allowances
<code>HR_Salary</code>	Salary history (one row per change)
<code>HR_PKALW</code>	Package allowance breakdown

→ Next: [Personal Info](#)

Personal Info (Tab 1)

The **Personal** tab captures the legal identity of the employee.

Fields

Group	Field	Notes
Name (EN)	First / Father / Grand-Father / Family	Required. Used on contracts, pay slips, certificates.
Name (AR)	الاسم / الأب / العائلة	Stored in <code>HR_EMP_First_A</code> , <code>HR_EMP_Father_A</code> , <code>HR_EMP_Family_A</code> . Required for Saudi labour-office filings.
Birth	Date of Birth, Place of Birth	
Identity	Gender, Nationality, Religion, Marital Status, Blood Group	All come from look-up tables (Data Setup).
Impairment	Impaired (yes / no)	Drives the <i>Disability</i> line in regulatory reports.

Tips

- The **full name** field (`HR_EMP_NAME` / `HR_EMP_NAME_A`) is computed automatically from the four name parts on save — never edit it directly.
- Use the **photo** placeholder on the right to attach an ID picture (drag-and-drop or click *Browse*). Photos are stored under `wwwroot/upload/` per the **Imaging** settings.
- The **Saudi Council Certificate** block on the *Qualifications* tab uses the *Nationality* set here to enable / disable validation.

Employment (Tab 2)

The **Employment** tab is what links a person to a job inside the hospital.

Fields

Field	DB column	Purpose
Employee Number	Main_Number	The number printed on the ID badge. Auto-allocated via the HR_Employee counter; can be overridden.
Previous Number	Previous_Number	Legacy code from your previous HR system, for cross-reference.
Accounting Number	Accounting_Number	The supplier code in the GL; used by Payroll to post salary to the correct vendor.
Insurance Number	Insurance_Number	GOSI / national insurance reference.
Attendance Card	Attendance_Card_Number	Card / badge number — fed by the time-and-attendance device.
Branch	HR_EMP_Branch	Required. Drives all branch-filtered reports.
Department	HR_EMP_Department	Required. Drives the cost-centre on payroll.
Position	HR_EMP_Position	Required. Determines default vacation / package.
Vacancy	HR_EMP_VACANCY	The specific opening this employee occupies.
Status	Status	Active / On Leave / Suspended / Terminated.
Category	Category	Free-form grouping (e.g. <i>Clinical, Admin, Support</i>).

Behaviour

- Changing **Branch + Department + Position** does **not** automatically create a HR_PosHist history row — use the **Transfer** personnel action (see [Transfer](#)) so the change is audited.
- The **Vacancy** field is validated against HR_Vacancy . An employee cannot occupy a vacancy that is inactive or already filled — use the **Clear Vacancy** action (HR_Employee_Clear_Vacancy) to release it.

Contracts (Tab 3)

Every employee has one **active contract** and (optionally) a history of expired or terminated contracts. The contract drives **basic salary, allowances, ticket entitlement, vacation days** and the **end-of-service formula**.

Contract form (`HR_Contract.ft`)

The form has two tabs: **Information** and **Position Vacancy History**.

Information tab

Field	DB column	Notes
Contract Number	<code>Contract_Number</code>	Auto-incremented serial.
Start / End Date	<code>Start_date</code> , <code>End_date</code>	End-of-service is calculated from these.
Married / Single	<code>Type_Married_single</code>	Affects family-ticket entitlement.
Permanent / Part-time	<code>Type_permanent_parttime</code> , <code>Parttime</code>	Part-time contracts skip GOSI deduction.
Tickets for Employee	<code>Tickets_for_employee</code>	Free yearly tickets.
Tickets for Family	<code>Tickets_for_Family</code>	
Basic Salary	<code>Basic</code>	The base for EOS and all <i>based-on-basic</i> allowances.
Housing	<code>Housing</code>	
Transportation	<code>Transportation</code>	
Mobile	<code>Mobile</code>	
Schooling	<code>Schooling</code>	
Year / Model of Car	<code>Year_Model_Car</code>	If the contract includes a company car.
Additional Allowances	<code>Addional_allowances</code>	Free-text amount.
Job Type	<code>Job_Type</code>	Free-text.
Title	<code>Title</code>	Job title printed on the contract document.
Overtime allowed	<code>Overtime_allowed</code>	Yes / No.
Vacation Days	<code>Vacation_days</code>	Annual leave entitlement.

Field	DB column	Notes
Period before vacation	Period_before_vacation	Months of service required before the employee can claim leave.
Package	PACKAGE	Reference to HR_Package . If set, basic/housing/transport/mobile are copied from the package and grey-locked.

Position Vacancy History tab

Displays the grid HR_PosHist.GT — every transfer / promotion shown chronologically: branch, department, position, vacancy, start, end.

Renewal & extension

SP	When fired
HR_Contract_Renew	Creates a brand-new contract record carrying forward the same package.
HR_Contract_Extend	Extends the End_date of the current contract without creating a new one. Sets CT_Extended = 1 .
HR_APRContract	Triggered from an Appraisal — auto-renews the contract using the appraisal's recommended package.
HR_EXTContract	Background SP that processes the <i>Extension</i> personnel action.

Alerts

Two stored procedures populate the dashboard alerts:

- HR_Action_ContractPending_Alert — contracts pending approval.
- The two views HR_Contract_30d / HR_Contract_6m feed the *Expiring contracts* drill-down list in the HR Overview.

Status values (HR_Contract_Status)

A Active · E Expired · T Terminated · R Renewed · X Extended

Salary & Allowances (Tabs 5 + 6)

Salary history (HR_Salary)

Every time the basic salary changes — through a new contract, a personnel action, or an appraisal raise — a row is inserted into `HR_Salary` . The tab shows the full timeline.

Column	Meaning
Effective Date	When the new salary starts.
Basic Salary	Base amount.
Housing / Transportation / Mobile	Standard allowances from the package.
Additional Allowances	Free amount.
SL_Appraisal	FK to the appraisal that triggered the raise (if any).
SL_Action	FK to the personnel action that triggered the change.
SL_Fixed	If checked, the row is locked and Payroll uses exactly these amounts (no further proration).
SL_InActive	Hide from active calculations (kept for audit).

Stored procedures that write into `HR_Salary` :

- `HR_ACTION_Salary_Add` — fired by *Promotion / Demotion*.
- `HR_APRS_Salary_Add` — fired by an appraisal raise.
- `HR_APRS_Salary_FIX` — locks the row after the appraisal cycle closes.

Allowances grids

Tab	Grid file	Table	Purpose
Allowances	<code>HR_A1w.GT</code>	<code>hr_employee_allowance</code>	Personal one-off or recurring add-ons.
Package allowances	<code>HR_PKALW.GT</code>	<code>HR_PKALW</code>	Standard allowance breakdown from the Package .
Periodic	<code>HR_PRDALW.GT</code>	<code>HR_PRDALW</code>	Recurring monthly allowances (Mobile top-up, schooling). Loaded into Payroll automatically.
Incentives	<code>HR_Incentive.GT</code>	<code>HR_Incentive</code>	Performance / spot bonuses. Linked to <code>HR_IncentiveType</code> .

How Payroll consumes these tables

When you click **Generate** on a Pay Run, the procedure `HR_MonthlySalaries` does roughly the following for every employee in the selected branch / department:

1. Read the current `HR_Salary` row whose Effective Date $\leq$ Period End.
2. Add every active `hr_employee_allowance` row (one-shot if start/end matches the period; recurring otherwise).
3. Add every active `HR_PRDALW` row.
4. Add the current month's `HR_Incentive` rows.
5. Subtract deductions (`HR_Deductions` , loan repayments `PR_Loan_Payments`).
6. Write one line per pay code into `PR_RegDet` and update the totals on `PR_Register` .

Leaves & Tickets (Tabs 7 + 8)

Leaves tab

The **Leaves** tab shows the employee's lifetime leave ledger (`hr_employee_vacation`).

Column	Meaning
Vacation Type	Annual, Sick, Educational, Hajj, Compassionate, Unpaid, ... (look-up <code>HR_VacationType</code>).
From / To	The leave window.
Days	Calendar days; weekends/holidays excluded via <code>HR_Holiday</code> .
Status	Pending → Approved → Taken → Reversed.
Travel Auth	FK to <code>HR_VAUTH</code> if the employee is travelling abroad.
Actual Leave	Real return date — may differ from planned.

The summary box on the right shows the formula:

Accrued + Earned – Used = Total Days

— a live read-out of `HR_EMP_VacDue` , `HR_EMP_VacTaken` , `HR_EMP_VacRemain` . It is recomputed by `HR_SP_VAC_CALC` whenever the form opens.

Tickets tab

`hr_employee_ticket` — one row per yearly ticket the employee is owed.

Column	Meaning
Year	Entitlement year.
Type	Employee / Family.
Issued	Yes if a ticket has been issued.
Amount	Cash value (when paid as cash-in-lieu).
Vacation	FK to the <code>hr_employee_vacation</code> row the ticket was used on.

Holidays

`HR_Holiday` stores official paid holidays. The day-count for vacation requests uses these to skip weekends / public holidays. Maintain it once a year under **Data Setup → HR → Holidays**.

Earned leaves (Tab 15)

A read-only view that runs `HR_ACTION_ACCRUED_LEAVE_CALC` to show:

$$(Contract\ Days - Unpaid\ Leaves\ >14\ days - Holidays) / 365 \times Annual\ Leave = Accrued\ Days$$

End of Service (Tab 11)

The **End of Service** tab shows the EOS settlement that will be paid if the employee leaves today. The figures are *computed live* and refreshed every time you open the form.

Fields

Field	DB column
End-of-Service Type	HR_EMP_EOS_Type (HR_EOS look-up)
Last working day	HR_EMP_EOS_LastDay
Basic salary used	HR_EMP_EOS_BasicSalary
Years of service	HR_EMP_EOS_Years
Months per year of service	HR_EMP_EOS_MonthForYear (Saudi labour law: ½ month for the first 5 years, full month afterwards)
EOS amount	HR_EMP_EOS_Amount
Service-Award difference	ServiceAward_Difference (manual top-up)

Procedures

Procedure	When
HR_SP_EOS_CALC	Live recompute on form open.
HR_EOS_DIF_CALC	Compute the difference between contract-period award and accumulated reserve for a single employee.
HR_EOS_DIF_CALC_ALL	Same, batch for every active employee. Run nightly.

Termination flow

The EOS amount is **finalised** when a *Termination* personnel action is applied:

1. Open the employee → **Actions** tab → **New** → Type *Termination*.
2. Fill in the *Termination* sub-tab (resignation, end-of-contract, Article 80, medical, etc.).
3. Fill the **Entitlements** lines (TERM_ENT_AccruedLeaves , TERM_ENT_DaysPay_Emp , TERM_ENT_Tickets , ...).
4. Send for **three-level approval** (Department Head → Project Director → Hospital Director).
5. On final approval HR_Action_Apply runs:
 - marks HR_Employee.Resigned = 1
 - closes the active contract

- locks `HR_Salary` rows
- generates the final pay-slip line in the next Pay Run.

Recruitment

The Recruitment pipeline turns an **open vacancy** into a **hired employee** in three stages:



Optionally backed by a **Recruitment Agency**.

Pages

- **Vacancies** — define what you are hiring for.
- **Candidates** — track applicants from CV to arrival.
- **Agencies** — manage external recruiters and their commissions.

Related lookups

Table	Purpose
HR_CandidateStatus	New / Screened / Interviewed / Offered / Rejected / Hired
HR_Vacancy_Status	Open / On Hold / Filled / Cancelled
HR_RecSource	LinkedIn, Bayt, Walk-in, Agency, Referral, ...
HR_VACClass	Vacancy classification (Critical / Standard / Replacement)
HR_POSCATEG	Position category — used for headcount budget reporting

Vacancies

A **Vacancy** is an approved opening — branch + department + position + requirements — that recruitment will fill.

Vacancy form (`HR_VACANCY.FT`)

Four tabs: **Information**, **History**, **Actions**, **Note**.

Information tab

Field	DB column
Code	<code>HVC_CODE</code> (auto-incremented from <code>HVC_CODE_TMP</code>)
Name (EN / AR)	<code>Name</code> , <code>HVC_Name_A</code>
Branch / Department / Position	<code>Branch</code> , <code>Department</code> , <code>Position</code>
Count	<code>Count</code> — number of identical seats this vacancy represents
Required Gender	<code>HVC_Gender</code>
Required Nationality	<code>HVC_Nationality</code>
Salary	<code>HVC_Salary</code> (target salary)
Recruitment Source	<code>HVC_RecSource</code>
Classification	<code>HVC_CLASS</code> (Critical / Standard / Replacement)
Status	<code>HVC_Status</code> (Open / Filled / On Hold / Cancelled)
ETA	<code>HVC_ETA</code> — expected fill date
Target Vacancy	<code>HVC_TargetVacancy</code> — used when one vacancy is being replaced by another
Transient	<code>HVC_Transient</code> — a temporary vacancy auto-created by a transfer

Transient vacancies

When you transfer an employee, the *Source* position momentarily has an employee leaving and the *Destination* position has an employee arriving. To keep headcount accounting clean, HMS auto-creates a **transient** vacancy on each side. Three SPs manage them:

- `hr_Vacancy_Create_Transient` — create.
- `hr_Vacancy_Transient_Process` — link to the originating action.
- `hr_Vacancy_Transient_Process_All` — nightly sweep.

Vacancy load

`HR_Vacancy_Load` is the SP that powers vacancy pickers everywhere (Employee form, Candidate form, Personnel Action transfer tab). It excludes filled / cancelled vacancies.

Reports

- **HR Vacancies** (`HR_Vacancies.ini` → `HR_Recruitment.rpt`) — open vacancies grouped by branch & department.
- **HR Recruitment** — same, with pipeline counts of candidates per vacancy.

Candidates

A **Candidate** is anyone you are considering for a vacancy. The record carries 95 % of the data an `HR_Employee` carries — so that on **Hire** the data simply copies across.

Candidate form (`HR_Candidate.FT`)

Five tabs: **Personal**, **Employment**, **Contact**, **Notes**, **Note List**.

Personal tab

Field	DB column	Notes
Number	<code>Number</code>	Candidate reference (CV-001...).
Name (EN/AR)	<code>First</code> , <code>Father</code> , <code>Grand_Father</code> , <code>Family</code> , <code>First_A</code> , <code>Father_A</code> , <code>Family_A</code>	
Date / Place of Birth	<code>Date_of_Birth</code> , <code>Place_of_Birth</code>	
Gender / Nationality / Religion	<code>Gender</code> , <code>Nationality</code> , <code>Religion</code>	
Marital	<code>Marital</code>	
Address / Phone / Mobile / Email / PO Box / ZIP	<code>Address</code> , <code>Phone</code> , <code>Mobile</code> , <code>Email</code> , <code>POBOX</code> , <code>ZIP</code>	
Origin Country Address / Phone	<code>Origin_Country_Address</code> , <code>Origin_Country_Phone</code>	
Spouse / Children	<code>Spouse_name</code> , <code>Children_number</code>	
Impaired	<code>Impaired</code>	
Photo	<code>image</code>	

Employment tab

Field	DB column
Vacancy	<code>VACANCY</code>
Position / Department / Branch	<code>Position</code> , <code>Department</code> , <code>Branch</code>
Category	<code>Category</code>
Status	<code>Status</code> (<code>HR_CandidateStatus</code>)
Agency	<code>Agency</code> (<code>HR_Agency</code>)

Field	DB column
ETA / PTA	ETA , PTA (expected / planned travel arrival)
Current sponsor name	Current_sponsor_name
Passport (Number / Place / Expiry / Issue date)	Passport_*
Residence (Number / Place / Expiry)	Residence_*

Hire workflow

1. Move the candidate's **Status** to *Offered* and obtain acceptance.
2. Click **Actions** → **Hire**. The system:
 - Inserts a row into `HR_Employee` (new `Id` , auto `Main_Number`).
 - Copies all personal/contact/passport/residence fields.
 - Sets `HR_Employee.HR_EMP_Candidate` = source candidate `Id` (audit link, also exposed as `EmployeeID` on the candidate row).
 - Closes the **Vacancy** (`HR_Vacancy.HVC_Status` → *Filled*) if the vacancy count drops to 0.
3. Open the new employee record and issue the first **Contract** (see [Contracts](#)).

Recruitment Agencies

External recruiters (manpower agencies) are recorded in `HR_Agency` and edited via `HR_Agency.FT`.

Fields

- Name, country, contact person, phone, e-mail.
- Commission rate (per hire or per month of salary).
- Active flag.

Where the link appears

- On a **Candidate** (Employment tab → *Agency*).
- On an **Employee** (`HR_EMP_Agency`) — useful for tracking which agency originally supplied the staff member.
- On the **Recruitment** report grouped by Agency.

Organisation

The **Organisation** group contains the four reference structures that every employee and contract hangs off:

Page	What it is
Departments	The cost-centres under each branch.
Positions	Job titles with default vacation days.
Packages	Standard salary templates re-used on contracts.
Periodic Allowances	Recurring monthly add-ons fed straight into Payroll.

These pages are normally maintained by an **HR Administrator** — front-line HR users only *consume* them via pickers.

Departments

`HR_Department` is the cost-centre dimension of the hospital.

Form (`HR_Department.FT`)

Field	DB column	Notes
Code	<code>HRD_Code</code>	Short alpha-numeric code (used on pay slips).
Name (EN)	<code>Name</code>	Required.
Name (AR)	<code>HRD_Name_Arabic</code>	
Cost Centre	<code>HRD_CstCtr</code>	FK to the GL cost-centre table; drives the salary GL line.
ID2	<code>ID2</code>	Secondary code for legacy interfaces.

Where it appears

- Mandatory on every **Employee** (`HR_EMP_Department`).
- Mandatory on every **Vacancy** (`HR_Vacancy.Department`).
- Selectable on **Pay Runs** (`PR_Register.PRR_Department`) so payroll can be run department-by-department.
- Reported on every HR roster (by-department staffing, by-department salary cost, etc.).

Tips

- Do not delete a department once an employee has been linked to it — inactivate it instead (add an `Inactive` lookup row in the local status setup).
- The **Cost Centre** value is read by `HR_MonthlySalaries` when the pay run posts to GL — make sure it matches an existing GL CC, or the journal will fail with a *missing CC* warning.

Positions

`HR_POSITION` is the catalogue of job titles available in the hospital.

Form (`HR_POSITION.FT`)

Field	DB column	Notes
Code	<code>HRPOS_CODE</code>	Short code printed on staffing-schedule reports.
Name (EN)	<code>Name</code>	Required.
Name (AR)	<code>HRPOS_Name_Arabic</code>	
Category	<code>HRPOS_Category</code>	FK to <code>HR_POSCATEG</code> (Medical / Nursing / Tech / Admin / Support).
Vacation Days per Year	<code>VacDaysPerYear</code>	The factory annual leave for any contract created on this position.
ID2	<code>ID2</code>	Secondary code.

Where it appears

- On every **Employee** (`HR_EMP_Position`) and **Vacancy** (`HR_Vacancy.Position`).
- On every **Candidate** (`HR_Candidate.Position`).
- On the **Staffing Schedule** report (`HR_StaffingSchedule.rpt`).
- The **Saudisation** report groups by `HRPOS_Category` to compute national / non-national ratios.

Packages

A **Package** is a re-usable salary template. Instead of typing basic

- housing + transport on every contract, you create the package once and pick it on the contract.

Form (`HR_PACKAGE.FT`)

Field	DB column
Name (EN)	<code>Name</code>
Name (AR)	<code>NAME_A</code>
Print Name (AR)	<code>HRP_PrintName_A</code> (short label printed on slips when space is tight)
Notes	<code>Note</code>

Allowance breakdown

Each package has child rows in `HR_PKALW` (one row per allowance type — basic, housing, transportation, mobile, schooling, ...):

Column	Meaning
Type	FK to <code>HR_ALWTYPE</code> .
Amount	Fixed amount, or
Percent	% of basic (Type-Married, Type-Single — both possible).
Currency	Currency of the package.

Maintained from the **Allowances** grid on the package form (`HR_PKALW.GT`).

Refresh propagation

When you change a package's amounts, **existing contracts are NOT updated automatically** — the change applies only to new contracts and to contracts when they are renewed via `HR_Contract_Renew` .

To push a package change to every active contract use the helper SP `HR_PACKAGE_UPDATE` (run from a SQL prompt with the package ID as parameter).

Periodic Allowances

Periodic allowances (`HR_PRDALW`) are recurring monthly amounts that are paid *outside* the salary package — typically *Mobile reimbursement, Schooling top-up, Housing increment, Acting allowance, ...*

Form (`HR_PRDALW.FT`)

Field	DB column
Employee	<code>EmployeeID</code> (picker <code>HR_Employee_Fast.ST</code>)
Allowance Type	<code>Type</code> (FK to <code>HR_PRDALWType</code>)
Amount	money
Frequency	Monthly / Quarterly / Yearly
Start Date / End Date	activity window
Active	yes/no
Banner	<code>HR_PRDALW_BANNER</code> SP populates the header

How payroll consumes them

`HR_MonthlySalaries` includes every `HR_PRDALW` row whose period overlaps the pay-run period and whose Active flag = 1. The amount lands on `PR_RegDet` under the matching pay code.

Tip

Use `HR_PKALW_ORG_Add` (admin helper) to bulk-add the same allowance to every employee in a department — e.g. when the board approves a *Critical-care allowance* for all ICU nurses.

Personnel Actions

A **Personnel Action** (`HR_Action.FT`) is the auditable record of any change to an employee's job that is not a routine data edit. Every action goes through a **three-level approval workflow** before it is applied.

Action types

Type	Tab	What it changes
Termination	Tab 2	Closes the contract, computes EOS, blocks future pay.
Promotion / Demotion	Tab 3	Title + salary change. Writes a new <code>HR_Salary</code> row.
Transfer	Tab 4	Branch / department / position change. Writes a <code>HR_PosHist</code> row and updates vacancies.
Salary Change	shares Promotion tab	Salary only, no title change.
Contract Renewal	(auto from Appraisal)	Inserts a new contract.
Extension	shares Promotion tab	Extends current contract <code>End_date</code> .

Approval workflow

Created → Department Head approval → Project Director approval → Hospital Director approval → Applied

- Each approval level stamps its **User + Date** on `HR_Action` (`APRV_DepHead` , `APRV_ProjDir` , `APRV_HospDir`).
- Approval levels can be **skipped** by an admin override (see *Policy Verification* tab).
- `HR_Action_Apply` is the SP that performs the final mutation once *all* required approvals are in.

Banner & alerts

- `HR_Action_BANNER` — top strip on the form showing employee name, current position, action serial, status.
- `HR_Action_Alert` — dashboard alert for actions pending **your** approval (filtered by `HR_ActionApproval`).

Form tabs

1. **Information** — type, date, employee, basic action data.
2. **Termination** — reason flags, last working day, entitlements.
3. **Promotion / Demotion** — new title, new vacancy, new basic.
4. **Transfer** — source vs destination branch / department / vacancy.
5. **Dept-Head Approval** — note, signature, date.
6. **Project-Dir Approval** — note, signature, date.
7. **Hospital-Dir Approval** — note, signature, date.
8. **Policy Verification** — admin override.

→ Details on the most-used actions:

- [Termination](#)
- [Promotion / Demotion](#)
- [Transfer](#)
- [Appraisals](#)

Termination

A **Termination** action ends the employment relationship and triggers the final EOS settlement.

Termination reasons (Tab 2 flags)

Flag	Meaning
TERM_Resignation	Employee resigned voluntarily.
TERM_ReContractNotOffered	Hospital decided not to renew.
TERM_ReContractNotWished	Employee declined to renew.
TERM_MedicalReason	Medical incapacity.
TERM_Article80	Saudi Labour Law Art. 80 — termination for cause.
TERM_DuringProbation	Within the probation period — reduced entitlements.
TERM_SCCFailed	Failure to obtain / renew the Saudi Council certificate.
TERM_Others	Free-text reason.
HAC_TermReason	FK to HR_TermReason look-up (free taxonomy you maintain).

Entitlements block

Filled by the HR officer before the action is submitted:

Field	Meaning
TERM_ENT_AccruedLeaves	Unused leave days to pay out.
TERM_ENT_TotalLeaves	Total leave balance (informational).
TERM_ENT_ServiceAward_TotalPeriod / _CompletedTerms	Which formula to use for end-of-service award.
TERM_ENT_Tickets	Pending tickets to cash out.
TERM_ENT_DaysPay_Emp	Days of salary owed to employee.
TERM_ENT_DaysPay_Hosp	Days the <i>employee</i> owes the hospital (notice not served).
HAC_TicketToDeduct	Cost of un-served-notice ticket.
HAC_VisaToDeduct	Visa cost to deduct if employee resigns before threshold.
HAC_LastWorkingDay	The last day the employee physically works.

Field	Meaning
HAC_TermLetterDate	When the termination letter was issued.

On apply

When the *Hospital Director* approval is stamped, HR_Action_Apply :

1. Sets HR_Employee.Resigned = 1 , Date_of_resignation = HAC_LastWorkingDay .
2. Closes the active contract (HR_contract.Status = 'T' , CT_Effective_End_Date = HAC_LastWorkingDay).
3. Inserts a PR_RegDet settlement line in the next pay run (one line per entitlement: accrued leave, tickets, EOS, notice).
4. Releases the **Vacancy** (HR_Vacancy.HVC_Status → *Open*) unless HVC_Transient = 1 .
5. Locks all HR_Salary rows for this employee.

Reports

- **HR Termination** (HR_Termination.ini).
- **HR Turnover** (HR_Turnover.ini).

Promotion / Demotion

A **Promotion / Demotion** action changes the employee's title and/or basic salary.

Fields (Tab 3)

Field	Meaning
DPRON_NewTitle	New job title (free-text or from HR_POSITION).
DPRON_NewVacancy	New vacancy the employee will occupy.
DPRON_Department	Optional department change.
Cur_Basic	Current basic salary (read-only, copied from contract).
New_Basic	New basic salary the HR officer is proposing.
Recom_IncDec	Calculated absolute increase / decrease.
Recom_IncDecPerc	Calculated %.

On apply

HR_Action_PROMOD_Apply runs:

1. Inserts a new row in HR_Salary with SL_Action = <this action ID> and Effective_date = HAC_Effective_Date .
2. Updates HR_Employee.HR_EMP_Position and the contract title.
3. If a new vacancy was supplied, occupies it and frees the previous one (transient vacancies are created if branch / dept changes — see [Vacancies](#)).
4. Stamps HAC_Action_Applied = 1 .

Reversal

If a promotion is later reversed, create a **new** action with HAC_ReverseAction = <ID of original> and select *Demotion*. The SP HR_Action_PROMOD_Apply detects the reversal flag, restores the previous salary row and inactivates the original raise.

Transfer

A **Transfer** moves an employee from one *Branch* + *Department* + *Vacancy* to another, without changing salary.

Fields (Tab 4)

Field	Source / Destination
HRTR_S_Branch	Source branch
HRTR_S_Department	Source department
HRTR_S_Vacancy	Source vacancy
HRTR_S_Main_Number	Source employee badge number (audit)
HRTR_D_Branch	Destination branch
HRTR_D_Department	Destination department
HRTR_D_Vacancy	Destination vacancy
HRTR_D_Main_Number	Destination badge number

On apply

HR_Action_TRANS_Apply :

1. Updates HR_Employee.HR_EMP_Branch / _Department / _VACANCY .
2. Inserts a row in HR_PosHist recording the move.
3. Creates a **transient** source vacancy via hr_Vacancy_Create_Transient if the source vacancy was the only one of its kind — guarantees headcount accounting balances.
4. Marks destination vacancy as filled.
5. Stamps HAC_Action_Applied = 1 .

Bulk historical import

Use HR_Action_HIST_Apply_All to reapply every historical transfer when you migrate from a legacy HR system (one-shot batch tool).

Appraisals

Appraisals (`HR_Appraisal.FT`) are the formal performance review issued at the end of each contract term. The outcome drives **Re-contracting** and the **annual raise**.

Form tabs

1. **Appraisal** — scoring.
2. **Re-Contracting** — the decision to renew / extend / not renew.

Scoring fields

Field	Lookup	Notes
Job Knowledge	<code>HR_APRFactor</code>	A / B / C / D / E rating.
Work Quality	<code>HR_APRFactor</code>	
Work Quantity	<code>HR_APRFactor</code>	
Overall Appraisal	<code>HR_APROverall</code>	Computed from the three factors (configurable in <code>HR_APRFactor.Weight</code>).
Appraisal Status	<code>HR_APRStatus</code>	Draft / Submitted / Approved / Cancelled.
Raise (amount)	<code>Raise</code>	Approved raise to be added to the next <code>HR_Salary</code> row.
Recontracting Status	<code>HR_RecontractingStatus</code>	Renew / Extend / Do not renew.
Employee Approval	<code>HR_EmpApproval</code>	Whether the employee has counter-signed.

On submit

`HR_Appraisal_Apply` runs:

1. If **Renew** → fires `HR_APRContract` to insert a new contract.
2. If **Extend** → fires `HR_Contract_Extend` to push out the end date.
3. If a **Raise** is approved → fires `HR_APRS_Salary_Add` to insert a new `HR_Salary` row with `SL_Appraisal = <appraisal ID>` .
4. Sets `APRS_Applied = 1` .

`HR_APRS_Salary_FIX` is a nightly tidy-up SP that locks the raise rows once their effective date is reached.

Banner

HR_Appraisal_BANNER shows: employee, current contract end, scoring summary, recommended raise.

Leaves & Travel

HMS handles three closely-related leave objects:

Page	Form	What it is
Vacation Requests	HR_Vacation.FT	The day-by-day annual / sick / educational leave request.
Travel Authorisation	HR_VAUTH.FT	Authorisation for an employee to travel abroad while on leave (used for ticket entitlement & re-entry visa).
Vacation Extensions	HR_Extension.FT	Extend an in-progress leave.

Leave types (`HR_VacationType`)

- **Annual** — counted against `HR_EMP_VacRemain`.
- **Sick** — counted separately; 30 full-pay + 60 half-pay days/year per Saudi labour law.
- **Educational** — exam / study leave.
- **Hajj** — once-in-employment.
- **Compassionate** — bereavement.
- **Unpaid** — does not accrue salary; days > 14 reduce service period.
- **Maternity / Paternity**.

Vacation Requests

Form (`HR_Vacation.FT`)

Six tabs: **Request** → **Educational Leave** → **Supervisor Approval** → **Director Approval** → **Actual Leave** → **Dependants Eligibility**.

Request tab

Field	Notes
Employee	Picker (<code>HR_Employee_Fast.ST</code>)
Vacation Type	<code>HR_VacationType</code> look-up
From / To	Planned dates — must not overlap an existing approved leave.
Days	Auto-calculated, holidays from <code>HR_Holiday</code> excluded.
Reason	Free text.
Travel Authorisation	Optional FK to <code>HR_VAUTH</code> if travelling abroad.
Replacement	Employee covering during the absence (optional).

Approval tabs

Two-level approval: **Supervisor** → **Director**. Each tab stamps user + date. Status flows `Pending` → `SupervisorApproved` → `Approved` → `Taken` → `Reversed` (lookup `HR_VacReqStatus`).

Actual Leave tab

When the employee returns, HR fills:

- Actual From / To dates.
- Days actually taken.
- Notes (e.g. early return, extension granted).

`HR_VacReq_CALC` recomputes the employee's accrued / used / remaining totals (`HR_EMP_VacDue` / `VacTaken` / `VacRemain`).

Validation procedures

SP	What it checks
<code>HR_DueVacations</code>	Drives the <i>Due Vacations</i> report and alert.

SP	What it checks
HR_Vacation_Alert	Dashboard alert: leaves starting in 7 days.
HR_Vacation_Alert_Residence	Cross-checks the employee's residence permit covers the leave + 14 days.
HR_Vacation_TravelALW_Validate	Validates travel allowance entitlement on the leave row.
HR_Vacation_RPT	Computes the figures on the <i>Vacation Statistics</i> family of reports (VacStat 1-8).

Reports

- **Due Vacations** — hr_DueVacations.rpt
- **Vacation Stats** — 8 ready-to-print pivots (HR_VacSTAT.rpt ... HR_VacSTAT4.rpt and hr_vacstat7/8.ini).

Travel Authorisation

`HR_VAUTH.FT` records the authorisation for an employee to travel abroad — needed for **re-entry visa**, **ticket entitlement** and **residence-permit validity** checks.

Key fields

- Employee, From / To dates.
- Destination country / city.
- Re-entry validity date (must be > To).
- Ticket entitlement: cash-in-lieu or in-kind (employee / family).
- Status (`HR_VAUTHStatus`): Pending / Approved / Cancelled / Used.

Linked actions

- `HR_VacAction` records the *VacAction* event when the auth is used.
- `HR_VacAction_Apply` consumes the ticket entitlement from `hr_employee_ticket`.
- `HR_VacAction_Submit` / `HR_VacAction_AutoApply` drive the approval workflow.

Reports

- **Employee Tickets** (`hr_EmployeeTickets.rpt`) — outstanding ticket ledger.
- **Expiring Documents** (`hr_ExpiringDocs.rpt`) includes residence expiry vs travel-auth dates.

Vacation Extensions

`HR_Extension.FT` is used when an employee on leave requests to **extend** the leave beyond the originally approved To-date.

Workflow

1. Open the *active* vacation row from the employee's Leaves tab.
2. Click **Actions** → **New Extension**.
3. Fill the new To-date, reason, and any additional unpaid days.
4. Supervisor / Director approval, then `HR_EXTContract` applies the change — `hr_employee_vacation` row is updated and accrual is recomputed via `HR_VacReq_REQUEST_CALC`.

Validation

- The extension cannot push the leave end-date past the **contract end-date** (unless the contract is also extended via `HR_Contract_Extend`).
- The extension is rejected if the employee's residence expires before the new end-date.

Visas

HR_VISA.FT records work-visa applications and renewals for expat staff.

Fields

Field	Notes
Employee	Picker.
Visa Type	HR_VisaType (Work / Family / Visit / Re-entry).
Status	HR_VISAStatus (Requested / Approved / Issued / Cancelled / Used).
Validity Start	Visa issue date.
Validity End	Expiry.
Note	Free text.

HR_VISA_BANNER shows the visa lifecycle at the top of the form.

Reports

- **Expiring Documents** (hr_ExpiringDocs.rpt) — includes visas expiring in the next 30/60/90 days.

Certificates

`HR_Certificate.FT` records professional certificates the employee holds — and most importantly the **Saudi Council Certificate** (SCC) which is mandatory for licensed clinical staff.

SCC fields (on the Employee form, Qualifications tab)

Field	DB column
Certificate Number	<code>HR_EMP_SaudiCouncilCert_NO</code>
Issue Date	<code>HR_EMP_SaudiCouncilCert_DATE</code>
Exam Date	<code>HR_EMP_SaudiCouncilCert_ExamDATE</code>
Valid (flag)	<code>HR_EMP_SaudiCouncilCert_Valid</code>
Expiry Date	<code>HR_EMP_SaudiCouncilCert_EXPDATE</code>
Profession	<code>HR_EMP_SaudiCouncilCert_Profession</code>
Status	<code>HR_EMP_SaudiCouncilCert_Status</code>
Not Applicable	<code>HR_EMP_SaudiCouncilCert_NA</code> (set for non-clinical staff)
Notes	<code>HR_EMP_SaudiCouncilCert_Note</code>

`HR_CCI_UPDATE` is the SP that refreshes SCC validity for all employees nightly. `hr_Certificate_ADD` is the helper that inserts a certificate row from the certificate form into the employee's qualifications.

Reports

- **Employee Certificates** (`HR_Emp_Certificate.rpt`) — three layouts (F1, F2, F3) for different licensing authorities.
- **SaudiCC** (`HR_SaudiCC.ini`) — staff list with current SCC status.

Sick Leave

Sick leave is recorded on two slightly different forms:

Form	Use case
MF_SickLeave.FT	Quick single-day sick leave entered by the employee's manager.
MF_SickLeave2.FT	Full medical sick-leave certificate issued by the hospital clinic — includes diagnosis, treating physician, ICD code, attachments. The MF_SickLeave2_SO and wMF_SickLeave2_CDC variants are used in clinics with a different print layout.

Fields

- Employee, From, To, Days.
- Diagnosis / ICD-10 (on the full version).
- Issuing physician (picker into the physician table).
- Attachments (lab results, prescriptions).
- Approved by HR (yes/no), notes.

Effect on payroll

- **Up to 30 days** in a service year → full-pay sick leave; no payroll deduction.
- **Days 31–90** → 75 % pay; the *Sick-deduction* pay code is added to the next pay run by HR_MonthlySalaries .
- **Days 91+** → unpaid; reduces the period used for end-of-service computation.


Payroll

The **Payroll (PR)** module turns HR data into monthly salaries.

Pages

- [Pay Codes](#) — the chart of earnings & deductions.
- [Pay Runs](#) — the monthly batch.
- [Registers & Pay Slips](#) — the resulting transactions and the printable pay slip.
- [Loans](#) — staff loans repaid through payroll.

Pipeline at a glance



Key tables

Table	Use
PR_PayCode	Earning / deduction codes (BAS, HOU, GOSI, LOAN, ...).
PR_PayRun	Header — period, generated by, message.
PR_Register	One per pay run × department (when run by department).
PR_RegDet	Line items — one per employee × pay code.
PR_Loan	Staff loans; repayment lines are inserted into PR_RegDet .
PR_PCPeriod / PR_PCType	Pay-code period & type look-ups.

Pay Codes

A **Pay Code** is one line on the pay slip. Maintain them under **Payroll** → **Pay Codes** (`PR_PayCode.FT`).

Fields

Field	DB column	Meaning
Code	<code>Code</code>	Short alpha code (BAS, HOU, TRA, MOB, OT, GOSI, LOAN, ...).
Internal Code	<code>iCode</code>	Used for system codes — never shown on slips.
Name	<code>Name</code>	Printed on the pay slip.
Type	<code>Type</code> (<code>PR_PCType</code>)	Earning / Deduction / Reimbursement / Informational.
Period	<code>Period</code> (<code>PR_PCPeriod</code>)	Monthly / Quarterly / Annual / One-shot.
Based On	<code>BasedOn</code>	Fixed / % of Basic / Formula.
Factor	<code>Factor</code>	% or multiplier when <i>Based On</i> needs it.
Account	<code>Account</code>	GL account this code posts to.
Class	<code>Class</code>	A / B / C grouping for summary reports.
TransRequired	<code>TransRequired</code>	If true, the code only appears when a corresponding HR transaction exists (e.g. <i>Overtime</i> only if <code>hr_employee_overtime</code> rows exist for the period).
Benefit Code	<code>PRP_BenefitCode</code>	Treated as a non-cash benefit for tax computations.

Tips

- Do **not delete** a code that has any `PR_RegDet` lines — older pay slips will lose their description. Inactivate by setting the *Status* flag instead.
- The order codes appear on the slip is driven by `PR_PayCode.Class + ID` — choose codes carefully to keep slips readable.

Pay Runs

A **Pay Run** is one monthly batch. Open **Payroll** → **Pay Run** (`PR_PayRun.FT`).

Fields

Field	DB column
Period Start	<code>PeriodStart</code> (first day of the month)
Period	<code>Period</code> (e.g. 2026-06)
GL Batch	<code>Vglbatch</code> (filled when posted to GL)
Created By	<code>CreatedBy</code>
Created On	<code>CreatedON</code>
Message	<code>MSG</code> (free-text log)

Workflow

1. Open Pay Run, click **New**.
2. Set Period Start, choose Branch and (optionally) Department, EOS status, vacation status, contract-start window, package filters. These map to `PR_Register.PRR_*` columns.
3. Click **Generate** — `HR_MonthlySalaries` runs:
 - Selects every active employee matching the filters.
 - Inserts one `PR_Register` per Branch (or per Department, depending on settings).
 - Inserts one `PR_RegDet` per employee × pay code.
 - Updates Totals on `PR_Register` (`Total` , `TotalPay` , `TotalDeduction`).
4. Review the **Registers** tab — drill into any line to see the computation.
5. Click **Post to GL** — `Vglbatch` is filled and the batch becomes read-only.
6. Print pay slips (`PR_PaySlip.rpt`) — one PDF per employee or batched.

Re-running

If you need to regenerate, **delete the un-posted register** first (or use the *Reverse* command on a posted register, which inserts a contra batch in GL). A new generation always creates a fresh `PR_Register` — never overwrites.

Registers & Pay Slips

PR_Register

The register is the **header** of a pay batch.

Column	Meaning
Description	Free-text title (e.g. <i>June 2026 – Riyadh</i>).
Period , PeriodStart	Pay period.
Date	Generation date.
Total , TotalPay , TotalDeduction	Sums.
Vglbatch	GL batch ID once posted.
GenSource	M = monthly, S = settlement, A = adjustment, T = termination.
PRR_Branch , PRR_Department	Filters used during generation.
PRR_Exlbranch , PRR_EXLPackage	Exclusion filters.
PRR_EOS_STATUS , PRR_VAC_STATUS	Include / exclude employees on EOS / on vacation.
MSG	Generation log.

PR_RegDet

One row per employee × pay code. Columns include Employee , PayCode , Amount , Note (e.g. *Proration: 18/30 days*).

Pay slip report

PR_PaySlip.rpt (with template PR_PaySlip.ini) — the printable slip. Layout sections:

- Header — employee name, number, department, period.
- Earnings block — every Type = Earning pay code.
- Deductions block — every Type = Deduction pay code.
- Net pay — TotalPay - TotalDeduction .
- Footer — payment method (bank), bank IBAN, sign-off lines.

The slip uses the employee's HR_EMP_NAME_A (Arabic) when the *Print in Arabic* parameter is set.

Register transactions report

PR_Register_Trans.rpt — flat list of every PR_RegDet row for the register, sortable by department / pay code. Useful for audit and GL reconciliation.

Loans

Staff loans are managed in `PR_Loan` and repaid automatically through payroll.

Fields

Field	Meaning
Employee	FK to <code>HR_Employee</code> .
Loan Type	<code>PR_LoanType</code> (Personal / Emergency / Housing / Car / Education).
Status	<code>PR_LoanStatus</code> (Requested / Approved / Active / Paid / Cancelled).
Amount	Principal.
Instalments	Number of monthly repayments.
Start Period	First payroll period to deduct.
Repayment / month	Computed, can be overridden.
Outstanding	Recomputed after each payroll run.

Workflow

1. HR creates a loan row, status *Requested*.
2. Finance / Director approves → status *Active*.
3. Each Pay Run reads active loans (`PR_Loan_Load`), computes the instalment, inserts a *LOAN* `PR_RegDet` line, and inserts a row into `PR_PKT_Loan` history.
4. When *Outstanding* = 0 the loan is auto-marked *Paid*.
5. The dashboard `PR_Loan_Alert` flags loans whose deduction failed because the employee's net pay would go below zero.

Banner

`PR_Loan_BANNER` shows: employee, principal, outstanding, % paid, months remaining.

HR Reports

All reports are stored under <HMS>/Report template/ as .ini parameter files and .rpt Crystal layouts. They are launched from the **Reports** ribbon button on each HR form.

Staff lists

Report	File	Purpose
All Employees	HR_Employees.rpt	Full active roster.
Employees (alt layout)	HR_Employees2.rpt	Compact one-line-per-employee.
Employees by Nationality	hr_EmployeeByNationality.rpt	Headcount grouped by passport country.
Employees by Religion	hr_employeebyreligion.rpt	
Employees by Sponsor	hr_EmployeeBySponsor.rpt	For multi-sponsor groups.
Employees by Agency	HR_Employees_Agency.rpt	Group by recruitment agency.
Insured staff	HR_Insurance.rpt , hr_Insured.rpt	GOSI / private insurance roster.
Saudisation	hr_saoudization.rpt	Saudi vs non-Saudi ratios per position category.
Staffing Schedule	HR_StaffingSchedule.rpt	Required vs filled per dept.
New Employees	HR_NewEmployees.rpt	Joiners in a date range.
End-of-Service	hr_endservice.rpt	EOS register, with computed amounts.
Termination	HR_Termination.ini	Leavers in a period.
Turnover	HR_Turnover.ini	Hires vs leavers ratio.

Vacations

Report	File
Due Vacations	hr_DueVacations.rpt
Vacation Statistics 1-8	HR_VacSTAT.rpt , HR_VacSTAT2-4.rpt , hr_vacstat7.ini , hr_vacstat8.ini

Salary

Report	File
Current Salaries	hr_CurrentSalaries.ini
Salary Change Log	HR_SalaryChange.rpt

Report	File
Salaries (long)	HR_Salaries.rpt , HR_SalaryEXT.rpt
Pay Slip	PR_PaySlip.rpt
Register Transactions	PR_Register_Trans.rpt

Tickets & Documents

Report	File
Employee Tickets	hr_EmployeeTickets.rpt
Expiring Documents	hr_ExpiringDocs.rpt
Sponsoring Employee	RP_SponsoringEmployee.rpt
Saudi Council Certificate	HR_SaudiCC.ini
Certificate (3 formats)	HR_Emp_Certificate.rpt , _F2.rpt , _F3.rpt

Recruitment & Appraisals

Report	File
Vacancies	HR_Vacancies.ini
Recruitment Pipeline	HR_Recruitment.rpt
Appraisals	HR_Appraisals.ini
Recontracting	HR_Recontracting.ini

Administration

The Administration sub-section is for the **HR Administrator** — the person who configures look-ups, security, alerts and dashboards.

- [Lookup Tables](#) — the 30+ reference tables that drive HR pickers.
- [Security & Approvals](#) — who can do what.
- [Alerts & Banners](#) — dashboard alert configuration.

The HR Overview dashboard (`HR_Overview.ST`)

The **HR** → **Overview** search pad is the manager's home page:

- Driving SP: `SPD_SP_HR_Overview`.
- Default filter: **All branches** — switchable to Abha, Dammam, Riyadh, Qassem, Jeddah.
- QuickFilter field: *Position* — type in the position name to narrow the list.
- Default toolbar buttons: **Edit** the selected employee, **New** employee.
- Alert highlighting: any row whose status contains *Expired* is shown red/bold (residence, passport, contract, SCC).

Lookup Tables

All HR look-ups are maintained under **Data Setup** → **HR**. They are ordinary tables that the picker dropdowns read from at form-open time (no service restart needed).

Master look-ups

Table	Used by
HR_Branch	Employee, Vacancy, Pay Run filter
HR_Department	Employee, Vacancy, Pay Run filter
HR_POSITION	Employee, Vacancy, Candidate
HR_POSCATEG	Position category (Saudisation report)
HR_Package	Contract
HR_ALWTYPE	Package allowance type
HR_PRDALWType	Periodic allowance type
HR_IncentiveType	Incentive type
HR_VacationType	Vacation request
HR_VACClass	Vacancy classification
HR_RecSource	Recruitment source
HR_RepFormat	Report format selector
HR_ValueType	Value-type look-up for action fields
HR_Holiday	Public holidays (vacation day-count)
HR_Category	Free employee grouping (Clinical / Admin / Support)
HR_EntryPort	Port of entry (immigration)
HR_Destination	Country of travel (TravelAuth)
HR_VisaType	Visa types
HR_TermReason	Termination reason taxonomy
HR_RecontractingStatus	Re-contract decision
HR_EOS	EOS type
HR_LU_Vacations	Vacation reason library
HR_LU_Deductions	Deduction library
HR_Agency	Recruitment agencies

Status look-ups (small code tables)

Table	Code values
HR_Status	Employee status (A/L/S/T)
HR_Contract_Status	A / E / T / R / X
HR_Vacancy_Status	O / F / H / C
HR_CandidateStatus	N / S / I / O / R / H
HR_APRStatus	Draft / Submitted / Approved / Cancelled
HR_APROverall	A / B / C / D / E ratings
HR_APRFactor	Per-factor rating with weight
HR_VAUTHStatus , HR_VISASStatus	Document workflow
HR_VACActionStatus , HR_VACActionStage , HR_VACActionType	Vacation action workflow
HR_VacReqStatus	Vacation request flow
PYR_Stage , PYR_Status	Payroll cycle status

Tip

Most look-ups have a `Name_A` Arabic column — fill it in if you print slips or contracts in Arabic, otherwise the English value is used as a fall-back.

Security & Approvals

HR security is enforced at two layers.

1. HMS user roles

The standard HMS user / group / role system gates access to **forms** and **menu entries** — typically the four HR roles shipped by default:

Role	Sees	Can edit
HR Administrator	Everything	Everything
HR Officer	Everything except <i>Salary</i> tab on employees outside own branch	Employees, candidates, vacancies, leaves
Department Manager	Only own department's employees	Approves first-level actions
Employee Self-Service	Own profile, own leave history	Submit leave & travel requests

Form-level access is bound at install time by mapping each `.FT` and `.ST` to a *security code* in the HMS admin tools.

2. Personnel-Action approval workflow

Even with full edit rights, a personnel action is **not applied** until the three approval levels stamp it:

```
HR Officer creates →
  Department Head approves      (APRV_DepHead + Date)
  Project Director approves     (APRV_ProjDir + Date)
  Hospital Director approves    (APRV_HospDir + Date)
    ↓
  HR_Action_Apply runs the actual mutation
```

- Approvers are configured per-branch in `HR_ActionApproval` / `HR_EmpApproval`.
- The dashboard alert `HR_Action_Alert` lists every action pending *your* approval — clicking it opens the action ready to sign.
- Approvals are append-only — they cannot be removed once stamped, only superseded by an *Override* on the *Policy Verification* tab (admin only, audited).

Alerts & Banners

Every HR form has a **Banner** (the static green strip at the top) and one or more **Alerts** (scrolling marquee strips below).

Banner procedures

Form	Banner SP
Employee	HR_EMPLOYEE_BANNER
Contract	HR_Contract_BANNER
Personnel Action	HR_Action_BANNER
Appraisal	HR_Appraisal_BANNER
Candidate	HR_Candidate_BANNER
Vacation	HR_VACATION_BANNER
VacAction	HR_VacAction_BANNER
Visa	HR_VISA_BANNER
Travel Auth	HR_VAUTH_BANNER
Periodic Allowance	HR_PRDALW_BANNER
Agency	HR_Agency_BANNER

A banner SP returns a small result-set the HMS framework renders as a read-only header (employee photo + name + key facts).

Alert procedures

Alerts pop on the dashboard *and* on the employee form when something needs attention.

SP	Triggers when
HR_EMP_Alert	Any document on this employee expires within 30 days.
HR_EMP_Note_Alert	Free-text employee note flagged as alert.
HR_EMP_Note_Alert_APRS	Appraisal-related employee note.
HR_Vacation_Alert	A leave is starting within 7 days.
HR_Vacation_Alert_Residence	Leave cross-checks residence validity.
HR_Action_Alert	A personnel action is pending your approval.
HR_Action_ContractPending_Alert	A contract renewal action is pending.

SP	Triggers when
PR_Loan_Alert	A loan instalment failed because net pay would go negative.
HR_ExpiringDocs	Drives the <i>Expiring Documents</i> drill-down list.

How alerts are configured

Each form's .FT file has one or more [Alert] , [Alert2] , ... sections specifying:

- Show — on/off.
- Procedure — which SP to call.
- Count — how many rows to scroll.
- Every — seconds between scroll steps.
- Duration — seconds each row is visible.
- Width — px width of the strip.

Data Model

Reference list of every HR / Payroll table shipped with HMS. All IDs are `int`. Every editable table has a matching `HR_PKT_*` **ghost table** (PKT = Pending Keyed Transaction) which holds the user's unsaved buffer; on **Save** the framework copies the PKT row into the live table.

Core master tables

Table	Purpose
HR_Employee	Master employee record.
HR_PKT_Employee	Edit buffer.
HR_Employee_child	Dependants (spouse + children).
HR_EMPLOYEE_Experience	Prior employment history.
hr_employee_qualification	Diplomas and certificates.
hr_employee_vacation	Vacation ledger.
hr_employee_ticket	Ticket entitlement & usage.
hr_employee_overtime	Overtime hours by date.
hr_employee_allowance	Personal allowances.
HR_Salary	Salary timeline (one row per change).
HR_PKALW	Package allowance breakdown.
HR_PRDALW	Periodic monthly allowances.
HR_Incentive	Performance / spot bonuses.

Organisation

Table	Purpose
HR_Branch	Branches / sites.
HR_Department	Departments (cost-centres).
HR_POSITION	Job titles.
HR_POSCATEG	Position category.
HR_Category	Generic employee grouping.
HR_Package	Salary package template.
HR_PosHist	Position history (audit).

Recruitment

Table	Purpose
HR_Vacancy	Open positions.
HR_Candidate	Applicants.
HR_Agency	Recruitment agencies.

Contracts & actions

Table	Purpose
HR_contract	Contracts.
HR_Action	Personnel actions.
HR_ActionType	Action-type look-up.
HR_ActionApproval	Per-branch approver matrix.
HR_Appraisal	Performance appraisals.
HR_EmpApproval	Employee-side approver matrix.
HR_EOS	End-of-service type lookup.
HR_TermReason	Termination reason taxonomy.
HR_VACAction , HR_VACActionStage/Status/Type	Vacation action workflow.

Documents

Table	Purpose
HR_VISA , HR_VisaType , HR_VISASstatus	Visa applications.
HR_VAUTH , HR_VAUTHStatus	Travel authorisations.
HR_Certificate	Generic certificate catalogue.
HR_ELeave	Educational-leave linked to vacation.
HR_LU_Vacations , HR_LU_Deductions	Reason libraries.

Payroll (PR)

Table	Purpose
PR_PayCode	Pay codes (earnings & deductions).

Table	Purpose
PR_PayRun	Pay-run header.
PR_Register	One per pay-run × branch.
PR_RegDet	Pay-slip line items.
PR_Loan	Staff loans.
PR_LoanType , PR_LoanStatus	Loan lookups.
PR_PCPeriod , PR_PCTYPE	Pay-code lookups.
PR_PKT_*	Edit-buffer ghosts.
PYR_Stage , PYR_Status	Payroll cycle status.

Lookups (status & rating)

HR_Status , HR_Contract_Status , HR_Vacancy_Status , HR_CandidateStatus , HR_APRStatus , HR_APROverall , HR_APRFactor , HR_RecontractingStatus , HR_VacReqStatus , HR_ALWTYPE , HR_PRDALWType , HR_IncentiveType , HR_VacationType , HR_RecSource , HR_RepFormat , HR_ValueType , HR_Holiday , HR_Branch , HR_Destination , HR_EntryPort , HR_Deductions , HR_VACClass .

Templates (FT / ST / GT)

The HMS UI is metadata-driven. Each window is one of three template files under `<HMS>/Forms` (legacy) or `<HMS>/FTP`, `<HMS>/STP`, `<HMS>/GTP` (current).

Suffix	Kind	Example
.FT	Form — single record edit window	HR_Employee.FT
.ST	Search pad / list window	HR_Employee_Fast.ST
.GT	Grid — child table embedded in a form	HR_Salary.GT
.BND	Binder — full-screen workspace	(no dedicated HR binder; opened via main menu)

HR forms (FTP/)

File	Purpose
HR_Employee.FT	Employee master form (16 tabs).
HR_Contract.ft	Contract edit.
HR_Action.FT	Personnel action.
HR_Appraisal.FT	Appraisal.
HR_Candidate.FT	Candidate.
HR_Vacation.FT	Vacation request.
HR_VacAction.FT	Vacation action / consumption.
HR_VACANCY.FT	Vacancy.
HR_Department.FT	Department.
HR_POSITION.FT	Position.
HR_PACKAGE.FT	Salary package.
HR_PRDALW.FT	Periodic allowance.
HR_VAUTH.FT	Travel authorisation.
HR_VISA.FT	Visa.
HR_Extension.FT	Leave extension.
HR_Agency.FT	Recruitment agency.
HR_Certificate.FT	Certificate.
MF_SickLeave.FT , MF_SickLeave2.FT	Sick-leave certificates.
PR_PayRun.FT	Payroll run.

File	Purpose
PR_PayCode.FT	Pay code.

HR list windows (STP/)

File	Purpose
HR_Overview.ST	Manager dashboard (branch-filtered, QuickFilter on Position).
HR_Employee.ST	Standard employee search.
HR_Employee_Fast.ST	Fast picker (used everywhere a <i>select employee</i> dropdown is shown).
HR_Employee_LB.ST	Lebanon-specific layout.
HR_DataEntry.ST	Mass-edit grid.
HR_Department.ST , HR_Position.ST , HR_Package.ST , HR_Candidate.ST	List per master table.
HR_Contract.ST , HR_Contract_30d.ST , HR_Contract_6m.ST	Contract list + expiry-window drill-downs.
HR_ContractReview.ST	Contracts to review.
HR_Action.ST , HR_Action_DRL.ST , HR_Action_STS.ST	Actions list & drill-downs.
HR_Salary_DRL.ST	Salary drill-down (from Employee).
HR_Appraisal.ST	Appraisals list.
HR_Agency.ST , HR_Certificate.ST	Lookups.
HR_Extension.ST , HR_Incentive.ST , HR_Passport.ST , HR_Residence.ST	Per-document lists.
HR_SalaryReview.ST	Salary review batch.
HR_SCC.ST	S.C.C. status list.
HR_VAUTH.ST , HR_VISA.ST	Document lists.
HR_VACATION_Family.ST	Vacations with family-ticket info.
HR_Package.ST , HR_PRDALW.ST	Package & periodic-allowance lookups.
Employer_DRL.ST	Sponsor drill-down.

HR child grids (GTP/)

File	Embedded in	Purpose
HR_PKALW.GT	Package & Contract	Package allowance breakdown.
HR_Alw.GT	Employee Allowances tab	Personal allowances.
HR_Salary.GT	Employee Salary tab	Salary history (read-only).
HR_PosHist.GT	Contract & Employee	Position history.
HR_Contract.GT	Employee Contracts tab	Contract list.
HR_APRContract.GT	Appraisal Re-Contracting tab	New contract preview.
HR_EXTContract.GT	Action Extension	Extension preview.
HR_vacation.GT	Employee Leaves tab	Vacation history.
HR_Eleave.GT	Vacation Educational-Leave tab	
HR_Quals.GT	Employee Qualifications tab	Diplomas & licences.
HR_Childs.GT	Employee Dependants tab	
HR_Experience.GT	Employee Experience tab	
HR_Ticket.GT	Employee Tickets tab	
HR_Overtime.GT	Employee Overtime tab	
HR_Incentive.GT	Employee Incentives tab	
HR_Contract.GT	Employee Contracts tab	

Stored Procedures

The HR module ships ~70 stored procedures. They fall into seven families.

1. Banners (read-only header strips)

HR_EMPLOYEE_BANNER , HR_Contract_BANNER , HR_Action_BANNER , HR_Appraisal_BANNER , HR_Candidate_BANNER ,
HR_VACATION_BANNER , HR_VacAction_BANNER , HR_VISA_BANNER , HR_VAUTH_BANNER , HR_PRDALW_BANNER ,
HR_Agency_BANNER , PR_Loan_BANNER .

2. Alerts (dashboard / form notifications)

HR_EMP_Alert , HR_EMP_Note_Alert , HR_EMP_Note_Alert_APRS , HR_Vacation_Alert ,
HR_Vacation_Alert_Residence , HR_Action_Alert , HR_Action_ContractPending_Alert , HR_ExpiringDocs ,
PR_Loan_Alert .

3. Lookup-population helpers (used by the *Data Setup* installer)

HR_Branch_Add , HR_EntryPort_Add , HR_Position_Add , HR_POSCATEG_Add , HR_ValueType_Add , HR_PKALW_Add ,
HR_PKALW_ORG_Add , hr_Certificate_ADD , HR_ACTION_Salary_Add , HR_APRS_Salary_Add ,
HR_PosHist_Initialize , HR_PosHist_ADD , HR_EMP_NewNumber , HR_PACKAGE_UPDATE , HR_CCI_UPDATE .

4. Calculations

HR_SP_VAC_CALC , HR_VacReq_CALC , HR_VacReq_REQUEST_CALC , HR_SP_EOS_CALC , HR_EOS_DIF_CALC ,
HR_EOS_DIF_CALC_ALL , HR_ACTION_ACCRUED_LEAVE_CALC , HR_ACTION_TOTAL_LEAVE_CALC , HR_APRS_Salary_FIX .

5. Workflow appliers (the SP that actually mutates state)

SP	Used by
HR_Action_Apply	Generic personnel-action apply (dispatches to one of the below).
HR_Action_PROMOD_Apply	Promotion / Demotion.
HR_Action_RETRA_Apply	Re-transfer (returning an employee to the original branch).
HR_Action_TRANS_Apply	Transfer.
HR_Action_HIST_Apply_All	Bulk re-apply of historical actions (migration tool).
HR_Action_Submit_Type	Submit a draft action with a specific type.
HR_Action_AutoApply	Nightly sweep that applies fully-approved actions.

SP	Used by
HR_Appraisal_Apply	Appraisal apply (raise + recontract).
HR_Appraisal_AutoApply	Nightly sweep for fully-approved appraisals.
HR_Contract_Renew	Issue a new contract from the current one.
HR_Contract_Extend	Extend the current contract's end-date.
HR_APRContract	Renew triggered from an appraisal.
HR_EXTContract	Background extension processor.
HR_VacAction_Submit	Submit a vacation action.
HR_VacAction_Apply	Apply a vacation action (consume tickets).
HR_VacAction_AutoApply	Nightly sweep.

6. Reports / batch

HR_Employee_RPT , HR_Vacation_RPT , HR_Account_Employees , HR_MonthlySalaries , HR_DueVacations , HR_ReContractingLetter , HR_EmpAcct_Gen , HR_EMPACCT_NEW , HR_Vacation_TravelALW_Validate .

7. Plumbing (framework hooks)

- HR_SP_FT_Process — generic process hook called by every HR form.
- HR_SP_Employee_Vacancy_PostProcess — post-save hook for the Employee form, keeps HR_Vacancy in sync.
- hr_Vacancy_Create_Transient , hr_Vacancy_Transient_Process , hr_Vacancy_Transient_Process_All — transient vacancy lifecycle.
- HR_Vacancy_Load — picker SP for all *Vacancy* dropdowns.
- HR_Employee_Clear_Vacancy — release an employee's vacancy without a personnel action (admin tool).
- PR_Loan_Load — picker SP for loan dropdowns.
- PR_Loan_Payments — generates the next instalment line in a pay run.

Glossary

Term	Definition
Accrued leave	Leave days the employee has earned but not yet used. Computed by <code>HR_ACTION_ACCRUED_LEAVE_CALC</code> .
Action	A formal change to an employee's job (transfer, promotion, termination, ...) that goes through three-level approval — see Personnel Actions .
Appraisal	End-of-term performance review — see Appraisals .
Banner	Static green strip at the top of an HMS form; rendered by a <code>*_BANNER</code> SP.
Binder (BND)	Full-screen workspace template (toolbar + side menu). HR has no dedicated binder — it is opened from the main menu.
Candidate	An applicant — see Candidates .
Contract	Time-bound employment contract — see Contracts .
EOS	End of Service award (gratuity) paid on leaving, per Saudi labour law — see End of Service .
Form (FT)	Single-record edit window — e.g. <code>HR_Employee.FT</code> .
Ghost / PKT	The edit-buffer table (<code>HR_PKT_*</code>). User changes live here until Save .
Grid (GT)	Child-table view embedded in a form — e.g. <code>HR_Salary.GT</code> .
HR Officer	Day-to-day HR user — creates employees, leaves, candidates.
HR Administrator	Configures look-ups, packages, periodic allowances, security.
Package	Salary template — see Packages .
Pay Code	One line on the pay slip — see Pay Codes .
Pay Run	One monthly payroll batch — see Pay Runs .
Periodic Allowance	Recurring monthly amount paid outside the package — see Periodic Allowances .
PKT table	See <i>Ghost</i> .
Register	Result of one pay run — see Registers .
S.C.C.	Saudi Council Certificate — licensure for clinical staff — see Certificates .
Search pad (ST)	List / search window — e.g. <code>HR_Employee_Fast.ST</code> .
Sponsor	Legal employer on the residence permit. Tracked in <code>HR_Employee.Current_sponsor_name</code> .
Transient vacancy	Auto-created temporary vacancy that keeps headcount balanced during a transfer — see Vacancies .
VacAction	Vacation action — a step in the vacation workflow (request, approve, take, return).
Vacancy	Approved opening to be filled — see Vacancies .

Term	Definition
Vglbatch	GL batch number written on <code>PR_Register.Vglbatch</code> once a payroll is posted to general ledger.