

Series 76 Electric Actuators

The data provided pertains to the **Series 76**, a line of heavy-duty electric actuators. These devices are critical components in industrial automation, used to remotely open, close, or precisely control valves and dampers in a wide range of applications, from HVAC systems to industrial processing plants.

Understanding the Data Tables

The provided tables contain the **Electrical Data** for the Series 76 actuators. This data is essential for engineers and technicians to select the correct actuator model for a specific application based on power availability and performance requirements.

The data is segmented based on several key criteria:

1. Enclosure Type:

- **Weatherproof:** Designed for general industrial use, protected against dust, rain, and environmental elements (compliant with CSA, CE, & UKCA standards).
- **Explosionproof:** Built with a more robust enclosure to be safely operated in hazardous environments where flammable gases or dust may be present (compliant with CSA, IECEx/ATEX standards).

2. Power Supply:

- **24V AC/DC:** Low voltage direct or alternating current.
- **110V Single Phase:** Standard North American voltage.
- **220V Single Phase:** Common international voltage.

3. Application Type:

- **On/Off:** The actuator operates in two positions: fully open or fully closed.
- **Modulating:** The actuator can be controlled to stop at any point in its 90-degree rotation, allowing for precise flow control.

Data Fields in the Tables

- **Base Part Number:** The unique identifier for each actuator model (e.g., 761A00-11380000/A).
- **Output Torque:** The rotational force the actuator can produce, measured in in-lbs (inch-pounds) and Nm (Newton-meters). This is a primary performance metric.

- **Duty Cycle (S4%):** The percentage of time the actuator can be in operation over a given cycle without overheating.
- **Operating Speed (Sec):** The time it takes for the actuator to complete a full 90-degree turn. For AC models, this can vary based on the power frequency (50 Hz vs. 60 Hz).
- **Full Load Current (FLA):** The electric current (in Amps) drawn by the motor under its maximum rated load.
- **Locked Rotor Current (LRA):** The current drawn by the motor at startup, which is significantly higher than the FLA.
- **Motor Power:** The power rating of the internal motor, measured in Watts.