

M03 Homework

Michael Vaden, mtv2eva

```
In [ ]: import pandas as pd
import numpy as np
```

Create a new notebook for your work.

Parse the Frankenstein text to generate TOKENS and VOCAB tables.

Create a list of sentences from the TOKENS table and a list of terms from the VOCAB table.

Generate ngram type tables and models, going up to the trigram level.

Get TOKENS and VOCAB

```
In [ ]: import configparser
config = configparser.ConfigParser()
config.read("../env.ini")
data_home = config['DEFAULT']['data_home']
output_dir = config['DEFAULT']['output_dir']
```

```
In [ ]: text_file = f"{data_home}/pg42324.txt"
```

```
In [ ]: OHCO = ['chap_num', 'para_num', 'sent_num', 'token_num']

LINES = pd.DataFrame(open(text_file, 'r', encoding='utf-8-sig').readlines(), columns=['line_str'])
LINES.index.name = 'line_num'
LINES.line_str = LINES.line_str.str.replace(r'\n+', ' ', regex=True).str.strip()

title = LINES.loc[0].line_str.replace('The Project Gutenberg EBook of ', '')
print(title)
```

Frankenstein, by Mary W. Shelley

```
In [ ]: clip_pats = [
    r"\\*\\*\\*s*START OF (?THE|THIS) PROJECT",
    r"\\*\\*\\*s*END OF (?THE|THIS) PROJECT"
]

pat_a = LINES.line_str.str.match(clip_pats[0])
pat_b = LINES.line_str.str.match(clip_pats[1])

line_a = LINES.loc[pat_a].index[0] + 1
line_b = LINES.loc[pat_b].index[0] - 1
print(line_a, line_b)

LINES = LINES.loc[line_a : line_b]
```

19 7671

```
In [ ]: chap_pat = r'^(?:LETTER|CHAPTER)\b'

chap_lines = LINES.line_str.str.match(chap_pat, case=True) # Returns a truth vector
```

```
In [ ]: LINES.loc[chap_lines]
```

Out[]:

| | line_str |
|----------|----------------|
| line_num | |
| 343 | LETTER I. |
| 467 | LETTER II. |
| 594 | LETTER III. |
| 636 | LETTER IV. |
| 918 | CHAPTER I. |
| 1085 | CHAPTER II. |
| 1299 | CHAPTER III. |
| 1555 | CHAPTER IV. |
| 1789 | CHAPTER V. |
| 2028 | CHAPTER VI. |
| 2292 | CHAPTER VII. |
| 2655 | CHAPTER VIII. |
| 2958 | CHAPTER IX. |
| 3165 | CHAPTER X. |
| 3385 | CHAPTER XI. |
| 3651 | CHAPTER XII. |
| 3856 | CHAPTER XIII. |
| 4061 | CHAPTER XIV. |
| 4245 | CHAPTER XV. |
| 4552 | CHAPTER XVI. |
| 4861 | CHAPTER XVII. |
| 5046 | CHAPTER XVIII. |
| 5324 | CHAPTER XIX. |
| 5572 | CHAPTER XX. |
| 5905 | CHAPTER XXI. |
| 6274 | CHAPTER XXII. |
| 6615 | CHAPTER XXIII. |
| 6867 | CHAPTER XXIV. |

```
In [ ]: LINES.loc[chap_lines, 'chap_num'] = [i+1 for i in range(LINES.loc[chap_lines].shape[0])]
```

```
In [ ]: LINES.chap_num = LINES.chap_num.ffill()

LINES = LINES.dropna(subset=['chap_num']) # Remove everything before Chapter 1

LINES = LINES.loc[~chap_lines] # Remove chapter heading lines; their work is done
LINES.chap_num = LINES.chap_num.astype('int') # Convert chap_num from float to int
```

```
In [ ]: CHAPS = LINES.groupby(OHCO[:1])\
        .line_str.apply(lambda x: '\n'.join(x))\
        .to_frame('chap_str')

CHAPS['chap_str'] = CHAPS.chap_str.str.strip()
```

```
In [ ]: para_pat = r'\n\n+'
# CHAPS['chap_str'].str.split(para_pat, expand=True).head()
PARAS = CHAPS['chap_str'].str.split(para_pat, expand=True).stack()\
        .to_frame('para_str').sort_index()
PARAS.index.names = OHCO[:2]
```

```
In [ ]: PARAS['para_str'] = PARAS['para_str'].str.replace(r'\n', ' ', regex=True)
PARAS['para_str'] = PARAS['para_str'].str.strip()
PARAS = PARAS[~PARAS['para_str'].str.match(r'^\s*$')]
```

```
In [ ]: sent_pat = r'[.?!;:]+ '
SENTS = PARAS['para_str'].str.split(sent_pat, expand=True).stack()\
        .to_frame('sent_str')
SENTS.index.names = OHCO[:3]
SENTS = SENTS[~SENTS['sent_str'].str.match(r'^\s*$')] # Remove empty paragraphs
SENTS.sent_str = SENTS.sent_str.str.strip() # CRUCIAL TO REMOVE BLANK TOKENS
```

```
In [ ]: token_pat = r"[\s',-]+"
TOKENS = SENTS['sent_str'].str.split(token_pat, expand=True).stack()\
        .to_frame('token_str')
TOKENS.index.names = OHCO[:4]

TOKENS['term_str'] = TOKENS.token_str.replace(r'[\W_]+', '', regex=True).str.lower()
TOKENS
```

```
Out[ ]:
```

| chap_num | para_num | sent_num | token_num | token_str | term_str |
|----------|----------|----------|-----------|--------------|--------------|
| 1 | 0 | 0 | 0 | _To | to |
| | | | 1 | Mrs | mrs |
| | | 1 | 0 | Saville | saville |
| | | | 1 | England | england |
| | | 2 | 0 | _ | |
| ... | ... | ... | ... | ... | ... |
| 28 | 86 | 0 | 7 | Frankenstein | frankenstein |
| | | | 8 | by | by |
| | | | 9 | Mary | mary |
| | | | 10 | W | w |
| | | 1 | 0 | Shelley | shelley |

75941 rows x 2 columns

```
In [ ]: TOKENS['term_str'] = TOKENS.token_str.replace(r'[\W_]+', '', regex=True).str.lower()
VOCAB = TOKENS.term_str.value_counts().to_frame('n').reset_index().rename(columns={'index': 'term_str'})
VOCAB.index.name = 'term_id'
VOCAB
```

```
Out[ ]:
```

| term_id | term_str | n |
|---------|-----------|------|
| 0 | the | 4200 |
| 1 | and | 2976 |
| 2 | i | 2854 |
| 3 | of | 2650 |
| 4 | to | 2105 |
| ... | ... | ... |
| 6973 | indecent | 1 |
| 6974 | pretended | 1 |
| 6975 | warmly | 1 |
| 6976 | hesitate | 1 |
| 6977 | shelley | 1 |

6978 rows x 2 columns

Create a list of sentences from the TOKENS table and a list of terms from the VOCAB table.

```
In [ ]: def token_to_padded(token, grouper=['sent_num'], term_str='term_str'):
    ohco = token.index.names # We preserve these since they get lost in the shuffle
    padded = token.groupby(grouper)\
        .apply(lambda x: '<s> ' + ' '.join(x[term_str]) + ' </s>')\
        .apply(lambda x: pd.Series(x.split()))\
        .stack().to_frame('term_str')
    #padded.index.names = ohco
    return padded
```

```
In [ ]: PADDED = token_to_padded(TOKENS, grouper=OHC0[:3], term_str='term_str')
```

Generate ngram type tables and models, going up to the trigram level.

```
In [ ]: ngrams = 2
widx = [f"w{i}" for i in range(ngrams)]
```

```
In [ ]: def padded_to_ngrams(padded, grouper=['sent_num'], n=2):
    ohco = padded.index.names
    ngrams = padded.groupby(grouper)\
        .apply(lambda x: pd.concat([x.shift(0-i) for i in range(n)], axis=1))\
        .reset_index(drop=True)
    ngrams.index = padded.index
    ngrams.columns = widx

    # ngrams = pd.concat([padded.shift(0-i) for i in range(n)], axis=1)
    # ngrams.index.name = 'ngram_num'
    # ngrams.columns = widx
    # ngrams = ngrams.fillna('<EOF>')

    return ngrams
```

```
In [ ]: ngrams = 1
widx = [f"w{i}" for i in range(ngrams)]

NGRAMS1 = padded_to_ngrams(PADDED, OHC0[:3], ngrams)
```

```
In [ ]: ngrams = 2
widx = [f"w{i}" for i in range(ngrams)]

def ngrams_to_models(ngrams):
    global widx
    n = len(ngrams.columns)
    model = [None for i in range(n)]
    for i in range(n):
        if i == 0:
            model[i] = ngrams.value_counts('w0').to_frame('n')
            model[i]['p'] = model[i].n / model[i].n.sum()
            model[i]['i'] = np.log2(1/model[i].p)
        else:
            model[i] = ngrams.value_counts(widx[:i+1]).to_frame('n')
            model[i]['cp'] = model[i].n / model[i-1].n
            model[i]['i'] = np.log2(1/model[i].cp)
            model[i] = model[i].sort_index()
    return model
M = ngrams_to_models(NGRAMS)
```

```
In [ ]: ngrams = 3
widx = [f"w{i}" for i in range(ngrams)]

NGRAMS3 = padded_to_ngrams(PADDED, OHCO[:2], ngrams)

M3 = ngrams_to_models(NGRAMS3)
```

```
In [ ]: ngrams = 1
widx = [f"w{i}" for i in range(ngrams)]

NGRAMS1 = padded_to_ngrams(PADDED, OHCO[:3], ngrams)

M1 = ngrams_to_models(NGRAMS1)
```

Questions

1.List six words that precede the word "monster," excluding stop words (and sentence boundary markers). Stop words include 'a', 'an', 'the', 'this', 'that', etc. Hint: use the df.query() method.

```
In [ ]: stop_words = ['a', 'an', 'the', 'this', 'that', '<s>']

NGRAMS.query("w1 == 'monster' & w0 not in @stop_words")
```

```
Out[ ]:          w0      w1
chap_num para_num sent_num
9         3      17 25  miserable monster
14        8       0  1  abhorred  monster
19       25       4 23  detestable monster
20       28       0  1   hideous  monster
28        4       9  5   hellish  monster
        17       6  2  gigantic  monster
```

```
In [ ]: print(list(NGRAMS.query("w1 == 'monster' & w0 not in @stop_words")['w0']))

['miserable', 'abhorred', 'detestable', 'hideous', 'hellish', 'gigantic']
```

2.List the following sentences in ascending order of bigram perplexity according to the language model generated from the text:

The monster is on the ice.

Flowers are happy things.

I have never seen the aurora borealis.

He never knew the love of a family.

```
In [ ]: TEST_SENTS = pd.DataFrame({'sent_str': ['The monster is on the ice.',
        'Flowers are happy things.',
        'I have never seen the aurora borealis.',
        'He never knew the love of a family.']})

TEST_SENTS.index.name = 'sent_num'
TEST_SENTS
```

```
Out[ ]:          sent_str
sent_num
0      The monster is on the ice.
1      Flowers are happy things.
2  I have never seen the aurora borealis.
3      He never knew the love of a family.
```

```
In [ ]: # Convert dataframe of sentences to TOKEN with normalized terms
K = TEST_SENTS.sent_str.apply(lambda x: pd.Series(x.split()).stack().to_frame('token_str'))
K['term_str'] = K.token_str.str.replace(r"[\W_]+", "", regex=True).str.lower()
K.index.names = ['sent_num', 'token_num']
TEST_TOKENS = K

#TEST_TOKENS.head()

In [ ]: ngrams = 2
widx = [f"w{i}" for i in range(ngrams)]

In [ ]: TEST_PADDED = token_to_padded(TEST_TOKENS)

In [ ]: TEST_NGRAMS = padded_to_ngrams(TEST_PADDED, 'sent_num', ngrams)

In [ ]: TEST_NGRAMS = TEST_NGRAMS.reset_index().rename({'level_1': 'token_num'}, axis=1).groupby(['sent_num', 'token_num']).sum()

In [ ]: def test_model(model, ngrams, sents):

    global widx

    assert len(model) == len(ngrams.columns)

    n = len(model)
    ohco = ngrams.index.names

    R = []
    for i in range(n):
        T = ngrams.merge(M[i], on=widx[:i+1], how='left')
        T.index = ngrams.index
        T = T.reset_index().set_index(ohco + widx).i #.to_frame(f"i{i}")

        # This how we handle unseen combos
        T[T.isna()] = T.max()
        R.append(T.to_frame(f"i{i}"))

    return pd.concat(R, axis=1)

R = test_model(M, TEST_NGRAMS, TEST_SENTS)
```

```
In [ ]: def compute_perplexity(results, test_sents, n=2):
    for i in range(n):
        test_sents[f"pp{i}"] = np.exp2(results.groupby(['sent_num'])[f"i{i}"].mean())
    return test_sents
```

```
In [ ]: PP = compute_perplexity(R, TEST_SENTS)
PP
```

```
Out [ ]:
```

| | sent_str | pp0 | pp1 |
|----------|--|------------|------------|
| sent_num | | | |
| 0 | The monster is on the ice. | 116.056265 | 80.733835 |
| 1 | Flowers are happy things. | 586.369721 | 534.302604 |
| 2 | I have never seen the aurora borealis. | 340.789117 | 138.907338 |
| 3 | He never knew the love of a family. | 170.793655 | 137.060591 |

3.Using the bigram model represented as a matrix, explore the relationship between bigram pairs using the following lists. Hint: use the .unstack() method on the feature n and then use .loc[] to select the first list from the index, and the second list from the columns.

- ['he','she'] to select the indices.
- ['said','heard'] to select the columns.

```
In [ ]: matrix_df = M[1].unstack()
matrix_df.loc[['he', 'she']].loc[:, (['n', 'i'], ['said', 'heard'])]
```

```
Out [ ]:
```

| | n | | i | |
|-----|------|-------|----------|----------|
| w1 | said | heard | said | heard |
| w0 | | | | |
| he | 21.0 | 5.0 | 4.857981 | 6.928370 |
| she | 3.0 | 3.0 | 6.409391 | 6.409391 |

4.Generate 20 sentences using the generate_text() function. Display the results.

```
In [ ]: def generate_text(M, n=250):

    if len(M) < 3:
        raise ValueError("Must have trigram model generated.")

    # Start list of words
    first_word = M[1].loc['<s>'].sample(weights='cp').index[0]

    words = ['<s>', first_word]
```

```

for i in range(n):
    bg = tuple(words[-2:])
    # Try trigram model
    try:
        next_word = M[2].loc[bg].sample(weights='cp').index[0]
    # If not found in model, back off ...
    except KeyError as e1:
        try:
            # Get the last word in the bigram
            ug = bg[1]
            next_word = M[1].loc[ug].sample(weights='cp').index[0]
        except KeyError as e2:
            next_word = M[0].sample(weights='p').index[0]

    words.append(next_word)

text = ' '.join(words[2:])
print('\n\n'.join([str(i+1) + ' ' + line.replace('<s>', '')\
    .strip().upper() for i, line in enumerate(text.split('</s>'))]))

```

```
In [ ]: generate_text(M3, n = 270)
```

```

1 THE KNOWLEDGE WHICH I ALONE POSSESSED WAS THE PERIOD FIXED FOR THE ENJOYMENT OF PLEASURE
2
3 YOU ARE WELL ACQUAINTED WITH HIM AT PRESENT EXISTING IN THE SUCCESS OF MY FATHER IS IN DEATH
4
5 THE SOFT AIR JUST RUFFLED THE WATER
6 I SAW MY FRIENDS MY WIFE AND MY HEART WHICH WAS TO DISCOVER ANY CLUE BY WHICH I REGARD MYSELF
7 I BELIEVED IN HER GUILT
8 THIS CHILD WAS THIN AND VERY HAPPY ONLY A FEW DAYS AT LAUSANNE IN THIS JOURNEY HAD BEEN THE CAUSE
9 AT LENGTH ARRIVED
10 I TROD HEAVEN IN MY OWN MIND BEGAN TO PLAY AND TO BECOME MY FELLOW CREATURES THEN COULD I DO MY DUTY
11 SHE SOMETIMES BEGGED JUSTINE TO FORGIVE HER UNKINDNESS BUT MUCH OFTENER ACCUSED HER OF HAVING CAUSED THE BEST MEANS OF MATERIALLY ASS
    ISTING THE PROGRESS OF YOUR MIND TO AN EXPRESSION OF WILDNESS AND EVEN MADNESS
12 BUT WHEN DANIEL NUGENT WAS CALLED SISTER OR AGATHA
13 THE PATRIARCHAL LIVES OF ALL EXCELLENCE AND ENDEAVOURED TO WELCOME ME
14 BESIDES SOME MONTHS IN PRISON
15 EVERY WHERE I AM LOST IN CONJECTURE AS TO CREATURES OF AN ENGLISH PHILOSOPHER THE KNOWLEDGE OF LANGUAGE
16 A FEW MISERABLE COWS AND OATMEAL FOR ITS HOSPITALITY
17 MELANCHOLY FOLLOWED BUT BY DEGREES ONE HERB FROM ANOTHER
18
19 THE WOUNDED DEER DRAGGING ITS FAINTING LIMBS TO SOME ONE A FRIEND OF MY LABOURS IN SOME DEGREE ALARMED ME
20 I RETIRED TO A HUMAN CREATURE

```

5. Compute the redundancy for each of the n-gram models using the MLE of the joint probability of each ngram type. In other words, for each model, just use the .mle feature...

Does R increase, decrease, or remain the same as the choice of n-gram increases in length?

N is computed as the number of all possible combinations for each ngram. So, for the bigram model N is the number of unigrams (i.e. the vocabulary size plus the sentence boundary signs) squared, and for the trigram model the value is cubed, i.e. $N = \text{len}(M[0].\text{index})^{i+1}$

```

In [ ]: M3[1]['p'] = M3[1].n / M3[1].n.sum()
        M3[2]['p'] = M3[2].n / M3[2].n.sum()

        M3[0]['h'] = M3[0]['p'] * M3[0]['i']
        M3[1]['h'] = M3[1]['p'] * M3[1]['i']
        M3[2]['h'] = M3[2]['p'] * M3[2]['i']

```

```

In [ ]: H1 = M3[0]['h'].sum()
        H2 = M3[1]['h'].sum()
        H3 = M3[2]['h'].sum()

```

```

In [ ]: n_terms1 = M3[0]['n'].count()
        n_terms2 = M3[1]['n'].count()
        n_terms3 = M3[2]['n'].count()

```

```

In [ ]: Hmax1 = np.log2(n_terms1)
        Hmax2 = np.log2(n_terms2)
        Hmax3 = np.log2(n_terms3)

```

```
R1 = 1 - (H1/Hmax1)
R2 = 1 - (H2/Hmax2)
R3 = 1 - (H3/Hmax3)
```

```
In [ ]: print(f"Unigram Redundancy: {R1}")
        print(f"Bigram Redundancy: {R2}")
        print(f"Trigram Redundancy: {R3}")
```

```
Unigram Redundancy: 0.30885786469975895
Bigram Redundancy: 0.6843823899586926
Trigram Redundancy: 0.8838055825847118
```