萬隆電線電纜股份有限公司

WAN LUNG ELECTRIC WIRE & CABLE MFG. CO., LTD.

NEOTECH CABLE

ITEM NO.		SPECIFICATION		
KCS-200	[(1/0.8 SPC	[(1/0.8 SPCx2C)+PP Tape+AL-Mylar+24x10/0.10+Paper]x1C		
CONSTRUCTION				
CONDUCTOR:Material: SPC			INSULATOR:Material: PE	
Size: 0.50 mm²		mm²	Thickness: 0.8 mm	
Stranding: 1/0.8 mm		mm	Diameter: 2.4 mm	
Diameter: 0.8 mm		mm	INNER JACKET:Material:	
SHIELD: T	Ype: Braid O	FC	Diameter: mm	
Strano	ing: 24x10/0.1	0 mm	Outer Jacket:Material: PVC	
GROUND WIRE:		mm	Diameter: 8.0 mm	
CHARACTERISTICS				

CHARACTERISTICS

TEST REPORT:

(1):CONDUCTOR RESISTANCE: 0.0334 0.0335 Ω/M at 20

(2):CAPACTANCE:K1:43.52 PF/M at 1KHz

K0:84.96 84.65 PF/M at 1KHz

(3):INDUCTANCE:K1:0.942 uH/m at 1KHz

K0:0.575 0.587 uH/m at 1KHz

104年03月24日 客戶: F019